Title: Spatial structure, phase, and the contrast of natural images

Author names and affiliations:

Reuben Rideaux [1,*]

Rebecca K. West [2,*]

Peter J. Bex [3]

Jason B. Mattingley [1,2]

William J. Harrison [1,2]

[1] Queensland Brain Institute, The University of Queensland, St Lucia 4072, Australia

[2] School of Psychology, The University of Queensland, St Lucia 4072, Australia

[3] Department of Psychology, Northeastern University, Boston 02115, USA

[*] Contributed equally

Corresponding author and email: William J Harrison (willjharri@gmail.com)

Key words: contrast sensitivity, visual search, image statistics, natural images

Abstract

The sensitivity of the human visual system is thought to be shaped by environmental statistics. A major endeavour in visual neuroscience, therefore, is to uncover the image statistics that predict perceptual and cognitive function. When searching for targets in natural images, for example, it has recently been proposed that target detection is inversely related to the spatial similarity of the target to its local background. We tested this hypothesis by measuring observers' sensitivity to targets that were blended with natural image backgrounds. Importantly, targets were designed to have a spatial structure that was either similar or dissimilar to the background. Contrary to masking from similarity, however, we found that observers were most sensitive to targets that were most similar to their backgrounds. We hypothesised that a coincidence of phase-alignment between target and background results in a local contrast signal that facilitates detection when target-background similarity is high. We confirmed this prediction in a second experiment. Indeed, we show that, by solely manipulating the phase of a target relative to its background, the target can be rendered easily visible or completely undetectable. Our study thus reveals a set of image statistics that predict how well people can perform the ubiquitous task of detecting an object in clutter.

Introduction

The human visual system is tasked with parsing the complexity of natural environments into a coherent representation of behaviourally relevant information. These operations have been shaped by various selective pressures over evolutionary and developmental timescales. Therefore, the perceptual computations that guide cognition and behaviour ultimately serve to extract functional information from rich and complex naturalistic environments (Carandini et al., 2005; Field, 1987; Olshausen & Field, 2005; Parraga et al., 2000; Simoncelli & Olshausen, 2001). For example, a common task is to find a pre-defined target object in a complex or cluttered visual environment. The vast majority of our knowledge of the visual system, however, has been derived from experiments using relatively sparse stimulus displays that are not representative of our typical visual diets. The aim of the present study was to investigate how natural image structure influences target detection. We tested how detection is influenced by the spatial structure, phase, and contrast of natural image backgrounds to determine the features that best predict detection sensitivity.

Luminance contrast plays a critical role in most visual tasks. The human visual system is tuned to detect contrast across a range of spatial and temporal frequencies. Neurons in primary visual cortex (V1) are classically understood as processing local regions of oriented contrast that can define the borders of objects (Hubel & Wiesel, 1959). Such properties of individual neurons govern phenomenal perception and are thought to be shaped by the statistics of natural environments (Barlow, 1961, 1972). The encoding of contrast within the visual system is most commonly studied with oriented grating stimuli, such as Gabor wavelets. Grating stimuli are conveniently characterised by a simple set of parameters: orientation, contrast, position, and spatial frequency. From a computational perspective, "Gabor wavelet analyses" allow the decomposition of any image into mathematically tractable component features. Such analyses are computationally efficient and are common in many computer vision applications. Early theory suggested that analogous decomposition processes occur in the visual system (Campbell & Robson, 1968). However, more recent studies suggest that individual visual neurons encode complex higher-order statistical information that is not necessarily predicted by Gabor parameters (e.g. Cadena et al., 2019).

One common approach to investigate contrast sensitivity in natural conditions is to have observers detect contrast-defined targets embedded in digital photographs or

movies. Relative to sensitivity as typically quantified with a uniform background, spatio-
temporal contrast sensitivity is diminished when viewing dynamic movies, particularly for
lower frequencies (Bex et al., 2009). Furthermore, during free viewing of natural movies,
the large-scale retinal changes caused by saccadic eye movements also diminish
sensitivity likely due to forward and backward masking (Dorr & Bex, 2013; Wallis et al.,
2015). In general, such studies have revealed that the sensitivity of the visual system does
indeed depend on naturalistic context (Bex & Makous, 2002; Geisler, 2008).

Researchers have further sought to understand the statistical regularities of natural
scenes that impact the detectability of targets. For example, various image structures,
such as the density of edges within close proximity to the target, negatively impact
detection sensitivity (Bex et al., 2009). Indeed, the discriminability of visual objects can be
predicted from the spatial proximity of surrounding visual clutter (Balas et al., 2009;
Greenwood et al., 2010, 2012; Harrison & Bex, 2014, 2015, 2017; Wallis et al., 2019).
More recently, it has been found that sensitivity scales inversely with the *structural*
similarity between target and background (Sebastian et al., 2017). Structural similarity
describes how similar two stimuli are in terms of the spatial distribution of phase-invariant
contrast. Sebastian et al found that observers' detection sensitivity decreases with
increasing similarity. These studies thus predict that targets are most difficult to detect
when they are similar to their backgrounds (Sebastian et al., 2017), particularly when
those backgrounds are dense with edges (Bex et al., 2009). Other studies that have
attempted to quantify the relationship between image statistics and sensitivity use post-hoc
computational means to estimate the influence of natural image structure on target
detection or apparent contrast (e.g. Haun & Peli, 2013; Wallis et al., 2015; Wallis & Bex,
2012). Very few studies, to the best of our knowledge, explicitly manipulated the
consistency of a target's appearance with the appearance of a natural image background
in an experimental design (e.g. Neri, 2014, 2017; Teufel et al., 2018).

The aim of the present study was to test observers' sensitivity to targets presented
on natural image backgrounds. Importantly, we designed the test stimuli a priori such that
targets approximated the appearance of, and were aligned with, the local structure of a
natural image background, or differed from the local structure. Based on previous studies
showing a negative impact of increasing target-background similarity on detection (Bex et
al., 2009; Sebastian et al., 2017), we expected to find worse detection sensitivity when
targets were aligned to the background – and therefore highly similar – than when they
were misaligned relative to the background. To anticipate our results, however, we found
the opposite, instead revealing that the influence of target-background similarity on
detection sensitivity depends almost entirely on the relative phase of the target.

A   B   C   D   E   Aligned   F   Misaligned

Figure 1. Stimulus generation method for testing sensitivity to contrast in natural images. A) An example source image taken from a collection of over 26,000 labelled images in the THINGS database (Hebart et al., 2019). B) We used a complement of derivative of Gaussian wavelets to filter each source image and compute the dominant orientation (top panel) and contrast energy (bottom panel) at each pixel location. Orientation is indicated by the inset colour wheel, which spans the full range (0 – 2pi) to indicate the preservation of the phase of the dominant filter. C) As shown by the white dashed circles, we selected target image regions according to the peaks of the oriented contrast maps. The number of targets varied from trial to trial from 1 to 16 in equally spaced log steps. D) Targets were oriented filters generated from the oriented contrast maps. These target features are thus aligned to the natural structure within the source image. Targets were then added to a natural image background, and observers were required to detect in which of two images the targets had been added. E and F) Targets were either aligned (E) or misaligned (F) with the background structure. Note that the same targets have been added to both examples but are more apparent in the aligned condition than the misaligned condition. As a guide, target filters are located at the intersection of pink and blue lines at the edges of panels D – F.

Methods

Participants. All observers were authors of the paper and had normal vision (RR, RW & WH). RW and RR were naïve to the specific experimental manipulations at the time of testing. The experiment was designed and carried out during a COVID-19 lockdown in Brisbane, Australia, in March 2021. Testing occurred, therefore, in each observer's private residence.

Design. We measured observers' sensitivity to contrast changes in natural images in a 2 (target-background alignment: aligned or misaligned) x 5 (number of targets: 1, 2, 4, 8, or 16) x 5 (target amplitude: 0, 0.05, 0.1, 0.2, or 0.4 of maximum) design. Each observer completed 40 trials per condition for a total of 2000 trials in a fully within-participants design.

Stimuli. Stimuli were programmed with the Psychophysics Toolbox (Brainard, 1997; Pelli, 1997) in MATLAB (v2018b, Mathworks) and were displayed either on a 15" MacBook Pro Retina or a 16" MacBook Pro Retina. Natural images of objects were taken from the THINGS database (Hebart et al., 2019), available via the Open Science Framework (https://osf.io/jum2f/). Images were converted to greyscale using the rgb2grey() function in MATLAB, and we assumed digital photos were encoded with a gamma of 2, and displays had a decoding gamma of 2.

We describe the stimulus generation process in detail below, but provide a brief overview here. On each trial, two natural images were displayed, both of which were normalised in their contrast. Images had a diameter of 2° and were presented to the left and right of a red fixation spot. The target stimulus was the one in which wavelet filters had been blended with the natural image; the distractor was a natural image with no target filters. The filters were designed to be similar or dissimilar from the underlying natural image structure. We generated target stimuli by blending a source image of a natural object with derivative of Gaussian wavelets (henceforth: *filters*). The blending process followed four steps: 1) find the dominant orientation of each pixel in a source image, 2) find the relative contrast of each pixel in the image, 3) draw some number of filters at the highest contrast image regions, and 4) combine the filters with a source image. We expand on these steps below.

First, we used a steerable filter approach to determine the dominant orientation at
every pixel in a given source image (Freeman & Adelson, 1991). Filters were directional
first derivative of Gaussians oriented at 0° and 90°:

Equation 1 $$G_1^{0°} = -2\frac{x}{\sigma} e^{-\frac{x^2+y^2}{\sigma^2}}$$

Equation 2 $$G_1^{90°} = -2\frac{y}{\sigma} e^{-\frac{x^2+y^2}{\sigma^2}}$$

Where σ is the standard deviation of the Gaussian, *x* and *y* are the coordinates of
each image pixel with point (0,0) at the centre, and *G* is the resulting filter. The Gaussian
standard deviation was 0.08°. Within a trial, each filter was convolved with a source image:

Equation 3 $$R^{0°} = G_1^{0°} * I$$

Equation 4 $$R^{90°} = G_1^{90°} * I$$

Where *I* is the source image with a mean of 0 and in the range [-1 1] and *R* is a filter
response at each pixel location. We combined the filter responses to find the dominant
orientation, $\hat{\theta}$, at each location:

Equation 5 $$\hat{\theta} = atan2\left(\sum_{\theta=0°}^{90°} R^\theta \sin(\theta), \sum_{\theta=0°}^{90°} R^\theta \cos(\theta)\right)$$

Second, we created a contrast map, *C*, of the filtered image by combining the filter
outputs as follows:

Equation 6 $$C = \sqrt{\sum_{\theta=0°}^{90°} R_\theta^2}$$

Third, we found the dominant orientation at the location of the contrast maxima:

Equation 7 $$C_0 = argmax\ C$$

Equation 8 $$\hat{\theta}_{cmax} = \hat{\theta}_{C_0}$$

C_0 indexes the x-y coordinates of the contrast maxima, and $\hat{\theta}_{cmax}$ is the orientation at
this location. We then steered a filter at this location as follows:

Equation 9 $$S = \cos\left(\hat{\theta}_{cmax}\right) G_{C_0}^{0°} + \sin\left(\hat{\theta}_{cmax}\right) G_{C_0}^{90°}$$

Here, *S* is the resulting filter stimulus in the range -1 to 1. Note the additional
subscript of the filters that indicates that the filters were centred on the location of the
contrast maxima, C_0. This is trivially achieved by centring the x-y coordinates in Equations
1 and 2 on the coordinates of C_0.

Finally, we created the target stimulus, τ, by combining the filter stimulus, *S*, with a
normalised source image:

Equation 10 $$\tau = 0.5 + \frac{2\alpha S + I_{norm}}{2}$$

Where α is the filter amplitude expressed as a proportion of maximum possible
contrast, and

Equation 11 $$I_{norm} = 2\rho \frac{I}{sd(I)}$$

Here, ρ is the image root mean square (RMS) contrast, and $sd(I)$ is the standard
deviation of the source image. RMS contrast was set to 0.2 based on the findings of
Sebastian et al (2017). The addition of 0.5 and denominator in Equation 10 normalises the
range of the source image to [0 1] for display. Prior to this step, the target image was
windowed in a circular aperture with a diameter matching the width of the source image
(i.e. 2°) and a raised cosine edge, transitioning to zero contrast in 6 pixels. To constrain

the filters generated by Equation 9 to appear within the windowed portion of the stimulus,
the same aperture was applied to the contrast map, C, prior to generating the stimulus.
Any values lower or higher than 0 or 1, respectively, in I_{norm} were clipped.

For trials in which multiple filters were combined with a source image, we used an
iterative procedure to draw *n* local maxima from the contrast image. Following the argmax
operation in Equation 7, we updated the contrast map to minimise the contrast at the
maxima:

Equation 12
$$C_n = \begin{cases} C_{n-1}[1 - f(\Delta\sigma, C_0)] & n > 1 \\ C & n = 1 \end{cases}$$

Where C_n is the contrast map for the *n*-th filter, and $f(C_0, \Delta\sigma)$ is a two-dimensional
Gaussian with a peak of 1 centred on the location of the maxima C_0, and a standard
deviation of $\Delta\sigma$. σ is the standard deviation of the basis filters, while Δ is a scaling factor
that determines the spatial extent of change in the contrast map. The effect of this
adjustment is the creation of a new local maxima at a different location than in the previous
iteration. The greater the value of Δ, the greater the spatial spread of filters.

Image selection. The 26,107 images in the THINGS database are grouped into
1,854 concepts (e.g. "dog", "cup", "brush" etc), such that there are at least 12 unique, high
quality images for each concept (Hebart et al., 2019). In each testing session (500 trials),
we selected 1000 source images from unique concepts such that no two images were
drawn from the same concept. The target background was thus always drawn from a
different concept than the distractor image. However, it was necessary that some concepts
were repeated across testing sessions, and it was also possible that some individual
images were also repeated across sessions (but never within sessions). On each trial, we
selected two images from the set of 500: one image for the target background, and a
second image was the distractor. On half the trials, the target filters were generated from
the target background and were therefore aligned with the background, while on the other
half of trials they were generated from the distractor image – but blended with the target
background – and were therefore misaligned relative to the target background.

Procedure. A typical trial sequence is shown in Figure 2. Each trial began with a
small red fixation spot in the centre of the display, followed by outlines of the upcoming
stimulus locations. Natural image backgrounds were followed by a blank of 500ms, after
which time the observer reported which of the two patches contained the target filter(s)
using the keyboard. Following the observer's response, the image patch with target filters
was re-displayed for an additional 500ms, outlined in green or red depending on whether
the observer's response was correct or incorrect, respectively. Feedback was provided to
facilitate observers reaching a stable level of performance. No breaks were programmed
but could be taken by withholding a response. Each session included ten repeats of each
trial type, all presented in random order, giving 500 trials per session and taking
approximately 15 minutes when no breaks were taken.

| 200 ms | 200 ms | 200 ms | 500 ms |

211
Figure 2. Schematic of typical trial sequence. The target and background could appear on the left or
right of the screen with equal probability. Following an observer's response, the background
containing the target filters was framed by a green or red circle depending on whether the response
was correct or incorrect, respectively.

Sensitivity analyses. We quantified observers' sensitivity to the target filters in
natural images in a generalised linear model (GLM) framework. We describe the most
pertinent aspects of the framework below, but, for the impatient reader, we note that these
equations accumulate to the fitglme() function in MATLAB, or, equivalently, the lmer()
function in R with the lme4 package (Bates et al., 2015).

In a standard single-interval detection paradigm in which a target is either present or
absent, sensitivity, *d'*, is calculated as:

Equation 13 $$d' = \phi H - \phi F$$

Where ϕ is the normal integral function, *H* is the proportion of hits, and *F* is the
proportion of false alarms. An observer's criterion, *c*, is calculated as:

Equation 14 $$c = \frac{1}{2}(\phi H + \phi F)$$

In a GLM, *d'* and *c* (bias) are computed as predictor weights β_1 and β_0, respectively,
that are passed through a probit link function, which is the normal integral function:

Equation 15 $$\eta_{[i]} = \beta_0 + \beta_1 S_{01[i]}$$

Equation 16 $$p(present_i) = \phi\eta_i$$

Where η is the sum of weighted linear predictors and S_{01} is the absence or presence
of the signal (i.e. 0 or 1, respectively) on the *i*-th trial. By fitting such a probit model,
estimates of the predictor weights β_1 and β_0 are identical to *d'* and *c*, respectively, as
calculated in Equation 13 and Equation 14. Whereas these equations fully specify
sensitivity and bias in a single interval present/absent judgement task, some small
modifications are needed to quantify sensitivity in a two-alternative forced choice task
(2AFC) as in our experiment. First, S_{01} denotes whether the target filter(s) appeared in the
left or right spatial interval, defined as -.5 or .5, respectively. Similarly, observers' reports
(i.e. "target appeared in the left or right interval"), were defined as -1 and 1, respectively.
Finally, in a 2AFC, observers have two opportunities to detect the target – once per spatial
interval – and so raw *d'* will be greater than in a single-interval detection design. Therefore,
sensitivity (but not bias) must be scaled by $\frac{1}{\sqrt{2}}$ (Macmillan & Creelman, 2004):

Equation 17 $$d'_{2AFC} = \frac{1}{\sqrt{2}}\beta_1 = \frac{1}{\sqrt{2}}(\phi H - \phi F)$$

Importantly, we can extend Equation 15 to quantify sensitivity to any number of other
predictors, x_ω:

Equation 18 $$\eta_{[i]} = \beta_0 + \beta_1 S_{01[i]} + \cdots + \beta_\omega x_{\omega[i]}$$

Consider, for example, the influence of filter amplitude (α) on an observer's
sensitivity:

Equation 19 $\qquad\qquad\qquad \eta_{[i]} = \beta_0 + \beta_1 \alpha_{[i]} S_{01[i]}$

Note that filter amplitude is entered into the model as an interaction with target
location because the model's predicted outcome is a spatial report; target amplitude alone
can only predict a change in bias. In preliminary model fits, we found that such bias was
not significantly different from zero, and thus included only interactive terms to facilitate
interpretability of the standard bias term, β_0. We selected other model predictors according
to the model that produced the lowest Akaike information criterion (AIC; see below).

Finally, we implemented this model as a multilevel GLM (GLMM) to partially pool
coefficient estimates across observers (Andrew Gelman & Hill, 2007). By using a GLMM,
we model each observer's predictor weights as having come from a population distribution
with mean μ and variance σ^2:

Equation 20 $\qquad\qquad\qquad \eta_{[i]} = \beta_{0,j} + \beta_{1,j} \alpha_{j[i]} S_{01,j[i]} + \cdots$

Where

Equation 21 $\qquad\qquad\qquad \beta_{\omega,j} = \mu_\omega + \epsilon_{\omega,j} \mid \sigma_\omega^2$

Here, $\epsilon_{\omega,j}$ is the offset for each predictor ω and observer j, relative to the parameter's
mean μ, contingent on the parameters' estimated population variance σ^2. The partial
pooling of observers' data in a GLMM results in more extreme values being pulled toward
the population mean estimate. Note that in our experiment, however, such pooling is
relatively minor due to the large number of trials, and therefore high precision, of each
observer's estimated performance.

We entered into the model the factors target amplitude, number of filters, and target-
background alignment, which, as noted above, were each entered as an interaction with
the spatial interval of the target. In hindsight, our inclusion of the condition in which target
amplitude was 0 was unnecessary. For all such trials, therefore, we set all predictors to
have a value of 0 so they were omitted from model calculations. The model fit was
improved by including nonlinear terms by raising amplitude and number of Gabors to the
exponents 0.5 and 2, respectively. We further tested all combinations of interactions, but
none improved the model fit as assessed by the Akaike information criterion.

Structural similarity. We quantified the similarity between targets and their
backgrounds using the same approach as Sebastian et al (2017 see their equation S9):

Equation 22 $\qquad\qquad\qquad r_{[i]} = \dfrac{A_{S[i]} \cdot A_{I[i]}}{||A_{S[i]}|| \; ||A_{I[i]}||}$

Where $r_{[i]}$ is the similarity between the steered filter targets (i.e. *S* in Equation 9) and
the background image *I* on trial *i*. $A_{S[i]}$ is the Fourier amplitude spectrum of the filters, and
$A_{I[i]}$ is the Fourier amplitude of the natural image background, both of which are vectors
and were computed by taking the absolute of the complex values of the Fourier
transforms. $r_{[i]}$ is thus a phase-invariant metric. Prior to computing $A_{I[i]}$, we windowed the
natural image background to include only the same regions as the locations of target
filters. This was achieved by first computing a contrast map in which two-dimensional
Gaussians were positioned at each target location. Gaussians had the same standard
deviation as the target filters and had their peaks normalised to one. We then computed
the elementwise product of the source image and this contrast map, which produced the
background image entered into Equation 22.

Results

We tested observers' ability to detect target filters that were blended with natural image backgrounds. Targets were designed such that they were either aligned or misaligned with the structure of the background. We tested detection of 1, 2, 4, 8 and 16 target filters and across a range of target amplitudes. We first describe our results in terms of raw accuracy, and then report the results of our modelling analysis in which we quantified observers' sensitivity in terms of *d'*.

The proportion of correct responses as a function of each factor is shown in Figure 3. The amplitude of the target most clearly impacts accuracy, such that accuracy increases approximately linearly with (log) target amplitude (Figure 3A). Although the relationship between proportion correct and the number of filters is less consistent (Figure 3B), there is a general increase in accuracy with increasing number of target filters. As described below, however, the relationship between number of filters and sensitivity was not significant. We also found a highly consistent effect of target-background alignment across observers (Figure 3C). Contrary to our expectations based on recent reports of similarity masking (Sebastian et al., 2017), however, we found better performance when target filters were aligned with their backgrounds than when they were misaligned with their backgrounds. This difference in performance is significant at the group level ($t(2) = 5.862$, $p = 0.028$, $d = 3.38$), but we more formally quantify the relationship between these factors in a GLMM below. Importantly, given the high measurement precision of these data (1000 observations per data point shown in Figure 3C), we can treat each observer as an independent replication of the effect, regardless of any specific inferential statistic (Smith & Little, 2018).

Figure 3. Proportion correct target identifications based on the three experimental factors: A) Target amplitude, B) Number of filters, and C) Target-background alignment. Colours represent different observers, as indicated by the legend in panel (A). The dotted line in each panel shows chance performance. There were 400 trials per data point in panels (A) and (B), and 1000 trials per data point in panel (C).

We estimated detection sensitivity as a function of the experimental factors with a GLMM. Modelled sensitivity is shown in Figure 4 in the same format as Figure 3. Target amplitude and target-background alignment were both significant contributors to the model. Importantly, as shown in Figure 4C, sensitivity was greater when target filters were aligned with the background than when they were misaligned. The number of filters did not predict sensitivity, which is consistent with the relatively noisier relationship between accuracy and the number of filters as shown in Figure 3B.

Figure 4. Modelled target detection sensitivity. A) Sensitivity varies systematically with target amplitude, but not the number of filters (B). C) Sensitivity depends on the target-background alignment, such that it is greater when filters are aligned with the background than when they are misaligned. Colours denote different observers as per Figure 3.

The perceptual performance described above reveals that observers were better able to detect targets on natural image backgrounds when the targets were aligned with the underlying spatial structure of the background than when the targets were misaligned with the background. These results are contrary to our expectations based on the data of Sebastian et al (2017) who found that sensitivity is inversely correlated with the *structural similarity* between target and background, a metric that scales from zero (no similarity) to one (perfect similarity). We therefore next tested whether observers' performance was instead *positively* correlated with target-background similarity using the same analysis of similarity as in this previous study (Equation 22).

Shown in Figure 5A are the histograms of similarity for all trials across observers, which, by design, can be separated according to the filter alignment relative to the background. The dashed vertical line shows the median similarity of all trials, regardless of target-background alignment. By isolating trials from each condition according to whether they fall above or below this arbitrary cut-off, we can test whether accuracy depends more on similarity or target-background alignment. Figure 5B shows the proportion of correct target detections for aligned and misaligned targets that were most and least similar to the background, respectively. As per the main analyses above, accuracy was greater for aligned than misaligned trials. The more diagnostic analysis is shown in Figure 5C, in which the proportion of correct target detections are shown for aligned trials that were *less* similar than the included misaligned trials (i.e. we limit the analyses to the tails of the similarity distributions). We again find that accuracy was higher for the aligned condition than the misaligned condition, in spite of the aligned targets having lower similarity with the background than the misaligned trials. Therefore, target-background alignment predicts performance much more strongly than target-background similarity.

Figure 5. Analysis of the influence of target-background similarity on perceptual performance. A) Histograms show structural similarity between targets and background separately for the aligned and misaligned conditions. The vertical dashed line is the median similarity of all trials. B) Proportion correct for misaligned trials that were lower in similarity than aligned trials, and vice versa. Accuracy for the misaligned trials is shown to the left of the median, and accuracy for the aligned trials is shown to the right of the median. C) Proportion correct for aligned trials that were lower in similarity than misaligned trials, and vice versa. Accuracy for the aligned trials is shown to the left of the median, and accuracy for the misaligned trials is shown to the right of the median. Note that proportion correct is higher in the aligned condition regardless of similarity. Data points are coloured according to observer, as per Figure 3A.

In a final analysis of perceptual performance, we attempted to replicate the findings of Sebastian et al (2017) using the condition in our experiment that is most analogous to the one in theirs, namely, the misaligned condition. In both this previous study and the misaligned condition of the present study, the blending of target filters and their backgrounds did not depend on any structural alignment. Instead, any incidental alignment can be quantified in terms of structural similarity. We therefore tested whether we found an inverse relationship between target-background similarity and detection accuracy for the misaligned condition. Figure 6 shows proportion correct for trials in similarity bins (bin width = 0.1) for each observer. We modelled these data with logistic regression, with random intercept and slopes grouped by observer (i.e. a logistic GLMM). Fits are shown as solid lines in Figure 6. There is a clear negative relationship between structural similarity and accuracy, with a mean slope of -0.96 (population standard deviation = 0.75). Similarity was not a significant predictor in the model (p = 0.13), but the trends are nonetheless consistent across observers and also with the data of Sebastian et al.

Figure 6. Proportion correct as a function of target-background similarity for misaligned trials only. A-C) show data for each observer, colour coded as in Figure 3. Solid lines are fits from a logistic GLMM, showing a negative relationship between similarity and detection accuracy, as reported by Sebastian et al (2017).

Discussion

We found that observers are better at detecting contrast-defined targets when they
are aligned with a natural image background compared with when they are misaligned
with the natural image background. The superior performance on aligned than misaligned
trials did not depend on the structural similarity of targets relative to backgrounds, in
contrast to the results of Sebastian et al (2017). Because the target filters tended to be
aligned with object edges (i.e. the points of highest contrast in natural images; see Figure
1 and Methods), these data also appear to contradict the findings of Bex et al (2009; see
also Wallis & Bex, 2012). Bex et al found that sensitivity was lower in image regions of
relatively high edge density, whereas we found higher sensitivity when targets were
aligned with edges than when they are randomly positioned.

A potentially simple explanation for the discrepancy between our data and earlier
work concerns the phase alignment of target filters and backgrounds: the *phase* of a target
filter relative to the phase of the local natural image background determines local contrast.
This fact is demonstrated in Figure 7. When target filters are designed to be aligned with
their background structure (left panels), local contrast depends strongly on phase. When
the targets and background are phase-matched, target-background amplitude is additive,
resulting in greater local contrast (top left panel). By inverting the phase of those same
filters, target-background amplitude is subtractive, reducing local contrast (bottom left
panel). Indeed, Bex and Makous (2002) speculated that this dependence of local contrast
on phase alignment explains a loss of sensitivity to phase-scrambled natural images. We
tested this hypothesis directly in Experiment 2.

Aligned (similarity = .89) Misaligned (similarity = .71)

408
Figure 7. A demonstration of the influence of filter phase on local contrast, and examples of
conditions tested in Experiment 2. Added to all panels are the same two target filters that were
designed to be phase-matched with the local spatial structure in the top left panel. Filters in the
bottom row have an inverse phase, and are therefore mismatched relative to the source image.
Filters are most apparent in the top left panel: one filter is aligned with the top horizontal edge of the
cracker, and the other is aligned to the left side of the vertical shadow of the thumb. Note that the
structural similarity metric described by Sebastian et al (2017) is phase invariant, and therefore the
filters have the same similarity score within each column. Target filters are located at the intersection
of pink and blue lines at the edges of each panel. In Experiment 2, we averaged observers'
performance over the misaligned conditions (right column), because phase alignment is relative only
to the source image.

Experiment 2

The results presented above reveal that the alignment of target filters with the spatial structure of the background determines detection sensitivity at least somewhat independently of target-background similarity. In Experiment 2 we tested our hypothesis that aligned targets are easier to detect because their amplitude is additive with the background amplitude, increasing local contrast. We therefore compared detection sensitivity to target filters that were either aligned or misaligned, and were either phase-matched or phase-mismatched with the original source image.

Methods

All methods were identical to those of the preceding experiment, with the following changes. This experiment was carried out in our testing lab on a Display++ monitor (Cambridge Research Systems) with 14bit luminance precision (i.e. our local lockdown had lifted). The experimental design was a 2 (alignment: aligned versus misaligned) x 2 (phase: phase-matched versus phase-mismatched) factorial design (see Figure 7 for example stimuli). All target filters had an amplitude of 0.15, which, based on the data shown in Figure 4, we expected to yield a mean d' of approximately 1. In all trials, there were four filters. Importantly, on half the trials, target filters were blended with the background as per Experiment 1, whereas in the other half of the trials the phase of the filters were reversed before blending. Note that, in the misaligned condition, the phase of the filters relative to the background is somewhat arbitrary, so in the analysis we average across these trials. Each observer completed a total of 800 trials, giving 200 trials per unique condition demonstrated in Figure 7. Testing took approximately 30 minutes per observer.

Results

In Experiment 2, we included conditions that provided an opportunity to replicate our findings from Experiment 1. As demonstrated in the top left panel of Figure 7, we included a condition in which target filters were both aligned and phase-matched to the natural background structure, as per the aligned condition of Experiment 1. We first compare observers' accuracy in this condition with the accuracy in the misaligned condition. The results are shown as connected points in Figure 8A, and reveal better performance in the (phase-matched) aligned condition than the misaligned condition for all observers. We therefore replicate the results from Experiment 1 under strict laboratory conditions. Also shown in Figure 8A are the results from the phase-mismatched condition, in which target filters were aligned with their backgrounds, but had their phase inverted. Importantly, phase-matched and phase-mismatched targets were well equated on similarity (phase-matched and phase-mismatched average similarities were .7 and 0.71, respectively). In the phase-mismatched condition, however, all observers were close to chance level, revealing they were unable to detect these targets (mean accuracy = 49%; RR = 45%, RW = 50%, WH = 51%).

Figure 8. Proportion of correct target detections in Experiment 2. A) Results are shown according to the two main experimental factors: target-background alignment (x-axis) and target-background phase alignment (grouped data points). Note that target-background similarity is matched across aligned conditions (see left column of Figure 7). Colours indicate different observers as per Figure 3. B-D) Proportion correct as a function of target-background similarity for misaligned trials only. Solid lines are fits from a logistic GLMM, showing a positive relationship between similarity and detection accuracy, in contrast to the fits of Experiment 1 data and results reported by Sebastian et al (2017).

We again tested whether there was an inverse relationship between accuracy and similarity in the condition most closely matching the condition tested by Sebastian et al (2017), i.e. the misaligned condition (see Figure 6). We again used a logistic GLMM, and similarity was binned in 0.1 steps. In contrast to the fitted model in Experiment 1, however, we found a non-significant positive relationship between similarity and proportion correct (slope = 0.33, population standard deviation = 0.28, p = 0.596). Fits to observers' data are shown in Figure 8B-D.

Discussion

The aim of Experiment 2 was to test the prediction that targets aligned with their natural image backgrounds are easier to identify than targets that are misaligned with their backgrounds (i.e. the results of Experiment 1) due to a difference in local contrast. The differences in local contrast across these conditions results from contrast additivity in the aligned condition when filters are phase-matched with their background. We tested this prediction in Experiment 2 by inverting the phase of target filters on half of the trials in which the filters were aligned with the background structure. Inverting the phase of target filters aligned with their background has a subtractive effect on local contrast, and, as we expected, rendered observers incapable of detecting the targets (Figure 8). The results of Experiment 2 thus support the notion that target-background similarity is not a useful metric of the detectability of targets per se, whereas phase-matched structural alignment is critical.

General Discussion

The aim of the present study was to test observers' ability to detect contrast-defined targets that have been blended with natural image backgrounds. We designed the target filters so that their orientations were either aligned or misaligned with the local background structure. Based on the recent report that detection sensitivity is inversely related to target-background similarity (Sebastian et al., 2017), we expected to find worse performance in the aligned condition relative to the misaligned condition. Across two experiments, however, we found superior detection of targets that were aligned and phased-matched to the structure of the background compared with targets that were misaligned with their backgrounds and were thus lower in similarity.

Our experiments show that observers' sensitivity does not linearly scale with similarity. In Experiment 1 we found a positive relationship between similarity and sensitivity: observers were most sensitive to targets in which target filters were aligned

with, and most similar to, background structure (Figure 3C and Figure 4C). We replicated
this finding in Experiment 2 (Figure 8A). When we limited our analyses to only trials in
which target filters were misaligned with the background structure, we found mixed results
across the two experiments: a negative relationship between detection accuracy and
target-background similarity in Experiment 1 (Figure 6), but a positive relationship in
Experiment 2 (Figure 8C-D). The cause of this difference in results across experiments is
not clear, but we note that we did not design either experiment to specifically measure the
relationship between similarity and sensitivity in this way, and neither model was
significant. Regardless, there was no clear evidence of an inverse relationship as
expected.

The limitation of similarity as a predictor of sensitivity is most apparent in our
Experiment 2 results. By matching or inverting the phase of filters aligned with the
background structure, we produced target-background images that were equivalent in
similarity but were different in their detectability (Figure 7 and Figure 8A). When phase was
inverted relative to the background, observers' performance was at chance level. The
phase-mismatched condition therefore removed the information observers depended on to
perform the task (i.e. contrast). A variant of the metric of similarity used here and by
Sebastian et al (2017) may better predict sensitivity if it encodes phase information.
However, Sebastian et al. used targets and a template-matching ideal observer model that
had a fixed phase, in which case sensitivity may indeed scale inversely with similarity. We
also note that the similarity between target filters and backgrounds in our study was
approximately double those reported by Sebastian et al, and so it is possible that a linear
inverse influence of similarity on sensitivity holds for relatively low levels of similarity.

Detection thresholds in our experiments are approximately an order of magnitude
greater than those reported by Sebastian et al. This is not particularly surprising given that
we did not attempt to replicate their design, and instead used stimuli and methods that
differed from theirs. One particular aspect of our experiments that would have likely
decreased sensitivity was the lack of spatial certainty in the position of targets. Target
filters could appear anywhere within the natural image background, maximising spatial
uncertainty. The ability to identify targets depends on spatial (un)certainty, particularly in
peripheral vision (Harrison & Bex, 2015, 2017; Levi et al., 1987). Sebastian et al reduced
spatial uncertainty by presenting targets at the same location on each target-present trial.
Lower thresholds should be expected with such reduced uncertainty relative to our
experiment in which observers had to search the entire background region.

We used images from the THINGS database as naturalistic backgrounds. The
THINGS database is a recently released database with over 26,000 images from 1854
categories (Hebart et al., 2019). Relatively little has been reported about the basic
statistical properties of the images in this database, and so it is possible that they may
deviate from what one may expect from typical natural images. In Figure 9 we show the
mean image spectra as a function of spatial frequency and orientation. This analysis
shows that THINGS images have, on average, the same basic image spectra as typically
found in natural images: contrast energy decreases with increasing spatial frequency
(Figure 9A), and there is an over representation of cardinal orientations (Figure 9B). It is
therefore unlikely that something in particular about the distribution of contrast energy in
the THINGS images played a key role in our results. However, it is likely that the visual
system performs different operations when processing visual objects like those in the
THINGS images compared with visual textures (Wallis et al., 2019). Sebastian et al (2017)
used images of scenes that had no particular focus on objects per se. To the best of our
knowledge, no study has investigated whether target detection differs on backgrounds of
things versus backgrounds of stuff.

Figure 9. Mean spectra of all images in the THINGS database. A) Mean contrast energy as a function of spatial frequency. The solid line is the fit of the function $1/f^{\alpha}$, which explains 99% of the variance. The free parameter, α, was 1.2. B) Mean contrast energy as a function of orientation. We computed contrast energy in the frequency domain using a series of raised cosine filters centred on a given orientation and spanning all spatial frequencies ("bow-tie filters"; full width half height = 12.5°). These data were then fit with a function that captures the over-representation of cardinals, as well as the greater contrast energy for horizontal contrast compared with vertical contrast [1]. This function explains 99% of the variance.

Several studies suggest that there are high-level influences over the tuning of low-level feature detectors like those used to detect targets in the present study. For example, Teufel et al (2018) found that prior knowledge about image content influences the detectability of oriented targets aligned to locally occluded edges. Neri (2017) similarly found that sensitivity is greatest on edges implied by image content, regardless of whether local contrast detectors would respond at the region of the target. Harrison & Rideaux (2019) further showed that edge detection in visual noise can be greatly influenced by the allocation of visual attention. Taken together, these findings suggest that the detectability of targets in the present study may have depended on the specific objects in background images, and how combinations of low-level and high-level factors guided observers' visual attention. However, we did not design our experiments to examine such possible differences across object images. The availability of repositories such as the THINGS database makes such questions possible to address in future studies.

In summary, we tested observers' ability to detect targets in natural image backgrounds. Observers were most sensitive to targets when they were aligned and phase-matched with their backgrounds. Inverting the phase of aligned targets reduced observers' detection performance to chance. To best model the image factors that predict human sensitivity to contrast defined targets in natural backgrounds, therefore, the phase of the target relative to the background must be considered.

---

[1] This function has the form: $E = (a - mag * |sin(2\theta)|^{b}) * (p * (cos(2\theta)) + p + 1)$, where E is contrast energy, θ is orientation in radians, and a, mag, b, and p are free parameters.

Author contributions

581   WJH and PJB designed the stimulus generation method and conceived the general
582 idea. WJH designed Experiment 1. WJH, RR, and JBM designed Experiment 2. WJH, RR,
583 and RKW conducted the experiments. WJH conducted all analyses and generated all
584 figures. RR, RKW and WJH wrote the first draft of the manuscript. All authors reviewed
585 and edited the manuscript.

Acknowledgements

587   This research was supported by an Australian Research Council Discovery Early
588 Career Award to WJH (DE190100136) and RR (DE210100790). JBM was supported by
589 the Australian Research Council (ARC) Centre of Excellence for Integrative Brain Function
590 (ARC Centre Grant CE140100007). PJB was supported by a National Institute of Health
591 R01 (EY029713).

References

Andrew Gelman, & Hill, J. (2007). *Data Analysis Using Regression and*
Multilevel/Hierarchical Models. Cambridge University Press.

Balas, B., Nakano, L., & Rosenholtz, R. (2009). A summary-statistic representation in
peripheral vision explains visual crowding. *Journal of Vision*, *9*(12), 1–18.
https://doi.org/10.1167/9.12.13

Barlow, H. B. (1961). Possible Principles Underlying the Transformations of Sensory
Messages. In W. A. Rosenblith (Ed.), *Sensory Communication* (Vol. 1, pp. 216–
234). The MIT Press. https://doi.org/10.7551/mitpress/9780262518420.003.0013

Barlow, H. B. (1972). Single Units and Sensation: A Neuron Doctrine for Perceptual
Psychology? *Perception*, *1*(4), 371–394. https://doi.org/10.1068/p010371

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects
Models Using lme4. *Journal of Statistical Software*, *67*(1), 1–48.
https://doi.org/10.18637/jss.v067.i01

Bex, P. J., & Makous, W. (2002). Spatial frequency, phase, and the contrast of natural
images. *Journal of the Optical Society of America A*, *19*(6), 1096–1106.
https://doi.org/10.1364/JOSAA.19.001096

Bex, P. J., Solomon, S. G., & Dakin, S. C. (2009). Contrast sensitivity in natural scenes
depends on edge as well as spatial frequency structure. *Journal of Vision*, *9*(10), 1–
19. https://doi.org/10.1167/9.10.1

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*(4), 433–436.

Cadena, S. A., Denfield, G. H., Walker, E. Y., Gatys, L. A., Tolias, A. S., Bethge, M., &
Ecker, A. S. (2019). Deep convolutional models improve predictions of macaque V1
responses to natural images. *PLOS Computational Biology*, *15*(4), e1006897.
https://doi.org/10.1371/journal.pcbi.1006897

Campbell, F. W., & Robson, J. G. (1968). Application of Fourier analysis to the visibility of
gratings. *The Journal of Physiology*, *197*(3), 551–566.

Carandini, M., Demb, J. B., Mante, V., Tolhurst, D. J., Dan, Y., Olshausen, B. A., Gallant,
J. L., & Rust, N. C. (2005). Do we know what the early visual system does? *Journal*
of Neuroscience, *25*(46), 10577–10597. https://doi.org/10.1523/JNEUROSCI.3726-
05.2005

Dorr, M., & Bex, P. J. (2013). Peri-Saccadic Natural Vision. *Journal of Neuroscience*,
33(3), 1211–1217. https://doi.org/10.1523/JNEUROSCI.4344-12.2013

Field, D. J. (1987). Relations between the statistics of natural images and the response
properties of cortical cells. *JOSA A*, *4*(12), 2379–2394.
https://doi.org/10.1364/JOSAA.4.002379

Freeman, W. T., & Adelson, E. H. (1991). The design and use of steerable filters. *IEEE*
Transactions on Pattern Analysis & \Idots.
http://www.computer.org/csdl/trans/tp/1991/09/i0891.pdf

Geisler, W. S. (2008). Visual Perception and the Statistical Properties of Natural Scenes.
Annual Review of Psychology, *59*(1), 167–192.
https://doi.org/10.1146/annurev.psych.58.110405.085632

Greenwood, J. A., Bex, P. J., & Dakin, S. C. (2010). Crowding changes appearance.
Current Biology, *20*(6), 496–501. https://doi.org/10.1016/j.cub.2010.01.023

Greenwood, J. A., Bex, P. J., & Dakin, S. C. (2012). Crowding follows the binding of relative position and orientation. *Journal of Vision, 12*(3). https://doi.org/10.1167/12.3.18

Harrison, W. J., & Bex, P. J. (2014). Integrating retinotopic features in spatiotopic coordinates. *Journal of Neuroscience, 34*(21), 7351–7360. https://doi.org/10.1523/JNEUROSCI.5252-13.2014

Harrison, W. J., & Bex, P. J. (2015). A unifying model of orientation crowding in peripheral vision. *Current Biology, 25*(24), 3213–3219. https://doi.org/10.1016/j.cub.2015.10.052

Harrison, W. J., & Bex, P. J. (2017). Visual crowding is a combination of an increase of positional uncertainty, source confusion, and featural averaging. *Scientific Reports, 7*, 45551. https://doi.org/10.1038/srep45551

Harrison, W. J., & Rideaux, R. (2019). Voluntary control of illusory contour formation. *Attention, Perception, and Psychophysics, 81*(5), 1522–1531. https://doi.org/10.3758/s13414-019-01678-8

Haun, A. M., & Peli, E. (2013). Perceived contrast in complex images. *Journal of Vision, 13*(13), 3. https://doi.org/10.1167/13.13.3

Hebart, M. N., Dickter, A. H., Kidder, A., Kwok, W. Y., Corriveau, A., Wicklin, C. V., & Baker, C. I. (2019). THINGS: A database of 1,854 object concepts and more than 26,000 naturalistic object images. *PLOS ONE, 14*(10), e0223792. https://doi.org/10.1371/journal.pone.0223792

Hubel, D. H., & Wiesel, T. N. (1959). Receptive fields of single neurones in the cat's striate cortex. *The Journal of Physiology, 148*, 574–591.

Levi, D. M., Klein, S. A., & Yap, Y. L. (1987). Positional uncertainty in peripheral and amblyopic vision. *Vision Research, 27*(4), 581–597.

Macmillan, N. A., & Creelman, C. D. (2004). *Detection theory: A user's guide.* https://doi.org/10.1016/0376-6357(93)90083-4

Neri, P. (2014). Dynamic engagement of human motion detectors across space-time coordinates. *Journal of Neuroscience, 34*(25), 8449–8461. https://doi.org/10.1523/JNEUROSCI.5434-13.2014

Neri, P. (2017). Object segmentation controls image reconstruction from natural scenes. *Plos Biology, 15*(8), e1002611. https://doi.org/10.1371/journal.pbio.1002611

Olshausen, B. A., & Field, D. J. (2005). How close are we to understanding v1? *Neural Computation, 17*(8), 1665–1699. https://doi.org/10.1162/0899766054026639

Parraga, C. A., Troscianko, T., & Tolhurst, D. J. (2000). The human visual system is optimised for processing the spatial information in natural visual images. *Current Biology.* http://www.sciencedirect.com/science/article/pii/S0960982299002626

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: Transforming numbers into movies. *Spatial Vision, 10*(4), 437–442.

Sebastian, S., Abrams, J., & Geisler, W. S. (2017). Constrained sampling experiments reveal principles of detection in natural scenes. *Proceedings of the National Academy of Sciences of the United States of America, 114*(28), E5731–E5740. https://doi.org/10.1073/pnas.1619487114

Simoncelli, E. P., & Olshausen, B. A. (2001). Natural image statistics and neural
representation. *Annual Review of Neuroscience*, *24*, 1193–1216.
https://doi.org/10.1146/annurev.neuro.24.1.1193

Smith, P. L., & Little, D. R. (2018). Small is beautiful: In defense of the small-N design.
Psychonomic Bulletin & Review, 1–19. https://doi.org/10.3758/s13423-018-1451-8

Teufel, C., Dakin, S. C., & Fletcher, P. C. (2018). Prior object-knowledge sharpens
properties of early visual feature-detectors. *Scientific Reports*, *8*(1), 10853.
https://doi.org/10.1038/s41598-018-28845-5

Wallis, T. S. A., & Bex, P. J. (2012). Image correlates of crowding in natural scenes.
Journal of Vision, *12*(7), 1–19. https://doi.org/10.1167/12.7.6

Wallis, T. S. A., Dorr, M., & Bex, P. J. (2015). Sensitivity to gaze-contingent contrast
increments in naturalistic movies: An exploratory report and model comparison.
Journal of Vision, *15*(8), 3. https://doi.org/10.1167/15.8.3

Wallis, T. S. A., Funke, C. M., Ecker, A. S., Gatys, L. A., Wichmann, F. A., & Bethge, M.
(2019). Image content is more important than Bouma's Law for scene metamers.
ELife, *8*, e42512. https://doi.org/10.7554/eLife.42512

697