*Two distinct networks containing position-tolerant representations of actions in the*

*human brain*

Elahé Yargholi[1*], Gholam-Ali Hossein-Zadeh[1,2], Maryam Vaziri-Pashkam[3]

[1] School of Cognitive Sciences, Institute for Research in Fundamental Sciences, Tehran, Iran

[2] School of Electrical and Computer Engineering, College of Engineering, University of Tehran,

Tehran, Iran

[3] National Institute of Mental Health (NIMH), Laboratory of Brain and Cognition, MD, USA

*corresponding author: elahe.yargholi@gmail.com, elahe.yargholi@ut.ac.ir

**Abstract**

Humans can recognize other people's actions in the social environment. This action recognition

ability is rarely hindered by the movement of people in the environment. The neural basis of this

tolerance to changes in the position of observed actions is not fully understood. Here, we aimed

to identify brain regions capable of generalizing representations of actions across different

positions and investigate the representational content of these regions. fMRI data were

recorded from twenty-two subjects while they were watching video clips of ten different human

actions in Point Light Display format. Each stimulus was presented in either the upper or the

lower visual fields. Multivoxel pattern analysis and a searchlight technique were employed to

identify brain regions that contain position-tolerant action representation: linear support vector

machine classifiers were trained with fMRI patterns in response to stimuli presented in one

position and tested with stimuli presented in another position. Results of this generalization test

showed above-chance classification in the left and right lateral occipitotemporal cortex, right

intraparietal sulcus, and right post-central gyrus. To explore the representational content of

these regions, we constructed models based on the objective measures of movements and

human subjective judgments about actions. We then evaluated the brain similarity matrix from

the cross-position classification analysis based on these models. Results showed cross-position

classifications in the lateral occipito-temporal ROIs were more strongly related to the subjective

judgments, while those in the dorsal parietal ROIs were more strongly related to the objective

movements. An ROI representational similarity analysis further confirmed the separation of the

dorsal and lateral regions. These results provide evidence for two networks that contain abstract

representations of human actions with distinct representational content.

*Keywords:* action observation, position invariance, fMRI, multivariate pattern analysis.

                                                    **Introduction**

Humans can rapidly and accurately recognize other people's actions in the social

environment. People's movement in the environment introduces often dramatic changes in the

viewpoint, size, and position of their image on the retina. This confounding variability renders

the action recognition task computationally challenging. Yet, humans' ability to recognize

actions is rarely hindered by this variability. A brain region that subserves human action

recognition ability is expected to: 1) contain information about various human actions and 2)

contain action representations that are tolerant to the variability in the visual input. Here, using

functional MRI and multi-voxel pattern analysis, we aim to identify such regions using changes

in the position of the actor as the source of variability. After identifying these regions, we aim to

explore their representational content and determine to what extent they relate to human

subjective judgments about actions or objective measures of body movements.

Previous studies that have explored tolerance of visual representations to variability in the input

have mostly focused on static pictures of objects and human bodies. Regions in both

occipitotemporal (Konen and Kastner, 2008; Cichy et al., 2011, 2013; Anzellotti et al., 2013;

Ramírez et al., 2014) and parietal cortices (Konen and Kastner, 2008) have been identified that

contain position, size, and viewpoint tolerant representation of static objects (Konen and

Kastner, 2008; Mur et al., 2010; Cichy et al., 2011, 2013; Anzellotti et al., 2013; Ramírez et al.,

2014; Xu and Vaziri-Pashkam, 2020). This characteristic has been proposed as a defining

feature of regions that contribute to human abstract object knowledge (Dicarlo and Cox, 2007).

In the domain of observed actions, despite the large body of literature that identifies regions in

the occipitotemporal and parietal cortices that respond to (Casper et al., 2010; Kalenine et al.,

2010; Grosbras et al., 2012; Watson et al., 2013; Urgesi et al., 2014) and contain information

about (e.g., Wheaton et al., 2004; Jastorff et al., 2010; Abdollahi et al., 2013;  Lignau and

Downing, 2015; Ferri et al., 2015; Hafri et al., 2017; Wurm et al., 2017b; Urgen et al., 2019;

Tucciarelli et al., 2019; Tarhan and Konkle, 2020; Urgen and Orban, 2021) observed actions,

evidence for the tolerance of these representations to changes in the position of the actors is

still scant.

Previous studies have extensively investigated the tolerance of action representations to

changes in viewpoint in both monkeys (Oram and Perrett, 1996; Vangeneugden et al., 2014;

Caggiano et al., 2011; Maeda et al., 2015; Maranesi et al., 2015; Barz et al., 2017; Simone et

al., 2017; Livi et al., 2019; Albertini et al., 2020; Lanzilotto et al., 2020) and humans (Grossman

et al., 2010; Ogawa and Inui, 2011; Oosterhof et al., 2012; Tucciarelli et al., 2015; Isik et al.,

2016). Results of these human studies provide evidence for viewpoint tolerance in the lateral

occipito-temporal (Grossman et al., 2010; Tucciarelli et al., 2015) and parietal cortices (Ogawa

and Inui, 2011; Oosterhof et al., 2012). In contrast to viewpoint tolerance, position tolerance has

not been extensively explored. Grossman et al. (2010) employed an fMRI adaptation approach

to investigate position tolerance in the human brain.  They found that a region in human STS

shows tolerance to variations in the position of observed actions. They did not systematically

investigate the position sensitivity of parietal action selective regions. The fMRI adaptation

technique used in this study may not have sufficient power in identifying the full scope of

position tolerance in action selective regions compared to other techniques such as multi-voxel

pattern analysis (MVPA, Haxby, 2012) that directly investigate the representational content of a

region. Roth and Zohary (2015) employed MVPA (correlation and cross-decoding) to study

position tolerance during observation of tool-grasping movements in humans. Their stimuli were

presented in various locations, and position tolerance was examined for presentations in the left

and right visual fields. They discovered that position information is gradually lost, and hand/tool

identity information is enhanced along the posterior-anterior axis in the dorsal stream. However,

their study was limited to grasping movements. It is not obvious if their results would generalize

to full-body movements.

Other studies that have employed MVPA have often used natural stimuli in which actions

happen at different positions, but they have averaged the responses across stimuli instead of

systematically investigating the tolerance of representations across changes in position.

Therefore it is hard to speculate about the extent of position tolerance in action selective regions

from these studies (Hafri et al., 2017; Wurm et al., 2017b; Tarhan and Konkle, 2020). As such, a

systematic investigation of position tolerance across dorsal and ventral action selective regions

is still missing in the literature. In this study, we will use MVPA and cross-position decoding

using a support vector machine classifier to search for position tolerant representations of

actions in the human brain. Finding these regions, we will then investigate their representational

content using a representational similarity analysis (Kriegeskorte et al., 2008).

Several theories have been proposed to characterize the role of individual action

selective regions in the processing of action stimuli. In the occipito-temporal cortex, a division of

labor has been suggested between regions such as EBA that process the form of the body and

regions such as STS that process the movement of the body (Giese & Poggio, 2003; Peelen et

al., 2006; Grossman et al., 2010; Michels et al., 2005; Downing et al., 2006; Vangeneugden et

al., 2016 refs from Vangeneugden; Jastorff and Orban, 2009). These studies do not elaborate

on the representational content of these regions. A few studies have taken a step further to

establish the principles of coding in action selective regions. Within the lateral occipital cortex,

Wurm et al. (2017b) have suggested that the neural representation of hand actions is organized

based on the extent of sociality and transitivity of these actions. Recently, in a study with a large

set of natural images of actions, Tucciarelli et al. (2019) compared the similarity in neural

representation with their semantic similarity obtained from behavioral ratings. They showed that

the neural organization of observed actions in the lateral occipito-temporal cortex is correlated

with the behavioral similarity judgments.

Investigations to the representational content of parietal action selective regions are

fewer in number, and their results are more subject to debate. Shmuelof and Zohary (2006,

2008) have proposed an effector dependent representation of hand actions in the anterior

intraparietal cortex, while others have argued actions are represented in an effector

independent manner in the inferior parietal lobe (Jastorff et al., 2010) as well as superior parietal

lobe and intraparietal sulcus (Vingehoets et al., 2012). One study (Jastorff et al., 2010)

suggested that action representations in the parietal cortex are related to the direction of the

action relative to the body.

Looking at the entire visual system, Tarhan and Konkle (2020) used an encoding model

to predict responses to natural videos. The feature space of their model captured the body parts

involved in an action and the action target. Based on the voxel tunning, they suggested that five

large-scale networks exist in the human brain that represent actions based on their sociality and

the spatial extent of their interaction envelope. All these studies have employed natural videos

of actions in which often a whole scene and objects are present. Employing natural stimuli may

lead to many confounding factors and difficulties in interpreting the results. Even though some

of these studies have taken steps to make sure low-level features are not contributing to their

results (Tucciarelli et al., 2019; Tarhan and Konkle, 2020), there is a possibility their results may

be related to the presence of special types of objects, scene contexts and semantic relations

between them (Kourtzi and Kanwisher, 2000; Senior et al., 2000; Johnson-Frey, 2004;

Buxbaum et al., 2006; Wurm et al., 2012; Schubotz et al., 2014; el-sourani et al., 2017; Wurm

and Schubotz, 2017; Wurm et al., 2017a; Leshinskaya et al., 2018).

Here, employing fMRI multivoxel pattern analysis, we decoded the position invariant

representation of human actions in point-light display (PLD) format. We used controlled stimuli

in PLD format to restrict the visual information to the bodily movements and identify regions

supporting abstract action representations. Using these controlled action stimuli, we localized

regions where action decoding was robust to changes in position. Employing PLD stimuli also

allowed us to determine the position and movements of individual limbs, to devise objective

measures for constructing similarity between actions. Using these objective measures of

similarity as well as subjective measures derived from behavioral experiments, we characterized

the representational content of action selective regions.

**Materials and Methods**

**Participants**

Twenty-five subjects (14 females, 20-38 years of age) took part in the fMRI experiment and 15 subjects (13 females, 25-38 years of age) took part in the behavioral experiment. All subjects were healthy and right-handed with normal visual acuity. They gave written informed consent and received payment for their participation. The experiments were approved by the ethics committee on the use of human subjects at the Iran University of Medical Sciences. Three fMRI subjects were later excluded due to excessive motion (see data analysis for more details) and the final analyses included the remaining 22 subjects.

**Functional MRI experiment**

In this experiment, we used videos of 10 different human actions in Point Light Display (PLD) format: Crawl, Cycle, Jumping Jack (henceforth referred to as Jump), Peddle, Play tennis, Salute, Spade, Stir, Walk, and Wave (Figure 1). These actions were selected from a larger set of human action videos in PLD format provided by Vanrie and Verfaillie (2004). We used a block design paradigm. Each run included twenty blocks with two blocks for each human action video. In one of the blocks for each action, the video was presented in the upper visual hemifield, and in the other, it was presented in the lower visual hemifield. The presentation order of the stimuli was counterbalanced across runs. Each block lasted 8 seconds. There was an 8-second blank period in the beginning, end, and between stimulus blocks of each run. Each run lasted 328 seconds. Each subject completed one session of 10 runs.

In each stimulus block, there were four repetitions of the same human action video. Each repetition lasted 1.5 seconds (frame rate 30), followed by a 0.5 second blank period. In a randomly chosen repetition in each block, the size of the dots became 50% larger for one

second. The point-lights, subtending ~0.25 degrees of visual angle, were in white color against

a black background. The center of the stimuli was presented ~4 degrees of visual angle

above/below the fixation point. The size of the area that the dots occupied during movements

was between 0.94 and 5.62 degrees in width and between 2.38 and 7.7 degrees in height.

The fixation point was a red circle of size ~0.25 degrees of visual angle. Subjects were

instructed to fixate on the fixation point at the center of the screen, watch the videos, detect the

change in the size of the point lights, and report it by pressing a response key with their right

index finger.

**Behavioral experiment**

To capture the similarity between our human action stimuli, we conducted a behavioral

experiment based on an inverse multi-dimensional scaling (IMDS) method proposed by

(Kriegeskorte & Mur, 2012). At the beginning of the experiment, one snapshot from each of the

ten action videos was presented along with a number 1-10 in two vertical columns at the left

border of the screen. On a separate screen, they were provided with numbered action videos,

and they could watch them as many times as they needed. Participants were asked to

rearrange the snapshots on the surface of a gray circle (drag and drop using the mouse)

according to the perceived similarity of their corresponding videos. The arrangement was

performed based on subjective judgments of overall similarity, and no other instructions were

given regarding the specific aspects they needed to focus on for the arrangement. A behavioral

dissimilarity matrix was obtained based on the final Euclidean distances on the circle for each

participant.

**MRI methods**

MRI data were collected at two centers: the school of Cognitive Sciences, Institute for

Research in Fundamental Sciences (Tehran, Iran) using a Siemens 3T Tim Trio MRI scanner

and a 32-channel head coil and the National Brain Mapping Lab (Tehran, Iran) using a Siemens

3T Prisma MRI scanner and 20-channel or 64-channel head coil. We were forced to switch MRI

equipment mid-experiment due to scanner/coil malfunction (data of 5 subjects were recorded at

the school of Cognitive Sciences, and data of 20 subjects were recorded at National Brain

Mapping Lab). We moved scanners to ensure that high-quality data was collected for all

subjects. Similar protocols were used across scanners, and the data recorded with different

equipment were comparable.

Subjects viewed the visual stimuli through a back-projection screen, and the task was

presented using MATLAB and Psychtoolbox-3 (Brainard, 1997). Functional images were

obtained using a $T2^*$-weighted single-shot gradient-echo EPI sequence with a repetition time

(TR) of 2 s, echo time (TE) 26, 90° flip angle, 30 transverse slices, and a voxel size of 3 × 3 × 4

$mm^3$. A high-resolution T1-weighted structural scan was also acquired from each participant

using an MPRAGE pulse sequence (TR = 1800 ms, TE = 3.44 ms, inversion time = 1100 ms, 7°

flip angle, 176 sagittal slices, and 1 × 1 × 1 $mm^3$ isotropic voxels).

**Data analysis**

Freesurfer (https://surfer.nmr.mgh. harvard.edu) and FS-FAST (Dale et al., 1999) were

employed for data preprocessing and general linear model (GLM) analysis. Preprocessing of

fMRI data included motion correction, slice timing correction, linear and quadratic trend removal,

and no spatial smoothing. Subjects with excessive head motion (more than 1.5 mm within a run

and 4 mm across runs) were excluded (3 subjects). Functional data were then resampled to the

cortical surface of individual subjects.

A run-wise GLM analysis was performed to obtain the beta values and their

corresponding t statistic for each human action and each presentation hemifield in each vertex

(10 human actions in the upper visual field and 10 human actions in the lower visual field

leading to 20 regressors). Linear and quadratic polynomial nuisance regressors and external

regressors from the estimated head movements were also included.

Wang atlas of visual topography (Wang et al., 2014) was used to localize retinotopic

areas for each subject: V1, V2, V3, hV4, VO1, VO2, MST, hMT, LO2, LO1, V3a, V3b, IPS0,

IPS1, IPS2, IPS3, IPS4, IPS5, SPL1 (Figure 3).

**Multivariate pattern analysis (MVPA)**

In-house MATLAB codes, LibSVM (Chang and Lin, 2011), and CoSMoMVPA (Oosterhof

et al., 2016) toolboxes were employed for searchlight and ROI analyses.

*Searchlight analysis*:

We performed action classification using a surface-based searchlight procedure to

obtain a map of classification accuracy (Oosterhof et al., 2011). In a leave-one-run-out cross-

validation procedure, samples (t-statistics of vertices) were partitioned to train and test sets. A

linear Support Vector Machine (SVM) was employed to perform pairwise brain decoding

classification for each presentation position (upper/lower visual hemifield) in individual brains

with a searchlight circle of 100 vertices on the surface. The decoding accuracy of a searchlight

was calculated as the average of all within position pairwise classification accuracies. The

resulting maps were then resampled to a common surface for the group-level statistical

analysis.

To determine regions showing position tolerance, we performed cross-position decoding

by training a classifier to discriminate pairs of actions presented in one position and testing its

accuracy in classifying the same pair of actions in the other position. A cross-position decoding

accuracy greater than the chance level would indicate position tolerance.

To obtain group-level statistics, p-values of classification accuracies were computed

using a binomial test, corrected for false discovery rate (Benjamini and Hochberg, 1995) at level

q1. The second-level p-value for each vertex was then determined as

243
$$Pr\left[Binomial(n, R * q1/(n * m)) \geq C\right]$$

With *C* denoting the number of participants for which that vertex was significant, *R* denoting the

sum of the counts of *C* across all vertices, *n* denoting the number of participants, and *m*

denoting the number of vertices. Under the null hypothesis, *C* has a binomial distribution with

size n and a probability that is approximately bounded by $R * q1/(n * m)$. Finally, the derived

second-level p-values were thresholded at the FDR level q2 to acquire the significant vertices at

the group-level (McMahon et al., 2019). This approach is more appropriate than the t-test for

comparing classification accuracies against chance level (See Allefeld et al., 2016 for a

discussion of why the t-test is not suitable in such cases).

From the searchlight group-level statistical analysis, we obtained clusters with significant

cross-positions classification accuracy. Contiguous clusters that passed the threshold were

selected as ROIs in which decoding of actions could be generalized across positions and used

in the next analyses to explore their representational structure. To ascertain that the ROI

selection and further analyses are statistically independent and prevent double-dipping, we

used a leave-one-subject-out approach (Etzel et al., 2013). The group-level statistical analysis

was applied to the searchlight results of all subjects except one, and the resulting ROI was

projected on the left-out subject to select the ROI in that subject. The procedure was repeated

for each subject. The same clusters were found consistently across all iterations.

***Comparing within and cross-position classification accuracies***

To directly compare within and cross-position classification accuracies, we performed

SVM classifications within each ROI obtained from the leave-one-subject out analysis described

above. The procedure for obtaining within- and cross-position classifications was the same as

the searchlight analysis with the addition of feature selection. Different ROIs don't include the

same number of vertices. This variation in the number of vertices across ROIs could influence

classification accuracies. To avoid this potential confounding factor, the pairwise classifications

were performed using the 100 most informative vertices in each ROI. To select the most

informative vertices, a t-test was applied on the training set, and 100 vertices with the lowest p-

values for discriminating between the conditions of interest in the training set were chosen

(Mitchell et al., 2004). It is noteworthy that the classification results didn't qualitatively differ

without feature selection.

***Exploring the representational content of the ROI***

To explore the representational content of the ROIs, we constructed models based on

the body-part movements and behavioral ratings and examined the correlation between these

models and the cross-position decoding accuracies for each ROI.

To obtain the body-part movement model, we divideded the point lights into five groups:

trunk (5 dots), left hand (2 dots), right hand (2 dots), left leg (2 dots), and right leg (2 dots). We

obtained the sum of the displacements of point lights in each group for each action video. From

the total displacements in each group, we obtained a five-element vector. Then, the Euclidean

distance between these five-element vectors was used to obtain a dissimilarity matrix based on

the body-part movement. This body-part movement model includes information on both the

pattern of body-part movement and the average of their movement for each action. Hence, for

further investigation, we examined two other models: body-movement-pattern and body-

movement-average. To obtain the body-movement-pattern model for each action, we

demeaned the corresponding five-element vector of the body-part movement model and

obtained the Euclidean distance between these new demeaned vectors to build a dissimilarity

matrix. The difference between the average values of body-part movement vectors was also

used to obtain the body-movement-pattern model.

To obtain the behavioral dissimilarity model, the results from the behavioral experiment

were used. In the behavioral experiment, the distance between stimuli indicates their

(dis)similarity. The obtained dissimilarity matrix for each subject was normalized by dividing

each value in the matrix by the maximum value. The pooled behavioral dissimilarity matrix was

then computed as an average of individual normalized behavioral dissimilarity matrices.

295  To obtain the correlation between the models and the action representations in each

296 ROI, the off-diagonal of the matrix obtained from the pairwise cross-position decoding

297 accuracies was vectorized. The off-diagonal of the dissimilarity matrices from the models were

298 also vectorized. The Kendall rank correlation between dissimilarity vectors and decoding

299 accuracy vectors was then calculated, and the correlation values were compared to

300 characterize the representational content of each ROI.

301 ***ROI similarity analysis***

302  We also performed the cross-position decoding accuracies for Wang's ROIs using a

303 similar procedure as that used for the ROIs obtained from the searchlight analysis. Following a

304 leave-one-run-out approach, a classifier was trained to decode pair of actions presented in one

305 position and tested with the same pair of actions in another position. We applied a t-test on the

306 training set to choose 100 vertices with the lowest p-values for discriminating between the

307 actions of interest in each ROI. Then, to investigate the representational similarity between

308 ROIs (Wang's ROIs and ROIs obtained from searchlight analysis), correlations were computed

309 between the vectorized matrices of pairwise cross-position decoding accuracy. One minus

310 these correlation values were used to obtain the distance between the ROI pairs, and these

311 distances were used to construct an ROI dissimilarity matrix. The ROI dissimilarity matrix was

312 first computed for individual subjects and then averaged across subjects to acquire group level

313 ROI dissimilarity matrix (Figure 7A).

314  Split-half reliability of ROI dissimilarity matrix was also evaluated; we randomly divided

315 subjects into two equal groups and correlated corresponding group-level ROI dissimilarity

316 matrices as a measure of reliability. This measure was calculated for 10000 random split-half

317 divisions and averaged to produce the final reliability measure. To examine the significance of

318 this reliability measure, we obtained the bootstrapped null distribution of reliability by random

319 shuffling of the labels in the correlation matrix separately for the two split-half groups and

320 calculating the reliability for 10000 random samples.

An MDS analysis was then performed on this ROI-dissimilarity matrix, and the first two

dimensions that captured most of the variance were used to produce an MDS diagram in which

the distance between each pair of ROIs represents the similarity between them (Vaziri-Pashkam

& Xu, 2018). The squared correlation ($r^2$) between two-dimensional distances in the MDS plots

and the original distances in the multi-dimensional space was used to quantify the variance

explained by the first two dimensions. We then fit two regression lines employing the total least

square method, with one line passing through the positions of the occipito-temporal regions and

the other passing through the positions of parietal regions.  The variance explained by the fitted

lines was also measured; two-dimensional distances between regions based on the predicted

positions on the lines were obtained, and the $r^2$ between these distances and the original

distances based on the input matrix to the MDS analysis was calculated. Similarly, we

computed the $r^2$ between distances based on the MDS plots and line predictions to determine

the variance explained by the two lines on the MDS plot.

335                                          **Results**

In the present study, we aimed to identify regions containing position tolerant

representations of actions and investigate the representational content of these regions using

fMRI multi-voxel pattern analysis. A stimulus set of ten different human action videos in PLD

format (Figure 1) was presented at two different positions in the visual display (upper and lower

visual hemifields), and t-values were extracted in each voxel of the brain for each of the actions

and each position. Employing a support vector machine classifier, within- and cross-position

decoding was then applied following a searchlight approach across the whole brain.

**Figure 1.** Representative frames of the 10 human action videos in PLD format used in the

experiment.

## Action decoding across the whole brain

To identify regions that showed selectivity for our action stimuli within each presentation

position (upper/lower visual fields), classifiers were trained and tested with fMRI responses for

stimuli presented within the same position. To identify regions showing position tolerance, we

performed a cross-position classification. Classifiers were trained with fMRI responses to stimuli

presented at the upper visual field and tested with fMRI responses to stimuli presented at the

lower visual field and vice versa. Both within- and cross-position classification were applied

using a surface-based searchlight method.

Figure 2A and B depict the result of the group analysis ($q1 = 0.05$ and $q2 = 0.01$) for

within- and cross-position classification accuracy, respectively. Comparison of these maps

reveals that a subset of the regions that show above chance within-position classification also

demonstrate generalization across positions. The group analysis showed significantly above

chance cross-position classification accuracy in the left and right lateral occipito-temporal

cortex, right intraparietal sulcus, and right post-central gyrus (Figure 2B).

**Figure 2.** Results of searchlight classification accuracy **A,** Significance maps of group analysis

for searchlight within-position classification accuracy (thresholded at $q1 = 0.05$ and $q2 = 0.01$)

**B**, Significance maps of group analysis for searchlight cross-position classification accuracy

(group thresholded at $q1 = 0.05$ and $q2 = 0.01$) **C**, five Clusters with significant cross-position

classification accuracy used as ROIs (note that the exact ROIs differ slightly across iterations of

the leave-one-subject-out procedure).

**Action decoding in ROIs**

To investigate the extent to which changes in position affect the representations in

individual regions, we used a leave-one subject out procedure (see methods) to extract ROIs

with above chance cross-decoding accuracy. Five clusters (Figure 2C) were selected based on

a searchlight analysis on all but one subject, and the selected clusters were used as ROIs for

the left-out subject.

**Figure 3.** Inflated brain surface from a representative participant showing the ROIs examined in lateral and ventral views with white outlines for Wang's ROIs and colorful outlines for functional ROIs obtained from searchlight analysis.

A linear SVM was employed for within- and cross-position classification within each ROI, using the 100 most informative vertices in each ROI (Mitchell et al., 2004). Figure 4A illustrates the results of within- and cross-position decoding accuracy for each of the ROIs. All ROIs had a significant decoding accuracy for cross- and within-position (group analysis with (q1 = 0.01, q2= 0.01). In the left and right lateral occipito-temporal and parietal ROIs, cross-position decoding accuracy was significantly lower than within-position decoding accuracy (paired t-test, p < 0.0075, FDR corrected q = 0.01), while this difference was not significant in bSTS and Post-Central regions (paired t-test, p > 0.13, FDR corrected q = 0.01). These results suggest a reduction in position sensitivity from posterior to anterior regions in both occipito-temporal and parietal cortices. To visualize this finding on the whole brain, we divided the cross-position by within-position classification accuracy in all vertices with above chance within-position accuracy.

The resulting map averaged across subjects is depicted in figure 4B. In line with the ROI

analysis, this map demonstrates an increase in position tolerance from posterior to anterior

regions in both occipito-temporal and parietal cortices.

**Figure 4. *A,*** Within and cross-position decoding accuracy for the ROIs obtained from

searchlight analysis. Error bars indicate standard errors of the means (** paired t-test, $p < 0.01$,

FDR corrected). The vertical dashed line separates occipito-temporal ROIs from parietal ROIs

***B,*** Maps of cross-position divided by within-position classification accuracy obtained from

searchlight analysis in vertices with significant within-position classification accuracy.

***Revealing the Representational content of the ROIs***

To uncover the principles that govern the organization of action representations in each

ROI, we used a representational similarity analysis (RSA, Kriegeskorte et al., 2008). We

constructed models based on the body-part movements and behavioral similarity ratings

performed on the videos by human observers (see methods). We then used correlation analysis

to investigate the similarity of action representations between models and ROIs according to

their cross-position pairwise decoding accuracies. The reliability of the behavioral dissimilarity

matrices was high (Cronbach Alpha = 0.7654). Models of stimuli (distance matrices obtained

from models) were also compared with each other; the Kendall correlation was calculated, and

its significance was examined applying permutation tests. The behavioral and body-part models

were not significantly correlated (Kendall correlation = 0.0394, p-value = 0.2562).

Figure 5 shows the Kendall correlations between the models and cross-position pairwise

decoding accuracies across participants for body-part movement and behavioral rating models.

**Figure 5.** Kendall correlation body-part movement (dark gray) and behavioral rating models

(light gray) and cross-position pairwise decoding accuracies for the individual ROIs. Error bars

indicate standard errors of the mean (permutation test or paired t-test, *$p$ < 0.05, **$p$ < 0.01,

FDR corrected). The vertical dashed line separates occipito-temporal ROIs from parietal ROIs.

Significant correlations were found with the body-part model in all ROIs except for L-

LOTC (permutation test, $p$ < 0.05 for R-LOTC and $p$ < 0.01 for bSTS, IPS, Post-Central) and

with the behavioral rating model in all ROIs except for IPS and Post-Central (permutation test, $p$

< 0.01).

A two-way repeated-measures ANOVA with model (body-part movement and behavioral

rating) and ROI as independent factors and correlation coefficient as the dependent variable

was performed. The effect of ROI ($F_{(4,84)} = 0.9303$, $p = 0.4504$),  and the effect of model

($F_{(1,84)} = 0.7636$, $p = 0.3921$) were not significant while the interaction between the two

($F_{(4,84)} = 36.8$, $p < 0.0001$) was significant. Individual comparisons within ROIs showed that

correlation coefficients were greater for the behavioral rating model in L-LOTC and R-LOTC and

for the body-part movement model in IPS and post-central (all $t(21) > 3.7117$, all $p < 0.0016$,

FDR-corrected).

**Figure 6.** Kendall correlation between body-movement-average (light gray) and body-

movement-pattern (dark gray) models and cross-position pairwise decoding accuracies for

individual ROIs. Error bars indicate standard errors of the mean (permutation test, *$p < 0.05$, **$p$

$< 0.01$, FDR corrected). The vertical dashed line separates occipito-temporal ROIs from parietal

ROIs.

We also constructed models based on the average of movement across all body-parts

(body-movement-average) and based on the pattern of movements in body parts (body-

movement-pattern ) separately (see methods). Figure 6 shows the average Kendall correlation

between the models and cross-position pairwise decoding accuracies across participants for

body-movement-pattern and body-movement-average models. As figure 6 shows, all ROIs

showed correlations with the body-movement-pattern model (permutation test, $p < 0.05$ for L-

LOTC and R-LOTC, $p < 0.01$ for bSTS, IPS and Post-Central, FDR corrected, 5 comparisons),

but body-movement-average models only showed correlations with the dorsal ROIs

(permutation test, $p < 0.01$, FDR corrected) and showed no significant correlation with the

lateral ROIs (permutation test, p > 0.05, FDR corrected).

A two-way repeated measure ANOVA with model and ROI as independent factors and

correlation coefficient as the dependent variable showed no significant effect of model ($F(1,84)$

= 0.0117, $p = 0.9148$) while the effect of ROI ($F(4,84) = 22.5280$, $p < 0.0001$),  and the

interaction between the two ($F(4,84) = 11.5105$, $p < 0.0001$) were significant. The significant

effect of ROI points to greater correlation coefficients in dorsal ROIs. Individual comparisons

within ROIs showed that correlation coefficients were greater for the pattern model in L-LOTC

($t(21) = 2.6553$, $p = 0.0370$, FDR-corrected) and for the average model in IPS ($t(21) = 4.9394$, $p$

= 3.4583e-04, FDR-corrected).

We also compared the behavioral rating model with the average and pattern models

applying two separate two-way repeated measure ANOVAs with model and ROI as independent

variables and correlation coefficient as the dependent variable.

Its result for the body-part-average and behavioral rating models showed no significant

effect of ROI ($F(4,84) = 1.1066$, $p = 0.3589$),  and model ($F(1,84) = 0.3031$, $p = 0.5878$) while

the interaction between the two was significant ($F(4,84) = 36..4416$, $p < 0.0001$). Individual

comparisons within ROIs showed that correlation coefficients were greater for the behavioral

rating model in L-LOTC and R-LOTC and for the body-movement-average model in IPS and

Post-Central (all $t(21) > 3.5686$, all $p < 0.0018$, FDR-corrected).

For the body-part-pattern and behavioral rating models results showed no significant

effect of model ($F(1,84) = 0.4335$, $p = 0.5174$) while the effect of ROI ($F(4,84) = 8.8253$, $p =$

0.0001),  and interaction between the two ($F(4,84) = 37.6654$, $p < 0.0001$) were significant.

Individual comparisons within ROIs showed that correlation coefficients were greater for the

behavioral rating model in L-LOTC and R-LOTC and for the body-movement-pattern model in

IPS and Post-Central (all $t(21) > 4.8254$, all $p < 0.0001$, FDR-corrected).

In sum, these results reveal dissociations between the classification accuracies in the

lateral and dorsal ROIs. In lateral ROIs, the cross-position decoding accuracies are more

correlated with behavioral ratings than any of the body-part movement models, while those in

dorsal ROIs are more correlated with the objective movement models.

***ROI similarity analysis***

In addition to the 5 clusters obtained from the searchlight analysis, we obtained the

cross-position decoding accuracy of retinotopic regions of interest across occipito-temporal and

parietal cortex (see methods). We calculated cross-position classification accuracies for these

ROIs following a similar procedure as that used for the ROIs obtained from searchlight analysis.

Then, to examine the representational similarity across all ROIs (including retinotopic ROIs and

ROIs obtained from searchlight analysis), we computed the one minus the correlation between

their cross-position decoding accuracy (Figure 7A). The resulting ROI dissimilarity matrix had

high split-half reliability of 0.8346, significantly higher than chance (bootstrapped null distribution

95% CI [–0.0011,0.0012]). To visualize region-wise distances, we then applied an MDS analysis

on this matrix. Figure 7B depicts the first two dimensions that captured most of the variance ($r^2 =$

0.5522). These results are consistent with the representational similarity analysis and further

suggest the presence of two separate networks for processing actions. One starting from the

early visual cortex going to the lateral surface of the brain, and another splitting from this

pathway towards the parietal cortex with the bSTS region landing right between the two

pathways. This observation was quantified through fitting two total least square lines to the

points on the MDS plot: one line was passed through occipito-temporal regions (V1, V2, V3,

hV4, VO1, VO2, MST, hMT, LO2, LO1, V3b, and V3a from the wang atlas, and L-LOTC, R-

LOTC, and bSTS from our ROI analysis) and the other line was passed through parietal regions

(IPS0, IPS1, IPS2, IPS3, IPS4, IPS5, and SPL1 from wang atlas and IPS and Post-Central from

our ROI analysis). These lines could explain 0.7950 percent of the variance of the positions of

the regions on the MDS plot and 0.4798 percent of the variance of the full multi-dimensional

space.

**Figure 7. *A,*** ROI dissimilarity matrix based on the correlation distance between their cross-

position decoding accuracy for Wang's ROI and ROIs obtained from searchlight analysis.

Lighter colors show higher correlations ***B,*** MDS plot of Wang's ROIs (light gray) and ROIs

obtained from searchlight analysis (dark gray) and a total least square regression line through

the occipito-temporal regions (the light gray line) and another through the parietal regions (the

dark gray line). The MDS plot and the lines could capture 0.5522 and 0.4798 percent of the

variance of the ROI dissimilarity matrix.

**Discussion**

In this article, we used point-light displays of human actions presented in either the

upper or the lower visual fields and examined the extent of position tolerance as well as the

representational content of action selective regions in the human brain. Using cross-position

decoding analysis, we found that regions in the Left and right lateral occipitotemporal cortex,

right intraparietal sulcus, and right post-central gyrus contain position tolerant representations of

action stimuli. Additionally, we investigated the representational content of these regions and

found that representations in parietal regions were related to the movements of the body-parts

while those in occipitotemporal regions were more related to human subjective judgments about

actions.

Our results, for the first time, provide a comprehensive understanding of position-tolerant

action representations in the human visual cortex. Our findings in the lateral occipital cortex are

consistent with those of Grossman et al. (2010) that applied fMRI adaptation and showed

position tolerant representation of actions in STS. However, they failed to find other position

invariant regions found in our study, especially the regions in the parietal cortex. This

discrepancy may be related to differences in design. Our block design paradigm and the use of

SVM classifiers may have provided us with a higher power and sensitivity to detect regions that

contain position-tolerant action representation (Coutanche et al., 2016). Roth and Zohary (2015)

investigated position invariance during observation of natural tool-grasping clips using MVPA

(correlation and cross-decoding classifier). They observed a gradual loss of position information

accompanied by enhancement of hand/tool identity along the posterior-anterior axis in the

dorsal stream. This result is consistent with our finding for the parietal cortex, but they didn't

observe such a gradient in the lateral stream. Their focus on grasping actions may have

lowered their chance of observing the full extent of position tolerance in the lateral occipito-

temporal cortex.

Most regions that contained position tolerant representations of actions in our study were

located in the right hemisphere. This laterality toward the right hemisphere is in line with the

results of previous studies. Beauchamp et al. (2003) investigated human motion versus tool

motion (natural and PLD video clips). They found that category-related responses were

lateralized with a significantly greater number of tool-preferring voxels in the left hemisphere and

a significantly greater number of human-preferring voxels in the right hemisphere. Grosbras et

al. (2012) performed a meta-analysis on three categories of human motion including the

movement of the whole body, hands and face. The conjunction of the three meta-analysis maps

showed convergence in the right posterior superior temporal sulcus and the bilateral junction

between middle temporal and lateral occipital gyri. Right laterality in parietal regions has also

been previously reported for observed limb movements (Grosbras et al., 2012; Pelphrey et al.,

2005).

After identifying the position-tolerant regions, we investigated their representational

content. In occipito-temporal cortex, we found that a model based on the behavioral ratings of

similarity was the best predictor of the cross-position pattern classification accuracies. These

results are consistent with a study by Tucciarelli et al. (2019) that used natural images of

different actions and showed that responses in the LOTC were correlated with the behavioral

ratings of semantic similarity between actions. Similar to our results, they also showed a lower

correlation in LOTC with a model based on body movements. On the other hand, they failed to

find a significant correlation with a body part model in the parietal cortex. This could be because

they used human ratings of body part movements as opposed to the objective measures we

used based on actual measures of body position. Humans may fail to consider the movement of

all body parts and only focus on just the main effector of action for their ratings. In addition, they

also employed an event-related design that has less power than our block design paradigm.

Thus, our results extend their findings and further elucidate the differences between parietal and

occipito-temporal action representations.

In a study with a large set of human action videos, Tarhan and Konkle (2020) used

behavioral rating to construct an encoding model to investigate action representations in the

human brain. Their behavioral ratings included questions related to body parts involved in the

action as well as the action target. Using a clustering analysis, they divided voxels into four

network, suggesting that one is driven by the social aspects of actions and four are driven by

the scale of the interaction envelope.   Consistent with our study, their clusters spanned both

occipitotemporal and parietal regions, with notable differences in response profile between the

two networks. However, it is difficult to be more specific in comparing their results to our findings

due to methodological differences. They used natural videos of everyday scenes containing

actions as stimuli. Other than human bodies or body parts performing the action, their stimuli

also contained objects and other scene elements. The use of natural stimuli makes it difficult to

determine if the clusters reflect responses to actions or the scene elements correlated with the

actions. Also, since we used a block design paradigm and aimed at determining the extent of

position invariance in action selective regions, we could only collect data from a small set of

actions. Future studies with a larger set of controlled PLD stimuli could test the extent to which

sociality and interaction envelope determine the responses in position invariant action selective

regions in the brain.

Investigating the representations of actions in the dorsal stream, Buccino et al. (2001)

suggested that dorsal regions represent actions based on action effectors. Jastorff et al. (2010),

Abdollahi et al. (2013), and Vannuscorps et al. (2018), on the other hand, provided evidence

that action representations in dorsal regions are organized based on the category of actions

independent of the effectors. Here, we show that a model based on body-part movement shows

high correlations with the pattern of classification accuracies in the dorsal stream regions. Our

body-part movement model was constructed based on the movement of all body parts, including

the trunk and the limbs. This model included more information than just the action effector. High

correlations of this model with the classification accuracies in the dorsal regions suggests that

dorsal regions may contain a more holistic representation of body parts during action

observation.

Even though lateral regions show higher correlations with the subjective model than the

body part model, their correlation with the body part movement was still above zero. Therefore

lateral regions show signatures of both objective and subjective measures. Nevertheless, more

detailed analysis of the body part model separating the patterns of movement from average

movements revealed further differences between the dorsal and lateral regions. While the

dorsal regions showed sensitivity to both pattern and average of movements, the lateral regions

showed only a correlation with a model based on patterns of movement. With the limited

number of stimuli in our set, we cannot perform a more nuanced analysis of the differences in

the sensitivity to various body parts between dorsal and lateral regions. Future experiments with

an expanded set of PLD stimuli could reveal potential differences between the two networks in

their body part representations.

In the domain of object representations, recent studies have revealed that both dorsal

and ventral stream regions contain object information independent of the position of objects

(Vaziri-Pashkam and Xu, 2019; Almeida et al., 2018), but data-driven analysis of object

representation still reveals the separation of these dorsal and ventral regions in their

representational (Vaziri-Pashkam and Xu, 2019). Here, focusing on action observation, we

showed that action representations become progressively less position-dependent from

posterior to anterior along both dorsal and lateral pathways. Moreover, employing either data-

driven (looking at ROI similarities) or model-based approaches, we observed a clear distinction

between representational content in two pathways. Looking more closely at the arrangement of

ROIs in the MDS plot, we can see that ROIs along the lateral surface follow a continuous

trajectory from early visual areas while dorsal ROIs are separated away from both early visual

and lateral ROIs. These results provide evidence for distinct representational content along the

two pathways.

Embodied cognition theories argue that recognition of observed actions relies on

sensory-motor simulation and taps into motor representation necessary for executing those

actions (Rizzolatti & Craighero, 2004; Pulvermüller, 2013). Motor, premotor, and parietal regions

that contain mirror neurons in Macaque monkeys have been proposed as potential regions

contributing to action recognition through motor simulation (Rizzolatti & Craighero, 2004). In our

study we failed to find position tolerant represenations in prefrontal and premotor regions, and

the representations in our parietal regions did not show correlation with the model based on

subjective judgments on actions. These results suggest that the motor, premotor and parietal

regions are unlikely to contribute to the subjective understanding of actions (Caramazza et al.,

2014). Nevertheless, it is still possible that parietal regions would contribute to action

observation during coupled motor interactions as well as motor imitations (Caspers et al., 2010)

through analysis of body part movements. Our results suggest distinct roles for dorsal and

lateral regions in action observation.

In summary, we found regions capable of representing highly abstract forms of observed

human actions, namely the point light display video clips of actions across changes in position.

These regions located in lateral occipito-temporal and parietal cortices contained distinct

representational content. The lateral regions reflected more strongly the human subjective

knowledge about objects, while the dorsal regions reflected only the objective bodily

movements. These results suggest the existence of two distinct networks that contain abstract

representations of human actions likely serving different purposes in the visual processing of

actions.

**References**

Abdollahi, R. O., Jastorff, J., & Orban, G. A. (2013). Common and segregated processing of

observed actions in human SPL. *Cerebral cortex*, *23*(11), 2734-2753.

Albertini, D., Gerbella, M., Lanzilotto, M., Livi, A., Maranesi, M., Ferroni, C. G., & Bonini, L.

(2020). Connectional gradients underlie functional transitions in monkey pre-

supplementary motor area. *Progress in neurobiology*, *184*, 101699.

Allefeld, C., Görgen, K., & Haynes, J. D. (2016). Valid population inference for information-

based imaging: From the second-level t-test to prevalence inference. *Neuroimage*, *141*,

378-392.

Almeida, J., Amaral, L., Garcea, F. E., Aguiar de Sousa, D., Xu, S., Mahon, B. Z., & Martins, I.

P. (2018). Visual and visuomotor processing of hands and tools as a case study of cross

talk between the dorsal and ventral streams. *Cognitive neuropsychology*, *35*(5-6), 288-

303.

Anzellotti, S., Fairhall, S. L., & Caramazza, A. (2013). Decoding representations of face identity

that are tolerant to rotation. *Cerebral Cortex*, *24*(8), 1988-1995.

Barz, F., Livi, A., Lanzilotto, M., Maranesi, M., Bonini, L., Paul, O., & Ruther, P. (2017).

Versatile, modular 3D microelectrode arrays for neuronal ensemble recordings: from

design to fabrication, assembly, and functional validation in non-human primates.

*Journal of neural engineering*, *14*(3), 036010.

Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: a practical and

powerful approach to multiple testing. *Journal of the Royal statistical society: series B*

*(Methodological)*, *57*(1), 289-300.

Brainard, D. H. (1997). The psychophysics toolbox. *Spatial vision*, *10*(4), 433-436.

Buccino, G., Binkofski, F., Fink, G. R., Fadiga, L., Fogassi, L., Gallese, V., ... & Freund, H. J.

(2001). Action observation activates premotor and parietal areas in a somatotopic

manner: an fMRI study. *European journal of neuroscience*, *13*(2), 400-404.

Buxbaum, L. J., Kyle, K. M., Tang, K., & Detre, J. A. (2006). Neural substrates of knowledge of

hand postures for object grasping and functional object use: Evidence from fMRI. *Brain*

*Research*, *1117*(1), 175-185.

Caramazza, A., Anzellotti, S., Strnad, L., & Lingnau, A. (2014). Embodied cognition and mirror

neurons: a critical assessment. *Annual review of neuroscience*, *37*, 1-15.

Caspers, S., Zilles, K., Laird, A. R., & Eickhoff, S. B. (2010). ALE meta-analysis of action

observation and imitation in the human brain. *Neuroimage, 50(3)*, 1148-1167.

Chang, C. C., & Lin, C. J. (2011). LIBSVM: A library for support vector machines. *ACM*

*transactions on intelligent systems and technology (TIST)*, *2*(3), 27.

Cichy, R. M., Chen, Y., & Haynes, J. D. (2011). Encoding the identity and location of objects in

human LOC. *Neuroimage*, *54*(3), 2297-2307.

Cichy, R. M., Sterzer, P., Heinzle, J., Elliott, L. T., Ramirez, F., & Haynes, J. D. (2013). Probing

principles of large‐scale object representation: Category preference and location

encoding. *Human Brain Mapping*, *34*(7), 1636-1651.

Coutanche, M. N., Solomon, S. H., & Thompson-Schill, S. L. (2016). A meta-analysis of fMRI

decoding: Quantifying influences on human visual population codes. *Neuropsychologia*,

*82*, 134-141.

Culham, J. C., Danckert, S. L., De Souza, J. F., Gati, J. S., Menon, R. S., & Goodale, M. A.

(2003). Visually guided grasping produces fMRI activation in dorsal but not ventral

stream brain areas. *Experimental brain research*, *153*(2), 180-189.

DiCarlo, J. J., & Cox, D. D. (2007). Untangling invariant object recognition. *Trends in cognitive*

*sciences*, *11*(8), 333-341.

Downing, P. E., Peelen, M. V., Wiggett, A. J., & Tew, B. D. (2006). The role of the extrastriate

body area in action perception. *Social Neuroscience*, *1*(1), 52-62.

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical surface-based analysis: I. Segmentation

and surface reconstruction. *Neuroimage*, *9*(2), 179-194.

El-Sourani, N., Wurm, M. F., Trempler, I., Fink, G. R., & Schubotz, R. I. (2018). Making sense of

objects lying around: How contextual objects shape brain activity during action

observation. *Neuroimage*, *167*, 429-437.

Etzel, J. A., Zacks, J. M., & Braver, T. S. (2013). Searchlight analysis: promise, pitfalls, and

potential. *Neuroimage, 78*, 261-269.

Ferri, S., Rizzolatti, G., & Orban, G. A. (2015). The organization of the posterior parietal cortex

devoted to upper limb actions: An fMRI study. *Human brain mapping*, *36*(10), 3845-

3866.

Giese, M. A., & Poggio, T. (2003). Neural mechanisms for the recognition of biological

movements. *Nature Reviews Neuroscience*, *4*(3), 179-192.

Grosbras, M. H., Beaton, S., & Eickhoff, S. B. (2012). Brain regions involved in human

movement perception: A quantitative voxel-based meta-analysis. *Human brain*

*mapping*, *33*(2), 431-454.

Grossman, E. D., Jardine, N. L., & Pyles, J. A. (2010). fMR-adaptation reveals invariant coding

of biological motion on human STS. *Frontiers in human neuroscience*, *4*, 15.

Hafri, A., Trueswell, J. C., & Epstein, R. A. (2017). Neural representations of observed actions

generalize across static and dynamic visual input. *Journal of Neuroscience*, *37*(11),

3056-3071.

Haxby, J. V. (2012). Multivariate pattern analysis of fMRI: the early beginnings. *Neuroimage*,

*62*(2), 852-855.

Isik, L., Koldewyn, K., Beeler, D., & Kanwisher, N. (2017). Perceiving social interactions in the

posterior superior temporal sulcus. *Proceedings of the National Academy of Sciences*,

*114*(43), E9145-E9152.

Jastorff, J., & Orban, G. A. (2009). Human functional magnetic resonance imaging reveals

separation and integration of shape and motion cues in biological motion processing.

*Journal of Neuroscience*, *29*(22), 7315-7329.

Jastorff, J., Begliomini, C., Fabbri-Destro, M., Rizzolatti, G., & Orban, G. A. (2010). Coding

observed motor acts: different organizational principles in the parietal and premotor

cortex of humans. *Journal of neurophysiology*, *104*(1), 128-140.

Johnson-Frey, S. H. (2004). The neural bases of complex tool use in humans. *Trends in*

*cognitive sciences*, *8*(2), 71-78.

Kalénine, S., Buxbaum, L. J., & Coslett, H. B. (2010). Critical brain regions for action

recognition: lesion symptom mapping in left hemisphere stroke. *Brain, 133(11),* 3269-

3280.

Konen, C. S., & Kastner, S. (2008). Two hierarchically organized neural systems for object

information in human visual cortex. *Nature neuroscience*, *11*(2), 224.

Kourtzi, Z., & Kanwisher, N. (2000). Activation in human MT/MST by static images with implied

motion. *Journal of cognitive neuroscience*, *12*(1), 48-55.

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis-

connecting the branches of systems neuroscience. *Frontiers in systems neuroscience*,

*2*, 4.

Kriegeskorte, N. & Mur, M. (2012). Inverse MDS: Inferring Dissimilarity Structure from Multiple

Item Arrangements. *Front. Psychol. 3*, 1–13.

Lanzilotto, M., Maranesi, M., Livi, A., Ferroni, C. G., Orban, G. A., & Bonini, L. (2020). Stable

readout of observed actions from format-dependent activity of monkey's anterior

intraparietal neurons. *Proceedings of the National Academy of Sciences*, *117*(28),

16596-16605.

Leshinskaya, A., Wurm, M. F., Caramazza, A., & Leshinskaya, A. (2018). Concepts of Actions

and their Objects. M Gazzaniga, GR Mangun, D Poepped. *The Cognitive*

*Neurosciences*, 757-765.

Lingnau, A., & Downing, P. E. (2015). The lateral occipitotemporal cortex in action. *Trends in*

*cognitive sciences, 19(5),* 268-277.

Livi, A., Lanzilotto, M., Maranesi, M., Fogassi, L., Rizzolatti, G., & Bonini, L. (2019). Agent-

based representations of objects and actions in the monkey pre-supplementary motor

area. *Proceedings of the National Academy of Sciences*, *116*(7), 2691-2700.

Maeda, K., Ishida, H., Nakajima, K., Inase, M., & Murata, A. (2015). Functional properties of

parietal hand manipulation–related neurons and mirror neurons responding to vision of

own hand action. *Journal of cognitive neuroscience*, *27*(3), 560-572.

Maranesi, M., Livi, A., & Bonini, L. (2015). Processing of own hand visual feedback during

object grasping in ventral premotor mirror neurons. *Journal of Neuroscience*, *35*(34),

11824-11829

McMahon, E. G., Zheng, C. Y., Pereira, F., Gonzalez, R., Ungerleider, L. G., & Vaziri-Pashkam,

M. (2019). Subtle predictive movements reveal actions regardless of social

context. *Journal of vision*, *19*(7), 16-16.

Michels, L., Lappe, M., & Vaina, L. M. (2005). Visual areas involved in the perception of human

movement from dynamic form analysis. *Neuroreport*, *16*(10), 1037-1041.

Mitchell TM, Hutchinson R, Niculescu RS, Pereira F, Wang XR, Just M, Newman S (2004)

Learning to decode cognitive states from brain images. *Machine Learning 57*:145–175.

Mur, M., Ruff, D. A., Bodurka, J., Bandettini, P. A., & Kriegeskorte, N. (2010). Face-identity

change activation outside the face system:"release from adaptation" may not always

indicate neuronal selectivity. *Cerebral Cortex*, *20*(9), 2027-2042.

Ogawa, K., & Inui, T. (2011). Neural representation of observed actions in the parietal and

premotor cortex. *Neuroimage*, *56*(2), 728-735.

Oosterhof, N. N., Connolly, A. C., & Haxby, J. V. (2016). CoSMoMVPA: multi-modal multivariate

pattern analysis of neuroimaging data in Matlab/GNU Octave. *Frontiers in*

*neuroinformatics*, *10*, 27.

Oosterhof, N. N., Tipper, S. P., & Downing, P. E. (2012). Viewpoint (in) dependence of action

representations: an MVPA study. *Journal of Cognitive Neuroscience*, *24*(4), 975-989.

Oosterhof, N. N., Wiestler, T., Downing, P. E., & Diedrichsen, J. (2011). A comparison of

volume-based and surface-based multi-voxel pattern analysis. *Neuroimage*, *56*(2), 593-

600.

Oram, M. W., & Perrett, D. I. (1996). Integration of form and motion in the anterior superior

temporal polysensory area (STPa) of the macaque monkey. *Journal of neurophysiology*,

*76*(1), 109-129.

Peelen, M. V., Wiggett, A. J., & Downing, P. E. (2006). Patterns of fMRI activity dissociate

overlapping functional brain areas that respond to biological motion. *Neuron*, *49*(6), 815-

822.

Pelphrey, K. A., Morris, J. P., Michelich, C. R., Allison, T., & McCarthy, G. (2005). Functional

anatomy of biological motion perception in posterior temporal cortex: an fMRI study of

eye, mouth and hand movements. Cerebral cortex, 15(12), 1866-1876.

Pulvermüller, F. (2013). Semantic embodiment, disembodiment or misembodiment? In search

of meaning in modules and neuron circuits. Brain and language, 127(1), 86-103.

Ramírez, F. M., Cichy, R. M., Allefeld, C., & Haynes, J. D. (2014). The neural code for face

orientation in the human fusiform face area. *Journal of Neuroscience*, *34*(36), 12155-

12167.

Rizzolatti, G., & Craighero, L. (2004). The mirror-neuron system. Annu. Rev. Neurosci., 27, 169-

192.

Roth, Z. N., & Zohary, E. (2015). Position and identity information available in fMRI patterns of

activity in human visual cortex. *Journal of Neuroscience*, *35*(33), 11559-11571.

Sartori, L., Begliomini, C., Castiello, U. (2013). Motor resonance in left- and right-handers:

evidence for effector-independent motor representations. *Front. Hum. Neurosci. 7, 33.*

Schubotz, R. I., Wurm, M. F., Wittmann, M. K., & von Cramon, D. Y. (2014). Objects tell us what

action we can expect: dissociating brain areas for retrieval and exploitation of action

knowledge during action observation in fMRI. *Frontiers in psychology*, *5*, 636.

Senior, C., Barnes, J., Giampietroc, V., Simmons, A., Bullmore, E. T., Brammer, M., & David, A.

S. (2000). The functional neuroanatomy of implicit-motion perception or 'representational

momentum'. *Current Biology*, *10*(1), 16-22.

Shmuelof, L., Zohary, E. (2006). A mirror representation of others' actions in the human anterior

parietal cortex. *J. Neurosci. 26*, 9736–9742.

Shmuelof, L., Zohary, E. (2008). Mirror-image representation of action in the anterior pari- etal

cortex. *Nat. Neurosci. 11*, 1267–1269.

Simone, L., Bimbi, M., Rodà, F., Fogassi, L., & Rozzi, S. (2017). Action observation activates

neurons of the monkey ventrolateral prefrontal cortex. *Scientific reports*, *7*(1), 1-13.

Tarhan, L., & Konkle, T. (2020). Sociality and interaction envelope organize visual action.

representations. *Nature Communications*, *11*(1), 1-11.

Tucciarelli, R., Turella, L., Oosterhof, N. N., Weisz, N., & Lingnau, A. (2015). MEG multivariate

analysis reveals early abstract action representations in the lateral occipitotemporal

cortex. *Journal of Neuroscience*, *35*(49), 16034-16045.

Tucciarelli, R., Wurm, M., Baccolo, E., & Lingnau, A. (2019). The representational space of

observed actions. *Elife, 8*, e47686.

Urgen, B. A., Pehlivan, S., & Saygin, A. P. (2019). Distinct representations in occipito-temporal,

parietal, and premotor cortex during action perception revealed by fMRI and

computational modeling. *Neuropsychologia, 127*, 35-47.

Urgen, B. A., & Orban, G. A. (2021). The unique role of parietal cortex in action observation:

Functional organization for communicative and manipulative actions. *bioRxiv*.

Urgesi, C., Candidi, M., & Avenanti, A. (2014). Neuroanatomical substrates of action perception

and understanding: an anatomic likelihood estimation meta-analysis of lesion-symptom

mapping studies in brain injured patients. *Frontiers in human neuroscience, 8*, 344.

Vangeneugden, J., Peelen, M. V., Tadin, D., & Battelli, L. (2014). Distinct neural mechanisms

for body form and body motion discriminations. *Journal of Neuroscience*, *34*(2), 574-585.

Vannuscorps, G., F Wurm, M., Striem-Amit, E., & Caramazza, A. (2018). Large-scale

organization of the hand action observation network in individuals born without hands.

*Cerebral Cortex*, *29*(8), 3434-3444.

Vanrie, J., & Verfaillie, K. (2004). Perception of biological motion: A stimulus set of human point-

light actions. *Behavior Research Methods, Instruments, & Computers*, *36*(4), 625-629.

Vaziri-Pashkam, M., & Xu, Y. (2019). An information-driven 2-pathway characterization of

occipitotemporal and posterior parietal visual object representations. *Cerebral Cortex*,

*29*(5), 2034-2050.

Wang, L., Mruczek, R. E., Arcaro, M. J., & Kastner, S. (2014). Probabilistic maps of visual

topography in human cortex. *Cerebral cortex*, *25*(10), 3911-3931.

Watson, C. E., Cardillo, E. R., Ianni, G. R., & Chatterjee, A. (2013). Action concepts in the brain:

an activation likelihood estimation meta-analysis. *Journal of cognitive*

*neuroscience*, *25*(8), 1191-1205.

Wheaton, K. J., Thompson, J. C., Syngeniotis, A., Abbott, D. F., & Puce, A. (2004). Viewing the

motion of human body parts activates different regions of premotor, temporal, and

parietal cortex. *Neuroimage*, *22*(1), 277-288.

Wurm, M. F., Artemenko, C., Giuliani, D., & Schubotz, R. I. (2017a). Action at its place:

Contextual settings enhance action recognition in 4-to 8-year-old

children. *Developmental psychology*, *53*(4), 662.

Wurm, M. F., Caramazza, A., & Lingnau, A. (2017b). Action categories in lateral

occipitotemporal cortex are organized along sociality and transitivity. *Journal of*

*Neuroscience*, *37*(3), 562-575.

Wurm, M. F., Cramon, D. Y., & Schubotz, R. I. (2012). The context–object–manipulation triad:

Cross talk during action perception revealed by fMRI. *Journal of Cognitive*

*Neuroscience*, *24*(7), 1548-1559.

Wurm, M. F., & Schubotz, R. I. (2017). What's she doing in the kitchen? Context helps when

actions are hard to recognize. *Psychonomic bulletin & review, 24*(2), 503-509.

Xu, Y., & Vaziri-Pashkam, M. (2020). The development of transformation tolerant visual

representations differs between the human brain and convolutional neural

networks. *bioRxiv.*