Dynamic aspects of plant water potential revealed by a microtensiometer

Vinay Pagay[1*]

[1] School of Agriculture, Food & Wine, Waite Research Institute, The University of Adelaide, PMB 1,
Glen Osmond, SA 5064, Australia

* Correspondence: vinay.pagay@adelaide.edu.au

Abstract

Water potential is a fundamental thermodynamic parameter that describes the activity of water. In
this paper, we describe the continuous measurement of plant water potential, a reliable indicator of
its water status, using a novel *in situ* sensor known as a 'microtensiometer' in mature grapevines under
field conditions. The microtensiometer operates on the principle of equilibration of water potentials
of internal liquid water with an external vapour or liquid phase. We characterised the seasonal and
diurnal dynamics of trunk water potentials (Ψ_{trunk}) obtained from microtensiometers installed in two
grapevine cultivars, Shiraz and Cabernet Sauvignon, and compared these values to pressure chamber-
derived stem (Ψ_{stem}) and leaf (Ψ_{leaf}) water potentials as well as leaf stomatal conductance. Diurnal
patterns of Ψ_{trunk} matched those of Ψ_{stem} and Ψ_{leaf} under low vapour pressure deficit (VPD) conditions,
but diverged under high VPD conditions. The highest diurnal values of Ψ_{trunk} were observed shortly
after dawn, while the lowest values were typically observed in the late afternoon. Differential
responses of Ψ_{trunk} to VPD were observed between cultivars, with Shiraz more sensitive than Cabernet
to increasing VPD over long time scales, and both cultivars had a stronger VPD response than soil
moisture response. On a diurnal basis, however, time cross correlation analysis revealed that Shiraz
Ψ_{trunk} lagged Cabernet Ψ_{trunk} in response to changing VPD. Microtensiometers were shown to operate
reliably under field conditions over several months. To be useful for irrigation scheduling of woody
crops, new thresholds of Ψ_{trunk} need to be developed.

Keywords: water potential, microtensiometer, soil moisture, irrigation, stomatal conductance,
pressure chamber, vapour pressure deficit

Introduction

Measurements of crop water status, which are essential for optimised irrigation scheduling, have historically relied on low throughput and high cost instruments, and labour intensive methods, that have decreased their utility and uptake by the farming community. One such method widely established to reliably quantify plant water status is the manual measurement of leaf or stem water potential (Shackel, 2011; Williams and Baeza, 2007), using a Scholander pressure chamber invented in the 1960s (Scholander *et al.*, 1965). To overcome some of the limitations of such manual techniques, several electronic plant-based sensors to continuously measure crop water status have recently been developed that are based on various sensing modalities. These include sap flow sensors (Ginestar *et al.*, 1998), thermal diffusivity sensors (Pagay and Skinner, 2018), dendrometers (Corell *et al.*, 2014), and thermal or infrared sensors (Jones, 1999). A recent review of several of these sensors as applied in tree fruit crops can be found in Scalisi *et al.* (2017).

Given the prevalence of water potential as a reliable crop water status metric, sensors to measure plant water potential have also been developed. These sensors, known as hygrometers or psychrometers, provide continuous measurements of water potential either as contact sensors on leaves or *in situ* sensors embedded in stems (Dixon and Tyree, 1984; McBurney and Costigan, 1984; Michel, 1977). Hygrometers measure the water potential of the vapour phase. They are prone to significant errors due to the requirement of isothermal conditions between the measurement junction and plant tissue (Dixon and Tyree, 1984). A 1 °K temperature difference between the plant tissue and sensor can result in a water potential error of over 7.7 MPa (Dixon and Tyree, 1984). Much like stem hygrometers, other *in situ* sensors embedded in the stems or trunks include those that measure the osmotic potential of the xylem tissue and calibrated to stem water potential (Meron *et al.*, 2015). The osmotic potential sensor requires proper fluidic contact between the sensor and the plant tissue, as well has long transients (order hours) associated with the measurement.

Tensiometers measure the water potential of an external matrix by equilibrating an internal, constant volume of water whose hydrostatic pressure is taken as the negative of the external water potential. Tensiometers were originally developed for measurement of soil matric potential (Richards, 1942) and have been used for irrigation scheduling of crops (Cormier *et al.*, 2020). Based on this principle, Pagay *et al.* (2014) developed MEMS-based tensiometers, so-called 'microtensiometers' (MT), for rapid measurements of the water potential of an external matrix. The MTs were previously shown to operate reliably down to below -10 MPa with short transients (equilibration or response times) of ~ 20 min. This measurement range and temporal resolution makes the sensors valuable for not only crop and soil water status monitoring, but also other contexts including meteorology, concrete curing and food processing, and other systems where the internal water status is required. Subsequent improvements on the original MT design for improved transients (faster response times) were made by Black *et al.* (2020). This second generation microtensiometer was used for both *in situ* and *ex situ* measurements of water potential in a range of matrices including foods.

This paper presents the first results of field experiments with MTs, embedded water potential sensors, in mature grapevines grown under different environmental and soil moisture conditions in a Mediterranean climate. We compared the dynamic MT responses of plant water potential to values of leaf and stem water potentials as measured by the Scholander pressure chamber over both long term and short term (diurnal) periods, and with other environmental metrics including soil moisture and atmospheric conditions. Our goal was to validate the use of MTs in a field context and to provide new insights into the dynamics of plant water potential.

Materials and Methods

Experimental site and plant material

Two commercial vineyard blocks located in the Coonawarra region of South Australia (37.29° S, 140.83° E) were selected for the trial. One block was planted in 1988 to *Vitis vinifera* cv. Cabernet Sauvignon grafted onto Schwarzmann rootstock, while the second block was planted in 2013 to *V. vinifera* cv. Shiraz (syn. Syrah) grafted onto Teleki 5C rootstock. Both vineyards were situated within 5 km of each other and planted over the dominant 'terrarossa' soil, characterised by a distinctive red-brown, thick, clay B horizon soils overlying limestone, the depth to which is variable. In each vineyard, three adjacent vines per cultivar were selected for measurements, and, additionally, the middle vine for continuous monitoring of soil and plant water status (see details below). Vineyard management, irrigation, and integrated pest management were applied to both blocks as per convention in the region for premium winegrape production.

Environmental monitoring and climatic conditions

Environmental (weather) data for the vineyard blocks was obtained from the Coonawarra weather station maintained by the Australian Bureau of Meteorology (BOM), Station ID: 026091. Daily maximum air vapour pressure deficit (VPD) was calculated using maximum temperature and minimum relative humidity (RH) daily data. The long-term (20-year) mean January temperature (MJT) for Coonawarra is 19.3°C and the growing degree days (GDD; base 10 °C; October-April) is 1511. The climate of the area is characterised as Mediterranean, with winter dominant rainfall and relative summer drought. Average annual rainfall for Coonawarra is approx. 569 mm (Bureau_of_Meteorology, 2021). Supplemental irrigation is typically required from December until March. The elevation of the region is between 57 m and 63 m above sea level.

Soil moisture measurements

Of the three sentinel adjacent vines in each cultivar/block, the middle vine was selected for continuous monitoring of soil moisture, temperature and electrical conductivity using a capacitance-based sensor (Model: Teros-12, Meter Group, Pullman, WA, USA) buried approx. 30 cm below the surface and approx. 10 cm from the trunk of the vine in the vine row. The hourly sensor data was wirelessly transmitted via telemetry to a Cloud-based server and visually displayed on a user interface (Greenbrain, Measurement Engineering Australia, Adelaide, SA, Australia).

Plant water status measurements

Leaf stomatal conductance

In each block, leaf stomatal conductance (g_s) was measured on the three sentinel vines per cultivar between 1200 – 1300 h. Measurements were performed on one fully-expanded, healthy leaf per vine using an open system infrared gas analyser (IRGA; LI-6400XT, LI-COR Biosciences Inc., Lincoln, NE, USA) with a 6 cm^2 cuvette. An external LED light source (LI-6400-02B) attached to the cuvette was used at a fixed PAR value of 1500 µmol m^{-2} s^{-1} due to the sometimes variable ambient light levels. The cuvette gas flow rate was set at 400 µmol s^{-1} and reference CO_2 was set to 400 ppm. The cuvette and leaf temperatures were at ambient (uncontrolled), while cuvette relative humidity with the leaf inserted was maintained within a range of 35-55%. After IRGA measurements were performed, the same leaf was excised to determine leaf water potential (see below). IRGA measurements were conducted

110   diurnally (every 2 h between 0800 and 2000 h) on two days of contrasting VPDs – high VPD (February
111   17, 2021) and low VPD (January 26, 2021) – that were typical of a Mediterranean region.

Leaf and stem water potentials

In each block, midday stem (Ψ_{stem}) and leaf water potentials (Ψ_{leaf}) were measured on adjacent mature
leaves of the same shoot between the hours of 1200-1300 using a Scholander pressure chamber (Soil
Moisture Equipment Corp., Santa Barbara, CA, USA). For Ψ_{stem} measurements, leaves were bagged
using an opaque aluminium-lined bag for a minimum of one hour prior to measurement to stop
transpiration and allow for equilibration of water potentials between the leaf and shoot (stem).
Measures of Ψ_{leaf} and Ψ_{stem} were performed on one leaf per vine from the three sentinel vines in each
block/cultivar. Leaf and stem water potentials were measured diurnally on the two measurement days
concurrently with IRGA measurements. The same leaf used for g_s measurement with the IRGA was
used to measure Ψ_{leaf}.

Trunk water potentials

On December 12, 2020, a total of four microtensiometers (MT; FloraPulse, Davis, CA, USA) were
embedded into the trunks of the grapevines, two MTs per vine per cultivar. Readers are referred to
Pagay *et al.* (2014) for a detailed description of the theory of tensiometry, and to Black *et al.* (2020)
for technical details of the MT sensor design, fabrication, calibration, and lab testing results
(performance under controlled conditions). Briefly, the MT consists of a micromachined piezoelectric
pressure sensor coupled to a nanoporous silicon membrane via a cavity of liquid water. The membrane
couples the external environment with the internal sensor water, allowing for the equilibration of
water potentials. Decreases in the external water potential, i.e. below saturation vapour pressure,
results in decreases in the hydrostatic pressure of the internal water (P_{liq}), as the liquid phase water
comes under tension or is stretched (P_{liq} < 0.1 MPa). This relationship is shown in Eqn. 1 below.

$$\Psi_w = \frac{RT}{v_w}\ln(p/p_{sat}(T)) \qquad\qquad \text{(Eqn. 1)}$$

where, Ψ_w is the water potential (= $P_{liq} - P_{atm}$), R is the ideal gas constant (8.314 J mol^{-1} K^{-1}), v_w is the
molar volume of water (1.8 x 10^{-5} m^3 mol^{-1}), p is the partial pressure of vapour, and p_{sat} is the saturation
vapour pressure at temperature, T. The ratio of p/p_{sat} is the relative humidity of the sample.

Two MTs (Fig. 1a) were embedded into each trunk of a woody, mature grapevine per cultivar. Sensor
installation consisted of the following steps: (1) removal of bark on a flat section of the trunk; (2)
removal of phloem tissue using a cork borer and spatula/blade; (3) insertion of a custom stainless steel
sleeve (Fig. 1b; OD: 14 mm, ID: 9 mm) using a hammer; (4) Drilling into the sleeve approx. 5 cm into
the trunk (within xylem tissue) and removing tissue; (5) filling the cavity with a kaolin-based mating
compound; (6) inserting the hydrated MT into the mating compound; (7) placing a stainless steel cap
to close the sleeve; (8) Covering the sleeve exterior at the trunk with silicone to ensure air and water
proofing; (9) wrapping plastic film around the sensor followed by a 25 mm thick foam batting with
reflective aluminium film to minimise exterior temperature fluctuations to the sensors (Fig. 1c). The
sensors equilibrated with the vine (through the mating compound) within two days of installation. The
MT data of trunk water potential (Ψ_{trunk}; value averaged for both sensors), was obtained every 20 min
wirelessly transmitted via telemetry to a Cloud-based server (Amazon Web Services, USA) and visually
displayed on a user interface (FloraPulse, Davis, CA, USA).

| (a) | (b) | (c) |

Figure 1: (a) Close up view of an individual microtensiometer showing the stainless steel packaging surrounding a protruding sensor chip. The tip of the chip consists of the nanoporous silicon membrane that allows for equilibration of water potentials between the exterior matrix and internal water; **(b)** MTs installed in a grapevine trunk within a stainless steel sleeve filled with kaolin mating compound; **(c)** Background: MT batting and reflective film to minimise temperature effects on water potential measurements of the sensor; Foreground: dataloggers and wireless transmitters of the MT (bottom unit, white box) and soil moisture sensor (top unit, red base).

Statistical analyses

Time-lagged cross correlation (TLCC) analysis was used in MATLAB programing software (v.9.8.0, R2020a, The MathWorks, Inc., Natick, MA, USA) to analyse the continuous (20-min interval) data of VPD and Ψ_{trunk} over the course of two days with contrasting VPDs: January 26, 2021 (low VPD day; daily max. VPD ~ 1.6 kPa) and January 24, 2021 (high VPD day; daily max. VPD ~ 6.7 kPa). TLCC analysis involves determining the correlations between two time series datasets that are shifted in time (Chatfield and Xing, 2019), and repeatedly calculating Pearson Product Moment Correlation (cross correlation) Coefficient (XCC) after each shift (Cheong, 2020). Resulting 'offset' values, which when selected at the highest normalised XCC in the series, indicate the time shift (lag or advancement) of a particular time series compared to the other. Time shifts were selected such that they aligned with the VPD and Ψ_{trunk} measurement interval of 20 min, therefore each offset represented 20 min.

Results

Environmental conditions and soil moisture

Measurements of environmental conditions and vine water status were made over the course of two days, one with high vapour pressure deficit (VPD) and the other with low VPD, during the 2020-21 growing season from 0800-2000 h. The low VPD day, January 26, 2021, was characterised by sunny and cool conditions, with the daily maximum temperature reaching just over 23 °C with a maximum VPD of 1.7 kPa at around 1400 h (Fig. 2 a,g). This VPD was maintained until around 1600 h after which a decrease in solar radiation and temperature resulted in a decrease. Photosynthetically active radiation (PAR) was highest earlier in the day, around 1100 h, and declining gradually after this time. On the high VPD day, February 17, 2021, maximum daily temperature was nearly 37 °C and maximum VPD was approx. 6.0 kPa (Fig. 2 d,j). This maximum VPD was reached around 1600 h and two hours later than the maximum PAR was reached. The maximum VPD on the high VPD day was reached two hours later than the maximum on the low VPD day. The high VPD day was also characterised by both warm mornings and evenings; VPD values exceeded 2 kPa, which was higher than the day-time maximum of the low VPD day.

Soil moisture measured using an *in situ* capacitance sensors placed approx. 30 cm below the surface and adjacent to the vine trunks indicated that the average volumetric water content (VWC) on the two measurement days were 24.0% and 30.6% on January 26 and February 17, respectively, in Shiraz;

185 in Cabernet Sauvignon the VWC values were 28.3% and 30.3% on January 26 and February 17,
186 respectively.

Diurnal patterns of vine water status

Patterns of leaf (Ψ_{leaf}), stem (Ψ_{stem}), and trunk (Ψ_{trunk}) water potentials of the same vines were
quantified over the course of the two measurements days under low and high VPD conditions for both
Shiraz and Cabernet Sauvignon grapevines (Fig. 2b,e,h,k). A general pattern was observed in all the
vines of a gradual decrease in water potential (Ψ_w) over the course of the day, reaching a minimum in
the mid-afternoon, followed by an increase in the evening. The water potentials observed across all
dates and cultivars ranged between -0.3 MPa and -1.0 MPa for Ψ_{trunk}, between -0.1 MPa and -0.95
MPa for Ψ_{stem}, and -0.25 and -1.5 MPa for Ψ_{leaf}. The lowest Ψ_w values were generally observed around
1400 h each day, after which the values increased gradually.

Figure 2: Diurnal patterns of VPD, PAR, trunk (Ψ_{trunk}), stem (Ψ_{stem}), leaf (Ψ_{leaf}) water potentials, and leaf stomatal conductance
(g_s) on low and high VPD days for Shiraz (SHI) and Cabernet Sauvignon (CAS) grapevines.

Under low VPD (~ 1.7 kPa) conditions, Shiraz grapevines had Ψ_{trunk}, Ψ_{stem}, and Ψ_{leaf} daily average
minimum values of -0.66, -0.96, and -1.30 MPa, respectively (Fig. 2b). Although the three Ψ_w values
were similar in the early morning (0800 h) and late evening (2000 h), they reached maximum
separation between 1200 h and 1400 h, during which time the difference between them were approx.
0.3, 0.3, and 0.6 MPa for $\Delta\Psi_{trunk-stem}$, $\Delta\Psi_{stem-leaf}$ and $\Delta\Psi_{trunk-leaf}$, respectively. In comparison, Cabernet
Sauvignon on the same day, i.e. under low VPD conditions, had Ψ_{trunk}, Ψ_{stem}, and Ψ_{leaf} daily average
minimum values of -0.12, -0.45 and -1.01 MPa, respectively (Fig. 2h), which were higher than the
values observed in Shiraz for all three metrics. Similar (but not identical) to Shiraz, the differences
between Ψ_w values were greatest around 1400 h; difference values were approx. 0.3, 0.3 and 0.9 MPa
for $\Delta\Psi_{trunk-stem}$, $\Delta\Psi_{stem-leaf}$ and $\Delta\Psi_{trunk-leaf}$, respectively. The diurnal patterns of Ψ_w were somewhat
different compared to Shiraz; Cabernet did not drop its Ψ_{trunk} and Ψ_{stem} as much as Shiraz under the
same conditions despite its Ψ_{leaf} dropping to slightly below -1 MPa.

Under high VPD (~ 6 kPa) conditions, Shiraz grapevines dropped their Ψ_{trunk}, Ψ_{stem} and Ψ_{leaf} values to -
1.1, -0.7, -1.5 MPa, respectively (Fig. 2e), which were considerably lower than during the low VPD day.

Under these high VPD conditions in both cultivars, patterns of Ψ_w early in the day were similar to the
patterns observed during the low VPD day; the values of Ψ_w followed the expected order of Ψ_{trunk} >
Ψ_{stem} > Ψ_{leaf} during the morning. However, a distinct shift in the pattern of Ψ_{trunk} was observed after
approx. 1400 h: Ψ_{trunk} dropped below Ψ_{stem}, reaching a minimum of -1.06 MPa around 1800 h,
matching values observed for Ψ_{leaf}. In comparison, Ψ_{stem} at the same time (1800 h) was -0.47 MPa.
There was a noticeable recovery (increase) in Ψ_{trunk} that started soon after 1800 h, matching the values
of Ψ_{leaf} during this period late in the day (1800 h – 2000 h). Under the same (high VPD) conditions,
patterns of Cabernet Sauvignon Ψ_w were similar to that of Shiraz. Cabernet had large differences
between Ψ_{trunk}, Ψ_{stem} and Ψ_{leaf} early in the day, and these reached their minimum values of -0.67, -
0.76, and -1.5 MPa, respectively, between 1400 – 1600 h (Fig. 2k). Much like Shiraz under similar (high
VPD) conditions, there was a distinct crossing-over of Ψ_{trunk} and Ψ_{stem} around 1600 h; Ψ_{trunk} dropped
to values below Ψ_{stem}, remaining in this position until the end of the day. Differences between the
various metrics of Ψ_w were more significant in Cabernet than in Shiraz; maximum difference values in
Cabernet were approx. 0.1, 0.8 and 0.9 MPa for $\Delta\Psi_{trunk-stem}$, $\Delta\Psi_{stem-leaf}$ and $\Delta\Psi_{trunk-leaf}$, respectively, while
in Shiraz the corresponding differences were 0.05, 0.7, and 0.7 MPa, respectively.

Leaf stomatal conductance (g_s) was measured concurrently with Ψ_w measurements, and on the same
leaf used to measure Ψ_{leaf}. Patterns of g_s mirrored Ψ_w in both cultivars and across both measurement
days under contrasting environmental conditions. In Shiraz, average g_s values were highest early in
the day, peaking around 124 mmol H_2O m^{-2} s^{-1} at 1000 h under low VPD conditions, and considerably
higher around 235 mmol H_2O m^{-2} s^{-1} also at 1000 h under high VPD conditions (Fig. 2c,d). Under high
VPD conditions, however, there was a precipitous decline in g_s after 1600 h down to similar values
observed under low VPD conditions by late day (2000 h). Within a two hour window, between 1600 h
and 1800 h, Shiraz g_s values dropped by an average of 49% or 110 mmol H_2O m^{-2} s^{-1}.

In Cabernet Sauvignon, g_s values increased steadily from morning until around 1400 h (max. g_s ~ 200
mmol H_2O m^{-2} s^{-1}) under low VPD conditions (Fig. 2i), decreasing rapidly to similar values as those
observed in Shiraz under the same conditions. In contrast with Shiraz under high VPD conditions,
Cabernet had lower g_s early in the day until around 1400 h, after which a steady decrease was
observed; g_s values late in the day matched those under low VPD conditions as well as Shiraz under
both environmental conditions.

Dynamics of soil-plant-environment interactions

Diurnal patterns of environmental conditions, soil moisture, and vine water status were studied over
a period of eight days between January 19 and January 26, 2021. This period encompassed a range of
environmental conditions including hot and cool days (with corresponding high and low VPDs), and
irrigation and precipitation events. There was an increasing temperature and VPD trend during the
first three days of this period, followed by a decrease on January 22nd leading to the highest VPD values
observed on January 24th (daily max. VPD ~ 6.7 kPa). Over this period, approx. 20 mm of irrigation was
applied in the Cabernet block and 8 mm in the Shiraz block, in addition to the nearly 10 mm of
precipitation received in the region on January 25th (Fig. 3a). Changes in soil moisture reflected these
events; VWC values in the Cabernet block increased between 10-14% with 7.6 mm of irrigation and
less than 5% with the extra rainfall of 10 mm (Fig. 3b). The same rain event resulted in the soil moisture
increasing by approx. 12% in the Shiraz block with the same soil type.

Trunk water potentials (Ψ_{trunk}), as measured continuously by the microtensiometers, were a composite reflection of both soil moisture and environmental conditions, in particular VPD. Patterns of diurnal oscillations of Ψ_{trunk} were entrained with those of VPD albeit with time offsets on specific days (reported below; Fig. 3a,c). The daily maximum values of Ψ_{trunk} were usually observed between 0700 – 0900 h, approx. 2-3 hours after sunrise, and ranged from -0.01 to -0.10 MPa for Cabernet Sauvignon, and -0.01 and -0.6 MPa for Shiraz over the observation period (Fig. 3c). The daily minimum values of Ψ_{trunk} were usually observed between 1620 – 1820 h, and values ranged between -0.12 and -0.59 MPa for Cabernet, and -0.67 and -1.99 MPa for Shiraz.

During the first three days (of the eight-day observation period), the increasing trend of daily maximum VPD from 1.86 kPa on January 19th to 4.21 kPa on January 21st resulted in a concomitant decline in daily minimum Ψ_{trunk} from -0.42 to -0.59 MPa (on Jan-20) in Cabernet Sauvignon, and -1.14 to -1.55 MPa in Shiraz (on Jan-24). Soil moisture levels did not vary for Shiraz during this period, while Cabernet vines received 7.6 mm of irrigation on January 20th that resulted in an increase of VWC from 22% to 36% (Fig. 3b). This irrigation event

Figure 3: Week-long diurnal patterns of VPD and PAR **(a)**, soil volumetric water content **(b)**, and Ψ_{trunk} **(c)** for Shiraz and Cabernet Sauvignon grapevines. Blue bars on top of (b) represent irrigation events of ~7 mm for Cabernet Sauvignon, the purple bar represents irrigation of ~8 mm in Shiraz, and the green bar represents a rain event of 9.6 mm.

resulted in an increase of minimum Ψ_{trunk} in Cabernet on January 20-21 from -0.59 MPa to -0.43 MPa despite higher VPD levels on January 21. The Ψ_{trunk} responses of both cultivars to these conditions mirrored those of VPD; higher VPD values resulted in lower Ψ_{trunk}. Shiraz Ψ_{trunk} appeared to be strongly coupled to VPD; Pearson correlation coefficients (R) were highly correlated with daily minimum Ψ_{trunk} and $\Delta\Psi_{trunk}$ (=max. Ψ_{trunk} - min. Ψ_{trunk}), whereas Cabernet was only weakly correlated for the $\Delta\Psi_{trunk}$ parameter (Table 1).

Table 1. Pearson correlation coefficients (R) of daily maximum VPD vs. minimum and maximum Ψ_{trunk} values, and diurnal Ψ_{trunk} differences ($\Delta \Psi_{trunk}$ = max. Ψ_{trunk} - min. Ψ_{trunk}) during the eight day observation period from January 19-26, 2021 for Shiraz and Cabernet Sauvignon. n=8.

	Cabernet Sauvignon			Shiraz		
Parameter	Max. Ψ_{trunk}	Min. Ψ_{trunk}	$\Delta\Psi_{trunk}$	Max. Ψ_{trunk}	Min. Ψ_{trunk}	$\Delta\Psi_{trunk}$
Pearson R	-0.10	-0.60	-0.70	-0.35	-0.94	-0.96
P-value	0.811	0.115	0.053	0.393	0.001	0.000

In the next period of three days, two warm-to-hot days were experienced between January 23-24 with maximum VPD values of 3.84 and 6.70 kPa, respectively. On the warmest of these days, January 24, minimum Ψ_{trunk} values dropped to -0.51 and -1.99 MPa in Cabernet and Shiraz, respectively. Irrigation applied in these blocks between January 23-24 resulted in higher maximum Ψ_{trunk} values, particularly in Shiraz, increasing from -0.60 to -0.40 MPa. On the same warm day (January 24), the diurnal decline in Ψ_{trunk} in Cabernet was approx. 0.5 MPa while in Shiraz the decline was approx. 1.6 MPa (Fig. 3c). On this warm day, Ψ_{trunk} continued to drop until around 1720 h in Cabernet and until around 1820 h in Shiraz (Note: the highest VPD value was observed around 1730 h). In comparison, on cooler (low VPD)

days, minimum Ψ_{trunk} values were typically observed around 1620 h and 1740 h for Cabernet and Shiraz, respectively. On these cooler days, the highest VPD is typically reached around 1600 h, close to the time of minimum Ψ_{trunk} of Cabernet, but one hour earlier than that of Shiraz, similar to the observation on the high VPD day. On cooler days with max. VPD < 2.0 kPa, diurnal changes in Ψ_{trunk} averaged 0.2 MPa for Cabernet, and 0.7 MPa for Shiraz. A marked improvement in vine water status (increase in Ψ_{trunk}) was observed from January 25th onward resulting from both increases in soil moisture (via irrigation and precipitation), and probably more significantly, decreases in VPD. By the end of the observation period, January 26, minimum Ψ_{trunk} values had risen to -0.12 and -0.67 MPa in Cabernet and Shiraz, respectively.

Figure 4: Linear regression analysis of VPD vs Ψ_{trunk} of Shiraz and Cabernet Sauvignon grapevines over the measurement period. Regression equations: Shiraz: Ψ_{trunk} = -0.3272 - 0.1696*VPD, R^2 = 0.51; Cabernet Sauvignon: Ψ_{trunk} = -0.1247 - 0.065*VPD, R^2 = 0.33. *P*-value for differences between slopes: < 0.001.

The relationships between VPD and Ψ_{trunk} for Cabernet and Shiraz for the period December 14, 2020 to February 10, 2021 (0600-2000 h) are presented in Fig. 4. There was a significant difference between cultivars in the sensitivity of vine water status to VPD (as indicated by the slopes of the regression lines) during the two-month peak summer period. Shiraz was more sensitive than Cabernet to changes in atmospheric conditions, dropping its Ψ_{trunk} by approx. 0.17 MPa kPa^{-1}. In comparison, Cabernet reduced its Ψ_{trunk} by approx. 0.07 MPa kPa^{-1}.

Time-lagged cross correlation analysis (TLCC) was used to analyse the time series datasets of VPD and Ψ_{trunk} across two days with contrasting environmental conditions or VPDs: January 26, 2021 (low VPD day; daily max. VPD ~ 1.6 kPa) and February 17, 2021 (high VPD day; daily max. VPD ~ 6.7 kPa). On the low VPD day, the diurnal pattern of VPD followed the typical trend increasing from around 0900 h to its maximum around 1500 h after which a gradual decline commenced until reaching its minimum around 2000 h (Fig.5a).

Figure 5: Diurnal plot on a low VPD day (maximum VPD ~ 1.6 kPa) of **(a)** VPD, **(b)** Ψ_{trunk} for Shiraz and Cabernet Sauvignon, and Pearson Product Moment (cross correlation) coefficient values for Cabernet **(c)** and Shiraz **(d)** showing leading or lagging of Ψ_{trunk} in response to changing VPD.

Ψ_{trunk} followed a similar but mirrored trend, increasing in the early hours of the day, then decreasing from around noon to its minimum value of around 1800 h before rising again (Fig. 5b). Cabernet Sauvignon (CAS) and Shiraz appeared to have very similar diurnal patterns of Ψ_{trunk} despite differences in absolute Ψ_{trunk} values. TLCC analysis between VPD and Ψ_{trunk} revealed that CAS had the minimum Pearson Product Moment (normalised cross correlation) coefficient (XCC) at an offset of -9 units or -180 min (each offset unit = 20 min), indicating that Ψ_{trunk} lagged VPD by 180 min (Fig. 5c). Similarly, Shiraz Ψ_{trunk} lagged VPD by 220 min (Fig. 5d).

332 .

Figure 6: Diurnal plot on a high VPD day (maximum VPD ~ 6.7 kPa) of **(a)** VPD, **(b)** Ψ_{trunk} for Shiraz and Cabernet Sauvignon, and Pearson Product Moment (cross correlation) coefficient values for Cabernet **(c)** and Shiraz **(d)** showing leading or lagging of Ψ_{trunk} in response to changing VPD.

On the high VPD day of January 24, the maximum VPD of the day of approx. 6.7 kPa was reached around 1700 h (Fig. 6a), while the minimum Ψ_{trunk} in both Shiraz and CAS were much lower than those on the low VPD day, reached around 1800 h (Fig. 6b). TLCC analysis revealed that CAS Ψ_{trunk} lagged

339 VPD by 80 min (Fig. 6c) while Shiraz Ψ_{trunk} lagged VPD by 120 min (Fig. 6d), both lower than the time
340 lags observed on the low VPD day.

Discussion

Microtensiometers (MT) provide a rapid and continuous *in situ* measurement of water potential in
virtually any matrix, and in our context, in woody grapevine trunks. *In situ* measurements of plant
water potential provide valuable estimates of their water status, which are critical for determining
irrigation schedules, i.e. when and how much water to apply, for irrigated crops. Although a number
of other plant-based sensors currently exist, only very few measure water potential continuously, and
those can be challenging to install and unsuitable for long term measurements in the field. MTs
overcome some of these limitations due to their small form factor thereby allowing them to be
embedded within the woody structures of the plant. This location minimises the risk of damage to the
sensing elements from farm machinery, as well as environmental and biotic factors. This first report
on the field testing of MTs in mature grapevine trunks under varying environmental conditions
provides valuable data of Ψ_{trunk} on their performance in comparison to traditional methods of water
potential measurement, e.g. leaf pressure chamber. To the best of our knowledge, this is the first
report of field testing results of MTs. To date, the only other reports of continuous *in situ* water
potentials are reported using stem psychrometers (Dixon and Tyree, 1984; McBurney and Costigan,
1984; Tran *et al.*, 2014) and an osmometric sensor (Meron *et al.*, 2015).

Diurnal patterns of vine water status

Plant water potential reflects the dynamic interplay between incident solar radiation, VPD, and soil
moisture availability, as well as several internal factors within the plant that regulate water transport
from the roots to leaves. In the present study, diurnal measurements of leaf, stem and, for the first
time, trunk water potentials were conducted on several days characterised by contrasting
environmental conditions with low (< 2.0 kPa) and high (> 6 kPa) VPDs (Fig. 2). During this time, soil
moisture content (volumetric water content), as measured by a capacitance sensor, varied two-fold
from approx. 18% to 36% in a well-drained soil. Previous studies documenting diurnal patterns of leaf
water potential (Ψ_{leaf}) showed similar trends to the present study; a hyperbolic or U-shaped curve is
typically observed with the highest values in the early hours of the day and lowest values in the
afternoon in grapevine (Smart, 1974; van Zyl, 1987) and other woody horticultural crops (Klepper,
1968; Olsson and Milthorpe, 1983; Smart and Barrs, 1973). In *Vitis vinifera* cv. Colombar (grafted onto
99R rootstock), sunlit leaves had lower Ψ_{leaf} compared to shaded leaves, and the former reached the
lowest Ψ_{leaf} earlier in the day (1200 h for sunlit compared to 1400 h for shaded), but only when there
was a deficit in soil moisture (van Zyl, 1987). In California, Williams and Baeza (2007) observed in
several red grape cultivars that the lowest Ψ_{leaf} was reached around 1600 h when the vines were either
well-watered, receiving irrigation equal or higher than full replacement (100%) of crop
evapotranspiration (ET$_c$), or deficit irrigated at 40% ET$_c$. In comparison, Thompson Seedless reached
its lowest Ψ_{leaf} by around 1300 h when well-watered and by 1000 h under non-irrigated conditions.
The Williams and Baeza study unfortunately did not report on the early morning or late day recovery
patterns in Ψ_{leaf} of these vines so difficult to compare with the current study. In Tempranillo grapevines
receiving 70% ET$_c$, Ψ_{leaf} and Ψ_{stem} were observed to be at their lowest values around 1400 h and at a
similar time to the highest VPD of the day (Cole and Pagay, 2015), corroborating with observations in
the present study.

Freeman *et al.* (1982) found in Chardonnay and Carignan that the lowest Ψ_{leaf} was reached between
1500 h – 1600 h in Davis, California conditions. In the Chasselas cultivar in Switzerland, Zufferey and

co-workers found that the diurnal patterns of Ψ_{stem} showed a similar U-shaped pattern, and reached a minimum value around 1430 h on a high VPD day (~ 3.0 kPa) independent of soil moisture and at the same time on a low VPD day (~ 1.5 kPa) in irrigated vines (Zufferey *et al.*, 2011). However, on a low VPD day without irrigation, the vines reached their minimum Ψ_{stem} values only around 1600 h likely due to the low transpiration rates. The effect of soil moisture on diurnal Ψ_{leaf} patterns is quite marked; irrigation of Shiraz in a warm climate resulted in the highest transpiration rates and lowest Ψ_{leaf} around 1200 h and 1500 h, respectively (Smart, 1974). In comparison, water-stressed vines reached their lowest Ψ_{leaf} also around 1500 h, but the highest transpiration rates were reached around 1100 h. Our diurnal observations indicated that the lowest Ψ_{leaf}, Ψ_{stem}, and Ψ_{trunk} were reached around 1400 h, 1600 h and 1800 h, respectively, on low VPD days, whereas these times were advanced on the high VPD day, particularly for Ψ_{stem} and Ψ_{trunk}. Williams and Baeza (2007) suggested that the influence of VPD on Ψ_{leaf} decreases as soil moisture decreases.

Modeling of diurnal patterns of Ψ_{leaf} predicted that the lowest values are likely to be reached around 1400 h, approx. two hours after the highest leaf transpiration rates are reached (Katerji et al. 1986). This transient (or delay) in Ψ_{stem} response can be attributed to the contributions of both plant tissue water (~ 13%) and root uptake of soil moisture (~ 87%) to the transpiration stream. These modelled patterns compare favourably with those obtained from lysimeters; maximum transpiration rates were reached between 1200 h and 1400 h (Williams *et al.*, 2012). The same study found that higher vine sizes or crop factors result in not only increased transpiration rates, as expected, but also a delayed peak by as much as two hours. Similar patterns of vine transpiration were observed in studies using sap flow and thermal dissipation sensors (Braun and Schmid, 1999; Pagay and Skinner, 2018). The diurnal measurements of leaf stomatal conductance (g_s) in the present study indicated that the highest values were reached in the afternoon on low VPD days and late morning on high VPD days. Reductions in g_s following this peak resulted in increases in Ψ_{leaf} and Ψ_{stem}, but not Ψ_{trunk}. This lack of response from Ψ_{trunk} might indicate a level of buffering of water potential in the woody organs of the plant, in this case the trunk, where xylem vessels are surrounded by parenchymal cells that can contribute water to the transpiration stream, the so-called 'capacitance effect' (Salomón *et al.*, 2017; Waring and Running, 1978).

Environmental conditions played a key role in determining patterns and values of Ψ_w; both Ψ_{leaf} and Ψ_{stem} were strongly influenced by VPD. Consistent with other studies, our study found a strong negative relationship between Ψ_{trunk} and VPD (Fig. 4). In California, across three cultivars, Williams and Baeza (2007) found that the slope of the VPD-Ψ_{leaf} relationship was 0.079 MPa kPa^{-1}while for the VPD-Ψ_{stem} relationship was 0.068 MPa kPa^{-1}. In comparison, our study found slopes for VPD-Ψ_{trunk} in Cabernet Sauvignon to be 0.07 MPa kPa^{-1} while for Shiraz this slope was higher at 0.17 MPa kPa^{-1}. The higher sensitivity of Shiraz grapevines to VPD might reflect its relatively anisohydric behaviour that has been previously reported (Dayer *et al.*, 2020; Schultz, 2003), with a weaker regulation of stomatal conductance (g_s) under either declining soil moisture or increasing VPD. In contrast, Cabernet Sauvignon's lower Ψ_{trunk} sensitivity to VPD suggests a tighter coupling to the environment – both soil moisture and VPD.

Temporal coupling of plant water status and atmosphere

Continuous measurements of plant water status provide a valuable dataset for the analysis of its temporal patterns as well as relationships with the environment, both soil and plant. Our characterisation of the dynamic nature of Ψ_{trunk} in Shiraz and Cabernet Sauvignon grapevines using MTs was done both inter- and intra-day (diurnally). Furthermore, using a time-lagged cross correlation statistical approach, we conducted a detailed temporal analysis of the interrelationships between VPD

and Ψ_{trunk} that revealed the differences between the two grapevine cultivars in their response to
different environmental conditions. Cross-correlation analysis has been used for signal processing and
pattern recognition in diverse fields including spectroscopy, seismology, finance, and quantum
information processing (Podobnik and Stanley, 2008). In plants, the response of water potential to the
environment has been characterised previously, but comparisons of different cultivars using *in situ*
measurements of Ψ_w have not been reported hitherto. The slower transient or response of Ψ_{trunk} to
changes in VPD over the course of a day in Shiraz compared to Cabernet (Fig. 5) may reflect its greater
capacity for root water uptake and/or increased capacitance from the parenchymal cells surrounding
xylem vessels. Although not specifically measured in this study, it is likely that the Shiraz vines had
bigger root systems (biomass) than Cabernet based on the visually larger canopies and higher leaf area
index (LAI) values (Shiraz LAI ~ 7.4; Cabernet LAI ~ 5.6; average LAI data obtained from an
accompanying study on 32 vines per cultivar).

Under environmentally demanding (high VPD) conditions, the Ψ_{trunk} of both cultivars were more
strongly coupled to VPD with shorter transients. The more rapid vine response under high VPD
conditions may result from higher transpiration rates and more open stomata, which allowed the
Ψ_{trunk} in Shiraz to drop to nearly -2 MPa compared to -0.6 MPa on the low VPD day. In comparison, the
relatively modest reduction of Cabernet Ψ_{trunk} of ~ 0.4 MPa when the VPD increased may indicate
near-isohydric behaviour. This observation is consistent with other reports of the stomatal behaviour
of Cabernet Sauvignon (Collins and Loveys, 2010), but in contrast to other reports that Cabernet
Sauvignon has anisohydric behaviour (Suter *et al.*, 2019).

The stem potential sensor based on osmometry tested in tangerine trees in Israel provided diurnal
Ψ_{stem} values that correlated temporally with trunk temperature and evapotranspiration (ET), showing
a stem water potential lag of approx. five hours with both parameters (Meron *et al.*, 2015). The same
sensor used in peach trees showed a lag of five hours with destructive, pressure chamber
measurements of Ψ_{stem} and a similar (ca. five hour) lag from ET. Our results indicate that the time lag
of Ψ_{trunk} was cultivar- and VPD-dependent; in the order of 3-4 hours on a low VPD day and 1-2 hours
on a high VPD day with Cabernet at the low end of these ranges.

Measurement of predawn water potential and its timing

The predawn water potential (Ψ_{pd}) is considered a reliable indicator of root xylem pressure potential
(Ψ_p) or soil matric potential (Ψ_m) based on the equilibration of Ψ_w between the plant and soil when
the canopy transpiration rate (*E*) is zero or negligible (Ameglio *et al.*, 1999; Jones, 2007). The Ψ_{pd} is
influenced by soil water content and distribution, root area/distribution, and soil and root hydraulic
conductivities (Garcia-Tejera *et al.*, 2021). It should be noted that Ψ_{pd} is not a reflection of the average
soil Ψ_w across the rhizosphere, but rather the Ψ_w of its wettest portion (Pagay *et al.*, 2016;
Schmidhalter, 1997). Furthermore, Ameglio *et al.* (1999) reported that Ψ_{pd} may not reflect plant Ψ_w
and hence has limited application for irrigation scheduling of crops. On a diurnal basis, our observation
that the maximum Ψ_w in the plant (based on Ψ_{trunk}), widely accepted as the Ψ_{pd} (Boyer, 1995), occurred
around 0700-0800 h, 2-3 hours after sunrise and that reported in the literature (Chone *et al.*, 2001;
Correia *et al.*, 1995; Williams and Araujo, 2002). The fundamental requirement for the equilibration
of plant and soil Ψ_w is that (nocturnal) transpiration is zero or near zero, which is sometimes not the
case in well-watered crops in warm-to-hot climates (Pagay, 2016). Previous studies characterising
diurnal canopy *E* showed that *E* reaches its minimum value (zero or near-zero) around 0100 h under
low VPD conditions and around 0600 h under high VPD conditions, under well-watered conditions
(Pagay, 2016). Using sap flow sensors in grapevines, Braun and Schmid (1999) observed that the
minimum canopy *E* for the day was reached around 2100 h, and *E* did not start increasing until approx.

0900 h, several hours after dawn, the next day. Differences between the times of minimum E and
highest Ψ_w diurnally may be the result of hydraulic resistances in the soil-plant continuum, which are
influenced by soil type, soil moisture, ambient VPD, and root biomass and distribution (Garcia-Tejera
et al., 2021; Sato *et al.*, 2006). Our observations of maximum plant Ψ_w being reached in the early
morning, between 0700-0800 h, are consistent with another study reporting that Ψ_{stem} does not start
decreasing from its maximum diurnal value until the early morning, approx. 0700 h (Cole and Pagay,
2015), but in contrast to another report that Ψ_{pd} decreases from 0330 h (Carbonneau *et al.*, 2004).
The observation has implications for the timing of measurement of Ψ_{pd}, if used as a metric for crop
irrigation scheduling as recommended previously (Stricevic and Caki, 1997). Donovan *et al.* (2001)
found that Ψ_{pd} and Ψ_p in several woody plants may not reflect Ψ_m even under well-watered conditions
without nocturnal transpiration. This was hypothesized to be due to the accumulation of high
concentrations of solutes in the leaves, although grapevines have only modest levels of osmotic
adjustment compared to many other woody horticultural crops (Rodrigues *et al.*, 1993).

Which plant water potential metric to use for irrigation scheduling?

MTs offer yet another plant water status metric, Ψ_{trunk}, that has been shown in this study to have a
different range of values compared to conventional measures of Ψ_{leaf} and Ψ_{stem}. These conventional
metrics have been well characterised for irrigation scheduling and thresholds have been suggested in
the literature (Deloire and Heyns, 2011; Romero *et al.*, 2010).

i.   Leaf water potential
The Ψ_{leaf} is a convenient measurement with the use of a leaf pressure chamber, although time and
labour intensive. The inherent variability of leaves in a plant (and even within a shoot or branch) make
this metric highly variable in its value (McCutchan and Shackel, 1992). Jones (1990) suggested that
Ψ_{leaf} may be an erroneous indicator of plant water status as Ψ_{leaf} homeostasis may occur under
different soil moisture and environmental conditions. This homeostasis in Ψ_{leaf} is exemplified no better
than in plants that lie at the opposite ends of the isohydric-anisohydric spectrum. Tardieu and
Simonneau (1998) found that in sunflower and barley, characterised as anisohydric where there is
weak coupling between soil moisture and stomatal conductance (g_s), Ψ_{leaf} declined in relation to VPD
and soil moisture. In contrast, maize, characterised as near-isohydric, where stomatal closure occurs
with declining soil moisture, Ψ_{leaf} was virtually unchanged under declining soil moisture until near
death. Grapevines cultivars also have been shown to vary in their homeostasis in Ψ_{leaf} under declining
soil moisture. For example, Syrah (syn. Shiraz) was shown to be relatively anisohydric compared to
Grenache, which was near-isohydric (Schultz, 2003). The differential response between cultivars is
thought to be related to leaf and xylem abscisic acid and hydraulic regulation (Dayer *et al.*, 2020).
Based on these physiological responses, the use of Ψ_{leaf} for irrigation scheduling of relatively isohydric
plants may underestimate their true water stress and therefore irrigation requirements potentially
leading to a vicious cycle.

ii.   Stem water potential
The Ψ_{stem} overcomes some of the liabilities associated with Ψ_{leaf}, particularly that of leaf-level
variability with a shoot or branch, as it integrates all the leaves of that shoot/branch, and is therefore
less variable than Ψ_{leaf} (Williams and Araujo, 2002). The Ψ_{stem} was also shown to be a more sensitive
indicator of plant water status than Ψ_{leaf} (Garnier and Berger, 1985) and could reliably discriminate
soil moisture deficits (Chone *et al.*, 2001) earlier than both Ψ_{leaf} and Ψ_{pd} (Selles and Berger, 1990).
Despite these advantages, from a practical standpoint, Ψ_{stem} is somewhat more involved, requiring
leaves to be enclosed in opaque bags to stop transpiration and allow Ψ_{leaf} and Ψ_{leaf} to equilibrate; this
needs to be done at least one hour prior to measurement in the pressure chamber (Chone *et al.*,

2001). This delayed measurement is not amenable to rapid measurements or automation, which
applies to Ψ_{leaf} also.

iii.   Trunk water potential

The Ψ_{trunk} is arguably the most stable of these three metrics, integrating all the leaves of the plant in
a stable tissue that is relatively unaffected by external factors as are Ψ_{leaf} and Ψ_{stem}. Our measurements
of these three vine Ψ_w metrics indicated that, in some instances, Ψ_{trunk} tended to be nearly 1 MPa
higher than Ψ_{leaf}, indicative of the high hydraulic resistances between the trunk and leaves. Previous
reports have shown that the highest hydraulic resistance in this pathway lies in the leaf, representing
as much as 30% of the overall resistance in the plant (Sack *et al.*, 2003), likely due to the fewer and
narrower xylem vessels in this section of the pathway compared to distal sections. The Ψ_{trunk} was also
susceptible to the least fluctuations diurnally, although this was only shown to be true under low VPD
conditions (Fig. 2). Its central location in the plant between the roots and leaves, as well as buffering
of xylem water status (pressure potential) via capacitance from adjoining parenchymal cells and
secondary xylem (Meinzer *et al.*, 2009) would be plausible reasons for the stability of the trunk's water
status. However, we observed that Ψ_{trunk} responded to changes in soil moisture (via irrigations) less
rapidly than to changes in VPD (Fig. 3), which suggests that the trunk may be well-coupled to the
leaves despite the high hydraulic resistances in the leaf petioles. A related and somewhat surprising
observation was made under high VPD conditions: we consistently observed the crossing over of the
Ψ_{trunk} and Ψ_{stem} lines in the mid-afternoon (Fig. 2e,k). The lower Ψ_{trunk} value (compared to Ψ_{stem}) during
warm afternoons indicates that the trunks of both cultivars were under considerably more water
stressed than the stems and similar to the leaves late in the afternoon. A plausible explanation for this
response is that the roots may be under water stress owing to transient water deficits at the soil-root
interface due to high transpiration rates under high VPD conditions. Pagay *et al.* (2016) reported that,
under high VPD conditions, low plant water potentials could result, if the capillary conductivity of soils
in the rhizosphere is inadequate to support high canopy transpiration rates.

Continuous measurements of Ψ_{trunk} using *in situ* microtensiometers, which were demonstrated in
field-grown plants for the first time in this study, offers a convenient measurement of plant water
status for irrigation scheduling. Furthermore, these *in situ* measurements of plant water potential
provide a powerful tool for physiological studies of plant hydraulics in a dynamic environment, for
example, studies on the limiting water potentials of plants as well as those involving cavitation and
embolism recovery dynamics. Microtensiometers are also amenable to automation, for example to
automate irrigation scheduling via a decision support system in which thresholds of Ψ_{trunk} are pre-
programmed in irrigation controllers for various crop phenological stages and that also incorporate
other relevant environmental parameters such as weather forecast and soil moisture data for
precision irrigation. The use of published Ψ_{stem} or Ψ_{leaf} thresholds to drive irrigation decisions should
be based on measurements of the specific metric for which the threshold has been developed; a
translation of those values to Ψ_{trunk} would not be appropriate due to physiological, hydraulic and
anatomical differences between plants.

Data availability statement

The data supporting the findings of this study are available upon request from the author.

Acknowledgements

The author thanks the following individuals for assistance with the project: Dr Franziska Doerflinger
(Plant and Food Research Australia), Dr Michael Santiago (FloraPulse), Mr Popolopoulos, Felipe

Canela, and Rochelle Schlank. The project was supported by funding from Wine Australia (project: UA
1803-1.3), and in-kind support by Katnook Estate and Wynns Coonawarra Estate.

References

Ameglio T, Archer P, Cohen M, Valancogne C, Daudet FA, Dayau S, Cruiziat P. 1999. Significance and
limits in the use of predawn leaf water potential for tree irrigation. Plant and Soil **207**, 155-167.

Black WL, Santiago M, Zhu SY, Stroock AD. 2020. *Ex situ* and *in situ* measurement of water activity
with a MEMS tensiometer. Analytical Chemistry **92**, 716-723.

Boyer JS. 1995. *Measuring the water status of plants and soils*: Academic Press.

Braun P, Schmid J. 1999. Sap flow measurements in grapevines (*Vitis vinifera* L.) - 1. Stem morphology
and use of the heat balance method. Plant and Soil **215**, 39-45.

Bureau_of_Meteorology. 2021.
http://www.bom.gov.au/climate/averages/tables/cw_026091.shtml. Date accessed: 03/04/2021.

Carbonneau A, Deloire A, Costanza P. 2004. Leaf water potential meaning of different modalities of
measurements. Journal International Des Sciences De La Vigne Et Du Vin **38**, 15-19.

Chatfield C, Xing H. 2019. *The analysis of time series : an introduction with R*. Boca Raton: CRC Press,
Taylor & Francis Group.

Cheong JH. 2020. Four ways to quantify synchrony between time series data.
https://doi.org/10.17605/OSF.IO/BA3NY. Accessed 15/03/2021.

Chone X, van Leeuwen C, Dubourdieu D, Gaudillere JP. 2001. Stem water potential is a sensitive
indicator of grapevine water status. Annals of Botany **87**, 477-483.

Cole J, Pagay V. 2015. Usefulness of early morning stem water potential as a sensitive indicator of
water status of deficit-irrigated grapevines (*Vitis vinifera* L.). Scientia Horticulturae **191**, 10-14.

Collins M, Loveys B. 2010. Optimising irrigation for different cultivars. Final report to Grape and Wine
Research & Development Corporation. Project Number CSP 05/02.

Corell M, Giron IF, Galindo A, Torrecillas A, Torres-Sanchez R, Perez-Pastor A, Moreno F, Moriana A.
2014. Using band dendrometers in irrigation scheduling Influence of the location inside the tree and
comparison with point dendrometer. Agricultural Water Management **142**, 29-37.

Cormier J, Depardieu C, Letourneau G, Boily C, Gallichand J, Caron J. 2020. Tensiometer-based
irrigation scheduling and water use efficiency of field-grown strawberries. Agronomy Journal **112**,
2581-2597.

Correia MJ, Pereira JS, Chaves MM, Rodrigues ML, Pacheco CA. 1995. ABA xylem concentrations
determine maximum daily leaf conductance of field-grown *Vitis vinifera* L plants. Plant Cell and
Environment **18**, 511-521.

Dayer S, Scharwies JD, Ramesh SA, Sullivan W, Doerflinger FC, Pagay V, Tyerman SD. 2020.
Comparing hydraulics between two grapevine cultivars reveals differences in stomatal regulation
under water stress and exogenous ABA applications. Frontiers in Plant Science **11**.

Deloire A, Heyns D. 2011. The leaf water potentials: principles, method and thresholds. Wineland
Magazine technical yearbook, 129-131.

Dixon MA, Tyree MT. 1984. A new stem hygrometer, corrected for temperature gradients and
calibrated against the pressure bomb. Plant Cell and Environment **7**, 693-697.

Donovan LA, Linton MJ, Richards JH. 2001. Predawn plant water potential does not necessarily
equilibrate with soil water potential under well-watered conditions. Oecologia **129**, 328-335.

Freeman BM, Kliewer WM, Stern P. 1982. Influence of windbreaks and climatic region on diurnal
fluctuation of leaf water potential, stomatal conductance, and leaf temperature of grapevines.
American Journal of Enology and Viticulture **33**, 233-236.

Garcia-Tejera O, Lopez-Bernal A, Orgaz F, Testi L, Villalobos FJ. 2021. The pitfalls of water potential
for irrigation scheduling. Agricultural Water Management **243**.

Garnier E, Berger A. 1985. Testing water potential in peach trees as an indicator of water stress.
Journal of Horticultural Science **60**, 47-56.

Ginestar C, Eastham J, Gray S, Iland P. 1998. Use of sap-flow sensors to schedule vineyard irrigation.
I. Effects of post-veraison water deficits on water relations, vine growth, and yield of Shiraz grapevines.
American Journal of Enology and Viticulture **49**, 413-420.

Jones HG. 1990. Physiological aspects of the control of water status in horticultural crops. Hortscience
25, 19-26.

Jones HG. 1999. Use of infrared thermometry for estimation of stomatal conductance as a possible
aid to irrigation scheduling. Agricultural and Forest Meteorology **95**, 139-149.

Jones HG. 2007. Monitoring plant and soil water status: established and novel methods revisited and
their relevance to studies of drought tolerance. Journal of Experimental Botany **58**, 119-130.

Klepper B. 1968. Diurnal pattern of water potential in woody plants. Plant Physiology **43**, 1931-1934.

McBurney T, Costigan PA. 1984. Rapid oscillations in plant water potential measured with a stem
psychrometer. Annals of Botany **54**, 851-853.

McCutchan H, Shackel KA. 1992. Stem water potential as a sensitive indicator of water stress in prune
trees (*Prunus domestica* L cv French). Journal of the American Society for Horticultural Science **117**,
607-611.

Meinzer FC, Johnson DM, Lachenbruch B, McCulloh KA, Woodruff DR. 2009. Xylem hydraulic safety
margins in woody plants: coordination of stomatal control of xylem tension with hydraulic
capacitance. Functional Ecology **23**, 922-930.

Meron M, Goldberg SY, Solomon-Halgoa A, Ramon G. 2015. Embedded stem water potential sensor.
In: Stafford, ed. *Precision agriculture '15*: Wageningen Academic Publishers, Wageningen, 527-532.

Michel BE. 1977. Miniature stem thermocouple hygrometer. Plant Physiology **60**, 645-647.

Olsson KA, Milthorpe FL. 1983. Diurnal and spatial variation in leaf water potential and leaf
conductance of irrigated peach trees. Australian Journal of Plant Physiology **10**, 291-298.

Pagay V. 2016. Effects of irrigation regime on canopy water use and dry matter production of
'Tempranillo' grapevines in the semi-arid climate of Southern Oregon, USA. Agricultural Water
Management **178**, 271-280.

Pagay V, Santiago M, Sessoms DA, Huber EJ, Vincent O, Pharkya A, Corso TN, Lakso AN, Stroock AD.
2014. A microtensiometer capable of measuring water potentials below-10 MPa. Lab on a Chip **14**,
2806-2817.

Pagay V, Skinner A. 2018. Continuous *in situ* measurements of crop water stress in 'Shiraz' grapevines
using a thermal diffusivity sensor. In: Herppich WB, ed. *International Symposium on Sensing Plant
Water Status - Methods and Applications in Horticultural Science*, Vol. 1197, 83-88.

Pagay V, Zufferey V, Lakso AN. 2016. The influence of water stress on grapevine (*Vitis vinifera* L.)
shoots in a cool, humid climate: growth, gas exchange and hydraulics. Functional Plant Biology **43**,
827-837.

Podobnik B, Stanley HE. 2008. Detrended cross-correlation analysis: A new method for analyzing two
nonstationary time series. Physical Review Letters **100**.

Richards LA. 1942. Soil moisture tensiometer materials and construction. Soil Science **53**, 241-248.

Rodrigues ML, Chaves MM, Wendler R, David MM, Quick WP, Leegood RC, Stitt M, Pereira JS. 1993.
Osmotic adjustment in water-stressed grapevine leaves in relation to carbon assimilation. Australian
Journal of Plant Physiology **20**, 309-321.

Romero P, Fernandez-Fernandez JI, Martinez-Cutillas A. 2010. Physiological thresholds for efficient
regulated deficit irrigation management in winegrapes grown under semiarid conditions. American
Journal of Enology and Viticulture **61**, 300-312.

Sack L, Cowan PD, Jaikumar N, Holbrook NM. 2003. The 'hydrology' of leaves: co-ordination of
structure and function in temperate woody species. Plant Cell and Environment **26**, 1343-1356.

Salomón RL, Limousin J-M, Ourcival J-M, Rodríguez-Calcerrada J, Steppe K. 2017. Stem hydraulic
capacitance decreases with drought stress: implications for modelling tree hydraulics in the
Mediterranean oak *Quercus ilex*. Plant, Cell & Environment **40**, 1379-1391.

Sato T, Abdalla OS, Oweis TY, Sakuratani T. 2006. Effect of supplemental irrigation on leaf stomatal
conductance of field-grown wheat in northern Syria. Agricultural Water Management **85**, 105-112.

Scalisi A, Bresilla K, Grilo F. 2017. Continuous determination of fruit tree water-status by plant-based
sensors. Italus Hortus **24**, 39-50.

Schmidhalter U. 1997. The gradient between pre-dawn rhizoplane and bulk soil matric potentials, and
its relation to the pre-dawn root and leaf water potentials of four species. Plant Cell and Environment
20, 953-960.

Scholander PF, Hammel HT, Bradstreet ED, Hemmingsen EA. 1965. Sap pressure in vascular plants -
negative hydrostatic pressure can be measured in plants. Science **148**, 339-346.

Schultz HR. 2003. Differences in hydraulic architecture account for near-isohydric and anisohydric
behaviour of two field-grown Vitis vinifera L. cultivars during drought. Plant Cell and Environment **26**,
1393-1405.

Selles G, Berger A. 1990. Physiological indicators of plant water status as criteria for irrigation
scheduling. International Symposium on Scheduling of Irrigation for Vegetable Crops under Field
Condition, Vols 1 and 2 **278**, 87-100.

Shackel K. 2011. A plant-based approach to deficit irrigation in trees and vines. Hortscience **46**, 173-
177.

Smart RE. 1974. Aspects of water relations of grapevine (*Vitis vinifera*). American Journal of Enology
and Viticulture **25**, 84-91.

Smart RE, Barrs HD. 1973. Effect of environment and irrigation interval on leaf water potential of 4
horticultural species. Agricultural Meteorology **12**, 337-346.

Stricevic R, Caki E. 1997. Relationships between available soil water and indicators of plant water
status of sweet sorghum to be applied in irrigation scheduling. Irrigation Science **18**, 17-21.

Suter B, Triolo R, Pernet D, Dai ZW, Van Leeuwen C. 2019. Modeling stem water potential by
separating the effects of soil water availability and climatic conditions on water status in grapevine
(*Vitis vinifera* L.). Frontiers in Plant Science **10**.

Tardieu F, Simonneau T. 1998. Variability among species of stomatal control under fluctuating soil
water status and evaporative demand: modelling isohydric and anisohydric behaviours. Journal of
Experimental Botany **49**, 419-432.

Tran N, Graham T, Zhang P, Bam P, Black K, Reeves R, Downey A, Dixon M. 2014. Irrigation
management strategies for nursery trees based on plant water status measured with automated stem
psychrometers. *CSPB Conference, CSPB Conference – Irrigation Management Strategies for Nursery*
Trees. Guelph, Ontario, Canada.

van Zyl JJ. 1987. Diurnal variation in grapevine water stress as a function of changing soil water status
and meteorological conditions. South African Journal of Enology and Viticulture **8**, 45-52.

Waring RH, Running SW. 1978. Sapwood water storage: its contribution to transpiration and effect
upon water conductance through the stems of old-growth Douglas-fir. Plant, Cell & Environment **1**,
131-140.

Williams LE, Araujo FJ. 2002. Correlations among predawn leaf, midday leaf, and midday stem water
potential and their correlations with other measures of soil and plant water status in Vitis vinifera.
Journal of the American Society for Horticultural Science **127**, 448-454.

Williams LE, Baeza P. 2007. Relationships among ambient temperature and vapor pressure deficit and
leaf and stem water potentials of fully irrigated, field-grown grapevines. American Journal of Enology
and Viticulture **58**, 173-181.

Williams LE, Baeza P, Vaughn P. 2012. Midday measurements of leaf water potential and stomatal
conductance are highly correlated with daily water use of Thompson Seedless grapevines. Irrigation
Science **30**, 201-212.

Zufferey V, Cochard H, Ameglio T, Spring JL, Viret O. 2011. Diurnal cycles of embolism formation and
repair in petioles of grapevine (*Vitis vinifera* cv. Chasselas). Journal of Experimental Botany **62**, 3885-
3894.