CellProfiler 4: Improvements in Speed, Utility and Usability

David R. Stirling[1], Madison J. Swain-Bowden[2], Alice M. Lucas[1], Anne E. Carpenter[1], Beth A. Cimini[1]*^,
Allen Goodman[1]*

[1]= Imaging Platform, Broad Institute of MIT and Harvard, Cambridge MA, USA

[2]= Software Department, Allen Institute for Cell Science, Seattle, WA, USA

***= These authors contributed equally**

^= To whom correspondence should be addressed, bcimini@broadinstitute.org

CellProfiler 4: Improvements in Speed, Utility and Usability

<u>**Abstract**</u>

Background

Imaging data contains a substantial amount of information which can be difficult to evaluate by

eye. With the expansion of high throughput microscopy methodologies producing increasingly large

datasets, automated and objective analysis of the resulting images is essential to effectively extract

biological information from this data. CellProfiler is a free, open source image analysis program which

enables researchers to generate modular pipelines with which to process microscopy images into

interpretable measurements.

Results

Herein we describe CellProfiler 4, a new version of this software with expanded functionality.

Based on user feedback, we have made several user interface refinements to improve the usability of

the software. We introduced new modules to expand the capabilities of the software. We also evaluated

performance and made targeted optimizations to reduce the time and cost associated with running

common large-scale analysis pipelines.

Conclusions

CellProfiler 4 provides significantly improved performance in complex workflows compared to

previous versions. This release will ensure that researchers will have continued access to CellProfiler's

powerful computational tools in the coming years.

<u>**Keywords**</u>

Image Analysis, Microscopy, Image Segmentation, Image Quantitation, Bioimaging

Background

Microscopy can be used to capture images which contain a wealth of information that can

inform biomedical research. Image analysis software can allow scientists to obtain quantitative

measurements from images that are otherwise difficult to capture via subjective observation. The

increasing use of automated microscopy now allows researchers to capture images of samples treated

with many thousands of individual compounds or genetic perturbations. Scientists increasingly image

cells in 3D or across time series; this expanding bulk of raw data necessitates automated processing and

analysis. Such analysis is best achieved through using software to perform automated detection of cells

or organisms and extract quantitative metrics which objectively describe the specimens.

Many microscopes are now sold with accompanying proprietary analysis packages, such as

MetaMorph (Molecular Devices), Elements (Nikon), Zen (Zeiss) and Harmony (Perkin Elmer). These

ecosystems are powerful but can lack the flexibility to work with data from other manufacturers'

equipment. Cost of these proprietary solutions can also limit accessibility, and their closed-source

nature can obscure exactly how scientists' data is being analyzed. Free, open-source software

packa(1)ges such as ImageJ, CellProfiler, QuPath, Ilastik and many others have therefore become

popular analysis tools used by researchers. ImageJ is the most widely-used package and excels in

performing analysis of single images, assisted by a vast array of community-developed plugins (1).

Numerous smaller packages are tooled towards specific types of data: for example, QuPath is a popular

program geared specifically towards pathology applications (2), while Ilastik delivers an interactive

machine learning framework to assist users in segmenting images (3).

In 2005 we introduced CellProfiler, an open-source image analysis program which allows users

without specific training to automate their image analysis by using modular processing pipelines (4).

CellProfiler has been widely adopted by the community, and is currently referenced more than 2000

times per year. Built-in modules provide a diverse array of algorithms for analyzing images, which can be

further extended through the use of community-developed plugins. In an independent analysis of 15

free image analysis tools CellProfiler scored highly in both usability and functionality (5). Our previous

release, CellProfiler 3, introduced support for analysis of 3D images to further expand the tool's

applications (6). However, some popular features from CellProfiler 2 could not be brought forward into

that release and certain modules struggled to operate efficiently in 3D pipelines.

<u>Implementation</u>

CellProfiler was originally written in MATLAB, but in 2010 was rewritten in Python 2, which

reached its official end-of-life in 2020. In order to ensure ongoing compatibility with future operating

systems we ported the software to the Python 3 language to create CellProfiler 4. This provided the

opportunity for a broader restructuring of the software's code to improve performance, reliability and

utility. CellProfiler 4 is available for download at cellprofiler.org.

As part of the migration to Python 3, we split the CellProfiler source code into two packages:

cellprofiler and cellprofiler-core. The new cellprofiler-core package contains all the critical functionality

needed to execute CellProfiler pipelines, whereas the cellprofiler repository now primarily contains the

user interface code and built-in modules. The core package has been developed to introduce a stable

API which will allow users to access CellProfiler's functionality as a Python package within popular

environments such as Jupyter (7) and for future integration with other packages and software suites.

User interface refinements

Guided by feedback from biologists, we have made several improvements to the CellProfiler

user interface with the goal of making the software more accessible and easier to use. The basic 3D

viewer introduced in CellProfiler 3.0 has now been replaced with a more fully-featured viewer which

allows users to inspect any plane in a volume (Figure 1A). We have also expanded the figure contrast

dialogs to give users more granular control over how images are displayed in both 2D and 3D mode

(Figure 1B). These changes will help users to better visualize and understand their data.

Other changes make it easier to develop and configure pipelines. We added an interface to

visualize which modules produce inputs needed by, or use outputs from, a module of interest, which will

aid in modifying complex pipelines (Figure 1C). We also revised the interface for selecting multiple

images for analysis within a module, replacing dropdown menus with a checklist in which multiple

images can be selected quickly and efficiently (Figure 1D). Furthermore, a new search filter in the "Add

module" popup allows users to more easily find desired modules by module name rather than by

category (Figure 1E).

We also restored some features which were previously lost in the migration from CellProfiler 2

to CellProfiler 3. Most notably, we rebuilt the Workspace Viewer, where users construct a customized

view of their data and can stay focused on a specific region of interest as the pipeline is modified (Figure

1F), making it much simpler to monitor and refine segmentation of problematic regions of an image. In

addition, new icons in the Test Mode pipeline interface provide a stronger visual indication of which

module is currently about to be executed, and provide the ability to return to and execute earlier

modules in the pipeline. This replicates and replaces the functionality of the slider widget from

CellProfiler 2, which could not be carried forward into CellProfiler 3 but was popular with users.

New and restored features

In CellProfiler 4 we introduced several new analysis features and settings. A common workflow

issue we identified was that analysts often segment highly variable objects in multiple stages (such as

segmenting and masking out bright objects to aid segmentation of similar-but-dimmer objects), but

previous versions could not simply treat resulting segmentations as a single object set when performing

and exporting measurements. To resolve this we added the CombineObjects module to allow users to

merge sets of objects which have been defined separately. A key issue when designing this module was

how to handle objects that would overlap if the sets were merged, therefore we built several strategies

detailed in Figure 2. The resulting merged set can then be carried forward throughout the pipeline

without the need to merge measurement tables outside of CellProfiler.

Many users were disappointed with the loss of the RunImageJ module (8) in CellProfiler 2.2; we

have now replaced it with the new RunImageJMacro module. The new module allows a user to export

images from CellProfiler into a temporary directory, execute a custom ImageJ macro on that directory

and then automatically import resulting processed images back into CellProfiler. In practice this will

allow users to access ImageJ functions and plugins within a CellProfiler pipeline, greatly expanding its

interoperability. Unlike its predecessor, the RunImageJMacro module relies on the user's copy of ImageJ

rather than a built-in copy. This allows users to take advantage of any new ImageJ upgrades and

simultaneously poses less danger to CellProfiler's stability because releases between the two softwares

need not be kept in sync.

We also upgraded several existing modules. We rewrote the Threshold module to allow all pre-

existing threshold strategies to be used in 'adaptive' mode, giving users more options in images with

highly-variable background. We have also added the Sauvola local thresholding method as an alternative

adaptive strategy (9). Previous versions of CellProfiler 2 shipped a version of the Otsu thresholding

method that log-transformed the data before applying the threshold; this assisted in the thresholding of

dim images, but led users to question why our Otsu values did not match those from other libraries such

as scikit-image (10). This inconsistent behavior could be confusing to users, so we began the process of

updating that implementation in CellProfiler 3 and completed it in CellProfiler 4. We added a dedicated

setting to log transform image data during application of any thresholding method. These new options

will assist users in segmenting challenging images.

New Measurements

We overhauled some measurement modules in CellProfiler 4. We redesigned

MeasureObjectSizeShape to record additional measurements now available in scikit-image, including

bounding box locations, image moments and inertia tensors, producing up to 60 new shape

measurements per object. We anticipate that these new features may be of particular value for training

machine learning models, which play an increasingly important role in performing object classification

on large data sets. In addition to new features, several of the previously 2D-exclusive measurements,

such as Euler Number and Solidity, are now also available when working with 3D images. Together these

expanded measurements provide researchers with even more metrics with which to investigate cellular

phenotypes.

<u>**Results**</u>

Performance improvements

A key focus in producing CellProfiler 4 has been improving performance of the software and

addressing common issues encountered by users. We revised our build packaging process to more

reliably bundle CellProfiler's Java dependencies so that additional software and system configuration is

no longer required to use the program. In doing so we also optimized the program's startup sequence,

which provided a substantial improvement in the time taken to initialize the software (Figure 3A).

Another critical area of focus for improvement has been in file loading (input/output, or I/O operations).

Combined improvements in Python's underlying directory scanning functions and optimizations to

CellProfiler's image loading procedures have dramatically reduced the time needed to add large folders

of images to the file list. This is particularly noticeable when using networked storage.

In our performance testing of an example analysis pipeline, overall performance was similar to

CellProfiler 3 (Figure 3B). However, executing this pipeline in Test Mode was inhibited by unnecessary

user interface updates between running individual modules. Optimizing the UI updates sent during test

mode reduced the time taken to run an image set in this mode (Figure 3C).

3   Running more complex analysis workflows such as 3D segmentation and the commonly used

4   Cell Painting assay (11) was time-consuming in CellProfiler 3. We therefore aimed to identify and refine

5   modules which displayed long execution times in these scenarios.

6   Optimizations across all modules produced a 50% performance improvement when running 3D

pipelines such as the 3D monolayer tutorial dataset (Figure 3D) (12). Within 3D workflows we had

identified the MedianFilter module as being particularly slow to process. By switching to the new

scipy.ndimage filter implementation we were able to substantially reduce the time taken to process

each image (Figure 4A).

Another key target was the MeasureTexture module, which exhibited long run times when

performing per-object measurements. Analysis revealed that this was caused by per-object functions

processing full-size masked arrays for each object to be measured. To improve performance we adjusted

these functions to produce and process arrays cropped down to the particular region of interest for each

object. In our testing this reduced the time taken to analyze each image from minutes down to seconds,

without any change in the resulting measurements (Figure 4B).

Major gains were also made in measurement of the Costes Colocalization Coefficient in the

MeasureColocalization module. This statistic requires the calculation of Costes' automatic threshold,

which is generated by thresholding the two images to be compared and then serially reducing the

thresholding value until the Pearson R correlation between the two thresholded images drops below a

value of 0. Our original implementation would reduce the candidate value in images scaled 0-1 by 1/255

at each step, which was inappropriate for 16-bit images containing 65,536 grey levels rather than the

256 present in 8 bit images. Testing 65,536 candidate thresholds in 16-bit images would be excessively

slow, so we introduced optional alternative implementations of the Costes automated thresholding method to resolve this inefficiency. Our first optimization maintained the canonical strategy of evaluating every possible threshold, but only measured the Pearson R correlation of the thresholded images if the new value produced a different total number of thresholded pixels than the previous value. We termed this "accurate" mode, but in images with large numbers of unique pixel values performance was unacceptably slow. We therefore introduced "fast" mode to the module, in which the candidate threshold is decreased in larger steps if the previous Pearson R value was substantially higher than 0. This improved performance when working with 8-bit images (Figure 5A), but was still inefficient with 16-bit images (Figure 5B). We subsequently devised an alternative implementation, dubbed "faster" mode, in which a weighted bisection search algorithm is used to consecutively narrow a window of possible target thresholds. By reducing the candidate window by 1/6 each cycle, we were able to calculate identical thresholds to the "accurate" method in seconds rather than hours. This opens up the ability to perform efficient Costes Colocalization calculations on 16-bit images (Figure 5B). In theory these accelerated methods could 'overshoot' the target threshold by a small margin in rare instances, but in our testing they consistently produced identical results to the "accurate" implementation. Nonetheless we have made all three strategies ("accurate", "fast" and "faster") available within the module settings. Other colocalization methods did not suffer from the same degree of performance issues, but additionally updating them to newer implementations reduced the time taken for the module to process without Costes features enabled (Figure 4C).

Together, these improvements will substantially reduce the computational time and power necessary to process images, particularly when working with large, complex data sets. This will have the added benefits of reducing resource costs for researchers, making large-scale analysis with CellProfiler more affordable and accessible. The reduction in analysis time will also reduce the environmental impact of running such pipelines.

Performance in common workflows

To examine the impact of our changes on performance on a large heterogeneous workflow, we compared the performance of CellProfiler 3 to CellProfiler 4 when running the Cell Painting assay protocol (11). This workflow is typically performed on large datasets in a cluster environment, so we selected a sample of 48 image sets from a published dataset and measured processing times on a single machine. Execution times were captured for each module across three independent runs of this dataset. The sum of these timings represents the total workload executed by each module, excluding file I/O operations. These measurements revealed a 10-fold reduction in total CPU time required to analyze each image (Figure 6A).

In keeping with our expectations, the refinements to MeasureTexture contributed the majority of the performance improvements that we observed (Figure 6B). We also noted small improvements in the MeasureImageQuality (Figure 6C), IdentifyPrimaryObjects (Figure 6D), MeasureGranularity (Figure 6E) and MeasureObjectSizeShape (Figure 6F) modules. Other modules in the pipeline exhibited similar performance in both versions or took negligible time to execute (Figure S1).

Discussion

As the adoption of high content microscopy methods continues to expand there may be several areas where CellProfiler could be expanded with new functionality. Analysis of tissue sections stands out as a potential area of improvement. The large file sizes associated with tissue specimens pose a challenge for image analysis, as system memory typically is not sufficient to load the entire image at once, a bottleneck which could be avoided by adopting packages such as Dask (13) as a means of handling such images by loading subsections of an image on-demand. This would expand the utility of CellProfiler within the digital pathology field.

We also aim to continue adding support for 3D analysis to modules that currently only support

2D workflows. While segmentation is possible in 3D pipelines, additional tools and measurements will

be valuable for laboratories using CellProfiler. Alongside this, further performance improvements will

continue to benefit researchers, particularly when working with large datasets.

The splitting of cellprofiler-core into a standalone package has also laid the groundwork for

producing a stable API for use in other Python-based applications. This will eventually allow users to

modify and execute pipelines from within environments such as Jupyter, which may be of benefit to

researchers looking to automate complex workflows. This API could provide a higher-level interface for

common image processing tasks such as object segmentation, which would simplify the workflow for

analyzing images directly within a Python environment and could serve as a bridge to Python tools

whose GUI is incompatible with CellProfiler's, such as Napari (14). The current implementation provides

access to all of CellProfiler's important classes and the ability to run pipelines or individual modules. For

future development we would like to introduce a more convenient system for programmatically

generating image sets without the need for the original input modules or CSV files.

In recent years there has been considerable development towards deep learning models which

can perform image segmentation in an automatic manner. Providing access to these algorithms would

be of substantial benefit to CellProfiler's users, however the need for dedicated hardware and software

to run these models poses a challenge for packaging and distribution. To avoid compatibility issues with

older hardware, as well as to minimise the software dependencies needed to run CellProfiler, our

approach has been to develop independent plugin modules which are distributed separately from the

main CellProfiler program. For CellProfiler 3 we previously released a plugin for NucleAIzer (15), and in

the future we hope to investigate integrations with other popular models such as Cellpose (16) and

Stardist (17).

Conclusions

The migration of CellProfiler to Python 3 will ensure that the software will remain accessible and

maintainable in the coming years. In CellProfiler 4 we have further refined the user interface and

introduced new modules and features to help scientists to develop and execute their analysis

workflows. The targeted performance improvements in this version will substantially reduce

computational costs associated with high throughput image analysis, broadening the potential

applications for this open-source software package.

Availability and Requirements

Project name: CellProfiler

Project home page: https://cellprofiler.org/

Operating system(s): Windows, MacOS, Linux

Programming language: Python 3

Other requirements: Java 1.6+ (JDK 14 bundled with builds)

License: BSD 3-Clause License

Any restrictions to use by non-academics: None

List of Abbreviations

API - Application Programming Interface

CP3 - CellProfiler 3

CP4 - CellProfiler 4

I/O - input/output

Declarations

Ethics approval and consent to participate

Not applicable.

Consent to publish

Not applicable.

Availability of data and materials

CellProfiler 4 is open-source software which has been made freely available to the scientific community.

Pre-compiled builds for Windows and MacOS, as well as documentation manuals, are available at

http://cellprofiler.org. Source code is available at https://github.com/CellProfiler/CellProfiler.

Benchmarking and visualizations presented in Figures 1C, 1D, 1F, 3A-C, 4B-C, and 5A was performed

with the publicly available pipelines and image set

"ExampleFly"(https://github.com/CellProfiler/examples/tree/master/ExampleFly)). Benchmarking and

visualizations presented in Figures 1A, 3D, and 4A were performed with the publicly available "3D

Monolayer" pipeline and image set which can be accessed at

https://github.com/CellProfiler/tutorials/tree/master/3d_monolayer . Cell Painting benchmarking

experiments in Figures 5B, 6, and S1 made use of a previously published data set (Plate 37983 from

https://bbbc.broadinstitute.org/BBBC025) and pipeline (analysis.cppipe from

https://github.com/carpenterlab/2016_bray_natprot/blob/master/supplementary_files/cell_painting_p

ipelines.zip, cited in (11)). The pipeline for this data set was originally written for CellProfiler 2, and so

was adjusted to run on CellProfiler 3 and CellProfiler 4 with comparable outputs. These adjusted

pipelines as well as the sample data and pipeline used to produce Figure 2 are provided in a public

GitHub repository (https://github.com/carpenterlab/2021_Stirling_submitted).

Competing interests

The authors declare that they have no competing interests.

Funding

This work was supported by National Institutes of Health grants (R35 GM122547 and P41 GM135019 to

AEC). This project has been made possible in part by grant numbers 2018-192059 to AG and 2020-

225720 to BAC from the Chan Zuckerberg Initiative DAF, an advised fund of Silicon Valley Community

Foundation. The funders had no role in study design, data collection and analysis, decision to publish, or

preparation of the manuscript.

Authors' contributions

DRS, MJS-B, AML, BAC, and AG developed the software. DRS wrote the manuscript, with editorial

contribution and supervision from AEC and BAC.

Acknowledgements

The authors would like to thank Katrin Leinweber, Vito Zanotelli, Erin Weisbart, Chris Allen, Nasim

Jamali, and Pearl Ryder for contributions to bug fixes and testing of pre-release versions of this software.

We also thank all the members of the bioimaging community who have provided feedback and

suggestions which have helped to guide this work.

1 References

2   1.   Schneider CA, Rasband WS, Eliceiri KW. NIH Image to ImageJ: 25 years of image analysis. Nat
3   Methods. 2012 Jul;9(7):671–5.

4   2.   Bankhead P, Loughrey MB, Fernández JA, Dombrowski Y, McArt DG, Dunne PD, et al. QuPath: Open
5   source software for digital pathology image analysis. Sci Rep. 2017 Dec 4;7(1):1–7.

6   3.   Berg S, Kutra D, Kroeger T, Straehle CN, Kausler BX, Haubold C, et al. ilastik: interactive machine
7   learning for (bio)image analysis. Nat Methods. 2019 Dec;16(12):1226–32.

8   4.   Carpenter AE, Jones TR, Lamprecht MR, Clarke C, Kang IH, Friman O, et al. CellProfiler: image
9   analysis software for identifying and quantifying cell phenotypes. Genome Biol. 2006 Oct
31;7(10):R100.

5.   Wiesmann V, Franz D, Held C, Münzenmayer C, Palmisano R, Wittenberg T. Review of free software
tools for image analysis of fluorescence cell micrographs [Internet]. Vol. 257, Journal of Microscopy.
2015. p. 39–53. Available from: http://dx.doi.org/10.1111/jmi.12184

6.   McQuin C, Goodman A, Chernyshev V, Kamentsky L, Cimini BA, Karhohs KW, et al. CellProfiler 3.0:
Next-generation image processing for biology. PLoS Biol. 2018 Jul;16(7):e2005970.

7.   Beg M, Taka J, Kluyver T, Konovalov A, Ragan-Kelley M, Thiery NM, et al. Using Jupyter for
Reproducible Scientific Workflows [Internet]. Vol. 23, Computing in Science & Engineering. 2021. p.
36–46. Available from: http://dx.doi.org/10.1109/mcse.2021.3052101

8.   Kamentsky L, Jones TR, Fraser A, Bray M-A, Logan DJ, Madden KL, et al. Improved structure,
function and compatibility for CellProfiler: modular high-throughput image analysis software.
Bioinformatics. 2011 Apr 15;27(8):1179–80.

9.   Sauvola J, Pietikäinen M. Adaptive document image binarization. Pattern Recognit. 2000
Feb;33(2):225–36.

10.   van der Walt S, Schönberger JL, Nunez-Iglesias J, Boulogne F, Warner JD, Yager N, et al. scikit-image:
image processing in Python. PeerJ. 2014 Jun 19;2:e453.

11.   Bray M-A, Singh S, Han H, Davis CT, Borgeson B, Hartland C, et al. Cell Painting, a high-content
image-based assay for morphological profiling using multiplexed fluorescent dyes. Nat Protoc. 2016
Sep;11(9):1757–74.

12.   Ljosa V, Sokolnicki KL, Carpenter AE. Annotated high-throughput microscopy image sets for
validation. Nat Methods. 2012 Jun 28;9(7):637–637.

13.   Rocklin M. Dask: Parallel computation with blocked algorithms and task scheduling. In: Proceedings
of the 14th python in science conference. Kathryn Huff and James Bergstra; 2015. p. 130–6.

14.   napari contributors (2019). napari: a multi-dimensional image viewer for python [Internet].
Available from: https://zenodo.org/record/4968798

15. Hollandi R, Szkalisity A, Toth T, Tasnadi E, Molnar C, Mathe B, et al. nucleAlzer: A Parameter-free Deep Learning Framework for Nucleus Segmentation Using Image Style Transfer. Cell Syst. 2020 May 20;10(5):453–8.e6.

16. Stringer C, Wang T, Michaelos M, Pachitariu M. Cellpose: a generalist algorithm for cellular segmentation. Nat Methods. 2021 Jan;18(1):100–6.

17. Schmidt U, Weigert M, Broaddus C, Myers G. Cell Detection with Star-Convex Polygons [Internet]. Medical Image Computing and Computer Assisted Intervention – MICCAI 2018. 2018. p. 265–73. Available from: http://dx.doi.org/10.1007/978-3-030-00934-2_30

Figure Legends

Figure 1 – User interface refinements in CellProfiler 4. (A) The new 3D viewer window with plane

controls in the top right. (B) Contrast and normalization adjustment popup available with any image

window. (C) Interface displayed when the "trace" command is called on a module. Arrow icons on the

left represent modules which provide data to or use data from the selected module (dot icon). (D)

Selection widget for choosing multiple images for analysis. Images sourced from disabled or missing

modules are highlighted. (E) "Add modules" pane in search mode, the modules list is filtered based on

the text entered into the search box. (F) The Workspace Viewer module displaying a custom overlay of

data from the example pipeline.

Figure 2 – Approaches for combining object sets within the CombineObjects module. Results represent

the output from different methods available within the module. "Merge" will join touching objects and

distribute conflicting regions to the nearest object from the initial set. "Preserve" will add only regions

of objects from the second set which did not overlap with the initial set. "Discard" will only add objects

with no overlap. "Segment" will add both object sets and re-segment disputed regions.

Figure 3 – General performance in CellProfiler 3 vs CellProfiler 4. Results represent independent runs

on a machine running Windows 10, using 1 worker process. (A) Time from launching the CellProfiler

executable to display of the full GUI (n=5). (B) Time taken to run the ExampleFly pipeline in Analysis

Mode (n=3). (C) Time to run the ExampleFly pipeline in Test Mode (n=5). (D) Time to run the 3D

monolayer tutorial pipeline in Analysis Mode (n=3).

Figure 4 – Module-specific performance improvements. Results from individual module testing on a

machine running Windows 10. (A) Execution time for the MedianFilter module running within the 3D

Monolayer pipeline (n=5). (B) Execution time when running per-object texture measurements on data

from the ExampleFly pipeline (n=5). (C) Execution time when running MeasureColocalization on 8-bit

images from the ExampleFly pipeline (n=5).

Figure 5 – Performance of alternative Costes automated thresholding strategies. Execution times for

the MeasureColocalization module performing 1 pairwise comparison with Costes features enabled,

using each algorithm on (A) 8-bit images from the ExampleFly pipeline (n=6) or (B) 16-bit images from

the example Cell Painting dataset (n=8). On 16-bit images results from CellProfiler 3 are calculated

incorrectly, but shown to illustrate relative performance.

Figure 6 – Performance of selected modules within the Cell Painting assay protocol. Numbers in

brackets within panel titles correspond to modules in Figure S1. (A) Total module execution time

(measured in CPU time) per image set for all modules in the pipeline. (B) Execution time for the

MeasureTexture module per image set. (C) Execution time for the MeasureImageQuality module per

image set. (D) Execution time for the IdentifyPrimaryObjects module per image set. (E) Execution time

for the MeasureGranularity module per image set. (F) Execution time for the MeasureObjectSizeShape

module per image set.

Figure S1 – Execution times of all modules within the Cell Painting example pipeline. Measured as per-

image CPU time taken for each module in the Cell Painting assay protocol (n=48). I/O loading operations

in the Images module are not recorded by these measurements.

Figure 1

Input:

Method:

Figure 2

Figure 3

Figure 4

a)

b)

Figure 5

Figure 6

Figure S1