High throughput measurement of *Arabidopsis thaliana* fitness traits

using deep learning

Peipei Wang[1,2‡], Fanrui Meng[1,2‡], Paityn Donaldson[1], Sarah Horan[1], Nicholas L. Panchy[3],

Elyse Vischulis[4], Eamon Winship[5*], Jeffrey K. Conner[1,6,7], Patrick J. Krysan[8], Shin-Han

Shiu[1,2,4,9], Melissa D. Lehti-Shiu[1]

[1]Department of Plant Biology, Michigan State University, East Lansing, MI, 48824, USA

[2]DOE Great Lake Bioenergy Research Center, Michigan State University, East Lansing,

MI, 48824, USA,

[3]National Institute for Mathematical and Biological Synthesis, University of Tennessee,

1122 Volunteer Blvd., Suite 106, Knoxville, TN, 37996-3410, USA

[4]Genetics and Genome Sciences Graduate Program, Michigan State University, East

Lansing, MI, 48824, USA

[5]Department Of Biochemistry and Molecular Biology, Michigan State University, East

Lansing, MI, 48824, USA

[6]W.K. Kellogg Biological Station, Michigan State University, 3700 E. Gull Lake Drive,

Hickory Corners, MI, 49060, USA.

[7]Ecology, Evolution, and Behavior Graduate Program, Michigan State University, East

Lansing, MI, 48824, USA

[8]Horticulture and Genome Center of Wisconsin, University of Wisconsin-Madison,

Madison, WI, 53705, USA

[9]Department of Computational Mathematics, Science, and Engineering, Michigan State

University, East Lansing, MI 48824, USA

‡: Joint first authors

*Current address: Bioinformatics Research Center, Aarhus University, Aarhus, Denmark

Authors for correspondence:

Shin-Han Shiu

Tel: +1-517-353-7196

Email: shius@msu.edu

Lab website: https://shiulab.github.io/

Melissa D. Lehti-Shiu

Tel: +1-517-884-4066

Email: lehtishi@msu.edu

Total word count for the main body: 6473 words

Introduction: 1235 words

Materials and Methods: 1660 words

Results: 2689 words

Discussion: 889 words

There are:

7 figures, all of them should be published in color

7 supplementary figures

10 supplementary tables

Summary

Revealing the contributions of genes to plant phenotype is frequently challenging

because the effects of loss of gene function may be subtle or be masked by

genetic redundancy. Such effects can potentially be detected by measuring plant

fitness, which reflects the cumulative effects of genetic changes over the lifetime

of a plant. However, fitness is challenging to measure accurately, particularly in

species with high fecundity and relatively small propagule sizes such as

Arabidopsis thaliana.

An image segmentation-based (ImageJ) and a Faster Region Based Convolutional

Neural Network (R-CNN) approach were used for measuring two Arabidopsis

fitness traits: seed and fruit counts.

Although straightforward to use, ImageJ was error-prone (correlation between

true and predicted seed counts, r^2=0.849) because seeds touching each other were

undercounted. In contrast, Faster R-CNN yielded near perfect seed counts

(r^2=0.9996) and highly accurate fruit counts (r^2=0.980).

By examining seed counts, we were able to reveal fitness effects for genes that

were previously reported to have no or condition-specific loss-of-function

phenotypes.

Our study provides models to facilitate the investigation of Arabidopsis fitness

traits and demonstrates the importance of examining fitness traits in the study of

gene functions.

Keywords: fitness traits; deep learning; machine vision; object detection;

Arabidopsis

Introduction

A major goal of biology is to understand the molecular basis for the development of

organisms and their adaptation to different environments (Mcdonald, 1983). One

approach is to evaluate the effects of genetic variants on phenotypes. However, it is often

challenging to investigate such effects because gene functions may be masked by genetic

redundancy (Bouché & Bouchez, 2001; Sun et al., 2012) and/or be condition specific

(Hirsch *et al.*, 1998; Meissner *et al.*, 1999). Moreover, the physiological and/or

developmental changes caused by loss of gene function may be too subtle to detect. This

challenge can be alleviated by measuring the effects of genetic variations on fitness (i.e.,

the ability of an individual to survive and reproduce) because it reflects the cumulative

effects of genetic changes over the lifetime of a plant. Accurate estimates of fitness are

therefore valuable for several fields of study, including plant genetics, evolution, and

plant breeding.

Among fitness measures, the most direct measure is the number of progeny produced

(Thomson & Hadfield, 2017). In *Arabidopsis thaliana*, a predominantly selfing plant, the

total number of seeds produced per plant is a particularly good estimate of fitness because

it incorporates both male and female contributions. However, because Arabidopsis seeds

are small (areas ranging from ~0.1–0.2 mm^2; Jahnke *et al.*, 2016) and produced in large

numbers (up to thousands of seeds per plant; Boyes *et al.*, 2001; Morales *et al.*, 2020), it

is difficult to obtain accurate seed counts. As a consequence, fruit (silique) number

(Busoms *et al.*, 2015) and total fruit length (Roux *et al.*, 2004; Busoms *et al.*, 2015;

Kerwin *et al.*, 2015) are often used to measure fitness. Both measures are correlated with

seed production, but fruit number is not perfectly correlated with seed number (e.g.,

r^2=0.960, Mauricio & Rausher, 1997) and correlations in fruit length are highly variable

across studies, ranging from and r^2=0.988 (Roux *et al.*, 2004) to r^2=0.256 (Gnan *et al.*,

2014). In addition, fruit numbers (up to 450 per plant; Hamidinekoo *et al.*, 2020) are

typically counted manually, and these counts can be error prone. Thus, to better measure

fitness, both fruit and seed numbers should be evaluated using methods that are not

hindered by propagule size or number.

Several programs have been designed to increase the efficiency and accuracy of seed

analyses. Some are aimed at measuring the properties of individual seeds (e.g., size and

shape) rather than obtaining high throughput seed counts (Herridge *et al.*, 2011; Tanabata

et al., 2012; Moore *et al.*, 2013). These approaches typically require that seeds be

separated before imaging, which increases the time needed for processing. Other systems

have been designed to separate seeds mechanically. For example, the *pheno*Seeder device

designed by Jahnke *et al.* (2016) separates seed using a "pick-and-place" robot and using

a large-particle flow cytometer to separate seeds Morales *et al.* (2020) were able to count

an average of 12,000 seeds per hour with high accuracy (relative error < 2%). A similar

number of seeds, approximately 10,000, can be processed per hour using the BELT

imaging system combined with the phenoSEED algorithm, which acquires images of

individual seeds as they pass through an imaging chamber (Halcro *et al.*, 2020).

Nonetheless, a drawback of these methods is that they require specialized equipment,

hindering their widespread adoption.

Another approach that has been increasingly used in plant biology for applications

such as measurement of fitness traits is machine vision, the application of machine

learning algorithms to image analysis (Mochida *et al.*, 2019). Deep learning approaches,

in particular Convolutional Neural Network (CNN)-based frameworks, have been

developed to detect vastly different objects (from cars to plant seeds) in images. For

example, the seeds of rice, lettuce, oat, and wheat, were detected with 96% recall and

95% precision using Mask R-CNN (Toda *et al.*, 2020). However, the detection of much

smaller objects using CNN-based approaches remains challenging (Cao *et al.*, 2019).

This is likely because CNNs create low-level abstractions of the images, and if the

objects are too small, the resulting abstractions are too simple to be used to distinguish

whether the object is present or not. Although the CNN-based models developed by Toda

et al. (2020) detected seeds with high accuracy, the smallest seeds tested were lettuce

seeds, which have areas ranging from 1.5–3.6 mm^2 (Penaloza *et al.*, 2005) and are ~10

times larger than Arabidopsis seeds. Another consideration is that the most convenient

way to count all the seeds from an Arabidopsis plant, which can produce thousands of

seeds (Boyes *et al.*, 2001; Morales *et al.*, 2020), would be to put all the seeds in a single

image, thus resulting in a relatively small ratio of seed size to image size. However, due

to the small image size (1024×1024 px^2 or 2000×2000 px^2) used in Toda et al. (2020),

the ratio of seed size to image size was relatively large (>5000 px^2 per barley seed), and

the number of seeds that could be included in an image was also limited. Therefore, it is

important to assess how well the CNN-based approaches perform in detecting objects as

small as Arabidopsis seeds in an image containing thousands of them.

CNN-based approaches have also been used in fruit counting. For example, using R-

CNN, wheat spikes can be detected, counted, and analyzed to estimate yield based on

images captured in the field (correlation between true and predicted counts: r^2=0.93 with

slope of 1.01; Hasan *et al.*, 2018). Starting from two pre-trained models (ResNet and

ResNext), Afonso *et al.* (2020) applied the Mask R-CNN approach to detect and count

tomato fruits from images captured in the greenhouse, obtaining an F1 of 0.94 when

fruits were only partially overlapping with each other. DeepPod, developed using the

LeNet and DenseNet-Basic models as a starting point, effectively counts Arabidopsis

fruits but results in a high number of false negatives when there are many fruits (r^2=0.90

with a slope of ~0.70; Hamidinekoo *et al.*, 2020). In addition, the inflorescences need to

be harvested when the fruits are still green, preventing the harvesting of seeds for future

propagation or analysis. Thus, it is important to develop tools or models to detect and

count mature fruits when seeds need to be saved for future experiments. Because

Arabidopsis fruits shatter easily when dry, such tools should ideally be able to count

fruits at different stages, including intact fruits and those that have already dehisced and

released seed, when it is necessary to score plants grown to maturity (Conner & Rush,

1997).

In this study, we evaluated two existing approaches—segmentation with ImageJ

(Schneider *et al.*, 2012) and a deep learning approach, Faster R-CNN (Ren *et al.*, 2017)—

for counting all the seeds an Arabidopsis plant produces in a single image. We also

applied Faster R-CNN to count fruits in whole plant images captured after seeds were

mature. To facilitate seed and fruit counting in diverse images, we established models

using input images with varying resolution, contrast, brightness, and blurriness. The final

seed and fruit models are provided and can be readily used by the research community.

Finally, we used our pipeline to count seeds for loss-of-function mutants of three genes

that were previously reported to have no obvious phenotype, a condition-specific

phenotype, or no reported phenotype. We showed that mutation of these genes does

indeed affect fitness, illustrating the importance of measuring fitness traits and the utility

of our pipeline in the investigation of gene functions.

Materials and Methods

Plant materials

T-DNA insertion mutants in the *Arabidopsis* Col-0 background and wild-type (WT)

Col-0 controls were used for training seed and fruit counting models. Information about

these lines is provided in **Tables S1 and S2**. Fitness data are reported for T-DNA

insertion mutants of *PURPLE ACID PHOSPHATASE 2* (*AtPAP2*, *At1g13900*,

SALK_013567C), *KINESIN 7.4* (*AtKIN7.4*, *At4g39050*, SALK130788C), and

RECEPTOR DEAD KINASE 1 (*AtRDK1*, *At4g34220*, SALK_112336). For these mutants,

multiple homozygous mutant and WT sibling plants were identified by PCR with gene-

specific primers (two to seven plants per genotype; **Table S3**). Seeds harvested from

these independent lines (referred to as sublines) were planted ($n = 5$–20 per subline, total

$n \geq 40$ per genotype) for comparison of fitness between mutants and WT, and each

mutant was compared with its WT sibling. This was done to reduce the chance that

observed fitness effects were due to other undetected T-DNA insertions.

For fitness analysis and seed counting, seeds were sown in 200-cell flats filled with

Arabidopsis mix (1:1:1 SureMix, vermiculite, and perlite), stratified for 5–7 days in the

dark at 4°C, then transferred to a growth chamber and grown under a 16-h light/8-h dark

cycle with a light intensity of 110–130 µmoles/m^2/s at 21°C. Genotypes were randomly

assigned to cells within a flat. Seedlings were thinned to one per cell after 1 week. Plants

were watered two to three times per week and grown to maturity. Intact fruits were

transferred to glassine envelopes and allowed to dry for at least one month before

counting seeds.

For fruit counts, seeds were sown in 200-cell flats filled with MetroMix 360,

stratified for 7 days in the dark at 4°C, then grown under a light intensity of ~150

μmoles/m^2/s at 21°C. Genotypes were randomly assigned to cells within a flat. Seedlings

were thinned to one per cell after 1 week. After five weeks (23 November 2018) flats

were transferred to a plot at Kellogg Biological Station. Plants were removed from the

field on 23 May 2019. Plants were cut at the base and imaged as described below.

Seed image scanning

Seeds were scattered on the lid of a 60-mm petri plate, which was then tapped with

fingers to ensure that seeds did not cover each other. For some plate lids counted with

ImageJ, seeds were separated from each other and moved away from the edges of the lid

using forceps. The lids were placed in a template made from white acrylic (295 mm ×

210 mm × 10 mm, **Fig. 1a**) on a standard desktop scanner. This template was designed to

be the same height as the plate lid to minimize artifacts resulting from light loss. Twelve

60-mm diameter holes (four rows × three columns) were cut into the template using a

laser cutter. There was 6 mm between holes in each row and 10 mm in each column. The

template was aligned to the top right corner of the scanner before every scan because

even small changes (<1 cm) in the location of the template required changing the

parameters for the circular search regions in the ImageJ algorithm (described in the

following section). Seeds were scanned at 1200 dots per inch and in 24-bit color, and

scans were saved as jpeg files.

Seed image processing and counting with ImageJ

The ImageJ (version 1.52a, https://imagej.nih.gov) workflow is shown in **Fig. 1**.

Scanned images were first converted into 8-bit grayscale bitmap format with the

im.convert('L') method in the Python Imaging Library

(https://pythonware.com/products/pil). An ImageJ macro was written to automate seed

counting. First, 12 circular search regions per scanned image were defined to confine the

search to the 12 plate lids containing the seeds. Second, a threshold was applied by

selecting pixels with intensities between 50 and 140, and pixels were converted to real

world units using a predefined line covering a known distance (the distance across the

plate lid, 60 mm). Third, seeds within the circular search regions were counted using the

"Analyze Particles" tool. Only above-threshold regions larger than 0.06 mm^2 and with a

circularity value (calculated as $C=4\pi \times [\text{area/perimeter}^2]$) of 0.25 to 1 were counted. The

image conversion program and the ImageJ macro were combined into a Windows batch

script (available in our Github repository, see **Data availability**), in which a for-loop was

used to quickly count seeds for images in sequence. It took approximately 5 min to fully

process 10 images.

Seed image processing and counting with Faster R-CNN

Each scanned image was first split into 12 sub images; each sub image contains a

single plate lid and is referred to as a "whole-plate image". In the initial Faster R-CNN

modeling trial, each whole-plate image was split into four quarter-plate images. Seeds on

the quarter-plate images were manually annotated using LabelImg v1.8.1 (Tzutalin,

2015). The ground truth annotations, i.e., the coordinates of the bottom-left (x_{min}, y_{min})

and upper-right (x_{max}, y_{max}) corners of each annotated seed area, were saved in extensible

markup language (xml) format, and then converted to comma-separated values (csv)

format. For images used for model training, the csv files were further converted to the

TFrecord format.

Faster R-CNN, performed using Tensorflow object detection API (Huang *et al.*, 2017)

and implemented in Tensorflow v1.13.2 (Abadi *et al.*, 2016) in python v3.6.4, was used

for seed detection. Faster R-CNN combines the generation of region proposals (i.e.,

circumscribing the areas of interest, a regression problem) and their classification (i.e., in

our case, the object is a seed or not) into a single pipeline (Ren *et al.*, 2017). In Faster R-

CNN, images were first processed by a feature extractor (Inception V2; Szegedy *et al.*,

2016), and the resulting feature maps were used to predict bounding boxes (referred to as

proposals) containing images of individual seeds (left panel in **Fig. S1**); then these

proposals were used to crop features from the feature maps (right panel in **Fig. S1**). These

cropped features were subsequently used for classification and bounding box regression.

To speed up the training process, a pre-trained model

(faster_rcnn_inception_v2_coco) was used as a starting point. To optimize Arabidopsis

seed detection, three hyperparameters were tested: proposals—the number of detected

regions (i.e., seeds) in an image; scales—relative sizes of detected regions; and aspect

ratios—shapes of the detected regions (**Fig. 2a** and **Fig. S1**). For the hyperparameter

space tested see **Table S4.** Each model was run on three graphics processing units

(GPUs) for 40,000 steps using the Adam optimizer, with a batch size of five (five random

images were used to train the model for each step) and a learning rate of 0.0002. A model

was saved every 10 minutes during the run as a model checkpoint.

To evaluate the model performance for hyperparameter tuning, validation set

images—seeds in these images were manually annotated but not used in the model

training—were fed into the frozen models in jpeg format, and model predictions were

output in csv files containing the coordinates of the bottom-left and upper-right corners of

each predicted seed area. Coordinates of ground truth annotations in validation set images

were compared with those of predicted seed areas using the measure IoU, which is

defined as the intersection (I) over (o) the union (U) of a ground truth area and a

prediction area. A seed was regarded as correctly detected if its IoU was ≥ 0.5. An IoU $<$

0.5 was considered to be a misprediction. The F-measure (F1) score was calculated as a

measure of performance for a model as follows: F1 $= \frac{2*precision*recall}{precision+recall}$, where precision $=$

$\frac{TP}{TP+FP}$ and recall $= \frac{TP}{TP+FN}$. TP (true positive) is the number of correctly detected seeds,

and FP (false positive) is the sum of the number of predicted seed areas that contain no

seeds and the number of predicted seed areas minus 1 (if the ground truth area was

detected more than once). FN (false negative) is the number of seeds with a maximum

IoU < 0.5 for any predicted area (i.e., the ground truth seed area was not detected).

For the hyperparameter tuning, we found that models with 100 proposals (Model$_{seed}$

1–21) had the least accuracy, with F1 < 0.750 (**Fig. S2a**), because there were more than

100 seeds in most of the validation images (**Table S5**). In contrast, models with 500

(Model$_{seed}$ 22–42) and 1000 proposals (Model$_{seed}$ 43–63) had F1 values around 0.970

(**Fig. S2b,c**). For models with 500 or 1000 proposals, scale-B and scale-C had higher F1

values than scale-A, but there were no differences between the F1 values of the seven

different aspect ratios (**Fig. S2b,c**). The combination of scale-B and aspect ratio-A was

used for downstream model building because the computational efficiency of this

combination was the highest among all combinations (**Fig. S3**). Three additional models

were established based on scale-B and aspect ratio-A with 3000, 5000, and 10,000

proposals (Model$_{seed}$ 64–66), but F1 values did not improve over those of Model$_{seed}$ 22–

63 (**Fig. S2d**). Even though building Faster R-CNN models with a higher number of

proposals requires more computational resources, we opted to use 10,000 proposals

(Model$_{seed}$ 66) for further model building to allow detection of a large number of seeds in

an image.

Fruit image capturing and counting with Faster R-CNN

Each dry Arabidopsis plant was placed on a pink paper background and photographed

with an iPhone 8 smartphone. The images were saved in jpeg format with dimensions of

3024×4032 pixels. Fruits in the images were manually annotated, and the annotated

coordinates were then converted to the csv and TFrecord formats, as conducted for the

seed images. The same pre-trained Faster R-CNN model used for seed counting was used

to build the fruit counting models, and the same three hyperparameters were tuned to

optimize the model performance but with a different hyperparameter space (**Table S6**).

For each hyperparameter combination, a model was saved after 6000 steps, when the

performance had converged. A final model was established using hyperparameters

selected based on performance on the validation set images.

Results

Seed counting using ImageJ

Because the "Analyze Particles" function of ImageJ is widely used for analysis of

seed morphology (Cervantes et al., 2016), we first attempted to develop a pipeline for

seed counting that incorporated ImageJ analysis based on segmentation of seed areas.

Using our seed scanning setup (see **Methods**), when fewer than 200 seeds were placed on

the plate lid and separated using forceps, seeds were detected and counted with high

accuracy (correlation between true and predicted seed counts, r^2, was 0.996,

slope=0.9998, 60 images, **Fig. 1b,c, Table S7**). Our ImageJ pipeline allowed the

detection of about 52 template images (total of 624 plate lids) per hour with a typical

laptop (Intel(R) Core i7-7500U CPU, 16GB RAM).

However, when seeds were placed on plate lids without separation, big clumps of

seeds were not counted by ImageJ, and small clumps where a small number of seeds were

touching each other were recognized as single seeds (**Fig. 3a**). The prediction accuracy of

ImageJ drops off as the number of seeds increases (**Fig. 3c, Table S8**); this is because the

more seeds there are on the plate lid, the more likely it is that seeds touch each other,

leading to an increase in the false negative rate of prediction. Moreover, the detection of

seeds could be disrupted by scratches or letters on the plate lids, and seeds outside the

predefined circular search regions were not detected (purple arrowheads in **Fig. S4**).

Thus, to obtain accurate counts based on segmentation, it is necessary to separate seeds

and confine them to the center of the plate lid, which is time consuming and not

amenable to high-throughput analysis.

Improved seed counting by Faster R-CNN

Next, we evaluated the performance of the deep learning approach Faster R-CNN in

seed counting. Since it is very time-consuming to annotate a large number of small

objects for model training, we adopted a two-step strategy to reduce the manual labor

needed for seed labeling. First, we split the 256 whole-plate images into 1024 quarter-

plate images, and manually labeled a subset (180) of these quarter-plate images to speed

up the training process. A total of 160 labeled quarter-plate images (*Training image set 1*

in **Fig. 2a**) were used to build the models, and the remaining 20 images were set aside as

the validation set (*validation image set* in **Fig. 2a**) to evaluate the performance of the

models. A model (Model$_{seed}$ 66) built with the optimal hyperparameter combination

(scale-B, aspect ratio-A and 10,000 proposals, for details about hyperparameter tuning,

see **Methods**) was used to detect seeds in the remaining 844 quarter-plate images to

produce "*in silico*" seed annotations for the second-round modeling (**Fig. 2a**). The

predicted coordinates of seeds for a set of four quarter-plate images were combined and

converted to the corresponding coordinates in the original whole-plate image. These

whole-plate seed coordinates were manually corrected (i.e., false negatives were

manually labeled, and false positives were removed) to produce a new set of seed

annotations, resulting in 211 labeled whole-plate images.

A new model, Model$_{seed}$ 67, with the same parameters as Model$_{seed}$ 66, was built

using 161 (*Training image set 2* in **Fig. 2b**) out of these 211 images (**Fig. 2**). The

remaining 50 labeled whole-plate images (*Test image set* in **Fig. 2b**) were used to

evaluate the performance of Model$_{seed}$ 67, which had an improved average F1 of 0.992

(**Table S8**) compared with the F1 (~0.970) of Model$_{seed}$ 66 (**Fig. S2**). Note that the test

set images were not used for training or validating Model$_{seed}$ 67; they were thus ideal for

independently testing the model. In contrast to the ImageJ approach, $Model_{seed}$ 67

correctly predicted seeds regardless of whether they were in contact with each other or

not (**Fig. 3b**), and the prediction accuracy was not influenced by the total number of

seeds in an image (r^2=0.9996, *p*=1.7e-83, **Fig. 3d**). The differences between true and

predicted seed counts were close to zero, much smaller than those in ImageJ analysis

(**Fig. 3e**). Furthermore, $Model_{seed}$ 67 allowed the detection and counting of seeds in about

240 whole-plate images per hour using 1 GPU (Nvidia Tesla K80) with 4 GB of GPU

memory in a UNIX cluster, or about 33 images per hour using a laptop with 16 GB of

memory. These results suggest that our Faster R-CNN-based models provide highly

accurate Arabidopsis seed counts and can be used for large-scale fitness studies.

Impact of seed density on the Faster R-CNN model

The number of seeds in an image has a detrimental effect on the performance of

ImageJ, but not on that of Faster R-CNN, as the correlation between the true and

predicted numbers of seeds is nearly perfect (**Fig. 3d**). This suggests that the Faster R-

CNN model performance was not affected by the seed density. To verify this, a measure

of seed density was needed because the same number of seeds could be evenly distributed

on a plate lid, or crowded in a specific area so that seed density was very high in some

parts of the lid but low in others. Thus, we generated the seed density index (SDI) as a

measure of seed density. First, a circle with a radius of 30 pixels (corresponding to 0.62

mm, approximate length of two seeds) was drawn from the center of a seed, then the

number of seeds with central points located within the circle were calculated. Finally, the

average number of seeds per circle in a whole-plate image was defined as the SDI (**Fig.**

4a).

Using this strategy, we calculated the SDIs of the test set images (for examples see

Fig. S5) and determined the Pearson's Correlation Coefficient (PCC) between SDI and

the performance of Model$_{seed}$ 67 on the test set images (**Fig. 4b**). The higher the seed

density, the lower the model performance (PCC between SDI and F1 was -0.581, p=9.8e-

06, **Fig. 4b**; for the correlation between SDI and other performance measures see **Fig. S6**).

Nevertheless, the effect of seed density on the performance of Model$_{seed}$ 67 was small, as

the F1 only dropped from 1.000 for an SDI of 1.157 to 0.971 for an SDI of 3.100 (**Fig. 4b,**

Table S8). An F1 of 0.971 with a recall of 0.968 indicates that for an image with 1000

seeds, there would only be 32 false negatives (seeds not detected) and 25 false positives

(seeds detected in an area with no seeds or a seed area counted more than once).

Consistent with this, there was no significant correlation between the SDI and the

difference between true and predicted seed counts (PCC=-0.206, p=0.15), in contrast to

the significant negative correlation observed for ImageJ (PCC=-0.886, p=1.2e-17, **Fig.**

3f). We also calculated SDIs for the predicted seed coordinates and found that the PCC

value between true and prediction-based SDIs was 0.997 (p=1.5e-54; **Fig. 4c**),

demonstrating that our Faster R-CNN model also predicts the locations of seeds very well.

Model improvement through data augmentation

Our goal is to provide a seed counting model that can be widely used by different

researchers, who may have seed images with different properties. Thus, we investigated

the utility of Model$_{seed}$ 67 for seed counting using images with four varying attributes:

resolution, contrast, brightness, and blurriness (**Fig. 5a**). These modified seed images

were created by modifying the properties of the test set images (**Fig. 2b,** for the image

property settings see **Table S9**). In the modified test set, there were 1750 images: the

original test set images (50) and modified images with 34 different attributes (34×50,

light green box, **Fig. 2b**). A slight but significant decrease in F1 was observed when the

brightness of the images was ≤ 0.60 (p=0.01, one-sided Wilcoxon signed-rank test)

relative to the original images, while the F1 dropped dramatically when the relative

brightness was ≥ 1.20 (p=6.4e-08, **Fig. 5b**). A significant decrease in F1 was also

observed when the relative contrast of images (relative to the original image) was ≤ 0.50

(p=1.0e-07) or ≥ 1.75 (p=5.0e-4), the relative blurriness was ≥ 1.50 (p=6.7e-10), or the

relative resolution was ≤ 0.50 (p=9.1e-10, **Fig. 5b**). These results suggest that although

Model$_{seed}$ 67 is suitable for a range of image qualities, the seed detection accuracy will

decrease dramatically when the image properties deviate from the training images beyond

a certain point.

To improve the robustness of Model$_{seed}$ 67, we applied data augmentation, in which

the size and properties of training datasets are increased so better prediction models can

be built (Shorten & Khoshgoftaar, 2019). To accomplish this, we used 20 of the 161

training set 2 images to produce additional images with 21 different property settings (21

$\times$ 20, darker green box, **Fig. 3b,** for the image property settings see **Table S9**). These 420

additional images, together with the original 161 images, were used to build a new model,

Model$_{seed}$ 68 (**Fig. 2b**), with the same hyperparameter settings as Model$_{seed}$ 67. Model$_{seed}$

68 was then used to detect seeds in the modified test set images. Although there was a

slight decrease in F1 when the relative blurriness was ≥ 3.00 (p=0.04, median F1

decrease=0.002) or when the relative resolution was ≤ 0.30 (p=0.02, median F1

decrease=0.003, **Fig. 5b**), Model$_{seed}$ 68 (blue, **Fig. 5b**) performed better than the non-

augmented Model$_{seed}$ 67 (red, **Fig. 5b**) in all situations and thus, the augmented model is

robust to different image properties.

Fruit counting using Faster R-CNN models

Compared with seed number, total fruit count is an even more frequently used proxy

for fitness. Because dry Arabidopsis fruits shatter easily, it is not always possible to

harvest all fruits produced by a single plant after seeds have matured, especially for

plants growing in the field. In this case, the best method would be to count all fruits

(including dehisced ones) and count seeds per fruit for a subset that haven't dehisced, and

then calculate total seed number by multiplying the number of seeds per fruit by the total

fruit number. Thus, to obtain more accurate estimates of seed production per plant, it is

necessary to record the numbers of both intact and shattered fruits. With these

considerations in mind, we developed Faster R-CNN models to count all fruits without

harvesting the fruits first. When capturing the images for fruit counting, a pink

background was used to maximize the contrast between the background and the dark, dry

fruits and the pale replum of shattered fruits that remained after the valves fell from the

fruit (**Fig. 6a,d**). Because there were much fewer fruits in each image than there were

seeds when performing seed counting, and the fruits were much larger, we manually

labeled the fruits in 120 images without using the two-step strategy used for seed

counting.

Eighty, 20, and 20 images were randomly selected and used as training, validation,

and test sets, respectively (**Fig. 6a**). Different combinations of hyperparameter values

(**Table S6**) were evaluated (Model$_{fruit}$ 1-75, **Fig. 6a**). Surprisingly, all models built with

different hyperparameter combinations performed similarly on images in the validation

set, with an average F1 of 0.925 (**Fig. S7**). Thus, to minimize the computational cost

(lower scales or aspect ratios) while maximizing the number of fruits detected per plant

(more proposals), the model built with scale$_{fruit}$-A, aspect ratio$_{fruit}$-A, and 500 proposals

(Model$_{fruit}$ 21) was used. Model$_{fruit}$ 21 was applied to the test set images, resulting in an

average F1 of 0.914 (**Table S10**). This F1 value translates into 1 false positive and 15

false negatives for an image with 100 fruits. Although the r^2 between true and predicted

fruit counts was 0.980 (p=6.7e-17), the detection error increased with an increasing

number of fruits in an image and, because the fitted line had a slope of 0.785, the error

was mostly due to undercounting or false negatives (**Fig. 6b,c**). Upon further

examination, we found that the majority of the false negatives were unopened fruits,

especially those that overlapped with the stem or with each other. One potential reason

for the failure to detect these fruits is that they are similar to the stem in color and shape.

Another reason may be the smaller number of labeled intact fruits (543) compared with

the number of pale replums (2082) in our training images. Thus, our model can

potentially be improved by increasing the number of intact fruits in the training set.

To assess the robustness of our model on images with different qualities, we applied

Model$_{fruit}$ 21 on test set images with different image properties (**Fig. 6d,** modified test set,

700 images, for the image property settings see **Table S9**). Significant decreases in F1

were observed when the relative image brightness was ≤ 0.70 (p=0.04) or ≥ 1.40

(p=0.02), the relative contrast was ≤ 0.50 (p=0.02) or ≥ 1.50 (p=0.03), the relative

blurriness was ≥ 2.0 (p=0.002), or the relative resolution was ≤ 0.6 (p=0.05) (**Fig. 6e**). By

including images with different properties (**Table S9**) in the training set (1840 images in

total), a new model, Model$_{fruit}$ 76, was established and applied to the modified test set. A

significant but slight decrease in the resulting F1 values was only observed when the

relative resolution was ≤ 0.3 (p=0.02, median F1 decrease=0.01) (**Fig. 6e**), indicating the

robustness of Model$_{fruit}$ 76. Using this model 180 images could be processed per hour

using a UNIX node with 1 GPU and 4 GB graphics memory, and 90 images per hour

could be processed using a laptop (1 CPU, 16 GB memory).

Effects of loss of gene function revealed by measuring fitness traits

To evaluate the importance of fitness traits in investigating gene functions and the

utility of our pipeline, the fruits and seeds produced by loss-of-function mutants of three

genes, *AtPAP2*, *AtKIN7.4*, and *AtRDK1*, were counted and compared with those of WT.

AtPAP2 was previously reported to modulate carbon metabolism, and overexpression of

AtPAP2 resulted in earlier bolting and a higher seed yield than WT, whereas a loss-of-

function mutant of *AtPAP2* (*pap2*) showed no significant differences in plant growth or

seed yield relative to WT (Sun et al., 2012). One possible explanation for the failure to

detect a difference between *pap2* and WT is genetic redundancy (Sun et al., 2012), but an

alternative reason could be that the difference is subtle and not easily detected. To

estimate yield, the authors measured seed weight per plant, seed weight per 100 mg of

seed, and the number of fruits per plant, and all three of these traits were not significantly

different between *pap2* and WT. It is possible that these measurements may not have

captured the differences in fitness between *pap2* and WT. To test this, we counted the

seeds of *pap2* plants (the same mutant line used by Sun *et al.*) using our seed counting

pipeline and observed a significant decrease in seed count compared with WT (p=5.1e-4,

Fig. 7a), consistent with the increased yield phenotype of the overexpression lines

described in Sun et al. (2012). This result indicates that the previous failure to detect a

decrease in seed yield may have been due to the fitness measure used (i.e., seed weight).

In contrast, there was no significant difference in fruit counts between the *pap2* and WT

plants (p=0.26, **Fig. 7b**).

AtRDK1 is involved in abiotic stress responses and functions in an ABA-dependent

manner (Kumar et al., 2017). Phenotypic differences between *rdk1* and WT were

previously observed to be condition specific, e.g., differences in cotyledon greening were

only observed in the presence of ABA (Kumar et al., 2017). In our study, without

imposing any specific treatment, *rdk1* produced significantly fewer seeds than WT

(p=4.9e-2, **Fig. 7c**), although there was no significant difference in fruit number (p=0.11,

Fig. 7d). This result suggests that fitness may reveal loss-of-function effects that are too

subtle to detect or are only detectable under specific conditions.

The third gene we evaluated, *AtKIN7.4*, belongs to the kinesin motor family,

members of which are involved in microtubule-based movement (Moschou et al., 2016).

No functions have been reported for *AtKIN7.4*. We found that the *kin7.4* mutant produced

significantly fewer seeds (p=2.9e-4, **Fig. 7e**) and fruits (p=1.3e-3, **Fig. 7f**) than WT,

indicating that loss of *AtKIN7.4* affects fitness, and in this case, the decrease in fitness

can be captured by measuring both fruit number and seed number.

Discussion

Fitness is one of the best measures of gene functionality because it reflects the ability of a

plant to survive and reproduce given all the phenotypic effects of the mutation over the

lifetime of the individual. For self-pollinating species such as Arabidopsis, fitness is

better assessed by counting the numbers of seeds than fruits, as they more directly reflect

the number of offspring and reproductive success. Due to the lack of an effective tool

enabling high throughput counting of small seeds en masse, seed counts are often

estimated indirectly, for example by dividing the total seed weight per plant by the

estimated individual seed weight in the same batch (Cvetkovic *et al.*, 2017), or by

multiplying the fruit count by the average fruit length (Kerwin *et al.*, 2015; Taylor *et al.*,

2019). However, these approaches may not yield accurate estimates of seed production

due to potential measurement errors and the imperfect correlation between seed number

and fruit length (Roux *et al.*, 2004). Here, we established a model employing a deep

learning approach, Faster R-CNN, to count Arabidopsis seeds—one of the smallest

objects analyzed using machine vision to date—with a near perfect accuracy (F1=0.992)

using images with multiple different properties or qualities. Our model outperforms

another CNN-based approach developed by Toda *et al.* (2020) (F1 of about 0.95), where

the detected objects were much larger than Arabidopsis seeds. In particular, the Faster R-

CNN-based predictions outperform those of ImageJ, a well-known platform with

macros/modules for segmentation and morphology extraction (Schneider *et al.*, 2012;

Cervantes *et al.*, 2016; Vasseur *et al.*, 2018). In addition, Faster R-CNN is less time

consuming because seeds can be accurately detected without first being separated or

confined to predefined regions.

One of the challenges when using deep learning approaches is the requirement for a

large number of labeled data (in our case, labeled seeds). To overcome this, we adopted a

two-step modeling strategy to reduce the labor needed for seed annotations. In step 1, we

split the images and used a subset of the split images to build a preliminary model

(F1<0.975) and applied it to the remaining images. While the predictions were not perfect,

this step drastically reduced the manual annotations needed because we only needed to

correct mis-predictions to boost our seed labels by ~5 fold (29,360 labels in the first-

round, 138,929 labels in the second-round). Using this much larger set of seed labels,

new models were built (step 2) that had improved model performance (F1=0.992),

indicating the effectiveness of our strategy.

The Faster R-CNN approach also shows promise in fruit detection and counting

(r^2=0.98, slope=0.79). The performance of our fruit counting model was better than that

of another recently published CNN-based approach, DeepPod (r^2=0.90, slope ~0.70,

Hamidinekoo *et al.*, 2020). In that paper, the task (i.e., fruit detection) was first divided

into four classification tasks: the detection of the tip, body, and base of the fruits and the

detection of the stem. The separately detected parts were then joined together as a whole

fruit. As the authors noted, this post-processing step affected the final fruit detection

performance. In our study, the fruits were labeled and detected as whole objects, thus

avoiding the need for post-processing. In addition, different from Hamidinekoo *et al.*

(2020), where most fruits and the stems in the images were fresh and green, fruits in our

study were dry and light brown to gray, or were shattered with only the pale replum

remaining. Thus, our fruit counting approach is expected to be applicable to a wider

range of Arabidopsis fruit developmental stages. This is especially important when plants

must be grown to maturity, and seed counts are estimated by multiplying the average

number of seeds per intact fruit by the total number of fruits (intact and dehisced).

Nevertheless, our fruit counting models did not perform as well as our seed counting

models and a published ImageJ-based segmentation and skeletonization approach

(r^2=0.91, slope= ~1; Vasseur *et al.*, 2018), which may be due to the much fewer labeled

fruits than labeled seeds (about 52 times more). Thus, the performance of the fruit

counting model is expected to be improved when more fruit labels are included to train

the model. In addition, one notable drawback of our approach is the undercounting at

higher fruit numbers; this was mainly due to overlap between intact fruits and between

intact fruits and stems. To remedy this, one approach is to rearrange the inflorescences

before capturing the images to keep fruits from overlapping with each other and with

stems. Another potential approach is to analyze multiple images (or frames of a movie)

taken at different angles or to examine the 3D reconstruction of the inflorescence.

By examining the fitness traits, especially seed counts, we were able to observe

phenotypic changes in loss-of-function mutants that were previously not detectable (*pap2*,

Sun et al., 2012) or condition specific (*rdk1*, Kumar et al., 2017). In addition, we

demonstrated the importance of *AtKin7.4*—the function of which has not been reported

previously— for fitness, in terms of both seed and fruit counts. Taken together, our

results illustrate the importance of fitness traits in the study of gene functions, and show

that Faster R-CNN-based models, which can almost perfectly detect and count

Arabidopsis seeds and also detect fruits with high accuracy, are valuable tools in large-

scale studies of plant fitness.

Figure legends

Fig. 1. Workflow and performance for seed counting using ImageJ when seeds were

deliberately separated. (**a**) Workflow. Seeds from 12 different plants were scattered and

manually separated from each other on the lids of 12 petri plate lids, which were placed

in a template and scanned. Twelve search areas, each with a diameter of 60 mm (yellow

circles), were predefined. A threshold was applied by selecting pixels with intensities

between 50 and 140 to separate the seed areas (red) from the background. Then pixels

were converted to real-world distance units in mm. The "Analyze Particles" tool was

used to detect and count the seeds. (**b**) An example of an image with detected seeds (left)

and an enlarged image showing the seeds (right). Red region with number: individual

detected seed area. (**c**) Correlation between true and predicted seed counts using ImageJ

when seeds were deliberately separated.

Fig. 2. Workflow for building Faster R-CNN-based seed counting models. (**a**) First-round

modeling for enriching annotated seed labels. Each of the 256 whole-plate images was

split into four quarter-plate images. Among the 1024 quarter-plate images, 180 were used

in first-round modeling, and the remainder (844) were used in second-round modeling

described in (**b**). Seeds in the 180 quarter-plate images were manually annotated, and

then these annotated images were further split into training set 1 (160) and a validation

set (20) to train and evaluate models, respectively. Sixty-three combinations of three

hyperparameters (i.e., 3 proposal numbers $\times$ 3 scales [A, B, and C] $\times$ 7 aspect ratios [AR-

A through G]; for scale and aspect ratio values see **Table S4**) were used to build 63

models. The optimal scale (B) and aspect ratio (AR-A) were selected based on the model

performance on validation set images (**Fig. S2**). An additional three models (Model$_{seed}$

64–66) were built using scale B, AR-A, and three larger proposal values, and the final

best model, Model$_{seed}$ 66, with 10,000 proposals, was applied to the 844 quarter-plate

images reserved for second-round modeling to generate *in silico* seed annotations. (**b**)

Second-round modeling. The 844 quarter-plate images with seed predictions from

Model$_{seed}$ 66 were rejoined together to reconstruct 211 whole-plate images with *in silico*

seed annotations, which were then manually curated and used as ground truth seed

annotations. Model$_{seed}$ 67 was built using 161 (training set 2) out of the 211 annotated

images with the same hyperparameters used in Model$_{seed}$ 66, and was evaluated using the

test set (50 independent images not used for modeling) and the modified test set (i.e., the

50 independent test set images plus 1,700 images modified from the test set images that

had different image properties [blurriness, brightness, contrast, and resolution values]).

For data augmentation, the image properties of 20 images from training set 2 were

modified, and the resulting 420 images were combined with training set 2 (161 images),

resulting in 581 images (modified training set 2), which were used to build Model$_{seed}$ 68.

The modified test set was used to evaluate the performance of Model$_{seed}$ 68.

Fig. 3. Comparison between the performances of ImageJ- and Faster R-CNN-based seed

counting methods for the test set images of seeds that were not deliberately separated. (**a,**

b) The same seed scan image analyzed by ImageJ (**a**) and Faster R-CNN (**b**). Three

different regions of the plate lid with different densities are outlined. Region 1 has low

seed density, region 2 has moderate density, and region 3 has a high density. In (**a**) the

red colored regions represent the segmented areas identified by ImageJ; seeds outlined in

yellow and assigned numeric IDs were counted. In (**b**) the blue rectangles represent seeds

618 detected by Faster R-CNN. (**c,d**) Correlation between true and predicted seed numbers

619 from ImageJ (**c**) and Faster R-CNN (**d**) analysis of the test set. (**e**) Distribution of

620 differences between true and predicted seed numbers. Red lines: ImageJ; blue lines:

621 Faster R-CNN. (**f**) Correlation between seed density index (SDI) and difference between

622 true and predicted seed counts. Each dot in (**c,d,f**) corresponds to one of the 50 test set

623 images. The red line in (**c**) is the regression line obtained using the loess method. The

624 blue lines in (**d,f**) are fitted regression lines for Faster R-CNN predictions. The red line in

625 (**f**) is the fitted linear regression line for ImageJ-based predictions. PCC: Pearson

626 correlation coefficient.

628 **Fig. 4.** Effect of seed density on the performance of the Faster R-CNN models. (**a**)

629 Examples with different seed density index (SDI) values. The radius of each circle is 30

630 pixels (0.62 mm). (**b,c**) Relationship between SDI and model performance (**b**) and

631 between the true SDI and SDI based on prediction (**c**) for test images. Each dot

632 corresponds to one of 50 test set images. Blue lines are the fitted linear regression lines.

633 F1: F1 value at 0.5 IoU (Intersection over Union). PCC: Pearson correlation coefficient.

635 **Fig. 5.** Improvement of model robustness using training images with different properties.

636 (**a**) Examples of seed images with different relative brightness, contrast, blurriness, and

637 resolution values that were derived from the same original image. (**b**) Model performance

638 for $Model_{seed}$ 67 and $Model_{seed}$ 68 on the modified test set (**Fig. 2b**). Red boxplot:

639 $Model_{seed}$ 67; blue boxplot: $Model_{seed}$ 68. F1: F1 value at 0.5 IoU.

Fig. 6. Fruit counting using Faster R-CNN models. (**a**) Fruit counting workflow. (**b**)

Relationship between true and predicted fruit numbers. (**c**) Relationship between fruit

number in an image and the model performance. PCC: Pearson correlation coefficient. (**d**)

Examples of the same fruit image with different relative brightness, contrast, blurriness,

and resolution values. (**e**) Model performance for $\text{Model}_{\text{fruit}}$ 21 and $\text{Model}_{\text{fruit}}$ 76 on test

images with different properties. Red boxplot: $\text{Model}_{\text{fruit}}$ 21; blue boxplot: $\text{Model}_{\text{fruit}}$ 76.

F1: F1 at 0.5 IoU; PCC: Pearson correlation coefficient.

Fig. 7. Fitness measurements for three mutants. (**a-b**) Seed (**a**) and fruit counts (**b**) of the

T-DNA mutant of *PURPLE ACID PHOSPHATASE 2* (*pap2*; $n = 47$) and wild type (WT;

$n = 43$). (**c-d**) Seed (**c**) and fruit counts (**d**) of the T-DNA mutant of *RECEPTOR DEAD*

KINASE1 (*rdk1*; $n = 50$) and WT ($n = 50$). (**e-f**) Seed (**e**) and fruit counts (**f**) of the T-

DNA mutant of *KINESIN 7.4* (*kin7.4*; $n = 48$) and WT ($n = 46$). *p*-values are from

Wilcoxon signed-rank tests.

Supplementary Figure Legends

Fig. S1. The architecture of Faster R-CNN. The seed images are first processed using a

feature extractor (Inception V2), which extracts features from the input images by

assigning importance (weights or biases) to the objects in the images. The output of the

feature extractor is a feature map, indicating the locations and strength (indicated by color

gradient) of the detected features in an image. Then a large number of anchors (rectangles

with different aspect ratios [width/height] and scales [relative size]) are generated and

placed uniformly throughout the feature map. By applying one of the key modules of

Faster R-CNN, Regional Proposal Network, each anchor is assigned an objectness score,

which is an indication of how likely it is that the anchor contains an object. A predefined

number of anchors (object proposals) are selected based on the rank of objectness scores.

Next, to determine whether an anchor contains an object and to adjust the anchors to

better fit the location of the seed, the feature maps and the proposals are processed using

another module, the Fast R-CNN Detector. Two scores are obtained: a classification

score (the likelihood that the proposal region contains a seed) and regression score (the

location of the detected seed)**.**

Fig. S2. Hyperparameter tuning for seed counting models. (**a-c**) Performance of 63

models (Model$_{seed}$ 1–63) trained on training set 1 with 100 (**a**), 500 (**b**), and 1,000 (**c**)

proposals at three scales (columns) and with seven aspect ratios (colored lines; for scale

and aspect ratio values see **Table S4**). Performance was evaluated using the validation set.

(**d**) Model performance for different proposals based on the scale-B and aspect ratio-A

combination. x axis: the number of training steps; y axis: F1 at 0.5 IoU.

Fig. S3. Computational efficiency of seed counting models. Computational efficiency of

seed counting models trained with training set 1, with 100 (**a**), 500 (**b**), and 1,000

proposals (**c**) at different scales (A, B, and C columns) and with different aspect ratios

(colored lines). x axis: the number of training steps; y axis: global steps per second.

Fig. S4. Example false negatives from ImageJ analysis and Faster R-CNN models. (**a,b**)

One example seed scan image analyzed by ImageJ (**a**) and the Faster R-CNN Model 67

(**b**). Purple arrowheads: example false negatives from ImageJ and Faster R-CNN; green

arrowheads: seeds correctly detected by Faster R-CNN.

Fig. S5. Example images with different SDI values. Six images of seeds in petri dish lids

with SDI values ranging from low (1.157) to high (3.100).

Fig. S6. Effect of seed density on the performance of the Faster R-CNN models using

different measures of performance. (**a-c**) Relationship between SDI and precision (**a**),

recall (**b**), and accuracy (**c**). Each blue dot represents one of the 50 test set images, and

lines are the fitted linear regression lines.

Fig. S7. Hyperparameter tuning for fruit counting models. Performance of fruit counting

models trained on images in the training set with different proposal numbers (rows) at

different scales (columns) and with different aspect ratios (colored lines). Performance

was evaluated using images in the validation set. For scale and aspect ratio values see

Table S6. x axis: the number of training steps; y axis: F1 at 0.5 IoU.

Acknowledgments

705   We thank Christina B. Azodi, Bethany M. Moore, Siobhan Cusack, and Liang Xu for

706   help in manual seed annotation, and Ally Schumacher for providing the photo of the

707   template. We thank Dirk Colbry for helpful discussions. This work was supported by the

708   U.S. Department of Energy Great Lakes Bioenergy Research Center (BER DE-

Author contributions

713   PW, FM, JKC, PJK, MDL, and SHS conceived and designed the study. PW, FM, PD, SH,

714   NLP, EV, EW, JKC, PJK, and MDL performed data collection and analysis. PW, FM,

715   MDL, and SHS wrote the manuscript. All authors read and approved the final manuscript.

Data availability

718   All the scripts used in this study and the final seed and fruit counting models are available

719   on Github at:

720   https://github.com/ShiuLab/Manuscript_Code/tree/master/2021_Arabidopsis_seed_and_f

721   ruit_count

References

Abadi M, Barham P, Chen JM, Chen ZF, Davis A, Dean J, Devin M, Ghemawat S,

Irving G, Isard M *et al.* 2016. TensorFlow: A system for large-scale machine

learning. *12th USENIX Symposium on Operating Systems Design and*

Implementation. USENIX Association:265-283.

Afonso M, Fonteijn H, Fiorentin FS, Lensink D, Mooij M, Faber N, Polder G,

Wehrens R. 2020. Tomato fruit detection and counting in greenhouses using

deep learning. *fronties in Plant Science* **11**:571299.

Bouché N, Bouchez D. 2001. Arabidopsis gene knockout: phenotypes wanted. *Current*

Opinion in Plant Biology **4**:111-117.

Boyes DC, Zayed AM, Ascenzi R, McCaskill AJ, Hoffman NE, Davis KR, Gorlach J.

2001. Growth stage-based phenotypic analysis of *Arabidopsis*: A model for high

throughput functional genomics in plants. *Plant Cell* **13**:1499-1510.

Busoms S, Teres J, Huang XY, Bomblies K, Danku J, Douglas A, Weigel D,

Poschenrieder C, Salt DE. 2015. Salinity Is an agent of divergent selection

driving local adaptation of *Arabidopsis* to coastal habitats. *Plant Physiology*

168:915-929.

Cao CQ, Wang B, Zhang WR, Zeng XD, Yan X, Feng ZJ, Liu YT, Wu ZY. 2019. An

improved Faster R-CNN for small object detection. *Ieee Access*:106838-106846.

https://doi.org/10.1109/Access.2019.2932731.

Cervantes E, Martin JJ, Saadaoui E. 2016. Updated methods for seed shape analysis.

Scientifica (Cairo) **2016**:5691825.

Conner JK, Rush S. 1997. Measurements of selection on floral traits in black mustard,

Brassica nigra. *Journal of Evolutionary Biology* **10**:327-335.

Cvetkovic J, Muller K, Baier M. 2017. The effect of cold priming on the fitness of

Arabidopsis thaliana accessions under natural and controlled conditions.

Scientific Reports **7**:44055.

Gnan S, Priest A, Kover PX. 2014. The genetic basis of natural variation in seed size

and seed number and their trade-off using *Arabidopsis thaliana* MAGIC lines.

Genetics **198**:1751-1758.

Halcro K, McNabb K, Lockinger A, Socquet-Juglard D, Bett KE, Noble SD. 2020.

The BELT and phenoSEED platforms: shape and colour phenotyping of seed

samples. *Plant Methods* **16**:49.

Hamidinekoo A, Garzon-Martinez GA, Ghahremani M, Corke FMK, Zwiggelaar R,

Doonan JH, Lu C. 2020. DeepPod: a convolutional neural network based

quantification of fruit number in *Arabidopsis*. *Gigascience* **9**:giaa012.

Hasan MM, Chopin JP, Laga H, Miklavcic SJ. 2018. Detection and analysis of wheat

spikes using Convolutional Neural Networks. *Plant Methods* **14**:100.

Herridge RP, Day RC, Baldwin S, Macknight RC. 2011. Rapid analysis of seed size in

Arabidopsis for mutant and QTL discovery. *Plant Methods* **7**:3.

Hirsch RE, Lewis BD, Spalding EP, Sussman MR. 1998. A role for the AKT1

potassium channel in plant nutrition. *Science* **280**:918-921.

Huang J, Rathod V, Sun C, Zhu ML, Korattikara A, Fathi A, Fischer I, Wojna Z,

Song Y, Guadarrama S *et al.* 2017. Speed/accuracy trade-offs for modern

convolutional object detectors. *Proceedings of the IEEE Computer Society*

Conference on Computer Vision and Pattern Recognition:3296-3297.

https://doi.org/10.1109/cvpr.2017.351.

Jahnke S, Roussel J, Hombach T, Kochs J, Fischbach A, Huber G, Scharr H. 2016.

phenoSeeder - A robot system for automated handling and phenotyping of

individual seeds. *Plant Physiology* **172**:1358-1370.

Kerwin R, Feusier J, Corwin J, Rubin M, Lin C, Muok A, Larson B, Li B, Joseph B,

Francisco M *et al.* 2015. Natural genetic variation in *Arabidopsis thaliana*

defense metabolism genes modulates field fitness. *eLife* **4**:e05604.

Kumar D, Kumar R, Baek D, Hyun TK, Chung WS, Yun DJ, Kim JY. 2017.

Arabidopsis thaliana RECEPTOR DEAD KINASE1 functions as a positive

regulator in plant responses to ABA. *Molecular Plant* **10**:223-243.

Mauricio R, Rausher MD. 1997. Experimental manipulation of putative selective agents

provides evidence for the role of natural enemies in the evolution of plant defense.

Evolution **51**:1435-1444.

Mcdonald JF. 1983. The Molecular-Basis of Adaptation - a Critical-Review of Relevant

Ideas and Observations. *Annual Review of Ecology and Systematics* **14**:77-102.

Meissner RC, Jin HL, Cominelli E, Denekamp M, Fuertes A, Greco R, Kranz HD,

Penfield S, Petroni K, Urzainqui A *et al.* **1999.** Function search in a large

transcription factor gene family in Arabidopsis: Assessing the potential of reverse

genetics to identify insertional mutations in R2R3 *MYB* genes. *Plant Cell*

11:1827-1840.

Mochida K, Koda S, Inoue K, Hirayama T, Tanaka S, Nishii R, Melgani F. 2019.

Computer vision-based phenotyping for improvement of plant productivity: a

machine learning perspective. *Gigascience* **8**:giy153.

Moore CR, Johnson LS, Kwak IY, Livny M, Broman KW, Spalding EP. 2013. High-

throughput computer vision introduces the time axis to a quantitative trait map of

a plant growth response. *Genetics* **195**:1077-1086.

Morales A, Teapal J, Ammerlaan JMH, Yin X, Evers JB, Anten NPR, Sasidharan R,

van Zanten M. 2020. A high throughput method for quantifying number and size

distribution of *Arabidopsis* seeds using large particle flow cytometry. *Plant*

Methods **16**:27.

Moschou PN, Gutierrez-Beltran E, Bozhkov PV, Smertenko A. 2016. Separase

promotes microtubule polymerization by activating CENP-E-Related Kinesin

Kin7. *Developmental cell* **37**:350-361.

Penaloza P, Ramirez-Rosales G, McDonald MB, Bennett MA. 2005. Lettuce (*Lactuca*

sativa L.) seed quality evaluation using seed physical attributes, saturated salt

accelerated aging and the seed vigour imaging system. *Electronic Journal of*

Biotechnology **8**:299-307.

Ren SQ, He KM, Girshick R, Sun J. 2017. Faster R-CNN: towards real-time object

detection with Region Proposal Networks. *Ieee Transactions on Pattern Analysis*

and Machine Intelligence:1137-1149.

https://doi.org/10.1109/TPAMI.2016.2577031.

Roux F, Gasquez J, Reboud X. 2004. The dominance of the herbicide resistance cost in

several *Arabidopsis thaliana* mutant lines. *Genetics* **166**:449-460.

Schneider CA, Rasband WS, Eliceiri KW. 2012. NIH Image to ImageJ: 25 years of

image analysis. *Nature Methods* **9**:671-675.

Shorten C, Khoshgoftaar TM. 2019. A survey on image data augmentation for deep

learning. *Journal of Big Data* **6**:60.

Sun F, Suen PK, Zhang Y, Liang C, Carrie C, Whelan J, Ward JL, Hawkins ND,

Jiang L, Lim BL. 2012. A dual-targeted purple acid phosphatase in *Arabidopsis*

thaliana moderates carbon metabolism and its overexpression leads to faster plant

growth and higher seed yield. *New Phytologist* **194**:206-219.

Szegedy C, Vanhoucke V, Ioffe S, Shlens J, Wojna Z. 2016. Rethinking the inception

architecture for computer vision. *Proceedings of the IEEE Computer Society*

822 *Conference on Computer Vision and Pattern Recognition*:2818-2826.

823 https://doi.org/10.1109/Cvpr.2016.308.

824 **Tanabata T, Shibaya T, Hori K, Ebana K, Yano M. 2012.** SmartGrain: high-

825 throughput phenotyping software for measuring seed shape through image

826 analysis. *Plant Physiology* **160**:1871-1880.

827 **Taylor MA, Wilczek AM, Roe JL, Welch SM, Runcie DE, Cooper MD, Schmitt J.**

828 **2019.** Large-effect flowering time mutations reveal conditionally adaptive paths

829 through fitness landscapes in *Arabidopsis thaliana*. *Proceedings of the National*

830 *Academy of Sciences of the United States of America* **116**:17890-17899.

831 **Thomson CE, Hadfield JD. 2017.** Measuring selection when parents and offspring

832 interact. *Methods in Ecology and Evolution* **8**:678-687.

833 **Toda Y, Okura F, Ito J, Okada S, Kinoshita T, Tsuji H, Saisho D. 2020.** Training

834 instance segmentation neural network with synthetic datasets for crop seed

835 phenotyping. *Communications Biology* **3**:173.

836 **Tzutalin. 2015.** LabelImg. Git code. https://github.com/tzutalin/labelImg. [accessed 12

837 July 2021].

838 **Vasseur F, Bresson J, Wang G, Schwab R, Weigel D. 2018.** Image-based methods for

839 phenotyping growth dynamics and fitness components in *Arabidopsis thaliana*.

840 *Plant Methods* **14**:63.

Supporting information

843 **Fig. S1.** The architecture of Faster R-CNN.

844 **Fig. S2.** Example false negatives from ImageJ analysis and Faster R-CNN models.

Fig. S3. Hyperparameter tuning for seed counting models.

Fig. S4. Computational efficiency of seed counting models.

Fig. S5. Example images with different SDI values.

Fig. S6. Effect of seed density on the performance of the Faster R-CNN models using

different measures of performance.

Fig. S7. Hyperparameter tuning for fruit counting models.

Table S1. Lines used for training seed counting models.

Table S2. Lines used for training fruit counting models.

Table S3. Lines used for analysis of fitness.

Table S4. Hyperparameter space for seed counting.

Table S5. Seed counts in 20 quarter-plate images in the validation set.

Table S6. Hyperparameter space for fruit (silique) counting.

Table S7. Seed counting using ImageJ.

Table S8. Seed counting for 50 test set seed images using $Model_{seed}$ 67.

Table S9. Image property setting for $Model_{seed}$ 68 and $Model_{fruit}$ 76.

Table S10. Fruit counting for 20 test fruit images using $Model_{fruit}$ 21.

Figure 1

(a)

(b)

(c)

Figure 2

(a) First-round modeling

Whole-plate images (256)

Split images ↓

Quarter-plate images (1,024)

Split dataset

Images for 1st round modeling (180)

Images for 2nd round modeling (844)

Manually annotate ↓

Images with manual annotations (180)

Split dataset

Training image set 1 (160)

Validation image set (20)

Train Faster R-CNN models ↓

Evaluate models

Hyperparameters

Proposal   Scale   Aspect ratio

Combinations

100   A   AR-A
500   B   AR-B
1,000 C   AR-C
           AR-D
           AR-E
           AR-F
           AR-G

Model_seed 1-63

3,000   B   AR-A
5,000
10,000

Model_seed 64-66

Best: Model_seed 66

(b) Second-round modeling

Model_seed 66-based quarter-plate *in silico* annot. (844)

Rejoin quarter-plate images ↓

Model_seed 66-based whole-plate *in silico* annot. (211)

Manually curate ↓

Images *with* annotations (211)

Split dataset

Training image set 2 (161)

Test image set (50)

Modify 20 images   Train   Model_seed 67   Evaluate   Modify all 50 images

Evaluate

Training image property settings

Blurriness   5
Brightness   4
Contrast   5
Resolution   7

Testing image property settings

Blurriness   5
Brightness   10
Contrast   10
Resolution   9

Modified training images (420)

Modified test images (1,700)

Include original ↓

Include original ↓

Modified training set 2 (581)

Modified test set (1,750)

Evaluate

Train   Model_seed 68   Evaluate

Generate predictions

Apply Model_seed 66

Figure 3

Figure 4

(a)

PCC = -0.581
p = 9.8e-06

PCC = 0.997
p = 1.5e-54

Figure 5

Figure 6

Figure 7