Parallel processing in speech perception with local and global representations of linguistic context

Christian Brodbeck[1,2,*], Shohini Bhattasali[3,4], Aura A. L. Cruz Heredia[3,5], Philip Resnik[3,4], Jonathan Z. Simon[2,6,7] & Ellen Lau[3]

1) Department of Psychological Sciences, University of Connecticut, Storrs, CT, U.S.A.
2) Institute for Systems Research, University of Maryland, College Park, Maryland, U.S.A.
3) Department of Linguistics, University of Maryland, College Park, Maryland, U.S.A.
4) Institute for Advanced Computer Studies, University of Maryland, College Park, Maryland, U.S.A.
5) Department of Psychology, University of Pennsylvania, Philadelphia, Pennsylvania, U.S.A.
6) Department of Electrical and Computer Engineering, University of Maryland, College Park, Maryland, U.S.A.
7) Department of Biology, University of Maryland, College Park, Maryland, U.S.A.

* christianbrodbeck@me.com

Keywords: temporal response functions, entropy, surprisal, MEG

Impact statement
Speech processing engages multiple predictive models, using sublexical, word- and sentence contexts in parallel to anticipate upcoming phonemes.

Abstract

Speech processing is highly incremental. It is widely accepted that human listeners continuously use the linguistic context to anticipate upcoming concepts, words, and phonemes. However, previous evidence supports two seemingly contradictory models of how a predictive context is integrated with the bottom-up sensory input: Classic psycholinguistic paradigms suggest a two-stage process, in which acoustic input initially leads to local, context-independent representations, which are then quickly integrated with contextual constraints. This contrasts with the view that the brain constructs a single coherent, unified interpretation of the input, which fully integrates available information across representational hierarchies, and thus uses contextual constraints to modulate even the earliest sensory representations. To distinguish these hypotheses, we tested magnetoencephalography responses to continuous narrative speech for signatures of local and unified predictive models. Results provide evidence that listeners employ both types of models in parallel. Two local context models uniquely predict some part of early neural responses, one based on sublexical phoneme sequences, and one based on the phonemes in the current word alone; at the same time, even early responses to phonemes also reflect a unified model that incorporates

sentence level constraints to predict upcoming phonemes. Neural source localization places the anatomical origins of the different predictive models in non-identical parts of the superior temporal lobes bilaterally, with the right hemisphere showing a relative preference for more local models. These results suggest that speech processing recruits both local and unified predictive models in parallel, reconciling previous disparate findings. Parallel models might make the perceptual system more robust, facilitate processing of unexpected inputs, and serve a function in language acquisition.

Introduction

Acoustic events in continuous speech occur at a rapid pace, and listeners face pressure to process the speech signal rapidly and incrementally (Christiansen and Chater, 2016). One strategy that listeners employ to achieve this is to organize internal representations in such a way as to minimize the processing cost of future language input (Ferreira and Chantavarin, 2018). Different accounts have been proposed for how listeners do this, many centered on the notion that they actively predict future input (Gagnepain et al., 2012), for instance using internalized generative models (Halle and Stevens, 1962). Such predictive strategies manifest in a variety of measures that suggest that more predictable words are easier to process (Hale, 2003; Levy, 2008; Smith and Levy, 2013). For instance, spoken words are recognized more quickly when they are heard in a meaningful context (Marslen-Wilson and Tyler, 1975), and words that are made more likely by the context are associated with reduced neural responses, compared to less expected words (Holcomb and Neville, 1991; Connolly and Phillips, 1994; Van Petten et al., 1999; Diaz and Swaab, 2007; Broderick et al., 2018). This contextual facilitation is pervasive, and is sensitive to language statistics (Willems et al., 2016; Weissbart et al., 2020; Schmitt et al., 2020), as well as the discourse level meaning of the language input for the listeners (van Berkum et al., 2003; Nieuwland and Van Berkum, 2006).

In speech, words are often predictable because they occur in sequences that form meaningful messages. Similarly, phonemes are predictable because they occur in sequences that form words. For example, after hearing the beginning /ɹɪv/, /ɝ/ would be a likely continuation forming *river*; /i/ would be more surprising, because *riviera* is a less frequent word, whereas /ʊ/ would be highly surprising because there are no common English words starting with that sequence. Phonemes that are thus inconsistent with known word forms elicit an electrophysiological mismatch response (Gagnepain et al., 2012), and responses to valid phonemes are proportionately larger the more surprising the phonemes are (Ettinger et al., 2014; Gwilliams and Marantz, 2015; Gaston and Marantz, 2017). Predictive processing is not restricted to linguistic representations, as even responses to acoustic features in early auditory cortex reflect expectations based on the acoustic context (Singer et al., 2018; Forseth et al., 2020).

Thus, there is little doubt that the brain uses context to facilitate processing of upcoming input, at multiple levels of representation. Here we investigate a fundamental question about the underlying cognitive organization: Does the brain develop a single, unified representation of the input? In other words, one representation that is consistent across hierarchical levels, effectively propagating information from the sentence context across hierarchical levels to anticipate even low-level features of the sensory input such as phonemes? Or do cognitive subsystems differ in the extent and kind of context they use to interpret their input? This question has appeared in different forms, for example in early debates about whether sensory systems are modular (Fodor, 1985), or whether sensory input and contextual constraints are combined immediately in speech perception (Marslen-Wilson and Tyler, 1975; Tanenhaus et al., 1995). A similar distinction has also surfaced more recently between the local and global architectures of predictive coding (Tabas and von Kriegstein, 2021).

A strong argument for a unified, globally consistent model comes from Bayesian frameworks, which suggest that, for optimal interpretation of imperfect sensory signals, listeners ought to use

the maximum amount of information available to them to compute a prior expectation for up-
coming sensory input (Jurafsky, 1996; Norris and McQueen, 2008). An implication is that speech
processing is truly incremental, with a unified linguistic representation that is updated at the pho-
neme (or an even lower) time scale (Smith and Levy, 2013). Such a unified representation is con-
sistent with empirical evidence for top-down modulation of sensory representations, for example,
suggesting that recognizing a word can bias subsequent phonetic representations (Luthra et al.,
2021), that listeners weight cues like a Bayes-optimal observer during speech perception (Bejjanki
et al., 2011; Feldman et al., 2009), and that they immediately interpret incoming speech with re-
gard to communicative goals (Chambers et al., 2004; Heller et al., 2016). A recent implementation
proposed for such a model is the global variant of hierarchical predictive coding, which assumes a
cascade of generative models predicting sensory input from higher level expectations (Clark, 2013;
Friston, 2010; Tabas and von Kriegstein, 2021). A unified model is also assumed by classical inter-
active models of speech processing, which rely on cross-hierarchy interactions to generate a glob-
ally consistent interpretation of the input (McClelland and Rumelhart, 1981; McClelland and
Elman, 1986; Magnuson et al., 2018).

However, there is also evidence for incomplete use of context in speech perception. Results from
cross-modal semantic priming suggest that, during perception of a word, initially multiple mean-
ings are activated regardless of whether they are consistent with the sentence context or not, and
contextually appropriate meanings only come to dominate at a later stage (Swinney, 1979;
Zwitserlood, 1989). Similarly, listeners' eye movements suggest that they initially consider word
meanings that are impossible given the syntactic context (Gaston et al., 2020). Such findings can
be interpreted as evidence for a two-stage model of word recognition, in which an earlier retrieval
process operates without taking into account the wider sentence context, and only a secondary
process of selection determines the best fit with context (Altmann and Steedman, 1988). Similarly,
at the sublexical level, experiments with non-words suggest that phoneme sequence probabilities
can have effects that are decoupled from the word recognition process (Vitevitch and Luce, 1999,
1998). However, it is also possible that such effects occur only due to the unnaturalness of exper-
imental tasks. For example, in the cross-modal priming task, listeners might come to expect a visual
target which is not subject to sentence context constraints, and thus change their reliance on that
context.

Finally, a third possibility is that a unified model coexists with more local models of context, and
that they operate in a parallel fashion. For example, it has been suggested that the two hemi-
spheres differ with respect to their use of context, with the left hemisphere relying heavily on top-
down predictions, and the right hemisphere processing language in a more bottom-up manner
(Federmeier, 2007).

Distinguishing among these possibilities requires a task that encourages naturalistic engagement
with the context, and a non-intrusive measure of linguistic processing. To achieve this, we analyzed
magnetoencephalography (MEG) responses to continuous narrative speech, using methods that
have previously shown electrophysiological brain responses related to predictive language mod-
els. Previous work, however, has tested either only for a local, or only for a unified context model,
by either using only the current word up to the current phoneme as context (Brodbeck et al.,
2018a; Gillis et al., 2021) or by using predictions from a complete history of phonemes and words

(Donhauser and Baillet, 2020). Because these two context models include overlapping sets of con-
straints, their predictions for neural responses are correlated, and thus need to be assessed jointly.
Furthermore, some architectures predict that both kinds of context model should affect brain re-
sponses separately. For example, a two-stage architecture predicts an earlier stage of lexical pro-
cessing that is sensitive to lexical statistics only, and a later stage that is sensitive to the global
sentence context. Here we directly test such possibilities by comparing the ability of different con-
text models to jointly predict brain responses.

Expressing the use of context through information theory

The sensitivity of speech processing to different definitions of context is formalized through con-
ditional probability distributions (Figure 1). Each distribution reflects an interpretation of ongoing
speech input, at a given level of representation. We here use word forms and phonemes as units
of representation (Figure 1-A), and all our predictors reflect information-theoretic quantities at
the rate of phonemes; however, this is a matter of methodological convenience, and similar mod-
els could be formulated using a different granularity (Smith and Levy, 2013). Figure 1-B shows an
architecture in which each level uses local information from that level, but information from higher
levels does not affect beliefs at lower levels. In this architecture, phonemes are classified at the
sublexical level based on the acoustic input and possibly a local phoneme history. The word level
decodes the current word from the incoming phonemes, but without access to the multi-word
context. Finally, the sentence level updates the sentence representation from the incoming word
candidates, and thus selects those candidates that are consistent with the sentence context. In
such a model, apparent top-down effects such as perceptual restoration of noisy input (Ganong,
1980; Leonard et al., 2016) are generated at higher level decision stages rather than at the initial
perceptual representations (Norris, 1994). In contrast, Figure 1-C illustrates the hypothesis of a
unified, global context model, in which priors at lower levels take advantage of information avail-
able at the higher levels. Here, the sentence context is used in decoding the current word by di-
rectly altering the prior expectation of the word candidates, and this sentence-appropriate expec-
tation is in turn used to alter expectations for upcoming phonemes.

Figure 1. **Information flow in local and unified architectures for speech processing**.

(A) Schematic characterization of the linguistic units used to characterize speech. The same phoneme can be invoked as part of a sublexical phoneme sequence, ph_k, or as part of $word_j$, $ph_{j,i}$.

(B) Each box stands for a level of representation, characterized by its output and a probability distribution describing the level's use of context. For example, the sublexical level's output is an estimate of the current phoneme, ph_k, and the distribution for ph_k is estimated as probability for different phonemes based on the sound input and a sublexical phoneme history. At the sentence level, $sentence_{j,i}$ stands for a temporary representation of the sentence at time j,i. Boxes represent functional organization rather than specific brain regions. Arrows reflect the flow of information: each level of representation is updated incrementally, combining information from the same level at the previous time step (horizontal arrows) and the level below (bottom-up arrows).

(C) The unified architecture implements a unified, global context model through information flowing down the hierarchy, such that expectations at lower levels incorporate information accumulated at the sentence level. Relevant differences from the local context model are in red. Note that while the arrows only cross one level at a time, the information is propagated in steps and eventually crosses all levels.

These hypotheses make different predictions for brain responses sensitive to language statistics. Probabilistic speech representations, as in Figure 1, are linked to brain activity through information theoretic complexity metrics (Hale, 2016). The most common linking variable is *surprisal*, which is equivalent to the difficulty incurred in updating an incremental representation of the input (Levy, 2008). Formally, the surprisal experienced at phoneme k is inversely related to the likelihood of that phoneme in its context:

$$I(ph_k) = -log_2(p(ph_k|context))$$

180 A second information theoretic measure that has been found to independently predict brain ac-
181 tivity is entropy (Brodbeck et al., 2018a; Donhauser and Baillet, 2020), a measure of the uncer-
182 tainty in a probability distribution. Phoneme entropy is defined as the expected (average) surprisal
183 for the next phoneme:

189
$$H_{ph}(ph_k) = -\sum_{ph}^{phonemes} p(ph_{k+1} = ph|context) \log_2(p(ph_{k+1} = ph|context))$$

184 In contrast to surprisal, which is a function of the expected probability of the current event only,
185 entropy is a function of the whole distribution of expectations. This makes it possible to distinguish
186 between phoneme entropy, the uncertainty about the next phoneme, and cohort entropy, the
187 uncertainty about the complete word form that matches the current partial input (for more details
188 see *Lexical context model* in *Methods*):

195
$$H_w(ph_{j,i}) = -\sum_{word}^{lexicon} p(word_j = word|context) \log_2(p(word_j = word|context))$$

Entropy might relate to neuronal processes in at least two ways. First, the amount of uncertainty
might reflect the amount of competition among different representations, which might play out
through a neural process such as lateral inhibition (McClelland and Elman, 1986). Second, uncer-
tainty might also be associated with increased sensitivity to bottom-up input, because the input is
expected to be more informative (Jaramillo and Zador, 2011; Auksztulewicz et al., 2019).

Models for responses to continuous speech
To test how context is used in continuous speech processing, we compared the ability of three
different context models to predict MEG responses, corresponding to the three levels in Figure 1-
B (see Figure 2). The context models all incrementally estimate a probability distribution at each
phoneme position, but they differ in the amount and kind of context they incorporate. Through-
out, we used n-gram models to estimate sequential dependencies because they are powerful lan-
guage models that can capture effects of language statistics in a transparent manner, with minimal
assumptions about the underlying cognitive architecture (Futrell et al., 2020; Levy, 2008; Smith
and Levy, 2013). An example of the complete set of predictors is shown in Figure 3.

Sublexical context model: A 5-gram model estimates the prior probability for the next phoneme
given the 4 preceding phonemes. This model reflects simple phoneme sequence statistics (Vi-
tevitch and Luce, 1999, 1998) and is unaware of word boundaries. Such a model is thought to play
an important role in language acquisition (Cairns et al., 1997; Chambers et al., 2003; Saffran et al.,
1996), but it is unknown whether it has a functional role in adult speech processing. The sublexical
model predicted brain responses via the phoneme surprisal and entropy linking variables.

Word context model: This model implements the cohort model of word perception (Marslen-Wil-
son, 1987), applied to each word in isolation. The first phoneme of the word generates a proba-
bility distribution over the lexicon, including all words starting with the given phoneme, and each
word's probability proportional to the word's relative unigram frequency. Each subsequent pho-
neme trims this distribution by removing words that are inconsistent with that phoneme. Like the
sublexical model, the lexical model can be used as a predictive model for upcoming phonemes,
yielding phoneme surprisal and entropy variables. In addition, the lexical model generates a prob-
ability distribution over the lexicon, which yields a cohort entropy variable.

Sentence context model: The sentence model is closely related to the word context model, but
each word's prior probability is estimated from a lexical 5-gram model. While a 5-gram model
misses longer-range linguistic dependencies, we use it here as a conservative approximation of
sentence level linguistic and interpretive constraints (Smith and Levy, 2013). The sentence model
implements cross-hierarchy predictions by using the sentence context in concert with the partial
current word to predict upcoming phonemes. Brain activity is predicted from the same three var-
iables as from the word context model.

We evaluated these different context models in terms of their ability to explain held-out MEG
responses, and the latency of the brain responses associated with each model. An architecture
based on local context models, as in Figure 1-B, predicts a temporal sequence of responses as
information passes up the hierarchy, with earlier responses reflecting lower order context models.
In contrast, a unified architecture, as in Figure 1-C, predicts that the sentence context model
should exhaustively explain brain responses, because all representational levels use priors derived
from the sentence context. Finally, architectures that entail multiple kinds of models predict that
different context models might explain response components, possibly in different anatomical ar-
eas.

Acoustic controls: In order to dissociate effects of linguistic processing from responses to acoustic
properties of the speech stimulus, all models controlled a gammatone spectrogram and an acous-
tic onset spectrogram (Brodbeck et al., 2020), as well as word onsets and phoneme onsets (Brod-
beck et al., 2018a).

Figure 2. **Models for predictive speech processing based on the sentence, word, and sublexical context, used to predict MEG data.**

(A) Example of word-by-word surprisal. The sentence (5-gram) context generally leads to a reduction of word surprisal, but the magnitude of the reduction differs substantially between words (across all stimuli, mean ± standard deviation, unigram surprisal: 10.76 ± 5.15; 5-gram surprisal: 7.43 ± 5.98; t_{8172} = 76.63, p < .001).

(B) Sentence level predictions propagate to phoneme surprisal, but not in a linear fashion. For example, in the word *happened*, the phoneme surprisal based on all three models is relatively low for the second phoneme /æ/ due to the high likelihood of word candidates like *have* and *had*. However, the next phoneme is /p/ and phoneme surprisal is high across all three models. On the other hand, for words like *find*, *on* and *Ohio*, the sentence-constrained phoneme surprisal is disproportionately low for subsequent phonemes, reflecting successful combination of the sentence constraint with the first phoneme.

(C) Phoneme-by-phoneme estimates of information processing demands, based on different context models, were used to predict MEG responses through multivariate temporal response functions (mTRFs) (Brodbeck et al., 2018b). An mTRF consists of multiple TRFs estimated jointly such that each predictor, convolved with the corresponding TRF, predicts a partial response, and the point-wise sum of partial responses constitutes the predicted MEG response. The dependent

measure (measured response) was the fixed orientation, distributed minimum norm source current estimate of the continuous MEG response. The blue arrow illustrates a single virtual current source dipole. Estimated signals at current dipoles across the brain were analyzed using a mass-univariate approach. See Methods for details. TRFs: temporal response functions.

Figure 3. **Stimulus excerpt with all 26 predictors used to model brain responses**. From the top: Phoneme-level information-theoretic variables, based on different context definitions: Sentence, word, and sublexical context; Intercepts for word- and phoneme-related brain activity, i.e., a predictor to control for brain activity that does not scale with the variables under consideration; and an auditory processing model, consisting of an acoustic spectrogram (sound envelopes) and an onset spectrogram (sound onsets), each represented by 8 predictors for 8 frequency bands.

Results

Twelve participants listened to ~47 minutes of a nonfiction audiobook. Multivariate temporal response functions (mTRFs) were used to jointly predict held-out, source localized MEG responses (Figure 2-C). To test whether each context model is represented neurally, the predictive power of the full model including all predictors was compared with the predictive power of a model that was estimated without the predictor variables belonging to this specific context model. Besides 11 right-handers, our sample included a single left-hander. While this participant's brain responses were more right-lateralized than average, excluding them did not change the conclusions from

277 any of the reported lateralization significance tests. We thus report results from the total sample,
278 but identify the left-hander in plots and source data.

Phoneme-, Word- and Sentence-constrained models co-exist in the brain

Each context model significantly improves the prediction of held-out data, even after controlling
for acoustic features and the other two context models (Figure 4-A). Each of the three context
models' source localization is consistent with sources in the superior temporal gyrus (STG),
thought to support phonetic and phonological processing (Mesgarani et al., 2014). In addition, the
sentence constrained model also extends to more ventral parts of the temporal lobe, consistent
with higher-level language processing (Hickok and Poeppel, 2007; Wilson et al., 2018). In compar-
ison, the predictive power of the acoustic features is highest in closer vicinity of Heschl's Gyrus
(Figure 4-D). At each level of context, surprisal and entropy contribute about equally to the
model's predictive power (Figure 4-B, Table 1).

289
Figure 4. **All context models significantly contribute to predictions of brain responses**.

(A) Each context model significantly improves predictions of held-out MEG data in both hemi-
spheres ($t_{max} \geq 6.16$, $p \leq .005$). Black bars below anatomical plots indicate a significant difference
between hemispheres. The white outline indicates a region of interest (ROI) used for measures
shown in (B), (C) and (E). Brain regions excluded from analysis are darkened (occipital lobe and
insula).
(B) Surprisal and entropy have similar predictive power in each context model. Each dot represents
the difference in predictive power between the full and a reduced model for one subject, averaged
in the ROI. Cohort- and phoneme entropy are combined here because the predictors are highly
correlated and hence share a large portion of their explanatory power. Corresponding statistics
and effect-size are given in Table 1. A single left-handed participant is highlighted throughout with
an unfilled circle. LH: left hemisphere; RH: right hemisphere.
(C) Even when tested individually, excluding variability that is shared between the two, cohort-
and phoneme entropy at each level significantly improve predictions. A significant effect of sen-
tence-constrained phoneme entropy is evidence for cross-hierarchy integration, as it suggests that
sentence level information is used to predict upcoming phonemes.
(D) Predictive power of the acoustic feature representations.
(E) The lateralization index ($LI = R/(L + R)$) indicates that the sublexical context model is more
right-lateralized than the sentence context model. Left: LI = 0; Right: LI = 1.
Significance levels: * $p \leq .05$; ** $p \leq .01$; *** $p \leq .001$. Statistics for A, D: Figure 4–Source Data 1.txt;
ROI data for B, C, E: Figure 4–Source Data 2.txt.

	Left hemisphere				Right hemisphere			
	Δ‰	$t(11)$	p	d	Δ‰	$t(11)$	p	d
Sentence context								
Surprisal	3.77	4.40**	.001	1.27	5.51	4.14**	.002	1.19
Entropy	3.40	5.96***	< .001	1.72	1.94	4.11**	.002	1.19
Cohort	0.83	3.41**	.006	0.98	0.39	2.45*	.032	0.71
Phoneme	0.85	5.18***	< .001	1.50	0.79	3.85**	.003	1.11
Word context								
Surprisal	0.78	3.62**	.004	1.04	1.71	5.76***	< .001	1.66
Entropy	1.26	4.43**	.001	1.28	1.31	4.39**	.001	1.27
Cohort	0.25	3.29**	.007	0.95	0.36	3.99**	.002	1.15
Phoneme	0.51	4.59***	< .001	1.32	0.66	3.61**	.004	1.04
Sublexical context								
Surprisal	0.64	4.88***	< .001	1.41	1.29	4.59***	< .001	1.33
Entropy	0.66	2.53*	.028	0.73	1.91	5.32***	< .001	1.54

Table 1. **Predictive power in mid/posterior STG ROI for individual predictors**. One-tailed *t*-tests and
Cohen's *d* for the predictive power uniquely attributable to the respective predictors. Data under-
lying these values is the same as for the swarm-plots in Figure 4-B and C (Figure 4-Source Data
2.txt).

Overall, the acoustic features explain more of the variability in brain responses than the linguistic
features (compare scales in Figure 4-A and D). This is likely because speech is an acoustically rich
stimulus, driving many kinds of auditory receptive fields. In contrast, the linguistic predictors rep-
resent very specific computations, likely represented in a small and specialized neural territory.
For the present purpose, what is critical is the consistency of the linguistic effects across subjects:
Figure 4-B and C, as well as the effect sized shown in Table 1 suggest that the linguistic modulation
of brain responses can be detected very reliably across subjects.

The significant predictive power of the local context models is inconsistent with the hypothesis of
a single, unified context model (Figure 1-C). Instead, it suggests that different neural representa-
tions incorporate different kinds of context. We next pursued the question of how these different
representations are organized hierarchically. Phoneme surprisal depends on the conditional prob-
ability of the current phoneme, and thus does not distinguish between whether what is predicted
is a single phoneme or the whole lexical completion (Levy, 2008; Smith and Levy, 2013). Entropy,
on the other hand, depends on the units over which probabilities are calculated, and can thus
potentially distinguish between whether brain responses reflect uncertainty over the next pho-
neme alone, or uncertainty over the word currently being perceived, i.e., over the lexical comple-
tion (see *Lexical context model* in *Methods*). This distinction is particularly interesting for the sen-
tence context model: if predictions are constrained to using context *within* a hierarchical level, as
in Figure 1-B, then the sentence context should affect uncertainty about the upcoming word, but
not uncertainty about the upcoming phoneme. On the other hand, a brain response related to
sentence-conditional phoneme entropy would constitute evidence for cross-hierarchy predic-
tions, with sentence level context informing predictions of upcoming phonemes.

Even though phoneme and cohort entropy were highly correlated (sentence context: $r = .92$; word
context: $r = .90$), each of the four representations was able to explain unique variability in the MEG
responses that could not be attributed to any of the other representations (Figure 4-C, Table 1).
This suggests that the sentence context model is not restricted to predicting upcoming words, but
also generates expectations for upcoming phonemes. This is thus evidence for cross-hierarchy top-
down information flow, indicative of a unified language model that aligns representations across
hierarchical levels. Together, these results thus indicate that the brain does maintain a unified
context model, but that it *also* maintains more local context models.

Different context models affect different neural processes
All three context models individually contribute to neural representations, but are these represen-
tations functionally separable? While all three context models improve predictions in both hemi-
spheres, the sentence constrained model does so symmetrically, whereas the lexical and sublexi-
cal models are both more strongly represented in the right hemisphere than in the left hemisphere
(Figure 4-A). This pattern might suggest an overall right-lateralization of linguistic processing; how-
ever, the predictive power of the joint linguistic model (predictors from all three levels combined)

is not significantly lateralized (t_{max} = 4.11, p = .134). These results thus suggests that linguistic pro-
cessing is bilateral, but that the hemispheres differ in what context models they rely on. Consistent
with this, the context models differ in their relative lateralization (Figure 4-E). The sublexical con-
text model is significantly more right-lateralized than the sentence model (t_{11} = 4.41, p = .001),
while the word model is only numerically more right-lateralized than the sentence model (t_{11} =
1.53, p = .154). These lateralization patterns suggests an anatomical differentiation in the repre-
sentations of different context models, with the left hemisphere primarily relying on a unified
model of the sentence context, and the right hemisphere more broadly keeping track of different
context levels.

Given that all three context models are represented in the STG, especially in the right hemisphere,
a separate question concerns whether, within a hemisphere, the different context models predict
activity in the same or different neural sources. While MEG source localization does not allow
precisely separating different sources in close proximity, it does allow statistically testing whether
two effects originate from the same or from a different configuration of neural sources (Lüt-
kenhöner, 2003). The null hypothesis of such a test (McCarthy and Wood, 1985) is that a single
neural process, corresponding to a fixed configuration of current sources, generates activity that
is correlated with all three context models. The alternative hypothesis suggests some differentia-
tion between the configuration of sources recruited by the different models. Results indicate that,
in the right hemisphere, all three context models, as well as the two acoustic models, originate
from different source configurations ($F_{(175, 1925)}$ ≥ 1.25, p ≤ .017). In the left hemisphere, the sen-
tence constrained model is localized differently from all other models ($F_{(179, 1969)}$ ≥ 1.38, p < .001),
whereas there is no significant distinction among the other models (possibly due to lower power
due to the weaker effects in the left hemisphere for all but the sentence model). In sum, these
results suggest that the different context models are maintained by at least partially separable
neural processes.

Sentence context affects early responses and dominates late responses
The TRFs estimated for the full model quantify the influence of each predictor variable on brain
responses over a range of latencies (Figure 2-C). Figure 5 shows the response magnitude to each
predictor variable as a function of time, relative to phoneme onset. For an even comparison be-
tween predictors, TRFs were summed in the anatomical region in which any context model signif-
icantly improved predictions. Note that responses prior to 0 ms are plausible due to coarticulation,
by which information about a phoneme's identity can already be present in the acoustic signal
prior to the conventional phoneme onset (Beddor et al., 2013; Salverda et al., 2003). Figure 5**Error!**
Reference source not found.-G shows the anatomical distribution of responses related to the dif-
ferent levels of context.

Surprisal quantifies the incremental update to a context model due to new input. A brain response
related to surprisal therefore indicates that the sensory input is brought to bear on a neural rep-
resentation that uses the corresponding context model. Consequently, the latencies of brain re-
sponses related to surprisal at different context models are indicative of the underlying processing
architecture. In an architecture in which information is sequentially passed to higher level repre-
sentations with broadening context models (Figure 1-B), responses should form a temporal se-
quence from narrower to broader contexts. However, in contrast to this prediction, the observed

responses to surprisal suggest that bottom-up information reaches representations that use the
sentence- and word-level contexts *simultaneously*, at an early response peak (Figure 5-A; peak in
the early time window for sentence context: 78 ms, SD = 24 ms; word context: 76 ms, SD = 11 ms).
Sublexical surprisal is associated with a lower response magnitude overall, but also exhibits an
early peak at 94 ms (SD = 26 ms). None of these three peak latencies differ significantly (all pairwise
$t_{11} \leq 2.01$, $p \geq .065$). This suggests a parallel processing architecture in which different context
representations are activated simultaneously by new input. Later in the timecourse the responses
dissociate more strongly, with a large, extended response reflecting the sentence context, but not
the word context starting at around 205 ms ($t_{max} = 5.27$, $p = .007$). The lateralization of the TRFs is
consistent with the trend observed for predictive power: a symmetric response reflecting the uni-
fied sentence context, and more right-lateralized responses reflecting the more local contexts (Fig-
ure 5-B).

407
Figure 5. **Early responses reflect parallel activation of all context models, later responses selec-**
tively reflect activity in the sentence-constrained model.
(A) Current magnitude of TRFs to phoneme surprise for each level of context (mean and within-
subject standard error (Loftus and Masson, 1994); y-axis scale identical in all panels of the figure).
To allow fair comparison, all TRFs shown are from the same symmetric ROI, including all current
dipoles for which at least one of the three context models significantly improved the response
predictions. Bars indicate time windows corresponding to source localizations shown in panel G.
(B) When plotted separately for each hemisphere, relative lateralization of the TRFs is consistent
with the lateralization of predictive power (Figure 4).
(C-D) TRFs to lexical cohort entropy are dominated by the sentence context model.

(E-F) TRFs to phoneme entropy are similar between context models, consistent with parallel use
of different contexts in predictive models for upcoming speech.
(G) All context models engage the superior temporal gyrus at early responses, mid-latency re-
sponses incorporating the sentence context also engage more ventral temporal areas. Anatomical
plots reflect total current magnitude associated with different levels of context representing early
(-50 – 150 ms), mid-latency (150 – 350 ms) and late (350 – 550 ms) responses. The color-scale is
adjusted for different predictors to avoid images dominated by the spatial dispersion characteris-
tic of MEG source estimates.
Peak latencies in the early time window: Figure 5-Source Data 1.txt; Pairwise tests of TRF time
courses: Figure 5-Source Data 2.txt.

The TRFs, convolved with the corresponding predictors generate partial predicted responses (cf.
Figure 2-C). This reconstruction thus allows decomposing brain responses into component re-
sponses corresponding to different predictors. Figure 6 uses this to simulate the responses corre-
sponding to the different context models, illustrating several of the observations made above. As
the sentence level was the most predictive power, so it also corresponds to higher amplitude re-
sponses than the other levels. Furthermore, the sub-sentence levels exhibit small modulations
close to surprising phonemes, corresponding to the mainly brief, low latency TRFs. In contrast,
response corresponding to the sentence level are dominated by larger waves, lagging surprising
phonemes by several hundred milliseconds, corresponding to the sustained higher TRF amplitudes
at later latencies.

438
Figure 6. **Decomposition of brain responses into context levels**. Predicted brain responses related
to processing different levels of context (combining surprisal and entropy predictors; mean and
within-subject standard error). Stem plots correspond to surprisal for the given level. Slow fluctu-
ations in brain responses are dominated by the sentence level, with responses occurring several
hundred milliseconds after surprising phonemes, consistent with the high amplitude at late laten-
cies in TRFs. Partial predicted responses were generated for each context model by convolving the
TRFs with the corresponding predictors; summing the predicted responses for the predictors cor-
responding to the same level; and extracting the magnitude (sum of absolute values) in the STG
ROI.

Sentence context dominates word recognition, all contexts drive phoneme predictions

Brain responses related to entropy indicate that neural processes are sensitive to uncertainty or competition in the interpretation of the speech input. Like surprisal, such a response suggests that the information has reached a representation that has incorporated the corresponding context. In addition, because entropy measures uncertainty regarding a categorization decision, the response to entropy can distinguish between different levels of categorization: uncertainty about the current word (cohort entropy) versus uncertainty about the next phoneme (phoneme entropy).

The TRFs to cohort entropy suggest a similar pattern as those to surprisal (Figure 5 C-D). Both cohort representations are associated with an early peak (sentence context: 56 ms, SD = 28 ms; word context: 80 ms, SD = 23 ms), followed only in the sentence constrained cohort by a later sustained effect. In contrast to surprisal, however, even early responses to cohort-entropy are dominated by the sentence context (t_{max} = 5.35, p = .004 at 43 ms; later responses: t_{max} = 7.85, p < .001 at 461 ms). This suggests that lexical representations are overall most strongly activated in a model that incorporates the sentence context.

In contrast to surprisal and cohort entropy, the responses to phoneme entropy are similar for all levels of context, dominated by an early and somewhat broader peak (Figure 5 E-F). There is still some indication of a second, later peak in the response to sentence-constrained phoneme entropy, but this might be due to the high correlation between cohort and phoneme entropy. A direct comparison of sentence-constrained cohort and phoneme entropy indicates that early processing is biased towards phoneme entropy (though not significantly) while later processing is biased towards cohort entropy (t_{max} = 4.74, p = .017 at 231 ms).

In sum, the entropy results suggest that all context representations drive a predictive model for upcoming phonemes. This is reflected in a short-lived response in STG, consistent with the fast rate of phonetic information. Simultaneously, the incoming information is used to constrain the cohort of word candidates matching the current input, with lexical activations primarily driven by a unified model that incorporates the sentence context.

Mid-latency, sentence-constrained processing engages larger parts of the temporal lobe

Source localization suggests that early activity originates from the vicinity of the auditory cortex in the upper STG, regardless of context (Figure 5-G**Error! Reference source not found.**). The precise source configuration in the right STG nevertheless differs between contexts in the early time window (sentence vs word: $F_{(175, 1925)}$ = 2.08, p < .001; word vs sublexical: $F_{(175, 1925)}$ = 5.99, p < .001). More notably, the sentence-based responses in the mid-latency window recruits more sources, localized to the middle and inferior temporal lobe. Accordingly, the sentence-based responses in the mid-latency window differs significantly from the early window (left hemisphere: $F_{(179, 1969)}$ = 1.72, p < .001; right hemisphere: $F_{(175, 1925)}$ = 5.48, p < .001). These results suggest that phonetic information initially engages a set of sources in the STG, while a secondary stage then engages more ventral sources that specifically represent the sentence context.

No evidence for a trade-off between contexts

We interpret our results as evidence that different context models are maintained in parallel. An alternative possibility is that there is some trade-off between contexts used, and it only appears

489 in the averaged data as if all models were operating simultaneously. This alternative predicts a
490 negative correlation between the context models, reflecting the trade-off in their activation. No
491 evidence was found for such a trade-off, as correlation between context models were generally
492 neutral or positive across subjects and across time (Figure 7).

493
Figure 7. **No evidence for a trade-off between context models.**
(A) Trade-off across subjects: Testing the hypothesis that subjects differ in which context model
they rely on. Each plot compares the predictive power of two context models in the mid/posterior
STG ROI, each dot representing % explained for one subject. The line represents a linear regression
with 95% bootstrap confidence interval (Waskom, 2021). None of the pairwise comparisons ex-
hibits a negative correlation that would be evidence for a trade-off between reliance on different
context models. Data from Figure 4-Source Data 2.txt.
(B) Trade-off over time: Testing the hypothesis that subjects alternate over time in which context
model they rely on. Each dot represents the partial correlation over time between the predictive
power of two context models for one subject, controlling for predictive power of the full model.
Correlations are shown separately for the left and the right hemisphere (L/R). Stars correspond to
a one-sample *t*-tests of the null-hypothesis that the average *r* across subjects is 0, i.e., that the two
context models are unrelated over time. None of the context models exhibited a significant nega-
tive correlation that would be evidence for a trade-off over time. Data in Figure 7-Source Data
1.txt.

Discussion

510 The present MEG data provide clear evidence for the existence of a neural representation of
511 speech that is unified across representational hierarchies. This representation incrementally inte-
512 grates phonetic input with information from the multi-word context within about 100 ms. How-
513 ever, in addition to this globally unified representation, brain responses also show evidence of
514 separate neural representations that use more local contexts to process the same input.

Parallel representations of speech using different levels of context

The evidence for a unified global model suggests that there is a functional brain system that pro-
cesses incoming phonemes while building a representation that incorporates constraints from the
multi-word context. A possible architecture for such a system is the unified global architecture

shown in Figure 1-C, in which a probabilistic representation of the lexical cohort mediates between
sentence and phoneme level representations: the sentence context modifies the prior expectation
for each word, which is in turn used to make low-level predictions about the phonetic input. While
there are different possible implementations for such a system, the key feature is that the global
sentence context is used to make predictions for and interpret low-level phonetic, possibly even
acoustic (Sohoglu and Davis, 2020) input.

A second key result from this study, however, is evidence that this unified model is not the only
representation of speech. Brain responses also exhibited evidence for two other, separate func-
tional systems that process incoming phonemes while building representations that incorporate
different, more constrained kinds of context: one based on a local word context, processing the
current word with a prior based on context-independent lexical frequencies, and another based
on the local phoneme sequence regardless of word boundaries. Each of these three functional
systems generates its own predictions for upcoming phonemes, resulting in parallel responses to
phoneme entropy. Each system is updated incrementally at the phoneme rate, reflected in early
responses to surprisal. However, each system engages an at least partially different configuration
of neural sources, as evidenced by the localization results.

Together, these results suggest that multiple predictive models process speech input in parallel.
An architecture consistent with these observations is sketched in Figure 8: three different neural
systems receive the speech input in parallel. Each representation is updated incrementally by ar-
riving phonemes. However, the three systems differ in the extent and kind of context that they
incorporate, each generating its own probabilistic beliefs about the current word and/or future
phonemes. For instance, the sublexical model uses the local phoneme history to predict upcoming
phonemes. The updates are incremental because the state of the model at time $k+1$ is determined
by the state of the model at time k and the phoneme input from time k. The same incremental
update pattern applies to the sublexical, word and sentence models.

Figure 8. An architecture for speech perception with multiple parallel context models. A model of information flow, consistent with brain signals reported here. Brain responses associated with Information theoretic variables provided separate evidence for each of the probability distributions in the colored boxes. From left to right, the three different context models (sentence, lexical and sublexical) update incrementally as each phoneme arrives. The cost of these updates is reflected in the brain response related to surprisal. Representations also include probabilistic representations of words and upcoming phonemes, reflected in brain responses related to entropy.

A listener whose goal is comprehending a discourse-level message might be expected to rely primarily on the unified, sentence constrained context model. Consistent with this, there is some evidence that this model has a privileged status. Among the linguistic models, the unified model has the most explanatory power and clearly bilateral representation (Figure 4). In addition, while activity in local models was short-lived, the unified model was associated with extended activation for up to 600 ms and recruitment of more ventral regions of the temporal lobe (Figure 5). This suggests that the update in the unified model is normally more extensive than the local models, and could indicate that the unified model most commonly drives semantic as well as form representations, while the short-lived local models might be restricted to form-based representations.

Implications for speech processing

A longstanding puzzle in the comprehension literature has been why activation of candidates not supported by context is sometimes reported (Swinney, 1979; Zwitserlood, 1989), if top-down sentence context rapidly feeds down to early levels of speech perception. Parallel activation of lexical candidates based on sentence and word context models can explain these findings. Short-lived

brain responses (up to 150 ms after phoneme onset) show evidence of parallel activation of sen-
tence-constrained as well as sentence-independent word candidates. The co-existence of these
two candidate sets can explain short-lived priming of sentence-inappropriate candidates. Whereas
brain responses related to sentence-independent candidates are transient, brain responses re-
lated to sentence-appropriate candidates exhibit a secondary, sustained response (150-550 ms),
explaining selective priming of sentence-appropriate candidates at longer delays.

If context-constrained candidates are immediately available, then why maintain alternative, sen-
tence-independent candidates or even sublexical probabilistic phoneme sequences? One func-
tional advantage might be faster recovery when sentence-based predictions turn out to be mis-
leading. Such an effect has been described in reading, where contextually unexpected continua-
tions are not associated with a proportional increase in processing cost (Frisson et al., 2017; Luke
and Christianson, 2016).

Similarly, a representation of sublexical phoneme sequences might be functionally relevant when
encountering input that is noisy or not yet part of the lexicon. Phoneme transition probabilities
are generally higher within words than between words, such that low probability phoneme tran-
sitions are cues to word boundaries (Cairns et al., 1997; Harris, 1955). Statistical phoneme se-
quence models might thus play an important role in language acquisition by bootstrapping lexical
segmentation of continuous speech (Cairns et al., 1997; Chambers et al., 2003; Saffran et al.,
1996). Even in adult speech perception, they might have a similar function when encountering
novel words, such as domain-specific vocabularies or personal names (Norris and McQueen,
2008). Finally, the linguistic context can be highly informative for phoneme recognition (Hitczenko
et al., 2020), and different levels of context might make complementary contributions.

Our results suggest that the different context models operate in parallel, without an apparent
trade-off, between subjects, or over time. However, our listening condition was also relatively uni-
form – listening to an audiobook in quiet background. It is conceivable that the different models
play more differentiated roles in different listening conditions, for example in unpredictable con-
versations or speech in noise.

Implications for word recognition
Perhaps the most surprising implication of our results is that multiple probabilistic cohort repre-
sentations seem to be maintained in parallel. This is most directly implied by the result that two
different cohort entropy predictors both explain unique variability in the data, one based on the
lexical frequency of each candidate, and another based on the contextual likelihood of each can-
didate. This is inconsistent with models in which each lexical candidate is assigned a single "acti-
vation" value (e.g. Morton, 1969). It might be more readily reconciled with models that distinguish
between a lexical item's entry in long-term memory, and its instantiation as a token for parsing a
speech signal, since such a mechanism allows for multiple tokens corresponding to the same lexi-
cal item (McClelland and Elman, 1986; Norris, 1994; Norris and McQueen, 2008). Yet, existing
models generally are restricted to a single "arena" for lexical competition, whereas our results
imply the possibility that the competition plays out in parallel in at least partially different brain
systems.

A second implication is that feedback from the sentence level context can and does affect pho-
neme processing. The observed phoneme entropy effects indicate that phoneme level expecta-
tions are modulated by the sentence context. This is inconsistent with some models of word recog-
nition that assume a pure bottom-up process (e.g. Norris et al., 2000). However, at the same time,
the parallel architecture we propose (Figure 8) addresses a central theoretical problem associated
with feedback in multi-stage architectures: Bayesian accounts of perception suggest that listeners
generate a prior, reflecting an estimate of future input, and compare this prior to the actual input
to compute a posterior probability, or interpretation of the sensory percept. In multi-stage archi-
tectures that allow different priors at sequential hierarchical levels (such as Figure 1-B), higher
levels receive the posterior interpretation of the input from the lower levels, rather than the un-
biased input itself. This is suboptimal when considering a Bayesian model of perception, because
the prior of lower level systems is allowed to distort the bottom-up evidence before it is compared
to the prior generated by higher levels (Norris et al., 2016). In contrast, the parallel representations
favored by the evidence presented here allows undistorted bottom-up information to be directly
compared with the context model for each definition of context. The parallel model can thus ac-
commodate empirical evidence for feedback while avoiding this theoretical problem associated
with sequential models.

Evidence for graded linguistic predictions

There is broad agreement that language processing involves prediction, but the exact nature of
these predictions is more controversial (DeLong et al., 2005; Huettig, 2015; Nieuwland et al., 2020,
2018; Pickering and Gambi, 2018). Much of the debate is about whether humans can represent
distributions over many likely items, or just predict specific items. Previous research showing an
early influence of sentence context on speech processing has typically relied on specifically de-
signed, highly constraining contexts which are highly predictive of a specific lexical item (Holcomb
and Neville, 1991; Connolly and Phillips, 1994; Van Petten et al., 1999; Rommers et al., 2013). In
such highly predictive contexts, listeners might indeed predict specific items, and such predictions
might be linked to the left-lateralized speech productions system (Federmeier, 2007; Pickering
and Gambi, 2018). However, such a mechanism would be less useful in more representative lan-
guage samples, in which highly predictable words are rare (Luke and Christianson, 2016). In such
situations of limited predictability, reading time data suggest that readers instead make graded
predictions, over a large number of possible continuations (Luke and Christianson, 2016; Smith
and Levy, 2013). Alternatively, it has also been suggested that what looks like graded predictions
could actually be pre-activation of specific higher-level semantic and syntactic features shared
among the likely items (Altmann and Kamide, 1999; Luke and Christianson, 2016; Matchin et al.,
2018; Pickering and Gambi, 2018; Van Berkum et al., 2005), without involving prediction of form-
based representations. The present results, showing brain responses reflecting sentence-con-
strained cohort- and phoneme entropy, provide a new kind of evidence in favor of graded proba-
bilistic and form-based predictions at least down to the phoneme level.

Bilateral pathways to speech comprehension

Our results suggest that lexical/phonetic processing is largely bilateral. This is consistent with ex-
tensive clinical evidence for bilateral receptive language ability (Gazzaniga and Sperry, 1967; Kutas

et al., 1988; Poeppel, 2001; Hickok and Poeppel, 2007), and suggestions that the right hemisphere
might even play a distinct role in complex, real-world language processing (Federmeier et al., 2008;
Jung-Beeman, 2005). In healthy participants, functional lateralization of sentence processing has
been studied in reading using visual half-field presentation (Federmeier and Kutas, 1999). Over-
whelmingly, results from these studies suggest that lexical processing in both hemispheres is dom-
inated by sentence meaning (Coulson et al., 2005; Federmeier et al., 2005; Federmeier and Kutas,
1999; Wlotko and Federmeier, 2007). This is consistent with the strong bilateral representation of
the unified model of speech found here. As in the visual studies, the similarity of the response
latencies in the two hemispheres implies that right-hemispheric effects are unlikely to be due to
inter-hemispheric transfer from the left hemisphere (Figure 5).

In addition to bilateral representation, however, our results also suggest that the two hemispheres
differ with respect to the context models they entertain. Visual half-field reading studies have in-
dicated a pattern of hemispheric differences, which has been interpreted as indicating that the
left hemisphere processes language in a maximally context-sensitive manner, whereas the right
hemisphere processes the sensory input in a bottom-up manner, unbiased by the linguistic context
(Federmeier, 2007). Our results suggest a modification of this proposal, indicating that both hem-
ispheres rely on sentence-based, graded predictions, but that the right hemisphere *additionally*
maintains stronger representations of local contexts. Finally, lateralization might also depend on
task characteristics such as stimulus familiarity (Brodbeck et al., 2018a), and in highly constraining
contexts the left hemisphere might engage the left-lateralized language production system to
make specific predictions (Federmeier, 2007; Pickering and Gambi, 2018).

Limitations of the sentence context model

We approximated the sentence context with a 5-gram model. This model provides an accurate
estimate of the sum of local constraints, based on a context of the four preceding words only.
However, it misses the more subtle influences of the larger context, both semantic constraints and
syntactic long-range dependencies, which might make the sentence level even more different
from the local context models. Furthermore, lexical N-gram models conflate the influence of syn-
tactic, semantic, and associative constraints (e.g., idioms). It is thus possible that work with more
sophisticated language models can reveal an even more complex relationship between global and
local contexts.

Conclusions

Prior research on the use of context during language processing has often focused on binary dis-
tinctions, such as asking whether context is or is not used to predict future input. Such questions
assumed a single serial or cascaded processing stream. Here we show that this assumption might
have been misleading, because different predictive models are maintained in parallel. Our results
suggest that robust speech processing is based on probabilistic predictions using different context
models in parallel, and cutting across hierarchical levels of representations.

Materials and Methods

Participants

Twelve native speakers of English were recruited from the University of Maryland community (6
female, 6 male, age mean = 21 years, range 19-23). None reported any neurological or hearing

impairment. According to self-report using the Edinburgh Handedness Inventory(Oldfield, 1971),
11 were right-handed and one left-handed. All subjects provided written informed consent in ac-
cordance with the University of Maryland Institutional Review Board. Subjects either received
course credit (n=4) or were paid for their participation (n=8). This sample size is comparable to the
most directly relatable previous research which either had a similar number of subjects, N=11
(Donhauser and Baillet, 2020) or a larger number of subjects but substantially less data per subject,
N=28 with single talker stimulus duration 8 min (Brodbeck et al., 2018a).

Stimuli

696 Stimuli consisted in eleven excerpts from the audiobook version of *The Botany of Desire* by *Michael*
697 *Pollan* (Pollan, 2001). Each excerpt was between 210 and 332 seconds long, for a total of 46
698 minutes and 44 seconds. Excerpts were selected to create a coherent narrative and were pre-
699 sented in chronological order to maximize deep processing for meaning.

Procedure

701 During MEG data acquisition, participants lay in a supine position. They were allowed to keep their
702 eyes open or closed to maximize subjective comfort and allow them to focus on the primary task
703 of listening to the audiobook. Stimuli were delivered through foam pad earphones inserted into
704 the ear canal at a comfortably loud listening level. After each segment, participants answered 2-3
705 questions relating to its content and had an opportunity to take a short break.

Data acquisition and preprocessing

Brain responses were recorded with a 157 axial gradiometer whole head MEG system (KIT, Kana-
zawa, Japan) inside a magnetically shielded room (Vacuumschmelze GmbH & Co. KG, Hanau, Ger-
many) at the University of Maryland, College Park. Sensors (15.5 mm diameter) are uniformly dis-
tributed inside a liquid-He dewar, spaced ~25 mm apart, and configured as first-order axial gradi-
ometers with 50 mm separation and sensitivity better than 5 fT·Hz$^{-1/2}$ in the white noise region (>
1 KHz). Data were recorded with an online 200 Hz low-pass filter and a 60 Hz notch filter at a
sampling rate of 1 kHz.

Recordings were pre-processed using mne-python (Gramfort et al., 2014). Flat channels were au-
tomatically detected and excluded. Extraneous artifacts were removed with temporal signal space
separation (Taulu and Simola, 2006). Data were filtered between 1 and 40 Hz with a zero-phase
FIR filter (mne-python 0.20 default settings). Extended infomax independent component analysis
(Bell and Sejnowski, 1995) was then used to remove ocular and cardiac artifacts. Responses time-
locked to the speech stimuli were extracted, low pass filtered at 20 Hz and resampled to 100 Hz.

Five marker coils attached to participants' head served to localize the head position with respect
to the MEG sensors. Head position was measured at the beginning and at the end of the recording
session and the two measurements were averaged. The FreeSurfer (Fischl, 2012) "fsaverage" tem-
plate brain was coregistered to each participant's digitized head shape (Polhemus 3SPACE FAS-
TRAK) using rotation, translation, and uniform scaling. A source space was generated using four-
fold icosahedral subdivision of the white matter surface, with source dipoles oriented perpendic-
ularly to the cortical surface. Regularized minimum ℓ2 norm current estimates (Dale and Sereno,
1993; Hämäläinen and Ilmoniemi, 1994) were computed for all data using an empty room noise

covariance (λ = 1/6). The temporal response function analysis was restricted to brain areas of in-
terest by excluding the occipital lobe, insula and midline structures based on the "aparc" Free-
Surfer parcellation (Desikan et al., 2006). Excluded areas are shaded gray in Figure 4. A preliminary
analysis (see below) was restricted to the temporal lobe (superior, middle and inferior temporal
gyri, Heschl's gyrus and superior temporal sulcus).

Predictor variables

Acoustic model

735   To control for brain responses to acoustic features, all models included an 8 band gammatone
736   spectrogram and an 8 band acoustic onset spectrogram (Brodbeck et al., 2020), both covering
737   frequencies from 20 to 5000 Hz in equivalent rectangular bandwidth (ERB) space (Heeris, 2018)
738   and scaled with exponent 0.6 (Biesmans et al., 2017).

Word- and phoneme segmentation

A pronunciation dictionary was generated by combining the Carnegie-Mellon University pronun-
ciation dictionary with the Montreal Forced Aligner (McAuliffe et al., 2017) dictionary and adding
any additional words that occurred in the stimuli. Transcripts were then aligned to the acoustic
stimuli using the Montreal Forced Aligner (McAuliffe et al., 2017) version 1.0.1. All models included
control predictors for word onsets (equal value impulse at the onset of each word) and phoneme
onsets (equal value impulse at the onset of each non-word initial phoneme).

Context-based predictors

747   All experimental predictor variables consist of one value for each phoneme and were represented
748   as a sequence of impulses at all phoneme onsets. The specific values were derived from three
749   different linguistic context models.

Sublexical context model

The complete SUBTLEX-US corpus (Brysbaert and New, 2009) was transcribed by substituting the
pronunciation for each word and concatenating those pronunciations across word boundaries
(i.e., no silence between words). Each line was kept separate since lines are unordered in the SUB-
TLEX corpus. The resulting phoneme sequences were then used to train a 5-gram model using
KenLM (Heafield, 2011). This 5-gram model was then used to derive phoneme surprisal and en-
tropy.

The surprisal of experiencing phoneme ph_k at time point k is inversely related to the likelihood of
that phoneme, conditional on the context (measured in bits): $I(ph_k) = -log_2(p(ph_k|context))$.
In the case of the 5-phone model this context consists of the preceding 4 phonemes, $ph_{k-4;...k-1}$.

The entropy H (Greek Eta) at phoneme position ph_k reflects the uncertainty of what the next pho-
neme, ph_{k+1} will be. It is defined as the expected (average) surprisal at the next phoneme,
$H_{ph}(ph_k) = -\sum_{ph}^{phonemes} p(ph_{k+1} = ph|context) \log_2(p(ph_{k+1} = ph|context))$.   Based   on
the 5-phone model, the context here is $ph_{k-3;...k}$.

Lexical context model

The lexical context model takes into account information from all phonemes that are in the same
word as, and precede the current phoneme (Brodbeck et al., 2018a) and is based on the cohort
model of word perception (Marslen-Wilson, 1987). At word onset, the prior for each word is pro-
portional to its frequency in the Corpus of Contemporary American English (COCA; Davies, 2015).

With each subsequent phoneme, the probability for words that are inconsistent with that pho-
neme is set to 0, and the remaining distribution is renormalized. Phoneme surprisal and entropy
are then calculated as above, but with the context being all phonemes in the current word so far.
In addition, lexical entropy is calculated at each phoneme position as the entropy in the distribu-
tion of the cohort $H_w(ph_{j,i}) = -\sum_{word}^{lexicon} p(word_j = word|context) \log_2(p(word_j =$
$word|context))$ where j is the index of the word, i is the index of the current phoneme within
word j, and the context consists of phonemes $ph_{j,1;...j,i-1}$.

This level thus allows two different levels of representation, phonemes and words, and two corre-
sponding entropy values, phoneme entropy and lexical entropy. Yet, we only include one version
of surprisal. The reason for this is that calculating surprisal over phonemes or over words leads to
identical results. This is because the kth phoneme of a word, together with the cohort at phoneme
k-1 exhaustively defines the cohort at phoneme k: $p(ph_k|cohort_{k-1}) \equiv p(cohort_k|cohort_{k-1})$.

Sentence context model
The sentence context model was implemented like the lexical context model, but with the addition
of lexical priors based on the 5-gram word context. A 5-gram model was trained on COCA (Davies,
2015) with KenLM (Heafield, 2011). Then, at the onset of each word, the cohort was initialized
with each word's prior set to its probability given the 4 preceding words in the 5-gram model.

Deconvolution
Deconvolution and statistical analysis were performed with Eelbrain (Brodbeck et al., 2021) and
additional scripts available at https://github.com/christianbrodbeck/TRF-Tools.

Multivariate temporal response functions (mTRFs) were computed independently for each subject
and each virtual current source (Brodbeck et al., 2018b; Lalor et al., 2009). The neural response at
time t, y_t was predicted jointly from N predictor time series $x_{i,t}$ convolved with a corresponding
mTRF $h_{i,\tau}$ of length T:

793
$$\hat{y}_t = \sum_i^N \sum_\tau^T h_{n,\tau} \cdot x_{i,t-\tau}$$

mTRFs were generated from a basis of 50 ms wide Hamming windows centered at $T =$
$[-100, ..., 1000)$ ms. For estimating mTRFs, all responses and predictors were standardized by
centering and dividing by the mean absolute value.

For estimation using 4-fold cross-validation, each subject's data were concatenated along the time
axis and split into 4 contiguous segments of equal length. The mTRFs for predicting the responses
in each segment (David et al., 2007) to minimize the $\ell 1$ error. The mTRF was iteratively modified
based on the maximum error reduction in the training set (the steepest coordinate descent) and
validated based on the error in the validation set. Whenever a training step caused an increase of
error in the validation set, the TRF for the predictor responsible for the increase was frozen, and
training continued until the whole mTRF was frozen. The 3 mTRFs from the 3 training runs were
then averaged to predict responses in the left-out testing segment.

Model comparisons

Model quality was quantified through the $\ell 1$ norm of the residuals. For this purpose, the predicted responses for the 4 test segments, each based on mTRFs estimated on the other 3 segments, were concatenated again. To compare the predictive power of two models, the difference in the residuals of the two models was calculated at each virtual source dipole. This difference map was smoothed (Gaussian window, SD = 5 mm) and tested for significance using a mass-univariate one-sample t-test with threshold-free cluster enhancement (TFCE) (Smith and Nichols, 2009) and a null distribution based on the full set of 4095 possible permutations of the 12 difference maps. For effect size comparison we report t_{max}, the largest t-value in the significant ($p \leq .05$) area.

The full model consisted of the following predictors: acoustic spectrogram (8 bands); acoustic on-set spectrogram (8 bands); word onsets; phoneme onsets; sublexical context model (phoneme surprisal and phoneme entropy); lexical context model (phoneme surprisal, phoneme entropy and word entropy); sentence context model (phoneme surprisal, phoneme entropy and word entropy).

For each of the tests reported in Figure 4, mTRFs were re-estimated using a corresponding subset of the predictors in the full model. For instance, to calculate the predictive power for a given level of context, the model was re-fit using all predictors except the predictors of the level under investigation. Each plot thus reflects the variability that can *only* be explained by the level in question. This is generally a conservative estimate for the predictive power because it discounts any explanatory power based on variability that is shared with other predictors. In order to determine the predictive power of linguistic processing in general, we also fit a model excluding all eight information-theoretic predictors from the three levels combined.

To express model fits in a meaningful unit, the explainable variability was estimated through the largest possible explanatory power of the full model (maximum across the brain of the measured response minus residuals, averaged across subjects). All model fits were then expressed as % of this value. For visualization, brain maps are not masked by significance to accurately portray the continuous nature of MEG source estimates.

Tests of lateralization

For spatio-temporal tests of lateralization (Figure 4-A and D) the difference map was first morphed to the symmetric "fsaverage_sym" brain (Greve et al., 2013), and the data from the right hemisphere was morphed to the left hemisphere. Once in this common space, a mass-univariate repeated measures t-test with TFCE was used to compare the difference map from the left and right hemisphere.

ROI analysis

To allow for univariate analyses of predictive power, an ROI was used including a region responsive to all context models (white outline in Figure 4-A). This ROI was defined as the posterior 2/3 of the combined Heschl's gyrus and STG "aparc" label, separately in each hemisphere.

To compare relative lateralization in this ROI (Figure 4-E), the predictive power in each hemisphere's ROI was rectified (values smaller than 0 were set to 0). The lateralization index (LI) was then computed as $LI = RH/(LH + RH)$.

 Tests of localization difference

A direct comparison of two localization maps can have misleading results due to cancellation be-
tween different current sources (Lütkenhöner, 2003) as well as the spatially continuous nature of
MEG source estimates (Bourguignon et al., 2018). However, a test of localization difference is pos-
sible due to the additive nature of current sources (McCarthy and Wood, 1985). Specifically, for a
linear inverse solver as used here, if the relative amplitude of a configuration of current sources is
held constant, the topography of the resulting source localization is also unchanged. Conse-
quently, we employed a test of localization difference that has the null hypothesis that the topog-
raphy of two effect in source space is the same (McCarthy and Wood, 1985). Localization tests
were generally restricted to an area encompassing the major activation seen in Figure 4, based on
"aparc" labels (Desikan et al., 2006): the posterior 2/3 of the superior temporal gyrus and Heschl's
gyrus combined, the superior temporal sulcus, and the middle 3/5 of the middle temporal gyrus.
For each map, the values in this area were extracted and *z*-scored (separately for each hemi-
sphere). For each comparison, the two z-scored maps were subtracted, and the resulting differ-
ence map was analyzed with a one-way repeated measures ANOVA with factor source location
(left hemisphere: 180 sources; right hemisphere: 176 sources). According to the null hypothesis,
the two maps should be (statistically) equal, and the difference map should only contain noise. In
contrast, a significant effect of source location would indicate that the difference map reflects a
difference in topography that is systematic between subjects.

TRF analysis

865 For the analysis of the TRFs, all 12 mTRFs estimated for each subject were averaged (4 test seg-
866 ments * 3 training runs). TRFs were analyzed in the normalized scale that was used for model
867 estimation.

TRF time-course

To extract the time course of response functions, an ROI was generated including all virtual current
sources for which at least one of the three context models significantly improved the response
predictions. To allow a fair comparison between hemispheres, the ROI was made symmetric by
morphing it to the "fsaverage_sym" brain (Greve et al., 2013) and taking the union of the two
hemispheres. With this ROI, the magnitude of the TRFs at each time point was then extracted as
the sum of the absolute current values across source dipoles. These time courses were resampled
from 100 Hz, used for the deconvolution, to 1000 Hz for visualization and for more accurate peak
time extraction. Peak times were determined by finding the maximum value within the early time
window (-50 – 150 ms) for each subject. Time-courses were statistically compared using mass-
univariate related measures *t*-tests, with a null distribution based on the maximum statistic in the
4095 permutations (no cluster enhancement).

TRF-localization

881 To analyze TRF localization, TRF magnitude was quantified as the summed absolute current values
882 in three time-windows, representing early (-50 – 150 ms), mid-latency (150 – 350 ms) and late
883 (350 – 550 ms) responses (see Figure 5). Maps were smoothed (Gaussian window, SD = 5 mm) and
884 tested for localization differences with the same procedure as described above (Tests of localiza-
885 tion difference).

Analysis of trade-off between context models

Several analyses were performed to detect a trade-off between the use of the different context models.

Trade-off by subject

One possible trade-off is between subjects: some subjects might rely on sentence context more than local models, whereas other subjects might rely more on local models. For example, for lexical processing, this hypothesis would predict that for a subject for whom the sentence context model is more predictive, the lexical context model should be less and vice versa. According to this hypothesis, the predictive power of the different context models should be negatively correlated across subjects. To evaluate this, we computed correlations between the predictive power of the different models in the in the mid/posterior STG ROI (see Figure 7-A).

Trade-off over time

A second possible trade-off is across time: subjects might change their response characteristics over time to change the extent to which they rely on the lower- or higher-level context. For example, the depth of processing of meaningful speech might fluctuate with the mental state of alertness. According to this hypothesis, the predictive power of the different context models should be anti-correlated over time. To evaluate this, we calculated the residuals for the different model fits for each time point, $res_t = abs(y_t - \hat{y}_t)$, aggregating by taking the mean in the mid/posterior STG ROI (separately or each subject). The predictive power was calculated for each model by subtracting the residuals of the model from the absolute values of the measured data (i.e., the residuals of a null model without any predictor). The predictive power for each level of context was then computed by subtracting the predictive power of a corresponding reduced model, lacking the given level of context, from the predictive power of the full model. Finally, to reduce the number of data points the predictive power was summed in 1 second bins.

For each subject, the trade-off between each pair of contexts was quantified as the partial correlation (Vallat, 2018) between the predictive power of the two contexts, controlling for the predictive power of the full model (to control for MEG signal quality fluctuations over time). To test for a significant trade-off, a one-sample *t*-test was used for the correlation between each pair of contexts in each hemisphere, with the null hypothesis that the correlation over time is 0 (see Figure 7-B).

References

Altmann G, Steedman M. 1988. Interaction with context during human sentence processing. *Cognition* **30**:191–238. doi:10.1016/0010-0277(88)90020-0

Altmann GTM, Kamide Y. 1999. Incremental interpretation at verbs: restricting the domain of subsequent reference. *Cognition* **73**:247–264. doi:10.1016/S0010-0277(99)00059-1

Auksztulewicz R, Myers NE, Schnupp JW, Nobre AC. 2019. Rhythmic Temporal Expectation Boosts Neural Activity by Increasing Neural Gain. *J Neurosci* **39**:9806–9817. doi:10.1523/JNEUROSCI.0925-19.2019

Beddor PS, McGowan KB, Boland JE, Coetzee AW, Brasher A. 2013. The time course of perception of coarticulation. *J Acoust Soc Am* **133**:2350–2366. doi:10.1121/1.4794366

Bejjanki VR, Clayards M, Knill DC, Aslin RN. 2011. Cue Integration in Categorical Tasks: Insights from
Audio-Visual Speech Perception. *PLOS ONE* **6**:e19812. doi:10.1371/journal.pone.0019812

Bell AJ, Sejnowski TJ. 1995. An Information-Maximization Approach to Blind Separation and Blind
Deconvolution. *Neural Comput* **7**:1129–1159. doi:10.1162/neco.1995.7.6.1129

Biesmans W, Das N, Francart T, Bertrand A. 2017. Auditory-Inspired Speech Envelope Extraction
Methods for Improved EEG-Based Auditory Attention Detection in a Cocktail Party Sce-
nario. *IEEE Trans Neural Syst Rehabil Eng* **25**:402–412. doi:10.1109/TNSRE.2016.2571900

Bourguignon M, Molinaro N, Wens V. 2018. Contrasting functional imaging parametric maps: The
mislocation problem and alternative solutions. *NeuroImage* **169**:200–211.
doi:10.1016/j.neuroimage.2017.12.033

Brodbeck C, Brooks TL, Das P, Reddigari S, Kulasingham JP. 2021. Eelbrain 0.35. Zenodo.
doi:10.5281/zenodo.4650416

Brodbeck C, Hong LE, Simon JZ. 2018a. Rapid Transformation from Auditory to Linguistic Repre-
sentations of Continuous Speech. *Curr Biol* **28**:3976-3983.e5.
doi:10.1016/j.cub.2018.10.042

Brodbeck C, Jiao A, Hong LE, Simon JZ. 2020. Neural speech restoration at the cocktail party: Au-
ditory cortex recovers masked speech of both attended and ignored speakers. *PLOS Biol*
18:e3000883. doi:10.1371/journal.pbio.3000883

Brodbeck C, Presacco A, Simon JZ. 2018b. Neural source dynamics of brain responses to continu-
ous stimuli: Speech processing from acoustics to comprehension. *NeuroImage* **172**:162–
174. doi:10.1016/j.neuroimage.2018.01.042

Broderick MP, Anderson AJ, Liberto GMD, Crosse MJ, Lalor EC. 2018. Electrophysiological Corre-
lates of Semantic Dissimilarity Reflect the Comprehension of Natural, Narrative Speech.
Curr Biol **28**:803-809.e3. doi:10.1016/j.cub.2018.01.080

Brysbaert M, New B. 2009. Moving beyond Kucera and Francis: a critical evaluation of current
word frequency norms and the introduction of a new and improved word frequency meas-
ure for American English. *Behav Res Methods* **41**:977–90. doi:10.3758/BRM.41.4.977

Cairns P, Shillcock R, Chater N, Levy J. 1997. Bootstrapping Word Boundaries: A Bottom-up Corpus-
Based Approach to Speech Segmentation. *Cognit Psychol* **33**:111–153.
doi:10.1006/cogp.1997.0649

Chambers CG, Tanenhaus MK, Magnuson JS. 2004. Actions and affordances in syntactic ambiguity
resolution. *J Exp Psychol-Learn Mem Cogn* **30**:687–696. doi:Doi 10.1037/0278-
7393.30.3.687

Chambers KE, Onishi KH, Fisher C. 2003. Infants learn phonotactic regularities from brief auditory
experience. *Cognition* **87**:B69–B77. doi:10.1016/s0010-0277(02)00233-0

Christiansen MH, Chater N. 2016. The Now-or-Never bottleneck: A fundamental constraint on lan-
guage. *Behav Brain Sci* **39**:e62. doi:10.1017/S0140525X1500031X

Clark A. 2013. Whatever next? Predictive brains, situated agents, and the future of cognitive sci-
ence. *Behav Brain Sci* **36**:181–204. doi:10.1017/S0140525X12000477

Connolly JF, Phillips NA. 1994. Event-Related Potential Components Reflect Phonological and Se-
mantic Processing of the Terminal Word of Spoken Sentences. *J Cogn Neurosci* **6**:256–266.
doi:10.1162/jocn.1994.6.3.256

Coulson S, Federmeier KD, Van Petten C, Kutas M. 2005. Right Hemisphere Sensitivity to Word-
and Sentence-Level Context: Evidence From Event-Related Brain Potentials. *J Exp Psychol*
Learn Mem Cogn **31**:129–147. doi:10.1037/0278-7393.31.1.129

Dale AM, Sereno MI. 1993. Improved Localizadon of Cortical Activity by Combining EEG and MEG
with MRI Cortical Surface Reconstruction: A Linear Approach. *J Cogn Neurosci* **5**:162–176.
doi:10.1162/jocn.1993.5.2.162

David SV, Mesgarani N, Shamma SA. 2007. Estimating sparse spectro-temporal receptive fields
with natural stimuli. *Netw Comput Neural Syst* **18**:191–212.
doi:10.1080/09548980701609235

Davies M. 2015. Corpus of Contemporary American English (COCA). doi:10.7910/DVN/AMUDUW

DeLong KA, Urbach TP, Kutas M. 2005. Probabilistic word pre-activation during language compre-
hension inferred from electrical brain activity. *Nat Neurosci* **8**:1117–1121.
doi:10.1038/nn1504

Desikan RS, Ségonne F, Fischl B, Quinn BT, Dickerson BC, Blacker D, Buckner RL, Dale AM, Maguire
RP, Hyman BT, Albert MS, Killiany RJ. 2006. An automated labeling system for subdividing
the human cerebral cortex on MRI scans into gyral based regions of interest. *NeuroImage*
31:968–980. doi:10.1016/j.neuroimage.2006.01.021

Diaz MT, Swaab TY. 2007. Electrophysiological differentiation of phonological and semantic inte-
gration in word and sentence contexts. *Brain Res* **1146**:85–100.
doi:10.1016/j.brainres.2006.07.034

Donhauser PW, Baillet S. 2020. Two Distinct Neural Timescales for Predictive Speech Processing.
Neuron **105**:385-393.e9. doi:10.1016/j.neuron.2019.10.019

Ettinger A, Linzen T, Marantz A. 2014. The role of morphology in phoneme prediction: Evidence
from MEG. *Brain Lang* **129**:14–23. doi:10.1016/j.bandl.2013.11.004

Federmeier KD. 2007. Thinking ahead: The role and roots of prediction in language comprehen-
sion. *Psychophysiology* **44**:491–505. doi:10.1111/j.1469-8986.2007.00531.x

Federmeier KD, Kutas M. 1999. Right words and left words: electrophysiological evidence for hem-
ispheric differences in meaning processing. *Cogn Brain Res* **8**:373–392. doi:10.1016/S0926-
6410(99)00036-1

Federmeier KD, Mai H, Kutas M. 2005. Both sides get the point: Hemispheric sensitivities to sen-
tential constraint. *Mem Cognit* **33**:871–886. doi:10.3758/BF03193082

Federmeier KD, Wlotko EW, Meyer AM. 2008. What's 'Right' in Language Comprehension: Event-
Related Potentials Reveal Right Hemisphere Language Capabilities. *Lang Linguist Compass*
2:1–17. doi:https://doi.org/10.1111/j.1749-818X.2007.00042.x

Feldman NH, Griffiths TL, Morgan JL. 2009. The influence of categories on perception: Explaining
the perceptual magnet effect as optimal statistical inference. *Psychol Rev* **116**:752–782.
doi:10.1037/a0017196

Ferreira F, Chantavarin S. 2018. Integration and Prediction in Language Processing: A Synthesis of
Old and New. *Curr Dir Psychol Sci* **27**:443–448. doi:10.1177/0963721418794491

Fischl B. 2012. FreeSurfer. *NeuroImage*, 20 YEARS OF fMRI20 YEARS OF fMRI **62**:774–781.
doi:10.1016/j.neuroimage.2012.01.021

Fodor JA. 1985. Précis of The Modularity of Mind. *Behav Brain Sci* **8**:1–5.
doi:10.1017/S0140525X0001921X

Forseth KJ, Hickok G, Rollo PS, Tandon N. 2020. Language prediction mechanisms in human audi-
tory cortex. *Nat Commun* **11**:5240. doi:10.1038/s41467-020-19010-6

Frisson S, Harvey DR, Staub A. 2017. No prediction error cost in reading: Evidence from eye move-
ments. *J Mem Lang* **95**:200–214. doi:10.1016/j.jml.2017.04.007

Friston KJ. 2010. The free-energy principle: a unified brain theory? *Nat Rev Neurosci* **11**:127–138.
doi:10.1038/nrn2787

Futrell R, Gibson E, Levy RP. 2020. Lossy-Context Surprisal: An Information-Theoretic Model of
Memory Effects in Sentence Processing. *Cogn Sci* **44**. doi:10.1111/cogs.12814

Gagnepain P, Henson RN, Davis MH. 2012. Temporal Predictive Codes for Spoken Words in Audi-
tory Cortex. *Curr Biol* **22**:615–621. doi:10.1016/j.cub.2012.02.015

Ganong WF. 1980. Phonetic categorization in auditory word perception. *J Exp Psychol Hum Percept*
Perform **6**:110–125. doi:10.1037/0096-1523.6.1.110

Gaston P, Lau E, Phillips C. 2020. How does(n't) syntactic context guide auditory word recognition?
doi:10.31234/osf.io/sbxpn

Gaston P, Marantz A. 2017. The time course of contextual cohort effects in auditory processing of
category-ambiguous words: MEG evidence for a single "clash" as noun or verb. *Lang Cogn*
Neurosci **33**:402–423. doi:10.1080/23273798.2017.1395466

Gazzaniga MS, Sperry RW. 1967. Language after section of the cerebral commissures. *Brain J Neu-*
rol **90**:131–148. doi:10.1093/brain/90.1.131

Gillis M, Vanthornhout J, Simon JZ, Francart T, Brodbeck C. 2021. Neural markers of speech com-
prehension: measuring EEG tracking of linguistic speech representations, controlling the
speech acoustics. *J Neurosci*. doi:10.1523/JNEUROSCI.0812-21.2021

Gramfort A, Luessi M, Larson E, Engemann DA, Strohmeier D, Brodbeck C, Parkkonen L, Hämä-
läinen MS. 2014. MNE software for processing MEG and EEG data. *NeuroImage* **86**:446–
460. doi:10.1016/j.neuroimage.2013.10.027

Greve DN, Van der Haegen L, Cai Q, Stufflebeam S, Sabuncu MR, Fischl B, Brysbaert M. 2013. A
Surface-based Analysis of Language Lateralization and Cortical Asymmetry. *J Cogn Neurosci*
25:1477–1492. doi:10.1162/jocn_a_00405

Gwilliams L, Marantz A. 2015. Non-linear processing of a linear speech stream: The influence of
morphological structure on the recognition of spoken Arabic words. *Brain Lang* **147**:1–13.
doi:10.1016/j.bandl.2015.04.006

Hale J. 2003. The Information Conveyed by Words in Sentences. *J Psycholinguist Res* **32**:101–123.
doi:10.1023/A:1022492123056

Hale JT. 2016. Information-theoretical Complexity Metrics. *Lang Linguist Compass* **10**:397–412.
doi:10.1111/lnc3.12196

Halle M, Stevens K. 1962. Speech recognition: A model and a program for research. *IRE Trans Inf*
Theory **8**:155–159. doi:10.1109/TIT.1962.1057686

Hämäläinen MS, Ilmoniemi RJ. 1994. Interpreting magnetic fields of the brain: minimum norm es-
timates. *Med Biol Eng Comput* **32**:35–42. doi:10.1007/BF02512476

Harris ZS. 1955. From Phoneme to Morpheme. *Language* **31**:190. doi:10.2307/411036

Heafield K. 2011. KenLM: Faster and Smaller Language Model QueriesProceedings of the 6th
Workshop on Statistical Machine Translation. Edinburgh, Scotland, UK. pp. 187–197.

Heeris J. 2018. Gammatone Filterbank Toolkit.

Heller D, Parisien C, Stevenson S. 2016. Perspective-taking behavior as the probabilistic weighing
of multiple domains. *Cognition* **149**:104–120. doi:10.1016/j.cognition.2015.12.008

Hickok G, Poeppel D. 2007. The cortical organization of speech processing. *Nat Rev Neurosci*
8:393–402. doi:10.1038/nrn2113

Hitczenko K, Mazuka R, Elsner M, Feldman NH. 2020. When context is and isn't helpful: A corpus
study of naturalistic speech. *Psychon Bull Rev* **27**:640–676. doi:10.3758/s13423-019-
01687-6

Holcomb PJ, Neville HJ. 1991. Natural speech processing: An analysis using event-related brain
potentials. *Psychobiology* **19**:286–300. doi:10.3758/BF03332082

Huettig F. 2015. Four central questions about prediction in language processing. *Brain Res*
1626:118–135. doi:10.1016/j.brainres.2015.02.014

Jaramillo S, Zador AM. 2011. The auditory cortex mediates the perceptual effects of acoustic tem-
poral expectation. *Nat Neurosci* **14**:246–251. doi:10.1038/nn.2688

Jung-Beeman M. 2005. Bilateral brain processes for comprehending natural language. *Trends*
Cogn Sci **9**:512–518. doi:10.1016/j.tics.2005.09.009

Jurafsky D. 1996. A Probabilistic Model of Lexical and Syntactic Access and Disambiguation. *Cogn*
Sci **20**:137–194. doi:10.1207/s15516709cog2002_1

Kutas M, Hillyard SA, Gazzaniga MS. 1988. Processing of Semantic Anomaly by Right and Left Hem-
ispheres of Commissurotomy Patients: Evidence from Event-Related Brain Potentials. *Brain*
111:553–576. doi:10.1093/brain/111.3.553

Lalor EC, Power AJ, Reilly RB, Foxe JJ. 2009. Resolving Precise Temporal Processing Properties of
the Auditory System Using Continuous Stimuli. *J Neurophysiol* **102**:349–359.
doi:10.1152/jn.90896.2008

Leonard MK, Baud MO, Sjerps MJ, Chang EF. 2016. Perceptual restoration of masked speech in
human cortex. *Nat Commun* **7**:13619. doi:10.1038/ncomms13619

Levy R. 2008. Expectation-based syntactic comprehension. *Cognition* **106**:1126–1177.
doi:10.1016/j.cognition.2007.05.006

Loftus GR, Masson MEJ. 1994. Using confidence intervals in within-subject designs. *Psychon Bull*
Rev **1**:476–490. doi:10.3758/BF03210951

Luke SG, Christianson K. 2016. Limits on lexical prediction during reading. *Cognit Psychol* **88**:22–
60. doi:10.1016/j.cogpsych.2016.06.002

Luthra S, Peraza-Santiago G, Beeson K, Saltzman D, Crinnion AM, Magnuson JS. 2021. Robust Lex-
ically Mediated Compensation for Coarticulation: Christmash Time Is Here Again. *Cogn Sci*
45. doi:10.1111/cogs.12962

Lütkenhöner B. 2003. Magnetoencephalography and its Achilles' heel. *J Physiol-Paris* **97**:641–658.
doi:10.1016/j.jphysparis.2004.01.020

Magnuson JS, Mirman D, Luthra S, Strauss T, Harris HD. 2018. Interaction in Spoken Word Recog-
nition Models: Feedback Helps. *Front Psychol* **9**:369. doi:10.3389/fpsyg.2018.00369

Marslen-Wilson W, Tyler LK. 1975. Processing structure of sentence perception. *Nature* **257**:784–
786. doi:10.1038/257784a0

Marslen-Wilson WD. 1987. Functional parallelism in spoken word-recognition. *Cognition*, Special
Issue Spoken Word Recognition **25**:71–102. doi:10.1016/0010-0277(87)90005-9

Matchin W, Brodbeck C, Hammerly C, Lau E. 2018. The temporal dynamics of structure and con-
tent in sentence comprehension: Evidence from fMRI-constrained MEG. *Hum Brain Mapp*
40:663–678. doi:10.1002/hbm.24403
McAuliffe M, Socolof M, Mihuc S, Wagner M, Sonderegger M. 2017. Montreal Forced Aligner:
Trainable Text-Speech Alignment Using KaldiInterspeech 2017. Presented at the Inter-
speech 2017. ISCA. pp. 498–502. doi:10.21437/Interspeech.2017-1386
McCarthy G, Wood CC. 1985. Scalp Distributions of Event-Related Potentials - an Ambiguity Asso-
ciated with Analysis of Variance Models. *Electroencephalogr Clin Neurophysiol* **61**:S226–
S227. doi:10.1016/0013-4694(85)90858-2
McClelland JL, Elman JL. 1986. The TRACE model of speech perception. *Cognit Psychol* **18**:1–86.
doi:10.1016/0010-0285(86)90015-0
McClelland JL, Rumelhart DE. 1981. An interactive activation model of context effects in letter
perception: I. An account of basic findings. *Psychol Rev* **88**:375–407. doi:10.1037/0033-
295X.88.5.375
Mesgarani N, Cheung C, Johnson K, Chang EF. 2014. Phonetic feature encoding in human superior
temporal gyrus. *Science* **343**:1006–1010. doi:10.1126/science.1245994
Morton J. 1969. Interaction of information in word recognition. *Psychol Rev* **76**:165–178.
doi:10.1037/h0027366
Nieuwland MS, Barr DJ, Bartolozzi F, Busch-Moreno S, Darley E, Donaldson DI, Ferguson HJ, Fu X,
Heyselaar E, Huettig F, Matthew Husband E, Ito A, Kazanina N, Kogan V, Kohút Z, Kulakova
E, Mézière D, Politzer-Ahles S, Rousselet G, Rueschemeyer S-A, Segaert K, Tuomainen J,
Von Grebmer Zu Wolfsthurn S. 2020. Dissociable effects of prediction and integration dur-
ing language comprehension: evidence from a large-scale study using brain potentials.
Philos Trans R Soc B Biol Sci **375**:20180522. doi:10.1098/rstb.2018.0522
Nieuwland MS, Politzer-Ahles S, Heyselaar E, Segaert K, Darley E, Kazanina N, Von Grebmer Zu
Wolfsthurn S, Bartolozzi F, Kogan V, Ito A, Mézière D, Barr DJ, Rousselet GA, Ferguson HJ,
Busch-Moreno S, Fu X, Tuomainen J, Kulakova E, Husband EM, Donaldson DI, Kohút Z,
Rueschemeyer S-A, Huettig F. 2018. Large-scale replication study reveals a limit on proba-
bilistic prediction in language comprehension. *eLife* **7**:e33468. doi:10.7554/eLife.33468
Nieuwland MS, Van Berkum JJA. 2006. When peanuts fall in love: N400 evidence for the power of
discourse. *J Cogn Neurosci* **18**:1098–111. doi:10.1162/jocn.2006.18.7.1098
Norris D. 1994. Shortlist: a connectionist model of continuous speech recognition. *Cognition*
52:189–234. doi:10.1016/0010-0277(94)90043-4
Norris D, McQueen JM. 2008. Shortlist B: A Bayesian model of continuous speech recognition.
Psychol Rev **115**:357–395. doi:10.1037/0033-295X.115.2.357
Norris D, McQueen JM, Cutler A. 2016. Prediction, Bayesian inference and feedback in speech
recognition. *Lang Cogn Neurosci* **31**:4–18. doi:10.1080/23273798.2015.1081703
Norris D, McQueen JM, Cutler A. 2000. Merging information in speech recognition: Feedback is
never necessary. *Behav Brain Sci* **23**:299–325. doi:10.1017/S0140525X00003241
Oldfield RC. 1971. The assessment and analysis of handedness: The Edinburgh inventory. *Neuro-
psychologia* **9**:97–113. doi:10.1016/0028-3932(71)90067-4
Pickering MJ, Gambi C. 2018. Predicting while comprehending language: A theory and review. *Psy-
chol Bull* **144**:1002–1044. doi:10.1037/bul0000158

Poeppel D. 2001. Pure word deafness and the bilateral processing of the speech code. *Cogn Sci*
25:679–693. doi:10.1207/s15516709cog2505_3

Pollan M. 2001. The Botany of Desire: A Plant's-Eye View of the World. Random House Publishing
Group.

Rommers J, Meyer AS, Praamstra P, Huettig F. 2013. The contents of predictions in sentence com-
prehension: Activation of the shape of objects before they are referred to. *Neuropsycho-*
logia **51**:437–447. doi:10.1016/j.neuropsychologia.2012.12.002

Saffran JR, Aslin RN, Newport EL. 1996. Statistical Learning by 8-Month-Old Infants. *Science*
274:1926–1928. doi:10.1126/science.274.5294.1926

Salverda AP, Dahan D, McQueen JM. 2003. The role of prosodic boundaries in the resolution of
lexical embedding in speech comprehension. *Cognition* **90**:51–89. doi:10.1016/S0010-
0277(03)00139-2

Schmitt L-M, Erb J, Tune S, Rysop A, Hartwigsen G, Obleser J. 2020. Predicting speech from a cor-
tical hierarchy of event-based timescales. *bioRxiv* 2020.12.19.423616.
doi:10.1101/2020.12.19.423616

Singer Y, Teramoto Y, Willmore BD, Schnupp JW, King AJ, Harper NS. 2018. Sensory cortex is opti-
mized for prediction of future input. *eLife* **7**. doi:10.7554/eLife.31557

Smith NJ, Levy R. 2013. The effect of word predictability on reading time is logarithmic. *Cognition*
128:302–319. doi:10.1016/j.cognition.2013.02.013

Smith SM, Nichols TE. 2009. Threshold-free cluster enhancement: Addressing problems of
smoothing, threshold dependence and localisation in cluster inference. *NeuroImage*
44:83–98. doi:10.1016/j.neuroimage.2008.03.061

Sohoglu E, Davis MH. 2020. Rapid computations of spectrotemporal prediction error support per-
ception of degraded speech. *eLife* **9**:e58077. doi:10.7554/eLife.58077

Swinney DA. 1979. Lexical access during sentence comprehension: (Re)consideration of context
effects. *J Verbal Learn Verbal Behav* **18**:645–659. doi:10.1016/S0022-5371(79)90355-4

Tabas A, von Kriegstein K. 2021. Adjudicating Between Local and Global Architectures of Predictive
Processing in the Subcortical Auditory Pathway. *Front Neural Circuits* **15**.
doi:10.3389/fncir.2021.644743

Tanenhaus MK, Spivey-Knowlton MJ, Eberhard KM, Sedivy JC. 1995. Integration of visual and lin-
guistic information in spoken language comprehension. *Science* **268**:1632–1634.
doi:10.1126/science.7777863

Taulu S, Simola J. 2006. Spatiotemporal signal space separation method for rejecting nearby inter-
ference in MEG measurements. *Phys Med Biol* **51**:1759. doi:10.1088/0031-9155/51/7/008

Vallat R. 2018. Pingouin: statistics in Python. *J Open Source Softw* **3**:1026. doi:10.21105/joss.01026

Van Berkum JJA, Brown CM, Zwitserlood P, Kooijman V, Hagoort P. 2005. Anticipating Upcoming
Words in Discourse: Evidence From ERPs and Reading Times. *J Exp Psychol Learn Mem*
Cogn **31**:443–467. doi:10.1037/0278-7393.31.3.443

van Berkum JJA, Zwitserlood P, Hagoort P, Brown CM. 2003. When and how do listeners relate a
sentence to the wider discourse? Evidence from the N400 effect. *Cogn Brain Res* **17**:701–
718. doi:10.1016/S0926-6410(03)00196-4

Van Petten C, Coulson S, Rubin S, Plante E, Parks M. 1999. Time course of word identification and
semantic integration in spoken language. *J Exp Psychol Learn Mem Cogn* **25**:394–417.
doi:10.1037//0278-7393.25.2.394

Vitevitch MS, Luce PA. 1999. Probabilistic Phonotactics and Neighborhood Activation in Spoken
1184   Word Recognition. *J Mem Lang* **40**:374–408. doi:10.1006/jmla.1998.2618

1185   Vitevitch MS, Luce PA. 1998. When Words Compete: Levels of Processing in Perception of Spoken
1186   Words. *Psychol Sci* **9**:325–329. doi:10.1111/1467-9280.00064

1187   Waskom M. 2021. seaborn: statistical data visualization. Zenodo. doi:10.5281/zenodo.4645478

1188   Weissbart H, Kandylaki KD, Reichenbach T. 2020. Cortical Tracking of Surprisal during Continuous
1189   Speech Comprehension. *J Cogn Neurosci* **32**:155–166. doi:10.1162/jocn_a_01467

1190   Willems RM, Frank SL, Nijhof AD, Hagoort P, van den Bosch A. 2016. Prediction During Natural
1191   Language Comprehension. *Cereb Cortex* **26**:2506–2516. doi:10.1093/cercor/bhv075

1192   Wilson SM, Bautista A, McCarron A. 2018. Convergence of spoken and written language processing
1193   in the superior temporal sulcus. *NeuroImage* **171**:62–74. doi:10.1016/j.neu-
1194   roimage.2017.12.068

1195   Wlotko EW, Federmeier KD. 2007. Finding the right word: Hemispheric asymmetries in the use of
1196   sentence context information. *Neuropsychologia* **45**:3001–3014. doi:10.1016/j.neuropsy-
1197   chologia.2007.05.013

1198   Zwitserlood P. 1989. The locus of the effects of sentential-semantic context in spoken-word pro-
1199   cessing. *Cognition* **32**:25–64. doi:10.1016/0010-0277(89)90013-9

1200