A Distributed Network for Multimodal Experiential Representation of Concepts

Jia-Qing Tong[1,2], Jeffrey R. Binder[1,2], Colin J. Humphries[1], Stephen Mazurchuk[1,2], Lisa L.

Conant[1], Leonardo Fernandino[1,3]

[1]Department of Neurology, Medical College of Wisconsin, Milwaukee, WI, USA

[2]Department of Biophysics, Medical College of Wisconsin, Milwaukee, WI, USA

[3]Department of Biomedical Engineering, Medical College of Wisconsin and Marquette

University, Milwaukee, WI, USA

Abbreviated title: Multimodal Concept Representation

Corresponding Author:

Leonardo Fernandino, Ph.D.

Department of Neurology

Medical College of Wisconsin

8701 W Watertown Plank Rd, Milwaukee, WI 53226

Email: lfernandino@mcw.edu

Office Phone: 414-955-7388

Key words: semantics, concept representation, representational similarity analysis, fMRI

Pages: 33

Figures: 4

Tables: 1

Extended Data Figures: 2

Financial interests or conflicts of interest: None.

Acknowledgements:

This work was supported by National Institute on Deafness and Other Communication Disorders

(NIDCD) grant R01 DC016622, by the Intelligence Advanced Research Projects Activity under

Grant FA8650-14-C-7357, and by a grant from the Advancing a Healthier Wisconsin Foundation

(Project #5520462). The authors thank Volkan Arpinar, Elizabeth Awe, Joseph Heffernan,

Steven Jankowski, Jedidiah Mathis, and Megan LeDoux for technical assistance, as well as

three anonymous reviewers for helpful comments and suggestions on a previous version of this

article.

Abstract

Neuroimaging, neuropsychological, and psychophysical evidence indicates that concept

retrieval selectively engages specific sensory and motor brain systems involved in the

acquisition of the retrieved concept. However, it remains unclear which supramodal cortical

regions contribute to this process and what kind of information they represent. Here, we used

representational similarity analysis of two large fMRI data sets, with a searchlight approach, to

generate a detailed map of human brain regions where the semantic similarity structure across

individual lexical concepts can be reliably detected. We hypothesized that heteromodal cortical

areas typically associated with the "default mode network" encode multimodal experiential

information about concepts, consistent with their proposed role as convergence-divergence

zones. In two studies involving different sets of concepts and different participants (both sexes),

we found a distributed, bihemispheric network engaged in concept representation, composed of

high-level association areas in the anterior, lateral, and ventral temporal lobe; inferior parietal

lobule; posterior cingulate gyrus and precuneus; and medial, dorsal, ventrolateral, and orbital

prefrontal cortex. In both studies, a multimodal model combining sensory, motor, affective, and

other types of experiential information explained significant variance in the neural similarity

structure observed in these regions that was not explained by unimodal experiential models or

by distributional semantics (i.e., word2vec similarity). These results indicate that, during concept

retrieval, lexical concepts are represented across a vast expanse of high-level cortical regions,

especially in the areas that make up the default mode network, and that these regions encode

multimodal experiential information.

Significance Statement

Conceptual knowledge includes information acquired through various modalities of experience,

such as visual, auditory, tactile, and emotional information. We investigated which brain regions

encode mental representations that combine information from multiple modalities when

participants think about the meaning of a word. We found that such representations are

encoded across a widely distributed network of cortical areas in both hemispheres, including

temporal, parietal, limbic, and prefrontal association areas. Several areas not traditionally

associated with semantic cognition were also implicated. Our results indicate that the retrieval of

conceptual knowledge during word comprehension relies on a much larger portion of the

cerebral cortex than previously thought, and that multimodal experiential information is

represented throughout the entire network.

Introduction

Conceptual knowledge is essential for everyday thinking, planning, and communication, yet

few details are known about where and how it is implemented in the brain. Assessments of

patients with brain lesions have shown that deficits in the retrieval and use of conceptual

knowledge can result from damage to parietal, temporal, or frontal cortical areas (Warrington

and Shallice, 1984; Gainotti, 2000; Neininger and Pulvermüller, 2003; Damasio et al., 2004).

Such neuropsychological findings have been extended by functional neuroimaging studies,

which implicate a set of heteromodal cortical regions including the angular gyrus, the anterior,

lateral, and ventral aspects of the temporal lobe, the inferior and superior frontal gyri, and the

precuneus/posterior cingulate gyrus, all showing stronger activations in the left hemisphere

(Binder et al., 2009; Hodgson et al., 2021). However, there is still debate on whether some of

these areas – particularly the angular gyrus, the superior frontal gyrus, and the

precuneus/posterior cingulate – are indeed involved in processing conceptual representations. It

has been suggested, for example, that confounding factors such as task difficulty may be

responsible for the angular gyrus activations found in the aforementioned studies (Humphreys

et al., 2021).

Functional MRI (fMRI) studies also show that, in addition to these heteromodal areas,

cortical areas involved in perceptual and motor processing are selectively activated when

concepts related to the corresponding sensory-motor aspects of experience are retrieved

(Meteyard and Vigliocco, 2008; Binder and Desai, 2011; Kiefer and Pulvermüller, 2012;

Kemmerer, 2014). These findings are in agreement with "grounded" theories of concept

representation, which predict that sensory-motor and affective representations involved in

concept formation are re-activated during concept retrieval (Damasio, 1989; Barsalou, 2008;

Glenberg et al., 2009).

Various models propose a central role for multimodal or supramodal hubs in concept

processing, though both the anatomical location and information content encoded in these hubs

remain unclear (Mahon and Caramazza, 2008; Binder and Desai, 2011; Lambon-Ralph et al.,

2017). One prominent theory postulates widespread and hierarchically organized convergence

zones in multiple brain locations (Damasio, 1989; Mesulam, 1998; Meyer and Damasio, 2009).

We previously proposed (Fernandino et al., 2016a) that these convergence zones are neurally

implemented in the multimodal connectivity hubs identified with the "default mode network"

(DMN) (Buckner et al., 2009; Sepulcre et al., 2012; Margulies et al., 2016). These areas closely

correspond to those identified in a neuroimaging meta-analysis of semantic word processing

(Binder et al., 2009). This idea is further supported by neuroimaging findings suggesting that the

precuneus, posterior cingulate gyrus, angular gyrus, dorsomedial and ventrolateral prefrontal

cortex, and lateral temporal areas encode multimodal information about the sensory-motor

content of concepts (Bonner et al., 2013; Fernandino et al., 2016a, 2016b, 2022; Murphy et al.,

2018).

In the present study, we used representational similarity analysis (RSA) with a whole-brain

searchlight approach to identify cortical regions involved in multimodal conceptual

representation. For a given set of stimuli (e.g., words), RSA measures the level of

correspondence between the similarity structure (i.e., the set of all possible pairwise similarity

distances) observed in the stimulus-related multivoxel activation patterns and the similarity

structure for the same stimuli computed from an *a priori* representational model (Kriegeskorte et

al., 2008). In contrast to previous RSA studies of concept representation, which used models

based on taxonomic relations or word-co-occurrence statistics (Bruffaerts et al., 2013; Devereux

et al., 2013; Anderson et al., 2015; Liuzzi et al., 2015; Martin et al., 2018; Carota et al., 2021),

we used an experiential model of conceptual content based on 65 sensory, motor, affective, and

other experiential dimensions (Binder et al., 2016). We used a searchlight approach

(Kriegeskorte et al., 2006; Kriegeskorte and Bandettini, 2007) to generate a map of cortical

regions where this multimodal experiential model predicted the neural similarity structure of

hundreds of lexical concepts. Identical analyses were conducted on two large datasets to

assess replication across different word sets and participant samples.

Materials and Methods

Participants

Participants in Experiment 1 were 39 right-handed, native English speakers (21 women, 18

men; mean age = 28.7; range: 20-41). Experiment 1 included data from 36 participants used in

Fernandino et al. (2022), with 3 new participants added. Participants in Experiment 2 were 25

native English speakers 20 women, 5 men; mean age = 26; range: 19-40). None of the

participants in Experiment 2 took part in Experiment 1. All participants in Experiments 1 and 2

were right-handed according to the Edinburgh handedness inventory (Oldfield, 1971) and had

no history of neurological disease. Participants were compensated for their time and gave

informed consent in conformity with a protocol approved by the Institutional Review Board of the

Medical College of Wisconsin.

Stimuli

The stimulus set used in Experiment 1 is described in detail in Fernandino et al. (2022). It

consisted of 160 object nouns (40 each of animals, foods, tools, and vehicles) and 160 event

nouns (40 each of social events, verbal events, non-verbal sound events, and negative events;

mean length = 7.0 letters, mean log HAL frequency = 7.61). Stimuli in Experiment 2 consisted of

300 nouns (50 each of animals, body parts, food/plants, human traits, quantities, and tools;

mean length = 6.3 letters, mean log HAL frequency = 7.83), 98 of which were also used in

Experiment 1.

Experiential Concept Features

Experiential representations for these words were available from a previous study in which

ratings on 65 experiential domains were used to represent word meanings in a high-dimensional

space (Binder et al., 2016). In brief, the experiential domains were selected based on known

neural processing systems – such as color, shape, visual motion, touch, audition, motor control,

olfaction – as well as other fundamental aspects of experience whose neural substrates are less

clearly understood, such as space, time, affect, reward, numerosity, and others. Ratings were

collected using the crowd sourcing tool Amazon Mechanical Turk, in which volunteers rated the

relevance of each experiential domain to a given concept on a 0-6 Likert scale. The value of

each feature was represented by averaging ratings across participants. This feature set was

highly effective at clustering concepts into canonical taxonomic categories (e.g., animals, plants,

vehicles, occupations, etc.; Binder et al., 2016) and has been used successfully to decode fMRI

activation patterns during sentence reading (Anderson et al., 2017, 2019).

Procedures

In both experiments, words were presented visually in a fast event-related procedure with

variable inter-stimulus intervals. The entire list was presented to each participant six times in a

different pseudorandom order across 3 separate imaging sessions (2 presentations per session)

on separate days.

On each trial, a noun was displayed in white font on a black background for 500 ms,

followed by a 2.5-second blank screen. Each trial was followed by a central fixation cross with

variable duration between 1 and 3 s (mean = 1.5 s). Participants rated each noun according to

how often they encountered the corresponding entity or event in their daily lives, on a scale from

1 ("rarely or never") to 3 ("often"). This familiarity judgment task was designed to encourage

semantic processing of the word stimuli without emphasizing any particular semantic features or

dimensions. Participants indicated their response by pressing one of three buttons on a

response pad with their right hand. Stimulus presentation and response recording were

performed with Psychopy 3 software (Peirce, 2007) running on a Windows desktop computer

and a Celeritas fiber optic response system (Psychology Software Tools, Inc.). Stimuli were

displayed on an MRI-compatible LCD screen positioned behind the scanner bore and viewed

through a mirror attached to the head coil.

MRI Data Acquisition and Processing

Images were acquired with a 3T GE Premier scanner at the Medical College of Wisconsin.

Structural imaging included a T1-weighted MPRAGE volume (FOV = 256 mm, 222 axial slices,

voxel size = 0.8 x 0.8 x 0.8 mm^3) and a T2-weighted CUBE acquisition (FOV = 256 mm, 222

sagittal slices, voxel size = 0.8 x 0.8 x 0.8 mm^3). T2*-weighted gradient-echo echoplanar images

were obtained for functional imaging using a simultaneous multi-slice sequence (SMS factor =

4, TR = 1500 ms, TE = 33 ms, flip angle = 50°, FOV = 208 mm, 72 axial slices, in-plane matrix =

104 x 104, voxel size = 2 x 2 x 2 mm^3). A pair of T2-weighted spin echo echo-planar scans (5

volumes each) with opposing phase-encoding directions was acquired before run 1, between

runs 4 and 5, and after run 8, to provide estimates of EPI geometric distortion in the phase-

encoding direction.

Data preprocessing was performed using fMRIPrep 20.1.0 (Esteban et al., 2018). After slice

timing correction, functional images were corrected for geometric distortion, which implemented

non-linear transformations estimated from the paired T2-weighted spin echo images. All images

were then aligned to correct for head motion before aligning to the T1-weighted anatomical

image. All voxels were normalized to have a mean of 100 and a range of 0 to 200. To optimize

alignment between participants and to constrain the searchlight analysis to cortical grey matter,

individual brain surface models were constructed from T1-weighted and T2-weighted anatomical

data using Freesurfer and the HCP pipeline (Glasser et al., 2013). We visually checked the

quality of reconstructed surfaces before carrying out the analysis. Segmentation errors were

corrected manually, and the corrected images were fed back to the pipeline to produce the final

surfaces. The cortex ribbon was reconstructed in standard grayordinate space with 2-mm

spaced vertices, and the EPI images were projected onto this space. A general linear model

was built to fit the time series of the functional data via multivariable regression. Each word (with

its six presentations) was treated as a single regressor of interest and convolved with a

hemodynamic response function, resulting in 320 (Experiment 1) or 300 (Experiment 2) beta

coefficient maps. Regressors of no interest included head motion parameters (12 regressors),

response time (z-scores), mean white matter signal, and mean cerebrospinal fluid signal. A *t*

statistical map was generated for each word, and these maps were subsequently used in the

searchlight RSA.

Surface-Based Searchlight Representational Similarity Analysis

RSA was carried out using custom Python and Matlab scripts. Searchlight RSA typically

employs spherical volumes moved systematically through the brain or the cortical grey matter

voxels. This method, however, does not exclude signals from white matter voxels that happen to

fall within the sphere, and which may contribute noise. Spherical volumes may also erroneously

combine non-contiguous cortical regions across sulci. Surface-based searchlight analysis

overcomes these shortcomings using circular 2-dimensional "patches" confined to contiguous

vertices on the cortical surface. At each vertex, a 5-mm radius patch around the seed vertex on

the midthickness surface was created, resulting in a group of vertices comprising each patch.

Representational dissimilarity matrices (RDMs) were calculated for the multimodal

experiential model (the model RDM) and for each searchlight ROI (the neural RDM). Each entry

in the neural RDM represented the correlation distance between fMRI responses evoked by two

different words. Neural RDMs were computed for each of the 64,984 searchlight ROIs. For the

model RDM, we calculated the Pearson correlation distances between each pair of words in the

65-dimensional experiential feature space. Ten additional RDMs were computed using pair-wise

differences on non-semantic lexical variables, namely, number of letters, number of phonemes,

number of syllables, mean bigram frequency, mean trigram frequency, orthographic

neighborhood density, phonological neighborhood density, phonotactic probability for single

phonemes, phonotactic probability for phoneme pairs, and word frequency

(https://www.sc.edu/study/colleges_schools/artsandsciences/psychology/research_clinical_facili

ties/scope/). These RDMs were regressed out of the model-based RDM prior to computing the

RSA correlations to remove any effects of orthographic and phonological similarity. An RDM

computed from the Jaccard distance between bitmap images of the word stimuli was also used

to control for low-level visual similarity between words. Spearman correlations were computed

between the residual model-based RDM (after regressing out the RDMs of no interest) and the

neural RDM for each ROI, resulting in a map of correlation scores on the cortical surface for

each participant.

Finally, second-level analysis was performed on the correlation score maps after alignment

of each individual map to a common surface template (the 32k_FS_LR mesh produced by the

HCP pipeline), Fisher z-transformation, and smoothing of the maps with a 6-mm FWHM

Gaussian kernel. A one-tailed, one-sample t-test against zero was applied at all vertices. FSL's

PALM was used for non-parametric permutation testing to determine cluster-level statistical

inference (10,000 permutations). We used a cluster-forming threshold of $z > 3.1$ ($p < 0.001$)

and a cluster-level significance level of $\alpha < 0.01$. The final data were rendered on the group

averaged HCP template surface.

Partial Correlation Analyses Controlling for Unimodal Models

To test whether the cortical areas identified by the multimodal experiential model indeed encoded information about multiple sensory-motor modalities, we conducted partial correlation RSAs in which RDMs encoding the effect of a single experiential modality were partialed out, one at a time, from the full-model RDM and from the neural RDM prior to computing the correlation between the two. This analysis tested whether the multimodal model predicted the neural similarity structure of lexical concepts, at each searchlight ROI, above and beyond what could be predicted by any unimodal model. Subsets of experiential features corresponding to specific modalities were selected to form the following 7 unimodal models: (a) visual ("Color", "Bright", "Dark", and "Pattern"); (b) auditory ("Sound", "Loud", "Low", and "High"); (c) tactile ("Touch", "Temperature", 'Weight", and "Texture"); (d) olfactory ("Smell"); (e) gustatory ("Taste"); (f) motor ("Manipulation", "Upper Limb", "Lower Limb", and "Head/Mouth"); and (g) affective ("Happy", "Sad", "Fearful", and " Angry"). In these analyses, all model-based RDMs were calculated using the Euclidean distance. The RDM representing the unique contribution of a given modality (say, visual) was obtained by partialling out the RDMs based on each of the other unimodal feature subsets (e.g., auditory, tactile, olfactory, gustatory, motor, and affective) from the RDM based on that modality to create an RDM that captured modality-specific content. The residual unimodal RDM was then partialed out of the full-model and the neural RDMs used in the RSA. We conducted 7 searchlight RSAs, each controlling for the effect of a single modalilty (as well as for the lexical and visual RDMs of no interest), resulting in 7 partial correlation maps. These analyses were constrained to a region-of-interest defined by the areas in which the RSA searchlight with the full experiential model reached significance in both experiments (the red areas in Figure 2). Each partial correlation map was thresholded at an FDR-corrected $P < 0.01$. The conjunction of the 7 thresholded maps revealed the areas in which the multimodal model explained significant variance that was not explained by any of the unimodal models.

Partial Correlation Analyses Controlling for a Non-Experiential Model

Since previous studies have found significant RSA correlations with concept similarities computed from distributional semantics (e.g., word2vec), we conducted a partial correlation RSA searchlight analysis to identify areas in which the multimodal experiential model predicted the neural similarity structure of concept-related activation patterns while controlling for the similarity structure predicted by word2vec. In this analysis, significant RSA correlations indicate that multimodal experiential information accounts for a degree of similarity among neural activation patterns that is not explained by the distributional model. Word2vec similarities were computed as the cosine between the 300-dimensional word vectors trained on the Google News dataset (approximately 100 billion words), based on the continuous skip-gram algorithm and distributed by Google (https://code.google.com/archive/p/word2vec).

We also compared the relative performance of the multimodal experiential model and word2vec by computing the mean semipartial RSA correlation for each model while controlling for the other, averaged across all vertices that reached significance in the main searchlight analysis. The difference between the mean RSA scores for the two models was tested via permutation test with 10,000 permutations.

Peak Identification in the Combined Dataset Across the Two Experiments

Finally, we combined the data from the two experiments by computing the mean RSA correlation with the multimodal experiential model across all 54 participants. This allowed us to identify distinct regions with high conceptual information content across all semantic categories investigated.

Results

Experiment 1

The mean response rate on the familiarity judgment task was 98.7% (SD 1.9%). Intra-individual consistency in familiarity ratings across the 6 repetitions of each word was evaluated

using intraclass correlations (ICCs) based on a single measurement, two-way mixed effects

model and the absolute agreement definition. Results suggested generally good overall intra-

individual agreement, with individual ICCs ranging from fair to excellent (mean ICC = 0.671,

range: 0.438 – 0.858, all ps < 0.00001) (Cicchetti, 1994). To examine consistency in familiarity

ratings across participants, responses to the 6 repetitions were first averaged within individuals,

and the ICC across participants was calculated using the consistency definition. The resulting

ICC of 0.586 (95% confidence interval [0.548, 0.625], p < .00001) suggested fair to good inter-

individual consistency.

Group-level searchlight RSA showed a bilateral, distributed network of regions where neural

similarity correlated with the semantic similarity index computed from the experiential model

(Figure 1, left). In the temporal lobe, these regions included the temporal pole, superior temporal

gyrus and sulcus (STG and STS), posterior middle temporal gyrus (pMTG), posterior inferior

temporal gyrus (pITG), and parahippocampal gyrus (PHG), all bilaterally. The left fusiform gyrus

(FG) was also involved. Parietal lobe involvement included angular and supramarginal gyri (AG

and SMG), posterior superior parietal lobule (pSPL), intraparietal sulcus (IPS), precuneus

(PreCun), and posterior cingulate gyrus (pCing), all bilaterally. Frontal lobe regions included the

inferior, middle, and superior frontal gyri (IFG, MFG, and SFG), ventral precentral sulcus

(vPreCS), rostral anterior cingulate gyrus (rACG), and orbital frontal cortex (OFC), all bilaterally.

The left anterior insula was also implicated.

Figure 1. Searchlight RSA results for the multimodal experiential model from Experiment 1 (left) and Experiment 2 (right). All results are significant at p < 0.001 and cluster corrected at α < 0.01. Colors represent t values.

Experiment 2

   The mean response rate on the familiarity judgment task was 99.2% (SD = 0.63%). Intra-individual consistency analysis showed generally good overall intra-individual agreement, with individual ICCs ranging from fair to excellent (mean ICC = 0.667, range: 0.464 – 0.843, all *p*s < 0.00001) (Cicchetti, 1994). The ICC across participants was 0.533 (95% confidence interval [0.548, 0.625], *p* < .00001), suggesting fair to good inter-individual consistency.

   As with Experiment 1, group-level searchlight RSA showed a bilateral, distributed network of regions where neural similarity correlated with semantic similarity as defined by the experiential

model (Figure 1, right). These areas largely coincided with those identified in Experiment 1,

including temporal pole, STG, STS, pMTG, pITG, FG, PHG, AG, SMG, IPS, pSPL, pCing,

PreCun, IFG, MFG, SFG, vPreCS, rACG, and OFC, all bilaterally; and left anterior insula. Areas

of overlap between the two experiments are shown in red in Figure 2. The percentage of

overlapping vertices between the two experiments, as measured by the Jaccard index, was

73.2%.

Figure 2. Cortical areas where the RSA correlation for the multimodal experiential model

reached significance in Experiment 1 (yellow), in Experiment 2 (blue), or in both experiments

(red).

Partial correlation analyses controlling for unimodal models

In both experiments, we found that all cortical areas detected in the main analysis showed

significant RSA correlations for the RDM based on the multimodal model after controlling for the

effects of each unimodal experiential model (Supplemental Data, Figure S1). These results

indicate that the relationships observed between the multimodal experiential model and neural

similarity patterns in these heteromodal regions could not be fully explained by any of the

unimodal models.

Partial correlation analyses controlling for a non-experiential model

In both experiments, we found that, even when word2vec similarity was controlled for, the

multimodal experiential model predicted the neural similarity pattern for lexical concepts in the

same regions found in the main analysis (Figure 3). The extent of the clusters was appreciably

reduced relative to the main analysis only in Experiment 2, particularly in the right hemisphere.

Figure 3. Searchlight RSA results for the multimodal experiential model after controlling for

word2vec similarity from Experiments 1 (left) and 2 (right). This analysis identified areas in

which the experiential model accounted for patterns of neural similarity that were not explained

by word2vec. All results are significant at p < 0.001 and cluster corrected at α < 0.01. Colors

represent t values. Extended Data Figure E2 shows the mean partial RSA score for each model,

averaged across all vertices that reached significance in the main analysis.

The mean semipartial RSAs comparing the performances of the two models showed that, in

both experiments, the neural similarity structure of concepts was significantly closer to the

similarity structure predicted by the multimodal experiential model than that predicted by

word2vec (Experiment 1: experiential = 0.011 (SE = 0.001), word2vec = -0.002 (SE = 0.001),

difference significant at p < 0.0001; Experiment 2: experiential = 0.010 (SE 0.001), word2vec =

0.004 (SE 0.001), difference significant at p < 0.0001.

Peak identification in the combined dataset

The combined map, averaged across participants from both experiments, clearly shows the

existence of distinct regions of high multimodal information content within the semantic network

(Figure 4). In the left hemisphere, local peaks were evident in the IFG, posterior MFG, posterior

SFS, mid-SFG, ventral PreCS, lateral OFC, AG, pIPS, pMTG/pSTS, PreCun, pCing,

retrosplenial cortex (RSC), anterior STS, lateral temporal pole, PHG and anterior FG, with

smaller peaks in similar right hemisphere regions (Table 1).

Table 1. Peaks in the combined RSA correlation map, averaged across all participants from both experiments. Peak labels correspond to those used in Figure 4. Coordinates refer to the MNI 152 2009 template space. Glasser parcel labels are taken from the surface-based atlas in Glasser et al. (2016).

Label	Experiment1		Experiment2		MNI coordinate			Glasser Parcel
	r	t	r	t	x	y	z	
L aSTS	0.0310	9.6846	0.0164	5.4968	-52	-5	-13	L_STSda
L pMTG	0.0231	5.7031	0.0495	6.2388	-62	-54	6	L_PHT
L FG	0.0149	6.2614	0.0109	4.8774	-38	-22	-24	L_TF
L PHC	0.0130	5.9539	0.0169	5.2829	-33	-33	-15	L_PHA2
L TP	0.0122	7.8297	0.0186	4.5259	-50	9	-31	L_TGd
L AG	0.0375	10.4097	0.0591	7.8860	-45	-67	23	L_PGi
L pIPS	0.0240	9.3430	0.0465	7.7980	-32	-73	40	L_IP1
L aIPS	0.0133	7.0900	0.0214	5.8797	-45	-43	46	L_IP2
L RSC	0.0338	10.7437	0.0322	5.6788	-7	-54	22	L_v23ab
L pCing	0.0264	8.4923	0.0240	7.1624	-3	-33	40	L_d23ab
L IFG$_{Tri}$	0.0710	7.9189	0.0672	7.2980	-46	32	14	L_IFSa
L OFC	0.0369	7.6686	0.0407	6.0822	-33	33	-13	L_47m
L IFG$_{Orb}$	0.0276	7.0624	0.0427	4.7093	-46	24	-9	L_47l
L SFG	0.0262	6.2200	0.0418	6.8846	-12	51	37	L_9p
L MFG	0.0230	7.9763	0.0324	5.8356	-39	6	49	L_55b
L SFS	0.0216	7.2827	0.0346	5.6016	-31	15	52	L_8Av
L PreCS	0.0177	5.5801	0.0336	4.7628	-47	4	27	L_6r
L dMPFC	0.0289	6.6695	0.0357	6.8968	-4	53	33	L_9m
R pSTS	0.0122	5.5690	0.0132	6.1890	61	-41	5	R_TPOJ1
R AG	0.0236	6.7504	0.0181	6.6492	48	-62	28	R_PGi
R pIPS	0.0143	5.9380	0.0129	6.8306	36	-66	48	R_IP1
R aIPS	0.0105	5.0085	0.0103	5.6255	50	-38	45	R_PFm
R pCing	0.0166	7.2148	0.0160	5.0762	3	-41	30	R_d23ab
R PreCun	0.0131	4.2406	0.0183	4.7893	12	-51	39	R_31pd
R RSC	0.0130	6.5836	0.0169	4.6987	5	-51	9	R_POS1
R IFG$_{Tri}$	0.0319	5.5993	0.0323	5.1412	51	35	12	R_IFSa
R OFC	0.0266	6.2474	0.0180	4.6262	33	34	-12	R_47m
R SFG	0.0137	6.1271	0.0180	5.3041	17	34	51	R_8BL
R SFS	0.0128	6.1521	0.0146	4.5023	33	17	52	R_8Av
R dMPFC	0.0204	5.2188	0.0175	6.0391	7	57	23	R_9m

Figure 4. RSA scores for the multimodal experiential model averaged across all participants in

Experiments 1 and 2 (n = 64). The RSA peaks reported in Table 1 are indicated.

Discussion

We sought to clarify the large-scale architecture of the concept representation system by

identifying cortical regions whose activation patterns encode multimodal experiential information

about individual lexical concepts. Across two independent experiments, each involving a large

number and a wide range of concepts (for a total of 522 unique lexical concepts), we detected

multimodal concept representation in widespread heteromodal cortical regions, bilaterally,

including anterior, posterior, and ventral temporal cortex, inferior and superior parietal lobules,

medial parietal cortex, and medial, dorsal, ventrolateral, and orbital frontal regions. In all of

these areas, the multimodal experiential model accounted for significant variance in the neural

similarity structure of lexical concepts that could not be explained by semantic structure derived

from word co-occurrence patterns or by unimodal experiential models. These results confirm

and extend previous neuroimaging studies indicating that the concept representation system is

highly distributed and that multimodal experiential information is encoded throughout the

system. The present study identified several distinct regions displaying relatively high

conceptual information content, including regions not typically associated with lexical semantic

processing, such as the orbitofrontal cortex, superior frontal gyrus, precuneus, and posterior

cingulate gyrus. We propose that these regions are good candidates for the convergence zones

postulated by certain models of concept representation and retrieval (Damasio, 1989; Mesulam,

1998; Meyer and Damasio, 2009).

Three previous RSA studies using semantic models and word stimuli implicated

anteromedial temporal cortex, particularly perirhinal cortex, as a semantic hub (Bruffaerts et al.,

2013; Liuzzi et al., 2015; Martin et al., 2018). All used semantic models based on crowd-

sourced feature production lists, and all used a feature verification task during fMRI (e.g.,

"WASP – Does it have paws?"). Validity issues with feature production lists have been noted

previously, such as the fact that some types of features are difficult to verbalize or

systematically ignored (Hoffman and Lambon Ralph, 2013). Another potential problem with

these RSA studies is that the verification task used during fMRI requires semantic processing of

the explicitly named feature, which logically must contribute to the observed neural activation

pattern but is not coded in the semantic model. These problems may have weakened the ability

of these studies to detect other regions involved in concept representation.

Prior studies combining searchlight RSA with either taxonomic (Devereux et al., 2013;

Carota et al., 2021) or distributional (Anderson et al., 2015; Carota et al., 2021) semantic

models have implicated more widespread regions, including posterior lateral temporal cortex,

inferior parietal lobe, posterior cingulate gyrus, and prefrontal cortex. Only one of these studies

(Anderson et al., 2015) reported any representational correspondence in medial or ventral

temporal areas. The two studies using taxonomic models (Devereux et al., 2013; Carota et al.,

2021) showed similar involvement of the left posterior superior temporal sulcus and MTG, with

extension into adjacent AG and SMG. In contrast, the two studies using distributional models

(Anderson et al., 2015; Carota et al., 2021) found little or no posterior temporal involvement, and

inferior parietal involvement was confined mainly to the left SMG. Frontal cortex involvement

was uniformly present but highly variable in extent and location across those studies. Two

studies reported involvement of the posterior cingulate/precuneus (Anderson et al., 2015;

Devereux et al., 2013).

Several factors may have negatively impacted sensitivity and reliability in those studies.

First, ROI-based RSAs show that, relative to experiential models of concept representation,

taxonomic and distributional models are consistently less sensitive to the neural similarity

structure of lexical concepts (Fernandino et al., 2022). Furthermore, most of the prior studies

used volume-based spherical searchlights, which typically sample a mix of grey and white

matter voxels, while the surface-based approach used in the present study ensures that only

contiguous cortical gray matter voxels are included, thus reducing noise from uninformative

voxels. Finally, the nature of the task and the particularities of the concept set used as stimuli

can affect both the sensitivity of the analysis and the cortical distribution of the RSA searchlight

map, and variations in these properties may underlie some of the variation in results across

studies. We dealt with this last issue by (1) employing large numbers of concepts from diverse

semantic categories and (2) by analyzing data from two independent experiments to identify

areas displaying reliable representational correspondence with the semantic model across

different concept sets and different participant samples.

The network of brain regions identified in the current study closely resembles the network

identified previously in a meta-analysis of 120 functional imaging studies on semantic

processing (Binder et al., 2009). It has been argued that some of these regions, such as the

angular gyrus, do not actually contribute to conceptual processing, only appearing to be

activated in semantic tasks due to differences in task difficulty (e.g., Humphreys et al., 2021).

The present results provide direct evidence that all brain regions highlighted in the previous

meta-analysis indeed represent conceptual information during semantic word processing. Unlike

previous studies based on cognitive subtraction paradigms, our RSA results cannot be

explained by systematic differences in difficulty or task requirements. In contrast to previous

RSA studies of concept representation (Anderson et al., 2015; Carota et al., 2021; Devereux et

al., 2013; Martin et al., 2018), the network includes extensive cortex in the anterior temporal

lobe, a region strongly implicated in high-level semantic representation (Lambon Ralph et al.,

2017). While the present study did not show significant RSA correlations in the anterior

ventrolateral temporal lobes, it is important to note that these regions (as well as the

ventromedial prefrontal cortex), exhibit typically low BOLD signal-to-noise ratios owing to

magnetic susceptibility effects. Therefore, the present data do not allow us to derive conclusions

about conceptual information content in these areas. Further studies using echo-planar imaging

parameters optimized for detecting BOLD signal in these areas are needed to address this

issue.

The concept representation network identified in the current study also closely resembles

the set of cortical regions referred to as the "default mode network" (DMN) (Buckner et al.,

2008). Several functional connectivity studies indicate that these areas function as hubs, or

convergence zones, for the multimodal integration of sensory-motor information (Buckner et al.,

2009; Sepulcre et al., 2012; Heuvel and Sporns, 2013; Margulies et al., 2016; Murphy et al.,

2018). They have been shown to be equidistant from primary sensory and motor areas in

"stepwise" functional connectivity analyses, sitting at the end of the principal gradient of cortical

connectivity going from unimodal to heteromodal areas. Activity in these areas has also been

associated with the level of experiential detail present in ongoing thought (Smallwood et al.,

2016; Sormaz et al., 2018). The current results provide novel evidence that activity patterns in

DMN regions also reflect conceptual content conveyed by individual words. This further

supports the view that concept retrieval is a major component of the brain's "default mode" of

processing (Binder et al., 1999, 2009; Andrews-Hanna et al., 2014; Yeshurun et al., 2021).

The finding of extensive frontal lobe involvement in concept "representation" deserves

comment. Studies of brain damaged individuals and functional imaging experiments in the

healthy brain have long been interpreted as supporting the classic view that ascribes to frontal

cortex an executive control rather than an information storage function in the brain (Stuss and

Benson, 1986; Kimberg and Farah, 1993; Thompson-Schill et al., 1997; Wagner et al., 2001).

Nevertheless, nearly all RSA studies of concept representation have observed similarity

structure correlations in prefrontal regions. While these observations do not speak directly to the

distinction between "storage" and "control" of information, we believe they can be reconciled

with the classic view by postulating a fine-grained organization of control systems, in which

prefrontal cortex is tuned, at a relatively small scale, to particular sensory-motor and affective

features. Neurophysiological studies in nonhuman primates provide evidence for tuning of

prefrontal neurons to preferred stimulus modalities (Romanski, 2007), as well as differential

connectivity across the prefrontal cortex with various sensory systems (Barbas and Mesulam,

1981; Petrides, 2005). A few human functional imaging studies provide similar evidence for

sensory modality tuning in prefrontal cortex (Greenberg et al., 2010; Michalka et al., 2015;

Tobyne et al., 2017). If conceptual representation in temporal and parietal cortex is inherently

organized according to experiential content, it seems plausible that controlled activation and

short-term maintenance of this information would require similarly fine-grained control

mechanisms. We propose that the information represented in these prefrontal regions reflects

their entrainment to experiential representations stored primarily in temporoparietal cortex,

providing context-dependent control over their level of activation.

Related to this issue is the question of how similar the many regions identified by RSA are to

each other in terms of their representational structure. Although RSA ensures that the neural

similarity structure of all these regions is related to the similarity structure encoded in the

semantic model, representational structure should be expected to vary to some degree across

distinct functional regions, given their unique computational properties and connectivity profiles.

More research is needed to investigate potential regional differences in representational

content.

Extended Data Figure E1. RSA results for the multimodal model after removing contributions

from each of 7 unimodal models representing visual, auditory, somatosensory, smell, taste,

action, and affective experiential content. Shown in red are the regions within the overlap map

from Figure 2 where the multimodal model explained additional variance compared to all of the

unimodal models in isolation.

Extended Data: Figure E2. Results of the semipartial correlation RSAs comparing the

multimodal experiential model and the distributional model word2vec in Experiment 1 (left) and

Experiment 2 (right). Experiential: Mean RSA scores for the experiential RDM after regressing

out the word2vec RDM, averaged across vertices. Word2vec: Mean RSA scores for the

word2vec RDM after regressing out the experiential RDM, averaged across vertices. Each

paired data point corresponds to one participant.

References

Anderson AJ, Binder JR, Fernandino L, Humphries CJ, Conant LL, Aguilar M, Wang X, Doko D, Raizada RDS (2017) Predicting neural activity patterns associated with sentences using a neurobiologically motivated model of semantic representation. Cerebral Cortex 27:4379–4395.

Anderson AJ, Binder JR, Fernandino L, Humphries CJ, Conant LL, Raizada RDS, Lin F, Lalor EC (2019) An integrated neural decoder of linguistic and experiential meaning. The Journal of Neuroscience 39:8969–8987.

Anderson AJ, Bruni E, Lopopolo A, Poesio M, Baroni M (2015) Reading visually embodied meaning from the brain: Visually grounded computational models decode visual-object mental imagery induced by written text. NeuroImage 120:309–322.

Andrews-Hanna JR, Smallwood J, Spreng RN (2014) The default network and self-generated thought: component processes, dynamic control, and clinical relevance. Ann Ny Acad Sci 1316:29–52.

Barbas H, Mesulam M (1981) Organization of afferent input to subdivisions of area 8 in the rhesus monkey. J Comp Neurol 200:407–431.

Barsalou LW (2008) Grounded cognition. Annual Review of Psychology 59:617–645.

Binder JR, Conant LL, Humphries CJ, Fernandino L, Simons SB, Aguilar M, Desai RH (2016) Toward a brain-based componential semantic representation. Cognitive Neuropsych 33:130–174.

Binder JR, Desai RH (2011) The neurobiology of semantic memory. Trends in Cognitive Sciences 15:527–536.

Binder JR, Desai RH, Graves WW, Conant LL (2009) Where is the semantic system? A critical review and meta-analysis of 120 functional neuroimaging studies. Cerebral Cortex 19:2767–2796.

Binder JR, Frost JA, Hammeke TA, Bellgowan PSF, Rao SM, Cox RW (1999) Conceptual
processing during the conscious resting state: A functional MRI study. J Cognitive Neurosci
11:80–93.

Bonner MF, Peelle JE, Cook PA, Grossman M (2013) Heteromodal conceptual processing in
the angular gyrus. NeuroImage 71:175–186.

Bruffaerts R, Dupont P, Peeters R, Deyne SD, Storms G, Vandenberghe R (2013) Similarity of
fMRI activity patterns in left perirhinal cortex reflects semantic similarity between words. The
Journal of Neuroscience 33:18597–18607.

Buckner RL, Andrews-Hanna JR, Schacter DL (2008) The brain's default network: anatomy,
function, and relevance to disease. Annals of the New York Academy of Sciences 1124:1–
38.

Buckner RL, Sepulcre J, Talukdar T, Krienen FM, Liu H, Hedden T, Andrews-Hanna JR,
Sperling RA, Johnson KA (2009) Cortical hubs revealed by intrinsic functional connectivity:
mapping, assessment of stability, and relation to Alzheimer's disease. The Journal of
Neuroscience 29:1860–1873.

Carota F, Nili H, Pulvermüller F, Kriegeskorte N (2021) Distinct fronto-temporal substrates of
distributional and taxonomic similarity among words: evidence from RSA of BOLD signals.
Neuroimage 224:117408.

Cicchetti DV (1994) Guidelines, criteria, and rules of thumb for evaluating normed and
standardized assessment instruments in psychology. Psychol Assessment 6:284–290.

Damasio AR (1989) Time-locked multiregional retroactivation: a systems-level proposal for the
neural substrates of recall and recognition. 33:25–62.

Damasio H, Tranel D, Grabowski T, Adolphs R, Damasio AR (2004) Neural systems behind
word and concept retrieval. Cognition 92:179–229.

Devereux BJ, Clarke A, Marouchos A, Tyler LK (2013) Representational similarity analysis
reveals commonalities and differences in the semantic processing of words and objects. The
Journal of Neuroscience 33:18906–18916.

Esteban O, Markiewicz CJ, Blair RW, Moodie CA, Isik AI, Erramuzpe A, Kent JD, Goncalves M,

DuPre E, Snyder M, Oya H, Ghosh SS, Wright J, Durnez J, Poldrack RA, Gorgolewski KJ

(2018) fMRIPrep: a robust preprocessing pipeline for functional MRI. Nat Methods 16:111–

116.

Fernandino L, Binder JR, Desai RH, Pendl SL, Humphries CJ, Gross WL, Conant LL,

Seidenberg MS (2016a) Concept representation reflects multimodal abstraction: A

framework for embodied semantics. Cerebral Cortex 26:2018–2034.

Fernandino L, Humphries CJ, Conant LL, Seidenberg MS, Binder JR (2016b) Heteromodal

cortical areas encode sensory-motor features of word meaning. Journal of Neuroscience

36:9763–9769.

Fernandino L, Tong J-Q, Conant LL, Humphries CJ, Binder JR (2022) Decoding the information

structure underlying the neural representation of concepts. Proc National Acad Sci

119:e2108091119.

Gainotti G (2000) What the locus of brain lesion tells us about the nature of the cognitive defect

underlying category-specific disorders: A review. Cortex 36:539–559.

Glasser MF, Sotiropoulos SN, Wilson JA, Coalson TS, Fischl B, Andersson JL, Xu J, Jbabdi S,

Webster M, Polimeni JR, Essen DCV, Jenkinson M, Consortium for the W-MH (2013) The

minimal preprocessing pipelines for the Human Connectome Project. NeuroImage 80:105–

124.

Glenberg AM, Webster BJ, Mouilso E, Havas D, Lindeman LM (2009) Gender, emotion, and the

embodiment of language comprehension. Emot Rev 1:151–161.

Greenberg AS, Esterman M, Wilson D, Serences JT, Yantis S (2010) Control of spatial and

feature-based attention in frontoparietal cortex. J Neurosci Official J Soc Neurosci 30:14330–

14339.

Heuvel MP van den, Sporns O (2013) Network hubs in the human brain. Trends in Cognitive

Sciences 17:683–696.

Hodgson VJ, Lambon Ralph MA, Jackson RL (2021) Multiple dimensions underlying the functional organization of the language network. Neuroimage 241:118444.

Hoffman P, Lambon Ralph M (2013) Shapes, scents and sounds: quantifying the full multi-sensory basis of conceptual knowledge. Neuropsychologia 51:14–25.

Humphreys GF, Lambon Ralph MA, Simons JS (2021) A unifying account of angular gyrus contributions to episodic and semantic cognition. Trends Neurosci 44:452–463.

Kemmerer D (2014) Cognitive Neuroscience of Language. New York, NY: Psychology Press.

Kiefer M, Pulvermüller F (2012) Conceptual representations in mind and brain: Theoretical developments, current evidence and future directions. Cortex 48:805–825.

Kimberg DY, Farah MJ (1993) A unified account of cognitive impairments following frontal lobe damage: The role of working memory in complex, organized behavior. J Exp Psychology Gen 122:411–428.

Kriegeskorte N, Bandettini P (2007) Analyzing for information, not activation, to exploit high-resolution fMRI. NeuroImage 38:649–662.

Kriegeskorte N, Goebel R, Bandettini P (2006) Information-based functional brain mapping. Proceedings of the National Academy of Sciences of the United States of America 103:3863–3868.

Kriegeskorte N, Mur M, Bandettini P (2008) Representational similarity analysis - connecting the branches of systems neuroscience. Frontiers in Systems Neuroscience 2:4.

Lambon Ralph MA, Jefferies E, Patterson K, Rogers TT (2017) The neural and computational bases of semantic cognition. Nature Reviews Neuroscience 18:42–55.

Liuzzi AG, Bruffaerts R, Dupont P, Adamczuk K, Peeters R, Deyne SD, Storms G, Vandenberghe R (2015) Left perirhinal cortex codes for similarity in meaning between written words: Comparison with auditory word input. Neuropsychologia 76:4–16.

Mahon BZ, Caramazza A (2008) A critical look at the embodied cognition hypothesis and a new proposal for grounding conceptual content. Journal of Physiology, Paris 102:59–70.

Margulies DS, Ghosh SS, Goulas A, Falkiewicz M, Huntenburg JM, Langs G, Bezgin G,

Eickhoff SB, Castellanos FX, Petrides M, Jefferies E, Smallwood J (2016) Situating the

default-mode network along a principal gradient of macroscale cortical organization. Proc

National Acad Sci 113:12574–12579.

Martin CB, Douglas D, Newsome RN, Man LL, Barense MD (2018) Integrative and distinctive

coding of visual and conceptual object features in the ventral visual stream. eLife 7:1493.

Mesulam M-M (1998) From sensation to cognition. Brain 121:1013–1052.

Meteyard L, Vigliocco G (2008) The role of sensory and motor information in semantic

representation. In: Handbook of Cognitive Science: An Embodied Approach (Calvo P,

Gomila T, eds), pp 291–312. San Diego, CA: Elsevier.

Meyer K, Damasio A (2009) Convergence and divergence in a neural architecture for

recognition and memory. Trends in Neurosciences 32:376–382.

Michalka SW, Kong L, Rosen ML, Shinn-Cunningham BG, Somers DC (2015) Short-term

memory for space and time flexibly recruit complementary sensory-biased frontal lobe

attention networks. Neuron 87:882–892.

Murphy C, Jefferies E, Rueschemeyer S-A, Sormaz M, Wang H, Margulies DS, Smallwood J

(2018) Distant from input: Evidence of regions within the default mode network supporting

perceptually-decoupled and conceptually-guided cognition. Neuroimage 171:393–401.

Neininger B, Pulvermüller F (2003) Word-category specific deficits after lesions in the right

hemisphere. Neuropsychologia 41:53–70.

Oldfield RC (1971) The assessment and analysis of handedness: the Edinburgh inventory.

Neuropsychologia 9:97–113.

Patterson K, Nestor PJ, Rogers TT (2007) Where do you know what you know? The

representation of semantic knowledge in the human brain. Nature Reviews Neuroscience

8:976–987.

Peirce JW (2007) PsychoPy--Psychophysics software in Python. J Neurosci Meth 162:8–13.

Petrides M (2005) Lateral prefrontal cortex: architectonic and functional organization.

Philosophical transactions of the Royal Society of London Series B, Biological sciences

360:781–795.

Romanski LM (2007) Representation and integration of auditory and visual stimuli in the primate

ventral lateral prefrontal cortex. Cereb Cortex 17:i61–i69.

Sepulcre J, Sabuncu MR, Yeo TB, Liu H, Johnson KA (2012) Stepwise connectivity of the

modal cortex reveals the multimodal organization of the human brain. The Journal of

Neuroscience 32:10649–10661.

Smallwood J, Karapanagiotidis T, Ruby F, Medea B, Caso I de, Konishi M, Wang H-T, Hallam

G, Margulies DS, Jefferies E (2016) Representing representation: Integration between the

temporal lobe and the posterior cingulate influences the content and form of spontaneous

thought. Plos One 11:e0152272.

Sormaz M, Murphy C, Wang H, Hymers M, Karapanagiotidis T, Poerio G, Margulies DS,

Jefferies E, Smallwood J (2018) Default mode network can support the level of detail in

experience during active task states. P Natl Acad Sci Usa 115:9318–9323.

Stuss DT, Benson DF (1986) The Frontal Lobes. United Kingdom: Raven Press.

Thompson-Schill SL, D'Esposito M, Aguirre GK, Farah MJ (1997) Role of left inferior prefrontal

cortex in retrieval of semantic knowledge: A reevaluation. Proc National Acad Sci 94:14792–

14797.

Tobyne SM, Osher DE, Michalka SW, Somers DC (2017) Sensory-biased attention networks in

human lateral frontal cortex revealed by intrinsic functional connectivity. Neuroimage

162:362–372.

Wagner AD, Paré-Blagoev EJ, Clark J, Poldrack RA (2001) Recovering meaning: left prefrontal

cortex guides controlled semantic retrieval. Neuron 31:329–338.

Warrington EK, Shallice T (1984) Category specific semantic impairments. Brain 107 (Pt

3):829–854.

Yeshurun Y, Nguyen M, Hasson U (2021) The default mode network: where the idiosyncratic

self meets the shared social world. Nat Rev Neurosci 22:181–192.