A Distributed Network for Multimodal Experiential Representation of Concepts

Jia-Qing Tong[1,2], Jeffrey R. Binder[1,2], Colin J. Humphries[1], Stephen Mazurchuk[1,2], Lisa L.

Conant[1], Leonardo Fernandino[1,3]

[1]Department of Neurology, Medical College of Wisconsin, Milwaukee, WI, USA

[2]Department of Biophysics, Medical College of Wisconsin, Milwaukee, WI, USA

[3]Department of Biomedical Engineering, Medical College of Wisconsin and Marquette

University, Milwaukee, WI, USA

Abbreviated title: Multimodal Concept Representation

Corresponding Author:

Leonardo Fernandino, Ph.D.

Departments of Neurology and Biomedical Engineering

Medical College of Wisconsin

8701 W Watertown Plank Rd, Milwaukee, WI 53226

Email: lfernandino@mcw.edu

Office Phone: 414-955-7388

Key words: semantics, concept representation, representational similarity analysis, fMRI

Pages: 33

Figures: 4

Supplementary Tables: 2

Financial interests or conflicts of interest: None.

Acknowledgements:

This work was supported by National Institute on Deafness and Other Communication Disorders

(NIDCD) grant R01 DC016622, by the Intelligence Advanced Research Projects Activity under

Grant FA8650-14-C-7357, and by a grant from the Advancing a Healthier Wisconsin Foundation

(Project #5520462). The authors thank Volkan Arpinar, Elizabeth Awe, Joseph Heffernan,

Steven Jankowski, Jedidiah Mathis, and Megan LeDoux for technical assistance.

Abstract

The architecture of the cortical system underlying concept representation is a topic of intense

debate. Much evidence supports the claim that concept retrieval selectively engages sensory,

motor, and other neural systems involved in the acquisition of the retrieved concept, yet there is

also strong evidence for involvement of high-level, supramodal cortical regions. A fundamental

question about the organization of this system is whether modality-specific information

originating from sensory and motor areas is integrated across multiple "convergence zones" or

in a single centralized "hub". We used representational similarity analysis (RSA) of fMRI data to

map brain regions where the similarity structure of neural patterns elicited by large sets of

concepts matched the similarity structure predicted by a high-dimensional model of concept

representation based on sensory, motor, affective, and other modal aspects of experience.

Across two studies involving different sets of concepts, different participants, and different tasks,

searchlight RSA revealed a distributed, bihemispheric network engaged in multimodal

experiential representation, composed of high-level association cortex in anterior, lateral, and

ventral temporal lobe; inferior parietal lobule; posterior cingulate gyrus and precuneus; and

medial, dorsal, ventrolateral, and orbital prefrontal cortex. These regions closely resemble

networks previously implicated in general semantic and "default mode" processing and are

known to be high-level hubs for convergence of multimodal processing streams. Supplemented

by an exploratory cluster analysis, these results indicate that the concept representation system

consists of multiple, hierarchically organized convergence zones supporting multimodal

integration of experiential information.

Significance Statement

It has long been known that information about visual, auditory, motor, affective, and other

features of our phenomenal experience originate in distinct brain regions. However, it is still

unclear how these processing streams converge to form multimodal concept representations.

Using fMRI together with a multimodal experiential model of conceptual content, we show in two

large studies that concept knowledge is represented across a distributed, bihemispheric network

including temporal, parietal, limbic, and prefrontal association cortices. These results argue

against the idea of a single centralized "hub" for concept representation, suggesting instead that

multiple high-level convergence zones encode conceptual information in terms of multimodal

experiential content.

Introduction

Concepts are the building blocks of meaning and are essential for everyday thinking, planning,

and communication, yet there remains considerable debate surrounding their neural

implementation. "Grounded" theories of concept representation postulate that sensory-motor

and affective representations involved in concept formation are re-activated during concept

retrieval (Damasio, 1989; Barsalou, 2008; Glenberg et al., 2009). Support for this claim includes

many studies showing that perceptual and motor processing areas are activated when

corresponding perceptual or motor information about concepts is retrieved (Meteyard and

Vigliocco, 2008; Binder and Desai, 2011; Kiefer and Pulvermuller, 2012; Kemmerer, 2014).

How these multiple modality-specific representations are combined during concept

retrieval, however, is not yet clear. Primate cortex contains multiple regions where information

converges across sensory modalities (Jones and Powell, 1970; Mesulam, 1998; Man et al.,

2013; Man et al., 2015). Portions of the human superior temporal sulcus (STS), for example, are

known to respond to tactile, auditory, and visual stimulation (Beauchamp et al., 2008). The

homolog of this region in macaque monkeys contains neurons that similarly respond to any of

these stimulation modalities (Bruce et al., 1981) and are anatomically connected to

corresponding unimodal cortex (Padberg et al., 2003). Other primate brain areas reported to

have multimodal characteristics include posterior parietal cortex (Andersen, 1997), prefrontal

cortex (Sugihara et al., 2006), parahippocampus (Damasio et al., 1982), and entorhinal cortex

(Van Hoesen et al., 1972). Possible human homologs of these regions include cortical areas

identified with the "default mode network", as suggested by a step-wise connectivity analysis of

resting-state fMRI (Sepulcre et al., 2012). Beginning with seed regions in multiple primary

sensory cortices, these authors showed that connections arising from these regions gradually

converge, over multiple connectivity steps, at high-level "hubs" that include much of the lateral

temporal cortex, angular gyrus, dorsomedial and inferolateral prefrontal cortex, posterior

cingulate gyrus and precuneus.

Various models propose a central role for multimodal or supramodal hubs in concept

processing, though both the anatomical location and information content encoded in these hubs

remain unclear (Mahon and Caramazza, 2008; Binder and Desai, 2011; Lambon Ralph et al.,

2017). One prominent theory proposes that the anterior temporal lobe (ATL) plays a unique role

in storing abstract concept representations. During concept retrieval, the central ATL hub would

activate modality-specific representations stored in unimodal cortical areas (the "spokes")

(Patterson et al., 2007). An alternative model postulates widespread and hierarchically

organized convergence zones in multiple brain locations (Damasio, 1989; Mesulam, 1998;

Meyer and Damasio, 2009). We have previously proposed that these convergence zones are

neurally implemented in the multimodal connectivity hubs identified by Sepulcre et al. (2012),

which closely correspond to the regions identified in a large neuroimaging meta-analysis of

semantic word processing (Binder et al., 2009). This idea is supported by neuroimaging findings

indicating that these cortical regions encode multimodal information about the experiential

content of lexical concepts (Bonner et al., 2013; Fernandino et al., 2016b; Fernandino et al.,

2016a; Fernandino et al., 2021).

Here we use representational similarity analysis (RSA) with a whole-brain searchlight

approach to identify cortical regions involved in multimodal conceptual representation. RSA

measures the level of correspondence between the similarity matrix for a set of stimuli (e.g.,

words) derived from neural data and the similarity matrix for the same stimulus set computed

from an *a priori* representational model (Kriegeskorte et al., 2008). We used a searchlight

approach (Kriegeskorte et al., 2008) to generate a map of cortical regions where this

representational correspondence holds true. We used an experiential model of conceptual

content as the basis for RSA (Binder et al., 2016). Unlike the abstract representations used in

previous RSA studies, this model encodes conceptual content explicitly in terms of 65 sensory,

motor, affective, and other experiential processes. Identical analyses were run on two large

datasets to assess replication across independent participant samples, word sets, and tasks.

The analyses provided strong evidence that the multimodal experiential content of lexical

concepts is represented across several high-level convergence zones.

Material and Methods

Experiment 1

Participants

Nineteen native English speakers (11 women, 8 men) participated in Experiment 1. Their mean

age was 26.4 years (range 20 to 38). All were right-handed according to the Edinburgh

handedness inventory (Oldfield, 1971) and had no history of neurological disease. All

participants in Experiments 1 and 2 were compensated for their time and gave informed consent

in conformity with a protocol approved by the Institutional Review Board of the Medical College

of Wisconsin.

Stimuli and Concept Features

The stimuli consisted of 242 words, including 141 nouns, 62 verbs, and 39 adjectives

(Supplementary Table 1). The noun concepts included inanimate objects, animate objects,

human roles (e.g., mother, doctor), settings (e.g., church, forest), and events. Stimuli were

selected by the Intelligence Advanced Research Projects Activity, which funded the study.

Experiential representations for these words were available from a previous study in which

ratings on 65 experiential domains were used to represent word meanings in a high-dimensional

space (Binder et al., 2016). In brief, the experiential domains were selected based on known

neural processing systems – such as color, shape, visual motion, touch, audition, motor control,

olfaction – as well as other fundamental aspects of cognition whose neural substrates are less

clearly understood, such as space, time, affect, reward, numerosity, and others. Ratings were

collected using the crowd sourcing tool Amazon Mechanical Turk, in which volunteers rated the

relevance of each experiential domain to a given concept on a 0-6 Likert scale. The value of

each feature was represented by averaging ratings across participants. This feature set was

highly effective at clustering concepts into traditional taxonomic categories (e.g., animals,

plants, vehicles, occupations, etc.) (Binder et al., 2016) and has been used successfully to

decode fMRI activation patterns during sentence reading (Anderson et al., 2017; Anderson et

al., 2019).

Stimulus Presentation and Tasks

Words were presented visually in a fast event-related procedure with variable inter-stimulus

intervals. The entire list was presented to each participant six times in a different pseudorandom

order across two separate imaging sessions (3 presentations per session).

Stimuli were presented in white font on a black background. Each trial began with

presentation of a single word for 500 ms, followed by a 1.5-sec fixation period (**Figure 1**).

Participants were instructed to read each word silently and think about the meaning of the word.

To ensure attention to the stimuli, a random 10% of the trials were followed by a semantic-

matching probe task, in which 2 words were shown side by side, and the participant indicated by

a button press which of the two was more similar in meaning to the word just presented (these

probe trials were not included in the analyses). All trials then concluded with presentation of a

nonverbal "reset" stimulus for 1.5 seconds, the aim of which was to suppress processing of the

previously presented word. The reset stimulus consisted of two grey squares presented side by

side and separated by a vertical black line. The participant indicated by a button press which of

the two squares was brighter. A variable fixation period of 0-4 sec followed all trials prior to the

beginning of the next trial.

Figure 1. Schematic illustration of the tasks used in Experiment 1.

Each presentation of 242 test words and 26 probe trials (268 trials in total) occurred over

the course of four imaging runs, each lasting 6 minutes. The four runs that comprised one

repeat of the entire list was referred to as a "set". To minimize lexical ambiguity, grammatical

class was used to block items by run. This was necessary because many of the nouns in the list

can also be used as verbs, and several had very different semantic features when used as

nouns vs. verbs (e.g., 'left', 'duck', 'saw', 'fence', 'spring'). Although the verbs in the set were all

in past tense, several are also used commonly as adjectival participles ('celebrated', 'damaged',

'lost', 'planned', 'used'). Thus, nouns and verbs were presented in different runs, and adjectives

were blocked with the nouns to separate them from the verbs. The nouns and adjectives were

distributed evenly across 3 of the 4 imaging runs in each set, with the runs balanced on word

class and noun category. Each of these 3 runs thus included 13 adjectives, 4-5 event nouns, 8

animate object nouns, 12-13 inanimate object nouns, 12-13 human role nouns, and 10 setting

nouns. The remaining run of each set contained all 62 verbs.

Stimuli for probe trials were selected pseudo-randomly with replacement. For the 3

noun-adjective runs, a random set of either 6 or 7 probe trial words was selected for each run

from the words comprising the other two noun-adjective runs, such that no stimulus used on a

probe trial was repeated within the same run. This was not possible for the verb run, since all 62

verbs were presented in the same run. Thus, for the verb run, 7 verbs appeared twice – one

time followed by a probe and one time without a probe.

Nine complete sets were composed in this way. Six were selected for each participant,

with counterbalancing across participants. In addition, the order of presentation within each run

was randomized for each participant to eliminate order effects at the group level.

MRI Data Acquisition and Processing

Images were acquired with a 3T GE 750 scanner at the Center for Imaging Research of the

Medical College of Wisconsin. High-resolution T1-weighted anatomical images were acquired

with a 3D spoiled gradient echo sequence (FOV = 240 mm, 220 axial slices, in-plane matrix =

256 x 224, voxel size = 1 x 1 x 1 mm^3). T2-weighted anatomical images were acquired with a

CUBE T2 sequence (FOV = 256 mm, 168 sagittal slices, in-plane matrix = 256 x 256, voxel size

= 1 x 1 x 1 mm^3). T2*-weighted gradient-echo echoplanar images were obtained for functional

imaging (TR = 2000 ms, TE = 24 ms, flip angle = 77°, FOV = 192 mm, 41 axial slices, in-plane

matrix = 64 x 64, voxel size = 3 x 3 x 3 mm^3).

Preprocessing was performed using AFNI. EPI images were corrected for slice timing.

All images were then aligned to the 3rd functional image in the series before aligning to the T1-

weighted anatomical image. All voxels were normalized to have a mean of 100 and a range of 0

to 200. A general linear model was built to fit the time series of the functional data via

multivariable regression. Each word was treated as a single regressor of interest, which

included the 6 repetitions of the word and excluded any probe task trials involving that word,

resulting in 242 beta coefficient maps. Regressors of no interest included 12 degrees of

freedom of head motion, response time for the reset task, and response time for the probe task

trials. Individual word, reset, and probe task event regressors were convolved with a

hemodynamic response function. A *t* statistical map was generated for each word and these

maps were subsequently used for the searchlight RSA.

Surface-Based Searchlight Representational Similarity Analysis

To optimize alignment between participants and to constrain the searchlight analysis to cortical

grey matter, individual brain surface models were constructed from T1-weighted and T2-

weighted anatomical data using Freesurfer and the HCP pipeline (Glasser et al., 2013). The

cortex ribbon was reconstructed in standard grayordinate space with 2-mm spaced vertices. We

visually checked the quality of reconstructed surfaces before carrying out the analysis.

Segmentation errors were corrected manually, and the corrected images were fed back to the

pipeline to produce the final surfaces. Only cortical grey matter was included in the analysis.

RSA was carried out using custom Python and Matlab scripts. Searchlight RSA typically

employs spherical volumes moved systematically through the brain or the cortical grey matter

voxels. This method, however, does not exclude signals from white matter voxels that happen to

fall within the sphere, and which may contribute noise. Spherical volumes may also erroneously

combine non-contiguous cortical regions across sulci. Surface-based searchlight analysis

overcomes these shortcomings using circular 2-dimensional "patches" confined to contiguous

vertices on the cortical surface. At each vertex, a fast-marching algorithm was applied to create

a 5-mm radius patch around the seed vertex on the midthickness surface, resulting in a group of

vertices comprising each patch. These vertices were then mapped one by one back to the

native volume space of the participant to label voxels associated with the surface patch. To

avoid partial-volume effects, we included only voxels that contained the entire middle 80% of the

cortical ribbon at the mapped vertex location. Each surface vertex was thus associated with a

group of voxels in native space (the searchlight ROI) for subsequent RSA.

Representational dissimilarity matrices (RDMs) were calculated for the semantic model

(the model RDM) and for each vertex-associated ROI (the neural RDM). Each entry in the

neural RDM represented the correlation distance between fMRI responses evoked by two

different words. Neural RDMs were computed for each of the 64,984 vertices. For the model

RDM, we calculated the cosine distances between each pair of words in the 65-dimensional

experiential feature space. A word length RDM, created by taking the absolute difference in

letter length between each word pair, was included as a covariate matrix of no interest. Pearson

correlations between neural RDMs and the model RDM were computed controlling for the word

length RDM, resulting in a partial correlation score map on the surface for each participant.

Finally, second level analysis was performed on the partial correlation score maps after

alignment of each individual map to a common surface template (generated by averaging the

individual 32k_FS_LR meshes produced by the HCP pipeline), Fisher z-transformation, and

smoothing of the maps with a 6-mm full width at half maximum Gaussian kernel. A one-tailed,

one-sample t-test against zero was applied at all vertices. FSL's PALM was used for non-

parametric permutation testing to determine cluster-level statistical inference. Cluster-level

statistical inference was implemented with a cluster-forming threshold of $z > 3.1$ ($p < 0.001$).

The distribution of the largest clusters across permutations, in which the correlations were

randomly sign-flipped 10,000 times, was calculated, and a significance level of $\alpha < 0.01$ was set.

The final data were rendered on the group averaged HCP template surface.

Experiment 2

Participants

Experiment 2 involved 22 right-handed, native English speakers (11 women, 11 men; mean age

29.1; range 20 to 41). None of the participants took part in Experiment 1. This dataset was

reported in a previous study (Fernandino et al., 2021).

Stimuli

Stimuli (see Supplementary Table 2) included 160 object nouns (40 each of animals, foods,

tools, and vehicles) and 160 event nouns (40 each of social events, verbal events, non-verbal

sound events, and negative events). Of the 320 concepts included in Experiment 2, 24 objects

and 9 events were also used in Experiment 1. Concept ratings on the same 65 experiential

domains used for the model in Experiment 1 were obtained for each concept using the same

crowd-sourcing methods as in Experiment 1.

Stimulus Presentation and Tasks

As in Experiment 1, words were presented visually in a fast event-related procedure with

variable inter-stimulus intervals, and the entire list was presented 6 times in random order over

three imaging sessions performed on separate days.

On each trial, a noun was displayed in white font on a black background for 500 ms,

followed by a 2.5-second blank screen. Each trial was followed by a central fixation cross with

variable duration between 1 and 3 s (mean = 1.5 s). Participants rated each noun according to

how often they encountered the corresponding entity or event in their daily lives, on a scale from

1 ("rarely or never") to 3 ("often"). This familiarity judgment task was designed to encourage

semantic processing of the word stimuli without emphasizing any particular semantic features or

dimensions. Participants indicated their response by pressing one of three buttons on a

response pad with their right hand. In contrast to Experiment 1, no reset task was used.

Each presentation of the 320 test words occurred over the course of 4 imaging runs.

Each session consisted of 2 presentations of the full list (8 runs).

MRI Data Acquisition and Processing

Images were acquired with a 3T GE Premier scanner at the Medical College of Wisconsin.

Structural imaging included a T1-weighted MPRAGE volume (FOV = 256 mm, 222 axial slices,

voxel size = 0.8 x 0.8 x 0.8 mm^3) and a T2-weighted CUBE acquisition (FOV = 256 mm, 222

sagittal slices, voxel size = 0.8 x 0.8 x 0.8 mm^3). T2*-weighted gradient-echo echoplanar images

were obtained for functional imaging using a simultaneous multi-slice sequence (SMS factor =

4, TR = 1500 ms, TE = 23 ms, flip angle = 50°, FOV = 208 mm, 72 axial slices, in-plane matrix =

104 x 104, voxel size = 2 x 2 x 2 mm^3). A pair of T2-weighted spin echo echo-planar scans (5

volumes each) with opposing phase-encoding directions was acquired before run 1, between

runs 4 and 5, and after run 8, to provide estimates of EPI geometric distortion in the phase-

encoding direction due to B0 inhomogeneities.

In addition to the preprocessing steps described above for Experiment 1, functional

images were also corrected for geometric distortion using AFNI's 3dQwarp, which implemented

non-linear transformations estimated from the paired T2-weighted spin echo images. As in

Experiment 1, each word was treated as a single regressor of interest and convolved with a

hemodynamic response function, resulting in 320 beta coefficient maps. Head motion vectors

were again included as regressors of no interest. Response time z-score on each trial of the

familiarity judgment task was also included as a covariate of no interest.

Surface-Based Searchlight Representational Similarity Analysis

RSA analysis, generation of group maps, and thresholding methods for Experiment 2 were

identical to those used for Experiment 1.

Hierarchical clustering based on neural similarity structure

Although the regions identified in Experiments 1 and 2 all show neural similarity structures that are correlated with the semantic model structure, it is possible that they vary somewhat in their information content. To investigate relative differences and similarities between the representational structure of the various regions identified in the RSAs, we performed hierarchical clustering analysis on the *neural* RDMs of these regions, as follows. First, the group maps from each experiment were thresholded at $p < .0005$ to separate minimally connected regions and highlight vertices with strong correlations to the semantic model. These maps were then overlapped to identify vertices common to both experiments. These steps resulted in 23 regions common to both analyses, which were used as regions of interest (ROIs) for the hierarchical clustering analysis. At the individual participant level, within each ROI, seed vertices with the highest correlation scores were combined iteratively until a set of approximately 100 voxels associated with these vertices was compiled. A neural RDM was then computed for each such voxel set, resulting in 23 RDMs for each individual. Pairwise RDM correlation was calculated for these 23 voxel sets at the individual level, resulting in a new 23 x 23 matrix in which each entry represented the correlation between neural RDMs of two ROIs. These matrices were then averaged across all 41 participants, and hierarchical clustering was implemented on this averaged matrix, excluding the diagonal. Ward's variance minimization algorithm was applied to calculate distances between clusters.

Results

Experiment 1. "Probe" trials requiring semantic forced-choice matching of 2 words with the preceding list word were presented after 10% of list words to encourage attention to the list words. One participant failed to provide responses on this task, probably due to inadequate instruction. For the remaining participants, the mean response rate was 95.5% (SD 4.2%), and mean accuracy was 82.1% (SD 7.0%). A perceptual "reset" task occurred after all list words

(and probe trials) with the aim of curtailing processing of the previous list word. The mean

response rate on this task was 98.9% (SD 2.5%), and mean accuracy was 96.1% (SD 4.6%).

Group-level searchlight RSA showed a bilateral, distributed network of regions where

neural similarity correlated with semantic similarity across the 242 list words (**Figure 2, left**).

Extensive temporal lobe involvement included much of the temporal pole, superior temporal

sulcus (STS) and middle temporal gyrus (MTG), and anterior fusiform and parahippocampal gyri

bilaterally. The inferior temporal gyrus (ITG) was also involved, more so on the left. Parietal lobe

involvement was mainly in the inferior parietal lobule, including angular and supramarginal gyri

(AG and SMG) bilaterally. Frontal lobe regions included the inferior frontal gyrus (IFG), much of

the superior frontal gyrus (SFG) laterally and medially, more restricted patches in the middle

frontal gyrus, and orbital frontal cortex bilaterally. Small regions of the precentral gyrus were

involved in both hemispheres, and there was substantial involvement of the right insula. On the

medial surface there was extensive involvement of the posterior cingulate gyrus and adjacent

precuneus bilaterally, and the rostral anterior cingulate cortex bilaterally.

Figure 2. Brain areas where similarity between the neural patterns evoked by concepts was

significantly correlated with concept similarity according to the semantic model. Results for

Experiment 1 (left) and Experiment 2 (right) are shown on dorsal, lateral, medial, and ventral

surface views. All results are significant at p < 0.001 and cluster corrected at α < 0.01. Colors

represent t values.

Experiment 2. The mean response rate on the familiarity judgment task was 98.6% (SD 2.3%).

Intra-individual consistency in familiarity ratings across the 6 repetitions of each word was

evaluated using intraclass correlations (ICCs) based on a single measurement, two-way mixed

effects model and the absolute agreement definition. Results suggested generally good overall

intra-individual agreement, with individual ICCs ranging from fair to excellent (mean ICC =

0.661, range: 0.438 – 0.858, all *p*s<0.00001) (Cicchetti, 1994). To examine consistency in

familiarity ratings across participants, responses to the 6 repetitions were first averaged within

individuals, and the ICC across participants was calculated using the consistency definition.

The resulting ICC of 0.595 (95% confidence interval [0.556, 0.635], p < .00001) suggested fair

to good inter-individual consistency.

As with Experiment 1, group-level searchlight RSA showed a bilateral, distributed

network of regions where neural similarity correlated with semantic similarity across the test

concepts (**Figure 1, right**). Most of these overlapped with those in Experiment 1, including

temporal pole, STS, MTG, AG, SMG, IFG, SFG, and posterior cingulate/precuneus (PCC)

bilaterally. Compared to Experiment 1, there was notably more extensive involvement of lateral

prefrontal cortex, including inferior and middle frontal gyri, bilaterally, and somewhat less

extensive ventral temporal lobe involvement. Areas of overlap between the two experiments are

shown in **Figure 3**.

Figure 3. Brain areas where neural similarity was significantly correlated with model similarity in both Experiment 1 and Experiment 2. LACC: left anterior cingulate cortex; LAG: left angular gyrus; LaSTG: left anterior superior temporal gyrus; LdPF: left dorsal prefrontal cortex; LIFG: left inferior frontal gyrus; LIPS: left intraparietal sulcus; LMT: left medial temporal lobe; LMTG: left middle temporal gyrus; LOFC: left orbital frontal cortex; LPCC: left posterior cingulate and precuneus cortex; LSMG: left supramarginal gyrus; LTP: left temporal pole; RAG: right angular gyrus; RaSTG: right anterior superior temporal gyrus; RdPF: right dorsal prefrontal cortex; RIFG: right inferior frontal gyrus; RIns: right insula; RMT: right medial temporal lobe; RMTG: right middle temporal gyrus; ROFC: right orbital frontal cortex; RPCC: right posterior cingulate and precuneus cortex; RSMG: right supramarginal gyrus; RTP: right temporal pole.

Hierarchical clustering of neural similarity structures. Overlap of the Experiment 1 and

Experiment 2 RSA maps showed 23 regions common to both (color-coded in **Figure 4, right**).

Degree of similarity between the neural RDMs extracted from each of these regions was

examined using hierarchical cluster analysis (**Figure 4, left**). The results revealed a division

between ROIs in the parietal lobe (PCC, AG, SMG, left intraparietal sulcus) and lateral temporal

lobe in one major cluster, and ROIs in the medial temporal lobe, temporal pole, and frontal lobes

in another major cluster. The parietal/lateral temporal cluster was further divided by hemisphere,

such that right AG, SMG, MTG, and anterior STG fell in one subcluster, and left parietotemporal

ROIs in another, along with left and right PCC. The other main cluster included a "limbic"

subcluster consisting of bilateral temporal poles, parahippocampus/hippocampus, and right

insula. A final subcluster included all frontal lobe ROIs and the left anterior STG.

Figure 4. Results of hierarchical clustering of neural similarity structures. Left: Dendrogram

based on the averaged similarity structures of neural data from 23 ROIs. The vertical axis

indicates linkage distance. Right: The 23 ROIs defined by overlapping the RSA maps from the

two experiments after thresholding each map at p < 0.0005 and cluster-correcting at α < 0.01.

Anatomical labels match those in Figure 3.

Discussion

We sought to clarify the large-scale architecture of the concept representation system by

identifying cortical regions whose activation patterns encoded multimodal experiential

information about individual lexical concepts. Previous whole-brain searchlight RSA studies on

this topic have used semantic representation models based on category membership, semantic

feature lists, or word co-occurrence statistics, producing highly variable results. Here we used a

model based entirely on multimodal experiential content with no explicit reference to taxonomic

or distributional similarity. Across two independent experiments, each involving a large number

and a wide range of concepts, we detected multimodal concept representation in widespread

heteromodal cortical regions, bilaterally, including anterior and posterior temporal cortex, inferior

parietal cortex, posterior cingulate gyrus and precuneus, and medial, dorsal, ventrolateral, and

ventral prefrontal regions. These results call into question the idea that information streams

originating in unimodal cortical areas are integrated at a single anatomically localized hub for

concept representation.

439   Four previous RSA studies using semantic models and word stimuli implicated

anteromedial temporal cortex, particularly perirhinal cortex, as a semantic hub (Devereux et al.,

2013; Liuzzi et al., 2015; Martin et al., 2018; Liuzzi et al., 2019). All used semantic models

based on crowd-sourced feature production lists, and all used a feature verification task during

fMRI (e.g., "WASP – Does it have paws?"). Validity issues with feature production lists have

been noted previously, such as the fact that many features people produce are multimodal or

highly abstract, and some types of features are difficult to verbalize or systematically ignored

(Hoffman and Lambon Ralph, 2013). Another potential problem with these RSA studies is that

the verification task used during fMRI requires semantic processing of the explicitly named

feature, which logically must contribute to the observed neural activation pattern but is not

coded in the semantic model. These problems may have weakened the ability of these studies

to detect other regions involved in concept representation.

Prior studies combining searchlight RSA with either taxonomic (Devereux et al., 2013;

Carota et al., 2021) or distributional (Anderson et al., 2015; Carota et al., 2021) semantic

models have implicated more widespread regions, including posterior lateral temporal cortex,

inferior parietal lobe, posterior cingulate gyrus, and prefrontal cortex. Only one of these studies

(Anderson et al., 2015) reported any representational correspondence in medial or ventral

temporal areas. The two studies using taxonomic models (Devereux et al., 2013; Carota et al.,

2021) showed similar involvement of the left posterior superior temporal sulcus and MTG, with

extension into adjacent AG and SMG. In contrast, the two studies using distributional models

(Anderson et al., 2015; Carota et al., 2021) found little or no posterior temporal involvement, and

inferior parietal involvement was confined mainly to the left SMG. Frontal cortex involvement

was uniformly present but highly variable in extent and location across the studies. Two studies

reported involvement of the posterior cingulate/precuneus (Devereux et al., 2013; Anderson et

al., 2015).

Several factors may have negatively impacted sensitivity and reliability in these studies.

First, ROI-based RSAs show that, relative to experiential models of concept representation,

taxonomic and distributional models are consistently less sensitive to the neural similarity

structure of lexical concepts (Fernandino et al., 2021). Furthermore, most of the prior studies

used volume-based spherical searchlights, which typically sample a mix of grey and white

matter voxels, while the surface-based approach used in the present study ensures that only

contiguous cortical gray matter voxels are included, thus reducing noise from uninformative

voxels. Finally, the nature of the task and the particularities of the concept set used as stimuli

can affect both the sensitivity of the analysis and the cortical distribution of the RSA searchlight

map, and variations in these properties may underlie some of the variation in results across

studies. We dealt with this issue by (1) employing large numbers of concepts from diverse

semantic categories and (2) by analyzing data from two independent experiments to identify

areas displaying reliable representational correspondence with the semantic model across

different concept sets and different tasks.

The network of brain regions identified in the current study closely resembles the

network identified previously in a meta-analysis of 120 functional imaging studies on semantic

processing (Binder et al., 2009). The results provide novel evidence that these brain regions,

consisting essentially of heteromodal association areas distant from primary sensory and motor

systems, represent conceptual information in terms of multimodal experiential content. In

contrast to previous RSA studies of concept representation (Devereux et al., 2013; Anderson et

al., 2015; Martin et al., 2018; Carota et al., 2021), the network includes extensive cortex in the

ATL, a region strongly implicated in high-level semantic representation (Lambon Ralph et al.,

2017). Although the current results support a role for the ATL in concept representation, they

argue against it having a unique role as a central integration hub.

The concept representation network identified in the current study also closely

resembles the set of brain regions referred to as the "default mode network" (Buckner et al.,

2008). This overlap supports the view that concept retrieval and manipulation are major

components of the brain's "default mode" of processing (Binder et al., 1999; Binder et al., 2009;

Andrews-Hanna et al., 2014). Our results add to prior evidence by showing that the

representational structure of neural activity in these regions reflects the experiential content of

lexical concepts.

The finding of extensive frontal lobe involvement in concept "representation" deserves

comment. Studies of brain damaged individuals and functional imaging experiments in the

healthy brain have long been interpreted as supporting the classic view that frontal cortex plays

an operational control rather than an information storage function in the brain (Stuss and

Benson, 1986; Kimberg and Farah, 1993; Thompson-Schill et al., 1997; Wagner et al., 2001).

Nevertheless, nearly all RSA studies of concept representation have observed similarity

structure correlations in prefrontal regions. Why would activity in these areas reflect semantic

content? We believe these observations can be reconciled with the classic view by postulating a

more fine-grained organization of control systems in the frontal lobe than is usually assumed in

semantic theories. Rather than being composed of large, homogeneous areas with a

nonspecific control function, control systems in the prefrontal cortex may be tuned, at a

relatively small scale, to particular sensory-motor and affective features. Neurophysiological

studies in nonhuman primates provide evidence for tuning of prefrontal neurons to preferred

stimulus modalities (Romanski, 2007), as well as differential connectivity across the prefrontal

cortex with various sensory systems (Barbas and Mesulam, 1981; Petrides, 2005). A few

human functional imaging studies provide similar evidence for sensory modality tuning in

prefrontal cortex (Greenberg et al., 2010; Michalka et al., 2015; Tobyne et al., 2017). If

conceptual representation in temporal and parietal cortex is inherently organized according to

experiential content, it seems plausible that controlled activation and short-term maintenance of

this information would require similarly fine-grained control mechanisms.

This hypothesis finds some support in a comparison of our two experiments. The

infrequent probe task procedure used in Experiment 1 was intentionally designed to minimize

explicit, goal-directed retrieval of semantic information, and the inclusion of a non-semantic

perceptual discrimination task after each trial likely encouraged participants to focus their

attention on this task rather than on semantic retrieval. In contrast, the task in Experiment 2

required participants to make a semantic decision about each word. Compared to Experiment 1,

the Experiment 2 results show much more extensive involvement of lateral prefrontal cortex. A

likely interpretation is that the explicit task in Experiment 2 led to stronger engagement of

feature-specific control networks in these frontal regions. We propose that the information

represented in these prefrontal regions reflects their entrainment to experiential representations

stored primarily in temporoparietal cortex, providing context-dependent control over their level of

activation.

Related to this issue is the question of how similar the many regions identified by RSA

are to each other in terms of their representational structure. Although RSA ensures that the

neural similarity structure of all these regions is related to the similarity structure encoded in the

semantic model, representational structure should be expected to vary to some degree across

distinct functional regions. An exploratory cluster analysis of the neural RDMs from these

regions suggests a broad distinction between two clusters, one consisting of medial and lateral

parietal cortex and posterior lateral temporal areas (across both hemispheres) and the other

consisting of medial, ventral, and anterior temporal areas, right insula, and frontal areas. There

was also evidence for a distinction between left and right parietotemporal representational

structures. These results are consistent with proposed distinctions between the functions of

frontal, posterior association, and limbic cortices, as well as longstanding claims regarding

interhemispheric differences in semantic representation (Beeman and Chiarello, 1998).

Interestingly, this analysis suggests that representations in the ATL are more similar to those in

prefrontal areas than to those in posterior temporal and parietal areas involved in the

representation of objects and events (Martin, 2007; Bedny et al., 2014). More research is

needed to understand the factors that underlie these regional differences in representational

content.

References

Andersen RA (1997) Multimodal integration for the representation of space in the posterior parietal

       cortex. Philos Trans R Soc Lond B Biol Sci 352:1421-1428.

Anderson AJ, Bruni E, Lopopolo A, Poesio M, Baroni M (2015) Reading visually embodied meaning from

       the brain: Visually grounded computational models decode visual-object mental imagery

       induced by written text. Neuroimage 120:309-322.

Anderson AJ, Binder JR, Fernandino L, Humphries CJ, Conant LL, Raizada RDS, Lin F, Lalor EC (2019) An

       integrated neural decoder of linguistic and experiential meaning. J Neurosci 39:8969-8987.

Anderson AJ, Binder JR, Fernandino L, Humphries CJ, Conant LL, Aguilar M, Wang X, Doko D, Raizada RDS

       (2017) Predicting neural activity patterns associated with sentences using a neurobiologically

       motivated model of semantic representation. Cereb Cortex 27:4379-4395.

Andrews-Hanna JR, Smallwood J, Spreng RN (2014) The default network and self-generated thought:

       Component processes, dynamic control, and clinical relevance. Ann N Y Acad Sci 1316:29-52.

Barbas H, Mesulam MM (1981) Organization of afferent input to subdivisions of area 8 in the rhesus

       monkey. J Comp Neurol 200:407-431.

Barsalou LW (2008) Grounded cognition. Annu Rev Psychol 59:617-645.

Beauchamp MS, Yasar NE, Frye RE, Ro T (2008) Touch, sound and vision in human superior temporal

       sulcus. Neuroimage 41:1011-1020.

Bedny M, Dravida S, Saxe R (2014) Shindigs, brunches, and rodeos: The neural basis of event words.

       Cogn Affect Behav Neurosci 14:891-901.

Beeman M, Chiarello C (1998) Right hemisphere language comprehension: Perspectives from cognitive

       neuroscience: Psychology Press.

Binder JR, Desai RH (2011) The neurobiology of semantic memory. Trends Cogn Sci 15:527-536.

Binder JR, Desai RH, Graves WW, Conant LL (2009) Where is the semantic system? A critical review and

meta-analysis of 120 functional neuroimaging studies. Cereb Cortex 19:2767-2796.

Binder JR, Frost JA, Hammeke TA, Bellgowan PS, Rao SM, Cox RW (1999) Conceptual processing during

the conscious resting state. A functional MRI study. J Cogn Neurosci 11:80-95.

Binder JR, Conant LL, Humphries CJ, Fernandino L, Simons SB, Aguilar M, Desai RH (2016) Toward a

brain-based componential semantic representation. Cogn Neuropsychol 33:130-174.

Bonner MF, Peelle JE, Cook PA, Grossman M (2013) Heteromodal conceptual processing in the angular

gyrus. Neuroimage 71:175-186.

Bruce C, Desimone R, Gross CG (1981) Visual properties of neurons in a polysensory area in superior

temporal sulcus of the macaque. J Neurophysiol 46:369-384.

Buckner RL, Andrews-Hanna JR, Schacter DL (2008) The brain's default network: Anatomy, function, and

relevance to disease. Ann N Y Acad Sci 1124:1-38.

Carota F, Nili H, Pulvermuller F, Kriegeskorte N (2021) Distinct fronto-temporal substrates of

distributional and taxonomic similarity among words: Evidence from rsa of bold signals.

Neuroimage 224:117408.

Damasio AR (1989) Time-locked multiregional retroactivation: A systems-level proposal for the neural

substrates of recall and recognition. Cognition 33:25-62.

Damasio AR, Damasio H, Van Hoesen GW (1982) Prosopagnosia: Anatomic basis and behavioral

mechanisms. Neurology 32:331-341.

Devereux BJ, Clarke A, Marouchos A, Tyler LK (2013) Representational similarity analysis reveals

commonalities and differences in the semantic processing of words and objects. J Neurosci

33:18906-18916.

Fernandino L, Conant LL, Humphries CJ, Binder JR (2021) Decoding the information structure underlying

the neural representation of concepts. bioRxiv:2021.2003.2016.435524.

Fernandino L, Humphries CJ, Conant LL, Seidenberg MS, Binder JR (2016a) Heteromodal cortical areas

encode sensory-motor features of word meaning. J Neurosci 36:9763-9769.

Fernandino L, Binder JR, Desai RH, Pendl SL, Humphries CJ, Gross WL, Conant LL, Seidenberg MS (2016b)

Concept representation reflects multimodal abstraction: A framework for embodied semantics.

Cereb Cortex 26:2018-2034.

Glasser MF, Sotiropoulos SN, Wilson JA, Coalson TS, Fischl B, Andersson JL, Xu J, Jbabdi S, Webster M,

Polimeni JR, Van Essen DC, Jenkinson M, Consortium WU-MH (2013) The minimal preprocessing

pipelines for the human connectome project. Neuroimage 80:105-124.

Glenberg AM, Webster BJ, Mouilso E, Havas D, Lindeman LM (2009) Gender, emotion, and the

embodiment of language comprehension. 1:151-161.

Greenberg AS, Esterman M, Wilson D, Serences JT, Yantis S (2010) Control of spatial and feature-based

attention in frontoparietal cortex. J Neurosci 30:14330-14339.

Hoffman P, Lambon Ralph MA (2013) Shapes, scents and sounds: Quantifying the full multi-sensory basis

of conceptual knowledge. Neuropsychologia 51:14-25.

Jones EG, Powell TP (1970) An anatomical study of converging sensory pathways within the cerebral

cortex of the monkey. Brain 93:793-820.

Kemmerer DL (2014) Cognitive neuroscience of language. New York, NY: Psychology Press.

Kiefer M, Pulvermuller F (2012) Conceptual representations in mind and brain: Theoretical

developments, current evidence and future directions. Cortex 48:805-825.

Kimberg DY, Farah MJ (1993) A unified account of cognitive impairments following frontal lobe damage:

The role of working memory in complex, organized behavior. J Exp Psychol Gen 122:411-428.

Kriegeskorte N, Mur M, Bandettini P (2008) Representational similarity analysis - connecting the

branches of systems neuroscience. Front Syst Neurosci 2:4.

Lambon Ralph MA, Jefferies E, Patterson K, Rogers TT (2017) The neural and computational bases of

semantic cognition. Nat Rev Neurosci 18:42-55.

Liuzzi AG, Dupont P, Peeters R, Bruffaerts R, De Deyne S, Storms G, Vandenberghe R (2019) Left

perirhinal cortex codes for semantic similarity between written words defined from cued word

association. Neuroimage 191:127-139.

Liuzzi AG, Bruffaerts R, Dupont P, Adamczuk K, Peeters R, De Deyne S, Storms G, Vandenberghe R (2015)

Left perirhinal cortex codes for similarity in meaning between written words: Comparison with

auditory word input. Neuropsychologia 76:4-16.

Mahon BZ, Caramazza A (2008) A critical look at the embodied cognition hypothesis and a new proposal

for grounding conceptual content. J Physiol Paris 102:59-70.

Man K, Kaplan J, Damasio H, Damasio A (2013) Neural convergence and divergence in the mammalian

cerebral cortex: From experimental neuroanatomy to functional neuroimaging. J Comp Neurol

521:4097-4111.

Man K, Damasio A, Meyer K, Kaplan JT (2015) Convergent and invariant object representations for sight,

sound, and touch. Hum Brain Mapp 36:3629-3640.

Martin A (2007) The representation of object concepts in the brain. Annu Rev Psychol 58:25-45.

Martin CB, Douglas D, Newsome RN, Man LL, Barense MD (2018) Integrative and distinctive coding of

visual and conceptual object features in the ventral visual stream. Elife 7.

Mesulam MM (1998) From sensation to cognition. Brain 121 (Pt 6):1013-1052.

Meteyard L, Vigliocco G (2008) 15 - the role of sensory and motor information in semantic

representation: A review. In: Handbook of cognitive science (Calvo P, Gomila A, eds), pp 291-

312. San Diego: Elsevier.

Meyer K, Damasio A (2009) Convergence and divergence in a neural architecture for recognition and

memory. Trends Neurosci 32:376-382.

Michalka SW, Kong L, Rosen ML, Shinn-Cunningham BG, Somers DC (2015) Short-term memory for space

and time flexibly recruit complementary sensory-biased frontal lobe attention networks. Neuron

87:882-892.

Oldfield RC (1971) The assessment and analysis of handedness: The edinburgh inventory.

Neuropsychologia 9:97-113.

Padberg J, Seltzer B, Cusick CG (2003) Architectonics and cortical connections of the upper bank of the

superior temporal sulcus in the rhesus monkey: An analysis in the tangential plane. J Comp

Neurol 467:418-434.

Patterson K, Nestor PJ, Rogers TT (2007) Where do you know what you know? The representation of

semantic knowledge in the human brain. Nat Rev Neurosci 8:976-987.

Petrides M (2005) Lateral prefrontal cortex: Architectonic and functional organization. Philos Trans R Soc

Lond B Biol Sci 360:781-795.

Romanski LM (2007) Representation and integration of auditory and visual stimuli in the primate ventral

lateral prefrontal cortex. Cereb Cortex 17 Suppl 1:i61-69.

Sepulcre J, Sabuncu MR, Yeo TB, Liu H, Johnson KA (2012) Stepwise connectivity of the modal cortex

reveals the multimodal organization of the human brain. J Neurosci 32:10649-10661.

Stuss DT, Benson DF (1986) The frontal lobes. New York: Raven Press.

Sugihara T, Diltz MD, Averbeck BB, Romanski LM (2006) Integration of auditory and visual

communication information in the primate ventrolateral prefrontal cortex. J Neurosci 26:11138-

11147.

Thompson-Schill SL, D'Esposito M, Aguirre GK, Farah MJ (1997) Role of left inferior prefrontal cortex in

retrieval of semantic knowledge: A reevaluation. Proc Natl Acad Sci U S A 94:14792-14797.

Tobyne SM, Osher DE, Michalka SW, Somers DC (2017) Sensory-biased attention networks in human

lateral frontal cortex revealed by intrinsic functional connectivity. Neuroimage 162:362-372.

Van Hoesen GW, Pandya DN, Butters N (1972) Cortical afferents to the entorhinal cortex of the rhesus

monkey. Science 175:1471-1473.

Wagner AD, Pare-Blagoev EJ, Clark J, Poldrack RA (2001) Recovering meaning: Left prefrontal cortex

guides controlled semantic retrieval. Neuron 31:329-338.

Figure Legends

Figure 1. Schematic illustration of the tasks used in Experiment 1.

Figure 2. Brain areas where similarity between the neural patterns evoked by concepts was

significantly correlated with concept similarity according to the semantic model. Results for

Experiment 1 (left) and Experiment 2 (right) are shown on dorsal, lateral, medial, and ventral

surface views. All results are significant at p < 0.001 and cluster corrected at α < 0.01. Colors

represent t values.

Figure 3. Brain areas where neural similarity was significantly correlated with model similarity in

both Experiment 1 and Experiment 2. LACC: left anterior cingulate cortex; LAG: left angular

gyrus; LaSTG: left anterior superior temporal gyrus; LdPF: left dorsal prefrontal cortex; LIFG: left

inferior frontal gyrus; LIPS: left intraparietal sulcus; LMT: left medial temporal lobe; LMTG: left

middle temporal gyrus; LOFC: left orbital frontal cortex; LPCC: left posterior cingulate and

precuneus cortex; LSMG: left supramarginal gyrus; LTP: left temporal pole; RAG: right angular

gyrus; RaSTG: right anterior superior temporal gyrus; RdPF: right dorsal prefrontal cortex;

RIFG: right inferior frontal gyrus; RIns: right insula; RMT: right medial temporal lobe; RMTG:

right middle temporal gyrus; ROFC: right orbital frontal cortex; RPCC: right posterior cingulate

and precuneus cortex; RSMG: right supramarginal gyrus; RTP: right temporal pole.

Figure 4. Results of hierarchical clustering of neural similarity structures. Left: Dendrogram

based on the averaged similarity structures of neural data from 23 ROIs. The vertical axis

indicates linkage distance. Right: The 23 ROIs defined by overlapping the RSA maps from the

two experiments after thresholding each map at p < 0.0005 and cluster-correcting at α < 0.01.

Anatomical labels match those in Figure 3.

Supplementary Materials

Adjective		Verb		Noun				
aggressive	soft	approached	left	accident	coffee	flower	office	team
angry	spiritual	arrested	liked	activist	commander	football	parent	television
big	tired	ate	listened	actor	company	forest	park	terrorist
black	used	blocked	lived	agreement	computer	girl	party	theater
blue	wealthy	bought	lost	airport	corn	glass	patient	ticket
clever	white	broke	marched	army	council	guard	pencil	tourist
cold	yellow	built	met	artist	couple	hall	pilot	tree
dangerous	young	carried	negotiated	author	court	highway	plane	trial
dark		celebrated	opened	ball	criminal	horse	policeman	vacation
dead		crossed	planned	banker	debate	hospital	politician	victim
dusty		damaged	played	baseball	desk	hotel	priest	voter
empty		delivered	put	beach	dime	hurricane	prison	water
expensive		destroyed	ran	bed	dinner	island	protest	window
famous		drank	read	bicycle	diplomat	journalist	reporter	winter
friendly		drew	saw	bird	doctor	judge	restaurant	witness
green		dropped	shouted	boat	dog	jury	river	woman
happy		ended	slept	book	door	lab	school	worker
heavy		feared	spoke	boy	driver	lake	scientist	
hot		fed	stayed	bread	duck	lawyer	soccer	
injured		fixed	stole	bridge	editor	magazine	soldier	
lonely		flew	survived	businessman	egg	man	spring	
long		found	threw	cabinet	election	mayor	stone	
loud		gave	took	camera	embassy	medicine	store	
new		grew	used	car	engineer	meeting	storm	
old		held	visited	cash	family	minister	street	
peaceful		helped	walked	cellphone	farmer	mob	student	
powerful		hiked	wanted	chair	feather	morning	summer	
red		interviewed	watched	chicken	fence	mountain	sun	
shiny		kicked	went	child	field	mouse	table	
sick		landed	worked	church	fish	newspaper	tea	
small		laughed	wrote	cloud	flood	night	teacher	

Supplementary table. 1. Words for experiment 1

Event				Object			
Negative	Nonverbal	Social	Verbal	Animal	Food/Plant	Tool	Vehicle
avalanche	chuckle	bash	lecture	hippopotamus	chestnut	scissors	ferry
battle	squeal	parade	eulogy	fish	ketchup	dime	ambulance
blizzard	screaming	conference	tribute	ant	cranberry	candle	train
bombing	sizzle	rally	deposition	goldfish	flower	stapler	automobile
brawl	screeching	party	showdown	turtle	raspberry	rake	boat
cyclone	applause	tournament	protest	tiger	custard	spatula	bobsled
downpour	siren	gathering	compliment	jackal	sauerkraut	umbrella	skateboard
drought	crescendo	musical	greeting	cricket	mushroom	axe	carriage
earthquake	snap	cruise	testimony	butterfly	pudding	crutches	helicopter
epidemic	growling	wedding	discourse	mosquito	ham	comb	barge
explosion	sneeze	convention	praise	chameleon	honey	tongs	tricycle
famine	boom	circus	rebuke	horse	lemonade	anchor	wagon
flood	thumping	pageant	rebuttal	salmon	tomato	ladle	sled
gunshot	shrieking	luncheon	dispute	alligator	chocolate	sandpaper	motorcycle
gust	sobbing	outing	comment	trout	banana	book	jeep
hail	clattering	jubilee	commemoration	chimpanzee	cider	faucet	van
hailstorm	gulp	expo	denial	chicken	broccoli	pencil	bus
hurricane	whine	reception	trial	duck	pumpkin	glass	plane
inferno	whimpering	banquet	huddle	baboon	bread	hoe	tractor
invasion	melody	reunion	advice	lion	cheese	fork	steamer
landslide	hiccup	dance	quarrel	mouse	champagne	camera	car
lightning	murmuring	feast	thanks	caterpillar	spaghetti	binoculars	rowboat
monsoon	roaring	safari	interrogation	hawk	eggplant	straw	taxi
murder	sigh	celebration	joke	moose	dandelion	calculator	convertible
outbreak	squeaking	fair	plea	snake	egg	stethoscope	streetcar
plague	wheezing	expedition	class	octopus	pineapple	corkscrew	limousine
raid	rumble	concert	recitation	dog	cucumber	cash	glider
riot	bang	symphony	dictation	hamster	milk	handsaw	truck
shooting	giggle	cookout	debate	cardinal	mustard	magazine	rocket
squall	reverberation	contest	sermon	penguin	tobacco	football	canoe
stampede	crackle	carnival	rant	whale	bean	microscope	locomotive
storm	rustle	festival	lesson	crow	jam	hammer	trolley
tempest	thunderclap	housewarming	threat	turkey	blueberry	thermometer	bicycle
thunderstorm	jingle	fiesta	wisecrack	elephant	asparagus	baseball	sleigh
tornado	clapping	march	grievance	bison	nectarine	keyboard	subway
twister	chattering	christening	complaint	cheetah	coffee	key	escalator
volcano	bellowing	prom	apology	rhinoceros	beer	ticket	sailboat
war	grunt	cocktails	commentary	chipmunk	cherry	newspaper	elevator
whirlwind	laughter	picnic	meeting	monkey	plant	hairbrush	submarine
wildfire	groaning	tour	squabble	dolphin	carrot	skillet	scooter

699 **Supplementary table. 2.** Words for experiment 2