Yuel: Compound-Protein Interaction Prediction with High Generalizability

Jian Wang[1] and Nikolay V. Dokholyan[1,2,3,4,*]

[1]Department of Pharmacology, Penn State College of Medicine, Hershey, PA 17033, USA.

[2]Department of Biochemistry & Molecular Biology, Penn State College of Medicine, Hershey, PA 17033, USA.

[3]Department of Chemistry, Pennsylvania State University, University Park, PA 16802, USA.

[4]Department of Biomedical Engineering, Pennsylvania State University, University Park, PA 16802, USA.

[#] These authors contributed equally to this work.

* Correspondence: E-mail: dokh@psu.edu, Tel: (717) 531-5177.

Keywords: neural network, compound-protein interaction, attention

ABSTRACT

Virtual drug screening has the potential to revolutionize the stagnant drug discovery field due to its low cost and fast speed. Predicting binding affinities between small molecules and the protein target is at the core of computational drug screening. Deep learning-based approaches have recently been adapted to predict binding affinities and claim to achieve high prediction accuracy in their tests, however, we show that current approaches are not reliable for virtual drug screening due to the lack of generalizability, i.e. the ability to predict interactions between unknown proteins and unknown small molecules. To address this shortcoming, we develop a compound-protein interaction predictor, Yuel. Upon comprehensive tests on various datasets, we find that out of all the deep-learning approaches surveyed, only Yuel can predict interactions between unknown compounds and unknown proteins. Additionally, Yuel can also be utilized to identify compound atoms and proteins residues that are involved in the binding.

INTRODUCTION

Drug discovery[1] has strongly benefited from virtual drug screening[2] techniques based on either

molecular docking[3–6] of a library of compounds to a target protein, or cheminformatics-based

approaches that utilize machine learning to derive knowledge from known binders to this target.

Yet, molecular docking is usually time-consuming, while cheminformatics-based approaches[7]

suffer from low accuracy when no ligand for a given target is known. Recently, deep learning has

been widely applied to various areas in biology and is seemingly heralding a trend to supersede

traditional methods due to its unparalleled performance, e.g., AlphaFold2[8] has stunned the protein

structure communication by sweeping the biennial protein 3D structure prediction competition,

CASP (the critical assessment of protein structure prediction)[9]. In the virtual drug screening field,

several deep learning-based neural networks[10–13] have emerged aiming at predicting compound-

protein interaction (CPI), such as DeepDTA[10], DeepConv-DTI[11], DeepAffinity[12], and MONN[13].

However, considering that the chemical space of potential drugs may be as large as 10^{60} small

molecules[14] and the human proteome consist of millions of protein species[15,16], a natural question

that arises is whether current neural network models are reliable for drug virtual screening when

training on a tiny dataset: typical compound-protein affinity datasets, such as the Davis[17] and the

PDBbind[18] datasets, only contain ten thousand to hundred thousand affinity data. Unfortunately,

we evaluate current methods and find that most are merely memorizing the inputs and outputs,

thus lacking the ability to predict the interaction between unknown compounds and unknown

proteins, which we refer to as generalizability. Here, we develop a new compound-protein

interaction predictor, *Yuel* (Figure 1A), which predicts CPI with high generalizability. Upon

comprehensive tests on various datasets, Yuel is the only method that can predict interactions

between unknown compounds and unknown proteins.

RESULTS & DISCUSSION

Yuel predicts compound-protein interaction with high generalizability

We train and test Yuel and two other neural networks, DeepDTA[10] and DeepConv-DTI[11], on two

datasets (PDBbind[18] and Davis[17]). We do not compare Yuel to DeepDTA and DeepConv-DTI

because MONN needs specific pairwise interactions between atoms in compounds and residues

in proteins for training and DeepAffinity does not provide convenient utilities for training with

custom datasets. We divide each of the two datasets into a training set and a test set at a ratio of

8 to 2, resulting in four datasets (Davis/train, Davis/test, PDBbind/train, PDBbind/test). Cross-

validation is not performed because we will use independent datasets for testing. We first train

Yuel, DeepDTA, and DeepConv-DTI on the training set (Davis/train and PDBbind/train) and test

them on the corresponding test set (Davis/test and PDBbind/test). By training on Davis/train, the

Spearman correlation between the experimental affinities and predicted affinities (Figure 1B) of

Yuel, DeepDTA, and DeepConv-DTI on Davis/test are 0.65, 0.63, and 0.55, respectively; by

training on PDBbind/train, the Spearman correlation on PDBbind/test are 0.76, 0.76, and 0.68,

respectively. All three methods demonstrate high predictive values, with the performance of Yuel

and DeepDTA demonstrating similar performance which is slightly higher than DeepConv-DTI.

However, this significant result for all three neural networks is not surprising as the training and

test sets are sourced from the same dataset, thus many proteins and compounds are shared

between the training set and the test set.

To evaluate the neural networks' ability to predict interactions between unknown proteins and

unknown compounds, we train the models on Davis and test them on PDBBind. Compounds and

proteins are dissimilar in these two datasets (Figure 1C&1D), so PDBbind can be used as an

independent dataset when training on Davis. Further, Davis has far less proteins (379) and

compounds (68) than PDBbind (proteins: 10251; compounds: 2509). We find the Spearman

correlations of *Yuel*, DeepDTA, and DeepConv-DTI are 0.489, 0.054, and -0.015 respectively,

suggesting that DeepDTA, and DeepConv-DTI cannot predict the interaction between unknown

proteins and unknown compounds, while *Yuel* can. Therefore, Yuel can predict a large number

of interactions between unknown proteins and unknown compounds by training on a small

number of dissimilar proteins and dissimilar compounds, thus showing its high generalizability.

We further train the three models on Davis and test them on a third dataset Metz[19]. The Metz

dataset contains interactions of 172 different protein kinases and more than 3800 compounds.

Yuel still outperforms DeepDTA and DeepConv-DTI in terms of the Spearman correlation (Figure

S1).

Yuel addresses the memorizing issue that exists in other neural network models

To test if networks are purely memorizing protein sequences or compound structures, we use

PDBbind/train for training, but then shuffle the residues of each protein sequence in PDBbind/test

for testing. Thus, the new protein sequences in the shuffled set are all chimeric and not supposed

to bind to the compounds. However, we find that the shuffling does not significantly affect the

performance of DeepDTA and DeepConv-DTI (Spearman correlation is 0.7 and 0.6, respectively)

(Figure 2). On the contrary, *Yuel*'s predictions fall drastically to a Spearman correlation of 0.2

(Figure 2A), in line with expectations. Thus, DeepDTA and DeepConv-DTI are essentially

predicting CPI by memorizing the compound structures. The memorization characteristic of

DeepDTA and DeepConv-DTI may be due to the low completeness (see Methods) of the PDBbind
dataset: each affinity data is nearly distinctly corresponding to only one compound. However, Yuel
does not exhibit this memorization characteristic when training on the same dataset. Thus, we
speculate that the memorization characteristic is mainly due to the inherent deficiencies of the
network architecture. Yuel is equipping with fully-connected (FC) layers that share weights
between different compound atoms and protein residues, which we refer to as feature-wise FC
layers (see Methods and Figure 3B); other neural networks employ regular FC layers that operate
the entire concatenated compound-protein feature matrix, which we refer to as position-wise FC
layers (see Methods and Figure 3A). Networks with position-wise FC layers may predict CPI by
memorizing the inputs by only optimizing the weights that representing atom-atom interactions in
the compound (W_{CC}) or residue-residue interactions (W_{PP}) in the protein instead of atom-residue
interactions (W_{CP} and W_{PC}) (see Methods).

To further compare feature-wise FC layers and position-wise FC layers, we create a new version
of Yuel by using the position-wise FC layers (Figure S2). We refer to this version of Yuel as Yuel-
cc (concatenated version of Yuel). We train and test Yuel-cc on Davis and PDBbind datasets. We
find that the Spearman coefficients of Yue-cc are 0.56 and 0.73 in the Davis and PDBbind
datasets, respectively (Figure 3C&3D). However, if we train Yue-cc on Davis but test it on
PDBbind, the Spearman coefficient is 0.11 (Figure 3E). Thus, by using the position-wise FC layers,
Yuel-cc loses the generalizability.

Identifying hotspot atoms and hotspot residues

When encoding the protein feature matrix, each row corresponds to a residue, and each column
corresponds to a specific feature. Similarly, each row of the compound feature matrix corresponds
to an atom, and each column corresponds to a feature of the atom. Yuel calculates the outer
product of the compound feature matrix by the protein feature matrix to obtain an attention matrix,
thus, each element of the attention matrix corresponds to the interaction between a compound
atom and a protein residue. Therefore, by comparing the values of different rows in the attention
matrix, we can compare the probability of different compound atoms interacting with the protein
so as to find the atoms most likely to bind the protein, which we refer to as hotspot atoms; similarly,
we refer to residues that are most likely to interact with compounds as hotspot residues. Since
different compound atoms have different predicted interactions with different residues (Figure 4A),
we adopt a strategy of adding up the interactions of an atom to all residues as the possibility that
this atom is a hotspot atom. This strategy results in an average AUC of 0.58 (Figure 4B) for
PDBbind. Similarly, the predicted interactions of most hotspot residues are ranked within 30

(Figure 4C). Particularly, for 2IHQ, Yuel can predict 9 out of the 11 hotspot atoms (Figure 4D&4E)

and 11 out of the 18 hotspot residues (Figure 4F).

METHODS

The Architecture of Yuel

Yuel requires two inputs to estimate interactions between a specific compound and the protein

target: (i) compound's 2D structure (SMILES[20] or INCHI[21] code) and (ii) protein's amino acid

sequence. Given the protein sequence, *Yuel* first encodes it using BLOSUM62 matrix[22]. Each

residue corresponds to a column in the BLOSUM62 matrix. The features of non-standard amino

acids are zero-initialized. Then, the protein features are updated through three 1-D convolution

layers. The sequence is zero-padded to a fixed length of 2048. Given the SMILES of the

compound, *Yuel* first employs rdkit[23] to represent it by a graph (*N, V, E*), where *N* is the number

of nodes, *V* is the feature vector of each atom, and *E* is the feature vector of each bond. The

feature of each atom is the concatenation of the one-hot encoding of atom type, number of bonds,

bond type, mass, and charge vectors. The feature of each bond is the bond order. The graph is

then subject to two graph convolution layers to update the features. The protein features and the

compound features are then subject to 5 feature-wise fully-connected layers, separately.

Following the fully-connected layers, the protein feature matrix and the compound feature matrix

are then multiplied to obtain an attention matrix. Each row of the attention matrix corresponds to

a compound atom, and each column corresponds to a protein residue. The maximum value of

each column is then selected and added up to get the final predicted CPI. We implement this

network using TensorFlow 2.3.1[24] and Sonnet 2. The GNN is implemented by the *graph_nets*[25]

library.

Position-wise fully-connected layers and feature-wise fully-connected layers

The major difference between Yuel and other neural network models lies in the fully-connected

layers. In other neural network models, such as DeepDTA and DeepConv-DTI, the CPI is

predicted by a function of the concatenated compound-protein feature matrix (Equation (1)):

$$P_{aff} = f(B) = f(WA)$$

$$= f\left(\begin{bmatrix} W_{CC} & W_{CP} \\ W_{PC} & W_{PP} \end{bmatrix}\begin{bmatrix} A(C) \\ A(P) \end{bmatrix}\right)$$

$$= f\left(\begin{bmatrix} \omega_{11} & \cdots & \omega_{1k} & \omega_{1(k+1)} & \cdots & \omega_{1n} \\ \cdots & \cdots & \cdots & \cdots & \cdots & \cdots \\ \omega_{k1} & \cdots & \omega_{kk} & \omega_{k(k+1)} & \cdots & \omega_{kn} \\ \omega_{(k+1)1} & \cdots & \omega_{(k+1)k} & \omega_{(k+1)(k+1)} & \cdots & \omega_{(k+1)n} \\ \cdots & \cdots & \cdots & \cdots & \cdots & \cdots \\ \omega_{n1} & \cdots & \omega_{nk} & \omega_{n(k+1)} & \cdots & \omega_{nn} \end{bmatrix}\begin{bmatrix} A_1 \\ \cdots \\ A_k \\ A_{k+1} \\ \cdots \\ A_n \end{bmatrix}\right) \qquad (1)$$

where B is the concatenated compound-protein feature matrix; W is the weight matrix of the FC
layer; $A(C)$ is the compound feature matrix before the FC layers; $A(P)$ is the protein feature matrix
before the FC layer; A is the concatenated compound-protein feature matrix before the FC layer;
W_{CC} is the weight matrix for atom-atom interactions in the compound; W_{PP} is the weight matrix for
residue-residue interactions in the protein; W_{CP} and W_{PC} are the weight matrices for compound-
protein interactions; ω_{ij} is the weight between A_i and A_j; A_1, A_2, …, and A_k are the features of
compound atoms before FC layers; A_{k+1}, A_{k+2}, …, and A_n are the features of protein residues
before FC layers. Importantly, the FC layer is applied directly to the concatenated compound-
protein feature matrix, and the weight vector ω_{ij} of the FC layer is dependent on the position i
and j of the compound atom ($i, j \leq k$) or protein residue ($i, j > k$). Thus, we refer to this kind of FC
layer as position-wise FC layer (Figure 3A).

In Yuel, the CPI is predicted by a function of the outer product of the compound feature matrix
and the protein feature matrix (Equation (2)).

$$P_{aff} = f\big(B(C) \otimes B(P)\big)$$

$$= f\left(\begin{bmatrix} B_1^T B_{k+1} & \cdots & B_1^T B_n \\ \cdots & \cdots & \cdots \\ B_k^T B_{k+1} & \cdots & B_k^T B_n \end{bmatrix}\right)$$

$$= f\left(\begin{bmatrix} (\omega(C)A_1)^T\omega(P)A_{k+1} & \cdots & (\omega(C)A_1)^T\omega(P)A_n \\ \cdots & \cdots & \cdots \\ (\omega(C)A_k)^T\omega(P)A_{k+1} & \cdots & (\omega(C)A_k)^T\omega(P)A_n \end{bmatrix}\right) \qquad (2)$$

where P_{aff} is the predicted affinity; $B(C)$ is the final compound feature matrix; $B(P)$ is the final
protein feature matrix; B_1, B_2, …, and B_k are the features of compound atoms; B_{k+1}, B_{k+2}, …, B_n
are the features of protein residues; $\omega(C)$ is the weight matrix for the compound; $\omega(P)$ is the
weight matrix for the protein; the outer product is calculated by treating the compound feature
matrix and the protein feature matrix as vectors with each element as a vector of the features of

a specific compound atom or protein residue. Crucially, the compound feature matrix ($B(C)$) and

the protein feature matrix ($B(P)$) are processed by FC layers, i.e. $\omega(C)$ and $\omega(P)$, separately. The

weight vector $\omega(C)$ of the compound FC layers is not dependent on the position of compound

atoms and it is the same for all compound atoms; similarly, the weight vector $\omega(P)$ of the protein

FC layers is the same for all protein residues. Thus, we refer to these FC layers as feature-wise

FC layers (Figure 3B).

There are three advantages of feature-wise FC layers compared to position-wise FC layers. First,

the weights in position-wise FC layers are dependent on the position of atoms and residues.

However, when predicting CPI, the protein sequence may lack some residues, which changes

the positions of residues, and the position of atoms in the compound may also be different if using

a different encoding algorithm. Thus, the position-wise FC layers may result in different affinities

for the same compound and the same protein. Second, most parameters of the weight matrix of

the position-wise FC layers are focused on atom-atom interactions in the compound (W_{CC}) and

residue-residue interactions in the protein (W_{PP}), while atom-residue interactions (W_{CP} and W_{PC})

are the critical ones for determining CPI, thus, the position-wise FC layers may make the network

inclined to memorize the 2D structure of the small molecule and the sequence of the protein by

optimizing W_{CC} and W_{PP} instead of W_{CP} and W_{PC}. Finally, since the weight matrix of the feature-

wise FC layers is the same for all atoms or residues, it has far fewer parameters than the weight

matrix of the position-wise FC layers, which makes the training of feature-wise FC layers much

more efficiency.

Dateset completeness

We propose a metric, the completeness of a dataset $C_{DS} = N_{interaction}/(N_{protein} \cdot N_{compound})$, to

evaluate whether a dataset is suitable for training a neural network model for CPI prediction.

$N_{protein}$ is the number of proteins; *$N_{compound}$* is the number of compounds; *$N_{interaction}$* is the number of

interactions in the dataset. If the completeness of a dataset is 1, it means that the interaction

between each compound and each protein is included in the dataset. The completeness of

PDBbind, Davis, and Metz is 0.00052, 0.35, and 0.14, respectively. Training DeepDTA or

DeepConv-DTI on a dataset with an extremely low completeness (e.g. PDBbind) will make the

network inclined to predict CPI by memorizing the protein or the compound structure because the

$N_{compound}/N_{interaction}$ ratio or the $N_{protein}/N_{interaction}$ is close to 1 (Figure 2A&2C&2E). When

training on a dataset with a high completeness (e.g. Davis), the overfitting issue in DeepDTA and

DeepConv-DTI is alleviated (Figure 2B&2D&2F). Unlike other NN-based methods, the reliability

of *Yuel* does not depend on the completeness of the training set.

Hyper-Parameter Selection

The number of atom features is 82, by using a similar encoding method in Shuya Li's work[13]. The first 63 atom features is the one-hot encoding of the atom element in the list of C, N, O, S, F, Si, P, Cl, Br, Mg, Na, Ca, Fe, As, Al, I, B, V, K, Tl, Yb, Sb, Sn, Ag, Pd, Co, Se, Ti, Zn, H, Li, Ge, Cu, Au, Ni, Cd, In, Mn, Zr, Cr, Pt, Hg, Pb, W, Ru, Nb, Re, Te, Rh, Tc, Ba, Bi, Hf, Mo, U, Sm, Os, Ir, Ce, Gd, Ga, Cs, and "unknown"; 6 features are the one-hot encoding of the degree of the atom; 6 features are the one-hot encoding of the explicit valence of the atom; 6 features are the one-hot encoding of the implicit valence of the atom; the last feature is whether the atom is aromatic. The number of bond features is 6, indicating whether the bond is single, double, triple, aromatic, conjugated, or in a ring. The number of residue features is 20, the number of amino acid types. The number of GNN layers is 2 and the number of CNN layers is 3. We choose 2 as the number of GNN layers because we consider each atom group as the center atom, the neighbor atoms of the center atom, and the neighbor atoms of the neighbor atoms. We choose 3 as the number of CNN layers such that each residue fragment contains 7 residues. After the last CNN layer, we concatenate 4 protein feature matrices together: the protein feature matrix before the first CNN layer, the protein feature matrix after the first CNN layer, the protein feature matrix after the second CNN layer, and the protein feature matrix after the third CNN layer. The max length of compound vector is 64 and the max length of protein vector is 2048. Since our model only uses the heavy atoms in compounds, 64 as the number of atoms is enough to cover most compounds; similarly, 2048 as the number of residues is enough to cover most proteins. The size of the feature dimension is 32 for most layers in the model. Before multiplying the compound feature matrix and the protein feature matrix, we subject them to 5 fully-connected layers, separately. The size of the feature dimension in the first 4 linear layers is 32*8, and the size of the last linear layer is 32*50.

Training

The objective is to minimize the mean squared error of the predicted binding affinity and the experimental binding affinity. During the training process, we use a mini-batch of 8 and the Adam stochastic optimizer[26] to optimize the model parameters. For each training batch, compounds with different numbers of atoms and proteins with different numbers of residues are zero-padded to obtain the same input feature lengths. During the training process, the padded regions of features are masked so that they do not contribute to the calculation of the losses and gradients. Yuel has about two million learnable parameters. A single Yuel model has 1411523 parameters if the *"nfeat"* variable is 32. We also train Yuel by setting the "nfeat" variable as 8, and the performance does not change significantly (Figure S3). Training Yuel by 200 epochs on a dataset containing 440000 CPIs needs 34 hours on a Linux server with one NVIDIA Tesla T4 GPU.

Datasets

Our benchmark datasets include the PDBbind dataset[18], the Davis dataset[17], and the Metz dataset[19]. The PDBbind dataset is a high-quality set of protein-ligand complexes with available structural data and corresponding binding affinities. The PDBbind dataset is compiled from the PDBbind database (version 2018, the general set), which contains a high-quality set of protein-ligand complexes with available structural data and corresponding binding affinities. Each complex was provided with an affinity value of certain measurement type. The Davis dataset contains interactions of 72 kinase inhibitors with 442 kinases covering >80% of the human catalytic protein kinome. The Davis dataset is obtained from the Supplementary Information of Davis et al. work[17]. The Metz dataset is obtained from the Supplementary Information of Metz et al. work[19]. The PDBbind dataset contains 2509 small molecules and 10251 proteins, with a total of 13,311 interactions. On average, each small molecule corresponds to only 5.3 interactions and each protein corresponds to only 1.3 interactions. The Davis dataset contains 68 small molecules and 379 proteins, with a total of 9125 interactions. On average, each small molecule corresponds to 134.2 interactions, and each protein corresponds to 24.1 interactions. The Metz dataset contains 1471 small molecules and 172 proteins, with a total of 35307 interactions. On average, each small molecule corresponds to 24.0 interactions, and each protein corresponds to 207.7 interactions. We divide each dataset into a training set and a test set at a ratio of 8 to 2.

DATA AVAILABILITY

Source codes and test data are deposited in: *https://bitbucket.org/dokhlab/yuel*. We provide a website to use Yuel: *https://yuel.dokhlab.org* or *https://dokhlab.med.psu.edu/cpi*.

ACKNOWLEDGEMENTS

We acknowledge support from the National Institutes for Health (R35 GM134864), National Science Foundation (2040667) and the Passan Foundation. We appreciate Congzhou Sha for his enthusiastic proofread of the manuscript.

DECLARATION OF INTERESTS

The authors declare no competing financial interest.

REFERENCES

1. Drews, J. Drug discovery: a historical perspective. *Science (80-.).* **287**, 1960–1964 (2000).

2. Kitchen, D. B., Decornez, H., Furr, J. R. & Bajorath, J. Docking and scoring in virtual screening for drug discovery: methods and applications. *Nat. Rev. Drug Discov.* **3**, 935–949 (2004).

3. Wang, J. & Dokholyan, N. V. MedusaDock 2.0: Efficient and Accurate Protein-Ligand Docking With Constraints. *J. Chem. Inf. Model.* **59**, 2509–2515 (2019).

4. Trott, O. & Olson, A. J. AutoDock Vina: improving the speed and accuracy of docking with a new scoring function, efficient optimization, and multithreading. *J. Comput. Chem.* **31**, 455–461 (2010).

5. Meiler, J. & Baker, D. ROSETTALIGAND: Protein-small molecule docking with full side-chain flexibility. *Proteins-structure Funct. Bioinforma.* **65**, 538–548 (2006).

6. Lang, P. T. *et al.* DOCK 6: Combining techniques to model RNA–small molecule complexes. *Rna* (2009).

7. Leach, A. R. & Gillet, V. J. *An introduction to chemoinformatics.* (Springer, 2007).

8. Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* 1–11 (2021).

9. Senior, A. W. *et al.* Protein structure prediction using multiple deep neural networks in the 13th Critical Assessment of Protein Structure Prediction (CASP13). *Proteins Struct. Funct. Bioinforma.* **87**, 1141–1148 (2019).

10. Öztürk, H., Özgür, A. & Ozkirimli, E. DeepDTA: deep drug–target binding affinity prediction. *Bioinformatics* **34**, i821–i829 (2018).

11. Lee, I., Keum, J. & Nam, H. DeepConv-DTI: Prediction of drug-target interactions via deep learning with convolution on protein sequences. *PLoS Comput. Biol.* **15**, e1007129 (2019).

12. Karimi, M., Wu, D., Wang, Z. & Shen, Y. DeepAffinity: interpretable deep learning of compound–protein affinity through unified recurrent and convolutional neural networks. *Bioinformatics* **35**, 3329–3338 (2019).

13. Li, S. *et al.* MONN: a multi-objective neural network for predicting compound-protein

interactions and affinities. *Cell Syst.* **10**, 308–322 (2020).

14. Bohacek, R. S., McMartin, C. & Guida, W. C. The art and practice of structure- based

drug design: a molecular modeling perspective. *Med. Res. Rev.* **16**, 3–50 (1996).

15. Ponomarenko, E. A. *et al.* The size of the human proteome: the width and depth. *Int. J.*

Anal. Chem. **2016**, (2016).

16. Smith, L. M. & Kelleher, N. L. Proteoform: a single term describing protein complexity.

Nat. Methods **10**, 186–187 (2013).

17. Davis, M. I. *et al.* Comprehensive analysis of kinase inhibitor selectivity. *Nat. Biotechnol.*

29, 1046–1051 (2011).

18. Liu, Z. *et al.* PDB-wide collection of binding data: current status of the PDBbind database.

Bioinformatics **31**, 405 (2015).

19. Metz, J. T. *et al.* Navigating the kinome. *Nat. Chem. Biol.* **7**, 200–202 (2011).

20. Weininger, D. SMILES, a chemical language and information system. 1. Introduction to

methodology and encoding rules. *J. Chem. Inf. Comput. Sci.* **28**, 31–36 (1988).

21. Stein, S. E., Heller, S. R. & Tchekhovskoi, D. V. An open standard for chemical structure

representation: The IUPAC chemical identifier. (2003).

22. Eddy, S. R. Where did the BLOSUM62 alignment score matrix come from? *Nat.*

Biotechnol. **22**, 1035–1036 (2004).

23. Landrum, G. RDKit: A software suite for cheminformatics, computational chemistry, and

predictive modeling. (2013).

24. Abadi, M. *et al.* Tensorflow: a system for large-scale machine learning. in *OSDI* vol. 16

265–283 (2016).

25. Scarselli, F., Gori, M., Tsoi, A. C., Hagenbuchner, M. & Monfardini, G. The graph neural

network model. *IEEE Trans. Neural Networks* **20**, 61–80 (2008).

26. Kingma, D. P. & Ba, J. Adam: A method for stochastic optimization. *arXiv Prepr.*

arXiv1412.6980 (2014).

FIGURES

Figure 1. Test of the ability of Yuel to predict compound-protein interaction. (A) The architecture

of Yuel. (B) Test of the performance of Yuel, DeepDTA, and DeepConv-DTI on the Davis and the

PDBbind dataset. (C) The histogram of the similarities of compounds between the Davis dataset

and the PDBbind dataset. (D) The histogram of the similarities of proteins between the Davis

dataset and the PDBbind dataset. The average value of the similarities between compounds in

the two datasets is 0.35, and the average similarity of proteins in the two dataset is 0.27.

Figure 2. Comparison of Yuel, DeepDTA, and DeepConv-DTI in the shuffled PDBbind and Davis datasets. The models are trained on the normal training set, but the amino acids in each sequence of the test set are shuffled. (A) The relationships between Yuel-predicted affinities and the experimental affinities in PDBbind/test. (B) The relationships between Yuel-predicted affinities and the experimental affinities in Davis/test. (C) The relationships between DeepDTA-predicted affinities and experimental affinities in PDBbind/test. (D) The relationships between DeepDTA-predicted affinities and experimental affinities in Davis/test. (E) The relationships between DeepConv-DTI-predicted affinities and experimental affinities in PDBbind/test. (F) The relationships between DeepConv-DTI-predicted affinities and experimental affinities in Davis/test.

Figure 3. Comparison of position-wise FC layers and feature-wise FC layers. (A) The protein
features and the compound features are first concatenated and flattened to a 1-D feature vector.
The 1-D feature vector is then subject to full-connected layers. (B) The protein features and the
compound features are first split to individual residue features and atom features. Each residue
feature and each atom feature is subject to fully-connected layers, individually. Finally, the residue
features and the atom features are multiplied to obtain an attention matrix. (C) The affinities
predicted by Yuel-cc versus the experimental affinities when training on Davis/train and testing
on Davis/test. (D) The affinities predicted by Yuel-cc versus the experimental affinities when
training on PDBbind/train and testing on PDBbind/test. (E) The affinities predicted by Yuel-cc
versus the experimental affinities when training on Davis/train and testing on PDBbind/test.

Figure 4. (A) The predicted protein-binding interactions of fours atoms in N-Aryl-Hydroxybicyclohydantoin (LG790), the ligand of the rat androgen receptor (PDB ID: 2IHQ). (B) The histogram of AUC calculated by using Yuel to predict hotspot atoms in LG790. (C) The ranks of hotspot residues in the protein of 2IHQ. (D) The ground-truth hotspot atoms in LG790. (E) The predicted hotspot atoms in LG790. (F) The predicted hotspot residues in the protein of 2IHQ.