The geometry of domain-general performance monitoring in the human medial frontal cortex

Zhongzheng Fu[1,2], Danielle Beam[1], Jeffrey M. Chung[3], Chrystal M. Reed[3], Adam N. Mamelak[1], Ralph Adolphs[2,4], Ueli Rutishauser[1,3,4,5,*]

[1] Department of Neurosurgery, Cedars-Sinai Medical Center, Los Angeles, CA, USA
[2] Division of Humanities and Social Sciences, California Institute of Technology, Pasadena, CA, USA
[3] Department of Neurology, Cedars-Sinai Medical Center, Los Angeles, CA, USA
[4] Division of Biology and Bioengineering, California Institute of Technology, Pasadena, CA, USA
[5] Center for Neural Science and Medicine, Department of Biomedical Sciences, Cedars-Sinai Medical Center, Los Angeles, CA, USA

*Correspondence: rutishauseru@csmc.edu

Abstract

Controlling behavior to flexibly achieve desired goals depends on the ability to monitor one's

own performance. It is unknown how performance monitoring can be both flexible to support

different tasks and specialized to perform well on each. We recorded single neurons in the

human medial frontal cortex while subjects performed two tasks that involve three types of

cognitive conflict. Neurons encoding predicted conflict, conflict, and error in one or both tasks

were intermixed, forming a representational geometry that simultaneously allowed task

specialization and generalization. Neurons encoding conflict retrospectively served to update

internal estimates of control demand. Population representations of conflict were compositional.

These findings reveal how representations of evaluative signals can be both abstract and task-

specific and suggest a neuronal mechanism for estimating control demand.

Introduction

44   Humans can rapidly learn to perform novel tasks given only abstract rules, even if task

45 requirements differ drastically. To achieve this, cognitive control needs to coordinate processes

46 across a diverse array of perceptual, motor and memory domains and at different levels of

47 abstraction over sensorimotor representations (*1–3*). A key component of cognitive control is

48 performance monitoring, which enables us to constantly evaluate whether we have made an error,

49 experienced conflict, and responded fast or slow (*4*, *5*). It provides task-specific information

50 about which processes cause an error or a slow response so that they can be selectively guided

51 (*6–15*), thereby solving the problem of "credit assignment" (*13*, *16*, *17*). At the same time,

52 performance monitoring needs to be flexible and domain-general to enable cognitive control for

53 novel tasks (*18*), to inform abstract strategies (e.g., "win-stay, lose-switch", exploration versus

54 exploitation (*19*, *20*)), and to initiate global adaptation in motor (*21–23*), arousal (*24–26*) and

55 emotional (*27–29*) states. As an example, errors and conflicts can have entirely different causes

56 in different tasks (task-specific) but all signify failure or difficulty to fulfill an intended abstract

57 goal (task-general); performance monitoring should satisfy both requirements. Enabled by its

58 broad connectivity with the lateral prefrontal cortex (LPFC), thalamic and brainstem structures

59 (*30*, *31*), the medial frontal cortex (MFC) serves a central role in evaluating one's own

60 performance and decisions (*4*, *10*, *13*, *17*, *20*, *25*, *32–43*). However, little is known about how

61 neural representation in the MFC can support both domain-specific and domain-general

62 adaptations. Understanding the underlying mechanisms requires recording from the same

63 neurons across multiple tasks, which has not been done.

64   Specialization and generalization place different constraints on neural representations (*44*,

65 *45*). Specialization demands separation of encoded task parameters, which can be fulfilled by

increasing the dimensionality of neural representation (*46*, *47*). By contrast, generalization

involves abstracting away details specific to performing a single task, which requires reducing

the representational dimensionality (*3*, *46*). Theoretical work shows that the geometry of

population activity can be configured to accommodate both of these seemingly conflicting

demands (*44*), provided that the constituent single neurons multiplex task parameters non-

linearly (*48*, *49*). While recent experimental work has shown that neuronal population activity is

indeed organized this way in the frontal cortex and hippocampus in macaques (*44*) and humans

(*50*) during decision making tasks, it remains unknown whether this framework is applicable to

the important topic of cognitive control. Here, we examine the hypothesis that neuronal

populations in the human MFC represent performance monitoring in such a format, thereby

enabling downstream processes for both domain-specific and domain-general control.

A key aspect of behavioral control is learning about the identity and intensity of control

needed to correctly perform a task and deploy control proactively based on such estimates.

Doing so requires integrating performance outcomes over multiple trials (*13*). BOLD-fMRI

studies localize signals related to control demand estimation to the insular-frontostriatal network

(*51*). However, no single-neuron substrate of these signals is known. Also, it is unknown how

these slowly varying state-like signals are updated after a trial and whether the underlying

substrate is domain-general or task-specific. We constructed a normative Bayesian model that

captures this learning process as iterative estimation of the probability of encountering a specific

type of conflict trial. A key prediction is that conflict is not only represented *ex ante* before an

action is produced, but also *ex post* as an outcome signal. Our model also predicts that estimated

conflict probability is slowly updated and relatively stable across adjacent trials. We tested these

predictions by tracking single neuron activity within the MFC while patients performed two

well-studied conflict tasks: the color-word Stroop task and the Multi-Source Interference Task

(MSIT, (*52*)).

Results

Task and behavior

Subjects (see **Table S1**) performed the MSIT and the Stroop task (**Fig. 1A** and **Methods**;

some patients only performed one task due to time constraints, **Table S1**). Conflict and errors

arose from different sources in these two tasks: competition between a prepotency of reading

over color naming in the Stroop task, and competition between the target response and either the

spatial location of target ("Simon effect", denoted by "fl") or flanking stimuli ("Flanker effect",

denoted by "si"), or both ("sf") in MSIT. In the MSIT, we refer to trials with or without a Simon

Effect conflict as "Simon" and "non-Simon" trials, respectively (and similarly for Flanker trials).

Stimulus sequences were randomized, with each type of trial occurring with a fixed probability

(Stroop: 33% were conflict trials; MSIT: 15%, 15% and 30% had si, fl, and sf types of conflict,

respectively; see **Methods** for details).

Subjects performed well, with an error rate of 6.3±5% and 6.0±5% in the Stroop and

MSIT tasks, respectively. Reaction times (RT) on correct trials were significantly prolonged in

the presence of conflicts (**Fig. 1B**, see figure for statistics). Participants' sequential performance

(RT and accuracy) were modeled with a Bayesian conflict learning framework, building on

existing models (*51*, *53*, *54*). Our model (**Fig. 1C**) assumes that participants iteratively estimated

how likely

they were to encounter a certain type of conflict (conflict probability) by updating their prior

estimate with the new evidence received (experienced conflict and RT) on each trial. Since trial

114
Figure 1. Tasks, Bayesian conflict learning model, reaction time analyses
(A) Tasks.
(B) RTs were significantly prolonged by conflict in MSIT (left, N=41 sessions) and Stroop (right, N=82 sessions).
(C) The updating process (left) and the decision process modelled as a drift diffusion process (right). Shown is the
MSIT model, which has the five variables the flexible learning rate (α), predicted Simon conflict (q_{si}), predicted
Flanker conflict (q_{fl}), observed Simon conflict (o_{si}), observed Flanker conflict (o_{fl}), and RT. Observables (trial
congruency, RT, and outcome) are shown in gray, internal variables in white. Arrows indicate information flow.
Horizontal and top-down edges represent the estimation of flexible learning rate, predicted conflict before stimulus
onset, and the bottom-up edges represent using the observed conflict labels and RT to update latent variables for the
next trial.
(D) Estimated mean of the prior for Simon probability (orange) and Flanker probability (blue) from an example
MSIT session. Markers placed on the top indicated the type of conflict present.
(E) Regression analyses of RT using linear mixed-effect models. Blue bars show regression coefficients; black bars
show confidence intervals. Conflict prior positively predicted RT in MSIT (top) and Stroop (bottom).
129
130 *$p < 0.05$, ** $p < 0.01$, *** $p < 0.001$, n.s., not significant ($p > 0.05$).
131

sequences were randomized, subjects could only estimate the probability that an upcoming trial

would involve a conflict, an experimental parameter that was fixed but unknown to the subject a

priori. RT generation was modeled as a drift-diffusion process (DDM), with drift rates depending

both on the type of conflict present and the current estimate of the priors. In the following

analyses, we refer to the means of the prior and posterior distributions as conflict "prior" (before

stimulus onset) or "posterior" (after action completion). We fit the combined model, which

encompasses both the Bayesian component and the DDM, to the behavior (RT, conflict) of our

subjects using expectation-maximization (see **Methods**; See **Fig. S2** for estimated DDM

hyperparameter values). To illustrate this process, **Fig. 1D** shows the measured behavior and the

model-derived prior estimates of an example MSIT session.

142   We validated the behavioral relevance of the Bayesian model by examining how well the

model-derived regressors predicted RT and errors. First, in addition to current trial conflict, the

model-estimated conflict prior had a significantly positive main effect on RT in both tasks (i.e.,

an increase in RT; **Fig. 1E;** $\chi^2(1) = 6.75$, p = 0.009 for Simon and $\chi^2(1) = 6.79$, p = 0.009 for

Flanker in MSIT; $\chi^2(1) = 28.1$, p < 0.001 for Stroop; likelihood ratio test). The extent to which

RT varied with the conflict prior depended on the type of conflict (in the case of MSIT, Simon

and Flanker separately), as indicated by a significant negative interaction term ($\chi^2(1) = 12.94$ for

Simon and $\chi^2(1) = 14.2$ for Flanker in MSIT; $\chi^2(1) = 33.3$ for Stroop. p < 0.001 for all conflict

types; likelihood ratio test). This relationship between conflict prior and RT remained

statistically significant when trial ID was added as nuisance variable (**Fig. S1A**), and when the

conflict prior was estimated without RT tuning (**Fig. S1B**; see **Methods** for details). Our model

yielded qualitatively similar results when applied to data from a separate group of healthy control

subjects (**Fig. S1D**; the same RT-tuned models were used). Also, model-derived conflict prior

was systematically related to errors: when conflict was estimated to be likely, subjects were *less*

likely to commit an error on this trial, suggesting that more control was engaged (**Fig. S1C**; for

MSIT we only considered "sf" trials where most errors occurred; significant main effect $\chi^2(1) =$

6.81, p = 0.009 for MSIT; significant interaction with non-significant main effect $\chi^2(1) = 18.59$,

p < 0.001 for Stroop; likelihood ratio test). Collectively, these behavioral data from two tasks

demonstrate that the iteratively estimated conflict probabilities were correlated with prolonged

RT and reduced error likelihood, consistent with prospective engagement of control.

We further validated our model by comparing it with alternative models. First, our model

explained significantly more variance in RT than a model that only has access to whether the

previous trial was a conflict trial or not (**Table S2**, right). This finding, consistent with prior

work (*51*), demonstrates that our participants incorporated conflict information from multiple

previous trials. Second, we considered two alternative classes of models with more free

parameters: a reinforcement learning model that performed trial-by-trial updating using a

constant learning rate (free parameter) and a model that did not update trial-by-trial (free

parameter is the constant conflict probability; "no updating" in **Table S3**). Parameters of these

alternative models were optimized by maximum likelihood (MLE), which required access to all

data. Our model performed significantly better than either class of alternative models (**Tables S2**

and **S3** for a summary of model comparisons). RT tuning significantly improved our model both

in terms of explaining RT (**Table S2**) and trial congruency (**Table S3**). Since the RT-tuned

Bayesian models explained the most behavioral variance of all models considered, we used them

for all neural analyses.

Figure 2

177
Figure 2. Recording locations and example neurons.
(A) Recording locations shown on top of the CIT168 Atlas brain. Each dot indicates the location of a microwire
bundle.
(B-D) Activity of three example neurons that show similar response dynamics in both tasks. Shown is a neuron
signaling action error (B), conflict by firing rate increase (C), and conflict by firing rate decrease (D). The black
triangles mark stimulus onset. Trials are resorted by type for plotting purposes only.
184

 Neuronal correlates of performance monitoring signals

We collected single-neuron recordings from two regions within the MFC (**Fig. 2A**): the

dorsal anterior cingulate cortex (dACC) and the pre-supplementary motor area (pre-SMA). We

isolated in total 1431 putative single neurons (Stroop: 593 in the dACC and 607 in the pre-SMA

across 32 participants (10 females); MSIT: 326 in the dACC and 412 in the pre-SMA in 12

participants (6 females)).

We identified neurons selective for prior mean or prior variance in the baseline period,

for conflict in the ex-ante and ex-post period, and for error, surprise, posterior, and posterior

variance in the ex-post epochs (see example neurons in **Fig. 2**; schematic of analysis epochs in

Fig. 3A; and a summary of overall cell counts in **Fig. 3B**). We pooled neurons across the dACC

and the pre-SMA for most analyses because neurons responded similarly (but see section

"Comparison between the dACC and the pre-SMA" for notable differences).

During baseline, neurons encoded the mean or the variance of the prior distribution for

conflict probability (**Fig. 3B**, blue; 18 and 13% of neurons in MSIT; 17 and 11% in Stroop).

Neurons also encoded conflict ex ante (15% and 12% of neurons in MSIT and Stroop,

respectively; **Fig. 3B**, green), consistent with previous reports (*34*, *39*). In the ex-post epoch (**Fig.**

3B, yellow), neurons encoded conflict (20% in MSIT; 17% in Stroop), conflict surprise (an

unsigned conflict prediction error generated by the experienced conflict given the conflict prior;

19% in MSIT; 10% in Stroop), errors (22% in MSIT; 19% in Stroop; see **Fig. 2A** for an

example), and the mean and variance of posterior distribution of conflict probability (14/26% in

MSIT; 20/12% in Stroop). The percentage of units selective for a given variable were

remarkably similar between the two tasks (**Fig. 3B**).

208
209
Figure 3. Single neuron tuning properties.
(A) Illustration of epochs used for analysis. Thick vertical bars represent physical events, the slim vertical bars
demarcate epochs.
(B) Percentage of neurons encoding the variable indicated in the two tasks. The color code is as indicated in (A).
Dotted lines represent 2.5th and 97.5th percentiles of the null distribution obtained from permutation. For all groups
shown, p < 0.001.
(C) Percentage of conflict neurons that are active in each time period. Early and late ex-post epochs denote 0-0.5s
and 0.5s-1s after button press.
(D) Percentage of conflict neurons that were also selective for error, surprise, posterior, or any combination of these
factors ("mix").
(E) Comparison of single-trial neuronal response latency of conflict neurons in dACC and pre-SMA (correct trials
only, t=0 is stimulus onset for ex-ante and button press for ex-post conflict neurons).
(F) Percentage of posterior neurons that were also selective for prior, conflict, surprise, or error signaling.
(G) Neuronal signature of updating conflict prior based on the posterior. Correlation is computed between the
difference between prior and posterior (behavioral update) and the difference between demeaned $FR_{ex-post}$ and
$FR_{baseline}$ (neural update) for all prior neurons.
226

Approximately 30% of conflict neurons were active exclusively in either the ex-ante,

early (0-0.5s after button presses) or late (0.5-1.5s after button presses) ex-post epochs (**Fig. 3C;**

note that 'ex-post' always refers to the period of 0-1s after button press unless specified as early

or late), with some (~12%) active throughout the trial after stimulus onset ("extended"). This

temporal distribution of conflict signals was strikingly similar between the MSIT and Stroop

tasks (**Fig. 3C**). We were particularly intrigued by neurons signaling conflict ex post (15-20% of

neurons in both tasks; **Fig. 2C-D** shows examples), which have not been reported before. This

conflict signal, which arises too late to be useful for within-trial cognitive control, was more

prominent compared to the one found in the ex-ante epoch in both tasks (15% vs 20%, $\chi^2(1) =$

5.08, p = 0.024 for MSIT; 12% vs 16%, $\chi^2(1) = 9.19$, p = 0.0024 for Stroop, chi-squared test).

Motivated by our Bayesian conflict learning framework, we posit that this ex-post conflict signal

serves as an "outcome" signal indicating that the trial was not only correct but also with or

without conflict. As we will show further below, this information is critical for updating the

conflict prior, thus dynamically adjusting the amount of cognitive control estimated for each

upcoming trial.

Many conflict neurons also signaled errors, surprise, posterior, or a conjunction of these

variables (**Fig. 3D**). This multiplexing of signals depended on the timing of conflict signals. The

proportion of conflict neurons that multiplexed posterior information (light green bars) increased

significantly towards the end of the ex-post epoch, when updating would be most complete

(proportion in the late ex-post epoch vs. that in all other epochs; $\chi^2(1) = 6.14$, p = 0.01 for MSIT;

$\chi^2(1) = 6.22$, p = 0.01 for Stroop, chi-squared test). Consistent with this idea, the group of

neurons signaling conflict exclusively in the ex-ante epoch showed the least multiplexing,

indicating a primary role in monitoring conflict during action production (proportion of "pure"

conflict neurons active only during the ex-ante epoch vs. those that are active in other epochs;

$\chi^2(1) = 5.31$, p = 0.02 for MSIT; $\chi^2(1) = 8.78$, p = 0.003 for Stroop, chi-squared test).

We next investigated when information about the cognitive variables identified above

was available at the population level. We assessed the temporal stability of a decoder trained

using data from one epoch and tested on data from a different epoch. Error decoders trained on

early ex-post data generalized poorly to later epochs, but the ones trained on late ex-post data

generalized well into earlier epochs (**Fig. S5A-B**), suggesting that new information emerged late

in time, possibly related to post-error adjustments (*34*). We also found that the conflict coding

patterns during the ex-ante epoch did not generalize well to the ex-post epoch, and vice versa

(**Fig. S5C-E**), confirming that the MFC encoded these two types of conflict information with

separate populations of conflict neurons. The magnitude of conflict prior (or posterior) could also

be decoded from population activity at the single-trial level. Decoding conflict prior from

activity in the baseline epoch generalized well to decoding conflict posterior in the ex-post epoch,

demonstrating temporally stable population coding of conflict across these epochs (**Fig. S6A-F**).

Representation of previous conflict was relatively weak (**Fig. S7A-C**; < 60% decoding accuracy),

which is consistent with our behavioral observation that previous conflict alone was a poor

predictor of RT compared to the integrated conflict prior (**Table S2**, right).

Posterior neurons demonstrated the greatest degree of multiplexing (**Fig. 3F**). Only ~18%

of posterior neurons signaled posterior exclusively, with the remainder also signaling prior,

conflict, surprise, or mixtures of these. This multiplexing may reflect the process of computing

the posterior from the prior, which incorporates these multiple variables. Supporting this

hypothesis, conflict prior-encoding neurons changed their ex-post firing rates by an amount that

was commensurate with the numerical change from prior to posterior (estimated by the

behavioral model) on a trial-by-trial basis (**Fig. 3G**, $p < 0.001$, t test against zero. Mean

correlations in Simon, Flanker and Stroop are 0.042, 0.032, 0.065, respectively), reflecting a

neural "updating" process.

The properties of conflict prior neurons differed from those of the other recorded neurons.

First, the trial-by-trial baseline spike rates of prior neurons (a time series) had higher self-

similarity than all other types of neurons studied (**Fig. S3C-D**; self-similarity quantified by α

values from the Detrended Fluctuation Analysis. **Fig.S3E-H** show DFA analysis of two example

neurons). Second, the spikes of prior neurons had significantly shorter action potential

waveforms compared to non-prior neurons (**Fig. S3I-J** right panels; more broadly, DFA alpha is

negatively correlated with spike width, shown in **Fig. S3I-J** left panels). Together, these data

demonstrate that error, conflict, and conflict prior (or posterior) information can be read out

reliably on each trial from the MFC population with high accuracy, with dynamic coding

patterns for conflict and error and static coding patterns for prior (or posterior).

Representational geometry of conflict within a single task

We next investigated the representational geometry of conflict when different types of

cognitive conflict coexist within a single task (MSIT) in the high dimensional neural state space

formed by all recorded neurons. We first tested whether the four MSIT conflict conditions are

separable along a one-dimensional line in the neural state space. This "coding dimension" was

defined as a vector flanked by the means of the "sf" and "none" trials (**Fig. 4A**, dotted lines for

an illustration; see **Methods**). Projecting left-out single trials from all four trial types (si, fl, sf,

non-conflict) onto this coding dimension allowed a decoder to differentiate between all pairs of

conflict conditions in the ex-ante epoch (**Fig. 4B**, left), and all but one pair (si vs. sf, $p = 0.11$) in

the ex-post epoch (**Fig. 4B**, right). Notably, the left-out si and fl conditions can be differentiated

well on

298
Figure 4. State-space representation of conflicts, prior, and posterior.
(A) State-space representation of conflict (left, ex-ante; right, ex-post) in MSIT task visualized in PCA space. Dotted
line is the vector used to classify pairs of conflict conditions in (B).
(B) Decoding accuracy from classification of pairs of conflict conditions in MSIT.
(C) Coding dimensions invariant between Simon and Flanker conflict. At each time point, a decoder is trained on
Simon vs. non-Simon and tested on held out Flanker vs. non-Flanker trials (gray), and vice-versa (black).
(D) Conflict representations are compositional. Decoders trained on one edge of the parallelogram were able to
differentiate between conditions along the opposite parallel edge (orange and blue edges shown in A, respectively,
shown on left and right). Dotted lines show 97.5[th] percentile of the null distribution.
(E-G) State-space representation of prior/posterior in MSIT and Stroop, visualized in PCA space. Green dots mark
baseline start, the two cyan squares delineate the range of stimulus onsets, blue dots mark button press and red dots
mark end of trial. Trials are aligned to button press. Color fades as the trial progresses.
311

this axis (decoding accuracy is 72% for ex-ante and 78% for ex-post data). Conflict conditions

were separable even after equalizing for RT across conditions (**Fig. S8C**; See **Methods** for RT

equalization), suggesting that the separation was independent of trial difficulty for which RT is a

proxy (*55*). We next investigated whether a common coding dimension exists for both Simon

and Flanker conflict by projecting the activity of single trials onto the coding dimension formed

by connecting, in the neural state space, the mean of Simon (si+sf) with the mean of non-Simon

(fl+none) separately for each time bin (and vice-versa for Flanker (fl+sf) vs non-Flanker

(si+none)). Data for testing were held out (not used for constructing the coding dimensions).

Coding dimensions for one type of conflict allowed decoding of the other type of conflict with

high accuracy (**Fig. 4C**; black trace, Flanker coding dimension decoding Simon vs. non-Simon;

gray trace, Simon coding dimension decoding Flanker vs. non-Flanker). Together, these data

demonstrate that within a single cognitive task, the MFC population formed a conflict

representation geometry that generalized across two types of conflict while at the same time also

allowing maximal separation between the different types of conflict.

We next tested whether the representation of conflicts was compositional. If true, relative

to the mean of "none" trials, the "sf" representation should be located where the linear vector

sum of Simon ("si") and Flanker ("fl") trials lands, forming a parallelogram with the none-sf axis

as the diagonal (**Fig. 4A**). A decoder trained to differentiate between the two classes connected

by one edge of this parallelogram should be able to decode the two classes connected by the

opposite edge (and vice-versa). Indeed, a decoder trained to differentiate "sf" from "fl" trials,

which is simply the axis connecting "sf" and "fl" (blue edge in **Fig. 4A**), was able to decode "si"

from non-conflict trials projected to this axis with above chance performance, and vice versa

(**Fig. 4D**, $p < 0.001$ for both the ex-ante and ex-post data, permutation test). The same was true

for the other pair of edges (**Fig. 4D**, testing blue edges in **Fig. 4A**; $p < 0.001$ for both the ex-ante

and ex-post data, permutation test). The parallelism was not perfect because the decoding

accuracy, while well above chance, was relatively low ($< 70\%$) compared to within-condition

decoding performance (**Fig. 4C**). Neurons that encoded Simon and Flanker non-linearly (as

measured by the F statistic of the interaction term between Simon and Flanker derived from an

ANOVA model) contributed the most to this deviation from parallelism at the population level

(**Fig. S8F**, $r = 0.74$, $p < 0.001$, for ex-post data; **Fig. S8E**, $r = 0.75$, $p < 0.001$, for ex-ante data;

Spearman's rank correlation). Thus, neurons that encoded non-linear mixtures of the two types

of conflict were the cause of deviation from linear compositionality. This representation structure

was disrupted on error trials: generalization performance dropped significantly in the ex-ante

(**Fig. S8D**; for both edges, 68% and 58% on correct trials vs. 56% and 47% on error trials) as

well as the ex-post epoch (**Fig. S8D**; for both edges, 55% and 66% on correct trials vs. 51% and

59% on error trials) on error trials. Collectively these data suggest that in the MSIT task, neural

representations of conflict were structured in a compositional way that separated the four conflict

conditions in a parallelogram, and this geometry was behaviorally relevant.

Representational geometry of conflict prior/posterior

Conflict prior can be viewed as a state (an initial condition) that is present before

stimulus onset and to which the population returns after completing a trial. To test this idea, we

binned trials by quartiles of conflict prior (or posterior. 4 "levels" were generated) and

aggregated data by these labels of conflict trial levels. PCA analysis revealed that the variability

across different levels of prior/posterior (~8% of explained variance) was captured mostly by a

single axis (PC3s in **Fig. 4E-G**; green dots mark trial start, red dot trial end), which was

orthogonal to most of the time-dependent state changes (captured by PC1s and PC2s, ~68% of

explained variance). At baseline (demarcated by green and cyan filled circles in **Fig. 4E-G**), the

neural state evolved with low speed (blue points in **Fig. S8G-I**). The neural state then changed

more quickly after stimulus onset (orange points in **Fig. S8G-I**; $p < 0.001$, paired t-test), before

eventually returning to baseline near the starting position (red filled circles in **Fig. 4E-G**; yellow

points in **Fig. S8G-I**). The distance between the four trajectories was thus stable across time,

consistent with representation of conflict prior (or posterior) being stable states. The PCA had no

access to the numerical order of conflict prior (or posterior) levels, but the projection values of

neural data onto PC3 followed this order (**Fig. S8J-L**, see **Legends** for statistics of the

multinomial logistic regression). Taken together, this shows that the representation of conflict

prior (or posterior) information in MFC is low-dimensional, stable across time and parametric,

consistent with the dynamics of line attractors.

Domain-general performance monitoring signals at the population level

We next investigated whether the geometry of performance monitoring representations

supports readout invariant across MSIT and Stroop, while simultaneously allowing maximal

separation of conditions specific to MSIT. We have demonstrated above that, within MSIT, a

geometry can be extracted that supports invariance across types of conflicts while keeping the

four conflict conditions separated. However, it remains unclear whether this representation is

task specific and only possible because of sharing a task set. Here, we studied the activity of the

same neurons in two behavioral tasks to test whether representations in MFC can be independent

of specific tasks sets (**Table S1** shows session information). We used demixed PCA (dPCA) (*56*)

to factorize population activity into coding dimensions for performance monitoring variables

(error, conflict and conflict prior (or posterior)) and task identity. The statistical significance of

the

Figure 5. Domain-general representation of performance monitoring signals.
(A) Task-invariant decoding of errors. Bar on the right shows the variance explained by the different dPCA
components.
(B) Task-invariant decoding of conflict. The bar on the right represents variance explained by the different dPCA
components (color code see figure legend).
(C) Separability of conflict conditions along the domain-general conflict axis in both the ex-ante (left) and ex-post
epochs (right). The dPCA coding dimension was constructed using Stroop, SF conflict and no conflict trials and
supported decoding of Stroop, Simon and Flanker conflicts ("task-invariant") as well as separation of Simon and
Flanker conditions.
(D) Task-invariant decoding of conflict prior. The dPCA coding axis was constructed using Stroop and Simon
conflict priors (binned by quartiles into four levels) and supported pairwise decoding of conflict prior levels in both
tasks. Bar at the bottom shows variance explained of dPCA components.
(E-F) Relationship between task-invariant single neuron tuning strength of error (E), conflict (F) and dPCA weights.
Pie charts show the percentages of *tuned* neurons (total number is N_{sig}) that had a significant main effect for
performance monitoring variable *only* ("task-invariant", red slice) and those that had a significant interaction effect
with the task identity ("task-dependent", blue slice). Scatter plots (left) shows significant correlation between task-
invariant coding strength and the corresponding dPCA weights. Y-axis shows correlation of firing rate of a neuron
with the given variable, after partialing out task identity (see Methods).
*$p < 0.05$, ** $p < 0.01$, *** $p <= 0.001$, n.s., not significant ($p > 0.05$).

extracted coding dimensions was assessed by out-of-sample decoding. The extent of "demixing"

was quantified by the angle between the performance monitoring and task identity coding

dimension.

The dPCA coding dimensions extracted using error and conflict contrasts (Stroop-Simon

and Stroop-Flanker separately) each explained 19-21% of variance, supported task-invariant

decoding and were orthogonal to the task identity dimension (**Fig. 5A** for error, **Fig. 5B** and **Fig.**

S9A for conflict decoding over time, and **Fig. 5C** for conflict decoding in the ex-ante and ex-post

epochs separately. $p < 0.001$, permutation tests; clusters with significant decoding performance

demarcated by horizontal bars; For error, angle = 94.47°, p=0.53, tau=-0.032; for Stoop-Simon

conflict, angle = 81.13°, p=0.19, tau=-0.048; for Stroop-Flanker conflict, angle = 78.6°, p=0.02,

tau=0.086; Statistics are Kendall rank correlation to test for difference vs. 90°, "n.s.", not

significantly different from orthogonality).

The task-invariant conflict coding dimension (extracted by removing the task difference

between MSIT *sf* and Stroop conflict trials and between non-conflict trials in both tasks) was

also able to differentiate 5 out of 6 pairs of conflict conditions with high accuracy (60% - 90%)

within MSIT in both the ex-ante and ex-post epochs (**Fig. 5C**; statistics see figure legend,

permutation tests). Task-invariant decoding did not change after RT equalization (e.g., selecting

conflict and non-conflict trials that had similar RTs), suggesting again that task-invariant

representations of error and conflict was not due to coincidental condition differences in

difficulty (**Fig. S9B-E**), for which RT is a proxy (*55*).

Similarly, the coding dimensions for Stroop-Simon conflict prior (**Fig. 5D**; or posterior,

Fig. S9G) and Stroop-Flanker conflict prior (**Fig. S9F**; or posterior, **Fig. S9H**) each explained

27-35% of variance, supported task-invariant decoding and were orthogonal to the task identity

dimension (see Legend for statistics). Importantly, this task generalizability did not compromise

the capacity of this coding dimension to separate different levels of prior (or posterior) within

Stroop or MSIT (**Fig. 5D**, **Fig. S9F-H**). Together, these data demonstrate that the neural

representation of performance monitoring signals in MFC is configured in such a way that it

supports generalization

between two different tasks while at the same time also allowing the readout of task-specific

information.

Domain-general performance monitoring signals at the single-neuron level

We sought to understand how single neuron tuning properties contributed to the

population geometry that simultaneously allowed task-invariant and task-specific readouts.

While some neurons encoded error, conflict, and conflict prior (or posterior) in a task-invariant

manner (**Fig. 2**), others encoded these variables in only one task. We assessed the level of task

specificity with a linear regression model with two main effects: the task identity and one of the

performance monitoring variables (see **Methods**). 33-66% of the recorded neurons were "task

invariant" as assessed by having a significant main effect of error, prior, conflict prior (or

posterior) but no significant interaction with task identity (**Fig. 5E-F, Fig. S11A-E**, red part of

pie charts). 37-63% of the recorded neurons were "task dependent" as assessed by a significant

interaction effect (**Fig. 5E-F**, **Fig. S11A-E**, blue part of pie charts). Both the task-invariant and

the task-dependent neurons contributed to the task-invariant coding dimensions as both were

assigned significantly larger absolute dPCA weights compared with non-selective ("other")

neurons (**Fig. 5E-F**, **Fig. S11A-E**, dot density plots). The dPCA weight assigned to each neuron

was correlated with the neuron's task-invariant single-neuron coding strength (scatter plots in

Fig. 5E-F, **Fig. S11A-E**; p < 0.001 for all panels, Pearson's correlation). Neurons with higher

self-similarity for baseline spike counts contributed more to the task-invariant coding dimension

of conflict prior (or posterior), after controlling for single-neuron coding strength (partial

correlation between absolute values of dPCA weights and DFA α values; r = 0.22 and r = 0.24, p

< 0.001 for Stroop-Simon prior and posterior; r = 0.16, p = 0.003 and r = 0.16, p = 0.002 for

Stroop-Flanker prior and posterior). These results reveal that a downstream neuron receiving

input from a random subset of MFC neurons can robustly extract domain-general performance

monitoring signals with a set of properly tuned connection weights.

Comparison between the dACC and the pre-SMA

The proportion of neurons selective for each tested variable were similar in dACC and

pre-SMA (**Fig. S3A-B).** Both areas contained similar proportions of task-invariant and task-

dependent neurons. Both areas independently supported compositional conflict coding and

domain-general readouts for error (**Fig. S10A-B**), conflict (**Fig. S10C-F**), and conflict prior (or

posterior; **Fig. S10G-N**). However, there were three notable differences between the two areas.

First, the temporal profiles of decoding performance for error, conflict and prior (or posterior)

were similar between the areas but decoding accuracy in pre-SMA was consistently higher (**Fig.**

S4A-E). Second, the task-invariant error response appeared earlier in pre-SMA than in dACC

($\Delta_{latency}$ = 0.55s for Stroop and 0.5s for MSIT), consistent with our previous report in the Stroop

task (*34*) (replicating this difference for MSIT is novel). Third, ex-ante conflict information was

first available in dACC, followed by pre-SMA (**Fig. 3E**; median difference = 138ms; p < 0.001,

Wilcoxon rank sum test; single-trial spike train latency). Third, by contrast, ex-post conflict

information was available first in pre-SMA, followed by dACC (**Fig. 3E**; median difference =

161ms; p = 0.002, Wilcoxon rank sum test). This pattern is consistent with a leading role of pre-

SMA in post-action performance monitoring (*34*), and that of dACC in conflict monitoring

during action selection.

Discussion

We show that some neurons encoded error, conflict and conflict prior (or posterior) in a

task-invariant way, some encoded these variables exclusively in one task only, and some

multiplexed domain/task information to varying degrees, intermixed at similar anatomical

locations within the MFC. Thus, at the single neuron level, neurons multiplex task identity and

performance monitoring variables nonlinearly (i.e., "mixed selectivity" (*47*, *48*)), making simple

interpretation of domain generality impossible. Population activity, however, could be factorized

into a task identity dimension and a task-invariant dimension that were orthogonal to each other.

The geometry of MFC population activity allows linear decoders to read out performance

monitoring variables with the same high accuracy (>80%) across tasks, and simultaneously to

discern different types of conflicts or different levels of conflict prior (or posterior) within a task.

Importantly, it was the *same* group of neurons that gave rise to this geometry. This contrasts with

neuroimaging studies that either report domain-specific and domain-general conflict signals

encoded by distinct groups of voxels (*57*, *58*), or an absence of domain-general conflict signals

(*59*) within the MFC.

Several influential studies have proposed that the lateral PFC is topographically

organized to subserve cognitive control, with more abstract processing engaging the anterior

regions (*1–3*, *60*, *61*). Unlike in the LFPC, we find that domain-general and domain-specific

neurons are intermixed within the MFC. The representational geometry we report here is well

suited to provide performance monitoring signals to these subregions: downstream neurons

within these LPFC regions can select performance monitoring information at different degrees of

abstraction by adjusting connection weights, similar to input selection mechanisms described in

the PFC (*62*). Curiously, we did not observe a prominent difference between the pre-SMA and

the dACC in the degree of domain generality of performance monitoring.

Domain-general error signals

A key component of performance monitoring and metacognitive judgement is the ability

to detect action errors without relying on external feedback (*63, 64*). Here, we show that a subset

of neurons not only signal error in the Stroop task (as previously reported in (*34*)) but also in the

MSIT (a novel finding). The error signal is thus domain-general, that is, abstracted away from

the sensory and motor details as well as the types of response conflicts encountered across the

two tasks (**Fig. 2B**). Remarkably, at the population level, these domain-general error neurons

enabled trial-by-trial readout of self-monitored errors with > 90% accuracy equally across tasks

(**Fig. 5A, E**). Such abstract action error signals, which indicate a mismatch between abstract

goals and action outcomes, may provide a basis for the processes that monitor the difference

between internal thoughts and reality, which are thought to be compromised in psychiatric

diseases such as schizophrenia (*65*). Given the fMRI-BOLD finding that the MFC is a domain-

general substrate for metacognition (*66*), an interesting open question is whether the same neural

mechanisms we describe here support metacognitive judgement across different domains, such

as perceptual or memory confidence.

Domain-specific performance monitoring

The causes of conflict and errors in the two tasks differs: distraction by the prepotent

tendency to read in the Stroop task, and distraction by location of target number (Simon) or by

numbers flanking the target (Flanker) in the MSIT. These performance perturbations call for

specific compensatory mechanisms, such as suppressing attention to task-irrelevant stimulus

dimensions. Consistent with this requirement, a subset of neurons signaled errors, conflict and

conflict prior (or posterior) exclusively in one task. At the population level, these neurons

contributed to successful decoding of the different types of conflicts within MSIT and gave rise

to a task identity dimension that supported robust decoding of which task the performance

disturbance occurred in (>90% accuracy), providing the domain-specific information about the

sources of performance disturbances for cognitive control. These results are broadly consistent

with the reported role of MFC neurons in credit assignment (*17*). The existence of task-specific

neurons also suggests that the performance monitoring circuitry can be rapidly and flexibly

reconfigured in different tasks to subserve different task sets (*67*, *68*), which is consistent with

the rapid reconfiguration of functional connectivity among cognitive control networks to enable

novel task performance (*69*).

Compositionality of conflict representation

Further insight into how representations can be both general and specific is offered by

examining the activity during "sf" conflict trials (both Simon and Flanker conflict) in the MSIT

task. The problem of whether conflict representations are compositional can be formulated as a

problem of cross-condition generalization: if Simon and Flanker conflict are linearly additive,

decoders trained to identify the presence of only Simon or Flanker conflict should generalize to

trials in which both types of conflict are present. We found that this was the case, with the neural

state approximately equal to the linear vector sum of the two neural states when the two types of

conflict are present individually. Conflict representations are thus additive to a large extent (with

the extent of deviation predicted by the degree of nonlinear mixing present). The (approximate)

factorization of conflict representation is important for both domain-specific and domain-general

adaptation: when different types of conflict occur simultaneously and the representation can be

factorized, downstream processes responsible for resolving each type of conflict can all be

initiated. On the other hand, domain-general processes can also read out the representation as a

sum and initiate domain-general adaptations.

Estimating control demand enabled by ex-post conflict neurons

Our Bayesian updating model predicts that conflict should be signaled twice: once during

response competition (*ex ante*), and again after the action has been committed (*ex post*). While

the former is a major prediction of conflict monitoring theory (*13*, *70*), the latter is a new

prediction of our model. Importantly, *separate* groups of neurons gave rise to these two types of

conflict signals (**Fig. 3C**) and the population activity patterns representing the two differ

substantially to prevent generalization (**Fig. S5C-E**), suggesting that the ex-post conflict signal is

not a continuation of the ex-ante conflict signal but instead a re-representation of experienced

response conflict by different neurons. We note that the ex-post conflict signal we documented

appears before onset of feedback and thus reflects metacognitive judgements. Our work is the

first to report ex-post conflict neurons in the dACC and pre-SMA in both tasks and ex-ante

conflict neurons in the pre-SMA. Also, our work replicates the finding of ex-ante conflict

neurons in the dACC (*39*). The ex-ante conflict signal may be useful for recruiting online

cognitive control (*70*), but provides an temporally unstable readout of the experienced conflict: it

intensifies before ultimately becoming subdued as one response option wins over. The ex-post

conflict signal, by contrast, abstracts over this temporal dynamics and integrates it into a stable

"conflict outcome" (*13*, *51*). This view of the ex-post conflict signal as an outcome signal is also

consistent with the widely reported role of MFC in representing outcomes (*4*, *37*). This

information is imperative for updating slowly varying representations of estimated conflict

probability.

Both conflict signals arise independent of external feedback, thus qualifying as correlates

of metacognitive self-monitoring (*63*, *64*). Interestingly, there is significant overlap between

error neurons and ex-post conflict neurons. Confirming this, we found common coding

dimensions in each task that supports the decoding of both error and conflict, though the

decoding accuracy is significantly lower for conflict than for error (**Fig. S8A-B**). The ex-post

conflict and error signals may be generated by a common process that compares a corollary

discharge signal with the sensory prediction of action outcomes generated by a cognitive

"forward model" (*71–73*) and may underlie the sense of agency (*74*). Future work is needed to

test this new hypothesis.

The neurons that reported conflict prior changed their firing rates trial-by-trial as

predicted from our behavioral model, and this "updating" in firing rates occurred after an action

was performed. The distinct functional properties of conflict prior neurons, i.e. significantly

narrower extracellular spike waveforms and higher self-similarity (autocorrelation) of trial-by-

trial baseline spike counts assessed by DFA (**Fig. S3C-J**), suggest that they are likely putative

interneurons with strong recurrent connectivity, consistent with a prior report where dACC

neurons that encode past outcomes have narrower extracellular waveforms (*75*). At the

population level, these single-neuron properties contribute to the formation of a task-invariant

line attractor dynamics that stably maintains the conflict prior. Computational modelling demonstrates the importance of inhibitory interneurons in maintaining information in working memory, which occurs on the scale of several seconds(*76*). Similar circuit-level mechanisms could provide a basis for retaining the history of performance monitoring and reward, which is on the scale of several minutes. These prior neurons might thus provide a neural substrate for proactive control and learning of value of control, both of which requires stable maintenance of learned information (*13*, *77*) . Future research should address the trade-off between flexible updating and stable maintenance of performance monitoring information. Together, the neuronal responses we found fit remarkably well to the parameters of a Bayesian model that used trial-wise updating to estimate upcoming conflict – a critical ingredient in the control of flexible behavior in changing environments.

Our findings will also be relevant to a mechanistic understanding of impaired control, such as may happen in children, under fatigue or substance influence, or in psychiatric disorders such as schizophrenia. Given our clear evidence both for domain-general and domain-specific representations, an intriguing future direction would be to ask whether impaired control may affect one of these differentially and could be compensated differentially.

604   **Supplementary Figures**

Figure S1

A

B

C

D

Linear mixed-effect models predicting RT with
trial IDs using RT-tuned priors (mTurk)

Figure S1 Behavioral models. Related to Figure 1.
Statistical significance of regressors is determined by comparing the full model and a reduced model with a particular regressor removed, using a likelihood ratio test.
(A) Linear mixed-effect model for RT that incorporates trial ID regressors for MSIT (left) and Stroop (right). Conflict priors used are from the Bayesian online learning models with RT tuning. We added the first, second and third -order trial ID regressors to model putative practice effects. The main effects of conflict priors, conflict, and their interaction are all significant even in the presence of trial ID regressors, suggesting these regressors capture behavioral effect that do not depend on trial ID.
(B) Same as (A), but for the Bayesian online learning models without RT tuning. Thus, in this instance, conflict prior is estimated based on conflict sequence alone. The main effects of conflict priors (not tuned by RT), conflict, and their interaction are all significant in the presence of trial ID regressors. Therefore, RT tuning improves conflict prior (see (A) and Table S2, S3), but this is not required.
(C) Mixed-effect logistic regression for predicting trial outcome (error or correct) for MSIT (left) and Stroop (right). Conflict priors used are from the Bayesian online learning models with RT tuning. For MSIT, we consider only "sf" trials for conflict trials, on which most of errors occur, and non-conflict trials. Conflict prior reduces error likelihood in both MSIT (significant main effect, $p = 0.009$) and Stroop (significant interaction term), $p < 0.001$.
(D) Behavioral analysis for data collected from independent control group in the MSIT task (online experiment, see methods). Same model as used in (A) is used.

Figure S2

A

B

625
626
627 **Figure S2. DDM hyperparameters used in Bayesian conflict learning models. Related to Figure 1.**
628
(A) Hyperparameters used in the Bayesian conflict learning model for MSIT.   and   are coefficients scaling
Simon and Flanker prior.   ,   ,   ,   are base drift rates in both Simon and Flanker present ("sf"),
Simon-only ("si"), Flanker-only ("fl"), non-conflict trials.   is the boundary separation. The effective drift rate was
the sum of the base drift rate and the scaled conflict prior. The base drift rates were significantly different from each
other (p < 0.001, ANOVA). Post-hoc pairwise testing from a multiple comparison test determined that   did not

differ significantly from v_{fl}; v_{sf} were significantly larger than either v_{si} or v_{fl}; both v_{si} and v_{fl} were significantly
larger than $v_{non-conflict}$.
(B) Hyperparameters used in the Bayesian conflict learning model for Stroop. vz is the coefficient scaling Stroop
conflict prior. $v_{conflict}$, $v_{non-conflict}$ are base drift rates in conflict and non-conflict trials. a is the boundary
separation. $v_{non-conflict}$ are significantly larger than $v_{conflict}$ across sessions (p < 0.001, t test).
Hyperparameters are used in the DDM likelihood function for tuning the conflict prior estimation process using an
expectation-maximization algorithm.
641

Figure S3

A MSIT

B Stroop

C MSIT **D** Stroop

E **F** **G** **H**

I MSIT **J** Stroop

643
644 **Figure S3. Neuronal selection by areas and long-range temporal correlation of prior/posterior neurons.**
645
(A) Percentages of significant neurons in both dACC (left) and pre-SMA (right) in MSIT.
(B) Percentages of significant neurons in both dACC (left) and pre-SMA (right) in Stroop.
Dotted lines represent 2.5^{th} and 97.5^{th} percentiles of the null distribution obtained from permutation. For all groups
shown, $p < 0.001$. Patterns of neuronal selection are similar between dACC and pre-SMA.
(C) Mean baseline DFA a value for different groups of neurons (left), and correlation between baseline DFA a value
and the coding strength of prior, which is assessed by the F statistic computed from regressing prior against baseline
spike counts (right) for MSIT. Separate data were used to compute a value and prior coding strength to avoid
selection bias. Prior neurons have significant larger baseline DFA a value than any other groups ($p < 0.001$,
ANOVA). The coding strength of prior was correlated strongly with the baseline a value ($r = 0.24$, $p < 0.001$).
(D) same as in (C) but computed for the Stroop task.
(E-H) Two example neurons (one orange one gray), showing waveforms (E), autocorrelation (F), power spectrum
(G), and fluctuation (H) s as a function of time intervals used to compute DFA a value (slope). The neuron with
narrower spike width has higher DFA a value ($r = -0.19$, $p < 0.001$).
(I) DFA a value is negatively correlated with spike width for MFC neurons (left) in MSIT. Prior and posterior
neurons as a group have significantly narrower spikes than other neurons (right).
(J) same as in (I) but for the Stroop task.
662

Figure S4

A

MSIT error

B

Stroop error

C

Simon conflict

D

Flanker conflict

E

Stroop conflict

Legends for A-E
— dACC
— pSMA

663
664
665
666 **Figure S4. Population decoding of error and conflict by areas.**
667
668 (A-E) Population decoding accuracy for MSIT error (A), Stroop error (B), Simon conflict (C), Flanker conflict (D),
669 Stroop conflict (E). For (A-E), black traces are from dACC data and grey traces are from pre-SMA data. Horizontal
670 bars at the top demarcate significant cluster as determined by the cluster-based permutation test (p < 0.05). Overall
671 dynamics are similar between dACC and pre-SMA, though the decoding accuracy on average is lower in the dACC.
672

Figure S5

673
674
675 **Figure S5. Temporal dynamics and cross-temporal generalization of error and conflict**
676
(A-E) Decoding accuracy as a function of time for MSIT error (A), Stroop error (B), Simon conflict (C), Flanker
conflict (D) and Stroop conflict (E). The three panels show data aligned to stimulus onset ("Stim"), midpoint
between 100ms after stimulus onset and button presses ("MP"), button press onset ("BP"). Dotted gray trace
represents within-time decoding accuracy, i.e., the data from the same epoch were used to train and test a decoder.
Green, blue and orange traces represent decoding accuracy of decoders trained with data from the epochs
demarcated by shading with the same colors, which is a test of the cross-temporal generalization of these decoders.
Horizontal bars demarcate the extent of significant clusters in time as determined by the cluster-based permutation
test (p < 0.5).
685

Figure S6

Figure S6. Temporal dynamics and cross-temporal generalization of conflict prior (or posterior).

(A-F) Decoding accuracy for classifying between pairs of Simon (A-B) Flanker (C-D) and Stroop (E-F) prior or posterior levels. Levels are quartile bins of the conflict prior. Color bars show decoding accuracy. Dotted frames mark the within-time decoding results, plots without dotted frames showed results from temporal generalization. Decoders that classify prior levels are trained using baseline spike counts (1.5s before stimulus onset), whereas decoders that classify posterior levels are trained using ex-post spike counts (2s after button press). To test temporal generalization of these decoders, prior-trained decoders are tested with posterior data and labels, and vice versa. Dashed boxes represent within-time decoding.

Figure S7

698
699
700 **Figure S7. Encoding of previous conflict.**
701
702 (A-C) Population decoding of Simon (A), Flanker (B), Stroop (C) on the immediately preceding trial in different
703 epochs. Dotted lines show 97.5% percentile from the null distribution (permutation). During baseline, there is
704 significant coding of past trial conflict as expected from the persistence of ex-post conflict signals. Coding of the
705 past trial conflict was non-significant during all other epochs except for past trial Stroop conflict in the early ex-post
706 epochs.
707
708 *p < 0.05, ** p < 0.01, *** p < 0.001, n.s., not significant (p > 0.05 or not significant determined using FDR).
709

Figure S8

Figure S8. Common coding dimensions for error and conflict and MSIT state space analyses.

(A) A common population coding dimension for error and conflict in MSIT. This coding dimension is extracted using dPCA, using an error contrast (error "sf" trials vs. "sf" trials) and a conflict contrast ("sf" trials vs. no conflict). "sf" trials are split into two non-overlapping groups for this. Plot show the decoding accuracy of both sf (apricot) vs no-conflict trials, and error "sf" vs. "sf" trials (out-of-sample). Horizontal bars at the top demarcate significant clusters, as determined by the cluster-based permutation test ($p < 0.05$).

(B) Same as in (A) but for Stroop data.

(C) Decoding accuracy of pairwise classification of conflict conditions after RT was equalized across conditions. Trials were selected such that RTs on si, fl, sf and non-conflict trials were equalized ($p > 0.1$, t test). Training data and left-out testing data from the four conflict conditions are projected to the population vector flanked by averages of non-conflict trials and sf trials, shown as the dotted line in Figure 4A. Color code represents decoding accuracy. This coding dimension separates the four conflict conditions well.

(D) Testing compositionality of conflict representation with condition generalization of decoding on *error* trials. Decoding accuracy were reduced on error trials compared to on correct trials (compare with Figure 4D). Dotted lines show 97.5^{th} percentile of the null distribution from permutation.

(E) Single neurons with nonlinear mixed-selectivity of Simon and Flanker conflict contribute to deviation of conflict representation from perfect linearity. Data used here are from the ex-ante epoch in (E) and ex-post epoch in (F). Nonlinear mixed-selectivity is measured by the F statistic of the interaction term between Simon and Flanker conflict in an ANOVA model with spike counts as the dependent variable. Each neuron's contribution to the deviation from linear additivity in the high dimensional neural space is quantified by the weight of the difference vector between "sf" and "si + fl". Scatter plot shows the relation between these two measures. Red line shows the linear fit.

(G-I) Distance between trajectories and average speed computed from trials binned by quartiles of Stroop (G), Simon (H), Flanker (I) conflict prior in the baseline (blue) and the ex-ante (orange) epoch, and trials grouped by Simon conflict posterior in the ex-post epoch (yellow). Trajectories are visualized in Figure 5E-G. The state space speed stays low during baseline, increases significantly during the ex-ante epoch and decreases back to a value similar to that during the baseline. Distance between trajectories is stable across time.

(J-L) Projection values on the coding dimension of Simon (J, $p < 0.001$ for both prior/posterior, prior $t(11996) = -39.5$, posterior $t(11996)=-47.5$), Flanker (K, $p < 0.001$ for both prior/posterior, prior $t(11996) = -38.2$, posterior $t(11996)=-43.6$) or Stroop (L, $p < 0.001$ for both prior/posterior, prior $t(11996) = -47.9$, posterior $t(11996)=-47.6$) prior or posterior (PC3 in Figure 5E-G). The order of projection values is on average consistent with the order of the prior/posterior levels, even though PCA does not have access to the order information.

748 **Figure S9. Task-invariant representation of performance monitoring signals.**

749
750 Because MSIT has two conflict conditions, Simon and Flanker, task invariance was investigated using Stroop/Simon
751 and Stroop/Flanker separately.

752
(A) Task-invariant decoding of conflict in MSIT (Flanker, yellow; Flanker red) and Stroop (green).
(B) Task-invariant decoding of errors in MSIT (salmon) and Stroop (crimson) after RTs were equalized across
conditions. The task-invariant coding dimension is extracted using dPCA that marginalizes out task information and
time. This dPCA coding dimension is extracted from the error contrast in Stroop (error conflict vs. correct conflict
trials) and the error contrast in MSIT (error "sf" trials and correct "sf" trials). Left, Accuracy for decoding errors as a
function of time. Bar on the right shows the variance explained by the different dPCA components (color code see
figure legend).
(C-D) Task-invariant decoding of conflict in MSIT (Simon, yellow; Flanker red) and Stroop (green) after RTs were
equalized across conditions. The dPCA coding dimension is extracted from conflict and non-conflict trials in Stroop
and either from Simon and non-Simon trials (C) or from Flanker and non-Flanker trials (D), by marginalizing out
task information and time. Left-out conflict trials and non-conflict trials in Stroop, and left-out Simon, non-Simon,
Flanker, non-Flanker trials in MSIT are projected and classified by this coding dimension. Left, decoding accuracy
of conflict as a function of time. The bar on the right shows variance explained by the different dPCA components
(color code see figure legend).
(E) Testing separability of conflict conditions in Stroop and MSIT using data from the ex-ante (left) and ex-post
epochs (right) after RTs were equalize across conditions. The dPCA coding dimension used in this analysis is
extracted by using conflict and non-conflict trials in Stroop and sf and non-conflict trials in MSIT by marginalizing
out task information. Because data from ROIs are used, temporal information is already marginalized out before
being used by the dPCA algorithm. Color coding represents decoding accuracy, orange numbers indicate the
numerical values of decoding accuracy of that pair of conflict conditions.
(F) Task-invariant decoding of all pairs of conflict prior levels in Stroop (lower triangle matrix) and Flanker (upper
triangle matrix). The dPCA coding dimension here is extracted using the Stroop conflict prior contrast (the 1^{st} vs. 4^{th}
quartile bins of Stroop conflict prior) and the Flanker conflict prior contrast (the 1^{st} vs. 4^{th} quartile bins of Simon
conflict prior), marginalizing out task information. Color code represents decoding accuracy. Bar at the bottom
shows variance explained of dPCA components.
(G) Same as in (F) but for Stroop-Simon posterior.
(H) Same as in (G) but for Stroop-Flanker posterior.
780

Figure S10

782 **Figure S10. Domain-general representation of performance monitoring signals (separated for the dACC and**
783 **the pre-SMA).**
784
(A) Task-invariant decoding of errors in both MSIT (salmon) and Stroop (crimson) using dACC neurons. This
dPCA coding dimension is extracted from the error contrast in Stroop (error conflict vs. correct conflict trials) and
the error contrast in MSIT (error "sf" trials and correct "sf" trials). This controls for trial conflict and isolates effects
related only to error. Left, Accuracy for decoding errors as a function of time. Bar on the right shows the variance
explained by the different dPCA components (color code see figure legend).
(B) Same as in (A) but for the pre-SMA.
(C-D) Task-invariant decoding of conflict in both MSIT (Simon, yellow; Flanker red) and Stroop (green), using
dACC data. Because MSIT has two conflict conditions, Simon and Flanker, task invariance was investigated using
Stroop/Simon and Stroop/Flanker conflicts separately. This dPCA coding dimension is extracted from conflict and
non-conflict trials in Stroop and either from Simon and non-Simon trials (C) or from Flanker and non-Flanker trials
(D), by marginalizing out task information and time. Left, decoding accuracy of conflict as a function of time. The
bar on the right shows variance explained by the different dPCA components (color code see figure legend).
(E-F) Same as in (C-D) but for pre-SMA data.
(G-H) Task-invariant decoding of all pairs of conflict prior levels. The dPCA coding dimension here is extracted
using the Stroop conflict prior contrast (the 1^{st} vs. 4^{th} levels of Stroop conflict posterior) and the Simon conflict prior
contrast (the 1^{st} vs. 4^{th} quartiles of Simon conflict prior) in (G), and Flanker conflict prior contrast (the 1^{st} vs. 4^{th}
quartiles of Flanker conflict prior) in (H), marginalizing out task information. Color code represents decoding
accuracy. Bar at the bottom shows variance explained of dPCA components.
(I-J) Same as in (G-H) but for conflict posterior.
(K-L) Same as in (G-H) but for pre-SMA data.
(M-N) Same as in (I-J) but for pre-SMA data.
806
807 Horizontal bars demarcate the extent of significant clusters in time as determined by the cluster-based permutation
808 test (p < 0.5).
809

Figure S11

Figure S11. Relation between single-neuron tuning properties and dPCA weights.

(A) Single-neuron contribution to task-invariant coding of conflict. Single-neuron coding strength of conflict is computed in the ex-ante epoch.

(B-E) Relationship between single neuron tuning strength of Stroop-Simon prior (B) Stroop-Flanker prior (C), Stroop-Simon posterior (D), Stroop-Flanker posterior (E) and dPCA weights. The data used for computing single-neuron coding strength is the same as used in constructing the corresponding dPCA coding dimensions.

Pie charts show the percentages of *tuned* neurons (total number is N_{sig}) that had a significant main effect for performance monitoring variable *only* ("task-invariant", red slice) and those that had a significant interaction effect with the task identity ("task-dependent", blue slice). Scatter plots (left) showed significant correlation between task-invariant coding strength and the corresponding dPCA weights. Right panel shows the regression weights between single neuron effect sizes and dPCA weights.

*p < 0.05, ** p < 0.01, *** p < 0.001, n.s., not significant (p > 0.05).

Table S1. Number of sessions and neurons recorded in each patient.

Patients ID	Age	Sex	Stroop			MSIT		
			# sessions	dACC	pSMA	# sessions	dACC	pSMA
P9HMH	M	55	1	9	0	NA	NA	NA
P11HMH	M	16	2	26	0	NA	NA	NA
P14HMH	M	31	2	5	0	NA	NA	NA
P16HMH	F	34	2	22	0	NA	NA	NA
P19HMH	M	34	1	13	0	NA	NA	NA
P21HMH	M	20	2	8	0	NA	NA	NA
P31HMH	M	30	1	3	0	NA	NA	NA
P41HMH	M	19	1	2	0	NA	NA	NA
P42HMH	M	29	1	2	0	NA	NA	NA
P24CS	F	47	2	17	46	NA	NA	NA
P25CS	F	36	2	32	0	NA	NA	NA
P26CS	F	36	1	16	0	NA	NA	NA
P27CS	M	45	1	2	2	NA	NA	NA
P29CS	M	19	1	9	9	NA	NA	NA
P31CS	M	31	2	38	9	NA	NA	NA
P32CS	M	19	1	0	5	NA	NA	NA
P33CS	F	44	4	66	25	NA	NA	NA
P34CS	M	70	5	26	0	1	4	0
P35CS	M	63	6	1	47	1	0	9
P36CS	M	45	6	8	64	NA	NA	NA
P37CS	F	33	11	107	40	5	64	17
P39CS	M	26	6	21	96	NA	NA	NA
P40CS	M	25	3	7	25	3	20	34
P42CS	F	25	5	83	60	8	45	97
P47CS	M	33	2	0	18	NA	NA	NA
P48CS	F	32	1	20	21	NA	NA	NA
P44CS	F	53	2	20	42	2	17	36
P49CS	F	24	NA	NA	NA	1	0	4
P51CS	M	17	NA	NA	NA	9	107	17
P55CS	F	43	NA	NA	NA	4	14	67
P56CS	M	48	3	4	15	NA	NA	NA
P60CS	M	67	NA	NA	NA	2	29	49
P61CS	F	52	4	7	79	4	7	77
P71CS	M	40	1	19	4	1	19	5

827
828 **Table S1. Number of sessions and neurons recorded**
829 Summary of number of neurons recorded in each subject. For some subjects, both the Stroop task and MSIT were
830 performed.
831

Table S2

BIC of RT

Compare RT tuned with no RT tuning or RL

	RT Tuned	no RT tuning	RL
MSIT	-686.3	-337.8	-450.9
Stroop	-1412.1	-904.1	-972.5

Compare RT tuned with previous conflict

	RT Tuned	Prev conflict
MSIT	-805.7	-440.1
Stroop	-1733.6	-1435.1

Table S2. Model comparisons for RT

Model comparison for RT using BIC. To test whether our RT-tuned Bayesian model explains variance in RT better than other models, we used linear mixed-effect models that considers subject variability (details of the model see **Methods**) and computed BIC for these models. The conflict prior is entered as a main fixed-effect and also as a by-session random effect. Here, conflict priors generated by four models are considered: "RT tuned", Bayesian conflict learning model with DDM hyperparameters and thus the conflict prior is tuned by RT. "No RT tuning", Bayesian conflict learning model without incorporating DDM likelihood for RT. "RL", a reinforcement learning model where the conflict probability is modelled as a "value" function and updated trial-by-trial by a simple update rule. "Prev conflict", a dummy variable indicating previous trial conflict. These linear mixed-effect models all have the same number of free parameters. A separate comparison was done between the RT tuned model with the model that uses the previous conflict (sub-table on the right) because the number of trials must be kept the same for the comparison and the "prev conflict" model did not consider the first trial for each session (there was no "prev conflict" in that case).

Table S3

BIC of conflict

	RT Tuned	no RT tuning	RL	no updating
MSIT	26517	26674	26958	28271
Stroop	23807	24039	24779	26498

849
850
851 **Table S3 Model comparison for trial congruency**
852
853 Model comparison for trial congruency using BIC. We used Bernoulli likelihood when computing BIC for the
854 conflict sequence. Note that the number of fitted parameters for Bayesian models is zero, for the "RL" model is one
855 (learning rate), and for "constant prior" model is one (the constant prior). BIC penalizes free parameters.
856

Methods

1. Tasks

Subjects performed a speeded version of the Stroop and Multi-Source Interference (MSIT) tasks. For the Stroop task, subjects were shown a series of randomly intermixed color words ("red", "green", "blue") printed in either red, green, or blue color (Fig. 1A). Subjects were instructed to name the color the word stimulus was printed in while ignoring its meaning and to do so as quickly and accurately as possible. For the MSIT task, subjects were shown an array of three numbers (0,1,2,3), out of which two were the same and the third of which was different (target). Subjects were instructed to press the button identical to the target number (which was unique) regardless of the position at which it was shown. For both tasks, all responses were recorded as button presses using an external response box (RB-740, Cedrus Corp., San Pedro, CA). For both tasks, the stimulus disappeared immediately when a button was pressed and was followed by a blank screen for 1s, followed by a feedback screen, which was shown for 1s. Subject were given three types of feedback: correct, incorrect or "too slow". The feedback in 10-15% of trials (regardless of whether they were correct or incorrect) was "too slow" based on an adaptive response threshold (see (34) for details), which we used to emphasize the need to respond quickly and thereby resulting in a sufficiently large error rate. The inter-trial interval was sampled randomly from a uniform distribution between 1.5s to 2s. Trial sequences were pseudo-randomized and designed to avoid back-to-back repetitions of the same stimulus. The proportion of conflict trials in the Stroop task was 33%; For MSIT, the proportions of Simon only ("si"), Flanker only ("fl"), Simon and Flanker coincident ("sf") trials are 15%, 15%, and 30%, respectively (the remaining 40% of trials have no conflict). The tasks were implemented in MATLAB (The Mathworks, Inc., Natick, MA) using Psychtoolbox-3 (78). The two tasks were performed in sequence, i.e., subjects finished blocks of one task first and then moved on to blocks of the other task. The order of task performed was randomized across experimental sessions.

2. Behavioral controls

As a control, we additionally collected behavioral data from N = 51 normal control subjects (24 females; age mean±sd: 44±11) using the Amazon mTurk platform. We implemented the MSIT task as described above using the jsPsych toolbox (79). These behavioral data were analyzed using the same methods as documented below. These control subjects exhibited a robust conflict prior effect like the patients (Fig. S1D).

3. Subjects

34 patients (see Table S1 for age and gender) who were evaluated for possible surgical treatment of their focal epilepsy using implantation of depth electrodes volunteered for the study and gave written informed consent. We only included patients with well-isolated single- neuron activity on at least one electrode in the dACC or preSMA. All research protocols were approved by the institutional review boards of Cedars-Sinai Medical Center, Huntington Memorial Hospital, and California Institute of Technology.

903
904 ### 4. Electrophysiological recordings
905
We analyzed data from up to 4 electrodes in each subject (bilateral dACC and pre-SMA. For
each depth electrode, there are eight microwires with high impedance microwires at the tip, and
eight macro contacts with low impedance along the shaft (AdTech Medical Inc.). Data from all
microwires and the most medial macro contact (which is placed within dACC or pre-SMA) are
analyzed in this paper. For recordings from microwires, the sampling rate was 32-40kHz and the
raw signal was acquired broadband (0.01Hz-9kHz). One microwire on each depth electrode was
designated as a local reference wire. For intracranial EEG recordings done with macro contacts,
the sampling rate was 2kHz (ATLAS, Neuralynx, Inc., Bozman, MT).
914
915 #### Electrode localization
916
Electrodes were localized using a combination of a pre-operative MRI and a postoperative
MRI/CT using standard procedures we described elsewhere (*34*, *80*).
Only electrodes that could be clearly localized to the dACC (cingulate gyrus or cingulate sulcus;
for patients with a paracingulate sulcus, electrodes were assigned to the dACC if they were
within the paracingulate sulcus or superior cingulate gyrus) or the pre-SMA (superior frontal
gyrus) were included.
923
924 #### Spike detection and sorting
925
926 We filtered the raw broadband signal with a zero-phase lag filter in the 300-3000Hz band. Spikes
927 were detected and sorted using a template-matching algorithm (*81*). Sorting quality is evaluated
928 using the same metrics reported in (*34*) and only well-isolated single units are included in this
929 paper. Channels with interictal epileptic events were excluded.
930
931 ### 5. Quantification and statistical analyses
932
933 #### Behavioral modelling and analyses
934
We developed a Bayesian conflict learning model to infer subjects' internal estimate of conflict
probability (details see below). For this analysis, we concatenated all blocks of an experiments
done in a single session. For trials with unusually long RTs (> 3 sd from the mean RT of the
session), we replaced the outlier's RT with the average RT computed from the neighboring 6
trials. We estimate the Bayesian model parameters using all trials but excluded error trials (after
fitting) for analyses that focuses on conflict and conflict prior. We then analyzed whether the
variance of RT was related to the estimated parameters using linear mixed-effect models (*82*).
For MSIT, the linear mixed-effect model is specified as follows (all models are represented in
Wilkinson's notation):
944

$$\log(RT) \sim Simon\ prior * Simon\ conflict + Flanker\ prior * Flanker\ conflict + (1 \\ + Simon\ prior + Flanker\ prior | sessionID : subjectID)$$

945
946 For Stroop, this is specified as:

$$\log(RT) \sim Stroop\ prior * Stroop\ conflict + (1 + Stroop\ prior | sessionID: subjectID)$$

Here, the fixed effects of Simon, Flanker and Stroop conflicts are dummy variables indicating
whether a particular trial involves conflict (value = 1) or not (value = 0). The fixed effects for
priors are obtained from our Bayesian conflict learning models as detailed below. To test if RT
was affected by conflict on the immediately preceding trial, represented by
$Simon\ prevConflict$, $Flanker\ prevConflict$ and $Stroop\ prevConflict$, we again
constructed a linear mixed-effect models for both MSIT and Stroop. For MSIT, the model is
specified as follows:

$$\log(RT) \sim Simon\ prevConflict * Simon\ conflict + Flanker\ prevConflict$$
$$* Flanker\ conflict + (1 | sessionID: subjectID)$$

957
958 For Stroop, this is specified as:

$$\log(RT) \sim Stroop\ prevConflict * Stroop\ conflict + (1 | sessionID: subjectID)$$

961 We investigated the effect of conflict prior on the likelihood of making an error using
962 generalized linear mixed-effect models. For MSIT, this model is given as

$$Outcome \sim Simon\ prior * SF + Flanker\ prior * SF + (1 + Simon\ prior$$
$$+ Flanker\ prior | sessionID: subjectID)$$

965 where SF is a dummy variable indicating whether the trial has both Simon and Flanker conflict
966 (value = 1) or non-conflict (value = 0). We restricted this analysis to sf trials because most errors
967 occurred on these trials. For Stroop, this model is given as

$$Outcome \sim Stroop\ prior * Stroop\ conflict + (1 + Stroop\ prior | sessionID: subjectID)$$

The response variable $Outcome$ is a categorical variable indicating whether the trial ended in a
correct (0) or incorrect (1) response.
To determine the statistical significance of each fixed effect, we compared the full model with a
reduced model where the fixed effect in question was removed using the likelihood ratio test. To
determine whether RT tuning of the model (see below) is necessary for conflict prior to explain
RT variance, we replaced the conflict prior with the one estimated without RT tuning and kept
all other terms the same. Statistical significance determined this way was indicated by stars or
"n.s" (non-significant) in Figures 1 and S1. To determine whether the conflict prior explains
variance in RT and error likelihood independent of practice, which is assumed to vary with the
trial number, we augmented the aforementioned mixed-effect models by including three
additional trial-ID terms: $trialID, trialID^2, trialID^3$ to capture variance related to the practice
effects.

Bayesian conflict learning models

Our models are structurally similar to those used in several previous studies (*51, 54*). Here, we
briefly highlight the modifications we made to extend these existing models to model behavior in
both the Stroop and MSIT tasks, the latter of which has two types of conflicts that are monitored
at the same time. Our models have the following parameters (see Fig. 1C for a schematic of the
model structure): 1) a flexible learning rate α, which captures the subject's belief in the rate of
change in control demand in the environment (i.e., a change in conflict probability), and 2)
conflict probability (q_s for Stroop conflict in the model for Stroop, q_{si} for Simon and q_{fl} for
Flanker conflicts in the model for MSIT). The models utilize two types of data (both of which
are only available after a trial's response has been made): 1) trial congruency o (value of 1
indicates an incongruent trial; o_s for Stroop congruency, o_{si} for Simon congruency and o_{fl} for
Flanker congruency; 2) reaction time RT, assigning Bernoulli likelihood function to the former
and the drift-diffusion model (DDM) likelihood function to the latter (details see below). Prior
work (*51*) uses a Gaussian likelihood function to describe RT generation, but we argue that the
use of DDM has several advantages over the Gaussian approach: 1) fewer parameters are used in
the DDM, making it computationally possible to model two types of MSIT conflict at the same
time; 2) the DDM parameters have physiological meaning and thus also provide a clear
physiological reasoning for conflict prior to affect specific components of the decision process; 3)
DDM has been widely used and validated as the generative framework to model RT during
decision making (*83, 84*).
1004
Estimating control demand is operationalized as estimating the probability that a certain conflict
(Stroop, Simon or Flanker) would occur in the block. One advantage of our models is that
conflict probability and the rate of change in conflict probability are both estimated in an online
manner, i.e., the models iteratively update their current estimates after every trial with new
incoming data (of that trial) using Bayes' law. This is consistent with the way human subjects
perform conflict tasks while estimating the associated control demand: they perform and estimate
trial-by-trial. Note that in this study the conflict probability was constant throughout the
experiment (unbeknownst to subjects). Nevertheless, we allow the model to infer the learning
rate α online because humans demonstrate inherent bias in believing that environmental statistics
are not stable (*85*). There is therefore no fitting involved for estimating α and thus the models are
not penalized for including this parameter in model comparisons. Note that we use a single α for
both types of conflicts in MSIT. To simplify model estimation, we made the Markovian
assumption that the current estimate of conflict probability depends only on the current trial
congruency and RT, and the estimated conflict probability on the last trial, but not on the full
history of past trial conflict probability (*54*). The iterative estimation of conflict probability then
involves combining the estimated conflict probability from the previous trial (prior), transition
functions capturing how the current estimate will change from the previous one (the probability
of current estimate conditional on previous estimate) and the likelihood function.
1023
1024 The model starts with a transition function for the learning rate α:
1025

$$p(\alpha_{i+1}|\alpha_i) = k\delta(\alpha_{i+1} - \alpha_i) + 1 - k$$

1026
1027 This formulation assumes that the learning rate has a probability k of having the same
1028 distribution as that of the preceding trial but with a probability 1-k of switching to a uniform
1029 distribution (over all possible α), because the learning rate is largely stable across time. The

transition function for conflict probability concerning the transition from the current estimate to a future estimate is computed in two steps. Here, we refer to the current-trial estimate of conflict probability for Stroop, Simon or Flanker generically as q_i, to which we assigned a uniform prior. The transition function is thus denoted as $p(q_{i+1}|q_i, \alpha_i)$. First, an auxiliary variable $q_{i+0.5}$ is constructed, which is a beta-distributed random variable with its mode being q_i and the sum of two parameters being $\frac{1}{\alpha_{i+1}}$:

$$v_{i+1} = \frac{1}{\alpha_{i+1}} - 2$$

$$q_{i+0.5} \sim Beta(q_i v_{i+1} + 1, v_{i+1} - q_i v_{i+1} + 1)$$

The conflict probability transition function is then constructed as

$$q_{i+1} \sim q_{i+0.5} + \alpha_{i+1}(o_i - q_{i+0.5})$$

The transition function adopts a classical update rule used in reinforcement learning models, and the learning rate controls the balance between past ($q_{i+0.5}$) and current information (o_i). For the MSIT model, we take the product of the transition functions computed separately for Simon and Flanker predicted conflict. Finally, we consider the likelihood function. Since the trial sequences were designed and re-used for different subjects, the estimated conflict probability would be the same across subjects for the same sequence, but this is inconsistent with the fact that such individual estimates should be subjective and different between participants. We thus incorporated RTs from each subject, which are assumed to be generated through a drift-diffusion process, to estimate a *subjective* conflict probability based on the assumption that a subjects' RT reflects the extent to which they engaged control. RT is assumed to be generated by a diffusion process. The two bounds of DDM used here represent the correct and wrong choice (not response options). The diffusion process accumulated the *difference* in the evidence between the target and distractor response (Fig. 1C, right), which is smaller for conflict trials and thus leads to longer RTs. We refer to the drift-diffusion likelihood function (*86*) for RT as $p_{DDM}\left(v_{si}, v_{fl}, v_{sf}, v_{non-conflict}, vz_{si}, vz_{fl}, a, q_{si}, q_{fl}\right)$ for the MSIT model, and $p_{DDM}\left(v_{conflict}, v_{stroop\,non-conflict}, vz, a, q_s\right)$ for the Stroop model. The hyperparameters specifying the DDM are boundary separation (a), base drift rates for Simon-only, Flanker-only, both Simon and Flanker present, and non-conflict trials in MSIT ($v_{si}, v_{fl}, v_{sf}, v_{non-conflict}$), base drift rates for conflict and non-conflict trials in Stroop ($v_{conflict}, v_{stroop\,non-conflict}$), and drift rate bias coefficients that scales the conflict probability of Simon, Flanker and Stroop (vz_{si}, vz_{fl}, vz). The effective drift rate is then the sum between the base drift rate and the drift rate bias (Fig. 1C). Here we made the assumption that conflict prior affects RT by biasing *drift rates* based on a previous work investigating the effect of choice history on RT (*87*). We also assumed that the drift rate diffusion started at the half point of the boundary separation (i.e., $z = 0.5$). With the Markovian assumption, the updating process for the MSIT model is thus given by

$$p\left(k, \alpha_{i+1}, q_{si,i+1}, q_{fl,i+1}|o_{si,\leq i+1}, o_{fl,\leq i+1}, RT_{\leq i+1}\right) \propto p\left(o_{si,i+1}, o_{fl,i+1}, RT_{i+1}|q_{si,i+1}, q_{fl,i+1}\right)$$

$$\iint \left[\int p\big(k, \alpha_i, q_{si,i}, q_{fl,i} \big| o_{si,\leq i}, o_{fl,\leq i}, RT_{\leq i}\big) p(\alpha_{i+1}|\alpha_i, k) d\alpha_i \right] p\big(q_{si,i+1}\big|q_{si,i}, \alpha_i\big) p\big(q_{fl,i+1}\big|q_{fl,i}, \alpha_i\big) dq_{si,i} dq_{fl}$$

The updating process for the Stroop model is given by

$$p\big(k, \alpha_{i+1}, q_{s,i+1} \big| o_{s,\leq i+1}, RT_{\leq i+1}\big)$$
$$\propto p\big(o_{s,i+1}, RT_{i+1}\big|q_{s,i+1}\big) \int \left[\iint p\big(k, \alpha_i, q_{s,i}\big| o_{s,\leq i}, RT_{\leq i}\big) p(\alpha_{i+1}|\alpha_i, k) d\alpha_i \right] p\big(q_{s,i+1}\big|q_{s,i}, \alpha_i\big) dq_{s,i}$$

The likelihood function is the product of Bernoulli likelihood for trial congruency and DDM likelihood for RT. For MSIT, the likelihood function is given as:

$$p\big(o_{si,i+1}, o_{fl,i+1}, RT_{i+1} \big| q_{si,i+1}, q_{fl,i+1}\big) = \big(1 - \big|o_{si,i+1} - q_{si,i+1}\big|\big)\big(1 - \big|o_{fl,i+1} - q_{fl,i+1}\big|\big) p_{DDM}$$

For Stroop, the likelihood function is given as:

$$p\big(o_{s,i+1}, RT_{i+1} \big| q_{s,i+1}\big) = \big(1 - \big|o_{s,i+1} - q_{s,i+1}\big|\big) p_{DDM}$$

These hyperparameters are estimated using an expectation-maximization (EM) algorithm as shown in earlier work (*51*). Briefly, the model parameters were at first estimated *without* incorporating the DDM likelihood for RT ("E" step). Hyperparameters were then fit by maximizing the DDM likelihood for the observed RT using the conflict priors obtained ("M" step). The DDM likelihood function with the fitted hyperparameters were then incorporated into the Bayesian updating process ("E" step) to generate a new set of conflict priors, which were then used to maximize the DDM likelihood over observed RT again. These steps were repeated until the convergence of both model parameters and hyperparameters (Euclidean distance between parameter vectors from successive iterations $< 10^{-5}$).

We considered three alternative classes of models: 1) reinforcement learning (RL) models; 2) constant model; 3) Bayesian learning model without RT tuning. For the RL model, we constructed a value function corresponding to the estimated conflict probability, and this estimate is also updated trial-by-trial using a Rescorla-Wagner rule. For MSIT, the update rule is:

$$q_{si,i+1} = q_{si,i} + \alpha\big(o_{si,i+1} - q_{si,i}\big)$$

$$q_{fl,i+1} = q_{fl,i} + \alpha\big(o_{fl,i+1} - q_{fl,i}\big)$$

For Stroop, the update rule is:

$$q_{s,i+1} = q_{s,i} + \alpha\big(o_{s,i+1} - q_{s,i}\big)$$

The free parameter α in the RL models was fit by maximizing the data likelihood (Bernoulli) for trial congruency. For the constant model, q_s, q_{si}, q_{fl} were fit directly by maximizing the data likelihood for trial congruency. For Bayesian conflict learning models without RT tuning, q_s, q_{si}, q_{fl} were estimated online but the likelihood function for RT was not incorporated in the process.

1104
We used the Bayesian Information Criterion (BIC) to compare the RT-tuned Bayesian conflict
learning models with the RL models, constant models and the non-RT tuned Bayesian conflict
learning models. We compared these models separately for their ability to explain trial
congruency and RT. For this analysis, we pooled all data from all sessions and computed the BIC
for each model and for each data type (RT or trial congruency), consistent with a previous study
(*54*). Results of model comparisons can be found in Tables S2 and S3.
1111
1112 *Selection of neurons*
1113
We defined the epochs of interests according to events in the tasks (Fig. 3A). The baseline epoch
starts at 1.5s before stimulus onset and ends at stimulus onset. This epoch is used to analyze
encoding of conflict prior. The ex-ante epoch is anchored to the midpoint of a period of time
starting at 100ms after stimulus onset (to account for the minimal delay needed for visual
information to reach the MFC) and ending at the time of button presses. We then defined the ex-
ante epoch as a 500ms window centered on the midpoint of this period. The rationale for
analyzing conflict signals in this epoch is as follows: at the early stage of stimulus processing,
information about the different response options is not yet fully processed and hence minimal
conflict; the conflict signal should reach its maximum when the different stimulus dimensions
that drive competing responses are fully available; and finally, it should subside after a response
is selected. We counted the number of spikes in these epochs and regressed the spike counts
against the different regressors (error, conflict, conflict surprise, conflict prior and conflict
posterior) using linear regression. For each regressor, we extracted a p value computed from the
F test. A neuron was deemed selective for this regressor when $p < 0.05$. For MSIT, since there
were both Simon and Flanker conflicts, neurons were selected when regressors related to either
Simon or Flanker conflict were significant (e.g., ex-ante conflict cells in MSIT were the union of
neurons selective for Simon conflict and Flanker conflict during the ex-ante epoch). To assess
whether a neuronal class is significantly present in the population, we derive a null distribution
by permuting the relation between spike counts and the regressor of interest for 1000 times. A p
value is computed by comparing the true proportion of selected neurons against this null
distribution. The 95th interval of the null distribution for each neuronal class is plotted as dotted
lines in Fig. 3B and Fig. S3A-B.
To statistically compare the extent of multiplexing between two groups of cells active in
different epochs (Fig. 3D), we used the chi-squared test and reported the p-value and effect size
of the test.
1139
1140 *Single-trial spike train latency*
1141
We estimated the onset latency in individual trials using Poisson spike-train analysis (Fig. 3E)
(*88*). This method detects the moments when the observed inter-spike intervals (ISI) deviate
significantly from that assumed by a constant-rate baseline Poisson process. We used the spike
rate averaged across the whole block of experiment as a baseline spike rates for each neuron.
This baseline rate was then used to compute a Poisson surprise metric across the spike train. We
started our detection algorithm from the onset of stimulus for each trial. For the ex-ante conflict
neurons (two columns on the left), we restricted the range in which the detection algorithm looks
for bursts to after stimulus onset and before button presses. This is because, by their definition,

ex-ante conflict neurons carried a conflict signal before action. For the ex-post conflict neurons
(two columns on the right), we restricted the range to 200ms before button presses and before
end of trial. We then extract the latency of the first significant burst. The statistical threshold for
detecting an onset was $p < 0.01$. Repeating the same procedure with a threshold of $p < 0.001$ did
not affect our conclusions. For these analyses, we only used the conflict trials as we focused on
the single-trial conflict response of selected conflict-encoding neurons.
1156
1157 *Detrended fluctuation analysis*
1158
Detrended fluctuation analysis (DFA) was first developed by Peng and colleagues (*89*, *90*) to
quantify self-similarity in time series data. We use DFA to quantify the self-similarity in baseline
spike counts on the scale of *trials.* First, the cumulative sum of the spike counts during baseline
was computed. To be consistent with prior literature we refer to this cumulative sum as the
signal profile. A set of trial window sizes were defined between the lower bound of 4 trials and
the upper bound of the block length. For each window size, we then partitioned the signal profile
into a series of data snippets. Partitioning was done such that two adjacent snippets had an
overlap of half the window size. We then removed the linear trend from each data snipped (using
least square regression) and computed the standard deviation across time. The mean of the
standard deviations across all snippets of identical window size was then computed (y axis of Fig.
S3H). Finally, the mean standard deviations were regressed linearly against the logarithmically
scaled time windows and the slope was extracted as the DFA α value (Fig. S3H shows the
fluctuations as a function of logarithmically transformed trial window sizes for two example
neurons).
For Fig S3C-D, we tested the relation between a neuron's baseline DFA α value and its tendency
to encode conflict prior. To avoid selection bias, we split trials into two sets of equal size, with
one half consisting of a consecutive run of trials. This is because DFA is used for time series data
and thus required the data be consecutive and temporally ordered. For randomization, we first
randomly sampled one trial from the first half of the block. Then a consecutive run of trials
starting with this randomly picked trial as the starting point were extracted. The consecutive set
was used to compute DFA α value while the rest of the trials were used to correlate with conflict
prior (Simon, Flanker or Stroop) using Spearman rank correlation.
1181
1182 *Decoding analysis (Support-vector machine)(Figs. S5,S6)*
1183
Data were aggregated from different experimental sessions to create pseudo-population data
matrices. We constructed for each trial a peri-stimulus time histogram (PSTH) using 500ms bins
in steps of 25ms. For all conflict or conflict prior -related decoding, we used correct trials only.
Since different behavioral sessions had different number of trials (some subjects participated in
less sessions than the others), we subsampled the same number of trials from each condition for
each neuron and repeat this process 50 times.
For error decoding (Fig. S5A-B), we subsampled 10 error trials and 10 correct conflict trials for
Stroop and 10 correct sf trials for MSIT. Since most errors occurred on high conflict trials, these
contrasts isolate the effect of error while controlling for the effect of conflict.
For conflict decoding (Fig. S5C-E), we subsampled 30 trials from each conflict conditions:
conflict and non-conflict trials for Stroop; Simon and non-Simon trials, Flanker and non-Flanker
trials for MSIT.

For conflict prior (or posterior, Fig. S6), trials were binned by quartiles of conflict prior (or
posterior) into four bins ("levels") separately. For each pair of levels, one decoder was trained
and tested. This analysis used spike counts from the ex-ante or ex-post epochs (ROIs).
For each time bin or ROI, we performed 5-fold cross validation using LIBSVM (*91*). We used
the linear kernel and set the *c* parameter to 1 for all analyses. In brief, trials were first randomly
split into 5 equal parts; each part was used in turn as the testing data while the rest of the four
parts were used as training data. Decoding accuracy was the proportion of correct classifications
among the 250 samples (50 resamples x 5 folds). Note that the resampling was done once to
generate testing and training sets for the whole time series and used for both within-time and
across-time decoding. For within-time decoding (All plots with dotted lines in Fig. S5 and plots
within dotted frames in Fig. S6), the SVM classifier trained using the training data from each
time bin was tested using the testing data from the same time bin. For cross-temporal decoding
(temporal generalization; all plots with solid lines in Fig. S5 and plots without dotted frames in
Fig. S6), the SVM classifier trained using the training data from each time bin were tested across
the trial using testing data gathered from other time bins.
1211
1212
1213 *Reaction times equalization*
1214
For analyses shown in Fig. S9B-E, we selected a subset of trials from each condition so that the
RTs did not differ significantly across conditions (e.g., equalizing RTs between conflict and non-
conflict trials in the Stroop data). Here we detail the RT equalization procedure we used to create
"RT equalized sets". We first selected a condition as the "anchor" condition. We sorted the RTs
of the anchor condition, and for each RT we searched in the target (to-be-equalized) condition(s)
for a trial whose RT did not differ from the anchor RT by more than 0.1s. If all RTs in the target
condition differed from the anchor RT by > 0.1s, the anchor RT was not included in the RT
equalized set. Once selected, the anchor RT and the target RT were both removed from the
original set to ensure that no trials were included twice in any RT equalized trial sets. This
procedure was repeated until one of the conditions considered were emptied. We confirmed post
hoc that RT equalization was successful by testing whether RTs were not significantly different
using ANOVA (p > 0.5 for all the RT equalized sets).
1227
1228
1229 *Decoding analysis (population activity vectors and demixed PCA)*
1230
Data were aggregated from different experimental sessions to create a pseudo-population. We
randomly selected one trial for each neuron from one condition and concatenate the data from
each neuron to form a single-trial testing data matrix. The rest of the trials were averaged for
each condition and concatenated to form a training data matrix. Coding dimensions were defined
based on the condition-averaged training data. To define the coding dimensions used to decode
conflict conditions within MSIT, we used the population activity vectors (a high dimensional
vector in the raw firing rate space) defined by the difference between the two condition means.
To define coding dimensions for the cross-task decoding problems we used dPCA to extract
demixed principal components (dPC). Details of which trials were used to define the coding
dimensions are given in the sections to follow. Both testing and training data were projected onto
the identified coding dimensions. The labels for testing data were assigned according to the label

of the nearest neighbor of the training data. To test condition generalization, we projected the
testing data from one pair of conditions to a coding dimension defined by another pair of
conditions (e.g., a Simon trial and non-Simon trial projected to the population vector flanked by
Flanker and non-Flanker trial averages) and classified using the labels of the nearest projected
training data. This decoding procedure was repeated 1000 times (resulting in 1000 single-trial
testing data matrices and the corresponding training data matrices), and the decoding accuracy
was defined by the proportion of correct classifications among these 1000 repetitions. To
determine statistical significance, we permuted the trial labels for 500 times and for each
permutation, we repeated all above steps to generate a null distribution. A p-value was computed
from comparing the true decoding accuracy with the null distribution.
1252
1253 *Pseudo-population matrices for MSIT state space analyses*
1254
For Fig. 4E-G, trials were binned by quartiles of conflict prior (or posterior) into four bins
("levels") separately. However, because conflict prior was updated into conflict posterior after
each button press, binning priors does not guarantee that the posteriors would fall into the same
bins. This is because updating is specific to each behavioral session and thus differs between
neurons. Averaging trials using only bins formed by prior quartiles would thus mix trials with
different levels of posterior for each neuron. To avoid this problem, we thus formed the data
matrix (which now includes the time dimension rather than a single ROI; spikes were counted in
500ms bins swept across the whole trial in steps of 25ms; spike trains were aligned to button
presses) by concatenating two submatrices: one that was constructed by averaging trials within
bins defined by prior quartiles using data *before* button presses, and one that was constructed
from averaging trials within bins defined by posterior quartiles for neural data *after* the button
press. We then used PCA to find the three PCs that explained the most variance for this matrix.
The concatenated data matrix was then projected onto these PCs to generate the visualization of
trajectory corresponding to prior (or posterior) levels.
1269
1270 *Population coding dimensions for conflicts within MSIT*
1271
We next describe how coding dimensions were defined in each case using population activity
vectors in the raw firing rate space. For Fig. 4B, the coding dimension was the population vector
flanked by the trial averages of sf and non-conflict trials (Fig. 4A, dashed lines). Classifications
were carried out between pairs of conflict conditions (e.g., between si and fl trials) as detailed
above. For Fig 4C, we took a bin-wise approach to investigate whether Simon conflict
representation generalize to Flanker representation, and vice versa. For this, we split trials into
four non-overlapping groups: Simon, Flanker, non-Simon, non-Flanker trial sets. We split sf and
non-conflict trials randomly in half. One half of sf trials were pooled with si trials to form the
Simon trial set, and one half of non-conflict trials were pooled with fl trials to form the non-
Simon trial set. The other half of sf trials were then pooled with fl trials to form the Flanker trial
set, and the other half of non-conflict trials were pooled with si trials to form non-Flanker trial
set. Using these trial sets, for each time bin we extracted two coding dimensions from the
training data: one population vector flanked by trial averages of Simon and non-Simon trials
(Simon coding dimension), and one population vector flanked by the trial averages of Flanker
and non-Flanker trials (Flanker coding dimension). We then projected the testing data from
Simon and non-Simon trials onto the Flanker coding dimension and classified the testing data

using the closest projected training data, and vice versa. For details of this classification
procedure see above paragraph. This assesses the extent to which coding of Simon and Flanker
conflict is abstract.
1291
1292 *Compositionality of conflict representations within MSIT*
1293
For Fig. 4D, the coding dimensions were taken to be the blue and orange edges as shown in
Figure 6A. The purpose of this analysis is to assess to what extent the representation of conflict
is compositional (within a task). We assumed that in the neuronal firing rate space, the
representation of Simon/Flanker conflict is a vector pointing from non-conflict trial averages to
the si/fl trial averages. Compositionality of such conflict representation would imply that the sf
representation (vector pointing from non-conflict trial average to the sf trial average) is equal to
the sum of the Simon and Flanker representations. According to the parallelogram law of vector
addition, this then corresponds to the blue and orange edges in Fig. 4A forming a parallelogram.
We tested the extent of parallelism in the data using decoding. The coding dimensions here were
defined by the following population vectors using training data: one flanked by non-conflict and
si trial averages (Fig. 4A, blue), one flanked by fl and sf trial averages (blue), one flanked by fl
and non-conflict trial averages (orange) and one flanked by si and sf trial averages (orange).
Left-out testing data from conditions flanking one of the blue or orange pair of edges were then
projected to the other edge in the pair and classified by the training data defining this edge. For
example, single-trial testing data of non-conflict and si trials were projected to the coding
dimension flanked by fl and sf trial averages and were classified by fl or sf trial averages.
1310
1311 *Relationship between single neuron tuning and the compositional conflict representations within*
1312 *MSIT*
1313
For Fig. S8E-F, the goal is to investigate the relation between the nonlinearity in single neuron
conflict coding and the deviation from compositionality in state space representation of conflict.
We denote the state-space representation of Simon and Flanker -only conflict as the population
vectors flanked by the trial averages of si and non-conflict and by the trial averages of fl and
non-conflict. We refer to the state space location occupied by the linear sum of Simon and
Flanker representation defined above as "s+f". The deviation from perfect compositionality is
then given by the population vector flanked by "sf" and "s+f". The loading of "sf" to the "s+f"
vector reflects the single neuron contribution to the deviation at the population level. To quantify
nonlinearity of conflict coding for each neuron, we first regressed the spike counts in the ex-ante
or ex-post epoch (1s) against three fixed effects: a Simon effect (dummy variable indicating the
presence or absence of Simon conflict on a trial), a Flanker effect (dummy variable indicating the
presence or absence of Flanker conflict on a trial) and the interaction term between these two.
We extracted the F statistic related to the interaction term, which captures the effect of nonlinear
mixing of Simon and Flanker conflict. We then extracted a population vector flanked by the sf
trial average and and "s+f", the sum of two population vectors one flanked by trial averages of si
trials and non-conflict trials, and one flanked by trial averages of fl trials and non-conflict trials.
We then correlated the loading of "sf" - "s+f" vector and the F statistics from a particular neuron.
1331
1332 *Quantification of state space dynamics*
1333

For Fig. S8G-I, we binned spike counts using 250ms bins swept across the trial in steps of 10ms.
The state-space speed was defined to be the Euclidean distance between population vectors of
adjacent time bins divided by the step size. We averaged the state-space speed across time within
an epoch. We also computed the Euclidean distance between pairs of trajectories (1^{st} and 2^{nd}, 2^{nd}
and 3^{rd},3^{rd} and 4^{th}) and averaged this across trajectories and across time bins within an epoch.
State-space speed and the averaged distance between trajectories were plotted against each other
in Figure 6I. Our method for extracting speed in state-space follows prior work (*92*).
1341
1342 *Testing ordinal relationship of prior (or posterior) projections*
1343
We analyzed the ordinal relation between neural projections of prior (or posterior) as shown in
Fig. S8J-L. PCA axes encoding prior/posterior variance were extracted from spike count data
collected in ROIs (baseline for prior and the ex-post epoch (0-1s after button presses) for
posterior). Since prior/posterior is continuously valued, we created four trial conditions by
binning the trials using quartiles of prior/posterior. For each type of prior or posterior (Simon,
Flanker and Stroop), we projected the left-out trial (not used for computing the PCA axis) onto
the PCA axis for each trial condition and this procedure was repeated 1000 times, yielding 1000
projected values for each trial condition. We then regressed the projected values (concatenated
into a vector) against their trial condition labels (1^{st},2^{nd},3^{rd},4^{th} quartile bins) using a multinomial
logistic regression with the assumption of ordinal relation between trial groups. Essentially, we
were testing whether the out-of-sample project values can reliably predict the trial condition they
belong to assuming that the conditions were ordinal. We reported the p-value and t-statistic of
the effect of projected values.
1357
1358
1359 *Demixed Principal Component Analyses (dPCA)*
1360
We used dPCA to extract task-invariant representation of performance monitoring signals. We
use "s", "si" and "fl" to denote Stroop, Simon and Flanker conflict condition, respectively. We
use "sf" to denote the condition where both Simon and Flanker conflict are present.
Analyses on conflict and conflict prior (or posterior) used only correct trials. We used dPCA as
described previously (*56*), with the following adaptions. The dPCA algorithm first decomposes
population neural activity into marginalized data matrices with respect to the variables of interest.
We constructed the marginalized population activity (referred generically as $\overline{X_\phi}$) with respect to
error ($\overline{X_{error}}$ in Fig. 5A) or conflict ($\overline{X_{conflict}}$, Fig. 5B, Fig. S9A) by marginalizing out *time* and
task identity dimensions (denoted by "$\langle \cdot \rangle_{task,t}$").
For interpretability, we investigated whether the neural representation is abstract across tasks
separately between Stroop and Simon conflict ("$s\ \&\ si\ conflict$" is an indicator variable
marking the presence or absence of conflict in either tasks) and between Stroop and Flanker
("$s\ \&\ fl\ conflict$" is an indicator variable marking the presence or absence of conflict in either
tasks). Set up this way, the "task" dimension captures variance related to task set differences
(Stroop vs. MSIT). To compute marginalized averages, we use N-dimensional population
activity
1377

$$\overline{X_{Stroop\ error\ \&\ MSIT\ error}} = \langle r(error, task, t) - \bar{r}(t) \rangle_{task,t}$$

1378

$$\overline{X_{s\ \&\ si\ conflict}} = \langle r(s\ \&\ si\ conflict, task, t) - \bar{r}(t)\rangle_{task,t}$$

1379

$$\overline{X_{s\ \&\ fl\ conflict}} = \langle r(s\ \&\ fl\ conflict, task, t) - \bar{r}(t)\rangle_{task,t}$$

1380
, where $\bar{r}(t)$ is the firing rate averaged across trials and time bins. For Figure S9B-D, these
definitions are the same except that RT equalized trial sets were used.
For Figure S8A-B, we sought a common coding dimension between error and conflict separately
in MSIT and Stroop, by marginalizing out the information about time and which pair of
conditions were contrasted (denoted by "$\langle \cdot \rangle_{contrast,t}$"; The "contrast" indicator, for MSIT it
indicates whether the contrast considered is sf vs. non-conflict or error sf vs. correct sf; for
Stroop it indicates whether the contrast considered is correct conflict vs. correct non-conflict or
error vs. correct conflict). For Fig S8A-B, we constructed the marginalized population activity
with respect to error vs conflict in both MSIT ($\overline{X_{MSIT\ error\ \&\ sf}}$, $MSIT\ error\ \&\ sf$ is an indicator
variable marking the presence or absence of errors and MSIT sf conflict) and Stroop
($\overline{X_{Stroop\ error\ \&\ s}}$, $Stroop\ error\ \&\ conflict$ is an indicator variable marking the presence or
absence of errors and Stroop conflict) as follows:
1393

$$\overline{X_{MSIT\ error\ \&\ sf}} = \langle r(MSIT\ error\ \&\ sf, contrast, t) - \bar{r}(t)\rangle_{contrast,t}$$

1394

$$\overline{X_{Stroop\ error\ \&\ s}} = \langle r(Stroop\ error\ \&\ s, contrast, t) - \bar{r}(t)\rangle_{contrast,t}$$

1395
1396
1397 For analyses in Figs. 5C-D, S9F-H and S10G-N investigating task-invariant coding of conflict
1398 prior and conflict posterior, we used data from *a single ROI* (ex-ante or ex-epoch) and hence
1399 only the task but not time dimension was marginalized out. For Fig. 5C, we investigate task
1400 invariance between Stroop conflict and MSIT sf conflict ($\overline{X_{s\ \&\ sf\ conflict}}$, $s\ \&\ sf\ conflict$ is an
1401 indicator variable marking the presence or absence of Stroop conflict and MSIT sf conflict):
1402

$$\overline{X_{s\ \&\ sf\ conflict}} = \langle r(s\ \&\ sf\ conflict, task) - \bar{r}(t)\rangle_{task}$$

1403
1404 For analyses in Fig. S9E, this definition the same except that RT equalized trial sets were used.
1405
Here again for interpretability, we investigated task invariance between Stroop and Simon prior
(or posterior; Figs. 5D, S9G, S10G,I,K,M) and between Stroop and Flanker prior (or posterior;
Fig. S9F,H, S10H,J,L,N) separately (e.g., $\overline{X_{s\ \&\ si\ prior\ (or\ posterior)}}$, $s\ \&\ si\ prior\ (or\ posterior)$
is an dummy variable marking the 1st and 4th levels of Stroop and Simon prior (or posterior);
$\overline{X_{s\ \&\ fl\ prior\ (or\ posterior)}}$, $s\ \&\ fl\ prior\ (or\ posterior)$ is an dummy variable marking the 1st and
4th levels of Stroop and Flanker prior (or posterior)):
1412

$$\overline{X_{s\ \&\ si\ prior}} = \langle r(s\ \&si\ prior\ (or\ posterior), task) - \bar{r}(t)\rangle_{task}$$

1413

$$\overline{X_{s\ \&\ fl\ prior}} = \langle r(s\ \&fl\ prior\ (or\ posterior), task) - \bar{r}(t)\rangle_{task}$$

1414

The algorithm then finds encoding (F_ϕ) and decoding (D_ϕ) matrices separately for each marginalized averages using the regularized reduced-rank regression:

$$L_\phi = \left\| \overline{X_\phi} - F_\phi D_\phi \bar{X} \right\|^2 + \mu \left\| F_\phi D_\phi \right\|^2$$

We assigned a fixed regularization coefficient μ to avoid overfitting ($\mu = 6e^{-6}$ determined from results reported in (56)). We used the columns of D_ϕ as the demixed principal components (dPC) and projected N-dimensional data (single-trial data for testing and trial-averaged data for training) to these dPCs. The numerical values of D_ϕ reflects the contribution for each neuron to task-invariant representation.

To test the statistical significance of coding dimensions, we randomly chose one trial for each trial type (e.g., one error trial and one correct trial) and constructed a single-trial activity matrix X_{test}. We then used the remaining trials to form the trial-averaged training data $\overline{X_{train}}$, which is used to find the dPCA coding dimensions. The left-out single-trial data X_{test} is then projected onto the first coding dimension that captures the most variance computed from X_{train}, and classified according to the closest class mean. We repeated this procedure 1000 times and determined the decoding accuracy as the proportion of correct classification among the 1000 test trials. We then generated the null distribution by shuffling the trial labels and then repeated the decoding procedure 500 times. For Figs. 5C-D, S9E-H, statistical significance is determined by comparing the true decoding accuracy with this null distribution. For Figs. 5A-B, S8A-B, S9A-D, S10A-F, statistical significance is determined by the cluster-based permutation test using this null distribution (93). The fraction of explained variance (Bars in Figs. 5A-D, S9A-H) for each marginalization is given by:

$$R_\phi{}^2 = \frac{\left\| \overline{X_\phi} \right\|^2 - \left\| \overline{X_\phi} - F_\phi D_\phi \bar{X} \right\|^2}{\left\| \overline{X_\phi} \right\|^2}$$

Single-neuron contribution to task-invariant coding dimensions

For Figs. 5E-F and S11, we quantified classified neurons by the extent of task invariance in their coding profile. Spike counts from two tasks were aggregated and regressed against a task identity dummy variable (0: Stroop, 1: MSIT), performance monitoring variable, and the interaction between these two regressors. Neurons with significant performance monitoring variable, but insignificant task identity were named "task-invariant". Neurons with significant interaction term were named "task-dependent". Neurons without any significant terms were named "others". We quantified the signed single-neuron coding strength by a partial correlation (used in the scatter plots in Figs. 5E-F and S11): correlation between spike counts and performance monitoring variable, after partialing out the task identity.
Performance monitoring variables can be error (error in either task is marked 1 and correct trials in either task is marked 0), conflict (conflict in either task is marked 1 and non-conflict in either task is marked 0), conflict prior (or posterior; 1st level in either task is marked 0 and 4th level in either task is marked 0).

References

1. E. Koechlin, C. Ody, F. Kouneiher, The Architecture of Cognitive Control in the Human Prefrontal Cortex. *Science*. **302**, 1181–1185 (2003).

2. D. Badre, M. D'Esposito, Functional Magnetic Resonance Imaging Evidence for a Hierarchical Organization of the Prefrontal Cortex. *J. Cogn. Neurosci.* **19**, 2082–2099 (2007).

3. D. Badre, D. E. Nee, Frontal Cortex and the Hierarchical Control of Behavior. *Trends Cogn. Sci.* **22**, 170–188 (2018).

4. M. Ullsperger, C. Danielmeier, G. Jocham, Neurophysiology of Performance Monitoring and Adaptive Behavior. *Physiol. Rev.* **94**, 35–79 (2014).

5. R. E. Passingham, S. L. Bengtsson, H. C. Lau, Medial frontal cortex: from self-generated action to reflection on one's own performance. *Trends Cogn. Sci.* **14**, 16–21 (2010).

6. J. D. Cosman, K. A. Lowe, W. Zinke, G. F. Woodman, J. D. Schall, Prefrontal Control of Visual Distraction. *Curr. Biol.* **28**, 414-420.e3 (2018).

7. C. Danielmeier, T. Eichele, B. U. Forstmann, M. Tittgemeyer, M. Ullsperger, Posterior Medial Frontal Cortex Activity Predicts Post-Error Adaptations in Task-Related Visual and Motor Areas. *J. Neurosci.* **31**, 1780–1789 (2011).

8. T. Egner, J. Hirsch, Cognitive control mechanisms resolve conflict through cortical amplification of task-relevant information. *Nat. Neurosci.* **8**, 1784–1790 (2005).

9. B. A. Purcell, R. Kiani, Neural Mechanisms of Post-error Adjustments of Decision Policy in Parietal Cortex. *Neuron*. **89**, 658–671 (2016).

10. J. G. Kerns, J. D. Cohen, A. W. MacDonald, R. Y. Cho, V. A. Stenger, C. S. Carter, Anterior Cingulate Conflict Monitoring and Adjustments in Control. *Science*. **303**, 1023–1026 (2004).

11. A. W. MacDonald, J. D. Cohen, V. A. Stenger, C. S. Carter, Dissociating the Role of the Dorsolateral Prefrontal and Anterior Cingulate Cortex in Cognitive Control. *Science*. **288**, 1835–1838 (2000).

12. E. K. Miller, J. D. Cohen, An Integrative Theory of Prefrontal Cortex Function. *Annu. Rev. Neurosci.* **24**, 167–202 (2001).

13. A. Shenhav, M. M. Botvinick, J. D. Cohen, The Expected Value of Control: An Integrative Theory of Anterior Cingulate Cortex Function. *Neuron*. **79**, 217–240 (2013).

14. R. Nigbur, M. X. Cohen, K. R. Ridderinkhof, B. Stürmer, Theta Dynamics Reveal Domain-specific Control over Stimulus and Response Conflict. *J. Cogn. Neurosci.* **24**, 1264–1274 (2012).

15. M. X. Cohen, S. van Gaal, Dynamic Interactions between Large-Scale Brain Networks
Predict Behavioral Adaptation after Perceptual Errors. *Cereb. Cortex*. **23**, 1061–1072
(2013).

16. S. D. McDougle, M. J. Boggess, M. J. Crossley, D. Parvin, R. B. Ivry, J. A. Taylor, Credit
assignment in movement-dependent reinforcement learning. *Proc. Natl. Acad. Sci.* **113**,
6797–6802 (2016).

17. M. Sarafyazd, M. Jazayeri, Hierarchical reasoning by neural circuits in the frontal cortex.
Science. **364** (2019), doi:10.1126/science.aav8911.

18. D. Badre, A. D. Wagner, Selection, Integration, and Conflict Monitoring: Assessing the
Nature and Generality of Prefrontal Cognitive Control Mechanisms. *Neuron*. **41**, 473–487
(2004).

19. A. Genovesio, P. J. Brasted, A. R. Mitz, S. P. Wise, Prefrontal Cortex Activity Related to
Abstract Response Strategies. *Neuron*. **47**, 307–320 (2005).

20. P. Domenech, S. Rheims, E. Koechlin, Neural mechanisms resolving exploitation-
exploration dilemmas in the medial prefrontal cortex. *Science*. **369** (2020),
doi:10.1126/science.abb0184.

21. J. R. Wessel, A. R. Aron, On the Globality of Motor Suppression: Unexpected Events and
Their Influence on Behavior and Cognition. *Neuron*. **93**, 259–280 (2017).

22. Y. Niv, N. D. Daw, D. Joel, P. Dayan, Tonic dopamine: opportunity costs and the control of
response vigor. *Psychopharmacology (Berl.)*. **191**, 507–520 (2007).

23. J. F. Cavanagh, T. V. Wiecki, M. X. Cohen, C. M. Figueroa, J. Samanta, S. J. Sherman, M. J.
Frank, Subthalamic nucleus stimulation reverses mediofrontal influence over decision
threshold. *Nat. Neurosci.* **14**, 1462–1467 (2011).

24. E. A. Crone, R. J. M. Somsen, B. V. Beek, M. W. V. D. Molen, Heart rate and skin
conductance analysis of antecendents and consequences of decision making.
Psychophysiology. **41**, 531–540 (2004).

25. R. B. Ebitz, M. L. Platt, Neuronal Activity in Primate Dorsal Anterior Cingulate Cortex
Signals Task Conflict and Predicts Adjustments in Pupil-Linked Arousal. *Neuron*. **85**,
628–640 (2015).

26. P. R. Murphy, E. Boonstra, S. Nieuwenhuis, Global gain modulation generates time-
dependent urgency during perceptual choice in humans. *Nat. Commun.* **7**, 13526 (2016).

27. R. B. Rutledge, N. Skandali, P. Dayan, R. J. Dolan, A computational and neural model of
momentary subjective well-being. *Proc. Natl. Acad. Sci.* **111**, 12252–12257 (2014).

28. E. Eldar, R. B. Rutledge, R. J. Dolan, Y. Niv, Mood as Representation of Momentum.
Trends Cogn. Sci. **20**, 15–24 (2016).

29. A. J. Shackman, T. V. Salomons, H. A. Slagter, A. S. Fox, J. J. Winter, R. J. Davidson, The
integration of negative affect, pain and cognitive control in the cingulate cortex. *Nat. Rev.*
Neurosci. **12**, 154–167 (2011).

30. T. Paus, Primate anterior cingulate cortex: Where motor control, drive and cognition
interface. *Nat. Rev. Neurosci.* **2**, 417–424 (2001).

31. P. Nachev, C. Kennard, M. Husain, Functional role of the supplementary and pre-
supplementary motor areas. *Nat. Rev. Neurosci.* **9**, 856–869 (2008).

32. F. Bonini, B. Burle, C. Liégeois-Chauvel, J. Régis, P. Chauvel, F. Vidal, Action Monitoring
and Medial Frontal Cortex: Leading Role of Supplementary Motor Area. *Science*. **343**,
888–891 (2014).

33. C. S. Carter, T. S. Braver, D. M. Barch, M. M. Botvinick, D. Noll, J. D. Cohen, Anterior
Cingulate Cortex, Error Detection, and the Online Monitoring of Performance. *Science*.
280, 747–749 (1998).

34. Z. Fu, D.-A. J. Wu, I. Ross, J. M. Chung, A. N. Mamelak, R. Adolphs, U. Rutishauser,
Single-Neuron Correlates of Error Monitoring and Post-Error Adjustments in Human
Medial Frontal Cortex. *Neuron*. **101**, 165-177.e5 (2019).

35. T. Gazit, T. Gonen, G. Gurevitch, N. Cohen, I. Strauss, Y. Zeevi, H. Yamin, F. Fahoum, T.
Hendler, I. Fried, The role of mPFC and MTL neurons in human choice under goal-
conflict. *Nat. Commun.* **11**, 3192 (2020).

36. S. R. Heilbronner, B. Y. Hayden, Dorsal Anterior Cingulate Cortex: A Bottom-Up View.
Annu. Rev. Neurosci. **39**, 149–170 (2016).

37. N. Kolling, M. K. Wittmann, T. E. J. Behrens, E. D. Boorman, R. B. Mars, M. F. S.
Rushworth, Value, search, persistence and model updating in anterior cingulate cortex.
Nat. Neurosci. **19**, 1280–1285 (2016).

38. A. Sajad, D. C. Godlove, J. D. Schall, Cortical microcircuitry of performance monitoring.
Nat. Neurosci. **22**, 265–274 (2019).

39. S. A. Sheth, M. K. Mian, S. R. Patel, W. F. Asaad, Z. M. Williams, D. D. Dougherty, G.
Bush, E. N. Eskandar, Human dorsal anterior cingulate cortex neurons mediate ongoing
behavioural adaptation. *Nature*. **488**, 218–221 (2012).

40. H. Tang, H.-Y. Yu, C.-C. Chou, N. E. Crone, J. R. Madsen, W. S. Anderson, G. Kreiman,
Cascade of neural processing orchestrates cognitive control in human frontal cortex. *eLife*.
5, e12352 (2016).

41. S. Ito, V. Stuphorn, J. W. Brown, J. D. Schall, Performance Monitoring by the Anterior
Cingulate Cortex During Saccade Countermanding. *Science*. **302**, 120–122 (2003).

42. V. Stuphorn, T. L. Taylor, J. D. Schall, Performance monitoring by the supplementary eye
field. *Nature*. **408**, 857–860 (2000).

43. C. Wang, I. Ulbert, D. L. Schomer, K. Marinkovic, E. Halgren, Responses of Human
Anterior Cingulate Cortex Microdomains to Error Detection, Conflict Monitoring,
Stimulus-Response Mapping, Familiarity, and Orienting. *J. Neurosci*. **25**, 604–613 (2005).

44. S. Bernardi, M. K. Benna, M. Rigotti, J. Munuera, S. Fusi, C. D. Salzman, The Geometry of
Abstraction in the Hippocampus and Prefrontal Cortex. *Cell*. **183**, 954-967.e21 (2020).

45. C. Stringer, M. Pachitariu, N. Steinmetz, M. Carandini, K. D. Harris, High-dimensional
geometry of population responses in visual cortex. *Nature*. **571**, 361–365 (2019).

46. J. J. DiCarlo, D. D. Cox, Untangling invariant object recognition. *Trends Cogn. Sci.* **11**, 333–
341 (2007).

47. S. Fusi, E. K. Miller, M. Rigotti, Why neurons mix: high dimensionality for higher cognition.
Curr. Opin. Neurobiol. **37**, 66–74 (2016).

48. M. Rigotti, O. Barak, M. R. Warden, X.-J. Wang, N. D. Daw, E. K. Miller, S. Fusi, The
importance of mixed selectivity in complex cognitive tasks. *Nature*. **497**, 585–590 (2013).

49. G. R. Yang, M. R. Joglekar, H. F. Song, W. T. Newsome, X.-J. Wang, Task representations
in neural networks trained to perform many cognitive tasks. *Nat. Neurosci.* **22**, 297–306
(2019).

50. J. Minxha, R. Adolphs, S. Fusi, A. N. Mamelak, U. Rutishauser, Flexible recruitment of
memory-based choice representations by the human medial frontal cortex. *Science*. **368**
(2020), doi:10.1126/science.aba3313.

51. J. Jiang, J. Beck, K. Heller, T. Egner, An insula-frontostriatal network mediates flexible
cognitive control by adaptively predicting changing control demands. *Nat. Commun.* **6**,
8165 (2015).

52. G. Bush, L. M. Shin, The Multi-Source Interference Task: an fMRI task that reliably
activates the cingulo-frontal-parietal cognitive/attention network. *Nat. Protoc.* **1**, 308–313
(2006).

53. J. Jiang, K. Heller, T. Egner, Bayesian modeling of flexible cognitive control. *Neurosci.
Biobehav. Rev.* **46**, 30–43 (2014).

54. T. E. J. Behrens, M. W. Woolrich, M. E. Walton, M. F. S. Rushworth, Learning the value of
information in an uncertain world. *Nat. Neurosci.* **10**, 1214–1221 (2007).

55. G. Gratton, M. G. Coles, E. Donchin, Optimizing the use of information: strategic control of
activation of responses. *J. Exp. Psychol. Gen.* **121**, 480–506 (1992).

56. D. Kobak, W. Brendel, C. Constantinidis, C. E. Feierstein, A. Kepecs, Z. F. Mainen, X.-L.
Qi, R. Romo, N. Uchida, C. K. Machens, Demixed principal component analysis of neural
population data. *eLife*. **5**, e10989 (2016).

57. J. Jiang, T. Egner, Using Neural Pattern Classifiers to Quantify the Modularity of Conflict–
Control Mechanisms in the Human Brain. *Cereb. Cortex*. **24**, 1793–1805 (2014).

58. T. A. Niendam, A. R. Laird, K. L. Ray, Y. M. Dean, D. C. Glahn, C. S. Carter, Meta-analytic
evidence for a superordinate cognitive control network subserving diverse executive
functions. *Cogn. Affect. Behav. Neurosci.* **12**, 241–268 (2012).

59. P. A. Kragel, M. Kano, L. Van Oudenhove, H. G. Ly, P. Dupont, A. Rubio, C. Delon-Martin,
B. L. Bonaz, S. B. Manuck, P. J. Gianaros, M. Ceko, E. A. Reynolds Losin, C.-W. Woo, T.
E. Nichols, T. D. Wager, Generalizable representations of pain, cognitive control, and
negative emotion in medial frontal cortex. *Nat. Neurosci.* **21**, 283–289 (2018).

60. S. Tsujimoto, A. Genovesio, S. P. Wise, Frontal pole cortex: encoding ends at the end of the
endbrain. *Trends Cogn. Sci.* **15**, 169–176 (2011).

61. F. A. Mansouri, E. Koechlin, M. G. P. Rosa, M. J. Buckley, Managing competing goals — a
key role for the frontopolar cortex. *Nat. Rev. Neurosci.* **18**, 645–657 (2017).

62. V. Mante, D. Sussillo, K. V. Shenoy, W. T. Newsome, Context-dependent computation by
recurrent dynamics in prefrontal cortex. *Nature*. **503**, 78–84 (2013).

63. N. Yeung, C. Summerfield, Metacognition in human decision-making: confidence and error
monitoring. *Philos. Trans. R. Soc. B Biol. Sci.* **367**, 1310–1321 (2012).

64. S. M. Fleming, R. J. Dolan, The neural basis of metacognitive ability. *Philos. Trans. R. Soc.
B Biol. Sci.* **367**, 1338–1349 (2012).

65. P. C. Fletcher, C. D. Frith, Perceiving is believing: a Bayesian approach to explaining the
positive symptoms of schizophrenia. *Nat. Rev. Neurosci.* **10**, 48–58 (2009).

66. J. Morales, H. Lau, S. M. Fleming, Domain-General and Domain-Specific Patterns of
Activity Supporting Metacognition in Human Prefrontal Cortex. *J. Neurosci.* **38**, 3534–
3546 (2018).

67. N. U. F. Dosenbach, K. M. Visscher, E. D. Palmer, F. M. Miezin, K. K. Wenger, H. C. Kang,
E. D. Burgund, A. L. Grimes, B. L. Schlaggar, S. E. Petersen, A Core System for the
Implementation of Task Sets. *Neuron*. **50**, 799–812 (2006).

68. M. F. S. Rushworth, M. E. Walton, S. W. Kennerley, D. M. Bannerman, Action sets and
decisions in the medial frontal cortex. *Trends Cogn. Sci.* **8**, 410–417 (2004).

69. M. W. Cole, J. R. Reynolds, J. D. Power, G. Repovs, A. Anticevic, T. S. Braver, Multi-task
connectivity reveals flexible hubs for adaptive task control. *Nat. Neurosci.* **16**, 1348–1355
(2013).

70. M. M. Botvinick, T. S. Braver, D. M. Barch, C. S. Carter, J. D. Cohen, Conflict monitoring
and cognitive control. *Psychol. Rev.* **108**, 624–652 (2001).

71. C.-C. Lo, X.-J. Wang, Cortico–basal ganglia circuit mechanism for a decision threshold in
reaction time tasks. *Nat. Neurosci.* **9**, 956–963 (2006).

72. D. Subramanian, A. Alers, M. A. Sommer, Corollary Discharge for Action and Cognition.
Biol. Psychiatry Cogn. Neurosci. Neuroimaging. **4**, 782–790 (2019).

73. W. H. Alexander, J. W. Brown, Medial prefrontal cortex as an action-outcome predictor. *Nat.*
Neurosci. **14**, 1338–1344 (2011).

74. P. Haggard, Sense of agency in the human brain. *Nat. Rev. Neurosci.* **18**, 196–207 (2017).

75. T. Kawai, H. Yamada, N. Sato, M. Takada, M. Matsumoto, Preferential Representation of
Past Outcome Information and Future Choice Behavior by Putative Inhibitory
Interneurons Rather Than Putative Pyramidal Neurons in the Primate Dorsal Anterior
Cingulate Cortex. *Cereb. Cortex.* **29**, 2339–2352 (2019).

76. N. Brunel, X.-J. Wang, Effects of Neuromodulation in a Cortical Network Model of Object
Working Memory Dominated by Recurrent Inhibition. *J. Comput. Neurosci.* **11**, 63–85
(2001).

77. T. S. Braver, The variable nature of cognitive control: a dual mechanisms framework. *Trends*
Cogn. Sci. **16**, 106–113 (2012).

78. D. H. Brainard, The Psychophysics Toolbox. *Spat. Vis.* **10**, 433–436 (1997).

79. J. R. de Leeuw, jsPsych: A JavaScript library for creating behavioral experiments in a Web
browser. *Behav. Res. Methods*. **47**, 1–12 (2015).

80. J. Minxha, C. Mosher, J. K. Morrow, A. N. Mamelak, R. Adolphs, K. M. Gothard, U.
Rutishauser, Fixations Gate Species-Specific Responses to Free Viewing of Faces in the
Human and Macaque Amygdala. *Cell Rep.* **18**, 878–891 (2017).

81. U. Rutishauser, E. M. Schuman, A. N. Mamelak, Online detection and sorting of
extracellularly recorded action potentials in human medial temporal lobe recordings, in
vivo. *J. Neurosci. Methods*. **154**, 204–224 (2006).

82. E. Aarts, M. Verhage, J. V. Veenvliet, C. V. Dolan, S. van der Sluis, A solution to
dependency: using multilevel analysis to accommodate nested data. *Nat. Neurosci.* **17**,
491–496 (2014).

83. M. L. Pedersen, M. J. Frank, G. Biele, The drift diffusion model as the choice rule in
reinforcement learning. *Psychon. Bull. Rev.* **24**, 1234–1251 (2017).

84. T. V. Wiecki, I. Sofer, M. J. Frank, HDDM: Hierarchical Bayesian estimation of the Drift-
Diffusion Model in Python. *Front. Neuroinformatics*. **7** (2013),
doi:10.3389/fninf.2013.00014.

85. A. J. Yu, J. D. Cohen, Sequential effects: Superstition or rational behavior? *Adv. Neural Inf.*
Process. Syst. **21**, 1873–1880 (2008).

86. D. J. Navarro, I. G. Fuss, Fast and accurate calculations for first-passage times in Wiener
diffusion models. *J. Math. Psychol.* **53**, 222–230 (2009).

87. A. E. Urai, J. W. de Gee, K. Tsetsos, T. H. Donner, Choice history biases subsequent
evidence accumulation. *eLife*. **8**, e46331 (2019).

88. D. P. Hanes, K. G. Thompson, J. D. Schall, Relationship of presaccadic activity in frontal
eye field and supplementary eye field to saccade initiation in macaque: Poisson spike train
analysis. *Exp. Brain Res.* **103**, 85–96 (1995).

89. R. Hardstone, S.-S. Poil, G. Schiavone, R. Jansen, V. V. Nikulin, H. D. Mansvelder, K.
Linkenkaer-Hansen, Detrended Fluctuation Analysis: A Scale-Free View on Neuronal
Oscillations. *Front. Physiol.* **3** (2012), doi:10.3389/fphys.2012.00450.

90. C. K. Peng, S. V. Buldyrev, S. Havlin, M. Simons, H. E. Stanley, A. L. Goldberger, Mosaic
organization of DNA nucleotides. *Phys. Rev. E Stat. Phys. Plasmas Fluids Relat.*
Interdiscip. Top. **49**, 1685–1689 (1994).

91. C.-C. Chang, C.-J. Lin, *ACM Trans. Intell. Syst. Technol.*, in press,
doi:10.1145/1961189.1961199.

92. M. G. Stokes, M. Kusunoki, N. Sigala, H. Nili, D. Gaffan, J. Duncan, Dynamic Coding for
Cognitive Control in Prefrontal Cortex. *Neuron*. **78**, 364–375 (2013).

93. E. Maris, R. Oostenveld, Nonparametric statistical testing of EEG- and MEG-data. *J.*
Neurosci. Methods. **164**, 177–190 (2007).

1683
1684