**TITLE**

Benchmarking long-read genome sequence alignment tools for human genomics applications

**AUTHORS**

Jonathan LoTempio Jr, BS; jlotempio@gwu.edu ; 1, 2, 3

Emmanuèle Délot, PhD; edelot@gwu.edu ; 1, 2, 4

Eric Vilain, MD, PhD; evilain@gwu.edu ; 1, 2, 3 *

1. Center for Genetic Medicine Research, Children's National Research Institute,

Children's National Hospital, 111 Michigan Avenue NW, Washington DC, 20010

2. Department of Genomics and Precision Medicine, George Washington University, 111

Michigan Avenue NW, Washington DC, 20010

13
14    3. International Research Laboratory (IRL2006) "Epigenetics, Data, Politics (EpiDaPo)",

15    Centre National de la Recherche Scientifique (CNRS), 2300 Eye St NW, Washington

16    DC, 20052

17
18    4. Center for Translational Research, Children's National Research Institute, Children's

19    National Hospital, 111 Michigan Avenue NW, Washington DC, 20010

20
* Corresponding author, evilain@gwu.edu

**KEYWORDS**

Long-read genome sequencing; nanopore; single-molecule real-time; benchmarking; reference-

guided genome alignment; human whole genome sequencing

**ABSTRACT**

**Background**

The utility of long-read genome sequencing platforms has been shown in many fields including

whole genome assembly, metagenomics, and amplicon sequencing. Less clear is the

applicability of long reads to reference-guided human genomics, the foundation of genomic

medicine. Here, we benchmark available platform-agnostic alignment tools on datasets from

nanopore and single-molecule real-time platforms to understand their suitability in producing a

genome representation.

**Results**

For this study, we leveraged publicly-available data from sample NA12878 generated on Oxford

Nanopore and Pacific Biosciences platforms. Each tool that was benchmarked, including

GraphMap, minimap2, and NGMLR, produced the same alignment file each time. However, the

different tools widely disagreed on which reads to leave unaligned, affecting the end genome

coverage and the number and locations of discoverable breakpoints. Only minimap2 was

computationally lightweight enough for use at scale. No alignment from one tool independently

resolved all large structural variants (10,000-100,000 basepairs) present in the Database of

Genome Variants (DGV) for sample NA12878. For variants larger than 1,000,000 basepairs,

nanopore sequence aligned with minimap2 and NGMLR, and single-molecule real-time

sequence aligned with NGMLR contained more breakpoints than are present in DGV.

**Conclusions**

When computational resources are not a limiting factor, it should be best practice to use an

analysis pipeline that generates alignments with both minimap2 and NGMLR, as neither results

in a comprehensive genome representation. When computational resources are limited, use of

minimap2 for human genome alignment produces files sufficient to answer hypotheses and

generate new questions.

## BACKGROUND

The diverse ecosystem of DNA preparation, sequencing, and mapping technologies is capable of generating computational representations of genome biology through different chemistries and processes (1–5). Sequencing-by-synthesis platforms produce highly accurate sequence data in the form of short reads (<300 basepairs, bp) (6) from high molecular weight DNA inputs. These molecular input libraries can be prepared for short-read sequencing (SRS) that are oriented in context long-range genome position through high-throughput chromatin confirmation capture (Hi-C) methods (7). In contrast, single-molecule real-time platforms can produce increasingly accurate reads on molecules >10 kilobasepairs (kbp) (8) while nanopore-based sequencing (9) and nanochannel-based mapping platforms (10) can sequence or visualize megabase-length DNA molecules (11). Each of these platforms has different abilities and available tools contributing to the diversity of projects enabled by these technologies (12,13).

Optical genome mapping (developed by Bionano Genomics) excels at detecting complex structural variants (SV), such as balanced translocations and deletions/insertions in the 1 kb to 1 Mb range, and its clinical utility was demonstrated in Duchenne (DMD) or facioscapulohumeral (FSHD) muscular dystrophies (14,15). But long-read sequence (LRS), developed by Pacific Biosciences and Oxford Nanopore Technologies, is the most appropriate technology to detect smaller variants in the 50 bp-1 kb range (16), especially in repetitive regions, and should therefore bring new diagnosis potential for diseases of trinucleotide repeat expansion and genome instability such as Huntington's Disease and Myotonic Dystrophies (17–21), as well as for discovery of SVs affecting regulatory regions of known genes. Fulfilling the promise of LRS for medical genetics requires understanding the tools that power the technology and their respective strengths.

LRS platforms have been shown to be capable of generating single, phaseable reads spanning

repetitive or complex genomic regions that remain unresolved in current human genome

assemblies (8,9,22,23). This has implication for resolution of highly homologous pseudogenes

and large SV, even in low-complexity genomic regions. Read lengths in the tens of kbp have

further allowed for end-to-end viral genome sequencing (24), while read lengths in the millions

of bp have the potential to span whole mammalian chromosomes (9,25). This potential for more

contiguous *de novo* human assembly has led to studies to specifically improve and benchmark

basecalling and polishing tools (26), as well as assembly tools (27–30) that can be applied to

human genomics.

For reference genome-guided experiments, LRS has proven useful for amplicon sequencing in

cancer detection (31) and for metagenomics (32–34), but the field is still in early days for

assessment of variation in high-coverage human whole genome sequence. Indeed, high-

coverage human whole genome sequence on LRS platforms has yet to be undertaken on the

scale of projects based on Illumina-developed SRS platform (35,36). This difference in data

availability is reflected in the number of tools for SV calling - including at least 21 for SRS and

five for LRS. (13). It is certain that, due to the richness of the sequence data and diminishing

cost of generating those data, these LRS platforms will be used in large-scale reference-guided

whole human genome projects that are presently dominated by SRS data production (37).

The value of LRS in resolving SV has been demonstrated by efforts aggregating callsets across

platforms and technologies to deeply characterize a genome (16). These experiments are

concerned mainly with understanding the full scope of the architecture of a genome, rather than

contrasting differences between results of one alignment tool or another. Each of these tools

showcase their utility and strengths in their initial publications, especially in terms of the

mapping quality of reads to the reference genome and precision and sensitivity to preserve

known variants in synthetic or downsampled genomic data, however, there have been no

studies that specifically benchmark LRS platforms and tools for reference-guided experiments.

To address this gap, we benchmarked LRS alignment tools with the datasets generated from

the Joint Initiative for Metrology in Biology's Genome in a Bottle Initiative (GIAB) sample,

NA12878, which was sequenced on Oxford Nanopore's MinION-platform by the Whole Genome

Sequencing Consortium (9) and on the Pacific Biosciences SMRT-sequence data by the

National Institute of Standards and Technology (38). We compared computational performance

(peak memory utilization, central processing unit (CPU) time, file size/storage requirements),

genome coverage depth (x-times), and quantified the reads left unaligned in any given

experiment. Since the resolution of large SVs is a key application of this technology, and also

allows us to compare the differences in genome alignments in an aggregate way, we ran the

SV-calling tool Sniffles to highlight differences in breakpoint location in each binary alignment

map (BAM) file (39). Taken together, these experiments present a comprehensive view of

differences in the products of LRS whole genome alignment pipelines.

**RESULTS**

All experiments were performed on the NA12878 sample, for which publicly available datasets

exist for both nanopore and SMRT sequencing, and rigorously annotated variants are available

in the Database of Genomic Variants (DGV) (40). We present our results in four sections: 1) the

tools that passed our exclusion criteria, 2) computational performance and benchmarking, 3) an

analysis of aligned and unaligned reads, 4) an analysis of structural variation present in each

alignment compared to a baseline.

## 1. Tools that passed the exclusion criteria

Following a literature review of available alignment tools, we established a set of inclusion

criteria (see Material and Methods), which accounted for both types of LRS data (a tool must be

able to handle both nanopore and SMRT reads), as well as the state of the field in terms of

software updates (must not have been superseded by another tool) and adoption of the tool, as

measured by citations (must be cited by manuscripts written by outside parties). All surveyed

tools and criteria are outlined in Table 1.

Three alignment tools, GraphMap, minimap2, and NGMLR, met inclusion criteria and were

included in this study (39,41,42). Kart was excluded because, while benchmarked in 2018

against minimap2 (42) it had not yet been cited by any work indexed in the Web of Knowledge

(43). Mashmap2 was also excluded, as it only had 10 citations. LAST and BLASR were

excluded because they did not have modes to account for both types of data (44,45). BWA-

MEM was excluded because it was superseded by minimap2 (46).

## 2. Computational performance and benchmarking

Computations were run three times on full node capacity on our university's high-performance

compute cluster (HPC), including 40 CPUs with a configuration described in the methods.

Further one-off runs were performed with restricted node capacity of 30, 20, and 10 CPUs. All

tools were run on default settings to reflect typical use in exploratory studies. Summaries of

findings can be examined in Table 2. Full reports on each run can be examined in Supplemental

Table S1, while a composite table of the output of samtools bamstats is available as

Supplemental Table S2.

**Minimap2 was the least resource-demanding tool.**

Minimap2 successfully aligned nanopore data every time with unrestricted and restricted

resources. Unrestricted runs used an average of 14.2 gigabytes (Gb) and the jobs took

~540 CPU hours (~13 wall clock hours) to complete.

Minimap2 also successfully aligned SMRT data every time with unrestricted or restricted

resources. The runs used an average of 16.9 Gb and the jobs took ~641 CPU hours

(~16 wall clock hours) to complete, a little longer than for the nanopore dataset.

Memory usage (see peak_rss columns in Supplemental Table S1) and runtime were

consistent across triplicate runs with unrestricted resources and did not change with

restriction of resources when the tool was used with either dataset. The consistency of

results, as well as the speed and relatively low computational demands of minimap2

make it a strong candidate for inclusion in clinical analysis pipelines.

**GraphMap was the most resource-intensive tool, resulting in 3/12 run failures.**

GraphMap successfully aligned nanopore data two out of three times in both restricted

and unrestricted resources runs. For the two successful unrestricted runs, an average of

~96 Gb memory was used and the jobs took an average of ~8,328 CPU hours (~208

wall clock hours) to complete. This was 6.6 times more memory and 13 times longer

than Minimap2. Memory usage was unchanged with resource restriction, but runtime did

increase by approximately 150,000 CPU seconds (~7.5 hours).

GraphMap successfully aligned SMRT data every time with unrestricted resources and

two out of three times with restricted resources. These runs used an average of ~50 Gb

memory and the jobs took an average of ~10,642 CPU hours (~266 wall clock hours, 11

days) to complete. All unrestricted resource jobs used ~50 Gb of memory. One restricted

run (30 threads) used ~49 Gb of memory while one (20) used ~46 Gb. The restricted run

limited to 10 threads failed due to time out at 14 wall clock days.

Runtime across all runs did not directly relate to memory usage or resource restriction

(Table 2, Supplemental Table S1. The resource-intensive requirements of GraphMap for

whole human genome alignment combined with failures to run in both datasets likely

precludes including it in the design of most analysis pipelines, however alignment files

from successful runs were included in further analyses.

**NGMLR completed all tasks, but performance was very resource-dependent.**

NGMLR successfully aligned nanopore data every time with unrestricted and restricted

resources. The unrestricted runs used an average of 33.8 Gb the jobs took ~2,539 CPU

hours (~63.5 wall clock hours) to complete, intermediary between Minimap2 and

GraphMap.

NGMLR was much faster on SMRT data. It successfully aligned every time even with

restricted resources. The runs used an average of 29.7 Gb the jobs took ~658 CPU

hours (~16.5 wall clock hours, almost 4 times faster than on the nanopore data) to

complete, on par with the time taken by Minimap2.

Memory usage and runtime were consistent with the average across triplicate runs, but,

unlike the other tools, NGMLR's performance was resource-dependent: runtime

increased and memory usage decreased with resource restriction. While more

computationally intensive than minimap2, there are no glaring concerns for NGMLR's

suitability for whole human genome alignment-based pipelines, as there is with

GraphMap.

**3.  Whole genome alignment**

**Aligned reads.** In every experiment that completed successfully, alignments of the same

genome with the same tool had the same genome coverage, whether resource-restricted or not

(Supplemental Table S1, column O). For this reason, one file generated from the first

unrestricted run was used for subsequent analysis (shown in Table 2).  Genome coverages of

~30x and ~44x were reported for nanopore (9) and SMRT (38,47) analyses respectively. We

calculated the actual coverage after read alignment to the hg38 reference by each tool.

GraphMap produced higher coverage genomes than expected on both nanopore (32.8

x) and SMRT (45.4x) datasets.

Minimap2 produced higher coverage nanopore genomes (33.4x), and expected (within

1x) coverage SMRT genomes (43.6).

NGMLR produced higher coverage nanopore genomes (31.1x) and lower coverage

(39.7x) SMRT genomes.

For nanopore data, coverage was higher than expected, by 3.7%, 9.3% and 11.3% for NGMLR,

GraphMap, and Minimap2 respectively. For SMRT data, GraphMap also produced slightly

higher than expected coverage (by 3.2%), while NGMLR came in at 9.8% lower than expected.

Minimap2 showed a small difference (-0.9%). These results are not sufficient evidence to pass

judgment on the utility of any tool, but prompted us to examine where those discrepancies come

from. We analyzed the unmapped reads to find the overlap in consensus-excluded reads.

**Unaligned reads.** The readname assigned to each read in a fastq retained in the BAM allowed

us to write an R script to directly compare the lists of reads that were not included in the

alignment by each alignment tool (Fig. 1).

**All tools agreed to leave ~1.6 million nanopore reads unaligned.** For the ~30x

nanopore dataset, all three tools agreed to exclude the same ~1.6 million reads. NGMLR

left the highest number of reads unaligned, ~3.3 million, which explains why it produced

the lowest coverage genome. It agreed with the other tools on approximately half of its

discarded reads. Minimap2 and NGMLR agreed to leave a further ~0.5 million reads

unaligned, while NGMLR and GraphMap agree on a separate ~0.48 million unaligned

reads and GraphMap and Minimap2 agree on ~0.4 million further unaligned reads.

**All tools agreed to leave ~1.2 million SMRT reads unaligned.** Similarly, for the ~44x

SMRT dataset, all three tools agreed to exclude the same ~1.2 million reads. NGMLR

left the highest number of reads unaligned, ~6 million, which explains why it produced

the lowest coverage genome. Minimap2 and NGMLR agree to leave a further ~1.6

million reads unaligned, while NGMLR and GraphMap agree on a separate ~0.78 million

unaligned reads and GraphMap and Minimap2 agree on ~0.01 million further unaligned

reads.

Perhaps the most interesting feature in this set of experiments is that NGMLR

independently excludes ~6.5 times more reads than GraphMap or Minimap2. When

compared to the nanopore data, this is ~1.5 times more reads than are independently

excluded by NGMLR.

**4.  Structural variation differences across alignments**

By examining the coverage of the genome and the overlap of the discarded reads, it became

clear that more detail was needed to understand the differences in alignment. To globally

compare the alignments to each other, and assess their usability for variant calling, we looked to

the SV known to be present in the NA12878 genome as curated by the DGV resource.

To compare the SV breakpoints preserved in the genome alignments created in this study, we

leveraged the sniffles SV caller because of its highly-detailed output files. We used the curated

SV present in DGV, annotated for presence in NA12878 as reference. Due to the different

nomenclature for SV type in the sniffles output VCF specification document (48) and the DGV

annotations, comparisons were limited to the four classes of variant that were most

unambiguously defined in both: insertions, deletions, duplications, and inversions.

Sniffles variants were graphed by SV length on the X-axis in shades of blue, contrasted with

DGV variants in red, organized by platform and SV type (Fig. 2). Deletions and insertions were

overestimated in all data sets compared to the number curated in DGV. Conversely, the

alignment files preserved fewer breakpoints recognized by sniffles as duplications and

inversions than are present in DGV. Globally, there are more indels <10,000 bp present in VCFs

than are present in DGV. This trend largely reverses above 10,000 bp, which is reflected in the

literature (16). The summary of variants is presented in Table 3, with granular counts by SV

length and type found in Supplemental Table S3.

**a.  Differences in variants among alignment files**

283               **Deletions** (Fig. 2, A, B). The total number of identified deletions varied widely,

284               from ~6,500 to ~14,300, across alignment files. For all three alignment tools, the

285               nanopore data yielded the most sniffles-identified deletions. Minimap2 preserved

the most deletions on both datasets. GraphMap-aligned genomes did not allow

detection of any deletions larger than 20 kbp in nanopore data and 6 kbp in

SMRT data.

**Insertions** (Fig. 2, C, D)**.** The total number of identified insertions also varied

(from ~6,000 to ~13,700). In contrast to deletions, the SMRT data yielded the

most insertions for all three alignment tools. Minimap2 again allowed

identification of the most insertions on both datasets. The three tools agreed for

insertions in the 1,000-4,000 bp range. Strikingly, none of the tools allowed

identification of insertions larger than 8,000 bp in nanopore sequence and 4,000

bp in SMRT sequence.

**Duplications and inversions: GraphMap preserved no breakpoints that**

**sniffles recognized as duplications or inversions.** Both minimap2 and

NGMLR datasets produced similar numbers of inversions (within 30-50 variants;

Fig. 2, E, F) and inversions (within 4-7 variants; Fig. 2, G, H). NGMLR allowed

calling of the highest number of duplications and inversions on both datasets,

outperforming minimap2 in all but three SV length bins for duplications. This was

particularly evident in the 6-10 kbp size range where no duplications were called

from the minimap2 datasets (5-10 kbp in nanopore data).

**b. Comparison to variants in DGV**

Broad trends emerged with comparison to a truthset. Deletions and insertions were

overestimated in all data sets compared to the number curated in DGV. Conversely, far

fewer duplications and inversions than are present in DGV were called on the LRS data.

While there were more indels <10,000 bp present in VCFs than are have been curated

in DGV, this trend largely reversed above 10,000 bp, where most known variants were

missed. DGV variants are shown in red in Fig. 2; details of counts are shown in

Supplemental Table S3. While these discrepancies may largely reflect the

characteristics of LRS output since DGV variants are curated from several data sources,

our analysis showed that the different alignment tools yielded different callsets from each

other as well.

**Deletions (Fig. 2A, B). The overestimation of deletions of all sizes called in**

**the LRS datasets compared to DGV ranged from 4.8 times more in the**

**SMRT/GraphMap data to 10.6 times more in the nanopore/Minimap2 data.**

For variants smaller than 10 kbp, the alignment files contained more SVs than

are present in DGV. Indeed, for both datasets and all three alignment tools, 10

times more SVs between 51-1000 bp were present in VCFs than are present in

DGV. Compared to the variants in DGV, minimap2 and NGMLR resolve tens of

variants less in each bin greater than 20,000 bp but less than 100,000 bp.

**Insertions (Fig. 2C, D). Sniffles identified more insertions ≤6,000 bp in**

**nanopore alignments and ≤4,000 bp in SMRT alignments than are present**

**in DGV.** For both datasets and all three alignment tools, more than 100 times

more insertions sized 51-1000 bp are present in VCFs compared to DGV. In

contrast, none of the tools were able to identify large insertions beyond 8 kbp or

4 kbp on the nanopore or SMRT data, respectively. DGV contains 934 insertions

between 9 and 80 kbp, yet none are resolved by Sniffles on any alignment file

from the nanopore or SMRT set.

**Duplications (Fig. 2E, F). None of the tools performed well for identification**

**of duplications.** NGMLR resolved at most half as many duplications present in

DGV while minimap2 resolved approximately 10%. GraphMap identified none.

NGMLR detected ~50 variants larger than 100,000 bp, compared to the 19

variants present in DGV.

**Inversions (Fig. 2G, H). GraphMap preserved no breakpoints Sniffles**

**identified as inversions; minimap2 and NGMLR alignments led to**

**overestimation of called small (51-1,000 bp) inversions.** In total, DGV

contains more inversions than are present in all VCFs. Less than a quarter of

DGV inversions are greater than 100 kbp, compared to around a third of similarly

sized variants in the VCFs, regardless of sequencing platform and alignment tool.

The fact that none of the callsets allowed identification of all large SVs of size greater

than 10 kbp present in DGV is a significant limitation when trying to use this technology

to identify the genetic conditions of known SV etiology in patient samples. Since these

variants have been curated by the community and have a high likelihood of being truly

present in the studied genome, it means that, rather than a specific alignment tool

underperforming, the long-read sequence platforms fall short at resolution of these

variants. This fact is critical when considering the specifics of diseases where structural

variation is a recognized etiology, such as DMD or FSHD, where variants range between

the tens and hundreds of thousands of kbp (14,15), beyond the size of variants

accurately detected in this study.

**DISCUSSION**

In this study we have highlighted the key differences between alignment files generated by three tools that have seen wide adoption for experiments involving the reference-guided alignment of large genomes. By using a well-characterized genome standard, NA12878, we were able to directly compare the performance of each tool on the sequencing datasets obtained on different platforms. We further analyzed the reads that were included or excluded from the alignment, and how these reads alignments revealed breakpoints that could be resolved as structural variants in genome architecture. We then compared those variants to a set of previously published variants discovered through multiple platforms.

Reassuringly, each alignment tool was internally consistent: when an alignment tool was given the same fastq and the same reference genome, it produced the same result as judged by bamstats and sniffles variant callsets. However, when looking across the alignment files produced by different tools on the same sequence data, the representations of the genome diverged in terms of which reads were included or excluded, and the numbers and types of variants that were present in VCFs.

This is impactful because the potential high value of LRS data in terms of potential for phasing and identification of epigenetic DNA modification (49). Since the majority of experiments that leverage large scale population surveys can be expected to rely on reference-guided alignment rather than *de novo* assembly because of both the cost and speed of analysis (50), it is key to understand the idiosyncrasies of each type of alignment files. Furthermore, clinical experiments in genomic medicine face human time constraints – speedier analyses will have higher appeal and adoption.

At this time, GraphMap does not show utility for producing whole genome alignments that

include structural variations when run on default parameters. The resource usage was large and

the time to complete the computation long with no added benefits to resolve SVs shown in this

study. This is not unexpected, as the tool was designed in large part to increase single

nucleotide variant sensitivity in noisy nanopore-sequenced reads (41); as such, the algorithm

used smooths out some of the complexity of genome architecture. This reduction in complexity

holds true for SMRT data as well, removing some of the key benefits of both LRS platforms.

Minimap2 used the least computational resources and ran successfully in the fastest time, an

important point, should these platforms be tied closer to bedside applications. On data from both

platforms, it allowed calling of the most insertions and deletions, but fell short on inversions and

duplications.

NGMLR was the most discerning aligner, in that it left the highest number of reads unmapped. It

used more compute power than Minimap2, but handled the SMRT-based data in nearly the

same amount of time, while taking considerably more time when handling nanopore-based data.

While it was designed specifically to resolve structural variation (39), it calls a high number of

very large variants (>100,000 bp) that have not been validated with other methodologies and

curated in DGV.

There is a great divergence in sniffles-called variants from alignment files generated by all tools

from the variants present in DGV. This is a concerning expansion of seminal findings in a

previous study (16) as none of the sniffles VCFs mirror the SVs present in the high-quality

curated DGV database. Small variants are present in sniffles VCFs a much higher level than in

DGV, and, conversely, between 10 and 100 kbp, each alignment tool produces an input for

Sniffles that falls short of the number of variants in DGV.

The points above are critical in designing pipelines for genome analysis and structural variant

discovery. In computationally unlimited research settings with onsite high-performance clusters,

there is value added in the generation of alignment files from both minimap2 and NGMLR.

These two perspectives on the same genome will account for some of the inherent differences

of each tool and the algorithms they use to handle read alignment (51). If computational

resources are limited, minimap2 is the best choice to move the greatest number of genomes

through the pipeline quickly; however, the loss of comprehensiveness must be considered in

cases where a suspected variant is not found.

This is impactful in genomic medicine. For example, as variants range from tens of kbp in FSHD

and hundreds of kbp to mbp in DMD, diagnostic of these disorders will likely not benefit from

data generated on LRS platforms at present, underscoring the need for optical mapping or

array-based technologies. However, disorders resulting from smaller SVs such as Huntington's

(~18-540 bp) (52), myotonic dystrophy 1 (~15-153 bp) and myotonic dystrophy 2 (~338-143,000

bp) (53) could be good candidates for deep study with LRS platforms based on the variants

present in alignment files from minimap2 and NGMLR. Accordingly, LRS has been used to

identify variants in many such disorders (21,54).

If pathogenic loci are known, a high diagnostic yield may be obtained by generating maps with

each available alignment tool, and use a structural variant caller such as NanoSV (55). Unlike

Sniffles, which provides a call of type of SV (deletion, insertion etc.), NanoSV only identifies

breakpoints in the alignment, without assigning those breakpoints an SV type. A robust

comparison of SV callers on nanopore datasets highlighted the relative strengths of variant

calling pipelines and may help users determine the best caller for their experiments (56).

NanoSV may be suitable for identifying breakpoints missed by Sniffles, but comes with the

further caveat that it is resource-intensive and may not scale in a clinical setting without vast

computational resources (56).

Answers to biological questions can also leverage tools that work with data upstream and

downstream of whole genome alignments; indeed, alternate solutions to discover differences in

genome structure have been proposed that leverage new tools. Tools designed to specifically

identify triplet repeat expansions in LRS data sets, such as Repeat Hidden Markov Model

(Repeat HHM) or Tandem-Genotypes, have shown the superiority of the approach compared to

other techniques (19,20). RepeatHMM uses raw, unaligned reads in alternate ways than whole

genome alignment to a reference (19). Rather than aligning LRS, reads can be analyzed

independently for microsatellites with specialized tools. The tandem-genotypes tool makes use

of a LAST whole-genome sequence alignment to detect copy number changes in the genome

(20). In line with this fact, LRS has been used to identify variants in many disorders (21).

The discrepancies between the VCFs generated from alignment files starkly show the need to

design experiments with the appreciation that the genomics ecosystem is not dominated by one

platform or pipeline and requires a multifaceted approach to discovery. We are at a position

where simply because the breakpoint is missing from the VCF from a long-read genome, we

cannot say that it is not present. We must therefore look across platforms and datatypes for

comprehensive genome representations (16).

**CONCLUSIONS**

As the cost of long-read sequencing catches up to that of inexpensive short-read sequencing,

the inevitable boom in data production will require well thought-out analysis pipelines. Pipeline

design always involves a set of tradeoffs. To accurately assess these tradeoffs, we must have a

rigorously benchmarked view into the tools available to create the analytic product. Here, we

looked to the differences in reference-guided human genome alignments to understand the

difference in each tool's alignment of the same genome, and how it affects a structural variant

callset. This informs our conclusion that, regardless of sequencing platform, when

computational resources are not a limiting factor, it should be best practice to align an LRS

human genome with both minimap2 and NGMLR to gain better insight into the architecture of a

genome of interest.

**MATERIALS AND METHODS**

**1. Tool selection criteria:**

a. Exclusion criteria were designed after a comprehensive literature review of

476            alignment tools. Starting with tools that were recommended by the developers of

477            each platform, we examined the tools that were cited or benchmarked against

478            new, platform specific tools. Since this yielded many software tools, we

479            established exclusion criteria to limit our experiments to tools that had seen

480            uptake by the community in terms of citations of that tool, while accounting for

481            the idiosyncrasies of LRS sequencing platforms in their design and

482            implementation. Since tools can be regularly updated or out-versioned, we

483            wanted to use only the most up to date software at the time of analysis.

485        **Inclusion criteria:**

486            i. Must be cited in more than 100 original papers other than the paper

487               where the tool is initially published

488            ii. Must be designed with specific parameters for data produced on Oxford

489               Nanopore Technologies and Pacific Biosciences platforms

490            iii. Must not be superseded by a new tool

492         b.  In our examination of structural variant calling pipelines, we elected to limit our

493             study to the variant caller sniffles due to the fact that the output files were more

494             descriptive than those produced by NanoSV. We were unable to install PBHoney

495             on our cluster.

**2.  Data**

**Reference genome**

GRCh38.p12 was accessed and downloaded on April 8, 2019 from

https://www.ncbi.nlm.nih.gov/assembly/GCF_000001405.38/ (57).

**Sequence data**

Nanopore sequence data were accessed on April 8, 2019, version rel5-guppy-0.3.0-

chunk10k.fastq, from AWS Open Data as made available by the Whole Genome

Consortium. SMRT sequence data were accessed on May 28, 2019, version

sorted_final_merged.bam from the NCBI FTP.

o  https://github.com/nanopore-wgs-consortium/NA12878/blob/master/Genome.md

509           (58)

o  ftp://ftp.ncbi.nlm.nih.gov/giab/ftp/data/NA12878/NA12878_PacBio_MtSinai/ (59)

**Database of genome variants**

DGV data were accessed on January 30, 2020 from

http://dgv.tcag.ca/dgv/docs/GRCh38_hg38_variants_2016-05-15.txt (60). The full set of

variants was reduced to 11,042 variants confirmed to be present in NA12878. 14 of

these variants were excluded as they were called on contigs present out of the main

reference assembly contigs.

**3. Hardware configuration**

Computations were performed on the George Washington University High Performance

Compute Center's Pegasus Cluster on SLURM-managed default queue compute nodes

with the following configuration: Dell PowerEdge R740 server with Dual 20-Core

3.70GHz Intel Xeon Gold 6148 processors, 192GB of 2666MHz DDR4 ECC Register

DRAM, 800 GB SSD onboard storage (used for boot and local scratch space), and

Mellanox EDR InfiniBand controller to 100GB fabric.

**4. Whole genome alignment tool benchmarking and analysis**

There versions of alignment tools used in this project included: GraphMap/0.5.2,

minimap2/2.16, and ngmlr/0.2.7.

- o  https://github.com/isovic/GraphMapLink (41)
- o  https://github.com/lh3/minimap2 (42)
- o  https://github.com/philres/ngmlr (39)

Computational metrics were printed from SLURM job records. Samtools 1.9 was used

for all alignment manipulations, alignment read depth coverage calculations, and to

extract unmapped reads (61). Samtools 1.10 was used to generate bamstats files. R

3.5.2 version Eggshell Igloo with the tidyverse packages were used to compare the

readnames across unmapped read files to assess the degree of overlap of unmapped

reads across alignment files. Genome coverage was calculated with samtools 1.9

assuming a 3 billion basepair genome. Binary conversion values were used for bytes

(1,073,741,824) and kilobytes (1,048,576) to gigabytes. CPU and wall clock hours were

calculated from CPU and wall clock seconds.

**5. Data reshaping and visualization**

As data were integrated across multiple sources and formats, they needed to be

reshaped for comparison and visualization. For example, the multiple separators found

in VCFs (commas and semicolon) are not directly usable in R or python. Relevant

dataframes from genome alignment files were reshaped with shell scripts and r scripts

whose methodology and key intermediate files are available as supplemental files to this

manuscript.

**6. Comparison of breakpoints**

Structural variants (SV) were called with sniffles/1.0.11 with default parameters. Only

variants called on the main GRCh38 assembly were included. R 3.5.2 was used to bin

and graph structural variants by SV Type with tidyverse packages and cutr (62,63).

Intermediary files and scripts are available upon request. Data from sniffles VCFs and

from DGV were subsetted by comparable fields including SV Type, SV Length, and

Chromosome since a common format was unavailable for direct comparison. Figures

were made with R packages tidyverse/ggplot and VennDiagram (64).

**DECLARATIONS**

• Ethics approval and consent to participate

○ N/A

• Consent for publication

○ N/A

**AVAILABILITY OF DATA AND MATERIALS**

All data and tools used for this study are publicly available at the URLs indicated above in

Methods. The scripts we used to process those data are available in supplementary materials

as S4.  Raw and post-processed VCFs, DGV source material, and other dataframes used to

create the figures are available at:

https://drive.google.com/drive/folders/1EImtHkYpOoUk7LOqPE__94r6CZSxk_fw?usp=sharing

(65)

Interested parties can further reach out to the authors for intermediate BAMs if needed.

**COMPETING INTERESTS**

EV is on the board of scientific advisors to Bionano Genomics

**FUNDING**

JL, ED, and EV are supported in part by A. James Clark Family Fund and Distinguished

Professorship in Molecular Genetics at Children's National Hospital. ED and EV are

supported by NIH Award Number U01HG011745 from the National Human Genome

Research Institute.

**AUTHORS CONTRIBUTIONS**

JL conceived of the study, performed the experiments, and wrote the manuscript.

ED gave comment and direction on experimental design, and edited the manuscript.

EV gave comment and direction on experimental design, edited the manuscript, and

allocated laboratory resources to the project.

**ACKNOWLEDGEMENTS**

Adam Kai Leung Wong, PhD, High Performance Computing Specialist for Genomics at

the GWU Computational Biology Institute provided critical support in preparing the HPC

for this study.

**REFERENCES**

**REFERENCES**

1.    Sanger F, Nicklen S, Coulson AR. DNA sequencing with chain-terminating inhibitors.

Proc Natl Acad Sci U S A. 1977;74(12):5463–7.

2.    Fuller CW, Middendorf LR, Benner SA, Church GM, Harris T, Huang X, et al. The

challenges of sequencing by synthesis. Vol. 27, Nature Biotechnology. Nat Biotechnol;

2009. p. 1013–23.

3.    Branton D, Deamer DW, Marziali A, Bayley H, Benner SA, Butler T, et al. The potential

and challenges of nanopore sequencing. Vol. 26, Nature Biotechnology. Nat Biotechnol;

2008. p. 1146–53.

4.    Ardui S, Ameur A, Vermeesch JR, Hestand MS. Single molecule real-time (SMRT)

sequencing comes of age: applications and utilities for medical diagnostics. Nucleic Acids

Res [Internet]. 2018 [cited 2019 Jul 10];46(5):2159–68. Available from:

http://www.ncbi.nlm.nih.gov/pubmed/29401301

5.    Levy-Sakin M, Pastor S, Mostovoy Y, Li L, Leung AKY, McCaffrey J, et al. Genome maps

across 26 human populations reveal population-specific patterns of structural variation.

Nat Commun [Internet]. 2019 [cited 2019 Jul 10];10(1):1025. Available from:

http://www.ncbi.nlm.nih.gov/pubmed/30833565

6.    Modi A, Vai S, Caramelli D, Lari M. The Illumina Sequencing Protocol and the NovaSeq

6000 System. In: Methods in Molecular Biology [Internet]. Humana Press Inc.; 2021 [cited

2021 Jun 14]. p. 15–42. Available from: https://link.springer.com/protocol/10.1007/978-1-

0716-1099-2_2

7.    Kronenberg ZN, Rhie A, Koren S, Concepcion GT, Peluso P, Munson KM, et al.

Extended haplotype-phasing of long-read de novo genome assemblies using Hi-C. Nat

Commun 2021 121 [Internet]. 2021 Apr 28 [cited 2021 Jun 4];12(1):1–10. Available from:

https://doi.org/10.1038/s41467-020-20536-y

8.    Wenger AM, Peluso P, Rowell WJ, Chang PC, Hall RJ, Concepcion GT, et al. Accurate

circular consensus long-read sequencing improves variant detection and assembly of a

human genome. Nat Biotechnol. 2019 Oct;37(10):1155–62.

9.    Jain M, Koren S, Miga KH, Quick J, Rand AC, Sasani TA, et al. Nanopore sequencing

and assembly of a human genome with ultra-long reads. Nat Biotechnol [Internet]. 2018

[cited 2019 Jul 10];36(4):338–45. Available from:

http://www.ncbi.nlm.nih.gov/pubmed/29431738

10.   Formenti G, Chiara M, Poveda L, Francoijs KJ, Bonisoli-Alquati A, Canova L, et al. SMRT

long reads and direct label and stain optical maps allow the generation of a high-quality

genome assembly for the european barn swallow (Hirundo rustica rustica). Gigascience

[Internet]. 2018 Nov 29 [cited 2021 Jun 14];8(1):1–9. Available from: http://orcid.org/0000-

0002-7554-5991.

11.   Pollard MO, Gurdasani D, Mentzer AJ, Porter T, Sandhu MS. Long reads: their purpose

and place. Vol. 27, Human molecular genetics. NLM (Medline); 2018. p. R234–41.

12.   Ho SS, Urban AE, Mills RE. Structural variation in the sequencing era [Internet]. Vol. 21,

Nature Reviews Genetics. Nature Research; 2020 [cited 2021 Jun 6]. p. 171–89.

Available from: /pmc/articles/PMC7402362/

13.   Mahmoud M, Gobet N, Cruz-Dávalos DI, Mounier N, Dessimoz C, Sedlazeck FJ.

Structural variant calling: The long and the short of it. Vol. 20, Genome Biology. BioMed

Central Ltd.; 2019. p. 246.

14.   Barseghyan H, Tang W, Wang RT, Almalvez M, Segura E, Bramble MS, et al. Next-

generation mapping: A novel approach for detection of pathogenic structural variants with

a potential utility in clinical diagnosis. Genome Med. 2017 Oct;9(1).

15.   Sharim H, Grunwald A, Gabrieli T, Michaeli Y, Margalit S, Torchinsky D, et al. Long-read

single-molecule maps of the functional methylome. Genome Res. 2019 Apr;29(4):646–

56.

16.   Chaisson MJP, Sanders AD, Zhao X, Malhotra A, Porubsky D, Rausch T, et al. Multi-

platform discovery of haplotype-resolved structural variation in human genomes. Nat

Commun [Internet]. 2019 [cited 2019 Jul 10];10(1):1784. Available from:

http://www.ncbi.nlm.nih.gov/pubmed/30992455

17.    Kantartzis A, Williams GM, Balakrishnan L, Roberts RL, Surtees JA, Bambara RA. Msh2-

Msh3 Interferes with Okazaki Fragment Processing to Promote Trinucleotide Repeat

Expansions. Cell Rep. 2012 Aug;2(2):216–22.

18.    Santoro M, Masciullo M, Silvestri G, Novelli G, Botta A. Myotonic dystrophy type 1: role of

CCG, CTC and CGG interruptions within DMPK alleles in the pathogenesis and

molecular diagnosis. Vol. 92, Clinical Genetics. Blackwell Publishing Ltd; 2017. p. 355–

64.

19.    Liu Q, Zhang P, Wang D, Gu W, Wang K. Interrogating the "unsequenceable" genomic

trinucleotide repeat disorders by long-read sequencing. Genome Med. 2017 Jul;9(1):65.

20.    Mitsuhashi S, Frith MC, Mizuguchi T, Miyatake S, Toyota T, Adachi H, et al. Tandem-

genotypes: robust detection of tandem repeat expansions from long DNA reads. Genome

Biol. 2019 Mar;20(1):58.

21.    Mantere T, Kersten S, Hoischen A. Long-read sequencing emerging in medical genetics

[Internet]. Vol. 10, Frontiers in Genetics. Frontiers Media S.A.; 2019 [cited 2021 Jun 4]. p.

426. Available from: www.frontiersin.org

22.    Huddleston J, Chaisson MJP, Steinberg KM, Warren W, Hoekzema K, Gordon D, et al.

Discovery and genotyping of structural variation from long-read haploid genome

sequence data. Genome Res. 2017 May;27(5):677–85.

23.    Ebbert MTW, Jensen TD, Jansen-West K, Sens JP, Reddy JS, Ridge PG, et al.

Systematic analysis of dark and camouflaged genes reveals disease-relevant genes

hiding in plain sight. Genome Biol 2019 201 [Internet]. 2019 May 20 [cited 2021 Jun

4];20(1):1–23. Available from:

https://genomebiology.biomedcentral.com/articles/10.1186/s13059-019-1707-2

24.    Walker A, Houwaart T, Wienemann T, Vasconcelos MK, Strelow D, Senff T, et al.

Genetic structure of SARS-CoV-2 reflects clonal superspreading and multiple

independent introduction events, North-Rhine Westphalia, Germany, February and March

2020. Eurosurveillance. 2020 Jun;25(22):2000746.

25.    Miga KH, Koren S, Rhie A, Vollger MR, Gershman A, Bzikadze A, et al. Telomere-to-

telomere assembly of a complete human X chromosome. Nature [Internet]. 2020 Sep 3

[cited 2021 Jun 4];585(7823):79–84. Available from: https://doi.org/10.1038/s41586-020-

2547-7

26.    Wick RR, Judd LM, Holt KE. Performance of neural network basecalling tools for Oxford

Nanopore sequencing. Genome Biol. 2019 Jun;20(1).

27.    Koren S, Rhie A, Walenz BP, Dilthey AT, Bickhart DM, Kingan SB, et al. De novo

assembly of haplotype-resolved genomes with trio binning. Nat Biotechnol. 2018

Dec;36(12):1174–82.

28.    Kolmogorov M, Yuan J, Lin Y, Pevzner PA. Assembly of long, error-prone reads using

repeat graphs. Nat Biotechnol. 2019 May;37(5):540–6.

29.    Ruan J, Li H. Fast and accurate long-read assembly with wtdbg2. Nat Methods. 2020

Feb;17(2):155–8.

30.    Cheng H, Concepcion GT, Feng X, Zhang H, Li H. Haplotype-resolved de novo assembly

using phased assembly graphs with hifiasm. Nat Methods [Internet]. 2021 Feb 1 [cited

2021 Jun 16];18(2):170–5. Available from: https://doi.org/10.1038/s41592-020-01056-5

31.    Norris AL, Workman RE, Fan Y, Eshleman JR, Timp W. Nanopore sequencing detects

structural variants in cancer. Cancer Biol Ther. 2016 Mar;17(3):246–53.

32.    Deshpande S V., Reed TM, Sullivan RF, Kerkhof LJ, Beigel KM, Wade MM. Offline next

generation metagenomics sequence analysis using minION detection software (MINDS).

Genes (Basel). 2019 Aug;10(8).

33.    Cuscó A, Catozzi C, Viñes J, Sanchez A, Francino O. Microbiota profiling with long

amplicons using Nanopore sequencing: full-length 16S rRNA gene and the 16S-ITS-23S

of the rrn operon. F1000Research. 2019 Aug;7:1755.

34. Sanderson ND, Street TL, Foster D, Swann J, Atkins BL, Brent AJ, et al. Real-time

analysis of nanopore-based metagenomic sequencing from infected orthopaedic devices

06 Biological Sciences 0604 Genetics 06 Biological Sciences 0605 Microbiology. BMC

Genomics. 2018 Sep;19(1).

35. Burgess DJ. The TOPMed genomic resource for human health. Nat Rev Genet [Internet].

2021 Apr 1 [cited 2021 Jun 16];22(4):200. Available from:

https://www.nature.com/articles/s41576-021-00343-x

36. NIH genome sequencing program targets the genomic bases of common, rare disease |

National Institutes of Health (NIH) [Internet]. [cited 2021 Jun 16]. Available from:

https://www.nih.gov/news-events/news-releases/nih-genome-sequencing-program-

targets-genomic-bases-common-rare-disease

37. De Coster W, Weissensteiner MH, Sedlazeck FJ. Towards population-scale long-read

sequencing. Nat Rev Genet [Internet]. 2021 May 28 [cited 2021 Jun 16];1–16. Available

from: http://www.nature.com/articles/s41576-021-00367-3

38. Zook JM, McDaniel J, Olson ND, Wagner J, Parikh H, Heaton H, et al. An open resource

for accurately benchmarking small variant and reference calls. Nat Biotechnol. 2019

May;37(5):561–6.

39. Sedlazeck FJ, Rescheneder P, Smolka M, Fang H, Nattestad M, Von Haeseler A, et al.

Accurate detection of complex structural variations using single-molecule sequencing.

Nat Methods. 2018 Jun;15(6):461–8.

40. MacDonald JR, Ziman R, Yuen RKC, Feuk L, Scherer SW. The Database of Genomic

Variants: A curated collection of structural variation in the human genome. Nucleic Acids

Res [Internet]. 2014 Jan 1 [cited 2021 Jun 16];42(D1):D986–92. Available from:

http://www.ebi.ac.uk/dgva

41.    Sović I, Šikić M, Wilm A, Fenlon SN, Chen S, Nagarajan N. Fast and sensitive mapping

of nanopore sequencing reads with GraphMap. Nat Commun. 2016 Apr;7.

42.    Li H. Minimap2: pairwise alignment for nucleotide sequences. Bioinformatics [Internet].

Volume 34(Issue 18):Pages 3094–3100. Available from:

https://academic.oup.com/bioinformatics/article/34/18/3094/4994778

43.    Lin H-N, Hsu W-L. Kart: a divide-and-conquer algorithm for NGS read alignment.

Bioinformatics. 2017 Aug;33(15):2281–7.

44.    Chaisson MJ, Tesler G. Mapping single molecule sequencing reads using basic local

alignment with successive refinement (BLASR): Application and theory. BMC

Bioinformatics. 2012 Sep;13(1).

45.    Li H, Durbin R. Fast and accurate long-read alignment with Burrows-Wheeler transform.

Bioinformatics [Internet]. 2010 Mar 1;26(5):589–95. Available from:

http://www.ncbi.nlm.nih.gov/pubmed/20080505

46.    Li H. Aligning sequence reads, clone sequences and assembly contigs with BWA-MEM.

2013 Mar 16; Available from: http://arxiv.org/abs/1303.3997

47.    GIAB Consortium. Genome in a Bottle [Internet]. 2021. Available from:

https://jimb.stanford.edu/giab

48.    The Variant Call Format Specification [Internet]. 2021. Available from:

https://github.com/samtools/hts-specs

49.    Ni P, Huang N, Zhang Z, Wang D-P, Liang F, Miao Y, et al. DeepSignal: detecting DNA

methylation state from Nanopore sequencing reads using deep-learning. Elofsson A,

editor. Bioinformatics [Internet]. 2019 Nov 1;35(22):4586–95. Available from:

https://academic.oup.com/bioinformatics/article/35/22/4586/5474907

50.    Mardis ER. The $1,000 genome, the $100,000 analysis? Vol. 2, Genome Medicine.

BioMed Central; 2010. p. 84.

51.    Jenko Bizjan B, Katsila T, Tesovnik T, Šket R, Debeljak M, Matsoukas MT, et al.

Challenges in identifying large germline structural variants for clinical use by long read

sequencing. Vol. 18, Computational and Structural Biotechnology Journal. Elsevier B.V.;

2020. p. 83–92.

52.    Counting CAG repeats in the Huntington's disease gene by restriction endonuclease

EcoP15I cleavage.

53.    Yum K, Wang ET, Kalsotra A. Myotonic dystrophy: disease repeat range, penetrance,

age of onset, and relationship between repeat size and phenotypes. Vol. 44, Current

Opinion in Genetics and Development. Elsevier Ltd; 2017. p. 30–7.

54.    Mitsuhashi S, Matsumoto N. Long-read sequencing for rare human genetic diseases. Vol.

65, Journal of Human Genetics. Springer Nature; 2020. p. 11–9.

55.    Cretu Stancu M, Van Roosmalen MJ, Renkens I, Nieboer MM, Middelkamp S, De Ligt J,

et al. Mapping and phasing of structural variation in patient genomes using nanopore

sequencing. Nat Commun. 2017 Dec;8(1):1–13.

56.    Zhou A, Lin T, Xing J. Evaluating nanopore sequencing data processing pipelines for

structural variation identification. Genome Biol [Internet]. 2019 Nov 14 [cited 2021 Jun

4];20(1). Available from: /pmc/articles/PMC6857234/

57.    Genome Reference Consortium. GRCh38.p12 [Internet]. [cited 2019 Apr 8]. Available

from: https://www.ncbi.nlm.nih.gov/assembly/GCF_000001405.38/

58.    WGS Consortium. NA12878 Nanopore Data [Internet]. [cited 2019 Apr 8]. Available from:

https://github.com/nanopore-wgs-consortium/NA12878/blob/master/Genome.md

59.    GIAB Consortium. NA12878 PacBio Data.

60.    The Cancer Genome Atlas. Database of Genomic Variants [Internet]. [cited 2020 Jan 30].

Available from: http://dgv.tcag.ca/dgv/docs/GRCh38_hg38_variants_2016-05-15.txt.

61.    Li H, Handsaker B, Wysoker A, Fennell T, Ruan J, Homer N, et al. The Sequence

Alignment/Map format and SAMtools. Bioinformatics. 2009 Aug;25(16):2078–9.

62.    Wickham H, Averick M, Bryan J, Chang W, McGowan L, François R, et al. Welcome to

777   the Tidyverse. J Open Source Softw. 2019 Nov;4(43):1686.

778 63. moodymudskipper/cutr: Enhanced cut And Useful Related Functions version 0.0.0.9000

779   from GitHub.

780 64. Chen H, Boutros PC. VennDiagram: A package for the generation of highly-customizable

781   Venn and Euler diagrams in R. BMC Bioinformatics. 2011 Jan;12(1):35.

782 65. Vilain Lab Google Drive [Internet]. [cited 2021 Jun 15]. Available from:

783   https://drive.google.com/drive/folders/1EImtHkYpOoUk7LOqPE__94r6CZSxk_fw?usp=sh

784   aring

 **TABLES**

| Tool | Version | Year | PMID | DOI | Web of Knowledge Citations (2015-20) | Platform | Included (Exclusion criterion) |
|---|---|---|---|---|---|---|---|
| **BWA-MEM** | 0.7 | 2011 | NA | arXiv:1303.3997 | NA | ILMN, ONT, PB | No (3) |
| **LAST** | V-984 | 2011 | 21209072 | 10.1101/gr.113985.110 | 367 | ILMN, PB | No (2) |
| **BLASR** | | 2012 | 22988817 | 10.1186/1471-2105-13-238 | 473 | PB | No (2) |
| **GraphMap** | 0.5.2 | 2016 | 27079541 | 10.1038/ncomms11307 | 113 | ONT, PB | Yes |
| **Mashmap2** | 2.0 | 2017 | 30423094 | 10.1093/bioinformatics/bty597 | 10 | ILMN, ONT, PB | No (1) |
| **Minimap2** | 2.17 | 2018 | 29750242 | 10.1093/bioinformatics/bty191 | 383 | ILMN, ONT, PB | Yes |
| **NGMLR** | 0.2.7 | 2018 | 29713083 | 10.1038/s41592-018-0001-7 | 141 | ONT, PB | Yes |
| **Kart** | 2.5.2 | 2019 | 31057068 | 10.1142/S0219720019500082 | 0 | ONT, PB | No (1) |

**Table 1. Long-read genome sequence alignment tools.**

The tools included in the study are highlighted in green. Shown in the last column is the criterion

failed by excluded tools (1= widely adopted, 2= platform agnostic, 3= not superseded by a

newer version), as delineated in the Materials and Methods. For details on specificity of

methodological approaches for aligners see Bizjan 2020. ILMN = Illumina SRS, ONT = Oxford

Nanopore Technologies, PB= Pacific Biosciences SMRT.

| | | Computational Benchmarking | | | | Genome Benchmarking | | |
|---|---|---|---|---|---|---|---|---|
| | Alignment Tool | Wall Clock Hours | CPU Hours | CPU Seconds | Peak Memory Usage (Gb) | x-coverage 3-billion bp | Mapped reads | Unmapped reads |
| **Nanopore** | GraphMap | 208.2 | 8327.9 | 29,980,420 | 96.30 | 32.8 | 13,254,609 | 2,637,289 |
| | Minmap2 | 13.5 | 540.5 | 1,945,707 | 14.16 | 33.5 | 13,217,207 | 2,674,691 |
| | NGMLR | 63.5 | 2538.7 | 9,139,347 | 33.81 | 31.1 | 12,602,742 | 3,288,411 |
| **SMRT** | GraphMap | 266.1 | 10642.4 | 38,312,720 | 50.06 | 45.4 | 38,471,526 | 2,349,178 |
| | Minmap2 | 16.0 | 641.5 | 2,309,293 | 16.93 | 43.6 | 37,661,104 | 3,159,600 |
| | NGMLR | 16.5 | 658.4 | 2,370,240 | 29.69 | 39.7 | 34,765,559 | 6,041,055 |

**Table 2. Benchmarking metrics summary.** Average runtime, memory usage, coverage, and

mapped and unmapped reads are shown for three identical runs of each tool, GraphMap,

minimap2, and NGMLR on NA12878 genomes with unlimited computational resources,

described in Materials and Methods. Data for each individual run and for the resource-restricted

runs are show in S1 and a summary of bamstats is shown in S2. Standard error was not

calculated as less than 3 measurements were available in some sets due to run failures.

| Structural Variant Type | Platform | GraphMap | Minimap2 | NGMLR | DGV Variants |
|---|---|---|---|---|---|
| DEL | Nanopore | 8,666 | 14,380 | 11,819 | 1,353 |
| | SMRT | 6,567 | 10,945 | 8,561 | |
| INS | Nanopore | 6,092 | 11,469 | 9,302 | 4,698 |
| | SMRT | 8,200 | 13,770 | 10,377 | |
| DUP | Nanopore | 0 | 127 | 774 | 1,619 |
| | SMRT | 0 | 155 | 820 | |
| INV | Nanopore | 0 | 98 | 183 | 237 |
| | SMRT | 0 | 102 | 190 | |

**Table 3.** Summary of deletions, insertions, inversions, and duplications present in Sniffles

variant call files and the Database of Genome Variants (DGV). No variants to alternate loci in

the hg38 reference genome were included in this study.

**FIGURE LEGENDS**

**Figure 1. Unmapped reads.** Venn diagrams show the total number of reads (in millions)

flagged as unmapped in the sorted BAM files produced by each of the three alignment tools,

GraphMap, Minimap2, and NGMLR. Panel A presents unmapped reads from the nanopore

dataset. Panel B presents unmapped reads from an SMRT dataset.

**Figure 2. Structural variants present in alignment VCFs**. Structural variants called by sniffles

on NA12878 BAMs. Calls in the three alignment datasets (shades of blue) compared to variants

present in the Database of Genomic Variants (red), organized by SV type, size, and platform. X-

axes represent size bins of structural variants, while y-axes represent the count of structural

variants present in that bin. GraphMap called only insertions and deletions on these data sets.

Please note that the y-axis represents 0-10,000 for insertions and deletion, 1-1,000 for

duplications and 1-100 for inversions.

**SUPPLEMENTAL TABLE OF CONTENTS**

820           S1: Table of computational metrics

821           S2: Table of samtools bamstats outputs

822           S3: Table of structural variant calls by size

823           S4: Supplemental methods: scripts and methodology