Benchmarking long-read genome sequence alignment tools for human genomics applications

Jonathan LoTempio Jr[1,2], Emmanuèle Délot[3,4], Eric Vilain[1,2]

[1] Institute for Clinical and Translational Science, University of California, Irvine, 1301 Hewitt Hall University of California, Irvine 843 Health Science Rd Irvine, CA
[2] International Research Laboratory (IRL2006) "Epigenetics, Data, Politics (EpiDaPo)", Centre National de la Recherche Scientifique (CNRS), 2300 Eye St NW, Washington DC, 20052
[3] Center for Genetic Medicine Research, Children's National Research and Innovation Campus, 7719 13th Place, Washington DC, 20012
[4] Department of Genomics and Precision Medicine, George Washington University, 2300 Eye St NW, Washington DC, 20052

Corresponding Author:
Eric Vilain
1301 Hewitt Hall University of California, Irvine 843 Health Science Rd Irvine, CA Email address: evilain@hs.uci.edu

Abstract

Background. The utility of long-read genome sequencing platforms has been shown in many fields including whole genome assembly, metagenomics, and amplicon sequencing. Less clear is the applicability of long reads to reference-guided human genomics, the foundation of genomic medicine. Here, we benchmark available platform-agnostic alignment tools on datasets from nanopore and single-molecule real-time platforms to understand their suitability in producing a genome representation.

Results. For this study, we leveraged publicly-available data from sample NA12878 generated on Oxford Nanopore and sample NA24385 on Pacific Biosciences platforms. Each tool that was benchmarked, including GraphMap2, LRA, Minimap2, NGMLR, and Winnowmap2 produced the same alignment file each time. However, the different tools widely disagreed on which reads to leave unaligned, affecting the end genome coverage and the number of discoverable breakpoints. Minimap2 and winnowmap2 were computationally lightweight enough for use at scale. No alignment from one tool independently resolved all large structural variants (10,000-100,000 basepairs) present in the Database of Genome Variants (DGV) for sample NA12878 or the truthset for NA24385.

Conclusions. It should be best practice to use an analysis pipeline that generates alignments with both minimap2 and winnowmap2 as both are lightweight and yield different views of the genome. If computational resources and time are not a factor for a given case or experiment, a

41 third representation from NGMLR will provide another view, and another chance to resolve a
42 case. LRA, while fast, did not work on the nanopore data for our cluster, but PacBio results were
43 promising in that those computations completed faster than Mininmap2. Graphmap2 is not an
44 ideal tool for exploration of a whole human genome generated on a long-read sequencing
45 platform.
46

Introduction

The diverse ecosystem of DNA preparation, sequencing, and mapping technologies is capable of
generating computational representations of genome biology through different chemistries and
processes on different sequencing and mapping platforms [1–5]. This has resulted in many
different approaches for making use of the data of different sources, with algorithms and the
tools built upon them used across platforms to differing success. Here we briefly outline the
differences between these platforms and analysis strategies so that we may consider an important
gap in applying the newest technologies to the problem of human genomics.
55

Sequencing-by-synthesis platforms produce highly accurate sequence data in the form of short-
reads (<300 basepairs, bp) [6] from high molecular weight DNA inputs. These molecular input
libraries can be prepared for short read sequencing (SRS) that are oriented in context long-
range genome position through high-throughput chromatin conformation capture (Hi-C) methods
[7]. In contrast, single-molecule real-time platforms can produce highly accurate reads through
circular consensus sequencing (CCS) on molecules >10 kilobasepairs (kbp) [8] while nanopore-
based sequencing [9] and nanochannel-based mapping platforms [10] can sequence or visualize
megabase-length DNA molecules [11]. Each of these platforms has different abilities and
available tools, which contributes to the diversity of projects enabled by these technologies
[12,13].
66

Optical genome mapping (developed by Bionano Genomics) excels at detecting structural
variants (SV), such as balanced translocations and deletions/insertions in the 1 kb to 1 Mb range,
and its clinical utility was demonstrated in Duchenne (DMD) or facioscapulohumeral (FSHD)
muscular dystrophies [14,15], and cancer. But long-read sequence (LRS), developed by Pacific
Biosciences and Oxford Nanopore Technologies among others, has been shown to be the most
appropriate technology to detect smaller variants in the 50 bp-1 kb range [16]. This is especially
true in repetitive regions of the genome and should therefore bring new diagnosis potential for
diseases of trinucleotide repeat expansion and genome instability such as Huntington's Disease
and Myotonic Dystrophies [17–21], as well as for discovery of SVs affecting regulatory regions
of known genes. Fulfilling the promise of LRS for medical genetics requires understanding the
tools that power the technology and their respective strengths.
78

LRS platforms have been further shown to be capable of generating single, phaseable reads
spanning repetitive or complex genomic regions that remain unresolved in all [8,9,22,23] but one

current human genome assembly [24]. This has implications for resolution of highly homologous
pseudogenes and large SV, even in low-complexity genomic regions, or from otherwise healthy
diploid samples. Read lengths in the tens of kbp have further allowed for end-to-end viral
genome sequencing [25], while read lengths in the millions of bp have the potential to span
whole mammalian chromosomes [9,26]. This potential for more contiguous de novo human
assembly has led to studies to specifically improve and benchmark basecalling and polishing
tools [27], as well as assembly tools [28–30] that can be applied to human genomics.
88
For reference genome-guided experiments, LRS has proven useful for amplicon sequencing in
cancer detection [31] and for metagenomics [32–34], but the field is still in early days for
assessment of variation in high-coverage human whole genome sequence. Indeed, high-coverage
human whole genome sequence on LRS platforms has yet to be undertaken on the scale of
projects based on Illumina-developed SRS platform [35,36]. This difference in data availability
is reflected in the number of tools for SV calling - including at least 21 for SRS and 9 for LRS
[13,37–40]. It is certain that, due to the richness of the sequence data and diminishing cost of
generating those data, these LRS platforms will be used in large-scale reference-guided whole
human genome projects that are presently dominated by SRS data production [41].
98
The value of LRS in resolving SV has been demonstrated by efforts aggregating callsets across
platforms and technologies to deeply characterize a genome [16]. These experiments are
concerned mainly with understanding the full scope of the architecture of a genome, rather than
contrasting differences between results of one alignment tool or another. Each of these tools
showcase their utility and strengths in their initial publications, especially in terms of the
mapping quality of reads to the reference genome and precision and sensitivity to preserve
known variants in synthetic or downsampled genomic data. However, there have been no studies
that specifically benchmark LRS platforms and tools for reference-guided experiments.
107
To address this gap, we benchmarked the most recent LRS alignment tools with the datasets
generated from the Joint Initiative for Metrology in Biology's Genome in a Bottle Initiative
(GIAB), specifically samples, NA12878 sequenced with nanopore technology and NA24385
sequenced with CCS technology. These were generated with Oxford 9.4 pore chemistry and with
Guppy5 basecalling performed by the Whole Genome Sequencing Consortium [9] and with
Pacific Biosciences RSII SMRT CCS technology by PacBio and the National Institute of
Standards and Technology [42]. We compared computational performance (peak memory
utilization, central processing unit (CPU) time, file size/storage requirements), genome depth and
basepair coverage, and quantified the reads left unaligned in any given experiment. We have
limited this study to tools that are platform agnostic and function on our cluster. Since the
resolution of large SVs is a key application of this technology, and also allows comparison of the
differences in genome alignments in an aggregate way, we ran the SV-calling tool Sniffles to
highlight differences in breakpoint location in each binary alignment map (BAM) file [43].

Taken together, these experiments present a comprehensive view of differences in the products
of LRS whole-genome alignment pipelines.
123

Materials & Methods

1. Tool selection criteria:

a. Exclusion criteria were designed after a comprehensive literature review of alignment tools. Starting with tools that were recommended by the developers of each platform, we examined the tools that were cited or benchmarked against new, platform-specific tools. We also used the website longreadtools.org, searching their database with the filters "nanopore", "pacbio", and "alignment". Since this yielded many software tools, we dove deeper and excluded any tools not designed for whole genome experiments. Tools which passed this test were then assessed for their suitability for use with nanopore and SMRT data and whether they produced a SAM/BAM file for analysis. Since tools can be regularly updated or out-versioned, we wanted to use only the most up to date software at the time of analysis.

b. In our examination of structural variant calling pipelines, we elected to limit our study to the variant caller sniffles due to the fact that the output files were most descriptive.

2. Data

Main experiments

Reference genome: GRCh38 was accessed on March 22, 2022 from ftp://ftp.ncbi.nlm.nih.gov/genomes/all/GCA/000/001/405/GCA_000001405.15_GRCh38/seqs_for_alignment_pipelines.ucsc_ids/GCA_000001405.15_GRCh38_no_alt_analysis_set.fna.gz

Sequence data

NA12878 data from the WGS Consortium, rel7 guppy 5 basecalls was accessed on March 22, 2022 from : https://github.com/nanopore-wgs-consortium/NA12878/blob/master/Genome.md

15kb insert size SMRT CCS data:

NA24385 was accessed from the human pangenomics consortium github on March 22, 2022 from: https://github.com/human-pangenomics/HG002_Data_Freeze_v1.0 SV truthsets

Structural variant truthsets for NA12878, updated February 25, 2020, from DGV were accessed on March 31, 2022 from: http://dgv.tcag.ca/dgv/app/downloads?ref=GRCh37/hg19 [71]

Structural variant truthsets from Pacific Biosciences and the GIAB consortium
were accessed on May 20, 2022 from: https://github.com/PacificBiosciences/sv-
benchmark [70]

There is a limitation in that these variants were called with alignments to
GRCh37. However, since this study is conserved with SV size, rather than
location, within 1,000 and 10,000 bp windows we are confident that this is a
minor limitation.

Pilot experiments (S4)

Reference genome

GRCh38.p12 was accessed and downloaded on April 8, 2019 from
https://www.ncbi.nlm.nih.gov/assembly/GCF_000001405.38/ [81].

Sequence data

Nanopore sequence data were accessed on April 8, 2019, version rel5-
guppy-0.3.0-chunk10k.fastq, from AWS Open Data as made available by
the Whole Genome Consortium. SMRT sequence data were accessed on
May 28, 2019, version sorted_final_merged.bam from the NCBI FTP.

https://github.com/nanopore-wgs-
consortium/NA12878/blob/master/Genome.md [82]

ftp://ftp.ncbi.nlm.nih.gov/giab/ftp/data/NA12878/NA12878_PacBio_MtSi
nai/ [83]

Database of genome variants

DGV data were accessed on January 30, 2020 from
http://dgv.tcag.ca/dgv/docs/GRCh38_hg38_variants_2016-05-15.txt [84].
The full set of variants was reduced to 11,042 variants confirmed to be
present in NA12878. 14 of these variants were excluded as they were
called on contigs present out of the main reference assembly contigs.

3. Hardware configuration

Computations were performed on the George Washington University High Performance
Compute Center's Pegasus Cluster on SLURM-managed default queue compute nodes
with the following configuration: Dell PowerEdge R740 server with Dual 20-Core
3.70GHz Intel Xeon Gold 6148 processors, 192GB of 2666MHz DDR4 ECC Register
DRAM, 800 GB SSD onboard storage (used for boot and local scratch space), and
Mellanox EDR InfiniBand controller to 100GB fabric.

199		
200	**4.**	**Whole genome alignment tool benchmarking and analysis**

The following tool versions were used in the work presented in the main tables and figures.

1. v1.3.3. https://github.com/ChaissonLab/LRA\ [48]
2. v0.6.3 https://github.com/lbcb-sci/graphmap2 [47]
3. v2.24 https://github.com/lh3/minimap2 [49]
4. v0.2.7 : https://github.com/philres/ngmlr [43]
5. v2.0.3 https://github.com/marbl/Winnowmap [50]

There versions of alignment tools used in the preliminary experiments of this project available in S4 included:

1. v0.5.2 https://github.com/isovic/GraphMapLink [55]
2. v2.16 https://github.com/lh3/minimap2 [49]
3. v0.2.7 https://github.com/philres/ngmlr [43]

All tools were run with default parameters and were flagged for nanopore or SMRT data based on the requirements of that experiment.

Computational metrics were printed from SLURM job records with seff and sacct with flags –format JobID, JobName, Elapsed, NCPUs, TotalCPU, CPUTime, ReqMem, MaxRSS, MaxDiskRead, MaxDiskWrite, State, ExitCode. Samtools 1.15.1 was used for all alignment manipulations, alignment read depth coverage calculations, and to extract unmapped reads (69). Samtools view -f 4 was used to generate bamstats files and python venn was used to compare the readnames across unmapped read files to assess the degree of overlap of unmapped reads across these subsetted alignment files. R 3.5.2 version Eggshell Igloo with the tidyverse packages were used for preliminary experiments on depreciated data shown in S4. Genome coverage was calculated with samtools coverage. Binary conversion values were used for bytes (1,073,741,824) and kilobytes (1,048,576) to gigabytes.

4. **Data reshaping and visualization**

As data were integrated across multiple sources and formats, they needed to be reshaped for comparison and visualization. For example, the multiple separators found in VCFs (commas and semicolons) are not directly usable in python pandas. Relevant dataframes from genome alignment files were reshaped with shell scripts and python scripts whose methodology and key intermediate files are available on our github [85].

5. **Comparison of breakpoints**

Structural variants (SV) were called with sniffles/1.0.11 with default parameters [43].
Only variants called on the main GRCh38 assembly were included. Python was used to
bin and graph structural variants by SV Type. Intermediary files and scripts are available
upon request. Data from sniffles VCFs and from DGV were subsetted by comparable
fields including SV Type, SV Length, and Chromosome since a common format was
unavailable for direct comparison. Figures were made with seaborn and matplotlib
[86,87] as well as Microsoft Excel.

Results

Rigorously annotated variants were drawn from the Database of Genomic Variants (DGV) [44]
for NA12878 and from a curated public repository for NA24385 [45]. We present our results in
four sections: 1) the tools that were included, 2) computational performance and benchmarking,
3) an analysis of aligned and unaligned reads, 4) an analysis of structural variation present in
each alignment compared to a baseline.

1.   Tools that passed the inclusion/exclusion criteria
Following a literature review of available alignment tools and search of long-read-tools.org [46],
we established a set of inclusion criteria (see Material and Methods), which accounted for both
types of LRS data (a tool must be able to handle both nanopore and SMRT reads), as well as the
state of the field in terms of software updates (must not have been superseded by another tool).
All relevant tools and their reason for exclusion are outlined in Table 1, with all tools annotated
as platform agnostic and relevant to genome alignment included in S1.

Five alignment tools, GraphMap2 [47], LRA [48], minimap2 [49], NGMLR [43], and
Winnowmap2 [50] were included in this study. Fifteen tools were excluded because they were
superseded by other tools, produced an alignment file in a non SAM format, were designed for
only one type of input data, or did not work on our cluster [51–64].

2.   Computational performance and benchmarking
Computations were run three times on a single node allocated fully on our university's high-
performance compute cluster (HPC), which includes 40 CPUs with a configuration described in
the methods. All tools were run with default parameters to reflect typical use in exploratory
studies. High level computational benchmarks can be found in Table 2. Full reports on each run
can be examined in Supplemental S2, while a composite table of the output of samtools coverage
is available as Supplemental S3.

Globally successful tools
Minimap2 was the least memory-demanding tool.

Minimap2 successfully aligned nanopore data every time with unrestricted and restricted
resources. Unrestricted runs used around 12.6 gigabytes (Gb) and the jobs took ~34 wall clock
hours to complete.
279
280 Minimap2 also successfully aligned SMRT data every time with unrestricted or restricted
281 resources. The runs used around 9 Gb and the jobs took ~11 wall clock hours to complete,
282 considerably faster than the (admittedly larger) nanopore dataset.
283
284 Memory usage and runtime were consistent across triplicate runs with unrestricted resources and
285 did not change with restriction of resources when the tool was used with either dataset. The
286 consistency of results, as well as the speed and relatively low computational demands of
287 minimap2 make it a strong candidate for inclusion in clinical analysis pipelines.
288
289 **Winnowmap2 was the fastest tool.**
290 Winnowmap2 was the fastest to run on any dataset. Specifically, it aligned the entire nanopore
291 dataset in around 15 wall clock hours, using only a little more than two times more memory than
292 minimap2. For SMRT, it was even faster at just over 3.5 wall clock hours and almost exactly
293 twice as much memory. These numbers were consistent over all runs.
294
295 Additionally, the high CPU efficiency of the jobs on our cluster were positive to note: over 80%
296 efficiency, relative to minimap2's ~7% efficiency. This is a measure of the ratio of CPU time
297 used to the wall clock time times the number of CPUs. In the case of our cluster, CPUs are fully
298 allocated to a node and not shared once allocated, but it does point the way towards either
299 choosing more efficient tools, or optimizing jobs.
300
301 **NGMLR completed 4/6 tasks and performance demanded great resources.**
302 NGMLR successfully aligned SMRT data every time but was the second slowest. The runs used
303 around 25 Gb and the jobs took around 22 wall clock hours to complete, nearly twice as long as
304 the next tool, minimap2.
305
306 NGMLR was much more inconsistent on nanopore data. It successfully aligned the data on our
307 first range finding experiment in approximately ~230 wall clock hours. Following this run, two
308 jobs were set with a time of 10 days, and both resulted in timeouts. The single successful run
309 used 36.34 Gb of memory, the most of all tools which produced an alignment.
310
Tools that presented a challenge
LRA did not work on nanopore-generated data
While LRA did show promise on SMRT data, aligning a genome in ~11 CPU days or ~6 wall
clock hours, we could not run it successfully with nanopore. Each run resulted in unresolvable

segmentation faults. In the case of SMRT data, it did fall in the front of the pack, aligning
genomes quickly with typical memory usage relative to its peers (~20-27GB)
317
GraphMap2 was the most resource-intensive tool
GraphMap2 took the longest, used the most memory, and had the most failures of all of the tools
we examined. It did not produce alignment files on nanopore data in the time limit of 14 days
imposed by our HPC. On the SMRT dataset which it was successful at aligning, it took more
than 5 times longer to produce an alignment file than the next slowest tool, NGMLR. It had the
highest memory usage, in excess of 89 GB nanopore on 44GB on SMRT.
324
3.   Whole genome alignment
Aligned reads show disagreement in coverage of each chromosome
In preliminary experiments that completed successfully, alignments of the same genome with the
same tool had the same genome coverage, whether resource-restricted or not (S4, column O). For
this reason, one file generated from the first run was used for subsequent analysis, shown in
Table 3, a summary of the coverage depth of each chromosome alignment and the percentage of
the basepairs of GRCh38 covered. Global genome coverage of ~30x was reported for nanopore
[9] and ~34x, 20x of which is present in the 15kbp insert set, was reported for SMRT [42,65,66]
data sets. Breaking down the summary into chromosomes highlights allows for more precision
than referring to a genome by its coverage as a uniform metric, since there is discrepancy across
the chromosomes.
336
For nanopore data, three alignment filles were measured, while for SMRT data, four files could
be included. Table 3 is hued horizontally by chromosome to highlight differences. It becomes
immediately apparent that minimap2 and winnowmap2 both retain the most reads (highest x
coverage) and cover the most basepairs of the reference. In plain language, they are the bluest
columns. The column which represents NGMLR-aligned data is the reddest in all cases,
suggesting that NGMLR is excluding the most reads and covering the fewest basepairs of the
reference genome, which may impact downstream analysis. The final tool, LRA, which only
worked on SMRT data, is intermediate with some light reds and whites in terms of coverage
depth, and some blues in terms of coverage of basepairs.
346
347 **Unaligned reads reveal differential exclusion of reads**
348 The readname assigned to each read in a fastq retained in the BAM allowed us to directly
349 compare the lists of reads that were not included in the alignment by each alignment tool with
350 python venn (Fig. 1) [67].
351
All tools agreed to leave ~1 million of the same nanopore reads unaligned, but differed in their
overall totals of unaligned reads. NGMLR left the highest number of reads unaligned, ~3.1
million, which explains why it produced the lowest coverage genome. It agreed with the other

tools on approximately half of its discarded reads. Minimap2 and NGMLR agreed to leave a
further ~0.5 million reads unaligned, while NGMLR and Winnowmap2 agreed on a separate
~0.2 million unaligned reads and Winnowmap2 and Minimap2 on ~0.03 million further
unaligned reads.
359
All tools agreed to leave 682 of the same SMRT reads unaligned. This is because winnowmap2
excludes less than 1000 reads in total, where the other tools excluded more reads over roughly
three orders of magnitude. NGMLR left the highest number of reads unaligned, ~200 thousand,
which explains why it produced the lowest coverage genome. LRA excluded around 90 thousand
reads in all, of which around 70 thousand are common to NGMLR. This also likely contributes
to its lower-coverage status shown in Table 3. Minimap2 leaves out just shy of 12 thousand reads
in all, most of which are shared with NGMLR and LRA.
367
368 In all, not enough information is available at this level of granularity to pass judgment on
369 whether or not tools include or exclude the right reads. For this, an examination of breakpoints is
370 required.
371
4.   Breakpoints reveal differences between competing alignments of the same genome
By examining the coverage of the genome and the overlap of the discarded reads, it became clear
that more detail was needed to understand the differences in alignment. To globally compare the
alignments to each other, and assess their usability for variant calling, we looked to the SV
known to be present in the NA12878 genome as curated by the DGV resource [44]. We ran a
pilot study on now depreciated datasets for linear SMRT data [68] before undertaking a study
with current technology. The results of these pilot experiments are available as S4 and point to a
gap between the largest SV curated in DGV and what is resolvable by long-read sequencing.
380
381 To expand upon these initial findings, we accessed the most up-to-date data generated on
382 nanopore and SMRT platforms. Presently, this includes the WGS consortium rel7 on NA12878
383 for nanopore and a new release of SMRT-CCS on NA24385. NA24385, the son of the
384 Ashkenazi trio, is not present in DGV, so a high quality callset released by PacBio in
385 collaboration with the Genome in a Bottle Consortium was used as a truthset [69].
386
We leveraged the sniffles SV caller because of its highly-detailed output files. Our truth sets
were the curated SV present in DGV and the set released by PacBio and GIAB for NA24385.
Due to the different nomenclature for SV type in the sniffles output and the NA24385 calls,
which follow VCF specification [70] but differ from DGV annotations, comparisons were
limited to the four classes of variant that were most unambiguously labeled: insertions, deletions,
duplications, and inversions.
393

The variants available for NA24385 were coded as all insertions or deletions, with subtypes
within including duplications. Therefore, the callsets from SMRT do not include inversions as
there was no baseline. Sniffles variants were graphed by SV length on the X-axis in shades of
blue, grey, and yellow, contrasted with DGV variants in red, organized by platform and SV type.
Figures are organized by platform and size of SV, specifically between 1001 and 100,000 bp, the
range at which LRS platforms are known to excel.
400

Nanopore
For the variants between 1,001 and 10,000 bp (Fig 2), alignment sets perform largely well on
calling deletions that are curated in DGV while inversions were largely missed in all alignments.
NGMLR alignments contained the highest number of breakpoints called as duplications. Above
the 2001-3000 bp bin, the total duplications in DGV eclipses the number of breakpoints called in
any of the alignment files. In contrast, there are very few insertions of this size range present in
DGV, but hundreds in our callsets. This could be due to a differential interpretation of the
breakpoints, where origin of inserted material has been ascertained (as a duplication) in DGV but
remains unattributed (as an insertion) in call sets.
410

In the 10,001-100,000 bp size range (S5), DGV largely contains more variants, with the
exception of inversions. Inversions present an interesting case here because DGV contains more
very large inversions than are reported (>80,001), but various callsets do well at smaller ranges.
Across deletions, insertions, and duplications, all alignment tools fall short of the curated
reference. It is most interesting that DGV had few insertions smaller than 10,000bp, but
hundreds greater than that threshold. The trend of VCFs from our alignment files overperforming
relative to DGV breaks down, and they highly underperform, calling only a few 10s of variants.
418

SMRT
The truthset for the SMRT dataset from NA24385 does not contain variants annotated as
inversions, so Fig 3 (SV 1001-10,000bp) and S6 (SV 10,001-100,000bp) only contain three
panels each. We can see immediately in Fig 3 that the bars generated from the reference set are
much closer to the height of the bars from the VCFs, and this is not affected by the use of only
the 15kbp insert set. There is one notable exception with regard to duplications. As with the
nanopore dataset, an NGMLR alignment contains the most duplications.
426

427   However, these duplications are far in excess of what is present in the reference set. This is
428   notable, as the reference set has been carefully validated. What was missed, versus what is a
429   false positive, is not resolvable in this experiment and likely not resolvable without wet lab
430   bench work or orthogonal validation.
431

The largest SV show a complex picture (S6). NGMLR calls the most and the largest deletions
and no tools do well for large insertions in absolute terms or relative to the truthset. However,

minimap2 and NGMLR preserve no breakpoints called as insertions. For duplications 10,001-
20,000bp, all tools except LRA resolve many more than are present in the reference. NGMLR
continues to include many more duplications than the other alignments, and more than the
reference.
438
The disparity between the number of large variants greater 10,001bp in the NA24385 truthset
versus the NA12878 is striking. This, along with the general lack of reference standards for all
publicly-available genomes, highlights the need for better, more comprehensive reference sets
for all publicly-available resources. Inability to resolve large duplications may yield false
negative results for conditions where structural variation is a recognized etiology, such as DMD
or FSHD, where variants range between the tens and hundreds of thousands of kbp [14,15],
beyond the size of variants accurately detected in this study. It is also a critical issue when the
technology is used for broad exploratory surveys seeking to identify new etiology in low-
complexity regions of the genome where long-read sequencing should shine.
448

Discussion

In this study we have highlighted the key differences between alignment files generated by
different tools. By using well-characterized genome standards, NA12878 and NA24385, we were
able to directly compare the performance of each tool on the sequencing datasets obtained on
different platforms. We further analyzed the reads that were included or excluded from the
alignment, and how these read alignments revealed breakpoints that could be resolved as
structural variants in genome architecture. We then compared those variants to sets of previously
published variants discovered through multiple platforms.
457
Reassuringly, each alignment tool was internally consistent: when an alignment tool was given
the same fastq and the same reference genome, it produced the same result as judged by bamstats
and sniffles variant callsets. However, when looking across the alignment files produced by
different tools on the same sequence data, the representations of the genome diverged in terms of
which reads were included or excluded and the numbers and types of variants that were present
in VCFs. This is impactful because of the potential high value of LRS data in terms of genome
phasing and identification of epigenetic DNA modification [71]. Since the majority of
experiments that leverage large scale population surveys can be expected to rely on reference-
guided alignment rather than de novo assembly because of both the cost and speed of analysis
[72], it is key to understand the idiosyncrasies of each type of alignment files prior to
generalizing clinical use for these technologies. Furthermore, clinical experiments in genomic
medicine face human time constraints – speedier analyses will have higher appeal and adoption.
470
471   At this time, GraphMap2 does not show utility for producing whole genome alignments that
472   include structural variations when run with default parameters. The resource usage was large and
473   the time to complete the computation was long and when it did work, sniffles could not call

474 variants on its product BAM. This is not unexpected, as the tool was designed in large part to
475 increase single nucleotide variant sensitivity in noisy nanopore-sequenced reads [47,55]
476
477 Minimap2 used the least memory while winnowmap2 ran successfully in the fastest time, an
478 important point, should these platforms be tied closer to bedside applications. On data from both
479 platforms, they both allowed calling of the most insertions and deletions, but fell short on
480 inversions and duplications.
481
482 NGMLR was the most discerning aligner, in that it left the highest number of reads unmapped. It
483 used more compute power than Minimap2 and took much longer (3-10 times) than the next
484 fastest tool. While it was designed specifically to resolve structural variation [43], it calls a high
485 number of SV that have not been validated with other methodologies or curated in DGV.
486
There is a great divergence in sniffles-called variants from alignment files generated by all tools
from the variants present in DGV. This is a concerning expansion of seminal findings in a
previous study [16] as none of the sniffles VCFs mirror the SVs present in the high-quality
curated DGV database. Furthermore, there are many genomes released across multiple consortia
including GIAB and the Human Pangenome Reference Consortium [73]. But not all of these
genomes are sequenced on multiple platforms, and comprehensive reference sets which are
harmonious across samples, genomes, and datasets are still limited.
494
This resulted in us using two reference sets for this project to accommodate the latest releases of
data. The callsets generated in our experiments used annotations which were different from the
NA12878 variants in DGV and the curated variant set for NA24385, which was surprising.
Finally, the most up to date variant benchmark for NA24385 is called on GRCh37-aligned
genomes, which is from 2009 and not as comprehensive as current builds [24,74]. Taken
together, this underscores the need for orthogonal approaches and collaboration between wet and
dry labs to solve this problem.
502
The points above are critical in designing pipelines for genome analysis and structural variant
discovery. In short, it is not a high burden to generate two alignment files per genome with each
minimap2 and winnowmap2. In computationally unlimited research settings, there is value added
in the generation of alignment files from NGMLR as well, although the time to complete these
experiments makes them less appealing. These three perspectives on the same genome will
account for some of the inherent differences of each tool and the algorithms they use to handle
read alignment [75]. If computational resources are limited, minimap2 is the best choice to move
the greatest number of genomes through the pipeline quickly with small memory needs;
however, the loss of comprehensiveness must be considered in cases where a suspected variant is
not found.
513

This is impactful in genomic medicine. For example, as variants range from tens of kbp in FSHD
and hundreds of kbp to mbp in DMD, diagnosis of these disorders will likely not benefit from
data generated on LRS platforms at present, underscoring the need for optical mapping or array-
based technologies. However, disorders resulting from smaller SVs such as Huntington's (~18-
540 bp) [76], myotonic dystrophy 1 (~15-153 bp) and myotonic dystrophy 2 (~338-143,000 bp)
[77] (61) could be good candidates for deep study with LRS platforms based on the variants
present in alignment files from minimap2, winnowmap2 and NGMLR. Accordingly, LRS has
been used to identify variants in many such disorders [21,78].

If pathogenic loci are known, a high diagnostic yield may be obtained by generating maps with
each available alignment tool, and use of a structural variant caller such as NanoSV [79]. Unlike
sniffles, which provides a call of type of SV (deletion, insertion etc.), NanoSV only identifies
breakpoints in the alignment, without assigning those breakpoints an SV type. A robust
comparison of SV callers on nanopore datasets highlighted the relative strengths of variant
calling pipelines and may help users determine the best caller for their experiments [80].
NanoSV may be suitable for identifying breakpoints missed by Sniffles, but comes with the
further caveat that it is resource-intensive and may not scale in a clinical setting without vast
computational resources [80].

Answers to biological questions can also leverage tools that work with data upstream and
downstream of whole genome alignments; indeed, alternate solutions to discover differences in
genome structure have been proposed that leverage new tools. Tools designed to specifically
identify triplet repeat expansions in LRS data sets, such as Repeat Hidden Markov Model
(Repeat HHM) or Tandem-Genotypes, have shown the superiority of the approach compared to
other techniques [19,20]. RepeatHMM uses raw, unaligned reads in alternate ways than whole
genome alignment to a reference [19]. Rather than aligning LRS, reads can be analyzed
independently for microsatellites with specialized tools. The tandem-genotypes tool makes use of
a LAST whole-genome sequence alignment to detect copy number changes in the genome [20].
In line with this fact, LRS has been used to identify variants in many disorders [21].

The discrepancies between the VCFs generated from alignment files starkly show the need to
design experiments with the appreciation that the genomics ecosystem cannot yet be dominated
by one platform or pipeline and requires a multifaceted approach to discovery. We are at a
position where simply because the breakpoint is missing from the VCF from an LRS genome, we
cannot say that it is not present. We must therefore look across platforms and data types for
comprehensive genome representations [16]. However, this requires more data from the
community - generation of NA24385 data on new nanopore chemistry would allow for direct
comparison to the current CCS standard, or alternatively new CCS data could be generated on
NA12878. This would address a critical gap in our ability to benchmark new tools in a platform-
agnostic manner.

Conclusions

As the cost of long-read sequencing catches up to that of inexpensive short read sequencing, the inevitable boom in data production will require well thought-out analysis pipelines. Pipeline design always involves a set of tradeoffs. To accurately assess these tradeoffs, we must have a rigorously benchmarked view into the tools available to create the analytic product. Here, we looked at the differences in reference-guided human genome alignments to understand the difference in each tool's alignment of the same genome, and how it affects a structural variant callset. This informs our conclusion that, regardless of sequencing platform, when computational resources are not a limiting factor, it should be best practice to align an LRS human genome with minimap2, winnowmap2, and NGMLR to gain better insight into the architecture of a genome of interest. When compute resources are limited, minimap2 is a strong choice, and when time is a limiting factor, winnowmap2 is the best choice.

Acknowledgements

Adam Kai Leung Wong, PhD, High Performance Computing Specialist for Genomics at the GWU Computational Biology Institute provided critical support in preparing the HPC for this study.

References

1.   Sanger F, Nicklen S, Coulson AR. DNA sequencing with chain-terminating inhibitors. Proc Natl Acad Sci U S A. 1977;74: 5463–5467. doi:10.1073/pnas.74.12.5463

2.   Fuller CW, Middendorf LR, Benner SA, Church GM, Harris T, Huang X, et al. The challenges of sequencing by synthesis. Nat Biotechnol. 2009;27: 1013–1023. doi:10.1038/nbt.1585

3.   Branton D, Deamer DW, Marziali A, Bayley H, Benner SA, Butler T, et al. The potential and challenges of nanopore sequencing. Nat Biotechnol. 2008;26: 1146–1153. doi:10.1038/nbt.1495

4.   Ardui S, Ameur A, Vermeesch JR, Hestand MS. Single molecule real-time (SMRT) sequencing comes of age: applications and utilities for medical diagnostics. Nucleic Acids Res. 2018;46: 2159–2168. doi:10.1093/nar/gky066

5.   Levy-Sakin M, Pastor S, Mostovoy Y, Li L, Leung AKY, McCaffrey J, et al. Genome maps across 26 human populations reveal population-specific patterns of structural variation. Nat Commun. 2019;10: 1025. doi:10.1038/s41467-019-08992-7

593   6.   Modi A, Vai S, Caramelli D, Lari M. The Illumina Sequencing Protocol and the NovaSeq
594   6000 System. Methods Mol Biol. 2021;2242: 15–42. doi:10.1007/978-1-0716-1099-2_2
595

596   7.   Kronenberg ZN, Rhie A, Koren S, Concepcion GT, Peluso P, Munson KM, et al.
597   Extended haplotype-phasing of long-read de novo genome assemblies using Hi-C. Nat Commun.
598   2021;12: 1935. doi:10.1038/s41467-020-20536-y
599

600   8.   Wenger AM, Peluso P, Rowell WJ, Chang P-C, Hall RJ, Concepcion GT, et al. Accurate
601   circular consensus long-read sequencing improves variant detection and assembly of a human
602   genome. Nat Biotechnol. 2019;37: 1155–1162. doi:10.1038/s41587-019-0217-9
603

604   9.   Jain M, Koren S, Miga KH, Quick J, Rand AC, Sasani TA, et al. Nanopore sequencing
605   and assembly of a human genome with ultra-long reads. Nat Biotechnol. 2018;36: 338–345.
606   doi:10.1038/nbt.4060
607

608   10.   Formenti G, Chiara M, Poveda L, Francoijs K-J, Bonisoli-Alquati A, Canova L, et al.
609   SMRT long reads and Direct Label and Stain optical maps allow the generation of a high-quality
610   genome assembly for the European barn swallow (Hirundo rustica rustica). doi:10.1101/374512
611

612   11.   Pollard MO, Gurdasani D, Mentzer AJ, Porter T, Sandhu MS. Long reads: their purpose
613   and place. Hum Mol Genet. 2018;27: R234–R241. doi:10.1093/hmg/ddy177
614

615   12.   Ho SS, Urban AE, Mills RE. Structural variation in the sequencing era. Nat Rev Genet.
616   2020;21: 171–189. doi:10.1038/s41576-019-0180-9
617

618   13.   Mahmoud M, Gobet N, Cruz-Dávalos DI, Mounier N, Dessimoz C, Sedlazeck FJ.
619   Structural variant calling: the long and the short of it. Genome Biol. 2019;20: 246.
620   doi:10.1186/s13059-019-1828-7
621

622   14.   Barseghyan H, Tang W, Wang RT, Almalvez M, Segura E, Bramble MS, et al. Next-
623   generation mapping: a novel approach for detection of pathogenic structural variants with a
624   potential utility in clinical diagnosis. Genome Med. 2017;9: 90. doi:10.1186/s13073-017-0479-0
625

626   15.   Sharim H, Grunwald A, Gabrieli T, Michaeli Y, Margalit S, Torchinsky D, et al. Long-
627   read single-molecule maps of the functional methylome. Genome Res. 2019;29: 646–656.
628   doi:10.1101/gr.240739.118
629

16.   Chaisson MJP, Sanders AD, Zhao X, Malhotra A, Porubsky D, Rausch T, et al. Multi-
platform discovery of haplotype-resolved structural variation in human genomes. Nat Commun.
2019;10: 1784. doi:10.1038/s41467-018-08148-z

17.   Kantartzis A, Williams GM, Balakrishnan L, Roberts RL, Surtees JA, Bambara RA.
Msh2-Msh3 interferes with Okazaki fragment processing to promote trinucleotide repeat
expansions. Cell Rep. 2012;2: 216–222. doi:10.1016/j.celrep.2012.06.020

18.   Santoro M, Masciullo M, Silvestri G, Novelli G, Botta A. Myotonic dystrophy type 1:
role of CCG, CTC and CGG interruptions within DMPK alleles in the pathogenesis and
molecular diagnosis. Clin Genet. 2017;92: 355–364. doi:10.1111/cge.12954

19.   Liu Q, Zhang P, Wang D, Gu W, Wang K. Interrogating the "unsequenceable" genomic
trinucleotide repeat disorders by long-read sequencing. Genome Med. 2017;9: 65.
doi:10.1186/s13073-017-0456-7

20.   Mitsuhashi S, Frith MC, Mizuguchi T, Miyatake S, Toyota T, Adachi H, et al. Tandem-
genotypes: robust detection of tandem repeat expansions from long DNA reads. Genome Biol.
2019;20: 58. doi:10.1186/s13059-019-1667-6

21.   Mantere T, Kersten S, Hoischen A. Long-Read Sequencing Emerging in Medical
Genetics. Front Genet. 2019;10: 426. doi:10.3389/fgene.2019.00426

22.   Huddleston J, Chaisson MJP, Steinberg KM, Warren W, Hoekzema K, Gordon D, et al.
Discovery and genotyping of structural variation from long-read haploid genome sequence data.
Genome Research. 2017. pp. 677–685. doi:10.1101/gr.214007.116

23.   Ebbert MTW, Jensen TD, Jansen-West K, Sens JP, Reddy JS, Ridge PG, et al.
Systematic analysis of dark and camouflaged genes reveals disease-relevant genes hiding in plain
sight. Genome Biol. 2019;20: 97. doi:10.1186/s13059-019-1707-2

24.   Nurk S, Koren S, Rhie A, Rautiainen M, Bzikadze AV, Mikheenko A, et al. The
complete sequence of a human genome. Science. 2022;376: 44–53. doi:10.1126/science.abj6987

25.   Walker A, Houwaart T, Wienemann T, Vasconcelos MK, Strelow D, Senff T, et al.
Genetic structure of SARS-CoV-2 reflects clonal superspreading and multiple independent
introduction events, North-Rhine Westphalia, Germany, February and March 2020. Euro
Surveill. 2020;25. doi:10.2807/1560-7917.ES.2020.25.22.2000746
668

26.   Miga KH, Koren S, Rhie A, Vollger MR, Gershman A, Bzikadze A, et al. Telomere-to-
telomere assembly of a complete human X chromosome. Nature. 2020;585: 79–84.
doi:10.1038/s41586-020-2547-7

27.   Wick RR, Judd LM, Holt KE. Performance of neural network basecalling tools for
Oxford Nanopore sequencing. Genome Biol. 2019;20: 129. doi:10.1186/s13059-019-1727-y

28.   Koren S, Rhie A, Walenz BP, Dilthey AT, Bickhart DM, Kingan SB, et al. De novo
assembly of haplotype-resolved genomes with trio binning. Nat Biotechnol. 2018.
doi:10.1038/nbt.4277

29.   Cheng H, Concepcion GT, Feng X, Zhang H, Li H. Haplotype-resolved de novo
assembly using phased assembly graphs with hifiasm. Nat Methods. 2021;18: 170–175.
doi:10.1038/s41592-020-01056-5

30.   Kolmogorov M, Yuan J, Lin Y, Pevzner PA. Assembly of long, error-prone reads using
repeat graphs. Nat Biotechnol. 2019;37: 540–546. doi:10.1038/s41587-019-0072-8

31.   Norris AL, Workman RE, Fan Y, Eshleman JR, Timp W. Nanopore sequencing detects
structural variants in cancer. Cancer Biol Ther. 2016;17: 246–253.
doi:10.1080/15384047.2016.1139236

32.   Deshpande SV, Reed TM, Sullivan RF, Kerkhof LJ, Beigel KM, Wade MM. Offline
Next Generation Metagenomics Sequence Analysis Using MinION Detection Software
(MINDS). Genes . 2019;10. doi:10.3390/genes10080578

33.   Cuscó A, Catozzi C, Viñes J, Sanchez A, Francino O. Microbiota profiling with long
amplicons using Nanopore sequencing: full-length 16S rRNA gene and the 16S-ITS-23S of the
rrn operon. F1000Research. 2019. p. 1755. doi:10.12688/f1000research.16817.2

34.   Sanderson ND, Street TL, Foster D, Swann J, Atkins BL, Brent AJ, et al. Real-time
analysis of nanopore-based metagenomic sequencing from infected orthopaedic devices. BMC
Genomics. 2018;19: 714. doi:10.1186/s12864-018-5094-y

35.   Burgess DJ. The TOPMed genomic resource for human health. Nat Rev Genet. 2021;22:
200. doi:10.1038/s41576-021-00343-x

36.   NIH genome sequencing program targets the genomic bases of common, rare disease. In:
National Institutes of Health (NIH) [Internet]. 14 Jan 2016 [cited 27 May 2022]. Available:

https://www.nih.gov/news-events/news-releases/nih-genome-sequencing-program-targets-
genomic-bases-common-rare-disease
710
711 37.   Heller D, Vingron M. SVIM: structural variant identification using mapped long reads.
712 Bioinformatics. 2019;35: 2907–2915. doi:10.1093/bioinformatics/btz041
713
714 38.   Jiang T, Liu Y, Jiang Y, Li J, Gao Y, Cui Z, et al. Long-read-based human genomic
715 structural variation detection with cuteSV. Genome Biol. 2020;21: 189. doi:10.1186/s13059-
716 020-02107-y
717
718 39.   Tham CY, Tirado-Magallanes R, Goh Y, Fullwood MJ, Koh BTH, Wang W, et al.
719 NanoVar: accurate characterization of patients' genomic structural variants using low-depth
720 nanopore sequencing. Genome Biol. 2020;21: 56. doi:10.1186/s13059-020-01968-7
721
722 40.   pbsv: pbsv - PacBio structural variant (SV) calling and analysis tools. Github; Available:
723 https://github.com/PacificBiosciences/pbsv
724
725 41.   Coster WD, De Coster W, Weissensteiner MH, Sedlazeck FJ. Towards population-scale
726 long-read sequencing. Nature Reviews Genetics. 2021. pp. 572–587. doi:10.1038/s41576-021-
727 00367-3
728
729 42.   Zook JM, McDaniel J, Olson ND, Wagner J, Parikh H, Heaton H, et al. An open resource
730 for accurately benchmarking small variant and reference calls. Nature Biotechnology. 2019. pp.
731 561–566. doi:10.1038/s41587-019-0074-6
732
733 43.   Sedlazeck FJ, Rescheneder P, Smolka M, Fang H, Nattestad M, von Haeseler A, et al.
734 Accurate detection of complex structural variations using single-molecule sequencing. Nat
735 Methods. 2018;15: 461–468. doi:10.1038/s41592-018-0001-7
736
737 44.   MacDonald JR, Ziman R, Yuen RKC, Feuk L, Scherer SW. The Database of Genomic
738 Variants: a curated collection of structural variation in the human genome. Nucleic Acids
739 Research. 2014. pp. D986–D992. doi:10.1093/nar/gkt958
740
741 45.   sv-benchmark: Public Benchmark of Long-Read Structural Variant Caller on PacBio
742 CCS HG002 Data. Github; Available: https://github.com/PacificBiosciences/sv-benchmark
743
744 46.   Amarasinghe SL, Ritchie ME, Gouil Q. long-read-tools.org: an interactive catalogue of
745 analysis methods for long-read sequencing data. Gigascience. 2021;10.
746 doi:10.1093/gigascience/giab003
747

748   47.   Marić J, Sović I, Križanović K, Nagarajan N, Šikić M. Graphmap2 - splice-aware RNA-
749   seq mapper for long reads. bioRxiv. 2019. p. 720458. doi:10.1101/720458
750
751   48.   Ren J, Chaisson MJP. lra: the Long Read Aligner for Sequences and Contigs.
752   doi:10.1101/2020.11.15.383273
753
754   49.   Li H. Minimap2: pairwise alignment for nucleotide sequences. Bioinformatics. 2018;34:
755   3094–3100. doi:10.1093/bioinformatics/bty191
756
757   50.   Jain C, Rhie A, Hansen NF, Koren S, Phillippy AM. Long-read mapping to repetitive
758   reference sequences using Winnowmap2. Nat Methods. 2022. doi:10.1038/s41592-022-01457-8
759
760   51.   Li H. Aligning sequence reads, clone sequences and assembly contigs with BWA-MEM.
761   arXiv [q-bio.GN]. 2013. Available: http://arxiv.org/abs/1303.3997
762
763   52.   Kiełbasa SM, Wan R, Sato K, Horton P, Frith MC. Adaptive seeds tame genomic
764   sequence comparison. Genome Res. 2011;21: 487–493. doi:10.1101/gr.113985.110
765
766   53.   Chaisson MJ, Tesler G. Mapping single molecule sequencing reads using basic local
767   alignment with successive refinement (BLASR): application and theory. BMC Bioinformatics.
768   2012;13: 238. doi:10.1186/1471-2105-13-238
769
770   54.   Liu B, Guan D, Teng M, Wang Y. rHAT: fast alignment of noisy long reads with
771   regional hashing. Bioinformatics. 2016;32: 1625–1631. doi:10.1093/bioinformatics/btv662
772
773   55.   Sović I, Šikić M, Wilm A, Fenlon SN, Chen S, Nagarajan N. Fast and sensitive mapping
774   of nanopore sequencing reads with GraphMap. Nat Commun. 2016;7: 11307.
775   doi:10.1038/ncomms11307
776
777   56.   Liu B, Gao Y, Wang Y. LAMSA: fast split read alignment with long approximate
778   matches. Bioinformatics. 2017;33: 192–201. doi:10.1093/bioinformatics/btw594
779
780   57.   Jain C, Koren S, Dilthey A, Phillippy AM, Aluru S. A fast adaptive algorithm for
781   computing whole-genome homology maps. Bioinformatics. 2018;34: i748–i756.
782   doi:10.1093/bioinformatics/bty597
783
784   58.   Nashta-Ali D, Aliyari A, Ahmadian Moghadam A, Edrisi MA, Motahari SA, Hossein
785   Khalaj B. Meta-aligner: long-read alignment based on genome statistics. BMC Bioinformatics.
786   2017;18: 126. doi:10.1186/s12859-017-1518-y
787

788   59.   Xiao C-L, Chen Y, Xie S-Q, Chen K-N, Wang Y, Han Y, et al. MECAT: fast mapping,
789   error correction, and de novo assembly for single-molecule sequencing reads. Nat Methods.
790   2017;14: 1072–1074. doi:10.1038/nmeth.4432
791
792   60.   Haghshenas E, Sahinalp SC, Hach F. lordFAST: sensitive and Fast Alignment Search
793   Tool for LOng noisy Read sequencing Data. Bioinformatics. 2019;35: 20–27.
794   doi:10.1093/bioinformatics/bty544
795
796   61.   Kumar S, Agarwal S, Ranvijay. Fast and memory efficient approach for mapping NGS
797   reads to a reference genome. J Bioinform Comput Biol. 2019;17: 1950008.
798   doi:10.1142/S0219720019500082
799
800   62.   Wei Z-G, Zhang S-W, Liu F. smsMap: mapping single molecule sequencing reads by
801   locating the alignment starting positions. BMC Bioinformatics. 2020;21: 341.
802   doi:10.1186/s12859-020-03698-w
803
804   63.   Jain C, Rhie A, Zhang H, Chu C, Walenz BP, Koren S, et al. Weighted minimizer
805   sampling improves long read mapping. Bioinformatics. 2020;36: i111–i118.
806   doi:10.1093/bioinformatics/btaa435
807
808   64.   Chakraborty A, Morgenstern B, Bandyopadhyay S. S-conLSH: alignment-free gapped
809   mapping of noisy long reads. BMC Bioinformatics. 2021;22: 64. doi:10.1186/s12859-020-
810   03918-3
811
812   65.   Genome in a bottle —. In: The Joint Initiative for Metrology in Biology [Internet]. [cited
813   27 May 2022]. Available: https://jimb.stanford.edu/giab
814
815   66.   HG002_Data_Freeze_v1.0: Human Pangenome Reference Consortium - HG002 Data
816   Freeze (v1.0). Github; Available: https://github.com/human-
817   pangenomics/HG002_Data_Freeze_v1.0
818
819   67.   Venn. In: PyPI [Internet]. [cited 18 Jun 2022]. Available: https://pypi.org/project/venn/
820   68.   Index of /giab/ftp/data/NA12878/NA12878_PacBio_MtSinai. [cited 18 Jun 2022].
821   Available: https://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/data/NA12878/NA12878_PacBio_MtSinai/
822
823   69.   Index of /giab/ftp/data/AshkenazimTrio/analysis/NIST_SVs_Integration_v0.6. [cited 18
824   Jun 2022]. Available: https://ftp-
825   trace.ncbi.nlm.nih.gov/giab/ftp/data/AshkenazimTrio/analysis/NIST_SVs_Integration_v0.6/
826

70.   hts-specs: Specifications of SAM/BAM and related high-throughput sequencing file
formats. Github; Available: https://github.com/samtools/hts-specs

71.   Ni P, Huang N, Zhang Z, Wang D-P, Liang F, Miao Y, et al. DeepSignal: detecting DNA
methylation state from Nanopore sequencing reads using deep-learning. Bioinformatics. 2019.
pp. 4586–4595. doi:10.1093/bioinformatics/btz276

72.   Mardis ER. The 1,000 genome, the 100,000 analysis? Genome Med. 2010;2: 84.
doi:10.1186/gm205

73.   Miga KH, Wang T. The Need for a Human Pangenome Reference Sequence. Annu Rev
Genomics Hum Genet. 2021;22: 81–102. doi:10.1146/annurev-genom-120120-081921

74.   GRCh37 - hg19 - Genome - Assembly - NCBI. [cited 27 May 2022]. Available:
https://www.ncbi.nlm.nih.gov/assembly/GCF_000001405.13/

75.   Bizjan BJ, Katsila T, Tesovnik T, Šket R, Debeljak M, Matsoukas MT, et al. Challenges
in identifying large germline structural variants for clinical use by long read sequencing.
Computational and Structural Biotechnology Journal. 2020. pp. 83–92.
doi:10.1016/j.csbj.2019.11.008

76.   Moncke-Buchner E. Counting CAG repeats in the Huntington's disease gene by
restriction endonuclease EcoP15I cleavage. Nucleic Acids Research. 2002. p. 83e–83.
doi:10.1093/nar/gnf082

77.   Yum K, Wang ET, Kalsotra A. Myotonic dystrophy: disease repeat range, penetrance,
age of onset, and relationship between repeat size and phenotypes. Curr Opin Genet Dev.
2017;44: 30–37. doi:10.1016/j.gde.2017.01.007

78.   Mitsuhashi S, Matsumoto N. Long-read sequencing for rare human genetic diseases.
Journal of Human Genetics. 2020. pp. 11–19. doi:10.1038/s10038-019-0671-8

79.   Cretu Stancu M, van Roosmalen MJ, Renkens I, Nieboer MM, Middelkamp S, de Ligt J,
et al. Mapping and phasing of structural variation in patient genomes using nanopore sequencing.
Nat Commun. 2017;8: 1326. doi:10.1038/s41467-017-01343-4

80.   Zhou A, Lin T, Xing J. Evaluating nanopore sequencing data processing pipelines for
structural variation identification. Genome Biology. 2019. doi:10.1186/s13059-019-1858-1
865

81.   GRCh38.p12 - hg38 - Genome - Assembly - NCBI. [cited 27 May 2022]. Available:
https://www.ncbi.nlm.nih.gov/assembly/GCF_000001405.38/

82.   Genome.md at master · nanopore-wgs-consortium/NA12878. Github; Available:
https://github.com/nanopore-wgs-consortium/NA12878

83.   Index of /giab/ftp/data/NA12878/NA12878_PacBio_MtSinai. [cited 27 May 2022].
Available: https://ftp.ncbi.nlm.nih.gov/giab/ftp/data/NA12878/NA12878_PacBio_MtSinai/

84.   Database of Genomic Variants [*** v107 ***]. [cited 27 May 2022]. Available:
http://dgv.tcag.ca/dgv/app/downloads?ref=GRCh37/hg19

85.   longread_alignment_benchmarking: Supplemental scripts for "Benchmarking long-read
genome sequence alignment tools for human genomics applications." Github; Available:
https://github.com/jlotempiojr/longread_alignment_benchmarking

86.   Waskom M. seaborn: statistical data visualization. J Open Source Softw. 2021;6: 3021.
doi:10.21105/joss.03021

87.   Hunter. Matplotlib: A 2D Graphics Environment. 2007;9: 90–95.
doi:10.1109/MCSE.2007.55

88.   longread_alignment_benchmarking: Supplemental scripts for "Benchmarking long-read
genome sequence alignment tools for human genomics applications." Github; Available:
https://github.com/jlotempiojr/longread_alignment_benchmarking

Tool	Year	PMID	DOI	Inclusion	If no, why?
BWA-MEM	2011	NA	arXiv:1303.3997	No	Superseded by Minimap2
LAST	2011	21209072	10.1101/gr.113985.110	No	Not parameterized for the nuances of current platforms
BLASR	2012	22988817	10.1186/1471-2105-13-238	No	Designed only for SMRT seq
YAHA	2012	22829624	10.1093/bioinformatics/bts456	No	Not parameterized for the nuances of current platforms
rHAT	2015	26568628	10.1093/bioinformatics/btv662	No	Designed only for SMRT seq
GraphMap	2016	27079541	10.1038/ncomms11307	No	Superseded by GraphMap2
LAMSA	2016	27667793	10.1093/bioinformatics/btw594	No	Depreciated dependencies resulting in seg fault
Mashmap2	2017	30423094	10.1093/bioinformatics/bty597	No	Does not use SAM format needed for variant caller
Meta-aligner	2017	28231760	10.1186/s12859-017-1518-y	No	Designed only for SMRT seq
MECAT	2017	28945707	10.1038/nmeth.4432	No	Superseded by Mecat2
MECAT2	2017	28945707	10.1038/nmeth.4432	No	Designed only for SMRT seq
lordFAST	2018	30561550	10.1093/bioinformatics/bty544	No	Runs resulted in partial completion and a seg fault
Minimap2	2018	29750242	10.1093/bioinformatics/bty191	Yes	
NGMLR	2018	29713083	10.1038/s41592-018-0001-7	Yes	
GraphMap2	2019	NA	10.1101/720458	Yes	
Kart	2019	31057068	10.1142/S0219720019500082	No	Designed only for SMRT, SBS
smsMap	2020	32753028	10.1186/s12859-020-03698-w	No	Does not use SAM format needed for variant caller
Winnowmap	2020	32657365	10.1093/bioinformatics/btaa435	No	Superseded by Winnowmap2
Winnowmap2	2020	NA	10.1101/2020.11.01.363887,	Yes	
LRA	2021	34153026	10.1371/journal.pcbi.1009078	Yes	
S-ConLSH	2021	33573603	10.1186/s12859-020-03918-3	No	Designed only for SMRT seq

Table 1. Long-read genome sequence alignment tools.

The tools included in the study are highlighted in this study. Further tools from LongReadTools.org are available in S1.

Platform	Tool	Wall Clock Time (D-H:M:S)	CPU Time (D-H:M:S)	CPU Efficiency	Memory Utilized (Gb)
Nanopore	Graphmap2	14-00:00:04	560-00:02:40	65.25%	90.19
		14-00:00:17	560-00:11:20	63.34%	94.58
		14-00:00:15	560-00:10:00	64.23%	89.68
	Minimap2	1-11:00:08	58-08:05:20	7.51%	12.43
		1-10:48:18	58-00:12:00	7.51%	12.80
		1-11:07:00	58-12:40:00	7.51%	12.78
	NGMLR	10-00:00:03	400-00:02:00	97.70%	35.86
		10-00:00:10	400-00:06:40	99.56%	34.38
		9-14:55:56	384-21:17:20	93.43%	36.34
	Winnowmap2	15:25:58	25-17:18:40	83.82%	29.48
		15:19:14	25-12:49:20	83.61%	30.02
		15:15:24	25-10:16:00	83.06%	28.74
SMRT-CCS	Graphmap2	5-01:33:22	202-14:14:40	98.88%	45.07
		5-02:54:53	204-20:35:20	98.81%	44.90
		5-06:49:25	211-08:56:40	98.52%	48.96
	LRA	6:53:00	11-11:20:00	33.20%	20.63
		6:53:04	11-11:22:40	33.11%	21.10
		6:32:33	10-21:42:00	33.22%	27.91
	Minimap2	11:02:04	18-09:22:40	7.51%	9.10
		11:06:03	18-12:02:00	7.51%	9.13
		10:55:09	18-04:46:00	7.52%	9.09
	NGMLR	21:50:29	36-09:39:20	99.20%	25.53
		22:24:38	37-08:25:20	99.19%	25.69
		21:58:53	36-15:15:20	99.53%	25.82
	Winnowmap2	3:39:42	6-02:28:00	88.10%	18.57
		3:43:42	6-05:08:00	88.32%	18.71
		3:40:32	6-03:01:20	87.91%	19.14

Table 2. Benchmarking metrics. Each of the three runs for each tool is shown in this table. All values are taken directly from slurm's sacct and seff features. All metrics are intuitive except for CPU efficiency, which is a measure of idle CPUs to CPU time over wall clock time.

	SMRT-CCS									Nanopore					
	Mean depth (x-depth)					Coverage of basepairs (%)					Mean depth (x depth)			Coverage of basepairs (%)		
	LRA	Minimap2	NGMLR	WM2		LRA	Minimap2	NGMLR	WM2		Minimap2	NGMLR	WM2	Minimap2	NGMLR	WM2
chr1	19.0627	20.0049	17.9711	20.002		91.7893	92.3244	91.1358	92.3622	chr1	37.7867	33.3715	37.4783	92.4802	91.4793	92.4861
chr2	20.0613	20.1343	19.9393	20.1463		98.7397	98.8041	98.707	98.6286	chr2	40.1079	36.3557	39.497	99.0601	98.8241	98.8272
chr3	20.1303	20.5557	20.0446	20.3575		98.984	99.5552	98.7438	99.5645	chr3	37.7894	36.5499	39.9339	99.773	98.8066	99.767
chr4	20.4284	20.7247	20.1254	21.8975		99.1528	99.0963	98.6843	99.2809	chr4	39.8297	36.1401	39.6729	99.4841	98.7817	99.5176
chr5	20.0292	20.3439	19.7821	20.0655		98.2323	98.1787	97.6187	98.2961	chr5	37.1564	35.9384	37.17	98.5218	98.0472	98.5096
chr6	19.9858	20.4916	19.9745	20.4963		98.795	99.0781	98.674	99.2314	chr6	37.4983	36.4317	38.3408	99.4746	98.9018	99.4822
chr7	19.5124	19.7661	19.3123	19.7686		98.1498	99.2092	97.7858	98.9308	chr7	37.5093	35.7748	37.3072	99.6968	98.4965	99.6698
chr8	20.0067	20.279	19.7645	20.272		98.5302	99.2526	98.1774	99.0982	chr8	37.2117	35.8164	37.4528	99.6024	98.4431	99.6027
chr9	17.085	17.2704	16.5087	17.2736		86.2352	86.2731	85.4122	86.3347	chr9	33.7857	31.5634	33.62	87.3625	86.6206	87.4715
chr10	19.8087	20.0826	19.4999	20.5247		98.2398	98.8789	98.1124	98.8153	chr10	37.9547	35.509	37.9365	99.3546	98.2053	99.3873
chr11	19.5361	19.8058	19.4349	19.8105		98.0161	99.1255	98.1379	98.264	chr11	37.5146	35.9223	37.282	99.562	98.5893	99.0318
chr12	19.6294	19.9493	19.6137	19.9618		98.3953	99.548	98.151	99.3563	chr12	37.9345	36.4544	37.6064	99.8008	98.397	99.7298
chr13	17.5257	18.1764	16.9585	17.6178		85.2628	85.3114	84.1626	85.3793	chr13	32.6205	30.5633	32.35	85.6486	84.3648	85.6546
chr14	16.815	16.8162	16.6225	16.9593		82.5962	82.5668	82.5949	82.5858	chr14	31.2147	30.4015	31.9599	82.5971	82.5928	82.5975
chr15	16.0919	16.3256	15.7467	16.3303		80.7849	81.7561	80.0048	81.9674	chr15	32.9232	30.434	32.7613	82.7815	80.8381	82.8274
chr16	18.4585	19.5281	18.1335	19.4345		89.1223	90.0939	87.9862	90.1285	chr16	36.9247	34.5339	37.2781	90.5049	88.4413	90.5183
chr17	18.0451	18.8278	18.0519	18.7767		95.1484	97.5541	94.7803	95.9119	chr17	37.2793	35.2194	36.9045	97.3704	95.1519	98.046
chr18	19.4328	19.7389	18.8198	19.7815		96.004	98.3045	94.3649	97.8677	chr18	36.8051	34.2153	36.5148	99.3802	94.1824	99.0731
chr19	16.8558	16.8674	16.5895	16.8926		95.0649	95.0588	94.9148	95.0692	chr19	36.3404	33.9213	39.4614	95.1037	95.0137	95.1095
chr20	19.34	20.0554	19.0343	20.1369		96.0126	98.1195	95.5606	98.0231	chr20	39.3238	35.3079	39.1318	99.1143	96.3336	99.1551
chr21	18.0549	18.4984	16.8995	18.2805		80.4792	80.4144	78.9093	80.16	chr21	35.4168	30.0951	34.298	81.3939	80.763	81.2955
chr22	13.9854	14.0173	13.3346	17.4726		72.7139	72.6378	72.5114	72.7444	chr22	32.7008	25.9485	31.1753	72.9147	72.9092	72.9018
chrX	9.8603	9.97983	9.73401	9.98727		97.639	97.9196	96.4952	98.0195	chrX	36.1372	33.9833	35.6273	99.1734	97.0137	98.9417
chrY	7.94848	8.21933	3.85465	8.37289		40.9697	40.9213	37.9947	40.8261	chrY	1.8305	0.501775	1.3745	3.1548	4.9006	2.37513
chrM	1010.03	1203.88	1203.67	1202.19		100	100	100	100	chrM	11954.1	11413.1	11685.6	100	100	100

Table 3. Chromosome level descriptions of the average number of reads covering each basepair, as well as the percentage of basepairs of the reference covered.

Cells are hued within a row by chromosome to compare coverage on each chromosome in each dataset. Winnowmap2 abbreviated as WM2.

Fig 1: Unmapped reads

Figure 1. Unmapped reads. Venn diagrams show the total number of reads flagged as unmapped in the sorted BAM files. Panel A presents unmapped reads from the nanopore dataset. Panel B presents unmapped reads from a SMRT dataset.

Fig 2: Nanopore SVs 1,001-10,000 bp

Figure 2. Nanopore SVs 1001-10,000bp.
Variants called by sniffles on each alignment file.
A. Deletions. B. Insertions. C. Inversions. D. Duplications.

Fig 3: SMRT-CCS SVs 1,001-10,000 bp

A

B

C

Figure 3. SMRT SVs 1001-10,000bp.
Variants called by sniffles on each alignment file.
A. Deletions. B. Insertions. C. Duplications.