Forward planning driven by context-dependent conflict processing in anterior cingulate cortex

Florian Ott[1], Eric Legler[1], Stefan J. Kiebel[1,2]

[1]Department of Psychology, Technische Universität Dresden, Dresden, Germany

[2]Centre for Tactile Internet with Human-in-the-Loop (CeTI), Technische Universität Dresden, Dresden, Germany

Abstract

Forward planning is often essential to achieve goals over extended time periods. However, forward planning is typically computationally costly for the brain and should only be employed when necessary. The explicit calculation of how necessary forward planning will be, is in itself computationally costly. We therefore assumed that the brain generates a mapping from a particular situation to a proxy of planning value to make fast decisions about whether to use forward planning, or not. Moreover, since the state space of real world decision problems can be large, we hypothesized that such a mapping will rely on mechanisms that generalize sets of situations based on shared demand for planning. We tested this hypothesis in an fMRI study using a novel complex sequential task. Our results indicate that participants abstracted from the set of task features to more generalized control contexts that govern the balancing between forward planning and a simple response strategy. Strikingly, we found that correlations of conflict with response time and with activity in the dorsal anterior cingulate cortex were dependent on context. This context-dependency might reflect that the cognitive control system draws on category-based cognition, harnessing regularities in control demand across task space to generate control contexts that help reduce the complexity of control allocation decisions.

Introduction

Many decisions have far-reaching consequences for the future, as they affect both internal bodily and external environmental states, in turn often conditioning potential future actions. Therefore, to achieve any long-term goals, people have to consider the future in some way. This can be achieved by planning multiple steps into the future to estimate the effects of potential action sequences (K. J. Miller et al., 2020; Simon et al., 2011; Tolman, 1948). However forward planning comes at a cost of using time and cognitive capacities, therefore people should only plan ahead when the benefits outweigh the costs and rely on fast and frugal strategies otherwise (Gershman et al., 2015; Gigerenzer et al., 2011; Kool et al., 2017; Lieder et al., 2020; Shenhav et al., 2013; Shenhav et al., 2017).

An intriguing question is how the brain controls when to engage in forward planning and when to use simpler strategies. Planning is often seen as one of the core functions of cognitive control (M. M. Botvinick et al., 2014; Goschke, 2013; E. K. Miller et al., 2001) and therefore the neural mechanisms involved in the regulation of cognitive control, might be similarly involved in the regulation of planning. A classic hypothesis proposes that the dorsal anterior cingulate cortex (dACC) plays a central role in cognitive control by monitoring processing conflicts that serve as a signal for the need for additional control (M. M. Botvinick et al., 2001). Empirical evidence supports the involvement of the dACC in conflict processing in response interference tasks (Kerns et al., 2004; E. H. Smith et al., 2019), value-based decision making (Pochon et al., 2008) and recently in tasks that require people to plan multiple steps into the future (Economides et al., 2015; Korn et al., 2018; Schwartenbeck et al., 2015).

In multi-step tasks, however, an intricate computational problem becomes apparent. How can the
brain control the use of forward planning in a way that maximizes long-term benefits, without having
to compute these benefits by forward planning beforehand? One solution to this paradox might be
for people to generate a mapping from a particular situation to a proxy of the value of planning that
allows them to quickly access the planning values later (Lee et al., 2021; Lieder et al., 2018).
Moreover, because the state space for real-world decision problems can be very large, it is unlikely
that people learn a value for every possible combination of states. Rather, they might use certain
task features to generalize clusters of states into particular contexts for which values are learned
(Lieder et al., 2018).

Here, we tested this principle in an fMRI study using a novel sequential decision making task. In the
task participants had to plan ahead to earn points by accepting offers while managing a limited
energy budget. Importantly, we designed the task such that situations with different levels of the
demand for planning occurred. With 448 possible combinations of task features and four different
offers participants could choose from, our task was quite complex. We therefore assumed that
participants used a simplified representation of planning value during control allocation decisions. An
initial analysis of choice frequencies showed that participants used a repetitive choice pattern for
two of the options, while responses were more balanced for the two other offers. From these choice
patterns, we hypothesized that participants generated two different groups of offer-dependent
representations of planning value. We refer to these two groups as control contexts (or short
context), with one context coding for a high a priori need for planning and the other context coding
for a low a priori need for planning. To further test the control context hypothesis, we analysed
response times and fMRI data using a specific conflict measure as a proxy for the value of forward
planning. We found that correlations of conflict with response time and with BOLD-activity in the
dACC were dependent on the context. Our results provide evidence for a mechanism by which the
brain harnesses regularities in the value of planning across tasks space to construct control contexts
that facilitate efficient allocation of control in complex tasks.

Methods

Participants

Forty participants took part in the experiment (22 women, mean age = 24.4, SD = 4.6).
Reimbursement was a fixed amount of 14€ or class credit plus a performance-dependent bonus
(mean bonus = 6.62€, SD = 0.39). The bonus was calculated as a linear function of the accumulated
points in the experiment. The study was approved by the Institutional Review Board of the
Technische Universität Dresden and conducted in accordance to ethical standards of the Declaration
of Helsinki. All participants were informed about the purpose and the procedure of the study and
gave written informed consent prior to the experiment. All participants had normal or corrected-to-
normal vision.

Experimental task

To investigate the context dependence of people's propensity to plan ahead, we designed a novel
open-ended sequential decision task in which participants had to accumulate as many points as
possible. We induced a necessity for planning by introducing a limited but replenishable energy
resource, which was required to accept offers. Planning was further encouraged by introducing
variation around the energy cost of accepting and by explicitly informing participants about how
these costs would change in the future. Unlike in experiments with a fixed deadline (Economides et
al., 2014; Ott et al., 2020; Schwartenbeck et al., 2015), the open-ended nature of the task provided
for every trial an opportunity to plan ahead multiple steps into the future. Importantly, the task

featured both situations in which planning was crucial to decide between the accept and reject
option, as well as situations that could be sufficiently solved by a simple heuristic.

In detail, the temporal structure of the task comprised three levels, the single trial, the current
segment, and the segment pair of the current and next segment. One segment consisted of four
trials. In a single trial, participants could either accept or reject an offer (selected by either a left or
right button press), where accepting the offer increased points by an indicated amount but decreases
energy by one or two units, depending on condition, see below. Rejecting always increased energy by
one. There were four equally probable offers, displayed as one, two, three or four trophies in the
middle of the screen. Accepting an offer increased points by the respective number of trophies,
thereby advancing the yellow point bar at the top of the screen (Fig 1A). The energy costs of
accepting varied between one, in low-cost segments (LC), and two in high-cost segments (HC). The
energy budget with a minimum of zero and a maximum of six was displayed as a blue bar at the
bottom of the screen. Initial energy in the first trial of the experiment was three. If participants had
maximum energy and chose to reject, no further energy was added, and the next trial started. If
participants accepted an offer with too little energy, no points were awarded, a warning was
displayed, and the next trial started. Participants were informed about the energy cost of the current
and the future segment by two symbols in the bottom right corner. The left symbol informed about
both the energy cost of the current segment and the current trial number in the segment. The right
symbol informed about the energy cost of the future segment. One flash indicated a low-cost
segment and two flashes a high-cost segment (Fig 1A).

Figure 1. Experimental Task. (A) Timeline of a single trial. Participants could accept an offer ($O = \{1,2,3,4\}$) displayed in the
middle of the screen to collect points (top yellow bar). Accepting an offer was associated with an energy cost. The current
energy cost within a 4-trial-segment was indicated by the left symbol on the bottom right of the screen. One flash indicates
an energy cost of 1 and two flashes an energy cost of 2. The right symbol on the bottom right indicates the energy cost of
the next segment. Participants could choose the reject option to replenish the energy budget (bottom blue bar) by 1. **(B)**
Temporal structure of the task: Four single trials formed a segment. Two consecutive segments formed a segment pair. **(C)**
A segment could feature one of two different energy costs, low energy costs (LC) or high energy costs (HC). There were four
different segment transitions LC/LC, LC/HC, HC/LC and HC/HC.

The experiment included a training session outside the MRI scanner (for task instructions see S1 Text) and three sessions inside. The training session comprised 144 trials across 36 segments with nine repetitions for each of the four possible transitions (Fig. 1C). The fMRI experiment comprised 240 trials across 60 segments with 15 repetitions per segment transition. On average, participants took 40 minutes to complete the fMRI experiment. The fMRI experiment was split into three sessions between which participants rested for two to three minutes without leaving the scanner. The sequence of segments and offers was pseudorandomized and identical for all participants. Segment sequences were generated such that each of the four segment transitions (Fig 1C) was sampled equally often. Similarly, offer sequences were generated such that the frequency of offers was balanced within segment transitions (raw behavioral data with all details about the offer sequences can be found at https://doi.org/10.5281/zenodo.5112965).

The timing of stimulus events in the fMRI experiment was as follows (see also Fig. 1A): each trial started with a fixation cross (0.5 seconds) in the middle of the screen to prepare participants for the upcoming decision. In the response phase, the offer appeared, and the choice options were surrounded by a frame to indicate that a decision is required. If participants did not respond within 5 seconds, they were timed out with a warning message, and the next trial began. In the selection phase (1-5 seconds, uniformly sampled and rounded to first decimal), the frame surrounding the unchosen option disappeared. In the feedback phase (1 second, fixed), energy or point changes were displayed, and the frame surrounding the chosen option turned green (or accordingly red if the energy budget was too low for accepting). In the intertrial interval (2-5 seconds, uniformly sampled and rounded to first decimal) choice options were unframed and the offer disappeared (Fig 1A). The training version of the stimulus was identical to the fMRI version except that there was no timeout for the response phase, there was not a selection phase and the intertrial interval was fixed to 1 second.

Computational model of choice behaviour

We considered three different computational-cognitive models of how participants select their responses. Firstly, following one standard assumption about participants' behaviour in such sequential decision making tasks, participants may have used forward planning across the current and the next segment ('planning strategy') to estimate the expected value of either accepting or rejecting (e.g. Kolling et al., 2014; Schwartenbeck et al., 2015). Secondly, in contrast, participants may have used some sort of heuristic to reduce the number of computations involved. An obvious choice for such a heuristic is the simple strategy to just base the accept/reject decision on the offer value ('simple strategy'). For example, participants may simply always reject the lower offer values 1 and 2, and always accept offer values 3 and 4, provided there was enough energy left to accept the offer. Thirdly, we also considered a hybrid strategy of these two extremes, where participants may choose to use forward planning only for specific offers but otherwise rely on a simple strategy ('hybrid strategy').

Planning strategy model (PM). Clearly, if participants used a greedy strategy of accepting all offers in the first few trials of the task, they will quickly run out of energy and might not be able to accept better offers in future trials. Therefore, to maximize the accumulated points, one has to plan ahead, anticipating future actions, energy costs and reward opportunities. To implement such a planning strategy, we assumed a finite horizon until the end of the next future segment since participants were only explicitly informed about the energy costs of the current and the next future segment. As each segment had four trials each, this resulted in a horizon of maximally 8 trials and minimally 5 trials, i.e. when a participant has to select the decision for the fourth trial of the current segment. To derive a policy that maximizes expected reward over this horizon we formalised our task as a Markov Decision Process (MDP) (Puterman, 2014; Sutton et al., 2018). We define

$$MDP = (T, S, A, p_t(s'|s,a), r_t(s,a)) \tag{1}$$

where $T = \{1, 2, \ldots, 8\}$ is the set of trials and $S = E \times O$ is the set of states with $E = \{0, 1, \ldots, 6\}$ the set of possible energy levels and $O = \{1, 2, 3, 4\}$ the set of offer values. $A = \{accept, reject\}$ is the set of actions.

Since participants successfully completed a training session and received detailed task instructions (S1 Text) prior to the main experiment, we assume that participants understood the rules of the task. In the model, this knowledge is represented by the transition probability $p_t(s' = (e', o')|s = (e, o), a)$, which is the probability to transition to a new state s' given the current state s (consisting of the offer value o and the current energy e) and the selected action a. Probabilities for allowed state transitions satisfy

$$p_t(e' = e - cc, o'|e, o, a = accept) = p(o), \quad e > cc, for\ all\ t \le 4$$
$$p_t(e' = 0, o'|e, o, a = accept) = p(o), \quad e < cc, for\ all\ t \le 4$$
$$p_t(e' = e - fc, o'|e, o, a = accept) = p(o), \quad e > fc, for\ all\ t > 4$$
$$p_t(e' = 0, o'|e, o, a = accept) = p(o), \quad e < fc, for\ all\ t > 4$$
$$p_t(e' = e + 1, o'|e, o, a = reject) = p(o), \quad e < 6, for\ all\ t$$
$$p_t(e' = e, o'|e, o, a = reject) = p(o), \quad e = 6, for\ all\ t \tag{2}$$

where $p(o)$ is the discrete uniform distribution over the possible offer values, cc is the energy cost in the current segment (1 or 2) and fc is the energy cost in the future segment (1 or 2). We model the different segment transitions $LC \to LC, HC \to LC, LC \to HC\ and\ HC \to HC$ as separate MDPs, substituting the respective values for cc and fc.

Immediate rewards, corresponding to the offer value, are generated upon successful acceptance. Formally, the reward function satisfies

$$r_t(s = (e, o), a = accept) = o, \quad if\ e \ge cc, for\ all\ t \le 4$$
$$r_t(s = (e, o), a = accept) = 0, \quad if\ e < cc, for\ all\ t \le 4$$
$$r_t(s = (e, o), a = accept) = o, \quad if\ e \ge fc, for\ all\ t > 4$$
$$r_t(s = (e, o), a = accept) = 0, \quad if\ e < fc, for\ all\ t > 4$$
$$r_t(s = (e, o), a = reject) = 0, \quad for\ all\ t \tag{3}$$

To determine the optimal policy that maximizes the expected reward over the current and future segment, the PM uses backward induction. The algorithm was implemented as follows :

1. Set $t = 9$ (if in the first trial of the segment) and define the state values after the decision in the final trial. To ensure that energy units left over after the eighth trial are considered to have utility, each remaining energy unit was multiplied by the quotient of the average offer value divided by the average energy costs.

$$V_{t=9}(s) = \frac{2.5}{1.5}e = 1.\bar{6}\,e \quad for\ all\ s_{t=9} \in S \tag{4}$$

2. Set $t = t - 1$ and compute state-action values

$$Q_t(s, a) = r_t(s, a) + \sum_{s' \in S} p_t(s'|s, a)V_{t+1}(s') \tag{5}$$

3. Update state values

$$V_t(s) = \underset{a}{argmax}(Q_t(s, a)) \tag{6}$$

189   **4.** If t = 1 stop. Otherwise, continue with step 2

190 Action selection in the PM relies on a decision variable (DV) computed as the difference between the
191 optimal state-action values

$$DV_{plan} = Q_t(s, a = accept) - Q_t(s, a = reject) \tag{7}$$

192 For a given state, positive values of DV indicate a greater long-term expected reward for accepting
193 and negative values of DV indicate greater long-term expected reward for rejecting.

194 Using a logistic regression approach, we define the probability to accept as

$$p(accept) = \frac{1}{1 + e^{-\eta}} \tag{8}$$

195 where

$$\eta = \beta_{plan}\, DV_{plan} + \theta_{basic}\, I_{basic} + \theta_{maxE}\, I_{maxE} + \theta_{minE\_LC}\, I_{minE\_LC} + \theta_{minE\_HC}\, I_{minE\_HC} \tag{9}$$

The planning weight β_{plan} captures the influence of DV_{plan} on choice behaviour. To allow for
systematic deviations from behaviour prescribed by DV_{plan}, we also included preference parameters
θ. These preference parameters simply model a participant's tendency to generally choose the
accept (or the reject option). The parameter θ_{basic} captures the preference in trials where
participants had enough energy to accept and did not reach the maximum energy level (termed basic
trials). We implemented this with a binary indicator variable I_{basic} that equals one if the current trial
was basic and zero if not. To model behaviour in trials with maximum or insufficient energy, we also
included three bias parameters θ_{maxE}, θ_{minE_HC} and θ_{minE_LC}. The first of these bias parameters
θ_{maxE} models the special case when participants had to choose on a trial with full energy. We expect
this bias parameter to be generally positive because a further reject choice would not increase the
energy further. For the other two bias parameters θ_{minE_HC} and θ_{minE_LC} we expect these to be
generally negative, i.e. participants will reject an offer if they have insufficient energy. Subsets of
these low- and max-energy trials are again selected by an appropriate binary indicator variable.

Simple strategy model (SM). Since forward planning or other elaborate anticipatory schemes might
incur considerable computational costs, participants may use a simple strategy, where action
selection is only based on offer value. We define the decision variable for the SM as offer value
centred across the four offer values 1 to 4:

$$DV_{simple} = o - 2.5 \tag{10}$$

213 The probability to accept is defined in the same way as for the PM

$$p(accept) = \frac{1}{1 + e^{-\eta}} \tag{11}$$

214 where

$$\eta = \beta_{simple}\, DV_{simple}\, I_{basic} + \theta_{basic}\, I_{basic} + \theta_{maxE}\, I_{maxE} + \theta_{minE\_LC}\, I_{minE\_LC} \\ + \theta_{minE\_HC}\, I_{minE\_HC} \tag{12}$$

Here, the parameter β_{simple} captures the influence of offer value on choice behaviour.

Hybrid strategy model (HM). To cover the case that participants may choose based on both, expected
long-term values and offer specific preferences, we use a hybrid strategy as a mixture of both
planning and simple strategy. Such a hybrid strategy enables the decision maker to still use forward

planning but mix this decision tendency with a simple strategy for each of the four offers. Like in the
PM, DV_{plan} is defined as the difference between the optimal state-action values

$$DV_{plan} = Q_t(s, a = accept) - Q_t(s, a = reject) \tag{13}$$

221   The probability to accept is defined as

$$p(accept) = \frac{1}{1 + e^{-\eta}} \tag{14}$$

222   Where now

$$\eta = \beta_{plan} DV_{plan} + \theta_{O1} I_{O1} + \theta_{O2} I_{O2} + \theta_{O3} I_{O3} + \theta_{O4} I_{O4} + \theta_{maxE} I_{maxE} \\ + \theta_{minE\_LC} I_{minE\_LC} + \theta_{minE\_HC} I_{minE\_HC} \tag{15}$$

In addition to the planning weight β_{plan} and the three bias parameters for extreme energy cases, the
HM adds, as compared to the PM, four offer-specific preference parameters ($\theta_{O1}, \theta_{O2}, \theta_{O3}, \theta_{O4}$). The
indicator variables ($I_{O1}, I_{O2}, I_{O3}, I_{O4}$) equal one if a specific offer was presented for basic trials (i.e.
energy was neither at maximum nor too low to accept). In other words, in contrast to the PM, the
four offer-specific bias parameters will indicate a relative dependence on the simple strategy. For
example, a negative offer-specific parameter will indicate a participants' preference to reject that
specific offer.

Model fitting and evaluation

Model fitting. Using a hierarchical Bayesian approach, we jointly estimated both participant- and
group-level parameters. For the PM and the SM, β and θ_{basic} were allowed to vary by participant.
For the HM β_{plan}, θ_{O1}, θ_{O2}, θ_{O3} and θ_{O4} were allowed to vary by participant. The parameters
θ_{minE_LC}, θ_{minE_HC} and θ_{maxE} were modelled as constant over participant. The participant
parameters were drawn from a normal distribution with respective group parameters μ and σ. These
group parameters were themselves modelled as draws from a weakly informative hyperprior
distribution: $\mu \sim Normal(0,2)$ and $\sigma \sim HalfNormal(0,2)$. A complete description of the models as
Stan code can be found online (https://doi.org/10.5281/zenodo.5112965). We fitted models using
Hamiltonian Markov Chain Monte Carlo as implemented in Stan (Carpenter et al., 2017) via the
PyStan interface (Stan Development Team, 2018, Version 2.19.1.1). We obtained 4,000 samples from
four chains of length 2,000 (1,000 warmup) from the posterior distribution over model parameters.
The potential scale reduction factor on split chains $\hat{R}$ was calculated (Gelman et al., 1992), indicating
convergence for all parameters ($\hat{R} \approx 1$).

Model comparison. We compared the predictive accuracy of the PM, SM and HM using leave-one-out
cross-validation approximated by Pareto-smoothed importance sampling (PSIS-LOO) (Vehtari et al.,
2017) as implemented in the python package ArViz (Kumar et al., 2019, Version 0.9.0). We obtained
the expected log pointwise predictive density (elpd) and its standard error on the deviance scale (-2*
elpd) and refer to this quantity as leave-one-out cross-validation information criterion (LOOIC).
Lower values of LOOIC indicate better model fit.

Posterior predictions. To further assess whether the best fitting HM captures the observed
behavioural pattern, we conducted posterior predictive checks using mixed predictive replication for
hierarchical models (Gelman et al., 1996). To compute predictive replications we first sampled the
group parameters (μ and σ) from the posterior and then sampled forty normally distributed
participant-level parameters from these group parameters. Replicated accept-reject responses were
generated for replicated participants and all trials by sampling from a Bernoulli distribution
$response\_rep \sim B(p)$, where p is the response probability as defined in equations 11 and 12. The

resulting array of replicated responses is of size $M = n_{samples} \times n_{participnts} \times n_{trials}$. Individual
dots in Figure 2A indicate choice proportions for 40 replicated participants averaged over 100
posterior samples. Bars represent averages over replicated participants and 100 samples, with error
bars indicating between participant standard deviation.

Parameter recovery. To ensure that our model parameters are identifiable, we performed a
parameter recovery analysis with the most complex model HM. We first generated simulated data
using posterior means of the participant level parameters β_{plan}, θ_{O1}, θ_{O2}, θ_{O3} and θ_{O4} and group
level parameters θ_{minE_LC}, θ_{minE_HC} and θ_{maxE}. Next, we refitted the model to the simulated data
and compared the estimated parameters to the known data-generating parameters. We considered
a known parameter recovered if its value was within the 95% posterior credibility interval (CI) of the
re-estimated parameter. Results showed that both, participant level parameters (>99%) and all group
level parameters, including those for β_{plan}, θ_{O1}, θ_{O2}, θ_{O3} and θ_{O4} could be reliably recovered from
the simulated data (for details see Jupyter Notebook at https://doi.org/10.5281/zenodo.5112965).

Agent simulations. For comparison with participants' measured performance, we computed the
performances of a PM, SM and HM agent. Each agent played through the 240 trials of the task,
receiving the same offers as the participants and the same initial energy of three. Each agent was
simulated 200 times and mean and standard deviation of the total accumulated points were
computed. In basic trials, agents selected responses probabilistically according to equations 8-9 (PM),
equations 11-12 (SM) and equations 14-15 (HM). The β and θ parameters were set to the mean
posterior of the inferred group level parameters. For the boundary energy trials, instead of using the
bias parameters θ_{minE_LC}, θ_{minE_HC} and θ_{maxE}, we equipped all agents with a fixed decision rule,
such that an agent always accepted if it had maximum energy and always rejected if energy was too
low. We also tested a random agent that selects actions randomly in basic trials (with a probability of
0.5 for accept) and uses the fixed decision rule for boundary energy trials. We further simulated a
deterministic version of the PM with $\beta_{plan} \to \infty$ and $\theta_{basic} = 0$. Independent two-sample t-tests
were used to compare the agents' performances.

Conflict and response time analysis
284 A key quantity for our analysis of response times (RT) and fMRI data was conflict.

$$conflict = -|Q_t(s, a = accept) - Q_t(s, a = reject)| = -|DV_{plan}| \qquad (16)$$

This corresponds to the similarity between long-term values for accepting and rejecting (see
equation 7). If, for a given trial and task state, the action-value difference is small, conflict is large.
Conversely, if the action-value difference is large, conflict is small. We consider conflict as a signal of
choice difficulty, reflecting the need for elaborate information processing such as planning. We
assume that participants do not calculate the conflict directly (which would require planning by
itself), but that they have quick and frugal access to a proxy for the conflict (Lee et al., 2021).

We analysed response times using hierarchical Bayesian linear regression estimating group- and
participant-level parameters simultaneously. We modelled log RT as the linear function

$$\log RT = \beta_0 + \beta_{conflict}C + \beta_{type}I + \beta_{interaction}CI \qquad (17)$$

where C is conflict (Eq. 16), I is a binary indicator variable that equals one if the current offer was 2
or 3 (which we call in the following intermediate) and zero if the current offer is 1 or 4 (which we call
in the following extreme). This classification into intermediate and extreme offers was based on
participants' choice behaviour (Fig. 2A). CI models the interaction between offer type and conflict.
The participant-level intercept β_0 and parameters $\beta_{conflict}$, β_{type} and $\beta_{interaction}$ were normally

distributed with group parameters μ and σ. We gave these group parameters a weakly informative
hyperprior: $\mu \sim Normal(0,10)$ and $\sigma \sim Half\,Normal(0,10)$. Models were fit in Stan via PyStan using
Hamiltonian Markov Chain Monte Carlo. We obtained 2,000 posterior samples from four chains of
length 1,000 (500 warmup). The potential scale reduction factor on split chains $\hat{R}$ was calculated,
indicating convergence for all parameters ($\hat{R} \approx 1$). We generated linear predictions of log RT using
2,000 posterior samples of the group hyper parameters ($\mu_0, \mu_{conflict}, \mu_{type}, \mu_{interaction}$) and
exponentiated back to the original RT scale for better interpretability. The regression lines in Figure
3C correspond to the median across samples and shaded areas to the 95% interval. All trials that
were not timed out (RT > 5s) were included in the analysis.

fMRI acquisition and preprocessing

fMRI data were acquired on a 3 T MRI scanner (Siemens Magnetom Trio Tim, Siemens Medical
Solutions, Erlangen, Germany) using a 32 channel head coil. On average, per participant, 942 volumes
were acquired across three sessions, using a T2*-weighted echo-planar sequence (TR=2360 ms,
TE=25 ms, flip angle=80°, FoV=192 mm). For each image, 48 axial slices of 2.5 mm were sampled in
descending order. Field maps were acquired after each functional session (TR=532 ms, short TE=5.32
ms, long TE=7.78 ms). Structural data were acquired using a T1-weighted MPRAGE sequence (TR =
2400 ms, TE=2.19 ms, flip angle=8°, FoV=272 mm).

fMRI data were preprocessed and analysed using SPM12 (Wellcome Trust Centre for Neuroimaging,
London, UK). Functional images were unwarped using individual field maps generated by SPM's field
map toolbox (Hutton et al., 2002), slice time corrected, realigned to the first image of the session,
spatially normalized to the MNI template using the unified segmentation approach (Ashburner et al.,
2005) and smoothed with an 8mm full-width at half-max (FWHM) Gaussian kernel.

fMRI Analysis

For each participant we specified and estimated a general linear model (GLM). Motivated by our
behavioural results, we included one event regressor with response phase (see Fig. 1A) onsets for
intermediate (2 and 3) offers and one event regressor with response phase onsets for extreme (1 and
4) offers. For each of these two event regressors, we included a parametrically modulated regressor
with trial-wise conflict values. Additional regressors of no interest were included: an event regressor
with response phase onsets for extreme energy trials (either maximum or insufficient energy) and an
event regressor with response phase onsets of accept choices (to control for the effect of action).
Onsets were modelled as stick function with duration 0. Regressors were convolved with the
canonical HRF. We also included the 6 movement parameter vectors as nuisance regressors. Images
of all three sessions were analysed together and a constant for each session was included in the
design matrix. For each participant the following first level contrasts were computed: intermediate >
extreme, extreme > intermediate, conflict_intermediate > conflict_extreme and a parametric effect
of conflict averaged across intermediate and extreme trials. Finally, we performed one-sample t-tests
on the contrast images of all participants to assess statistical significance on the group-level.
Statistical parametric maps were initially thresholded with $p = 0.001$ (see Tables S2-S5). Voxels with a
family-wise-error corrected p-value < 0.05 were considered significant.

dACC and dorsolateral prefrontal cortex (dlPFC) are commonly associated with conflict processing (E.
K. Miller et al., 2001). Therefore, we defined a priori regions of interest (ROI), which we used for
small volume correction (SVC). ROIs were defined using the WFU-Pickatlas software (Maldjian et al.,
2003) with a dilation factor of 1. The ROI for the dACC encompassed dorsal Brodmann area (BA) 32,
clipped at z = 18 in MNI-space (S1 Fig). The ROI for the dlPFC encompassed BA46 and BA9. Generated
masks are available at https://doi.org/10.5281/zenodo.5112965.

Results

Behavioural results

Choice behaviour. We first analysed choice behaviour across offer values in basic trials (i.e. excluding trials where energy was at max or too low to accept) and found that participants accepted offer 1 only in a few trials (mean = 1%, SD = 2%) and conversely accepted offer 4 in the majority of trials (mean = 98%, SD = 3%) (Fig 2A). Choice behaviour was more balanced between accepting and rejecting for offer 2 (mean = 14%, SD = 12%) and 3 (mean = 77%, SD = 13%). To further quantify the balance between accepting and rejecting, we computed the distance between choice frequencies and the 50% chance level and compared these distances across offer values. Distances from chance level were larger for offer 1 and 4 compared to offer 2 and 3 (pairwise Wilcoxon signed-rank tests, p < 0.001). There was no significant difference between offer 1 and offer 4 (Wilcoxon signed-rank test, p = 0.094). We also found that the distance from chance level was greater for offer 2 than for offer 3 (Wilcoxon signed-rank test, p < 0.001).

From this pattern, we hypothesised that participants might have categorised the choice given an extreme offer 1 or 4 as generally easy and the choice given an intermediate offer 2 or 3 as generally hard. We hypothesized that this categorisation into what we call control contexts predetermines the actual planning investment in a given trial. In the following we will test this hypothesis and provide further insights using model-based analysis of choice behaviour, analysis of response times and analysis of fMRI BOLD-signals.

In addition to the offer value, we found, using logistic regression, that participants' choice behaviour was also influenced by other task features (S1 Table). Participants chose more often the accept option if they had more energy units and likewise if the current energy cost of accepting was low (current segment = LC). Participants chose more often the accept option if the upcoming energy cost was high (future segment = HC), showing that participants considered information about the future segment when making a decision.

Figure 2. Choice behaviour and modelling results. (A) Plot of accept choices across offer values for participants and posterior predictions for the best fitting Hybrid model. Bars represent the mean acceptance frequency across participants or across simulated participants under the Hybrid model. Error bars represent standard deviation (SD). Dots represent individual participant data. The dotted line represents 50% chance level. **(B)** Model comparison: Planning strategy model (PM), simple strategy model (SM) and hybrid strategy model (HM). Error bars represent standard errors (SE) of the LOOIC. The asterisk indicates the winning model. **(C)** Estimated parameters of the winning hybrid strategy model. Large black dots represent posterior means of group parameters with error bars depicting 95% credibility intervals. Grey curves represent kernel density estimates for the posterior distributions of group parameters. Semi-transparent small dots represent posterior means of participant-level parameter estimates.

A combination of forward planning and simple offer specific preferences fitted behaviour best.
We considered three different strategies of how participants select their responses. First,
participants may have fully relied on forward planning across the current and the next segment to
select actions that maximize the expected value (PM). Second, participants may have used a simple
strategy just dependent on the offer value (SM). To illustrate the difference between these two
strategies, let us consider a (for convenience deterministic) agent in the first trial of a segment, with
three energy units, where the current and the future energy cost is 2 (segment pair HC/HC) and offer
3 is presented. A planning agent would reject the offer and replenish its energy reserves in order to
be able to accept potential better offers in the future. In contrast, an agent following a simple
strategy, e.g. who always accepts offers 3 and 4 and rejects offer 1 and 2, would accept the offer 3.
We also considered a third alternative that participants use a mixture between planning and a simple
strategy (HM) to achieve a good trade-off between the benefits and costs of the respective strategies
depending on the current task situation.

We compared how well the three cognitive computational models fitted participants' behaviour
using leave-one-out cross validation. We found, as shown in Figure 2B, that the HM explained
participant behaviour substantially better (LOOIC = 3622.5, SE = 108) than the PM (LOOIC = 5006, SE
= 117.5) and the SM (LOOIC = 4613.2, SE = 109.4). We also simulated posterior predictions from the
winning HM and plotted acceptance frequencies across offer values, showing that the model closely
captures the behavioural pattern of participants (Fig 2A).

Parameter estimates of the HM demonstrate both evidence for forward planning and usage of a
simple strategy as quantified by four offers-specific preferences (Fig 2C). We found a positive weight
on the planned value difference (mean group parameter β_{plan} = 1.79, 95% CI = [1.45, 2.15]). This
indicates that participants, when making a decision, accounted for its future consequences. We also
found preference parameters different from zero for all four offers. For offer one (mean group
parameter θ_{O1} = -3.39, 95% CI = [-4.76, -2.37]) and offer two (mean group parameter θ_{O2} = -0.96,
95% CI = [-1.47, -0.47]), participants showed a preference for rejecting (indicated by negative
parameter values). For offer three (mean group parameter θ_{O3} = 1.77, 95% CI = [1.43, 2.11]) and
offer four (mean group parameter θ_{O4} = 3.56, 95% CI = [2.97, 4.28]), participants showed a
preference for accepting (indicated by positive parameter values). We explicitly modelled special
cases, where participants had either maximum energy (θ_{maxE}) or not enough energy to accept
(θ_{minE_LC} and θ_{minE_HC}), see also Methods. As expected, participants showed a bias to accept in
maximum energy trials and a bias to reject in low energy trials (see Fig 2C).

Critically, we found evidence that participants who account for the long-term consequences of their
actions by e.g. planning, earn more points. Post-hoc correlation analysis revealed that participants
with a larger fitted planning parameter β_{plan} of the winning hybrid model accumulated more points
throughout the experiment (r = 0.521, p = 0.001, Fig *Figure* **3**A) and had slower average response
times (r = 0.374, p = 0.017, Fig Figure **3**B).

We also simulated planning, simple and hybrid agents using posterior means of the estimated group parameters (see methods) and compared their performances (accumulated points). While the performance of the planning agent (mean = 332.9, SD = 4.4) was not significantly different from the simple agent (mean = 332.1, SD = 5.1), t = -1.7, p = 0.09, the performance of the hybrid agent (mean = 340.8, SD = 4.4) was significantly higher than the performances of these two agents (t-tests, p < 0.001). Participants' performance (mean = 335.8, SD = 6.9) was higher than that of the planning and simple agent but lower than that of the hybrid agent (t-tests, p < 0.001). Note that, in principle, the planning strategy would be superior to the hybrid strategy if the β_{plan} parameter is very high. A deterministic planning agent ($\beta_{plan} \to \infty$ and $\theta_{basic} = 0$) achieves 445 points, but participants implementing such a high β_{plan} would be required to plan ahead precisely in each trial. With a hybrid strategy, participants can compensate for a moderate degree of planning by using simple offer-specific preferences. Our model-based analysis provided evidence that the subjects prefer a hybrid strategy when playing the task. One reason for the difference between the participants' performance and that of the hybrid agent could be occasional lapses by the participants. We also simulated a random agent that was clearly inferior to all agents and the participants (mean = 247.6, SD = 7.9).

Greater conflict-driven increase of response times in intermediate than extreme trials.
To test how control contexts influence the way participants evaluate the need for control to license cognitive resources for planning, we analysed the relationship between conflict and response times. We expected that larger conflicts generally lead to increased response times, but that this increase is particularly pronounced for offers 2 and 3. Bayesian linear regression indeed showed that conflict was significantly more predictive for log RT for the intermediate offers 2 and 3 compared to the extreme offers 1 and 4 (group parameter $\beta_{interaction}$ = 0.04, 95% CI = [0.02 0.07]). We also found a significant positive main effect of conflict (group parameter $\beta_{conflict}$ = 0.08, 95% CI = [0.05 0.11]) and offer type (group parameter $\beta_{is\_intermediate}$ = 0.18, 95% CI = [0.14 0.23]) on log RT. Figure 3C shows fitted regression lines on the untransformed RT scale.

FMRI results
A frontal network is more activated in intermediate than extreme trials.
We next tested where brain activity was higher during intermediate compared to extreme offers (Intermediate > Extreme) expecting to see greater activity in frontal areas related to planning and cognitive control (E. K. Miller et al., 2001). We indeed found significantly greater activity in dACC and right dlPFC (Fig 4A, Table 1, and S1 Table).

Figure 4. Different activation of dACC for intermediate versus extreme offers (A) dACC and right dlPFC were significantly more activated during intermediate compared to extreme offers. **(B)** Bilateral PPC was significantly more activated during extreme compared to intermediate offers. Activations displayed at p < 0.001 uncorrected. See Table 1 for peak MNI-coordinates and statistics, significant at p<0.05 FWE corrected.

Table 1. Summary of fMRI Results

Region	t	FWE p value		MNI coordinates		
		whole brain	SVC	x	y	z
Intermediate > Extreme						
dACC	7.26	< 0.001	< 0.001	-4	16	52
dlPFC R	5.12	0.180	0.018	52	34	24
Occipital L	6.98	< 0.001		-18	-92	-10
Occipital R	6.38	0.007		20	-84	-8
Extreme > Intermediate						
PPC (BA 40) L	6.68	0.003		-60	-44	38
PPC (BA 40) R	5.49	0.072		64	-32	28
Conflict						
dACC	4.82	0.290	0.007	10	24	44
anterior Insula L	5.62	0.041		-30	24	-2
anterior Insula R	6.50	0.004		38	20	0
Conflict: Intermediate > Extreme						
dACC	4.32	0.744	0.030	8	2	40
posterior MTG R	5.69	0.040		56	-64	6

Regions significant (p < 0.05 FWE corrected) at the whole brain level or small volume correction (SVC) based on a priori regions of interest. Only clusters with more than 10 voxels were reported. BA, Brodmann area; L, left; R, right; dACC, dorsal anterior cingulate cortex; dlPFC, dorsolateral prefrontal cortex; Occipital, occipital lobe; VS, ventral Striatum; PPC, posterior parietal cortex; MTG, middle temporal gyrus.

We also tested where brain activity was greater during extreme versus intermediate trials (Extreme > Immediate) and found increased activity in bilateral posterior parietal cortex, where the cluster in the left hemisphere was significant at the whole brain corrected level (PPC; Fig 4B, Table 1 and S3 Table). Besides its role in sensory attenuation, posterior parietal cortex is also involved in sensorimotor transformations during decision making (Andersen et al., 2009). This suggests that participant decisions for extreme offers might be related to low-level sensorimotor processes, coupling simple stimulus cues to actions. A network including left ventral Striatum (VS), posterior cingulate cortex (PCC) and bilateral Amygdala emerged at a lower threshold (see S3 Table). These regions have been shown to encode value information during reward-based choice (Bartra et al., 2013). Higher activation in these areas during extreme trials might indicate an increased salience of offer value information instigating a simple response strategy based on offers-specific preferences. However, this idea requires further research.

Context-dependent conflict processing in dACC.

One obvious reason for the effects in the categorical contrast Intermediate > Extreme could be that average conflict was higher in intermediate trials than in extreme trials (S2 Fig). Another possibility would be that the brain areas involved in processing conflict are modulated by the context. In other words, is conflict processed differently in the brain when the subject is in an intermediate compared to an extreme trial? Behavioural results in Fig. 3C indicate such a context-dependent mechanism, showing that reaction times increased more with conflict during intermediate than extreme trials. To test this context dependency using brain activity we included conflict as parametric modulator in our GLM, separately for intermediate and extreme offers.

We first looked at the effect of conflict averaged across conditions finding a significant positive correlation with BOLD-activity in the dACC (Fig 5A, Table 1 and S4 Table). Additionally, we found a significant positive effect of conflict in bilateral anterior Insula (Fig 5A, Table1 and S4 Table).

Figure 5. Effects of conflict. (A) BOLD-activity in dACC and bilateral anterior Insula (AI) correlated with conflict. **(B)** The
correlation of BOLD-activity in dACC with conflict was significantly increased during intermediate versus extreme offers.
Activations displayed at p < 0.001 uncorrected. See Table 1 for peak MNI-coordinates and statistics, significant at p<0.05
FWE corrected.

We next tested our hypothesis about the context-dependent processing of conflict using a contrast
between the parametric modulator of conflict for intermediate offers minus the parametric
modulator of conflict for extreme offers (Conflict Intermediate > Conflict Extreme). We found that
BOLD-activity in dACC and right posterior middle temporal gyrus (pMTG) was more strongly
correlated with conflict during intermediate offers compared to extreme offers (Fig 5D, Table 1 and
S5 Table). An effect in dlPFC emerged at a lower threshold (see S5 Table).

Discussion

We used a novel sequential task with a complex task space to investigate how people decide when to
plan ahead. We found evidence that participants use readily available features of the task space,
namely offer values, to construct contexts that condition the balancing between forward planning
and a simpler response strategy. We further provided evidence that the context-dependency of
planning might be mediated by context-dependent conflict processing involving dACC. Our study
provides initial evidence that the human ability to efficiently allocate cognitive control in complex
tasks is supported by category-based cognition that harnesses regularities in control demand to
generate control contexts.

Normatively, a decision about the engagement into elaborate planning should find the optimal trade-
off between the benefits and costs of such planning in a given situation (Shenhav et al., 2013). It is
however unlikely that people calculate the expected value of planning explicitly because this would
require planning itself. Previous studies have therefore argued that people must have quick and
automatic access to a proxy of the value of planning (Lee et al., 2021; Lieder et al., 2018). It is a
largely unresolved question how humans learn such proxies to decide about their engagement into
effortful planning. A hallmark of learning is that people generalize individual sensorimotor
experiences into broader categories allowing them to react adequately to novel instances of a
learned category (Konidaris, 2019; E. E. Smith et al., 1981; Tenenbaum et al., 2011; Yee, 2019).
Recent research suggests that the brain leverages similar generalisation mechanisms when deciding
about the allocation of cognitive control or when computing meta-control (Bhandari et al., 2017; M.
Botvinick et al., 2020; Lieder et al., 2018; Marković et al., 2020; Schwöbel et al., 2021). Here, we
tested this principle using a complex planning task, where the demand for planning changed
depending on the current situation as defined by a configuration of task features including offer
value, energy, current energy cost, future energy cost and trial within a segment.

Our results showed that from a rich set of task features people identified the most relevant feature
dimension, namely the offer values, to construct contexts that allowed them to decide efficiently
about the investment in effortful planning. In particular, we found that participants constructed two

contexts, one for the extreme offers 1 and 4, associated with a low prior tendency for planning, and
one for the intermediate offers 2 and 3 associated with a high prior tendency for planning. Three
pieces of converging evidence supported this conclusion: First, responses in an intermediate context
were more mixed between accepting and rejecting compared to an extreme context. Second, our
model-based analysis suggested that the mixed response profile for the intermediate offers can be
explained by participants planning ahead multiple steps into the future. Third, the findings that the
correlation of conflict with response times and dACC activity depended on the current context
further corroborated that participants had learned an offer-specific context structure.

To investigate the usage of forward planning or simple heuristics and its determining factors, we
designed a task where both types of decision making can occur. Our computational analysis indeed
revealed that a model including both, planning and simple offers-specific preferences, fitted
behaviour substantially better, than a model that relied on planning or a simple strategy alone. Our
model implemented planning as a search through a decision tree, calculating expected long-term
state-action values. However, due to the high computational cost of such an exhaustive search, it is
unlikely that participants planned in exactly this way. We therefore assumed that participants used
some sort of approximate planning, reducing planning complexity while still accommodating for an
action's future consequences. Pruning of decision trees (Huys et al., 2012), adjusting the planning
depth (Keramati et al., 2016) or the division of a decision problem into smaller subproblems (Huys et
al., 2015) are just some ways of how people can adjust planning complexity. While we cannot say
anything about the exact implementation of planning, we found that the fitted individual planning
weights of the winning hybrid model correlated with RT, suggesting that participants engaged in
some kind of forward planning.

Our finding that BOLD activity in the dACC correlated with conflict is consistent with the view that the
dACC monitors the need for effortful controlled processing (M. M. Botvinick et al., 2001; Shenhav et
al., 2013; Shenhav et al., 2017). In our task, when it was not clear at the beginning of a trial whether
accepting or rejecting is the best option (i.e. if the conflict was high), participants needed to generate
additional information by planning ahead which could then help to adjudicate between the two
options. While dACC might have played a central role in detecting the need for additional planning, a
distributed network including dlPFC and other structures might have been involved in the additional
information sampling. The finding that dlPFC was more active in the demanding intermediate context
is consistent with the view that dlPFC is central to planning (Fuster, 2015). In order for planning
processes to have an impact on the decision, it is often necessary to inhibit a prepotent response
first. We found evidence that such prepotent responses played a role in in our task as well, as our
model-based analysis revealed non-negative choice preference parameters for all offers. Previous
research suggests that such prepotent responses could have been inhibited by a hyper-direct
pathway from the ACC to the basal ganglia, effectively increasing time until movement generation
and thus allowing planning structures to influence decision making (Cavanagh et al., 2011; Gluth et
al., 2012; Wiecki & Frank, 2013; Wiecki, Sofer, et al., 2013).

The anterior insula (AI) is often coactivated with the ACC in classical cognitive control tasks (Duncan
et al., 2000) and sequential tasks alike (e.g. Schwartenbeck et al., 2015). Previous research suggests
that, besides of its role in interoception and general awareness (Craig et al., 2009), the AI appears to
be specifically involved in the representation and learning of uncertainty (Bossaerts, 2010; Loued-
Khenissi et al., 2020; Singer et al., 2009). Translated to our task, the AI could have relayed
information about uncertainty (or conflict) to the dACC, which then initiates adaptive behavioural
change in the form of planning.

We found that the correlation of activity in the dACC with conflict (which we take to be a proxy for
the value to plan ahead) depended on context. One possible explanation for this pattern could be
that the dACC has access to a hierarchical representation of learned conflicts, whereby conflicts
encoded at a finer level of task space are subsumed under conflicts encoded at the level of context.
In other words, states of similar difficulty could be grouped into a more general category that e.g.
simply indicates whether the decision is easy or difficult. In contexts with a high prior expectation of
conflict, i.e. in an intermediate context, the dACC could access conflict at a more fine-grained level to
enable the appropriate level of planning. Conversely, in a context with low prior expectation of
conflict, i.e. in an extreme context, the dACC would not access information beyond that at the coarse
context level, as the overall need for planning was low anyway. Speculating on the algorithmic
implementation of such a process, the context-dependent prior assumption about conflict could set
the threshold for the meta-decision problem of inferring the need of planning. In an intermediate
context, a high meta-threshold would grant enough time for a state-level readout of conflict,
whereas in an extreme context the need for planning would have been determined before state-level
conflicts were accessed. We also found evidence that right posterior middle temporal gyrus (pMTG)
is more correlated with conflict in an intermediate than in an extreme context. Previous research
implicated the pMTG in category-based cognition (Martin, 2007). It is therefore an intriguing
possibility that the pMTG is also capable of forming abstract categories of choice difficulty that
support the context-dependent evaluation of planning demands. Although we can only speculate
about the role of pMTG, the question how brain mechanism for structured knowledge acquisition
and cognitive control interact is an important direction for future research. Overall, our findings are
generally consistent with the view that people exploit the structure of a task for efficient storage and
access of the value of control (Lieder et al., 2018).

Data availability

595 Data and analysis code used in this article is publicly available at
596 https://doi.org/10.5281/zenodo.5112965. The repository includes: raw behavioural data and fMRI
597 statistical maps underlying Figures 4 and 5; source code for reproducing Figures 2, 3 and S2; source
598 code implementing the model fitting, validation and comparison procedures, and agent simulations.

Acknowledgements

600 The authors thank Florian Bolenz and Philipp T. Neukam for valuable comments and suggestions. This
601 work was funded by the German Research Foundation (DFG, Deutsche Forschungsgemeinschaft), SFB
602 940 - Project ID 178833530, and TRR 265 - Project ID 402170461.

Competing interests

604 No competing interests declared

Supplementary information

606 **S1 Table. Logistic regression of choice (accept = 1, reject = 0) against task features.**

	Estimate	SE	z-value	P(>|z|)	
Intercept	-12.53	0.33	-37.58	$< 10^{-20}$	***
Offer value	3.65	0.09	40.80	$< 10^{-20}$	***
Energy	0.63	0.04	15.30	$< 10^{-20}$	***
Current segment (LC=1 , HC=0)	2.38	0.11	22.55	$< 10^{-20}$	***
Future segment (LC=1, HC=0)	-0.24	0.09	-2.75	0.00593	**

Trial		-0.02	0.04	-0.57	0.56753		

607 Trials were pooled across participants (N = 40). Trials in which energy was at maximum or too low to accept any offer were
608 excluded.

609 **S2 Table. fMRI results for the contrast: intermediate > extreme**

	cluster size	t	FWE p value		MNI coordinates		
Region	(voxels)		whole brain	SVC	x	y	z
Dorsal anterior cingulate	929	7.26	<0.001	<0.001	-4	16	52
Occipital L	1252	6.98	<0.001		-18	-92	-10
Occipital R	1475	6.38	0.007		20	-84	-8
Dorsolateral prefrontal R	106	5.12	0.180	0.018	52	34	24
Superior parietal L	76	4.68	0.456		-28	-64	52
Putamen R	95	4.64	0.486		20	16	-4
Angular R	112	4.54	0.580		34	-70	44
Occipital L	92	4.51	0.602		-24	-84	14
Anterior Insula L	45	4.09	0.918		-26	18	0
Dorsolateral prefrontal L	30	4.06	0.935	0.223	-48	32	24
Precentral L	21	3.98	0.961		-36	-12	50
Inferior parietal R	50	3.97	0.964		36	-48	38
Superior frontal L	11	3.71	0.997		-24	40	-14
Precuneus R	128	3.69	0.998		6	-62	34

610 The table contains all clusters with more than 10 voxels that survived uncorrected statistical thresholding with p < 0.001.

611 **S3 Table. fMRI results for the contrast: extreme > intermediate**

	cluster size	t	FWE p value		MNI coordinates		
Region	(voxels)		whole brain	SVC	x	y	z
Posterior parietal L	483	6.68	0.003		-60	-44	38
Posterior parietal R	439	5.49	0.072		64	-32	28
Posterior cingulate	106	5.15	0.169		6	-6	36
Amygdala L	186	4.92	0.280		-24	-2	-18
Middle temporal L	391	4.90	0.296		-48	-64	6
Middle temporal R	237	4.86	0.323		48	-12	-12
Amygdala R	94	4.56	0.560		28	-2	-18
Ventral striatum	23	4.40	0.701		-4	22	-10
Middle temporal R	109	4.20	0.858		66	-48	10
Anterior cingulate	16	4.09	0.920		-4	32	4
Anterior Insula R	20	3.87	0.984		30	20	-16
Superior frontal R	17	3.71	0.997		10	48	26

612 The table contains all clusters with more than 10 voxels that survived uncorrected statistical thresholding with p < 0.001.

613 **S4 Table. fMRI results for parametric effect of conflict**

	cluster size	t	FWE p value		MNI coordinates		
Region	(voxels)		whole brain	SVC	x	y	z
Anterior Insula R	523	6.50	0.004		38	20	0
Anterior Insula L	600	5.62	0.041		-30	24	-2
Dorsal anterior cingulate	644	4.82	0.290	0.007	10	24	44
Thalamus R	40	4.29	0.718		8	-18	-12
Pallidum L	29	4.01	0.909		-12	0	-4
Supplementary Motor Area R	24	3.78	0.983		12	8	62

614 The table contains all clusters with more than 10 voxels that survived uncorrected statistical thresholding with p < 0.001.

615 **S5 Table. fMRI results for the contrast: conflict intermediate > conflict extreme**

	cluster size	t	FWE p value		MNI coordinates		
Region	(voxels)		whole brain	SVC	x	y	z
Middle temporal R	489	5.69	0.040		56	-64	6
Anterior Insula R	389	5.05	0.196		36	-8	18
posterior cingulate L	29	4.79	0.345		-16	-32	40
Occipital L	441	4.75	0.378		-48	-74	24
Precuneus R	117	4.54	0.551		10	-50	10
Dorsolateral prefrontal R	208	4.49	0.592	0.083	54	28	6
Angular R	50	4.41	0.667		38	-62	26
Precuneus R	50	4.36	0.712		12	-44	40
Dorsal anterior cingulate	105	4.32	0.744	0.03	8	2	40
Cuneus L	91	4.28	0.774		-10	-68	26
Superior temporal R	32	4.16	0.859		46	-42	22
Thalamus L	32	4.08	0.905		-6	-30	-2
Occipital L	35	4.03	0.929		-24	-86	38
Occipital L	26	3.93	0.966		-16	-48	0
Superior temporal R	19	3.90	0.971		44	-14	-10

Precentral R	117	3.83	0.984	40	-18	58
Superior temporal L	44	3.72	0.995	-54	-20	12
Thalamus R	20	3.72	0.995	8	-30	-2
Precuneus R	60	3.71	0.996	16	-60	26
Supplementary motor area R	21	3.69	0.997	4	-8	58
Middle temporal L	12	3.69	0.997	-62	-52	0

The table contains all clusters with more than 10 voxels that survived uncorrected statistical thresholding with p < 0.001.

S1 Figure. Definition of anatomical ROIs for small volume correction. dACC (green), dlPFC (yellow).

S2 Figure. Encountered conflict levels plotted for intermediate (2, 3) and extreme (1, 4) offers. Histograms contain data of all forty participants. Dashed lines indicate the mean.

S1 Text. Task instructions. Participants were guided step by step through the task on the computer screen. Written instructions were accompanied by an arrow pointing towards the stimulus element currently addressed. The written instructions were:

- Dear participant, the experiment is about collecting as many points as possible. Depending on your score at the end of the experiment, you will be paid a monetary bonus.
- The current score is indicated by the upper yellow bar.
- You can get points by accepting offers.
- The current offer is presented in the middle of the screen. The magnitude of offers varies between 1 and 4, represented by the number of golden trophies. The offers are drawn at random, having the same occurrence probability of 25%.
- However, accepting an offer is associated with energy costs. Your current energy level is represented by the lower blue bar. If you accept an offer and do not have enough energy, no points will be credited to you and the next trial will begin.

◆ You can replenish your energy account by selecting the "reject" option. This will increase
your energy level by 1 and the next trial will begin.
◆ The energy level can have a maximum value of 6.
◆ The experiment is divided into segments, each consisting of 4 trials. Two numbers are
displayed on the screen to indicate how far you are in the current segment.
◆ There are 2 different segment types, in which the energy costs for accepting an offer differ.
In segments with 1 flash, 1 energy unit is subtracted when you accept an offer. In segments
with 2 flashes, 2 energy units are subtracted when you accept an offer. The left blue-orange
box at the bottom right of the screen informs you about the type of the current segment.
◆ In addition to the type of the current segment, information about the energy costs in the
next segment is available. This can be seen in the right blue-orange box at the bottom right
of the screen.
◆ Breaks: During the main experiment in the scanner, you have the possibility to pause twice.
The pause screen is automatically displayed. You decide when you are ready to continue the
experiment. Note: After a pause your score will be reset to 0. This has no effect on your final
bonus. Your score is counted continuously.
◆ Deadline: You have a maximum of 5 seconds for each decision. If you exceed this time limit,
the next trial will begin without points being awarded.
◆ Training: Before the main experiment in the scanner starts, you will be given a few training
trials on the PC to familiarize yourself with the experiment. There is no deadline in the
training and the points gained here have no effect on the bonus paid out. Please try to get as
many points as possible anyway. The training phase will end automatically.

References

Andersen, R. A., & Cui, H. (2009). Intention, action planning, and decision making in parietal-frontal
circuits. *Neuron, 63*(5), 568-583.
Ashburner, J., & Friston, K. J. (2005). Unified segmentation. *Neuroimage, 26*(3), 839-851.
Bartra, O., McGuire, J. T., & Kable, J. W. (2013). The valuation system: a coordinate-based meta-
analysis of BOLD fMRI experiments examining neural correlates of subjective value.
Neuroimage, 76, 412-427.
Bhandari, A., Badre, D., & Frank, M. J. (2017). Learning cognitive control.
Bossaerts, P. (2010). Risk and risk prediction error signals in anterior insula. *Brain Structure and
Function, 214*(5-6), 645-653.
Botvinick, M., Wang, J. X., Dabney, W., Miller, K. J., & Kurth-Nelson, Z. (2020). Deep reinforcement
learning and its neuroscientific implications. *Neuron*.
Botvinick, M. M., Braver, T. S., Barch, D. M., Carter, C. S., & Cohen, J. D. (2001). Conflict monitoring
and cognitive control. *Psychological review, 108*(3), 624.
Botvinick, M. M., & Cohen, J. D. (2014). The computational and neural basis of cognitive control:
charted territory and new frontiers. *Cognitive science, 38*(6), 1249-1285.
Carpenter, B., Gelman, A., Hoffman, M. D., Lee, D., Goodrich, B., Betancourt, M., . . . Riddell, A.
(2017). Stan: A probabilistic programming language. *Journal of Statistical Software, 76*(1).
Cavanagh, J. F., Wiecki, T. V., Cohen, M. X., Figueroa, C. M., Samanta, J., Sherman, S. J., & Frank,
M. J. (2011). Subthalamic nucleus stimulation reverses mediofrontal influence over decision
threshold. *Nature neuroscience, 14*(11), 1462-1467.
Craig, A. D., & Craig, A. (2009). How do you feel--now? The anterior insula and human awareness.
Nature Reviews Neuroscience, 10(1).
Duncan, J., & Owen, A. M. (2000). Common regions of the human frontal lobe recruited by diverse
cognitive demands. *Trends in neurosciences, 23*(10), 475-483.
Economides, M., Guitart-Masip, M., Kurth-Nelson, Z., & Dolan, R. J. (2014). Anterior cingulate cortex
instigates adaptive switches in choice by integrating immediate and delayed components of
value in ventromedial prefrontal cortex. *Journal of Neuroscience, 34*(9), 3340-3349.
Economides, M., Guitart-Masip, M., Kurth-Nelson, Z., & Dolan, R. J. (2015). Arbitration between
controlled and impulsive choices. *Neuroimage, 109*, 206-216.
Fuster, J. (2015). *The prefrontal cortex*: Academic Press.

Gelman, A., Meng, X.-L., & Stern, H. (1996). Posterior predictive assessment of model fitness via
realized discrepancies. *Statistica sinica*, 733-760.
Gelman, A., & Rubin, D. B. (1992). Inference from iterative simulation using multiple sequences.
Statistical science, 7(4), 457-472.
Gershman, S. J., Horvitz, E. J., & Tenenbaum, J. B. (2015). Computational rationality: A converging
paradigm for intelligence in brains, minds, and machines. *Science, 349*(6245), 273-278.
Gigerenzer, G., & Gaissmaier, W. (2011). Heuristic decision making. *Annual Review of Psychology,*
62, 451-482.
Gluth, S., Rieskamp, J., & Büchel, C. (2012). Deciding when to decide: time-variant sequential
sampling models explain the emergence of value-based decisions in the human brain. *Journal*
of Neuroscience, 32(31), 10686-10698.
Goschke, T. (2013). Volition in action: intentions, control dilemmas and the dynamic regulation of
intentional control. *Action science: Foundations of an emerging discipline*, 409-434.
Hutton, C., Bork, A., Josephs, O., Deichmann, R., Ashburner, J., & Turner, R. (2002). Image distortion
correction in fMRI: a quantitative evaluation. *Neuroimage, 16*(1), 217-240.
Huys, Q. J., Eshel, N., O'Nions, E., Sheridan, L., Dayan, P., & Roiser, J. P. (2012). Bonsai trees in
your head: how the Pavlovian system sculpts goal-directed choices by pruning decision trees.
PLoS computational biology, 8(3), e1002410.
Huys, Q. J., Lally, N., Faulkner, P., Eshel, N., Seifritz, E., Gershman, S. J., . . . Roiser, J. P. (2015).
Interplay of approximate planning strategies. *Proceedings of the National Academy of*
Sciences, 112(10), 3098-3103.
Keramati, M., Smittenaar, P., Dolan, R. J., & Dayan, P. (2016). Adaptive integration of habits into
depth-limited planning defines a habitual-goal–directed spectrum. *Proceedings of the National*
Academy of Sciences, 113(45), 12868-12873.
Kerns, J. G., Cohen, J. D., MacDonald, A. W., Cho, R. Y., Stenger, V. A., & Carter, C. S. (2004).
Anterior cingulate conflict monitoring and adjustments in control. *Science, 303*(5660), 1023-
1026.
Kolling, N., Wittmann, M., & Rushworth, M. F. (2014). Multiple neural mechanisms of decision making
and their competition under changing risk pressure. *Neuron, 81*(5), 1190-1202.
Konidaris, G. (2019). On the necessity of abstraction. *Current Opinion in Behavioral Sciences, 29*, 1-7.
Kool, W., Gershman, S. J., & Cushman, F. A. (2017). Cost-benefit arbitration between multiple
reinforcement-learning systems. *Psychological science, 28*(9), 1321-1333.
Korn, C. W., & Bach, D. R. (2018). Heuristic and optimal policy computations in the human brain
during sequential decision-making. *Nature communications, 9*(1), 325.
Kumar, R., Carroll, C., Hartikainen, A., & Martín, O. A. (2019). ArviZ a unified library for exploratory
analysis of Bayesian models in Python.
Lee, D. G., & Daunizeau, J. (2021). Trading mental effort for confidence in the metacognitive control of
value-based decision-making. *eLife, 10*, e63282.
Lieder, F., & Griffiths, T. L. (2020). Resource-rational analysis: understanding human cognition as the
optimal use of limited computational resources. *Behavioral and brain sciences, 43*.
Lieder, F., Shenhav, A., Musslick, S., & Griffiths, T. L. (2018). Rational metareasoning and the
plasticity of cognitive control. *PLoS computational biology, 14*(4), e1006043.
Loued-Khenissi, L., Pfeuffer, A., Einhäuser, W., & Preuschoff, K. (2020). Anterior insula reflects
surprise in value-based decision-making and perception. *Neuroimage, 210*, 116549.
Maldjian, J. A., Laurienti, P. J., Kraft, R. A., & Burdette, J. H. (2003). An automated method for
neuroanatomic and cytoarchitectonic atlas-based interrogation of fMRI data sets. *Neuroimage,*
19(3), 1233-1239.
Marković, D., Goschke, T., & Kiebel, S. J. (2020). Meta-control of the exploration-exploitation dilemma
emerges from probabilistic inference over a hierarchy of time scales. *Cognitive, Affective, &*
Behavioral Neuroscience, 1-25.
Martin, A. (2007). The representation of object concepts in the brain. *Annu. Rev. Psychol., 58*, 25-45.
Miller, E. K., & Cohen, J. D. (2001). An integrative theory of prefrontal cortex function. *Annual review*
of neuroscience, 24(1), 167-202.
Miller, K. J., & Venditto, S. J. C. (2020). Multi-step Planning in the Brain. *Current Opinion in Behavioral*
Sciences, 38, 29-39.
Ott, F., Marković, D., Strobel, A., & Kiebel, S. J. (2020). Dynamic integration of forward planning and
heuristic preferences during multiple goal pursuit. *PLoS computational biology, 16*(2),
e1007685.
Pochon, J.-B., Riis, J., Sanfey, A. G., Nystrom, L. E., & Cohen, J. D. (2008). Functional imaging of
decision conflict. *Journal of Neuroscience, 28*(13), 3468-3473.

Puterman, M. L. (2014). *Markov decision processes: discrete stochastic dynamic programming*: John
Wiley & Sons.
Schwartenbeck, P., FitzGerald, T. H., Mathys, C., Dolan, R., & Friston, K. (2015). The dopaminergic
midbrain encodes the expected certainty about desired outcomes. *Cerebral Cortex, 25*(10),
3434-3445.
Schwöbel, S., Marković, D., Smolka, M. N., & Kiebel, S. J. (2021). Balancing control: a Bayesian
interpretation of habitual and goal-directed behavior. *Journal of mathematical psychology,*
100, 102472.
Shenhav, A., Botvinick, M. M., & Cohen, J. D. (2013). The expected value of control: an integrative
theory of anterior cingulate cortex function. *Neuron, 79*(2), 217-240.
Shenhav, A., Musslick, S., Lieder, F., Kool, W., Griffiths, T. L., Cohen, J. D., & Botvinick, M. M. (2017).
Toward a rational and mechanistic account of mental effort. *Annual review of neuroscience,*
40, 99-124.
Simon, D. A., & Daw, N. D. (2011). Neural correlates of forward planning in a spatial decision task in
humans. *Journal of Neuroscience, 31*(14), 5526-5539.
Singer, T., Critchley, H. D., & Preuschoff, K. (2009). A common role of insula in feelings, empathy and
uncertainty. *Trends in Cognitive Sciences, 13*(8), 334-340.
Smith, E. E., & Medin, D. L. (1981). *Categories and concepts* (Vol. 9): Harvard University Press
Cambridge, MA.
Smith, E. H., Horga, G., Yates, M. J., Mikell, C. B., Banks, G. P., Pathak, Y. J., . . . Botvinick, M. M.
(2019). Widespread temporal coding of cognitive control in the human prefrontal cortex.
Nature neuroscience, 1-9.
Stan Development Team. (2018). *PyStan: the Python interface to Sta*n, Version 2.19.1.1. http://mc-
stan.org.
Sutton, R. S., & Barto, A. G. (2018). *Reinforcement learning: An introduction*: MIT press.
Tenenbaum, J. B., Kemp, C., Griffiths, T. L., & Goodman, N. D. (2011). How to grow a mind: Statistics,
structure, and abstraction. *Science, 331*(6022), 1279-1285.
Tolman, E. C. (1948). Cognitive maps in rats and men. *Psychological review, 55*(4), 189.
Vehtari, A., Gelman, A., & Gabry, J. (2017). Practical Bayesian model evaluation using leave-one-out
cross-validation and WAIC. *Statistics and Computing, 27*(5), 1413-1432.
Wiecki, T. V., & Frank, M. J. (2013). A computational model of inhibitory control in frontal cortex and
basal ganglia. *Psychological review, 120*(2), 329.
Wiecki, T. V., Sofer, I., & Frank, M. J. (2013). HDDM: Hierarchical Bayesian estimation of the drift-
diffusion model in Python. *Frontiers in neuroinformatics, 7*, 14.
Yee, E. (2019). Abstraction and concepts: when, how, where, what and why? In: Taylor & Francis.