Disparate energy consumption despite similar network activity

Michael Deistler[1,2], **Jakob H. Macke**[1,2,3*], **Pedro J. Gonçalves**[1,4*]

[1]Machine Learning in Science, Excellence Cluster 'Machine Learning', Tübingen University, Tübingen, Germany; [2]Computational Neuroengineering, Department of Electrical and Computer Engineering, Technical University of Munich, Germany; [3]Max Planck Institute for Intelligent Systems, Tübingen, Germany; [4]Center of Advanced European Studies and Research (caesar), Bonn, Germany

Abstract

Neural circuits can produce similar activity patterns from vastly different combinations of channel and synaptic conductances. These conductances are tuned for specific activity patterns but might also reflect additional constraints, such as metabolic cost or robustness to perturbations. How do such constraints influence the range of permissible conductances? Here, we investigate how metabolic cost affects the parameters of neural circuits with similar activity in a model of the pyloric network of the crab *Cancer borealis*. We use a novel machine learning method to identify a range of network models that can generate activity patterns matching experimental data. We find that neural circuits can consume largely different amounts of energy despite similar circuit activity. We then study how circuit parameters get constrained by minimizing energy consumption and identify circuit parameters that might be subject to metabolic tuning. Finally, we investigate the interaction between metabolic cost and temperature robustness. We show that metabolic cost can vary across temperatures, but that robustness to temperature changes does not necessarily incur an increased metabolic cost. Our analyses show that, despite metabolic efficiency and temperature robustness constraining circuit parameters, neural systems can generate functional, efficient, and robust network activity with widely disparate sets of conductances.

Introduction

Neural activity arises from the interplay of mechanisms at multiple levels, including single-neuron and network mechanisms. Several experimental and theoretical studies have found that neural systems can produce similar activity from vastly different membrane and synaptic conductances [1–5], a property sometimes referred to as parameter degeneracy [6, 7]. Such parameter degeneracy has been argued to be a prerequisite for natural selection [6] and translates into potential mechanisms of compensation for perturbations of the systems' parameters [3, 5, 8–13]. However, in addition to a specific target activity, neural systems are likely subject to additional constraints such as the requirement to be energy efficient [14–16]. In order to understand experimentally observed variability and probe potential compensation mechanisms in functioning neural systems, it is thus crucial to characterise the extent of the systems' parameter degeneracy under such additional constraints.

Neuronal activity accounts for the majority of the energy consumed by the brain [17–19]. Energy is stored in the ionic gradients across the cell membrane, and consumed mostly by action potentials and synaptic mechanisms. Maintaining the ionic gradients requires the action of ion pumps, which consume ATP [14, 20]. Previous work has investigated the metabolic efficiency in small neural systems, often at the single neuron level and with few ion channels

---

*These authors contributed equally to this work

For correspondence: michael.deistler@uni-tuebingen.de; Jakob.Macke@uni-tuebingen.de; pedro.goncalves@uni-tuebingen.de

38 (often sodium, potassium, and leak) [14, 21, 22]. In these studies, it has been demonstrated that energy consump-
39 tion of single neurons can be reduced by tuning maximal conductances or time constants of gating variables, while
40 maintaining electrophysiological characteristics, e.g. spike width. However, questions regarding energy efficiency of
41 neural systems remain: First, it is unclear how previous findings in models with only sodium, potassium, and leak
42 currents extrapolate to the context of complex patterns of neuronal activity such as burst firing, which arise through
43 the interaction of a larger diversity of currents. Second, synaptic currents interact with single neuron properties
44 [11, 20, 23], raising the question of how membrane and synaptic conductances should be tuned in order to achieve
45 low metabolic cost. Third, energy efficiency has often been characterised for parts of, rather than the whole neural
46 system within which it operates. For example, the energy efficiency of single neurons is often studied in isolation of
47 the neural network it is immersed in [24–26], which precludes the full characterisation of how the operation of neural
48 systems impacts energy efficiency. Lastly, metabolic cost is only one of many constraints under which neural circuits
49 operate, and it is often unknown whether energy efficiency trades-off with other constraints (for a study of how en-
50 ergy efficiency trades off with temperature robustness in a single neuron model of the grasshopper, see Roemschied
51 et al. [27]).

52 Here, we investigate the energy efficiency of the pyloric network in the stomatogastric ganglion (STG) of the crab
53 *Cancer borealis* [28, 29], a canonical example of a neural system with parameter degeneracy [5]. The pyloric network
54 produces a triphasic motor pattern, and consists of a pacemaker kernel (anterior burster neuron, AB, and two pyloric
55 dilator neurons, PD), as well as two types of follower neurons (a single lateral pyloric, LP, and several pyloric, PY,
56 neurons), interconnected by inhibitory synapses. A model of this circuit with three model neurons (AB/PD, LP, PY),
57 each with eight membrane currents, and seven inhibitory synapses (Fig. 1a, details in Methods) has been shown to
58 be capable of producing similar network activity with widely different parameters [5].

59 We start by characterising the parameter degeneracy of this model: We apply a recently introduced machine learn-
60 ing tool for simulation-based inference, Sequential Neural Posterior Estimation (SNPE) [13] to estimate the full set of
61 membrane and synaptic conductances for which the model reproduces experimental data. We reduce the number of
62 model simulations required to run SNPE by introducing an additional classifier which detects and rejects parameter-
63 combinations that produce non-bursting model outputs [30]. After characterising the parameter degeneracy in the
64 model, we show that disparate circuit configurations can have different energy consumption despite similar activity.
65 Notably, a reduced but significant parameter degeneracy is present in the model even when enforcing circuits to have
66 *both* similar activity and energy consumption. Furthermore, energy consumption is linearly predictable from circuit
67 parameters, allowing us to identify circuit parameters that most strongly influence energy consumption. We then
68 show that individual neurons in the pyloric network can be tuned separately to minimize their energy consumption,
69 and thereby achieve low energy consumption at the circuit level. Finally, since the crab *Cancer borealis* is subject to
70 daily and seasonal fluctuations in temperature, we study the trade-off between metabolic cost and robustness to
71 changes in temperature [31–34]. We find that metabolic cost can vary across temperatures, but that the system can
72 be energy efficient and temperature robust at the same time.

Results

Disparate energy consumption despite similar network activity

75 We studied the metabolic cost in a model of the pyloric network (Fig. 1a). In this model, disparate sets of maximal
76 membrane and synaptic conductances can give rise to similar network activity [5]. As an example, we simulated
77 two such circuit configurations (Fig. 1b) and computed their metabolic cost using a previously described measure of
78 energy consumption [35]. In this measure, the energy for each ion channel is the time integral of the product of the
79 membrane current and the respective difference between the membrane voltage and the reversal potential. The
80 energy consumed by the entire neural circuit is the sum of the energies across channels of all neurons (details in
81 Methods).

82 Although the two simulated circuit configurations produce similar network activity, even at the single-spike level
83 (Fig. 1c), the total energy consumption (Fig. 1d) as well as the moment by moment energy consumption differ sub-
84 stantially (Fig. 1e). A closer inspection of the energy consumed by each current in the PY neuron during the action
85 potentials [36] shows that the difference in energy between these two network configurations is also evident in the
86 energy consumed by the sodium current Na, the delayed-rectifier potassium current Kd, and the transient calcium

Figure 1. Similar activity with different energy consumption. (a) Computational model of the pyloric network consisting of three model neurons (AB/PD, LP, PY) and seven synapses. (b) Traces with similar circuit activity (traces from top to bottom: AB/PD, LP, PY) despite different circuit parameters (parameter values not plotted). Scale bars indicate 50 mV. (c) Close-up of two spikes in the PY neural activity shown in (b). (d) Total energy consumption divided by the duration of the simulation (10 seconds) for the traces shown in (b). The left trace has 3-fold lower metabolic cost than the right trace. (e) Consumed energy at each time point. Scale bar indicates 100 μJ/s. (f) The energy consumed by each of the ion currents during the two spikes shown in (c).

current CaT (Fig. 1f).

Disparity in energy consumption in models matching experimental data

The example above illustrates that the model of the pyloric network can, in principle, produce the same activity with different metabolic costs. However, it is unclear how broad the range of metabolic costs associated with the same network output is. In order to address this, we need to identify the full space of maximal membrane and synaptic conductances (31 parameters in total) that match experimental measurements of network activity and to characterise the energy consumption of each of these configurations.

We used a recently introduced machine learning tool for simulation-based inference, Sequential Neural Posterior Estimation (SNPE) [13], to estimate the set of circuit parameters (the posterior distribution) consistent with data and prior assumptions about the parameters. In SNPE, random parameters which specify network configurations are initially sampled from the prior distribution (in our case a uniform distribution within plausible parameter ranges) and used to simulate network activity. Subsequently, a neural-network based density estimator is trained on these simulated network activities to learn which parameter sets produce network activity that is compatible with empirical observations. In order to generate the training data for the neural network, SNPE requires millions of model simulations to accurately infer the set of data-compatible parameters. To improve the simulation efficiency and make the neural network predict parameter sets that more closely match experimental data, we introduced a modification of the algorithm (Fig. 2a): A technical challenge for SNPE is that parameter sets sampled from the prior distribution might produce simulation results that are not 'valid', i.e. produce clearly non-sensible data: E.g., if there are no bursts, phase gaps between bursts are not defined (Fig. 2a, forth panel, red). For SNPE, these 'invalid' simulations are discarded immediately. In order to reduce the fraction of simulations that are discarded, we introduce a classifier to predict whether a parameter set will lead to a 'valid' or an 'invalid' simulation output [30] (Fig. 2a, second panel). Once the classifier is trained on an initial set of simulations, parameters are immediately discarded without running the simulation, if the classifier confidently predicts that the simulation will be invalid (details in Methods). We name the distribution of parameters that are accepted by the classifier the 'restricted prior' (Fig. 2a, third panel). Once sufficiently many valid simulations are performed, SNPE proceeds by training a deep neural density estimator to estimate the posterior distribution over parameters of the model [13] (Fig. 2a, last two panels, proof of convergence to the correct posterior distribution in Methods).

We used this procedure to infer the posterior distribution over maximal membrane and synaptic conductances of the model of the pyloric network given salient and physiologically relevant features of experimentally measured

Figure 2. Bayesian inference reveals wide range of energy consumption. (a) Inferring the posterior distribution by combining a rejection classifier and a deep neural density estimator. First, a classifier (trained on an initial set of simulations) predicts which circuit parameters sampled from the prior produce 'valid' simulation outputs. We then proceed by sampling from the part of the parameter space that is accepted by the classifier, i.e. the 'restricted prior'. All 'valid' data (green) are used to train a deep neural density estimator, all 'invalid' data are discarded (red) [13]. Once this estimator is trained, it can be evaluated on experimental data to return the posterior distribution over model parameters. (b) Experimental data recorded from the pyloric network [37]. Arrows indicate a subset of the physiologically relevant features, namely the cycle period (1), phase delays (2), phase gaps (3), and burst durations (4) (see Methods for details). (c) Simulation output from a parameter set sampled from the prior distribution. The traces are: AB/PD (top), LP (middle), PY (bottom). Scale bars correspond to 500 ms and 50 mV. (d) Subset of the marginals and pairwise marginals of the 31-dimensional restricted prior, i.e. the subspace of parameters for which the model produces bursting activity. All maximal conductances are given in mS/cm^2. (e) Subset of the marginals and pairwise marginals of the posterior distribution, i.e. the subspace of parameters for which the model matches experimental data shown in panel (b) (full posterior distribution in Appendix 1 Fig. 1). (f) Sample from the restricted prior producing bursting activity but not matching experimental data. (g) Sample from the posterior distribution closely matching features of the experimental data. (h) Histograms over energy consumed by each neuron (blue, orange, green) as well as by entire circuit (black). Trace with lowest energy consumes 9 times less energy than trace with highest energy. (i) Same as in (h), but for energy per spike.

data. These features are the cycle period, burst durations, duty cycles, phase gaps, and phase delays of the triphasic rhythm (Fig. 2b, details in Methods) [37]. Following the definitions established in previous studies [4, 5], we did not constrain the number of spikes or the spike shapes. Below, we describe the results obtained for a specific experimental preparation. We qualitatively reproduced all results with two additional experimental preparations (Appendix 1 Fig. 9, Appendix 1 Fig. 10, Appendix 1 Fig. 11, Appendix 1 Fig. 12, Appendix 1 Fig. 13, Appendix 1 Fig. 14) [37].

When simulating the pyloric network model with parameter sets sampled from the prior distribution, 99% of simulations do not produce spikes or bursts and hence characteristic summary features of the circuits are not defined (Fig. 2c). The restricted prior (Fig. 2d) is narrower than the prior distribution, but considerably broader than the posterior (Fig. 2e, full posterior distribution in Appendix 1 Fig. 1; comparison between prior, restricted prior, and posterior in Appendix 1 Fig. 2). Parameters sampled from the restricted prior often produce activity with well-defined

Figure 3. Metabolic constraints on individual circuit parameters. (a) Left: Energy consumption of 35,939 models that match experimental data. The orange area corresponds to the energy consumption in the lowest 2% quantile, red area to the top 98% quantile. Middle: Distribution of the maximal conductance of the transient calcium channel (CaT) in the PY neuron in the 2% (orange) and 98% quantile (red). Right: Distribution of the maximal conductance of the delayed-rectifier potassium channel (Kd) in the AB/PD neuron in the 2% (orange) and 98% quantile (red). (b) Standard deviation of parameters for models with energy consumption in the lowest 2% quantile. Standard deviation is normalized to the standard deviation of the parameters across all 35, 939 models in our database. (c) Subset of the parameter values of the five most efficient circuit configurations in our database. (d) The network activity produced by two of these five configurations. Scale bar indicates 500 ms and 50 mV. (e) The energy consumption of the two configurations shown in panel (d). (f) Subset of circuit parameters of the two solutions shown in panel (b). Despite similar network activity and low energy consumption, several parameters differ by more than 2-fold. The membrane conductances are scaled by the following factors (left to right): 100, 10, 10, 100, 100, 10000.

summary features (Fig. 2f), but do not generally match experimental data, whereas samples from the posterior closely
match experimental data (Fig. 2g). By using the classifier to reject 'invalid' simulations, we required half as many
simulations compared to 'classical' SNPE [13] and achieved a higher accuracy (Appendix 1 Fig. 3). For the subsequent
analyses, we only considered posterior samples whose activity was within a prescribed distance to the experimental
data, and discarded all other samples (details in Methods). We simulated 1 million parameter configurations sampled
from the posterior, out of which approximately 3.5% fulfilled the distance criterion, leading to a database of 35, 939
parameter sets whose activity closely matched experimental data. Sampling from the prior distribution rather than
the posterior would have required approximately 600 billion simulations to obtain 35, 939 parameter sets that fulfill
our criterion (60, 000 times more than with our method).

We computed the energy consumption of each of the 35, 939 circuit activities (Fig. 2h). The circuit configuration
with lowest total energy consumes nine times less energy than the circuit configuration with highest total energy.
To ensure that the difference in energy does not only stem from different numbers of spikes within a burst, we also
computed the average energy consumed during a spike (energy per spike) in each of the neurons (Fig. 2i). As with total
energy, energy per spike strongly varies across parameter configurations. These results show that, despite similar
circuit function, different parameter sets can have vastly different energy consumption. Below, we investigate the
mechanisms giving rise to this phenomenon.

Metabolic constraints on individual circuit parameter ranges

143 How strongly does enforcing low energy consumption constrain the permissible ranges of circuit parameters? We
144 inspected the circuit parameters of the 2% most and least efficient configurations within our database of 35, 939
145 model configurations (Fig. 3a, left). For some circuit parameters, the range of values producing efficient activity is
146 clearly different from the range of values producing energetically costly activity (e.g. the maximal conductance of the

Figure 4. Influence of circuit parameters on energy consumption. (a) Illustration of linear regression from circuit parameters θ (taken from our database of $35,939$ configurations) onto energy consumption E. (b) The linear regression accurately predicts the energy consumption on a test set of 300 circuit configurations (black dots). Grey line is the identity function. (c) Weights w of the linear regression. Left: Weights of the maximal membrane conductances. Right: Weights of the maximal synaptic conductances. (d) Weights w as a function of energy consumption (both normalized), for all membrane currents (arrows highlight three illustrative examples). Membrane conductances on the top left consume little energy, but their maximal conductances correlate strongly with energy consumption. Conductances on the bottom right consume a lot of energy, but their maximal conductances correlate weakly with energy consumption. (e) Top: The gating variable n^4 of the Kd current in the PY neuron during activity produced by two circuit configurations (black and red) which are identical apart from the magnitude of $\overline{g}_{Kd}$. Bottom: The product of gating variable and maximal conductance $n^4 \cdot \overline{g}_{Kd}$ for the same configurations. (f) Top: Weights of a linear regression onto the energy per spike in the PY neuron. Bottom: Weights of a linear regression onto the number of spikes in the PY neuron.

transient calcium current in the PY neuron, Fig. 3a, middle). For other parameters, the range does not change (e.g. the
maximal conductance of the delayed-rectifier potassium current in the AB/PD neuron, Fig. 3a, right). To quantify how
strongly low energy consumption constrains parameters, we compared the parameter standard deviation across
all $35,939$ model configurations to that of the most efficient 2% (Fig. 3b). Most parameters in the circuit barely get
constrained by energy consumption (values close to one in Fig. 3b). The parameters that get constrained the most by
enforcing low energy consumption are the Na and CaT conductances of the AB/PD neuron, the CaS conductance of
the LP neuron, and the Na, CaT, CaS, and leak conductances of the PY neuron. However, for all of these parameters,
a large fraction of variability remains.

In order to ensure that the remaining variability of circuit parameters does not stem from the remaining variabil-
ity of energy consumptions within the lowest 2% quantile, we inspected the five most efficient configurations in our
database of $35,939$ model configurations. Even these five circuit configurations have strongly disparate circuit param-
eters (Fig. 3c). Despite having similar activity (Fig. 3d) and very low (and similar) metabolic cost (Fig. 3e), their circuit
parameters are disparate (Fig. 3f). These results demonstrate that metabolic efficiency constrains the range of some
circuit parameters, but it is possible to achieve low metabolic cost and similar network activity with widely disparate
circuit parameters.

Conductances of energetically costly channels do not necessarily correlate with energy consumption

164 We wanted to understand how each circuit parameter affects energy consumption. We performed a linear regression
165 from circuit parameters (taken from our database of $35,939$ model configurations) onto the energy consumption of
166 these circuits (Fig. 4a). This linear regression achieved a high accuracy, demonstrating that energy consumption
167 can be linearly predicted from circuit parameters (Fig. 4b; a non-linear regression with a neural network leads to

similar results and is shown in Appendix 1 Fig. 4; details in Methods). The regression weights w indicate how strongly energy consumption is correlated with each parameter value (Fig. 4c). The maximal sodium conductance $\overline{g}_{Na}$ and the transient calcium conductance $\overline{g}_{CaT}$ of the AB/PD and PY neuron as well as the slow calcium conductance $\overline{g}_{CaS}$ of the AB/PD, LP, and PY neuron are most strongly correlated with energy consumption: Increases of these conductances are associated with an increase in energy consumption, and thus, small conductance values correspond to metabolically more efficient solutions. The synaptic conductances are weakly correlated with energy consumption, which can be explained by the low values of the maximal synaptic conductances: The synaptic strengths range up to 1000 nS, whereas the membrane conductances can range up to 0.4 mS (i.e. $4 \cdot 10^5$ nS), such that synapses consume only 0.08% of the total energy in the circuit. These results demonstrate that energy consumption can be linearly predicted from circuit parameters, and that energy consumption is most strongly correlated with the maximal conductances of sodium as well as slow and transient calcium.

How do different currents affect total energy consumption? Do they directly consume energy, or do they trigger processes that then require energy? We addressed these questions by comparing the fraction of energy consumed by each current (as defined by our measure of energy [35], Fig. 1f) to the linear regression weight w associated with its maximal conductance (Fig. 4d). We found that some currents consume a lot of energy, although their maximal conductances barely correlate with energy consumption, e.g. the Kd current in the PY neuron (Fig. 4d, bottom right arrow), while other currents consume little energy, but nonetheless their maximal conductances are correlated with energy consumption, e.g. the CaS and CaT currents of the PY neuron (Fig. 4d, top left arrows).

We investigated the neuronal mechanisms that give rise to these behaviors. First, to understand how currents can consume large amounts of energy despite their maximal conductance only weakly correlating with energy, we investigated the effects of the delayed-rectifier potassium conductance $\overline{g}_{Kd}$ on circuit activity. We simulated two circuit configurations, identical apart from the magnitude of $\overline{g}_{Kd}$ in the PY model neuron. In the configuration with higher $\overline{g}_{Kd}$, the gating variable n did not reach as high values as for the other configuration, thus leading to a similar effective conductance $n^4 \cdot \overline{g}_{Kd}$ (Fig. 4e). This demonstrates that changes in the maximal conductance $\overline{g}_{Kd}$ only weakly influence the current and thereby the energy consumption. Thus, despite the potassium current consuming a lot of energy due to a large flow of ions (compared to other channels), its maximal conductance $\overline{g}_{Kd}$ only weakly correlates with energy consumption. Second, to understand how maximal conductances can correlate with energy consumption despite their channels consuming little energy, we disentangled the correlation of circuit parameters with energy consumption into two parts: The energy *per spike* and the number of spikes. We fitted two additional linear regression models: One regression from circuit parameters onto number of spikes in the PY neuron and one regression from circuit parameters onto energy per spike in the PY neuron. We again find good predictive performance of these models, showing that the energy per spike and the number of spikes can also be linearly predicted from circuit parameters (regression performance in Appendix 1 Fig. 5). The energy per spike is strongly correlated with the sodium conductance (Fig. 4f, top), whereas the number of spikes is most strongly correlated with the maximal conductance of transient calcium (also with sodium, slow calcium, and transient potassium conductances, Fig. 4f, bottom). This demonstrates that increases in the maximal conductance of transient calcium lead to a higher number of spikes, which involve increased energy consumption through other currents. We verified this hypothesis by simulating two configurations that were identical apart from the magnitude of $\overline{g}_{CaT}$ in the PY model neuron and found that the configuration with higher $\overline{g}_{CaT}$ indeed produced more spikes per burst. This shows that, despite the calcium channel consuming little energy itself, increasing $\overline{g}_{CaT}$ can lead to higher energy consumption by increasing the number spikes, which involve energy consumption through other currents (mostly sodium and potassium). Overall, our analyses demonstrate that currents which consume a lot of energy are not necessarily the ones which influence energy the most.

Neurons can be tuned individually to achieve minimal circuit energy

We wondered how single neurons interact to produce functional and efficient circuit activity. Can the energy of the entire circuit be minimized by optimizing the energy of each neuron individually? And does the circuit retain functional activity when neurons are individually optimized for low energy efficiency? Within our database of 35,939 model configurations, there is a weak correlation between the energies consumed by pairs of neurons, which suggests that the energy consumption between neurons might be independent from one another (Fig. 5a; AB/PD versus LP, correlation coefficient $r = -0.006$, p-value $p = 0.23$; LP versus PY, $r = 0.02$, $p = 3 \cdot 10^{-6}$; AB/PD versus PY, $r = -0.03$, $p =$

Figure 5. Neurons can be tuned individually to achieve minimal circuit energy consumption. (a) Black dots: Energy consumed by each neuron separately. 100 randomly selected parameter configurations from our database of 35, 939 configurations. Black line: Linear regression shows a weak correlation between the energy consumed by pairs of neurons. (b) We select the five most efficient parameter configurations for each neuron separately, and search with Markov chain Monte Carlo (MCMC) for synaptic conductances such that the target circuit activity is achieved. (c) The activity produced by two parameter configurations produced with the strategy described in (b). (d) A subset of the membrane (left) and synaptic (right) conductances for the configurations in panel (c). Despite generating similar network activity, the configurations have very different circuit parameters. The membrane conductances are scaled with the following factors (left to right): 10, 10000, 1, 100, 10000. (e) Histogram over the energy consumption of all 35, 939 models in our database (blue, orange, green, black) and the energy consumption of the configurations produced with the strategy described in panel (b) (red). (f) Histogram of the posterior log-probability for samples from the prior distribution (grey), for the 35, 939 models in our database (black), and for the configurations produced with the strategy described in panel (b) (red).

---

218 $8 \cdot 10^{-9}$). We thus investigated whether we could optimize the parameters of each neuron individually for low energy
219 consumption and still retain functional circuit activity. We searched our database of 35, 939 model configurations for
220 the single neuron models with minimal energy consumption individually. We selected the five most efficient single
221 neuron parameter combinations for each of the neurons and assembled them into 125 (5^3) network configurations.
222 We then identified synaptic conductances that match each of these configurations with Markov chain Monte Carlo
223 (Fig. 5b, details in Methods). Notably, given the already estimated full posterior distribution, this step does not require
224 additional simulations.

225 For each of the 125 combinations of membrane conductances, we found a set of synaptic conductances for which
226 the network activity closely resembles experimentally measured activity (Fig. 5c). The resulting configurations have
227 disparate parameters (Fig. 5d) but highly similar network activity. Furthermore, we found that the resulting configura-
228 tions have similar and very low energy consumption. The energy consumption of these circuits is significantly smaller
229 than that of any of the configurations in our database of 35, 939 model configurations (Fig. 5e). This demonstrates
230 that optimizing a specific neuron for energy efficiency does not preclude the connected neurons from being energy
231 efficient. Thus, our results suggest that the pyloric network can be optimized for energy efficiency by tuning neurons
232 individually for low energy consumption.

233 We estimated how likely are these energy-efficient circuits under the estimated posterior. We found that all these
234 models have similar posterior log-probability as the 35, 939 model configurations in our database (Fig. 5f), i.e. these
235 are as likely to underlie the experimentally measured activity as the database models. Thus, the low-energy config-
236 urations were not sampled when generating our original model database because of the high dimensionality of the
237 parameter space, and we cannot exclude the possibility that there might be unsampled regions in parameter space
238 with even more energy-efficient circuit configurations.

Figure 6. Temperature robustness does not preclude energy efficiency. (a) Top: Experimental data at 11°C. Bottom: Experimental data at 27°C [37]. (b) Left: Posterior distribution given experimental data at 11°C. Right: Posterior given experimental data at 11°C and 27°C. (c) Simulations for a parameter set drawn from the posterior distribution matching experimental data at 11°C and 27°C. Simulations at 11°C (top) and 27°C (bottom). (d) Cycle frequency (left), phase of LP neuron (middle) and phase of PY neuron (right) for parameter set shown in panel (c), simulated at temperatures between 11°C and 27°C. Green dots are the values of the experimental preparations. (e) Energy consumption at 11°C versus 27°C for 967 circuits sampled from the posterior (in (b) right). In grey, the identity line. (f) Influence of circuit parameters and Q_{10} values on energy consumption at 27°C. Weights w obtained by linear regression, similarly to Fig. 4. (g) Green: Distribution of the energy consumption of circuits matching experimental data at 11°C. Purple: Distribution of the energy consumption of circuits that match data at 11°C and are robust at 27°C. Pink: Distribution of the energy consumption of circuits that match experimental data at 11°C and 27°C.

Robustness to temperature does not require an increased metabolic cost

The crab *Cancer borealis* experiences daily and yearly fluctuations in temperature which in turn influence the chemical
and physical properties of neurons [31–33]. Nonetheless, neural circuits such as the pyloric network can maintain
their functionality in the presence of these temperature variations. As temperature increases, the cycle frequency of
the circuit increases exponentially, but the phases between bursts remain relatively constant [34, 38]. We investigated
whether the pyloric network trades off robustness to changes in temperature with energy efficiency, i.e. whether
temperature-robust solutions are more energetically costly.

    The temperature-dependence of a biophysical parameter R is captured by the Q_{10} value and is defined as follows:

$$R_T = R_{ref} Q_{10}^{(T-T_{ref})/10},$$

where R_{ref} is the parameter value at the reference temperature $T_{ref} = 11°C$. We extended the model of the pyloric
network to include Q_{10} values for all maximal membrane and synaptic conductances (details in Methods) [39, 40]. We
then used SNPE to identify all maximal membrane and synaptic conductances, as well as the associated Q_{10} values
(41 parameters in total) that match experimental recordings at 11°C and 27°C (Fig. 6a) [37]. We set the previously
identified posterior distribution (Fig. 2e) over circuit parameters given experimental data at 11°C as the new prior
distribution, and then applied SNPE to match the model with experimental data at 27°C (Fig. 6b, full posterior in Appendix 1 Fig. 7, details in Methods). We sampled circuit parameters and Q_{10} values from the resulting distribution

and selected samples whose activity closely matched experimental data at 11°C and 27°C (Fig. 6c). Overall, we generated a database of 967 sets of circuit parameters and Q_{10} values. When simulating at temperatures between 11°C and 27°C, these circuits show the characteristic exponential increase in cycle frequency as well as the constant phase relationship between bursts observed experimentally (Fig. 6d) [34].

We asked whether the energy consumed by the circuit at 11°C is proportional to the energy consumed at 27°C. We found that, despite the number of spikes in our model being higher at higher temperatures, the total energy consumption is lower at 27°C (Fig. 6e; note that, for one of the three preparations, the energy consumptions at 11°C and 27°C are similar). This occurs because at higher temperatures, the increase in the number of spikes is accompanied by an increase in channel time constants and respective decrease in energy per spike (Appendix 1 Fig. 8). In addition, there is a clear correlation between energy consumptions at 11°C and 27°C (Pearson-correlation coefficient: 0.66), although circuit configurations with similar efficiency at 11°C can show a range of energy consumptions at 27°C (Fig. 6e). A potential reason for this range of energies at 27°C (for fixed energy at 11°C) is the influence of Q_{10} values on the energy consumption. To investigate this, we performed a linear regression to predict energy consumption at 27°C from circuit parameters and Q_{10} values and inspected the linear regression weights w (Fig. 6f): Indeed, Q_{10} values correlate strongly with energy consumption, and the direction and magnitude of their influence follows that of the corresponding maximal membrane conductances.

Does temperature robustness have an influence on metabolic cost? We computed the energy consumed at 11°C for three different scenarios: First, for all models in our database of $35,939$ model configurations matching experimental data recorded at 11°C (same as Fig. 2h). Second, for all models in our database of $35,939$ model configurations that are also functional at 27°C (i.e. produce triphasic activity). Third, for all models in our database of 967 model configurations matching experimental data recorded at 11°C and 27°C. In all three of these scenarios, the distribution of metabolic cost was similar (Fig. 6g. Note that the slightly different average energy consumption between the first and the third scenario occurred only in two of the three preparations, see Appendix 1 Fig. 11 and Appendix 1 Fig. 14). In particular, all three scenarios contained configurations that produce energy efficient circuit function. This demonstrates that enforcing temperature robustness does not require the pyloric network to be less energy efficient.

Overall, our analyses indicate that Q_{10} values can contribute to the energy efficiency of the circuit and might, therefore, be the subject of tuning for metabolic efficiency. In addition, we showed that temperature robustness does not entail additional metabolic cost.

Discussion

Neural systems undergo environmental and neuromodulatory perturbations to their mechanisms. The parameter degeneracy of neural systems, i.e. the ability to generate similar activity from disparate parameters, confers a certain degree of robustness to such perturbations [6–9, 41, 42]. However, not all system configurations might be equally desirable, with some configurations being more energy efficient than others [14]. Here, we analysed the energy consumption of parameter configurations with similar activity in the pyloric network of the stomatogastric ganglion. We found that, even when the network activity is narrowly tuned to experimental data, the energy consumption can strongly vary between parameter configurations. Furthermore, we studied how membrane and synaptic conductances influence energy consumption [14], and demonstrated that neurons in the pyloric network can be tuned individually to achieve low energy consumption. Lastly, we showed that temperature robustness does not preclude energy efficiency. These findings were facilitated by a methodological advance that increased the efficiency of previously published tools for simulation-based inference [13, 30, 43, 44].

Relation to previous work on metabolic cost of neural systems

There has been extensive work on quantifying the metabolic cost of biophysical processes in single neurons [14, 21, 22, 24–26], and how single neurons subject to functional constraints can be tuned to minimize energy consumption [14, 22, 25]. However, so far, it has been unclear how energy efficiency impacts the parameter degeneracy of neural systems. While a plausible hypothesis would have been that energy efficiency reduces or eliminates degeneracy altogether, here we found that parameter degeneracy is preserved for most parameters, even within circuits with highly similar energy consumption. Nevertheless, we should note that our findings are based on two simplifying assumptions: First, we studied simple single-compartment neurons rather than more realistic multi-compartment

neuron models [45]; and second, the energy measure is derived directly from the Hodgkin-Huxley model [35], rather than taking into account all the complexity of the ionic exchange leading to ATP consumption [14, 20, 22, 25].

Which circuit parameters influence energy consumption the most? Consistent with previous work at the single neuron level, we found that total energy consumption of the pyloric network is strongly influenced by the sodium current [25], but also by the transient and slow calcium currents. The maximal sodium conductance is the most prominent driver of the energy per spike: Increases in the conductance lead to an increase of metabolic cost per spike [14, 25]. In contrast, calcium currents influence energy consumption through the number of spikes within a burst, despite not consuming much energy themselves. Our results suggest that the maximal conductances of sodium and calcium might be regulated for metabolic efficiency. We thus predict that these conductances are less variable in nature than expected by computational models only matching network activity.

Previous studies have demonstrated that synaptic mechanisms can consume a substantial amount of energy [20, 46, 47]. In contrast, in the considered model of the pyloric network, synaptic currents consume only a minor fraction of energy (approximately 0.08% of the total energy is consumed by synapses, whereas Attwell and Laughlin [20] report 40% of energy per action potential being consumed by synaptic mechanisms). This difference is largely due to the low number of connections in the pyloric network [48]: Each neuron projects to up to two other model neurons, whereas the synaptic energy consumption reported in Attwell and Laughlin [20] is based on the assumption of 8000 synaptic boutons per neuron. Thus, models of more complex neural circuits driven by excitatory, recurrent connectivity, such as the ones found in the cortex, might spend a larger fraction of energy on synaptic mechanisms.

Interplay between metabolic cost and robustness to perturbations

Neural circuits are likely constrained by energy consumption, but also by other requirements, e.g. robustness to perturbations such as fluctuations in temperature or pH [34, 39, 40, 49–53]. We investigated the interplay between energy consumption and temperature robustness. Consistent with previous work in a single neuron model of the grasshopper [27], we found that temperature robustness does not require an increased metabolic cost. Whether these results will generalize with the inclusion of the robustness to additional external perturbations, e.g. pH fluctuations [52, 54], or internal perturbations, e.g. neuromodulation [38], remains a subject for future work.

Increasing the efficiency of simulation-based inference

We used a previously introduced tool, SNPE [13, 44] to identify all models consistent with experimentally measured activity as well as prior knowledge about realistic parameter ranges. We improved the efficiency of the method by introducing a classifier that rejects 'invalid' simulations [30]. By using this classifier, we were able to improve the accuracy of SNPE while requiring only half as many simulations [13]. Because of this larger simulation-budget, the resulting posterior distributions became more accurate. Notably, the trained neural density estimator is amortized, i.e. one can obtain the posterior distribution for multiple experimental preparations without running further simulations or training a new neural network.

The classifier-enhanced SNPE can be applied to other modelling studies in neuroscience. In particular, the classifier to predict 'invalid' simulations is valuable whenever there are parameter values for which the computational model of interest produces ill-defined features: E.g. the spike shape cannot be defined in cases where a neuron model does not produce spikes. Our method has the potential to significantly speed up inference in these scenarios.

Implications for the operation of neural circuits

Our findings suggest that neural circuits can show a range of possible metabolic costs, depending on the underlying biophysical parameters, even with highly specific functional requirements under constant perturbations. This raises the question of whether such diversity of metabolic costs is present in real biological systems, or whether and how these systems are tuned for metabolic efficiency.

Acknowledgments

We thank Sara A. Haddad and Eve Marder for sharing their data and discussions, Martin Stemmler for discussions, and Poornima Ramesh, Richard Gao, and Jan Boelts for discussions and comments on the manuscript. The authors thank the International Max Planck Research School for Intelligent Systems (IMPRS-IS) for supporting MD. This work was supported by the German Research Foundation (DFG) through SFB 1089 'Synaptic Microcircuits' and Germany's

Methods

Code availability

Code to reproduce the figures is available at https://github.com/mackelab/stg_energy. Code for running SNPE and training a classifier to reject 'invalid' simulations is available in our toolbox: https://github.com/mackelab/sbi [55]. A tutorial for how to use these features can be found on our website https://mackelab.org/sbi.

Data from the crustacean stomatogastric ganglion

We analyzed extracellular recordings of the stomatogastric motor neurons that are involved in the triphasic pyloric rhythm in the crab *Cancer borealis* [37]. The first dataset as seen in Fig. 2 and Fig. 6 is from files 845_082_0044 and 845_082_0064, preparation 1. The second dataset as seen in Appendix 1 Fig. 9 and Appendix 1 Fig. 11 is from files 857_016_0049 and 857_016_0069, preparation 1. The third dataset as seen in Appendix 1 Fig. 12 and Appendix 1 Fig. 14 is from files 845_078_0027 and 845_078_0040, preparation 2. All preparations were decentralized, i.e. the axons of the descending modulatory inputs were severed. The data were recorded at 11°C and 27°C. Full experimental details in Haddad and Marder [38].

Circuit model of the crustacean stomatogastric ganglion

The circuit model of the crustacean stomatogastric ganglion was adapted from Prinz et al. [5]. The model is composed of three single-compartment neurons, AB/PD, LP, and PY, where the electrically coupled AB and PD neurons are modeled as a single neuron. Each of the model neurons contains 8 currents, a Na^+ current I_{Na}, a fast and a slow transient Ca^{2+} current I_{CaT} and I_{CaS}, a transient K^+ current I_A, a Ca^{2+}-dependent K^+ current I_{KCa}, a delayed rectifier K^+ current I_{Kd}, a hyperpolarization-activated inward current I_H, and a leak current I_{leak}. In addition, the model contains 7 synapses. As in Prinz et al. [5], these synapses are simulated using a standard model of synaptic dynamics [56]. The synaptic input current into the neurons is given by $I_s = \overline{g}_s s(V_{post} - V_s)$, where $\overline{g}_s$ is the maximal synapse conductance, V_{post} the membrane potential of the postsynaptic neuron, and V_s the reversal potential of the synapse. The dynamics of the activation variable s are given by

$$\frac{ds}{dt} = \frac{\overline{s}(V_{pre}) - s}{\tau_s},$$

with

$$\overline{s}(V_{pre}) = \frac{1}{1 + \exp((V_{th} - V_{pre})/\delta)} \quad \text{and} \quad \tau_s = \frac{1 - \overline{s}(V_{pre})}{k_-}.$$

Here, V_{pre} is the membrane potential of the presynaptic neuron, V_{th} is the half-activation voltage of the synapse, δ sets the slope of the activation curve, and k_- is the rate constant for transmitter-receptor dissociation rate.

As in Prinz et al. [5], we model two types of synapses, since AB, LP, and PY are glutamatergic neurons whereas PD is cholinergic. We set $E_s = -70$ mV and $k_- = 1/40$ ms for all glutamatergic synapses and $E_s = -80$ mV and $k_- = 1/100$ ms for all cholinergic synapses. For both synapse types, we set $V_{th} = -35$ mV and $\delta = 5$ mV. The membrane area is $0.628 \cdot 10^{-3}$ cm^2.

For each set of membrane and synaptic conductances, we numerically simulate the circuit for 10 seconds with a step size of 0.025 ms. At each time step, each neuron receives Gaussian noise with mean zero and standard deviation 0.001 mV·ms$^{-0.5}$.

We applied SNPE to infer the posterior over 24 membrane parameters and 7 synaptic parameters, i.e. 31 parameters in total. The 7 synaptic parameters are the maximal conductances $\overline{g}_s$ of all synapses in the circuit, each of which is varied uniformly in logarithmic domain from 0.01 nS to 1000 nS, with the exception of the synapse from AB to LP, which is varied uniformly in logarithmic domain from 0.01 nS to 10000 nS. The membrane parameters are the maximal membrane conductances for each neuron. The membrane conductances are varied over an extended range of previously reported values [5, 13]: The prior distribution over the parameters [Na, CaT, CaS, A, KCa, Kd, H, leak] is uniform with lower bounds $p_{low} = [0, 0, 0, 0, 0, 25, 0, 0]$ mS cm^{-2} and upper bounds $p_{high} = [500, 7.5, 8, 60, 15, 150, 0.2, 0.01]$ mS cm^{-2} for the maximal membrane conductances of the AB neuron, $p_{low} = [0, 0, 2, 10, 0, 0, 0, 0.01]$ mS cm^{-2} and $p_{high} = [200, 2.5, 12, 60, 10, 125, 0.06, 0.04]$ mS cm^{-2} for the maximal membrane conductances of the LP neuron, and $p_{low} = [0, 0, 0, 30, 0, 50, 0, 0]$ mS cm^{-2} and $p_{high} = [600, 12.5, 4, 60, 5, 150, 0.06, 0.04]$ mS cm^{-2} for the maximal membrane conductances of the PY neuron.

We computed 15 summary features proposed by Prinz et al. [5], and 3 additional features [13]. The features proposed by Prinz et al. [5] are 15 salient features of the pyloric rhythm, namely: Cycle period T (s), AB/PD burst duration d_{AB}^b (s), LP burst duration d_{LP}^b (s), PY burst duration d_{PY}^b (s), gap AB/PD end to LP start $\Delta t_{AB\text{-}LP}^{es}$ (s), gap LP end to PY start $\Delta t_{LP\text{-}PY}^{es}$ (s), delay AB/PD start to LP start $\Delta t_{AB\text{-}LP}^{ss}$ (s), delay LP start to PY start $\Delta t_{LP\text{-}PY}^{ss}$ (s), AB/PD duty cycle d_{AB}, LP duty cycle d_{LP}, PY duty cycle d_{PY}, phase gap AB/PD end to LP start $\Delta\phi_{AB\text{-}LP}$, phase gap LP end to PY start $\Delta\phi_{LP\text{-}PY}$, LP start phase ϕ_{LP}, and PY start phase ϕ_{PY}. Note that several of these values are only defined if each neuron produces rhythmic bursting behavior. In addition, for each of the three neurons, we computed the maximal duration of its voltage being above -30 mV. We did this as we observed—for many model simulations and in contrast with experimental data— long plateaus at around -10 mV during the bursts, and wanted to detect such traces. If the maximal duration was below 5 ms, we set this feature to 5 ms. To extract the summary features from the observed experimental data, we first found spikes by searching for local maxima above a hand-picked voltage threshold, and then extracted the 15 above described features. For the experimental preparation, we set the additional 3 features to 5 ms.

At temperatures higher than 11°C, we include Q_{10} values to simulate the biochemical changes of the network parameters. These are defined by an Arrhenius-type factor

$$R_T = R_{ref} \, Q_{10}^{(T - T_{ref})/10},$$ (1)

where R_{ref} is the parameter value at the reference temperature T_{ref} = 11°C, and R_T is the parameter value at temperature T. Each maximal conductance has a different Q_{10}, but the Q_{10} value is the same across neurons [40]. We introduce one Q_{10} for the glutamatergic synapses and one for the cholinergic synapses. The prior distribution for the Q_{10} values is a uniform distribution between 1 and 2 for all maximal conductances but the hyperpolarization current, for which the prior bounds are 1 and 4 [34]. The Q_{10} values for the time constants are fixed to 2.4 for most m-gates and 2.8 for all h-gates. Following the results from Caplan et al. [39], the Q_{10} values for the m-gates of KCa and CaS as well as for the calcium buffer have lower values: 2.0 for CaS and the calcium buffer and 1.6 for KCa. The Q_{10} value for the time constants of the synapses is 1.7.

Energy consumption

To compute the energy consumption E of a specific network activity, we followed the approach of Moujahid et al. [35]. For each neuron, we computed the energy as:

$$E = \int \sum_m g_m (V - V_m)^2 + \sum_s g_s (V - V_s)^2 \, dt,$$ (2)

where g_m is the effective conductance of channel m (i.e. the product of the respective gating variables, maximal conductance and membrane area) and g_s is the effective synaptic conductance s into the specific neuron. V_m is the reversal potential of the membrane current m and V_s is the reversal potential of the synapse s. The units of energy are $[S \cdot V^2 \cdot s = J]$, where S are Siemens, V are Volt, s are seconds, and J are Joules. The total energy consumption was defined as the sum of the energy consumed by each of the three neurons. Throughout the manuscript, we report the energy per second, which we obtained by dividing the total energy consumption by the duration of the simulation (10 seconds).

The energy per spike was defined as the energy consumed during bursts divided by the respective number of spikes.

 Simulation-based inference

 We extended Sequential Neural Posterior Estimation [13] by using a classifier to predict 'invalid' simulation outputs.

 The resulting algorithm is described in algorithm 1.

Algorithm 1: SNPE

Input: simulator with (implicit) density $p(\mathbf{x}|\boldsymbol{\theta})$, observed data $\mathbf{x}_o$, prior $p(\boldsymbol{\theta})$, rejection criterion $g(\mathbf{x}) \in \{0, 1\}$, classification neural network $G_\zeta(\theta)$, density family q_ψ, neural network $F(\mathbf{x}, \phi)$, number of cycles C of classifier training, simulation count for each cycle N_c

randomly initialize ϕ, ζ

$\tilde{p}_1(\boldsymbol{\theta}) := p(\boldsymbol{\theta})$

$N := 0$

for $c = 1$ **to** C **do**

    for $i = 1 \dots N_c$ **do**

        sample $\boldsymbol{\theta}_{N+i} \sim \tilde{p}_c(\boldsymbol{\theta})$

        simulate $\mathbf{x}_{N+i} \sim p(\mathbf{x}|\boldsymbol{\theta}_{N+i})$

        evaluate whether 'valid' $\mathbf{r}_{N+i} = g(\mathbf{x}_{N+i})$

    $N \leftarrow N + N_c$

    train $\zeta \leftarrow \underset{\zeta}{\arg\min} \sum_{j=1}^{N} \mathcal{L}_e(\boldsymbol{\theta}_j, \mathbf{r}_j)$ `// classifier training`

    $T \leftarrow$ Tune classifier threshold s.t. false negative rate < 1%

    $U(\theta) \leftarrow G_\zeta(\theta) > T$

    $\tilde{p}_c(\boldsymbol{\theta}) :\propto U(\theta)p(\boldsymbol{\theta})$

    train $\phi \leftarrow \underset{\phi}{\arg\min} \sum_{j=1}^{N} \mathcal{L}_d(\boldsymbol{\theta}_j, \mathbf{x}_j)$ `// neural density estimator training`

return $q_{F(\mathbf{x}_o, \phi)}(\boldsymbol{\theta})$

 Proof of convergence of SNPE with classifier

Below, we prove that the posterior distribution inferred by our method converges to the true posterior distribution. SNPE—with the classifier—minimizes the following loss function with respect to the neural network parameters ϕ:

$$\mathcal{L}_d = -\frac{1}{N} \sum_i \log(q_\phi(\boldsymbol{\theta}_i|\mathbf{x}_i))$$

$$\xrightarrow{N \to \infty} -\mathbb{E}_{p(\boldsymbol{\theta}, \mathbf{x})}[\log(q_\phi(\boldsymbol{\theta}|\mathbf{x}))]$$

$$= -\mathbb{E}_{U(\theta)p(\boldsymbol{\theta})p(\mathbf{x}|\theta)}[\log(q_\phi(\boldsymbol{\theta}|\mathbf{x}))],$$

where $U(\theta)$ is a constant $U(\theta) = c > 0$ at least on the posterior support and $U(\theta) = 0$ elsewhere. Then:

$$\mathcal{L}_d = -\iint U(\theta)p(\boldsymbol{\theta})p(\mathbf{x}|\boldsymbol{\theta}) \log(q_\phi(\boldsymbol{\theta}|\mathbf{x})) \, d\boldsymbol{\theta}d\mathbf{x}$$

$$= -\int p(\mathbf{x}) \int U(\theta)p(\boldsymbol{\theta}|\mathbf{x}) \log(q_\phi(\boldsymbol{\theta}|\mathbf{x})) \, d\boldsymbol{\theta}d\mathbf{x}$$

Since $U(\theta) > 0$ at least on the support of $p(\theta|\mathbf{x})$:

$$\mathcal{L}_d = -\int p(\mathbf{x})c \int p(\boldsymbol{\theta}|\mathbf{x}) \log(q_\phi(\boldsymbol{\theta}|\mathbf{x})) \, d\boldsymbol{\theta}d\mathbf{x}$$

 Since the integrand of the integral over θ is proportional to the Kullback-Leibler-divergence between the true posterior

 $p(\theta|\mathbf{x})$ and the inferred posterior $q_\phi(\boldsymbol{\theta}|\mathbf{x})$, $\mathcal{L}_d$ is minimized if and only if $q_\phi(\boldsymbol{\theta}|\mathbf{x}) = p(\theta|\mathbf{x})$ for all $\mathbf{x}$ on the support of $p(\mathbf{x})$.

Classifier of 'valid' simulations

The algorithm includes a classifier $U(\boldsymbol{\theta})$ trained to predict 'valid' simulations. We use a cross-entropy loss $\mathcal{L}_e$. We enforce the classifier $U(\boldsymbol{\theta})$ to be constant, with $U(\boldsymbol{\theta}) = c > 0$ at least on the posterior support and $U(\boldsymbol{\theta}) = 0$ elsewhere:

1. In order for $U(\boldsymbol{\theta})$ to be uniform, we parameterize it as a thresholded binary classifier.
2. To ensure that $c > 0$ at least on the posterior support, we choose the classifier threshold such that there are few false-negatives, i.e. the classifier accepts the parameters if these lie within the posterior support.

If we train the classifier $U(\boldsymbol{\theta})$ with a large enough number of simulations, so that some are 'valid', the trained classifier includes the posterior support. In order to sample from $U(\boldsymbol{\theta})p(\boldsymbol{\theta})$, we sample from the prior over parameters $p(\theta)$ and accept the sampled parameters according to the classifier output.

Inference of the posterior distribution given experimental data at 11°C

Overall, we performed three cycles of simulation and classifier training in order to learn the restricted prior. In the first round, we simulated 3 million parameter sets sampled from the prior. Among these, only 0.97% produced 'valid' summary features. We trained a classifier to detect parameter sets leading to 'valid' simulation outputs. We used a residual neural network with 80 hidden units, two blocks, a dropout rate of 43%, and a batchsize of 199. To deal with 'valid'/'invalid' unbalanced data, we subsampled 'invalid' samples in every epoch. We post-hoc tuned the threshold of the classifier such that the ratio of false-negatives was below 1% on a held-out test set. We then drew 3 million samples from the resulting restricted prior. Out of these, 5.17% produced 'valid' summary features. We then repeated this procedure and out of 3 million simulations from the resulting restricted prior, 8.45% produced good simulations. Overall, in comparison to Gonçalves et al. [13], we used half as many simulations (9 million versus 18.5 million), but generated a database of 'valid' simulations 2.5 times larger. We then used all 438,608 'valid' parameter sets to obtain the posterior distribution with SNPE (see Gonçalves et al. [13] for details). As deep neural density estimator, we chose a neural spline flow (NSF) [57] with 10 transform layers, each consisting of a residual block with two hidden layers, each with 200 hidden units.

Lastly, to ensure that the activity produced by samples from the posterior closely matched experimental data, we sampled 1 million parameter sets from the inferred posterior distribution and performed an additional rejection step, whereby posterior samples had to produce activity within a prescribed distance to the experimental data:

- cycle duration and burst durations deviated from the experimental features by a maximum distance of 0.02 standard deviations of all simulations accepted by the classifier, i.e. 20.6 ms for the cycle duration, and [15.0, 13.5, 11.5] ms for the burst durations (of AB/PD, LP, and PY neurons).
- duty cycles, phase gaps, phase delays, and phases deviated from the experimental features by a maximum distance of 0.2 standard deviations.

Out of 1 million samples from the posterior, 35,939 samples fulfilled all these criteria. Notably, these samples are no longer unbiased samples from the posterior distribution as estimated by SNPE, but they make up a database of model configurations whose activity closely matches experimental data.

Regression neural network

We performed a linear regression to identify the contribution of the circuit parameters to the total energy consumption using scikit-learn [58]. In order to test the robustness of the linear regression findings, we trained a regression network to identify directions in the parameter space predictive of total energy consumption. The regression network had the following characteristics: A Residual Network (ResNet) with one hidden layer with 20 hidden units, ReLU activation functions, and 50% dropout rate [59, 60]. We trained the network with a mean-squared error loss.

After training the regression network, we searched for directions that were most predictive of the network output $f(\cdot)$. To do so, we followed the procedure described in Constantine [61] and computed:

$$M = \mathbb{E}_{\boldsymbol{\theta} \sim p(\boldsymbol{\theta}|\mathbf{x}_o)}[\nabla_{\boldsymbol{\theta}} f(\boldsymbol{\theta}) \nabla_{\boldsymbol{\theta}} f(\boldsymbol{\theta})^T]. \tag{3}$$

Intuitively, M captures how much the regression function $f(\cdot)$ changes in different directions of the parameter space, computed as an expected value over posterior samples. We estimated this expected value with a Monte Carlo mean over 10,000 samples from the posterior distribution. We then computed the eigenvalue decomposition of M: The

470 eigenvectors of highest eigenvalue are directions in the parameter space along which the output of the regression
471 neural network is most sensitive to changes.

Sampling synaptic conductances, given energy efficient single-neuron configurations
472
473 In order to investigate whether efficient single-neuron parameters could lead to efficient and robust network activ-
474 ity, we first searched our database of $35,939$ network configurations for the five configurations that had the lowest
475 metabolic cost in each neuron individually. We combined these single neuron configurations to generate $5^3 = 125$
476 configurations of membrane conductances. For each of the configurations, we then sampled $1,000$ synaptic configu-
477 rations from the distribution:

$$p(\boldsymbol{\theta}_s|\boldsymbol{\theta}_m, \mathbf{x}_o) \propto p(\boldsymbol{\theta}_s, \boldsymbol{\theta}_m|\mathbf{x}_o), \tag{4}$$

478 where $\boldsymbol{\theta}_s$ and $\boldsymbol{\theta}_m$ are the synaptic and membrane conductances, respectively. We drew these samples with Markov
479 chain Monte Carlo: Specifically, we used Slice Sampling with axis-aligned updates [62]. We then simulated each of
480 these $5^3 \cdot 1000$ configurations. 72 out of the 5^3 configurations contained at least one sample that fulfilled our (distance
481 to experimental data) criteria, and 123 configurations contained a sample that fulfilled a slightly wider criteria (allowing
482 twice as much distance from the experimental data). For the remaining two configurations, we drew another 10,000
483 samples with MCMC and for each of them found at least one configuration whose activity fulfilled the slightly wider
484 criteria. The histograms in figures Fig. 5e,f are produced with all simulations that fulfilled the narrow criteria.

Posterior distribution given experimental data at 27°C
485
In order to infer the posterior distribution given experimental data at 27°C, we started by sampling 3 million param-
eter sets from the 31-dimensional posterior distribution at 11°C:

$$p(\boldsymbol{\theta}|\mathbf{x}_o^{11}) \propto p(\mathbf{x}_o^{11}|\boldsymbol{\theta})p(\boldsymbol{\theta}).$$

We then drew 3 million sets of Q_{10} values from the prior distribution over Q_{10} values (Q_{10} prior in Methods, Circuit
model of the crustacean stomatogastric ganglion). We simulated these 3 million parameter sets at 27°C, from which
approximately 18% were 'valid' and were used to train a deep neural density estimator (see Proof of convergence of
SNPE with classifier). The hyperparameters of the neural density estimator were the same as the ones chosen for the
inference at 11°C. Since this density estimator was trained on parameters sampled from the posterior distribution at
11°C, the inferred posterior is an approximation to:

$$p(\boldsymbol{\theta}|\mathbf{x}_o^{27}, \mathbf{x}_o^{11}) \propto p(\mathbf{x}_o^{27}|\boldsymbol{\theta})p(\boldsymbol{\theta}|\mathbf{x}_o^{11}) \propto p(\mathbf{x}_o^{27}|\boldsymbol{\theta})p(\mathbf{x}_o^{11}|\boldsymbol{\theta})p(\boldsymbol{\theta}),$$

486 where $\mathbf{x}_o^{11}$ and $\mathbf{x}_o^{27}$ are the features of the experimental data recorded at 11°C and 27°C, respectively. In other words,
487 the resulting posterior distribution matches prior knowledge about circuit parameters as well as experimental data
488 at 11°C and 27°C. Note that we inferred the posterior distribution at 11°C while ignoring the Q_{10} values because the
489 Q_{10} values, by definition, do not influence the circuit activity at the reference temperature (which is assumed to be
490 11°C).

Metabolic efficiency at 27°C
491
492 For panels Fig. 6e,f and Fig. 6g (pink plot), we analyzed 967 simulations that closely matched experimental data
493 recorded at 11°C and 27°C. For Fig. 6g (purple plot), we simulated, at 27°C, the $35,939$ circuit configurations that
494 match experimental data recorded at 11°C. Out of these, 8121 were robust, i.e. displayed pyloric activity at 27°C.

References
495

496 [1] J. Golowasch, L. Abbott, and E. Marder. Activity-dependent regulation of potassium currents in an identified neuron of the
497 stomatogastric ganglion of the crab cancer borealis. *Journal of Neuroscience*, 19(20):RC33–RC33, 1999.

498 [2] J. Golowasch, M. S. Goldman, L. Abbott, and E. Marder. Failure of averaging in the construction of a conductance-based neuron
499 model. *Journal of neurophysiology*, 87(2):1129–1131, 2002.

500 [3] M. S. Goldman, J. Golowasch, E. Marder, and L. Abbott. Global structure, robustness, and modulation of neuronal models.
501 *Journal of Neuroscience*, 21(14):5229–5238, 2001.

[4] A. A. Prinz, C. P. Billimoria, and E. Marder. Alternative to hand-tuning conductance-based models: construction and analysis of databases of model neurons. *Journal of Neurophysiology*, 90(6):3998–4015, 2003.

[5] A. A. Prinz, D. Bucher, and E. Marder. Similar network activity from disparate circuit parameters. *Nature Neuroscience*, 7(12):1345, 2004.

[6] G. M. Edelman and J. A. Gally. Degeneracy and complexity in biological systems. *Proceedings of the National Academy of Sciences*, 98(24):13763–13768, 2001.

[7] E. Marder and A. L. Taylor. Multiple models to capture the variability in biological neurons and networks. *Nature Neuroscience*, 14(2):133, 2011.

[8] J. N. MacLean, Y. Zhang, B. R. Johnson, and R. M. Harris-Warrick. Activity-independent homeostasis in rhythmically active neurons. *Neuron*, 37(1):109–120, 2003.

[9] J. N. MacLean, Y. Zhang, M. L. Goeritz, R. Casey, R. Oliva, J. Guckenheimer, and R. M. Harris-Warrick. Activity-independent coregulation of ia and ih in rhythmically active neurons. *Journal of Neurophysiology*, 94(5):3601–3617, 2005.

[10] R. N. Gutenkunst, J. J. Waterfall, F. P. Casey, K. S. Brown, C. R. Myers, and J. P. Sethna. Universally sloppy parameter sensitivities in systems biology models. *PLoS Computational Biology*, 3(10):e189, 2007.

[11] R. Grashow, T. Brookings, and E. Marder. Compensation for variable intrinsic neuronal excitability by circuit-synaptic interactions. *Journal of Neuroscience*, 30(27):9145–9156, 2010.

[12] T. O'Leary, A. C. Sutton, and E. Marder. Computational models in the age of large datasets. *Current Opinion in Neurobiology*, 32:87–94, 2015.

[13] P. J. Gonçalves, J.-M. Lueckmann, M. Deistler, M. Nonnenmacher, K. Öcal, G. Bassetto, C. Chintaluri, W. F. Podlaski, S. A. Haddad, T. P. Vogels, et al. Training deep neural density estimators to identify mechanistic models of neural dynamics. *Elife*, 9:e56261, 2020.

[14] A. Hasenstaub, S. Otte, E. Callaway, and T. J. Sejnowski. Metabolic cost as a unifying principle governing neuronal biophysics. *Proceedings of the National Academy of Sciences*, 107(27):12329–12334, 2010.

[15] B. Sengupta, A. A. Faisal, S. B. Laughlin, and J. E. Niven. The effect of cell size and channel density on neuronal information encoding and energy efficiency. *Journal of Cerebral Blood Flow & Metabolism*, 33(9):1465–1473, 2013.

[16] B. Sengupta and M. B. Stemmler. Power consumption during neuronal computation. *Proceedings of the IEEE*, 102(5):738–750, 2014.

[17] J. Astrup, P. M. Sørensen, and H. R. Sørensen. Oxygen and glucose consumption related to na+-k+ transport in canine brain. *Stroke*, 12(6):726–730, 1981.

[18] J. Astrup, P. M. Sørensen, and H. R. Sørensen. Inhibition of cerebral oxygen and glucose consumption in the dog by hypothermia, pentobarbital, and lidocaine. *Anesthesiology: The Journal of the American Society of Anesthesiologists*, 55(3):263–268, 1981.

[19] L. Sokoloff. Energetics of functional activation in neural tissues. *Neurochemical research*, 24(2):321–329, 1999.

[20] D. Attwell and S. B. Laughlin. An energy budget for signaling in the grey matter of the brain. *Journal of Cerebral Blood Flow & Metabolism*, 21(10):1133–1145, 2001.

[21] H. Alle, A. Roth, and J. R. Geiger. Energy-efficient action potentials in hippocampal mossy fibers. *Science*, 325(5946):1405–1408, 2009.

[22] M. B. Stemmler, B. Sengupta, S. Laughlin, and J. Niven. Energetically optimal action potentials. In *Advances in neural information processing systems*, pages 1566–1574, 2011.

[23] S. Onasch and J. Gjorgjieva. Circuit stability to perturbations reveals hidden variability in the balance of intrinsic and synaptic conductances. *Journal of Neuroscience*, 40(16):3186–3202, 2020.

[24] B. C. Carter and B. P. Bean. Sodium entry during action potentials of mammalian neurons: incomplete inactivation and reduced metabolic efficiency in fast-spiking neurons. *Neuron*, 64(6):898–909, 2009.

[25] B. Sengupta, M. Stemmler, S. B. Laughlin, and J. E. Niven. Action potential energy efficiency varies among neuron types in vertebrates and invertebrates. *PLoS Comput Biol*, 6(7):e1000840, 2010.

[26] G. Yi, Y. Fan, and J. Wang. Metabolic cost of dendritic ca2+ action potentials in layer 5 pyramidal neurons. *Frontiers in neuroscience*, 13, 2019.

[27] F. A. Roemschied, M. J. Eberhard, J.-H. Schleimer, B. Ronacher, and S. Schreiber. Cell-intrinsic mechanisms of temperature compensation in a grasshopper sensory receptor neuron. *Elife*, 3:e02078, 2014.

[28] R. M. Harris-Warrick, E. Marder, A. I. Selverston, M. Moulins, T. J. Sejnowski, and T. A. Poggio. *Dynamic biological networks: the stomatogastric nervous system*. MIT press, 1992.

[29] E. Marder and D. Bucher. Understanding circuit dynamics using the stomatogastric nervous system of lobsters and crabs. *Annu. Rev. Physiol.*, 69:291–316, 2007.

[30] J.-M. Lueckmann, P. J. Goncalves, G. Bassetto, K. Öcal, M. Nonnenmacher, and J. H. Macke. Flexible statistical inference for mechanistic models of neural dynamics. In *Advances in Neural Information Processing Systems*, pages 1289–1299, 2017.

[31] L. Stehlik, C. MacKenzie Jr, and W. Morse. Distribution and abundance of four brachyuran crabs on the northwest atlantic shelf. *Fishery Bulletin*, 89(3):473–492, 1991.

[32] M. J. Donahue, A. Nichols, C. A. Santamaria, P. E. League-Pike, C. J. Krediet, K. O. Perez, and M. J. Shulman. Predation risk, prey abundance, and the vertical distribution of three brachyuran crabs on gulf of maine shores. *Journal of Crustacean Biology*, 29 (4):523–531, 2009.

[33] C. J. Krediet and M. J. Donahue. Growth-mortality trade-offs along a depth gradient in cancer borealis. *Journal of Experimental Marine Biology and Ecology*, 373(2):133–139, 2009.

[34] L. S. Tang, M. L. Goeritz, J. S. Caplan, A. L. Taylor, M. Fisek, and E. Marder. Precise temperature compensation of phase in a rhythmic motor pattern. *PLoS Biol*, 8(8):e1000469, 2010.

[35] A. Moujahid, A. d'Anjou, F. Torrealdea, and F. Torrealdea. Energy and information in hodgkin-huxley neurons. *Physical Review E*, 83(3):031912, 2011.

[36] L. M. Alonso and E. Marder. Visualization of currents in neural models with similar behavior and different conductance densities. *eLife*, 8:e42722, 2019.

[37] S. A. Haddad and E. Marder. Recordings from the c. borealis stomatogastric nervous system at different temperatures in the decentralized condition, July 2021. URL https://doi.org/10.5281/zenodo.5139650.

[38] S. A. Haddad and E. Marder. Circuit robustness to temperature perturbation is altered by neuromodulators. *Neuron*, 100(3): 609–623, 2018.

[39] J. S. Caplan, A. H. Williams, and E. Marder. Many parameter sets in a multicompartment model oscillator are robust to temperature perturbations. *Journal of Neuroscience*, 34(14):4963–4975, 2014.

[40] L. M. Alonso and E. Marder. Temperature compensation in a small rhythmic circuit. *Elife*, 9:e55470, 2020.

[41] E. Marder. Variability, compensation, and modulation in neurons and circuits. *Proceedings of the National Academy of Sciences*, 108(Supplement 3):15542–15548, 2011.

[42] E. Marder, M. L. Goeritz, and A. G. Otopalik. Robust circuit rhythms in small circuits arise from variable circuit components and mechanisms. *Current Opinion in Neurobiology*, 31:156–163, 2015.

[43] G. Papamakarios, T. Pavlakou, and I. Murray. Masked autoregressive flow for density estimation. In *Advances in Neural Information Processing Systems*, pages 2338–2347, 2017.

[44] D. Greenberg, M. Nonnenmacher, and J. Macke. Automatic posterior transformation for likelihood-free inference. In *International Conference on Machine Learning*, pages 2404–2414, 2019.

[45] G. Le Masson, S. Przedborski, and L. Abbott. A computational model of motor neuron degeneration. *Neuron*, 83(4):975–988, 2014.

[46] W. B. Levy and R. A. Baxter. Energy-efficient neuronal computation via quantal synaptic failures. *Journal of Neuroscience*, 22 (11):4746–4755, 2002.

[47] B. Sengupta, M. B. Stemmler, and K. J. Friston. Information and efficiency in the nervous system—a synthesis. *PLoS Comput Biol*, 9(7):e1003157, 2013.

[48] M.-J. Cabirol-Pol, D. Combes, V. S. Fénelon, J. Simmers, and P. Meyrand. Rare and spatially segregated release sites mediate a synaptic interaction between two identified network neurons. *Journal of neurobiology*, 50(2):150–163, 2002.

[49] L. S. Tang, A. L. Taylor, A. Rinberg, and E. Marder. Robustness of a rhythmic circuit to short-and long-term temperature changes. *Journal of Neuroscience*, 32(29):10075–10085, 2012.

[50] A. Rinberg, A. L. Taylor, and E. Marder. The effects of temperature on the stability of a neuronal oscillator. *PLoS Comput Biol*, 9 (1):e1002857, 2013.

[51] T. O'Leary and E. Marder. Temperature-robust neural function from activity-dependent ion channel regulation. *Current Biology*, 26(21):2935–2941, 2016.

[52] J. A. Haley, D. Hampton, and E. Marder. Two central pattern generators from the crab, cancer borealis, respond robustly and differentially to extreme extracellular ph. *Elife*, 7:e41877, 2018.

[53] S. Gorur-Shandilya, E. M. Cronin, A. C. Schneider, S. A. Haddad, P. Rosenbaum, D. Bucher, F. Nadim, and E. Marder. Mapping circuit dynamics during function and dysfunction. *bioRxiv*, 2021.

[54] J. Ratliff, A. Franci, E. Marder, and T. O'Leary. Neuronal oscillator robustness to multiple global perturbations. *Biophysical Journal*, 2021.

[55] A. Tejero-Cantero, J. Boelts, M. Deistler, J.-M. Lueckmann, C. Durkan, P. J. Gonçalves, D. S. Greenberg, and J. H. Macke. Sbi–a toolkit for simulation-based inference. *arXiv preprint arXiv:2007.09114*, 2020.

[56] L. Abbott and E. Marder. Modeling small networks, 1998.

[57] C. Durkan, A. Bekasov, I. Murray, and G. Papamakarios. Neural spline flows. In *Advances in Neural Information Processing Systems*, pages 7511–7522, 2019.

[58] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

[59] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[60] N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

[61] P. G. Constantine. *Active subspaces: Emerging ideas for dimension reduction in parameter studies*. SIAM, 2015.

[62] R. M. Neal. Slice sampling. *The annals of statistics*, 31(3):705–767, 2003.

Supplementary material

Supplementary figures

Supplementary Figure 1. Full posterior distribution over circuit parameters given experimental data at 11°C. Panels on the diagonal are marginals, panels on the upper right are pairwise marginals. The first 24 parameters are membrane conductances, the last 7 parameters are synaptic conductances. All membrane conductances are maximal conductances and are given in mS/cm^2, all synaptic conductances are given in nS.

Summary features of prior samples
[st. dev. of samples]

Summary features of restricted prior samples
[st. dev. of samples]

Summary features of posterior samples
[st. dev. of samples]

Supplementary Figure 2. Summary features of activity produced by sampling from the prior, the restricted prior, and the posterior. Experimentally observed activity in green. The boxplots indicate maximum, 75% quantile, median, 25% quantile, and minimum. All summary features are z-scored with the mean and standard deviation of all simulations from prior samples.

Supplementary Figure 3. Accuracy of the enhanced version of SNPE versus accuracy in [13]. While we used half as many simulations (9 million versus 18 million), the accuracy of the method improved. (a) Median squared discrepancy between the experimentally measured activity and the activity produced by samples from the posterior. When using the classifier (red), the activity produced by posterior samples is closer to experimental activity than without the classifier (blue). (b) Reduction of mean squared discrepancy between our previous results and the presented method. All distances are computed after z-scoring the summary features with the mean and standard deviation of all prior samples.

Supplementary Figure 4. Neural network regression from circuit parameters onto the total energy consumption. (a) Performance of a neural network predicting the total energy from circuit parameters. (b) Eigenvalue-spectrum of the trained neural network reveals a single dominating direction (details in Methods). (c) The eigenvector corresponding to the strongest eigenvalue is similar to the linear regression weights w (Fig. 4c).

Supplementary Figure 5. Performance of linear regression. Left: Performance of linear regression from circuit parameters (taken from our database of 35, 393 models) onto energy per spike in the PY neuron. Right: Performance of linear regression from circuit parameters onto the average number of spikes within a burst.

Supplementary Figure 6. Influence of maximal conductance of transient calcium current on circuit function. Left: Voltage trace in the PY neuron during activity produced by two circuit configurations (black and red) which are identical apart from the magnitude of $\overline{g}_{CaT}$. Right: The average number of spikes per burst in the PY neuron for the two configurations. The configuration with higher $\overline{g}_{CaT}$ produces more spikes.

Supplementary Figure 7. Full posterior distribution over 31 circuit parameters and 10 Q_{10} parameters given experimental data at 11°C and 27°C.

Supplementary Figure 8. Energy consumption of the circuit at 11°C and at 27°C. Energy per spike (left) and number of spikes (right) for parameter configurations simulated at 11°C and 27°C. The energy per spike is smaller at higher temperatures, but the number of spikes is higher at higher temperatures.

Supplementary Figure 9. Analysis of a second experimental preparation. (a) Experimental data recorded at 11°C. (b) Sample from posterior distribution matches the experimental data. (c) Energy consumption of 2804 model configurations that closely match experimental data. (d) Weights w of a linear regression from circuit parameters onto total energy consumption.

Supplementary Figure 10. Tuning neurons individually, for a third experimental preparation. (a) Black dots: Energy consumed by each neuron separately. Black line: Linear regression (correlation coefficient $r = -0.003$, p-value $p = 0.39$; LP versus PY, $r = 0.19$, $p = 0.007$; AB/PD versus PY, $r = 0.006$, $p = 0.77$). (b) The activity produced by two parameter configurations produced with the strategy described in Fig. 5b. (c) A subset of the membrane (left) and synaptic (right) conductances for the configurations in panel (c). The membrane conductances are scaled with the following factors (left to right): 100, 100, 10,000, 100, 10,000. (d) Histogram over the total energy consumption of all 6926 model configurations in our database and the energy consumption of the configurations produced with the strategy described in Fig. 5b (red). (e) Histogram of the posterior log-probability for samples from the prior distribution (grey), for the 6926 models in our database (black), and for the configurations produced with the strategy described in Fig. 5b (red).

Supplementary Figure 11. Analysis of temperature robustness of a second experimental preparation. (a) Experimental data recorded at 27°C. (b) Sample from posterior distribution matches the experimental data. (c) Energy consumption at 11°C versus energy consumption at 27°C. (d) Green: Distribution of the energy consumption of circuits matching experimental data at 11°C. Purple: Distribution of the energy consumption of circuits that match data at 11°C and are robust at 27°C. Pink: Distribution of the energy consumption of circuits that match experimental data at 11°C and 27°C.

Supplementary Figure 12. Analysis of a third experimental preparation. (a) Experimental data recorded at 11°C. (b) Sample from posterior distribution matches the experimental data. (c) Energy consumption of 6926 model configurations that closely match experimental data. (d) Weights w of a linear regression from circuit parameters onto total energy consumption.

Supplementary Figure 13. Tuning neurons individually, for a second experimental preparation. (a) Black dots: Energy consumed by each neuron separately. Black line: Linear regression (correlation coefficient $r = -0.009$, p-value $p = 0.39$; LP versus PY, $r = 0.21$, $p = 0.0012$; AB/PD versus PY, $r = 0.059$, $p = 0.10$). (b) The activity produced by two parameter configurations produced with the strategy described in Fig. 5b. (c) A subset of the membrane (left) and synaptic (right) conductances for the configurations in panel (c). The membrane conductances are scaled with the following factors (left to right): 100, 10, 10,000, 100, 10,000. (d) Histogram over the total energy consumption of all 2804 model configurations in our database and the energy consumption of the configurations produced with the strategy described in Fig. 5b (red). (e) Histogram of the posterior log-probability for samples from the prior distribution (grey), for the 2804 models in our database (black), and for the configurations produced with the strategy described in Fig. 5b (red).

Supplementary Figure 14. Analysis of temperature robustness of a third experimental preparation. (a) Experimental data recorded at 27°C. (b) Sample from posterior distribution matches the experimental data. (c) Energy consumption at 11°C versus energy consumption at 27°C. (d) Green: Distribution of the energy consumption of circuits matching experimental data at 11°C. Purple: Distribution of the energy consumption of circuits that match data at 11°C and are robust at 27°C. Pink: Distribution of the energy consumption of circuits that match experimental data at 11°C and 27°C.