Precision dynamical mapping using topological data analysis reveals a unique hub-like *transition state* at rest

Manish Saggar[a*], James M. Shine[b], Raphaël Liégeois[c], Nico U. F. Dosenbach[d], Damien Fair[e]

[a]Department of Psychiatry and Behavioral Sciences, Stanford University, Stanford, CA, USA
[b]Brain and Mind Center, The University of Sydney, Sydney, New South Wales, Australia
[c]Institute of Bioengineering, École Polytechnique Fédérale de Lausanne, Switzerland
[d]Departments of Neurology, Radiology, Pediatrics and Biomedical Engineering, Washington University School of Medicine, St. Louis, MO, USA
[e]Department of Pediatrics, University of Minnesota Medical School, Minneapolis, MN, USA

* Corresponding Author: saggar@stanford.edu

Competing Interests Statement: No conflicts of interest to report.

Acknowledgements: This work was supported by an NIH Director's New Innovator Award (DP2; MH119735), an NIH Career Development Award (K99/R00; MH104605), and an MCHRI Faculty Scholar Award to M.S. The Midnight Scan Club data acquisition was supported by grants from the National Institute of Health (NS088590); the Jacobs Foundation (2016121703); and the Kiwanis Neuroscience Research Foundation to N.U.F.D. Funding for the Human Connectome Project data acquisition were provided by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research (as part of the Human Connectome Project, WU-Minn Consortium; Principal Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) and by the McDonnell Center for Systems Neuroscience at Washington University. R.L. was supported by the National Centre of Competence in Research - Evolving Language grant (51NF40_180888). D.F. was supported by grants from the National Institute of Health (MH096773, MH115357, and DA041148). The authors thank Timothy O. Laumann, Abraham Z. Snyder, and Ryan V. Raut for discussions and helpful comments on a draft of the manuscript. We also thank Ryan V. Raut for providing processed Midnight Scan Club dataset.

Tables: 0

Figures: 7

Words (in the main text): ~6500

Abstract

Even in the absence of external stimuli, neural activity is both highly dynamic and organized

across multiple spatiotemporal scales. The continuous evolution of brain activity patterns during

rest is believed to help maintain a rich repertoire of possible functional configurations that relate

to typical and atypical cognitive phenomena. Whether these transitions or "explorations" follow

some underlying arrangement or instead lack a predictable ordered plan remains to be

determined. Here, using a *precision dynamics* approach, we aimed at revealing the rules that

govern transitions in brain activity at rest at the single participant level. We hypothesized that by

revealing and characterizing the overall landscape of whole brain configurations (or states) we

could interpret the rules (if any) that govern transitions in brain activity at rest. To generate the

landscape of whole-brain configurations we used Topological Data Analysis based Mapper

approach. Across all participants, we consistently observed a rich topographic landscape in

which the transition of activity from one state to the next involved a central hub-like "transition

state." The hub topography was characterized as a shared attractor-like basin where all canonical

resting-state networks were represented equally. The surrounding periphery of the landscape had

distinct network configurations. The intermediate transition state and traversal through it via a

topographic gradient seemed to provide the underlying structure for the continuous evolution of

brain activity patterns at rest. In addition, differences in the landscape architecture were more

consistent within than between subjects, providing evidence of idiosyncratic dynamics and

potential utility in precision medicine.

1. Introduction

Spontaneous brain activity in the absence of sensory input is considered to be highly structured in both space and time[1] with amplitudes at least as large as stimulus-driven activity[2,3]. The ongoing patterns of cortical activity are thought to continually evolve over time and have been shown to encode multidimensional behavioral activity[4]. It is believed that the continuous evolution of cortical activity patterns could reflect multiple functions, namely, recapitulating (or expecting) sensory experiences[5–8], maintaining a rich repertoire of possible functional configurations[9,10], continuing top-down prediction/expectation signal for updating representation of the world[1], reflecting changes in the behavioral and cognitive states[11], and has been shown to be largely bistable[12–14]. However, it is not fully established whether transitions in intrinsic brain activity *follow* some underlying arrangement or instead *lack* a predictable ordered plan. Characterizing the rules underlying transitions in cortical activity has the potential to advance our understanding of the neural basis of cognition, and also to better anchor psychiatric disorders onto more robust biological features[15,16].

Since its inception, functional magnetic resonance imaging (fMRI) has been used to non-invasively measure blood oxygen level-dependent (BOLD) signal as a proxy for neural activity[17]. Several fMRI studies have significantly advanced our understanding of brain functioning in healthy and patient populations by successfully identifying static or long-time-averaged measures of intrinsic functional organization[18–23]. To measure brain's intrinsic functional architecture, i.e., in the absence of any task (resting-state), co-fluctuations in the BOLD signal are assessed (a.k.a., resting-state functional connectivity). Although the dynamical aspect of brain activity has long been known to be critical in electrophysiology, low spatiotemporal resolution of the human neuroimaging has slowed down embracing dynamical analysis of the brain[24]. However, time-varying analysis of fMRI data is gathering momentum due to recent advances in data acquisition methods, such as multi-band[25,26] and multi-echo[27] imaging that enhance spatiotemporal resolution of the acquired data and facilitate development of novel data analytics[28–36].

Time varying analyses of intrinsic human neuroimaging data have revealed richer dynamics than previously appreciated, including existence of: fast switching between metastable states[37]; intermittent periods of globally coordinated co-fluctuations across spatially distributed brain regions[30]; large-scale metastable cortical waves[24,38]; and hierarchical temporal organization at the group level[34]. Further, individual differences in time varying signals at rest have been associated with a wide range of cognitive and behavioral traits and even shown to be more sensitive than static (or averaged) functional connectivity[29]. Typically, a time varying analysis first characterizes a set of brain states at the group level, followed by examining individual differences in frequency or duration of such states. A brain state is typically defined as a transient pattern of whole brain activation (or functional connectivity) and is usually characterized by activation of (or connectivity in) known large-scale brain networks (a.k.a. resting state networks). Importantly, typical time-varying analyses (e.g., using sliding window-based approaches) have been prone to be affected by sampling variability and physiological artifacts in the fMRI data[39,40]. With that said, however, work using simultaneous wide-field optical imaging and whole-brain fMRI has established a direct link between resting-state hemodynamics in the awake and anesthetized brain and the underlying patterns of excitatory neural activity[41–43]. Thus, while the ongoing hemodynamics as measured by noninvasive fMRI

are coupled to excitatory neural activity, novel methods are required to carefully parse neuronal
dynamics while discounting artifactual transitions, with a goal towards deciphering the 'rules'
that determine whole-brain transitions across brain states. For example, it is unclear whether the
temporal transitions in brain activity (or connectivity) are best conceptualized as a continuous (or
gradual) evolution[44–46] or discrete (or binary) switches[47–49]. Further, it is also unclear whether
transition from one so-called brain state to another is direct or does the brain pass through a set
of intermediary states. Lastly, while previous work defined brain states at the *group level*, it is
unclear whether individual differences exist in terms of the configuration of brain states
themselves.
115
The low spatiotemporal resolution and high complexity of the fMRI data make the study of
whole-brain dynamics at the single person level (n=1) a challenging endeavor. Specifically, low
signal-to-noise ratio of the BOLD signal[50] and the typically short duration of resting state fMRI
scans (~5-15 min[51]) impedes precise characterization at the individual subject level. Further, high
cost of MR data acquisition and excessive participant burden limit the amount of data that can be
gathered. Fortunately, in the past few years, there is a growing momentum towards collecting
and sharing fMRI data using a precision functional mapping approach, where each participant is
sampled at multiple occasions (>=10) yielding hours' worth of data for each individual[52–55]. Due
to the vast heterogeneity in network topology from person to person, these approaches are
critical to unveiling basic principles of brain function and organization. We argue that a similar
approach for *precision dynamics* will be vital for deciphering the rules regarding how the human
brain dynamically adapts from one configuration to the next and how these transitions relate to
cognition and various psychopathologies[56–59].
129
In the current work, using a precision dynamics approach and the Midnight Scan Club (MSC)
dataset[53], we aimed at revealing the overall landscape of at-rest whole-brain configurations (or
states) at the single individual level. We hypothesized that by revealing and characterizing the
overall landscape we could interpret the rules that govern transitions in brain activity at rest. The
MSC dataset includes individually defined parcellations and ~5 hours of resting state fMRI data
for each participant – both of which allowed us to examine the topology and dynamics of at-rest
whole-brain configurations in an unprecedented detail. We also addressed previous
methodological limitations by using tools from the field of topological data analysis (TDA),
which are designed to learn the underlying topology (or shape) of high dimensional datasets that
are relatively sparse and noisy[60,61]. Specifically, here, we used the TDA-based Mapper approach
that generates the shape of the underlying dataset as a graph (a.k.a., shape graph)[32,62,63]. Mapper
has been previously shown to capture task-evoked transitions in the whole-brain activity patterns
at the highest spatiotemporal resolution[31]. Unlike previous time varying analytics, Mapper does
not require splitting or averaging data across space or time (e.g., windows) at the outset. Further,
Mapper does not require any a priori knowledge about number of whole-brain configurations and
does not impose strict assumptions about mutual exclusivity of brain states[37]. Lastly, the
presented results were not only validated in the MSC dataset using split half analysis, but were
also independently validated using a separate dataset from the Human Connectome Project[25]
(n=100, unrelated individuals).
149
150
151

152
2. Results

2.1 Estimating reliable landscape of whole-brain configurations at the single participant level

Our first aim was to utilize the TDA-based Mapper approach to reliably estimate individually specific landscape (or manifold) of whole-brain configurations. To ensure the replicability of our findings, we first split the MSC data for each participant into two halves (discovery and replication sets) – each with ~2.5 hours of data per participant. Thus, for each participant, out of a total of ten sessions (each 30 mins long), we assigned odd sessions to the discovery and even sessions to the replication set.

After rigorous preprocessing (see Methods and Gordon et al.[53] for details), the individually specific parcellated data were fed into the TDA-based Mapper pipeline[31], which consists of four main steps. First, the high-dimensional neuroimaging data are embedded into a lower dimension d, using a non-linear filter function f. Importantly, information loss incurred during dimensionality reduction is putatively recovered during the partial clustering step[64,65] (third step in the Mapper pipeline). To better capture the intrinsic geometry of the data, a nonlinear filter function based on neighborhood embedding was used[31] (see Methods for benefits of this non-linear approach). Second, overlapping d-dimensional binning is performed to allow for compression and to reduce any destructive effects of noise. Third, partial clustering within each bin is performed, where the original high dimensional information is used for coalescing (or separating) data points into nodes in the low-dimensional space and hence allows for partially recovering information loss incurred due to dimensionality reduction. Lastly, to generate a graphical representation of the data landscape, nodes from different bins are connected if any data points are shared between them. **Fig. S1** provides step-by-step representation of the Mapper pipeline.

In contrast to traditional graphical representations of neuroimaging data, nodes in the Mapper-generated shape graph represent clusters of highly similar whole-brain volumes (or time frames (TRs)), and edges connect any two nodes that share one or more whole-brain volumes. This approach naturally embeds temporal patterns within the spatial structure of the graph, which in turn confers several benefits for interrogating the spatiotemporal characteristics of the resting brain. For instance, using this shape graph, we can track how the resting brain dynamically evolves across different functional configurations at the individual-subject level. Importantly, our approach does not require any time-window averaging, which could potentially blur the data and has been shown to lead to artifactual findings due to head movement artifacts and sampling variability[39,40].

To reveal the rules that govern transitions between whole-brain configurations at-rest, we examined: (a) the topological properties of the shape graph, such as the degree distribution and existence of hubs; (b) the relationship between the Mapper embedding and canonical resting state networks; and (c) the transitions between whole-brain configurations. See **Fig. 1** for our analytical approach. In addition to individual variability in the characteristics of Mapper-generated landscapes, we also report the central tendency (or group average) of the dynamical landscape at rest. To account for linear properties of the data (e.g., serial auto-correlation) and sampling variability issues, we compared results with two null models, namely, the phase randomized null[66] and the multivariate autoregressive null model[40]. Lastly, the results revealed

from the MSC dataset were independently validated using a separate dataset from the Human
Connectome Project[25] (HCP; n=100 unrelated individuals).

Fig. 1: Estimation and characterization of the dynamical structure underlying transitions in intrinsic brain activity using our TDA-based Mapper approach. Here, we present data from a representative participant (MSC-01; odd sessions). [A] Individualized parcellated data from the highly sampled Midnight Scan Club (MSC) individuals[53] was split into two halves: odd sessions (2.5 hours) and even session (2.5 hours) sets. The Mapper approach was independently run on each set to generate the underlying structure as a graph. Each graph consists of nodes and edges, where the nodes could in turn contain multiple whole-brain volumes (or TRs; size of a node represents the number of TRs). The nodes are connected if they share TRs. [B] The Mapper-generated graph can be characterized in several ways. Here, we examine topological properties by annotating the graph nodes using nodal degree. [C] The graph can also be annotated with meta-information to characterize the mesoscale structure. Here, we show annotation using the activation of individual-specific resting state networks (RSNs). A pie-chart based annotation is used to reveal the proportion of time frames with each node belonging to different RSNs. [D] Similarly the graph can also be annotated using other available meta-information, e.g., session information.

2.2 Topological properties of the landscape reveal existence of hub nodes

We first characterized the Mapper-generated graphs by calculating nodal degree, which measures the strength (or number) of connections (or edges) per node. In the context of the shape graph, high degree nodes represent whole-brain activation patterns that are shared by many other nodes (i.e., are visited often in the temporal evolution of the data). The degree distribution for each participant and their corresponding splits (odd and even sessions) were further characterized to determine whether they deviated from what might be expected for linear properties of the data

(e.g., autocorrelation in the BOLD signal). We accomplished this goal by comparing the degree
distribution from the real data with multiple instances of the two pre-defined null models (phase
randomization and multivariate AR model). As evident from the degree distribution plots (**Fig.**
2A), the real data contained heavy (or fat) tail distributions as compared to both null models. The
heavy tail distribution is iconic for most real-world networks and indicates existence of highly
connected nodes[67–70]. This finding was independently replicated in both halves of the MSC data.
Statistical difference in the proportion of high-degree nodes (>20) in the real versus null data was
assessed using one-way ANOVAs for both odd ($F_{(2,27)}=5.27$, $p=0.012$) and even sessions
($F_{(2,27)}=7.15$, $p=0.003$).
233
Highly connected nodes that are also topologically central (i.e., influential) in the graph are
known as hub nodes. Hub nodes are hypothesized to act as focal points for the convergence and
divergence of information in the network[70]. Existence of hub nodes in the Mapper-generated
graph would indicate the presence of nodes (or whole-brain configurations) that are visited often,
potentially as intermediate (or transition) state. To examine the existence of hub nodes in the
Mapper-generated landscapes, we estimated the closeness centrality of highly connected
nodes[71,72]. This measure associates the nodes with shortest average path lengths as being the
most influential (or central) for the graph. Nodes with high closeness centrality can receive
information from other parts of the network in a short time (and *vice versa*). Across both halves
of the data and all participants, topologically central highly connected hub nodes occurred in the
shape graph (**Fig. 2B** highlights the hub nodes in a representative participant and supplementary
figure **Fig. S2** shows hub nodes across all MSC participants).
246
247

[A]

Odd sessions (~2.5 hours data)

Even sessions (~2.5 hours data)

248
Fig. 2: Characterizing the Mapper-generated graph using degree distribution. [A] Degree distributions
averaged across the ten participants, separately for odd and even sessions. For examining linear vs.
nonlinear aspects, two null models were used, namely, the phase randomized null and the multivariate
autoregressive null model. As evident from the degree distribution plots, real data were significantly fat
tailed (>20) compared to both nulls. This finding was independently replicated in both halves of the data.
The shaded area represents standard error around the mean (S.E.M.). [B] Mapper-generated graphs for a
representative participant (MSC-01), highlighting hub nodes (i.e., nodes with high degree (>20) and high
centrality (top 1%)). Similar plots were observed across all MSC dataset participants (see **Fig. S2**).

Although substantial data censoring was performed to reduce the impact of head movement
related artifacts, several additional analyses were performed to examine whether the observation

of high degree (and hub) nodes was associated with such artifacts. First, we examined whether
the presence of high degree nodes was associated with head movement or global signal
variations. No difference in framewise displacement (FD) or global signal was observed between
brain volumes represented by high and low degree nodes of the shape graph (ps>0.15 for FD and
ps>0.75 for global signal), for either split of the data. Second, we examined whether the
percentage of frames censored due to head movement was related with percentage of high degree
nodes. No significant relation was observed of either splits of the data (ps>0.20). Third, we
applied frame censoring to the data generated from null models to examine whether the presence
of high degree nodes was merely due to temporal masking. As shown in supplementary **Fig. S5**,
high degree nodes were not present in the null data even after frame censoring.
270
Further, parameter perturbation analysis was performed to make sure topological properties of
the graph were stable across a moderate range of Mapper parameters and the high degree nodes
in the real data were not an artifact of Mapper parameters (see Methods). Similar work was
previously done to show Mapper-generated graphs were stable across different parameter
combinations[31]. As shown in supplementary **Fig. S6**, for a large portion of Mapper parameter
values, the proportion of high-degree nodes in the real data were significantly higher than null
data.
278
279   Overall, the presence of hub nodes in the dynamical landscape (across all participants) provides
280   evidence for whole-brain configurations that i) are often visited during rest; ii) are highly
281   conserved at the individual subject level; and iii) may act as a 'switch' between different
282   configurations to putatively organize the spontaneous activity during rest.
283
2.3 Hub nodes represent uniform (mean) activation across all RSNs, whereas peripheral
nodes represent increased activation in one (or more) RSNs
To relate Mapper-generated graphs to canonical neuroanatomical depictions of the resting brain,
we annotated nodes in the Mapper graph using the relative engagement of a set of canonical
large-scale resting state networks (RSNs). Importantly, we leveraged a set of individually-
defined network assignments that were pre-defined for individuals in the MSC dataset[53]. **Fig.**
3A-B shows a Mapper-generated graph for a representative participant (MSC-01, odd sessions),
where each node is annotated by activation in the RSN. In this view, each node is annotated
using a pie-chart notation to show the proportion of brain volumes (or TRs) that have any RSN
activated (above certain threshold). The mean signal for each RSN was z-scored and a threshold
of 0.5 S.D. above the mean was used to denote activation of an RSN (other thresholds produced
similar results).
296
As shown in **Fig. 3C**, the topography of the Mapper-generated landscape provides important
insights into the temporal architecture of the resting brain. Topologically highly connected and
central hub nodes contained brain volumes in which no characteristic RSN was activated above
the mean, whereas nodes with brain volumes dominated by one (or more) RSN(s) tend to occupy
the peripheral corners of the landscape. The maps for all individual subjects demonstrated this
same basic pattern, although there was evidence to suggest that different combinations of RSNs
were dominant in different individuals. For instance, the default mode, ventral attention, and
auditory networks clearly dominated the periphery of MSC-01 landscape, across both splits of

the data, but other participants had a different combination of networks dominating their
landscapes (**Fig. S3**).
307

[A] MSC-01 odd sessions

[B] MSC-01 even sessions

Legend:
- Default Mode
- Visual
- Ventral Attn.
- Salience
- Fronto-parietal
- Dorsal Attn.
- Cingulo-oper.
- Somato-motor
- Auditory
- Motor
- None of the above

[C]

Nodes **dominated** by increased activation in the **AUD**, followed by SM network.

Nodes **dominated** by increased activation in the **VAN**, followed by VIS network.

Hub nodes **uniformly** represent all networks

Nodes **dominated** by increased activation in the **DMN**, followed by MOT, SAL, FRP, and DAN.

Individual **specific** brain parcellation for MSC-01

308
309

Fig. 3: Annotating Mapper-generated graphs based on individual-specific large-scale resting state networks (RSNs). **[A-B]** Mapper-generated graph for a representative participant (MSC-01; **[A]** odd and **[B]** even sessions) are shown. Here, each node is annotated by activation in the known large-scale resting state networks. Each node is annotated using a pie-chart to show the proportion of RSNs activated within each node. As evident, for MSC-01, for both odd and even sessions, the Mapper-generated graph has mainly three networks dominating on the periphery of the dynamical landscape: default mode, ventral attention, and auditory network. **[C]** Zoomed-in view of the Mapper graph generated using MSC-01 odd sessions. The nodes with dominating RSNs are located more towards the periphery of the landscape, while the hub nodes of the landscape are not dominated by any RSN and rather have uniform mean-level distribution across all RSNs. Four zoomed-in circles highlight four exemplary nodes, where the peripheral nodes have one (or more) RSNs in majority and the central node has no network dominating. Box plots represent activation (z-scored) in the corresponding RSNs across all time frames (TRs) within each highlighted node. We also present *representative* whole-brain activation maps for each of the three peripheral nodes, thresholded using mixture modeling[73]. The inset on the bottom shows individual-specific parcellation for the participant MSC-01.

2.4 RSN-based topography of landscapes is highly subject specific and stable across sessions

To quantify the subject-specificity and examine whether Mapper-generated landscapes were stable within participants, we computed similarity between RSNs in terms of their co-localization on the Mapper-generated graphs. If two networks are co-localized on the graph, then they activate (or deactivate) synchronously. **Fig. 4A-B** presents network similarity matrices for three representative participants across their odd and even sessions. As evident, qualitatively, the network similarity matrices are comparable across odd and even sessions. To quantify subject specificity in terms of network similarity, we compared network similarity matrices across sessions and participants using Pearson's correlation. As evident in **Fig. 4C,** high within-participant correspondence (i.e., high similarity between odd and even sessions) for network similarity matrices was observed as compared to between participant correspondence, suggesting dynamical landscapes are subject-specific and stable (over sessions).

Lastly, we computed the central tendency of the dynamical landscape topography by averaging the network similarity plots across participants. As evident in **Fig. 4D**, the group averaged topography presents a different picture than the individual topographies. Across both halves of the data, group-averaged topography represents more synchrony between higher order cognitive networks (e.g., default mode, fronto-parietal, etc.) than unimodal sensorimotor networks (e.g., visual, auditory, etc.). However, this discrimination between network types is evident due to group averaging and is not necessarily present at the individual participant level. At the participant level, subject-specific combinations of higher order cognitive networks and unimodal sensorimotor networks are observed to be in synchrony. In summary, individual subjects demonstrated idiosyncratic, yet highly replicable, topological signature at the level of canonical resting state networks.

352
Fig. 4: Dynamical landscapes and their organization are subject specific. [A-B] Mapper-generated graphs
annotated by RSN activation for two representative participants (MSC01-02) are shown. Both split halves
(odd and even sessions) are shown for each participant. For each half, the figure also shows a similarity
(correlation) matrix between RSNs, where high correlation between two RSNs suggest co-location on the
Mapper-generated graph. As evident through Mapper-graph annotations and between network
correlations there was high degree of similarity between two halves of the same participant. **[C]** To
quantify between- vs within-participant correspondence across network similarity matrices, network
similarity matrices were compared across split halves from all participants. As shown in the between
subject matrix, high correspondence was observed for within-participant matrices, suggesting dynamical
landscapes demonstrated idiosyncratic, yet highly replicable, topological signature at the level of
canonical resting state networks. **[D]** Central tendency of the dynamical landscape, averaged over ten
highly sampled individuals, for odd and even sessions.
365
366

2.5 Traversal on the Mapper-generated landscape revealed a topographic gradient with hub-nodes as a putative transition state

Next, we used a variance-based approach to examine whether the traversal on the landscape - i.e. going from one corner to the next (or towards the center) – was smooth (i.e., continuous) or bumpy (i.e., discrete). To this end, we estimated the mean activation for each RSN (across all the brain volumes) within each node, followed by estimating variation (standard deviation; S.D.) in the mean network-level activation across all RSNs. High variance (or S.D.) indicated dominance of one or more RSNs, whereas low variance indicated uniformity across mean RSN activation. As shown in **Fig. 5A** (using a representative participant, MSC-01), annotating Mapper-generated graphs using this variance-based approach revealed a *topographic gradient* in the dynamical landscape, where the peripheral nodes had higher variance with a continual decrease in variance when going towards the center of the graph. To further illustrate the gradient between peripheral dominating nodes and central hub (non-dominating) nodes, using MSC-01, **Fig**. **5A** shows three trajectories (one for each of the three dominating networks) and the corresponding boxplots for a sample of nodes from each trajectory – starting from the dominating node on the periphery and moving towards the hub (or non-dominating) nodes. As evident, peripheral nodes represent time frames where one or more RSNs were more activated than others, while as one traverses towards the center of the graph the nodes represent time frames with uniform mean-level activation across all RSNs. **Fig. 5B** shows average distribution of S.D. values, over ten MSC participants, for hub nodes (blue) and other nodes (orange). As evident, the hub nodes had significantly lower S.D. values than non-hub nodes (for both splits of the data; odd: $F(1,18)=132.96$, $p = 9.57 \times 10^{-10}$ and even: $F(1,18)=102.7$, $p=7.3 \times 10^{-09}$) – suggesting uniform distribution across all RSNs. Similar gradients were observed across all ten MSC participants (**Fig. 5C** and **Fig. S4**).

Fig. 5: Annotating the traversal on Mapper-generated landscape using a variance-based approach revealed a dynamical *topographic gradient*. To quantify the variation in RSN-based dominance, we first estimated mean activation for each RSN across the time frames within each node, followed by estimating variation in mean activation across RSNs. High variance (or S.D.) indicated dominance of one or more RSN while low variance (or S.D.) indicated uniformity across RSN activation. **[A]** Annotating Mapper-generated graphs using variance-based approach revealed a dynamical *topographic* gradient, where the peripheral nodes had higher variance with a continual decrease in variance when going towards the center of the graph. The graph is shown from a representative participant (MSC-01; odd sessions). Three trajectories are shown, starting from peak dominance for each of the three RSNs (default mode, ventral attention, and auditory) and ending towards the middle of the graph with nodes of no particular network

dominating. Boxplots, for representative nodes on each trajectory, represent activation (z-scored) in the
corresponding RSNs across all time frames (TRs) within each represented node. **[B]** Group averaged
distribution of S.D. values, over ten MSC participants, for hub nodes (blue) and other nodes (orange) is
shown, with S.E.M. as shaded value. Evidently, the hub nodes had significantly low variance across mean
RSN activation (indicating uniformly distributed RSN), while the non-hub nodes were highly variant across
mean RSN activation. **[C]** Shows variance-based annotation of Mapper graphs for two other participants
from MSC dataset (odd sessions). The topographic gradient was observed consistently across
participants and for both even and odd sessions (see **Fig**. **S4**).

To confirm whether the brain configuration represented by the hub nodes does indeed act as a
putative switch, we examined changes in brain activation patterns in the time domain, i.e., at the
single time frame (or brain volume) level. The RSN-based proportions from each graph node
were propagated to the individual time frames (or TRs) represented by that node. For nodes
dominated by any particular RSN, the encompassing TRs were assigned the dominant RSN. For
hub nodes, where RSNs were uniformly distributed, the encompassing TRs were assigned a new
label (Hub). **Fig. 6A** depicts labels for each TR, across the ten MSC participants, separately for
the two splits of the data. To better characterize transitions in RSN-based states we estimated the
discrete-time finite-state Markov chains[74] for each participant and data half. Note the strong
visual similarity between rows of the two session matrices.

Fig. 6B shows transition probabilities estimated from the Markov chain estimation averaged
across all participants, separately for the two splits of the data. While estimating Markov chains
and associated transition probabilities, we ignored putatively artifactual transitions associated
with frames discarded due to head movement and due to stitching the sessions together. As
evident from the estimated transition probabilities, brain configuration represented by the hub
nodes (or our putative transition state) was observed to be the most sought-after destination from
any other RSN-dominated state. **Fig. 6C** shows the same result at the individual participant level,
such that from any other RSN-dominant state the brain was more likely to transition to the hub
transition state – providing evidence for the hub state to be a likely intermediary between any
two RSN-dominating states. Transition probabilities can also be represented as a graph (show in
Fig. 6D). Lastly, we observed the transition probabilities to be highly subject-specific and
reliable across sessions (**Fig. 6E**). A one-way ANOVA showed transition probability matrices
across the two halves of data were more similar within participant (highly correlated) than across
participants ($F(1,398) = 307.86$, $p=1.83 \times 10^{-51}$).

In summary, traversal directly on the Mapper-generated landscape revealed a continuous
evolution of brain dynamics – a *dynamic topographic gradient*. Similar traversal in the time
domain (at single frame level) revealed that the brain configurations represented by hub nodes
acted as a putative switch (or a transition state) between different RSN-dominated
configurations. Further, the transition probabilities between states were individual-specific,
indicating a putative future application in precision medicine.

Fig. 6: Traversal in the temporal domain at the single frame level. [A] Depicts transitions in brain activation over time frames in terms of dominant individual-specific RSNs (or hub-like states). Each time frame (TR) was labeled from the Mapper-generated shape-graphs by propagating the RSN-based annotation from each graph node to the time frames represented by that node. In addition to RSNs, a new label representing hub-nodes was also generated. As evident, hub state was often visited by participants across both data splits. Only showing a subset of timeframes (first 600 frames) for each participant for ease of viewing. **[B]** A discrete-time Markov chain was estimated using RSN-based labels for each participant and data split. While estimating transition probabilities, transitions due to motion censoring and session boundaries were discarded. Here, we present transition probability matrix averaged over all 10 MSC participants. Diagonals were suppressed to better illustrate transition probabilities across states. The hub state was observed to be the most sought-after destination from any other state. **[C]** Boxplots

462   depicting high probability of transitioning into the hub state from any other state, across all participants.
463   **[D]** Estimated Markov chain averaged across all participants. As evident, the hub-state was observed to
464   be most central and with highest in-degree. **[E]** The transition probability matrices (as show in **B**) were
465   reliably estimated at the individual participant level (i.e., high within-participant similarity), indicating a
466   putative application in precision medicine approaches.
467
2.6 Replicating main results in an independent dataset
Although split-half data validation was performed for the MSC dataset, we further replicated the
main results in an independent multi-session resting state fMRI dataset (100 unrelated
participants from the Human Connectome Project (HCP)[25]). In the HCP dataset, four 15 min
sessions of resting state scans were acquired over a period of two days. Thus, for each individual,
we could analyze up to 1 hour of resting state fMRI data. It is important to note that the HCP
data were substantially lower in scan duration than the MSC dataset (with 5 hours of resting state
fMRI data per individual). Further, instead of using individually-defined parcellation, we used a
group parcellation (Gordon atlas with 333 brain regions[75]).
477
After generating Mapper landscapes for each HCP participant, we first compared the degree
distribution of graphs generated from real versus null data (from phase randomization and
multivariate AR models). Like the MSC data, the HCP data also showed heavy (fat) tail
distributions as compared to both null models. Statistical difference in the proportion of high-
degree (>20) nodes in the real versus null data was assessed using one-way ANOVA ($F(2, 225)$
$= 288.11$, $p = 8.88 \times 10^{-63}$; **Fig. 7A**). Mapper-generated landscapes from the HCP data also
contained hub-nodes (**Fig. 7B**).
485
Next, we annotated Mapper-generated graphs using the relative engagement of a set of canonical
large-scale resting state networks (RSNs). As opposed to individually-defined networks for the
MSC dataset, we used a group parcellation (Gordon atlas with 333 brain regions[75]) for the HCP
data. Results are shown for three representative participants in the **Fig. 7C**. We observed highly
connected and central hub nodes contained brain volumes where no particular RSN was
activated, whereas nodes with brain volumes dominating from one particular RSN tend to
occupy the peripheral corners of the landscape. The maps for individual subjects all
demonstrated this same basic pattern, although there was evidence to suggest that different
combinations of RSNs were dominant in different individuals.
495
Lastly, for the HCP dataset, we examined traversal on the landscape as well as temporal
evolution of brain activation patterns at the single time-frame level. Using a variance-based
approach, as for the MSC-dataset, we again observed a *smooth topographic gradient* in the
dynamical landscape of HCP participants, where the peripheral nodes had higher variance with a
continual decrease in variance when going towards the center of the graph (**Fig. 7C-D**). For the
temporal evolution of brain activation patterns at the single TR level RSN-based proportions
from each graph node were propagated to the individual time frames (or TRs) represented by that
node. **Fig. 7E** depicts RSN-based labels for each TR, across the 30 representative HCP
participants. Using discrete-time finite-state Markov chains, we also estimated transition
probabilities, while ignoring putatively artifactual transitions associated with frames discarded
due to head movement and due to stitching together sessions. In parallel to the MSC data, the
HCP data also provided evidence for the hub-state to be the most sought-after destination from
any other RSN-dominated state; thereby providing a putative role of intermediating between
other RSN-dominant states (**Fig. 7F-G**).

510
511
Fig. 7 Replicating results using an independent dataset from the Human Connectome Project (HCP). [A]
Degree distribution of graphs generated from the real versus null data (from phase randomization and
multivariate AR models) revealed heavy (fat) tail distributions in the real data. **[B]** Highlight hub nodes for
three representative participants. **[C]** Annotating Mapper-generated graphs using the relative engagement

of a set of canonical large-scale resting state networks (RSNs). Like MSC data, the HCP dataset also
revealed that highly connected and central hub nodes contained brain volumes where no particular RSN
was activated, whereas nodes with brain volumes dominating from one particular RSN tend to occupy the
peripheral corners of the landscape. Using a variance-based approach, like the MSC-dataset, we again
observed a *smooth topographic gradient* in the dynamical landscape of HCP participants. **[D]** Traversal in
the temporal domain at the single frame level for 30 representative HCP participants. Only showing a sub-
set of timeframes for ease of view. Color depicts transitions in brain activation over time frames in terms
of dominant individual-specific RSN (or hub-like state). **[E]** Group averaged distribution of S.D. values, over
all the HCP participants, for hub nodes (blue) and other nodes (orange) is shown, with S.E.M. as shaded
value. **[F]** Group averaged transition probability matrix derived using Markov chains, indicating the hub-
state to be the most sought-after destination from any other RSN-dominated state. Diagonal values were
set to zero for ease of visualization. **[G]** Estimated Markov chain for two representative participants. As
evidence the hub-state was observed to be most central and with highest in-degree.
529
3. Discussion
Understanding how the brain dynamically adapts its distributed activity in the absence of any
extrinsic stimuli lies at the core of understanding cognition. Although several innovative
approaches have been developed to study the dynamical properties of intrinsic brain activity at
rest, the organizational principles governing transitions in spontaneous activity are not fully
understood. For example, it is unclear whether transition from one brain state to another is direct,
or whether the brain passes through a set of characteristic intermediary states. Further, while
previous work defined brain states at the group level, it is unclear whether individual differences
exist in terms of how the brain states themselves are configured. Lastly, more work is needed to
understand whether temporal transitions in brain activity are best conceptualized as continuous
or discrete. To address these foundational questions, using a precision dynamics approach at the
single participant level, we constructed the overall landscape of whole-brain configurations at
rest. Altogether, four robust findings are observed: (1) across all participants, the landscape of
whole-brain configurations contains centrally located hub-nodes that are often visited and likely
acted as a *switch* or transition state between different configurations to organize the spontaneous
brain activity; (2) transitions occur as a smooth dynamic topographic gradient in the landscape,
suggesting a continuous (as opposed to discrete) setup for brain state transitions at rest; (3)
importantly transition probabilities between one state to another, at the level of a single time
frame, are subject-specific and provide a stable signature of that individual; and (4) while the
hub-nodes are characterized by a uniform representation of canonical RSNs, the periphery of the
landscape is dominated by a *subject-specific* combination of RSNs (which are also stable across
sessions). All the findings reported in this work are corroborated using split-half validation and
replication in an independent dataset. Together, using precision dynamics we identify several
rules or principles organizing spontaneous brain activity.
554
We begin the discussion by first providing a coarse viewpoint of our results that aligns well with
previous and more recent works that have identified brain dynamics at rest as a bistable
phenomenon. We then dive deeper into the rich subject-specific idiosyncrasies that our work
revealed as our approach allowed precision analytics. We then provide a discussion on how our
approach can putatively address common limitations of the previous work. Lastly, we provide
limitations of our work and avenues for future applications.
561
Coarse viewpoint: *bistable brain dynamics at rest*
From a coarse vantage point, the presence of low-amplitude (or close to mean activation) hub
configurations versus high-amplitude peripheral configurations points towards bistable brain

dynamics at rest. This bistable phenomenon is in line with the previous theoretical[12–14] and recent
empirical work that has also shown brain dynamics during the resting state to be predominantly
bistable[34,76,77]. In contrast to the null models, real data revealed significantly higher numbers of
hub nodes that were centrally located in the landscape and were representing whole-brain
configurations with mean-level activity across all RSNs. The periphery of the landscape, on the
other hand, was representative of one or a few dominant RSNs.
571
Using Hidden Markov Models (HMM), van der Meer and colleagues recently reported brain
dynamics during rest to be primarily driven by whole-brain configurations where all RSNs were
uniformly expressed with amplitude close to mean network activities, while configurations with
dominant RSNs were only evident sporadically[76]. At the coarse level, our results are in line with
these findings as we also observed intrinsic brain activity to be largely driven by whole-brain
configurations with uniform RSN representation (i.e., hub-nodes), while configurations with
dominant RSNs (i.e., peripheral nodes) were evident sporadically. However, it is important to
note that we used precision connectomics data (with longer duration scans) and individual-level
definition of brain configurations (as opposed to group-level in case of HMM). These data and
methodological enhancements led us to examine finer details about resting brain dynamics as
detailed in the next sub-section.
583
In another work, also using HMMs, Vidaurre and colleagues found that transitions in intrinsic
brain activity are stochastic and cycles between two major meta-states, where the first meta-state
was associated with unimodal networks (i.e., sensorimotor) and the second meta-state involves
regions related to higher order cognition[34,78]. Across individuals, the authors observed one of the
two meta-states to be dominant, such that the brain cycled between networks within a meta-state
more frequently than across meta-states. To anchor the topographical properties of the observed
landscape of whole-brain configurations, we computed similarity between RSNs in terms of their
co-localization on the Mapper-generated graph. Co-localization of two networks on the Mapper-
generated graph implies higher chances of co-activation. As shown in **Fig. 4D**, at the group-
level, we also observed a hierarchy of network co-localization, broadly separating unimodal
sensorimotor and higher-order cognitive networks. This group-level hierarchy was stable across
sessions. However, we also observed individual differences in network co-localization that were
highly subject-specific and not exactly following the hierarchy between unimodal and higher-
order networks, suggesting the promise of precision dynamics over group-level approaches.
598
In another recent work, Esfahlani and colleagues showed bistable brain dynamics at rest using
edge-level co-fluctuations. The authors observed the resting brain to oscillate between high- and
low-amplitude edge-level co-fluctuations. Further, the authors showed that the relatively short-
lived high-amplitude edge co-fluctuations i) drove the functional organization of the resting brain
(estimated using functional connectivity; rsFC) ii) were observed to be highly correlated with
high-amplitude BOLD (activity) fluctuations; and iii) were more similar within than between
subjects[77,79]. Although we examined transitions in whole-brain activity (as compared to co-
fluctuations between regions), we also observed the amplitude-level dichotomy, such that the
peripheral nodes of the landscape contained high-amplitude network-specific activations while
the hub-nodes contained mean-level low-amplitude activations. We also found that the co-
localization of RSNs (primarily driven peripheral nodes) were highly subject specific.
610

From the metabolic point of view, Zalesky and colleagues showed that the resting brain
dynamically transitions between high- and low-efficiency states[30]. The high efficiency states
were characterized by global coordination across brain regions, thus optimizing information
processing at a putatively larger expense of metabolic energy. The low efficiency states on the
other hand were characterized by lack of global coordination and putatively requiring minimal
metabolic expenditure. Although our results are based on whole-brain activation patterns and do
not use sliding windows, the whole-brain configurations represented by hub nodes could
putatively require minimal metabolic expenditure due to the low or close to mean activation
amplitude, whereas the configurations represented by the peripheral nodes could potentially
require high metabolic expenditure as they show high amplitude network-specific activation. It is
important to note that the approaches that focus on co-fluctuations between brain regions might
miss brain configurations represented by hub-nodes due to their low-amplitude and putatively
low co-fluctuations between brain regions. Future work is required to carefully combine
activation-based fluctuations in brain dynamics with fluctuations in coordination across brain
regions to better understand how changes in network activations relate to co-fluctuations.
626
Fine viewpoint: *rich and idiosyncratic intrinsic brain*
Our approach was developed to examine brain activity dynamics at the single participant level,
as opposed to previous approaches that have used group-level data to define states[30,34,76]. Thus,
along with precision connectomics data, our precision dynamics approach facilitated finer
examination of dynamical organization at rest than before. Although across participants we
observed bistable brain dynamics of transitioning between hub and peripheral states, our
approach also revealed a large degree of individual variability in terms of the configuration of
peripheral nodes. Different combinations of resting state networks dominated peripheral nodes,
albeit these combinations were highly subject-specific and consistent across sessions. Further,
estimated temporal transition probabilities between RSN-dominated states were also more
similar within- than between-participants. Overall, pointing towards future application of our
approach in precision medicine.
639
Examining the traversal on the landscape as well as across the individual timeframes suggest that
the brain configurations represented by hub-nodes were putatively acting as a *transition state*
between different parts of the landscape (and respective brain configurations or states). At the
single timeframe level, the hub state was also observed to be the most sought-after destination
from any other RSN-dominated state. Thus, suggesting a putative intermediary and faciliatory
role of the low (or close to mean) amplitude hub states in enabling neural *switching* between
high-amplitude RSN-dominated states. Descriptively, the hub-nodes can be thought of serving a
role akin to transportation hubs (e.g., the Grand Central Station for trains), such that these hub-
nodes facilitate efficient travel as well as cost-effective transportation architecture. It is also
possible that the hub nodes represent washout (or recovery) configurations of the brain between
high-amplitude brain states represented by the peripheral nodes. Future work using our precision
dynamics approach in conjunction with theoretical biophysical modeling[80] and neuromodulation
experiments[81] is needed to better understand how the hub-states facilitate transitions in the
intrinsic brain.
654
When the Mapper-generated graphs were annotated by variability in mean activation across
RSNs, a smooth topographic gradient was consistently observed across all participants. The

spontaneous brain activity was observed to be spatiotemporally organized in a continuous
gradient with hub- and peripheral-nodes at the opposite ends of the spectrum. Recent work has
shown existence of spatial gradients that provide organizational principle for the anatomical
organization of large-scale brain networks as a spectrum from unimodal to heteromodal
networks[82]. Here, we provide evidence for a dynamical topographic gradient organizing
spontaneous brain activity at rest. Looking forward, our precision dynamics approach can be
used to understand differences in temporal organization across various mental health disorders.
664
Methodological advances: *addressing previous issues*
Our TDA-based Mapper approach provides a novel avenue to conceptualize fluctuations in brain
dynamics at rest, while addressing several limitations with similarly aimed previous approaches.
Broadly speaking, most of the previous approaches conceptualized transitions in the at-rest brain
by either estimating inter-regional (or inter-voxel) co-fluctuations over time (e.g., sliding
window Pearson's correlation[44], dynamical conditional correlation[45], and multiplication of
temporal derivatives[46]) or by exploring brain activations on the basis of sparse events (e.g., co-
activation patterns[83], paradigm-free mapping[48] and point process analysis[49]). Further, previous
work clustered the observed transitions into a set of configurations (or states) at the group level,
thereby putatively missing subject-level idiosyncrasies[30,34,76]. Although several key insights were
revealed using previous approaches, e.g., bistability of the resting brain[76] and applications in
clinical realms have been attempted[84], several methodological limitations were also
identified[28,39,85]. First, it is unclear what spatiotemporal scale is ideally suited for studying brain
dynamics, i.e., what window length (or threshold for tagging sparse events) is ideal for
measuring transitions[28]. Further, a priori knowledge is also required to estimate the number of
configurations (or states) during clustering. Second, recent work using linearity preserving
surrogate data showed that some of the findings recovered using time-varying analysis could be
artifactual due to sampling variability[39,86]. Third, statistical models like HMM also require strict
assumptions related to the mutual exclusivity of brain states and require a priori knowledge about
number of states[76].
685
Our Mapper-based approach can work directly at the spatiotemporal scale at which the data were
acquired and thus bypasses the issues associated with sliding-window based analysis (e.g., how
to choose window-length and reduce artifacts related with sampling variability). Recently, a
similar Mapper-based approach was shown to capture and track the task-evoked brain dynamics
that matched known ground truth transitions associated with the experimental design[31]. Further,
our Mapper-based approach also distinguishes itself from the category of exploring dynamics
based on sparse events, because the output does not necessarily assume that brain dynamics arise
from only a subset of significant events but permits exploration of the *continuous* unfolding of
dynamics across each time frame. Further, the Mapper-based approach does not require
estimation of correlation (or connectivity) between parcellated brain regions and instead use
whole-brain activation maps to extract the overall landscape of brain dynamics. Lastly, no
assumptions are required to be made regarding mutual exclusivity of brain states or resting state
networks. Instead, Mapper generated graphs can be later annotated (e.g., using pie-chart based
visualization) to reveal overlapping communities (or states).
700
Limitations and future work

Some limitations of our work and associated avenues for future work should also be noted.
Although we used a precision individual connectomics dataset to show stable results with ~2.5
hours of resting state fMRI data per individual, acquiring that much data from individual patients
will initially only be feasible in cases where the clinical needs are very high, e.g., when planning
neurosurgical interventions such as resecting epileptic foci. Thus, we also replicated the main
findings in an independent cohort from the HCP, with ~1 hour of rsfMRI data per individual.
However, future work is required to examine whether our approach would work with datasets
that are not as dense (e.g., traditional rsfMRI scans of 10-20 min of rsfMRI data) – potentially
leveraging alternative acquisition paradigms[87].
711

Another potential limitation and avenue for future work includes combining activation-based
dynamics with co-fluctuation of signal across brain regions. New methods are being developed
that can provide fluctuations in functional connectivity at the single frame[35]. Thus, in the future,
TDA-based approaches could be used to combine different degrees of interactions between brain
regions ranging from brain activations themselves to higher-order interactions. Future work is
also required to better understand what purpose the hub state serves in intrinsic dynamics and
whether similar hub states can be seen under other states of consciousness (e.g., anesthesia or
sleep). One putative hypothesis could be that the intermittent hub state corresponds to a wash-out
period required by the brain before moving from one precise brain configuration to the next.
Lastly, due to better signal to noise ratio, we restricted our analysis to cortical activity only.
Future work is thus required to include sub-cortical structures and cerebellum to better
understand their role in the dynamical organization of the brain.
724

Although the topology of Mapper-generated graphs was largely similar across participants, key
subject-specific idiosyncrasies were also observed. For example, which networks (or group of
networks) dominated the periphery of the landscape was highly subject-specific and reliable
across sessions. Further, the Markov chains, estimated from individual time-frame data, were
also observed to be not only subject-specific but also reliable across sessions. These results
provide preliminary evidence that our Mapper-related approach contains potential utility for
precision medicine approaches. Due to the small number of participants in the MSC dataset and
only a moderate group size of the HCP cohort used here, we did not attempt to associate
topological properties of Mapper-generated landscapes and trait behavior (e.g., intelligence); as
large samples are required for reproducible brain-behavioral phenotypic associations[88]. Future
work, using data from large consortia (e.g., leveraging the Adolescent Brain Cognitive
Development (ABCD) Study; [89] (n>11,000)) such brain-behavior associations could be
examined.
738

Conclusions
Altogether, we present a novel approach to reveal the rules governing transitions in intrinsic
brain activity that could be useful in understanding both typical and atypical cognition. Our work
extends previous work both methodologically and conceptually. We observed the dynamical
landscape of at-rest brain to contain a shared attractor-like basin that acted like an intermediate
state where all canonical resting-state networks were represented equally, while the surrounding
periphery had distinct network configurations. Traversal through the landscape suggested
continuous evolution of brain activity patterns at rest. Lastly, differences in the landscape

architecture were more consistent within than between subjects, providing evidence that this
approach contains potential utility for precision medicine approaches.

References

1. Ringach, D. L. Spontaneous and driven cortical activity: implications for computation. *Curr. Opin. Neurobiol.* **19**, (2009).
2. Arieli, A., Shoham, D., Hildesheim, R. & Grinvald, A. Coherent spatiotemporal patterns of ongoing activity revealed by real- time optical imaging coupled with single-unit recording in the cat visual cortex. *J. Neurophysiol.* **73**, (1995).
3. Chen, Y., Geisler, W. S. & Seidemann, E. Optimal decoding of correlated neural population responses in the primate visual cortex. *Nat. Neurosci.* **9**, (2006).
4. Stringer, C. *et al.* Spontaneous behaviors drive multidimensional, brainwide activity. *Science (80-.).* **364**, (2019).
5. O'Neill, J., Pleydell-Bouverie, B., Dupret, D. & Csicsvari, J. Play it again: reactivation of waking experience and memory. *Trends in Neurosciences* vol. 33 (2010).
6. Berkes, P., Orbán, G., Lengyel, M. & Fiser, J. Spontaneous cortical activity reveals hallmarks of an optimal internal model of the environment. *Science (80-.).* **331**, (2011).
7. Luczak, A., Barthó, P. & Harris, K. D. Spontaneous Events Outline the Realm of Possible Sensory Responses in Neocortical Populations. *Neuron* **62**, (2009).
8. Han, F., Caporale, N. & Dan, Y. Reverberation of Recent Visual Experience in Spontaneous Cortical Waves. *Neuron* **60**, (2008).
9. Barttfelda, P. *et al.* Signature of consciousness in the dynamics of resting-state brain activity. *Proc. Natl. Acad. Sci. U. S. A.* **112**, 887–892 (2015).
10. Hansen, E. C. A., Battaglia, D., Spiegler, A., Deco, G. & Jirsa, V. K. Functional connectivity dynamics: Modeling the switching behavior of the resting state. *Neuroimage* **105**, 525–535 (2015).
11. Fernandez, L. M. J. *et al.* Highly Dynamic Spatiotemporal Organization of Low-Frequency Activities During Behavioral States in the Mouse Cerebral Cortex. *Cereb. Cortex* **27**, (2017).
12. Freyer, F., Roberts, J. A., Ritter, P. & Breakspear, M. A Canonical Model of Multistability and Scale-Invariance in Biological Systems. *PLoS Comput. Biol.* **8**, (2012).
13. Freyer, F., Aquino, K., Robinson, P. A., Ritter, P. & Breakspear, M. Bistability and non-Gaussian fluctuations in spontaneous cortical activity. *J. Neurosci.* **29**, (2009).
14. Valdes, P. A., Jimenez, J. C., Riera, J., Biscay, R. & Ozaki, T. Nonlinear EEG analysis based on a neural mass model. *Biol. Cybern.* **81**, (1999).
15. Saggar, M. & Uddin, L. Q. Pushing the boundaries of psychiatric neuroimaging to ground diagnosis in biology. *eNeuro* **6**, (2019).
16. Huys, Q. J. M., Maia, T. V & Frank, M. J. Computational psychiatry as a bridge from neuroscience to clinical applications. *Nat. Neurosci.* **19**, 404–413 (2016).
17. Chen, J. E. & Glover, G. H. Functional Magnetic Resonance Imaging Methods. *Neuropsychology Review* vol. 25 289–313 (2015).
18. Filippini, N. *et al.* Distinct patterns of brain activity in young carriers of the APOE-epsilon4 allele. *Proc. Natl. Acad. Sci.* **106**, 7209–7214 (2009).
19. Yeo, B. T. T. *et al.* The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *J. Neurophysiol.* **106**, 1125–1165 (2011).
20. Glasser, M. F. *et al.* A multi-modal parcellation of human cerebral cortex. *Nature* **536**,

171–178 (2016).

21. Fair, D. A. *et al.* Functional brain networks develop from a 'local to distributed'
organization. *PLoS Comput. Biol.* **5**, e1000381 (2009).

22. Dosenbach, N. U. F. *et al.* Distinct brain networks for adaptive and stable task control in
humans. *Proc. Natl. Acad. Sci.* **104**, 11073–11078 (2007).

23. Dosenbach, N. U. F., Fair, D. A., Cohen, A. L., Schlaggar, B. L. & Petersen, S. E. A dual-
networks architecture of top-down control. *Trends Cogn. Sci.* **12**, 99–105 (2008).

24. Roberts, J. A. *et al.* Metastable brain waves. *Nat. Commun.* **10**, (2019).

25. Smith, S. M. *et al.* Resting-state fMRI in the Human Connectome Project. *Neuroimage* **80**,
144–168 (2013).

26. Feinberg, D. A. *et al.* Multiplexed echo planar imaging for sub-second whole brain FMRI
and fast diffusion imaging. *PLoS One* **5**, e15710 (2010).

27. Kundu, P., Inati, S. J., Evans, J. W., Luh, W.-M. & Bandettini, P. A. Differentiating
BOLD and non-BOLD signals in fMRI time series using multi-echo EPI. *Neuroimage* **60**,
1759–1770 (2012).

28. Preti, M. G., Bolton, T. A. & Van De Ville, D. The dynamic functional connectome:
State-of-the-art and perspectives. *Neuroimage* (2016)
doi:10.1016/j.neuroimage.2016.12.061.

29. Liégeois, R. *et al.* Resting brain dynamics at different timescales capture distinct aspects
of human behavior. *Nat. Commun.* **10**, (2019).

30. Zalesky, A., Fornito, A., Cocchi, L., Gollo, L. L. & Breakspear, M. Time-resolved resting-
state brain networks. *Proc. Natl. Acad. Sci.* **111**, 10341–10346 (2014).

31. Saggar, M. *et al.* Towards a new approach to reveal dynamical organization of the brain
using topological data analysis. *Nat. Commun.* **9**, (2018).

32. Geniesse, C., Sporns, O., Petri, G. & Saggar, M. Generating dynamical neuroimaging
spatiotemporal representations (DyNeuSR) using topological data analysis. *Netw.*
Neurosci. **3**, (2019).

33. Lurie, D. J. *et al.* Questions and controversies in the study of time-varying functional
connectivity in resting fMRI. *Netw. Neurosci.* **4**, (2020).

34. Vidaurre, D., Smith, S. M. & Woolrich, M. W. Brain network dynamics are hierarchically
organized in time. *Proc. Natl. Acad. Sci. U. S. A.* **114**, (2017).

35. Faskowitz, J., Esfahlani, F. Z., Jo, Y., Sporns, O. & Betzel, R. F. Edge-centric functional
network representations of human cerebral cortex reveal overlapping system-level
architecture. *Nat. Neurosci.* **23**, (2020).

36. Casorso, J. *et al.* Dynamic mode decomposition of resting-state and task fMRI.
Neuroimage **194**, (2019).

37. Baker, A. P. *et al.* Fast transient networks in spontaneous human brain activity. *Elife* **3**,
e01867 (2014).

38. Muller, L. *et al.* Rotating waves during human sleep spindles organize global patterns of
activity that repeat precisely through the night. *Elife* **5**, (2016).

39. Laumann, T. O. *et al.* On the Stability of BOLD fMRI Correlations. *Cereb. Cortex* (2016)
doi:10.1093/cercor/bhw265.

40. Liégeois, R., Laumann, T. O., Snyder, A. Z., Zhou, J. & Yeo, B. T. T. Interpreting
temporal fluctuations in resting-state functional connectivity MRI. *NeuroImage* vol. 163
(2017).

41. Ma, Y. *et al.* Resting-state hemodynamics are spatiotemporally coupled to synchronized

and symmetric neural activity in excitatory neurons. *Proc. Natl. Acad. Sci. U. S. A.* **113**,
(2016).

42. Lake, E. M. R. *et al.* Simultaneous cortex-wide fluorescence Ca2+ imaging and whole-
brain fMRI. *Nat. Methods* **17**, (2020).

43. Kong, X. *et al.* Anatomical and Functional Gradients Shape Dynamic Functional
Connectivity in the Human Brain. *bioRxiv* (2021).

44. Calhoun, V. D., Miller, R., Pearlson, G., Adali, T. & Adal\i, T. The chronnectome: time-
varying connectivity networks as the next frontier in fMRI data discovery. *Neuron* **84**,
262–274 (2014).

45. Lindquist, M. A., Xu, Y., Nebel, M. B. & Caffo, B. S. Evaluating dynamic bivariate
correlations in resting-state fMRI: a comparison study and a new approach. *Neuroimage*
101, 531–546 (2014).

46. Shine, J. M. *et al.* Estimation of dynamic functional connectivity using Multiplication of
Temporal Derivatives. *Neuroimage* **122**, 399–407 (2015).

47. Liu, X., Chang, C. & Duyn, J. H. Decomposition of spontaneous brain activity into
distinct fMRI co-activation patterns. *Front. Syst. Neurosci.* **7**, 101 (2013).

48. Petridou, N., Gaudes, C. C., Dryden, I. L., Francis, S. T. & Gowland, P. A. Periods of rest
in fMRI contain individual spontaneous events which are related to slowly fluctuating
spontaneous activity. *Hum. Brain Mapp.* **34**, 1319–1329 (2013).

49. Tagliazucchi, E., von Wegner, F., Morzelewski, A., Brodbeck, V. & Laufs, H. Dynamic
BOLD functional connectivity in humans and its electrophysiological correlates. *Front.*
Hum. Neurosci. **6**, 339 (2012).

50. Parrish, T. B., Gitelman, D. R., LaBar, K. S. & Mesulam, M. M. Impact of signal-to-noise
on functional MRI. *Magn. Reson. Med.* **44**, (2000).

51. Anderson, J. S., Ferguson, M. A., Lopez-Larson, M. & Yurgelun-Todd, D.
Reproducibility of single-subject functional connectivity measurements. *Am. J.*
Neuroradiol. **32**, 548–555 (2011).

52. Choe, A. S. *et al.* Reproducibility and Temporal Structure in Weekly Resting-State fMRI
over a Period of 3.5 Years. *PLoS One* **10**, e0140134 (2015).

53. Gordon, E. M. *et al.* Precision Functional Mapping of Individual Human Brains. *Neuron*
95, 791--807.e7 (2017).

54. Laumann, T. O. *et al.* Functional System and Areal Organization of a Highly Sampled
Individual Human Brain. *Neuron* **87**, 657–670 (2015).

55. O'Connor, D. *et al.* The healthy brain network serial scanning initiative: A resource for
evaluating inter-individual differences and their reliabilities across scan conditions and
sessions. *GigaScience* vol. 6 (2017).

56. Damaraju, E. *et al.* Dynamic functional connectivity analysis reveals transient states of
dysconnectivity in schizophrenia. *NeuroImage Clin.* **5**, 298–308 (2014).

57. Demirtas, M. *et al.* Dynamic functional connectivity reveals altered variability in
functional connectivity among patients with major depressive disorder. *Hum. Brain Mapp.*
37, 2918–2930 (2016).

58. Rashid, B., Damaraju, E., Pearlson, G. D. & Calhoun, V. D. Dynamic connectivity states
estimated from resting fMRI Identify differences among Schizophrenia, bipolar disorder,
and healthy control subjects. *Front. Hum. Neurosci.* **8**, 897 (2014).

59. Sourty, M. *et al.* Identifying Dynamic Functional Connectivity Changes in Dementia with
Lewy Bodies Based on Product Hidden Markov Models. *Front. Comput. Neurosci.* **10**, 60

(2016).

60.   Lum, P. Y. *et al.* Extracting insights from the shape of complex data using topology. *Sci.*
Rep. **3**, 1236 (2013).

61.   Carlsson, G. Topology and data. *Bull. Am. Math. Soc.* **46**, 255–308 (2009).

62.   Singh, G., Mémoli, F. & Carlsson, G. Topological Methods for the Analysis of High
Dimensional Data Sets and 3D Object Recognition. *Eurographics Symp. Point-Based*
Graph. (2007) doi:10.2312/SPBG/SPBG07/091-100.

63.   Phinyomark, A., Ibanez-Marcelo, E. & Petri, G. Resting-State fMRI Functional
Connectivity: Big Data Preprocessing Pipelines and Topological Data Analysis. *IEEE*
Trans. Big Data **3**, (2017).

64.   Singh, G., Mémoli, F. & Carlsson, G. E. Topological methods for the analysis of high
dimensional data sets and 3d object recognition. *SPBG* (2007).

65.   Geniesse, C., Sporns, O., Petri, G. & Saggar, M. Generating dynamical neuroimaging
spatiotemporal representations (DyNeuSR) using topological data analysis. *Netw.*
Neurosci. **3**, (2019).

66.   Prichard, D. & Theiler, J. Generating surrogate data for time series with several
simultaneously measured variables. *Phys. Rev. Lett.* **73**, 951–954 (1994).

67.   Sporns, O. & van den Heuvel, M. P. Network maps of the human brain's rich club. *Netw.*
Sci. 1–3 (2013) doi:10.1017/nws.2013.8.

68.   van den Heuvel, M. P., Bullmore, E. T. & Sporns, O. Comparative Connectomics. *Trends*
Cogn. Sci. **20**, 345–361 (2016).

69.   Bassett, D. S. Brain network analysis: a practical tutorial. *Brain* **139**, (2016).

70.   Fornito, A., Zalesky, A. & Bullmore, E. T. *Fundamentals of Brain Network Analysis*.
Fundamentals of Brain Network Analysis (2016). doi:10.1016/C2012-0-06036-X.

71.   Sporns, O., Honey, C. J. & Kötter, R. Identification and classification of hubs in brain
networks. *PLoS One* **2**, e1049 (2007).

72.   van den Heuvel, M. P. & Sporns, O. Network hubs in the human brain. *Trends Cogn. Sci.*
17, 683–696 (2013).

73.   Gorgolewski, K. J., Storkey, A. J., Bastin, M. E. & Pernet, C. R. Adaptive thresholding for
reliable topological inference in single subject fMRI analysis. *Front. Hum. Neurosci.*
(2012) doi:10.3389/fnhum.2012.00245.

74.   Norris, J. R. Discrete-time Markov chains. in *Markov Chains* (2013).
doi:10.1017/cbo9780511810633.003.

75.   Gordon, E. M. *et al.* Generation and Evaluation of a Cortical Area Parcellation from
Resting-State Correlations. *Cereb. Cortex* **26**, (2016).

76.   Meer, J. N. va. der, Breakspear, M., Chang, L. J., Sonkusare, S. & Cocchi, L. Movie
viewing elicits rich and reliable brain state dynamics. *Nat. Commun.* **11**, (2020).

77.   Esfahlani, F. Z. *et al.* High-amplitude cofluctuations in cortical activity drive functional
connectivity. *Proc. Natl. Acad. Sci. U. S. A.* **117**, (2020).

78.   Majeed, W. *et al.* Spatiotemporal dynamics of low frequency BOLD fluctuations in rats
and humans. *Neuroimage* **54**, (2011).

79.   Betzel, R. F., Cutts, S. A., Greenwell, S. & Sporns, O. Individualized event structure
drives individual differences in whole-brain functional connectivity. *bioRxiv* (2021).

80.   Breakspear, M. Dynamic models of large-scale brain activity. *Nat. Neurosci.* **20**, 340–352
(2017).

81.   Mann, K., Deny, S., Ganguli, S. & Clandinin, T. R. Coupling of activity, metabolism and

behaviour across the Drosophila brain. *Nature* **593**, (2021).

82. Margulies, D. S. *et al.* Situating the default-mode network along a principal gradient of
macroscale cortical organization. *Proc. Natl. Acad. Sci. U. S. A.* **113**, 12574–12579
(2016).

83. Liu, X. & Duyn, J. H. Time-varying functional network information extracted from brief
instances of spontaneous brain activity. *Proc. Natl. Acad. Sci. U. S. A.* **110**, 4392–4397
(2013).

84. Du, Y. *et al.* Dynamic functional connectivity impairments in early schizophrenia and
clinical high-risk for psychosis. *Neuroimage* (2018)
doi:10.1016/j.neuroimage.2017.10.022.

85. Keilholz, S. D. Review Article: The Neural Basis of Time-Varying Resting State
Functional Connectivity. *Brain Connect.* (2014) doi:10.1089/brain.2014.0250.

86. Liégeois, R., Laumann, T. O., Snyder, A. Z., Zhou, J. & Yeo, B. T. T. Interpreting
temporal fluctuations in resting-state functional connectivity MRI. *NeuroImage* (2017)
doi:10.1016/j.neuroimage.2017.09.012.

87. Lynch, C. J. *et al.* Rapid Precision Functional Mapping of Individuals Using Multi-Echo
fMRI. *Cell Rep.* **33**, (2020).

88. Marek, S. *et al.* Towards Reproducible Brain-Wide Association Studies. *bioRxiv* (2020).

89. Casey, B. J. *et al.* The Adolescent Brain Cognitive Development (ABCD) study: Imaging
acquisition across 21 sites. *Developmental Cognitive Neuroscience* vol. 32 (2018).