Title: Pupil correlates of decision variables in mice playing a competitive mixed-strategy game

Authors: Hongli Wang[1], Heather K. Ortega[1], Huriye Atilgan[2], Cayla E. Murphy[2], Alex C. Kwan[2,3]

[1]Interdepartmental Neuroscience Program,

[2]Department of Psychiatry,

[3]Department of Neuroscience,

Yale University School of Medicine, New Haven, Connecticut, 06511, USA

Correspondence: alex.kwan@yale.edu

Abstract

In a competitive game involving an animal and an opponent, the outcome is contingent on the

choices of both players. To succeed, the animal must continually adapt to competitive pressure,

or else risk being exploited and lose out on rewards. In this study, we demonstrate that head-

fixed mice can be trained to play the iterative competitive game 'matching pennies' against a

virtual computer opponent. We find that the animals' performance is well described by a hybrid

computational model that includes Q-learning and choice kernels. Comparing between matching

pennies and a non-competitive two-armed bandit task, we show that the tasks encourage

animals to operate at different regimes of reinforcement learning. To understand the

involvement of neuromodulatory mechanisms, we measure fluctuations in pupil size and use

multiple linear regression to relate the trial-by-trial transient pupil responses to decision-related

variables. The analysis reveals that pupil responses are modulated by observable variables,

including choice and outcome, as well as latent variables for value updating, but not action

selection. Collectively, these results establish a paradigm for studying competitive decision-

making in head-fixed mice and provide insights into the role of arousal-linked neuromodulation

in the decision process.

INTRODUCTION

Animals learn from the outcomes of their past actions. The decision-making process can be casted in the framework of reinforcement learning (Sutton and Barto, 1998), which provides a quantitative approach to characterize how animals choose among multiple options based on prior experience. This approach, when applied to rodents and combined with powerful molecular, genetic, electrophysiological, and imaging methods, has yielded novel insights into the neural circuits involved in reward-based learning (Bari et al., 2019; Groman et al., 2019; Hattori et al., 2019; Ito and Doya, 2009; Sul et al., 2011; Sul et al., 2010; Tai et al., 2012). To date most studies in rodents relied on tasks involving a pure strategy, where there is always a particular action that is optimal in a given situation. However, pure strategies are not always available. For instance, in a two-player game (e.g., rock-paper-scissors) where the outcome depends on both the animal's and an opponent's choices, pure strategies are inadequate because an opponent can predict tendencies and exploit to win. Instead, the animal should adopt a mixed strategy, in which two or more pure strategies are chosen probabilistically. Analyses of behavior under competitive pressure fall into the purview of game theory (Camerer, 2003), and provide a unique window into the social and adaptive aspects of decision-making (Lee, 2008).

Research in humans and non-human primates has identified numerous brain regions contributing to decision-making during two-player games. For example, a functional imaging study in humans showed widespread representation of reward signals in the brain during multiple types of games against computerized opponents (Vickery et al., 2011). Signals related to choices and the mentalization of an opponent's actions were localized to several brain regions including the prefrontal cortex (Hampton et al., 2008; Vickery et al., 2011). Electrophysiological recordings in macaque monkeys demonstrated spiking activity patterns that suggest neural representations of various decision variables in prefrontal cortical regions, lateral intraparietal cortex, and amygdala (Barraclough et al., 2004; Chang et al., 2013; Dal Monte et al., 2020; Haroush and Williams, 2015; Seo et al., 2007, 2009). However, there have only been a few reports of rodents engaging in two-player games (Tervo et al., 2014; Wood et al., 2016), and the associated neural correlates are less clear.

The neuromodulator norepinephrine (NE) may have an important role for performance during two-player games. Prior literature has linked central noradrenergic tone to behavioral flexibility (Aston-Jones and Cohen, 2005; Bouret and Sara, 2005). In one pioneering study, Tervo et al.

taught rats to play a matching pennies game with a computer opponent (Tervo et al., 2014). By

manipulating neural activity in locus coeruleus (LC), they showed that elevating central NE tone

can suppress firing in the anterior cingulate cortex, which in turn reduces the influence of

reinforcement history and promotes stochastic behavior. A different way to study

neuromodulatory tone is to measure pupil size, which is often treated as a readout of NE levels

in the neocortex (Gilzenrat et al., 2010; Joshi et al., 2016; Reimer et al., 2016). Studies of

pupillary dynamics during tasks further support the idea that NE is important for flexible

decisions. For instance, the baseline pupil size is shown to correlate with biases in the explore-

exploit trade-off and attentional set shifting (Jepma and Nieuwenhuis, 2011; Pajkossy et al.,

2017). The trial-by-trial transient change in pupil size is reported to associate with many task-

relevant variables including upcoming choice, expected outcome, values of the choices, and

uncertainties (de Gee et al., 2014; Hess and Polt, 1960; Qiyuan et al., 1985; Van Slooten et al.,

2018). Given these prior results, it seems likely that pupil fluctuations can be leveraged to study

the neuromodulatory mechanisms underlying adaptive action selection during competitive two-

player games.

We have two goals for the current study. First, we want to know if head-fixed mice can compete

proficiently in a two-player game. Second, we want to characterize pupil fluctuations to gain

insights into the role of neuromodulation in decision-making under competitive pressure. To this

end, we designed a behavioral paradigm for a head-fixed mouse to play iterative matching

pennies against a computer-controlled virtual opponent. We found that mice can perform at a

level close to the optimal reward rate by exhibiting choice behavior consistent with a mix of

reinforcement learning and choice perseveration. We underscored the unique choice behavior

during matching pennies, by comparing with performance in the more widely used two-armed

bandit task. Finally, we measured within-trial changes in pupil size, and showed that the

transient pupillary responses are associated with the choice, outcome, and latent variables for

value updating.

MATERIALS AND METHODS

Animals

All animal procedures were conducted in accordance with procedures approved by the

Institutional Animal Care and Use Committee at Yale University. Adult male C57BL/6J mice

(>P56; #000664, Jackson Laboratory) were used for all experiments. Mice were housed in

groups of 3-5 animals with 12-hr-dark/12-hr-light cycle control (lights off at 19:00).

Surgical Procedures

Anesthesia was induced with 2% isoflurane in oxygen before the surgery. The isoflurane was

lowered to 1–1.2% during the surgical procedures. The mouse was placed on a water-

circulating heating pad (TP-700, Gaymar Stryker) in a stereotaxic frame (David Kopf

Instruments). After injecting carprofen (5 mg/kg, s.c.; #024751, Butler Animal Health) and

dexamethasone (3 mg/kg, s.c.; Dexaject SP, #002459, Henry Shein Animal Health), the scalp

was removed to expose the skull. A custom-made stainless-steel head plate (eMachineShop)

was glued onto the skull with MetaBond (C&B, Parkell, Inc.). Carprofen (5 mg/kg, s.c.) was

injected each day for the following three days. Mice were given 7 days to recover from the

surgery before any behavioral training.

Behavioral setup

The training apparatus was based on a previous design from our prior studies (Siniscalchi et al.,

2016; Siniscalchi et al., 2019). Detailed instruction to construct the apparatus is available at

https://github.com/Kwan-Lab/behavioral-rigs. The mouse with a head plate implant was head-

fixed to a stainless-steel holder (eMachineShop). The animal sat inside an acrylic tube

(8486K433; McMaster-Carr), which limited gross movements though allowed postural

adjustments. A lick port with two lick spouts was positioned in front of the subject. The spouts

were constructed with blunted 20-gauge stainless-steel needles. Contact with the lick spout –

which was how the animal indicated its choices – was detected through wires that were

soldered onto the spout and a battery-powered lick detection electronic circuit. Output signals

from the circuit were sent to a computer via a data acquisition unit (USB-201, Measurement

Computing) and logged by the Presentation software (Neurobehavioral Systems, Inc.). Water

delivery from the lick spouts was controlled independently for each spout by two solenoid fluid

valves (MB202-V-A-3-0-L-204; Gems Sensors & Controls). The amount of water was calibrated

to ~4 µL per pulse by adjusting the duration of the electrical pulse sent by the Presentation

software via a second data acquisition unit (USB-201, Measurement Computing). Two speakers

(S120, Logitech) were placed in front of the mouse to play the sound cue. The whole setup was

placed inside an audio-visual cart with walls lined with soundproof acoustic foams (5692T49,

McMaster-Carr). A monochrome camera (GigE G3-GM11-M1920, Dalsa) with a 55 mm

telecentric lens (TEC-55, Computar) was aimed at the right eye. Video was acquired at 20 Hz. A

dimmable, white light source (LT-T6, Aukey) was used to provide ambient light, such that the

baseline pupil size was moderate and fluctuations around the baseline was detectable. The

computer running the Presentation software would send TTL pulses to a computer controlling

the camera through a USB data acquisition device (USB-201; Measurement Computing). The

camera-connected computer would run a custom script written in MATLAB 9.7 (MathWorks) that

logged the timing of the TTL pulses so that the behavioral log files generated by the

Presentation software could be aligned to the video recordings. In a small subset of

experiments, we captured videos from both left and right eyes by mounting two identical camera

systems on both sides of the animal.

Behavioral training – Matching pennies

All of the procedures for initial shaping as well as the final matching pennies task were written

using the scripting language in the Presentation software. The animals were fluid-restricted.

Water was provided during the one behavioral session daily. On the days when the animals

were not trained (typically 1 day a week), a water bottle was placed in the home cage for 5 min

of ad libitum consumption. All animals underwent two shaping phases before training. For phase

1 (2 days), the animals were habituated to the apparatus. They may lick either spout. A water

reward would be delivered for every lick in the corresponding spout, as long as a minimum of 1

s has occurred since the last reward. The session would terminate after the animals acquired

100 rewards. For phase 2 (~4 weeks), the animals were introduced to the trial structure and

learned to suppress impulsive licks. At the start of each trial, a 5 kHz sound cue lasting for 0.2 s

was played. From the onset of the sound cue, the mouse had a window of 2 s to make a

response by licking either of the spouts. If a lick was detected during the response window, a

water reward would be delivered in the corresponding spout and there was a fixed 3 s period for

consumption following the lick. If no lick was detected, the fixed 3 s consumption window would

still be presented following the end of the response window. From the end of the consumption

window, an inter-trial interval (ITI) began. The duration of the ITI in seconds was drawn from a

truncated exponential distribution with $\lambda = 1/3$ and boundaries of 1 and 5. If the animal emitted

one or more licks during the ITI, then additional time drawn again from the same distribution

would be appended to the ITI. If the mouse licked again during the appended time, yet another

additional time would be appended, up to a total of 5 draws including the initial draw. When the

ITI ended, a new trial would begin. This trial timing was the same as what would be used for

matching pennies. Particularly, the goal for the shaping was to habituate and introduce lick

suppression. Although the mouse could theoretically get water from either spout, the animal

tended to favor heavily one spout during the shaping procedures. The animal would advance to

playing the matching pennies game when the average number of ITI draws per trial was lower

than 1.2 for three consecutive sessions.

For matching pennies, the mouse played against a virtual opponent in the form of a computer

agent. At the start of each trial, the agent made a choice (left or right). If the mouse selected the

same choice as the computer, a water reward would be delivered in the corresponding spout.

Otherwise, no reward was presented. Importantly, the computer agent was designed to provide

competitive pressure by acting according to prediction of the animal's choices. Specifically, it

was programmed to be the same as 'algorithm 2' (Barraclough et al., 2004; Lee et al., 2004) or

'competitor 1' (Tervo et al., 2014) in previous studies. Briefly, the agent had a record of the

mouse's entire choice and reward history within the current session. The agent calculated the

conditional probabilities that the animal would choose left given sequences of the preceding N

choices (N = 0 – 4) and sequences of preceding N choice-outcome combinations (N = 1 – 4).

The binomial test was used to test each of the 9 conditional probabilities against the null

hypothesis that the mouse would choose left with a probability of 0.5. If none of the null

hypothesis was rejected, the agent would randomly choose either target with equal probabilities.

If one or more hypotheses were rejected, the agent would generate the counter choice with the

statistically significant conditional probability that was farther away from 0.5. A session would

terminate automatically when no response was logged for 10 consecutive trials. When an

animal reached a 40% reward rate for 3 consecutive sessions (~4 weeks), then its performance

was considered stable and the subsequent sessions were included in the following analysis.

Behavioral training – Two-armed bandit

We used the same training apparatus and the same scripting language in the Presentation

software to program the two-armed bandit task, which had the same trial timing as matching

pennies. The shaping procedures relied on similar tactics, but the details were different,

involving three shaping phases before training. For phase 0 (1 day), the experimenter manually

delivered 50 water rewards through each port (for a total of 100 rewards) and monitored for

consistent licking. A 5 kHz sound cue lasting for 0.2 s was played at the same time as water

delivery. If the animal was not licking to consume the water rewards, the experimenter used a

blunted syringe to guide the animal to lick the spout. For phase 1 (1 day), the animal was

introduced to the trial structure and learned to suppress impulsive licks. At the start of each trial,

A 5 kHz sound cue lasting for 0.2 s was played. From the onset of the sound cue, the mouse

had a window of 5 s to make a response by licking either of the spouts. If a lick was detected

during the response window, a water reward would be delivered from the corresponding spout

and there was a fixed 3 s period for consumption following the lick. If no lick was detected, no

reward was given during the consumption period. Next, an ITI began. The duration of the ITI in

seconds was drawn from a truncated exponential distribution with λ = 1/3 and boundaries of 1

and 5. If the animal emitted one or more licks during the ITI, then additional time drawn again

from the same truncated exponential distribution would be appended to the ITI. If the mouse

licked again during the appended time, yet another additional time would be appended, up to a

total of 5 draws including the initial draw. When the ITI ended, a new trial would begin. The

session ends after the animal accumulates 100 rewards. In particular, the goal for phase 1 was

to habituate and introduce lick suppression. For phase 2, the animal continued to lick following

the cue for a water reward in a similar fashion to phase 1. However, the response window was

shortened to 2 s, meaning the animal had only 2 s to lick following the cue to receive reward.

The trial timing with shortened response window was the same as what would be used for the

two-armed bandit task. Moreover, the animal must alternate sides (choose left if the last reward

came from a right lick, and vice versa). They would not be rewarded for choosing the same

spout repeatedly to discourage the development of a side bias. The animal could proceed to the

final task if they achieved 200 rewards in a single session.

For the two-armed bandit task, the two options (left and right) were associated with different

reward probabilities. In each trial, when an animal chose an option, a reward was delivered

stochastically based on the assigned reward probability. In our implementation, there were two

sets of reward probabilities: 0.7:0.1 and 0.1:0.7. A set of reward probabilities was maintained

across a block of trials. Within a block, once the mouse had chosen the option with high reward

probability (hit trials) for ten times, then on any given trial there was a probability of 1/11 that the

reward probabilities would change. Thus, the number of trials in a block after ten hits followed a

geometric distribution with μ = 11. There were no explicit cues to indicate a block switch,

therefore the animal had to infer the current situation through experience. A session would

terminate automatically when no response was logged for 20 consecutive trials. Animals are

considered proficient when they chose the spout with higher reward probability on at least 50%

of trials on 3 consecutive sessions.

Preprocessing of behavioral data

A total of 115 sessions from 13 mice were included in the study. For matching pennies, data

came from 81 sessions from 5 mice. For two-armed bandit, data came from 34 sessions from 8

mice, including 26 sessions from 4 mice with single-pupil recording and 8 sessions from the

other 4 mice with double-pupil recording. All of the sessions contained both behavioral and

pupillometry data. For behavior, the log file saved by the Presentation software contained

timestamps for all events that occurred during a session. Analyses of the behavioral data were

done in MATLAB. For matching pennies, towards the end of each session, the animals tended

to select the same option for around 30 trials before ceasing to respond. To avoid these

repetitive trials in the analyses, for each session, the running 3-choice entropy (see below) of a

30-trial window was calculated, and the MATLAB function *ischange* was used to fit with a

piecewise linear function. The trial when the fitted function fell below a value of 1 was identified

as the 'last trial', and all subsequent trials were discarded for the analysis. In cases if the

performance recovered after the detected last trial to a value greater than 1, or if the fitted

function did not fall below a value of 1 and no 'last trial' was detected, the entire session was

used for analysis.

Analysis of behavioral data – Entropy

To quantify the randomness in the animals' choices, the 3-choice entropy of the choice

sequence is calculated by:

$$Entropy = -\sum_k p_k \, log_2 \, p_k \tag{1}$$

where p_k is the frequency of occurrence of a 3-choice pattern in a session. Because there were

2 options to choose from, there were $2^3 = 8$ potential patterns possible. The maximum value for

entropy is 3 bits.

Analysis of behavioral data – Computational models

To quantify the choice behavior, we considered 5 computational models. The primary model

used in the paper is a Q-learning with forgetting model plus choice kernels (FQ_RPE_CK)

(Katahira, 2015; Wilson and Collins, 2019). On trial n, for a choice c_n that leads to an outcome

r_n, the action value Q_n^i associated with an action i is updated by:

262
$$Q_{n+1}^i = \begin{cases} Q_n^i + \alpha (r_n - Q_n^i) & \text{if } c_n = i \\ (1-\alpha)Q_n^i & \text{if } c_n \neq i \end{cases} \qquad (2)$$

264   where α is the learning rate, and the forgetting rate for the unchosen action. In our task, there

265   are two options, so $i \in \{L, R\}$. For the outcome, r_n = 1 for reward, 0 for no reward. Moreover, to

266   capture the animal's tendency to make decisions based purely on previous choices, there are

267   choice kernels K_n^i updated by:

269
$$K_{n+1}^i = \begin{cases} K_n^i + \alpha_K(1 - K_n^i) & \text{if } c_n = i \\ (1-\alpha_K)K_n^i & \text{if } c_n \neq i \end{cases} \qquad (3)$$

271   where α_K is the learning rate of the choice kernel. For action selection, the probability to choose

272   action i on trial n is given by a softmax function:

274
$$P(c_n = i) = \frac{exp(\beta Q_n^i + \beta_K K_n^i)}{\sum_j exp(\beta Q_n^j + \beta_K K_n^j)} \qquad (4)$$

276   where β and β_K are the inverse temperature parameters for action values and choice kernels

277   respectively.

279   We compared the FQ_RPE_CK model against 4 other models. For the win-stay-lose-switch

280   model (WSLS), the probability to choose action i on trial n is given by:

282
$$P(c_n = i) = \begin{cases} p & \text{if } r_{n-1} = 1 \\ 1-p & \text{if } r_{n-1} = 0 \end{cases} \qquad (5)$$

284   where p is the probability that the animal followed the win-stay-lose-switch strategy.

286   For the Q-learning model (Q_RPE), the action value is updated by:

288
$$Q_{n+1}^i = \begin{cases} Q_n^i + \alpha (r_n - Q_n^i) & \text{if } c_n = i \\ Q_n^i & \text{if } c_n \neq i \end{cases} \qquad (6)$$

290   and the probability to choose action i at trial n is then given by:

$$P(c_n = i) = \frac{exp(\beta Q_n^i)}{\sum_j exp(\beta Q_n^j)} \tag{7}$$

294 For the forgetting Q-learning model (FQ_RPE), the action values are updated by equation (2),

295 and the probability to choose action i on trial n is given by equation (7).

297 For the differential Q-learning model (DQ_RPE) (Caze and van der Meer, 2013; Katahira,

298 2018), the action value is updated by:

$$Q_{n+1}^i = \begin{cases} Q_n^i + \alpha_R(1 - Q_n^i) & \text{if } c_n = i, \ r_n = 1 \\ Q_n^i + \alpha_U(1 - Q_n^i) & \text{if } c_n = i, \ r_n = 0 \\ Q_n^i & \text{if } c_n \neq i \end{cases} \tag{8}$$

where α_R and α_U are the learning rates for rewarded and unrewarded trials, respectively. The

probability to choose action i on trial n is given by equation (7).

Analysis of behavioral data – Model fitting and comparison

To fit the computational models to the behavioral data, for each subject, the sequence of

choices and outcomes were concatenated across sessions. Each model was fitted to the data

using a maximum-likelihood algorithm implemented with the *fmincon* function in MATLAB, with

the constraints $0 \leq \alpha, \alpha_K, \alpha_R, \alpha_U \leq 1$, $0 < \beta, \beta_K$, and $0 \leq p \leq 1$. These fits also yielded latent

decision variables such as action values and choice kernels that would be used for the

subsequent multiple linear regression analyses. For model comparison, we calculated the

Bayesian information criterion (BIC) for each of the model fits.

Preprocessing of pupillometry data

To extract the coordinates of the pupil from the video recordings, we used DeepLabCut (DLC)

2.0 (Mathis et al., 2018; Nath et al., 2019), ran on Jupyter Notebook on Google's cloud servers.

A small subset of the video frames was manually analyzed, with the experimenter annotating 5

labels including the central, uppermost, leftmost, lowermost, and rightmost points of the pupil.

The annotated frames were fed to DLC to train a deep neural network, which analyzed the

remainder of the video to produce the 5 labels. From the labels, the pupil diameter was

computed by taking the distance between the leftmost and rightmost labels. We did not use the

other labels, because the estimates of the lowermost points were unstable, sometimes jumping
in consecutive frames due to interference from the lower eyelid. The pupil diameter signal was
further processed through a 4 Hz lowpass filter with the MATLAB function *lowpass*. Then any
frames with outliers that were greater than 3 scaled median absolute deviation (MAD) from the
median were deleted using the MATLAB function *isoutlier*. Using a 10-minute moving window to
account for drift over a session, the signal was converted to z-score. Finally, we calculated the
pupil response for each trial by subtracting the instantaneous z-score from -1 to 5 s relative to
cue onset by the baseline z-score, which was defined as the mean z-score from -2 to -1 s
relative to cue onset.

Analysis of pupil data – Multiple linear regression
To determine how pupil responses may relate to choices and outcomes, we used multiple linear
regression:

$$
\begin{aligned}
pupil\ response(t) = b_0 &+ b_1 c_{n+1} + b_2\, r_{n+1} + b_3 c_{n+1} r_{n+1} \\
&+ b_4 c_n + b_5 r_n + b_6 c_n r_n \\
&+ b_7 c_{n-1} + b_8 r_{n-1} + b_9 c_{n-1} r_{n-1} \\
&+ b_{10} c_{n-2} + b_{11} r_{n-2} + b_{12} c_{n-2} r_{n-2} \\
&+ b_{13} \overline{r_n^{\mathrm{MA}}} + b_{14} r_n^{\mathrm{Cum.}} + \varepsilon(t)
\end{aligned}
\tag{9}
$$

where $pupil\ response(t)$ is the pupil response at time t in trial n, $c_{n+1}, c_n, c_{n-1}, c_{n-2}$ are the
choices made on the next trial, the current trial, the previous trial, and the trial before the
previous trial, respectively, $r_{n+1}, r_n, r_{n-1}, r_{n-2}$ are the outcomes for the next trial, the current trial,
the previous trial, and the trial before the previous trial, respectively, $b_0, \ldots, b_{14}$ are the
regression coefficients, and $\varepsilon(t)$ is the error term. Choices were dummy-coded as 0 for left
responses and 1 for right responses. Outcomes were dummy-coded as 0 for no-reward and 1
for reward. For the last 2 predictors in Eq. 9, $\overline{r_n^{\mathrm{MA}}}$ is the average reward over the previous 20
trials, given by the equation:

$$
\overline{r_n^{\mathrm{MA}}} = \frac{\sum_{i=0}^{19} r_{n-i}}{20}
\tag{10}
$$

349 The term $r_n^{\mathrm{Cum.}}$ indicates the normalized cumulative reward during the session, calculated by:

$$351 \qquad r_n^{\text{Cum.}} = \frac{\sum_{i=1}^n r_i}{\sum_{i=1}^N r_i} \qquad (11)$$

353   where n denotes the current trial number and N is the total number of trials in the session.

355   To determine how pupil responses may relate to latent decision variables for action selection,

356   we used multiple linear regression:

$$
\begin{aligned}
pupil\ response(t) = {}& b_0 + b_1 c_n + b_2\, r_n + b_3 c_n r_n \\
& + b_4 c_{n-1} + b_5 r_{n-1} + b_6 c_{n-1} r_{n-1} \\
& + b_7 (Q_n^{\text{L}} - Q_n^{\text{R}}) + b_8 Q_n^{\text{chosen}} \\
& + b_9 (K_n^{\text{L}} - K_n^{\text{R}}) + b_{10} K_n^{\text{chosen}} \\
& + b_{11} \overline{r_n^{\text{MA}}} + b_{12} r_n^{\text{Cum.}} + \varepsilon(t)
\end{aligned}
\qquad (12)
$$

where Q_n^{L} and Q_n^{R} denote the action values of the left and right choices in trial n, respectively,

Q_n^{chosen} is the value of the action chosen in trial n, K_n^{L} and K_n^{R} are the choice kernels of the left

and right choices in trial n, respectively, K_n^{chosen} is the choice kernel of the action chosen in trial

n.

To determine how pupil responses may relate to latent decision variables for value updating, we

used multiple linear regression, adapting the equation from (Sul et al., 2010):

$$
\begin{aligned}
pupil\ response(t) = {}& b_0 + b_1 c_n + b_2\, c_{n-1} + b_3 r_{n-1} \\
& + b_4 (Q_n^{\text{L}} - Q_n^{\text{R}}) + b_5 (r_n - Q_n^{\text{chosen}}) \\
& + b_6 (K_n^{\text{L}} - K_n^{\text{R}}) + b_7 (1 - K_n^{\text{chosen}}) \\
& + b_8 \overline{r_n^{\text{MA}}} + b_9 r_n^{\text{Cum.}} + \varepsilon(t)
\end{aligned}
\qquad (13)
$$

where $r_n - Q_n^{\text{chosen}}$ is the reward prediction error (RPE), and $1 - K_n^{\text{chosen}}$ is the error term used

to update the choice kernels, or choice kernel error (CKE).

For each session, the regression coefficients were determined by fitting the equations to data

using the MATLAB function *fitlm*. The fit was done in 100-ms time bins that span from -3 to 5 s

relative to cue onset, using mean pupil response within the time bins. To summarize the results,

for each predictor, we calculated the proportion of sessions in which the regression coefficient

was different from zero ($P < 0.01$). To determine if the proportion was significantly different from

chance, we performed a chi-square test against the null hypothesis that there was a 1%

probability that a given predictor was mischaracterized as significant by chance in a single

session.

Code accessibility

The data and code that support the findings of this study will be made publicly available at

http://github.com/Kwan-Lab.

RESULTS

Mice played matching pennies against a computer opponent

We trained head-fixed mice to play matching pennies against a computer opponent (***Figure***

1A). In this iterative version of matching pennies, each trial the mouse and the computer would

choose left or right. The mouse received a water reward only if the actions matched. The

corresponding payoff matrix is shown in ***Figure 1B***. This game was challenging for the mouse

because the computer opponent had access to the complete history of choices and rewards

over the session, and was programmed to predict the mouse's next choice in order to make the

counter action (see Materials and Methods; same as 'algorithm 2' in (Lee et al., 2004) and

'competitor 1' in (Tervo et al., 2014)). ***Figure 1C*** shows the trial structure. A 0.2 s, 5 kHz sound

cue indicated the start of the trial. Within a 2-s response window, the mouse could make a

directional tongue lick to the left or right spout to indicate its choice. Based on the animal's and

computer's choices and the payoff matrix, the animal might receive a water reward after the

response. To minimize pre-cue licks, the inter-trial interval was drawn from a truncated

exponential distribution and would extend if the mouse could not suppress licking (see Materials

and Methods). Mice were trained daily and, on average, took about 4 weeks to follow the trial

timing to suppress pre-cue licking, and then another 4 weeks playing matching pennies to

achieve a performance threshold of 40% reward rate for 3 consecutive sessions. All the data

and analyses presented in the paper came from sessions after the threshold was attained.

The dataset for matching pennies included 81 behavioral sessions with concurrent pupil

measurements (n = 5 mice). For matching pennies, the Nash equilibrium indicates that rational

players should choose left and right with equal probabilities, which would yield a long-run

reward rate of 50%. In an example session, plotting the choices and rewards for a mouse and

the choices for the computer showed that the animal indeed exhibited a great degree of

stochasticity in its choice pattern (**Figure 1D**). This could be seen more clearly by looking at the

cumulative occurrences of various plausible 3-choice sequences (**Figure 1E**). Although there

was sometimes a slight preference for certain patterns, such as for right-right-right early in this

example session, throughout this session the animal continually employed different choice

sequences. On average, animals performed 513±13 trials per session (mean±s.e.m.; **Figure**

1F). The entropy for 3-choice sequences, a measure of the stochasticity in choices, was

2.87±0.02 bits, close to the theoretical upper bound of 3 bits. Consequently, the computer was

only mildly effective at predicting the mouse's choices, and mice earned an average reward rate

of 44.0±0.5%. We note that although the reward rate compared favorably with the optimal

reward rate of 50%, the difference was statistically significant ($P = 1.4 \times 10^{-20}$, one-sample one-

tailed t-test). For the inter-trial interval, 98.4% of the trials fell within the truncated exponential

distribution used to produce the random durations, and only 1.6% of the trials forming a small

tail reflecting the extended duration triggered by a pre-cue impulsive lick (**Figure 1G**). Response

times were stereotypical and similar for the left and right spouts (**Figure 1H**). These inter-trial

interval and response time analyses demonstrate effective pre-cue lick suppression and that the

animal makes the first physical indication of its choice after cue onset. Altogether, the results

show that head-fixed mice can play matching pennies against a computer opponent. Given that

humans and macaques likewise play matching pennies imperfectly and not at Nash equilibrium

(Erev and Roth, 1998; Lee et al., 2004), here we found that reward rate was decent but also

suboptimal for mice, suggesting that the animals had certain residual tendencies that were

exploited by the computer opponent.

Figure 1. Performance of head-fixed mice in a matching pennies game.

(A) A schematic illustration of the competitive game. Head-fixed mouse makes a left or right choice by licking the spouts. A computer monitors the mouse's past choices and outcomes, generating its own left or right choice every trial. **(B)** The payoff matrix of the game. The mouse receives a water reward if it chooses the same choice as the computer does in the same trial. **(C)** Trial timing: the mouse waits for a go cue, licks a spout to indicate its response, and the outcome is delivered immediately. A random inter-trial interval follows the outcome. **(D)** An example session. The reward rate for this session was 52.1%. Top: the mouse's choices and outcomes. Bottom: the computer's choices. Blue and red bars indicate right and left choices respectively. Black bars indicate rewards. **(E)** Cumulative number of different 3-choice patterns detected as the mouse progressed in the session shown in (D). **(F)** Summary from 81 sessions. Left: the average trials performed each session is 513±13. Middle: the average entropy of the 3-choice sequences is 2.87±0.02. Right: the average reward rate is 44.0%±0.5%. **(G)** The histogram of the inter-trial interval durations for all trials. Inter-trial interval would range from 4 to 8 s-long if the mouse did not lick to trigger additions to the inter-trial interval. **(H)** The response times for trials in which the mouse chose left (left) or right (right).

Animals' behavior was captured by a hybrid model with reinforcement learning and choice kernels

What is the strategy that characterizes the tendencies in the animal's behavior? Previous studies in macaque monkeys found that reinforcement learning can account in part for the animals' behavior in matching pennies (Lee et al., 2004; Seo et al., 2007). We therefore

compared between a range of strategies: win-stay-lose-switch (WSLS), and reinforcement

learning algorithms including Q-learning (Q_RPE), differential Q-learning (DQ_RPE), and

forgetting Q-learning (FQ_RPE) (Ito and Doya, 2009) (see Materials and Methods). Fitting each

model to the behavioral data, the Bayesian information criterion (BIC) values indicated that

FQ_RPE was most consistent with the choice behavior of the mice. To further improve the

model, we noted that mice exhibited serial choice dependence and sometimes favored picking

the same choice in successive trials (e.g., **Figure 1E**). To capture perseverative behavior, we

added choice kernels (Wilson and Collins, 2019) to create the FQ_RPE_CK algorithm. **Figure**

2A illustrates graphically the FQ_RPE_CK scheme (henceforth called the 'hybrid model'), with

reinforcement learning through FQ_RPE and perseveration through choice kernels. Note that

both the action values and choice kernels were updated on a trial-by-trial basis, and each had

its own learning rate (α and α_K) and inverse temperature parameters (β and β_K; see Materials

and Methods). A comparison of all 5 models indicated that the hybrid model provided the most

accurate fit to the behavioral data (**Figure 2B**). **Figure 2C** shows a representative session in

which we plotted the animal's choices and outcomes along with the latent variables, including

action values and choice kernels, estimated by the hybrid model. The model-estimated

probability of choosing left (black line, **Figure 2C**) tracked the actual choice pattern (gray line,

Figure 2C). Taken together, these analyses indicate that the mouse's behavior during matching

pennies can be quantified using a hybrid model including reinforcement learning and choice

kernels. For the remainder of the analyses, we will quantify the animal's strategy using the

hybrid model.

Figure 2. Computational modeling of the animals' behavior during matching pennies.

(A) Schematic of the hybrid FQ_RPE_CK model. Q_L, Q_R denote the action values for left and right choices; K_L, K_R denote the choice kernels for left and right choices. The agent chooses based on a weighted sum of action-value and choice-kernel differences ($\Delta Q, \Delta K$). The chosen action is used to compute the choice kernel error (CKE), which is used to update the choice kernels. The outcome is used to calculate the reward prediction error (RPE), which is used to update the action values. **(B)** Model comparison using BIC. **(C)** An example of the time course of the latent variables and predicted behavior. Top: Long red and blue bars indicate rewarded left and right choices; short red and blue bars indicate unrewarded left and right choices. Gray line shows the observed probability to choose left, smoothed by a gaussian kernel. Black line shows the probability to choose left predicted by the hybrid model. Middle: the action values of left (red) and right (blue) choices estimated by the hybrid model. Bottom: the choice kernels of left (red) and right (blue) choices estimated by the hybrid model.

Learning strategy in matching pennies in contrast to two-armed bandit task

To gain further insights into how the mouse competes against a computer opponent, we compared performance between matching pennies and the two-armed bandit task, which is a popular, non-competitive paradigm for assaying reward-based learning in rodents. In our implementation of the two-armed bandit, trials were organized into blocks, and each block was associated with one of two sets of reward probabilities (top panel, *Figure 3A*). The block switched randomly (see Materials and Methods) so that the mouse could not predict the switch

with certainty and must infer based on past choices and outcomes. Moreover, the timing of each

trial was design to be exactly the same between matching pennies and two-armed bandit

(**Figure 1C**). The bottom panel of **Figure 3A** presents an example session of a mouse engaging

in two-armed bandit, showing that the mouse readily adapting its actions in response to the

reversing reward probabilities. The same hybrid FQ_RPE_CK model could be used to quantify

the behavior, with the estimated choice probability tracking the mouse's choice pattern (**Figure**

supplement 1). Overall, mice performed the task well, averaging 702±26 trials per session with

a 43.5±1.1% reward rate (n = 26 sessions from 4 mice; **Figure 3B**). Model comparison based

on BIC indicated that the hybrid model outperformed win-stay lose-switch and other Q-learning-

based algorithms (**Figure 3C**).

A head-to-head comparison of the fitted learning parameters highlights the distinct modes of

operation employed by the mice for matching pennies versus two-armed bandit (**Figure 3D – I**).

In matching pennies, the choice kernel was weighed more strongly than reinforcement learning

during action selection ($\beta_K/(\beta_K+\beta)$ = 0.76±0.04; **Figure 3D**), although the sum of inverse

temperatures is relatively low, indicating high level of exploration ($\beta_K+\beta$ = 2.15± 0.07). The ratio

of learning rates suggests that the choice kernels were updated slower than the action values

(α_K/α = 0.22±0.04), which is illustrated by the example in **Figure 2C**, where the action values

fluctuate more rapidly than the choice kernels. In two-armed bandit, the fitted learning

parameters were significantly different. Namely, choice kernels had less weight ($\beta_K/(\beta_K+\beta)$ =

0.29±0.03; **Figure 3G**; P = 0.02, two-sided Wilcoxon rank-sum test) and inverse temperature

was higher ($\beta_K+\beta$ = 4.50±0.40; P = 0.02), indicating that the animals relied more on

reinforcement feedback to guide decisions and had a lower tendency to explore.

These disparate sets of fitted model parameters for the two tasks led to learning in different

regimes, which could be visualized by looking at the weighted sum of action-value and choice-

kernel differences, the crucial parameter for the softmax function for action selection each trial.

Here, on most matching pennies trials, animals decided with a weighted sum close to zero, i.e.,

with near equal probabilities of choosing left and right, making it difficult for the computer

opponent to predict their choice (**Figure 3E**). By contrast, performance during two-armed bandit

involved weighted sums lying at more extreme values (**Figure 3H**). This difference is consistent

with the animal spending considerable number of trials exploiting the high-reward-probability

side in a block, and only needed to adapt around a block switch. In both cases, the observed

choice probability (dots) fitted well to the softmax function used for action selection (dashed line,
Figure 3E and 3H).
505
Finally, to determine how varying the balance between reinforcement learning and choice kernel
would affect performance, we simulated choice behavior in the two tasks using a computer
agent, varying $\beta_K/(\beta_K+\beta)$ while fixing α_K/α and $\beta_K+\beta$. For matching pennies, the simulations
revealed that the reward rate was relatively stable if the computer agent used mostly
reinforcement learning or a hybrid strategy (***Figure 3F***). However, if the computer agent based
its actions exclusively on choice kernels, the performance declined precipitously. It was
intriguingly to see the $\beta_K/(\beta_K+\beta)$ estimated from behavioral data lied around the threshold
between these two conditions, indicating that the animals might have settled on a hybrid
strategy that balanced a tradeoff between reward and effort. For two-armed bandit, reward rate
is maximized if the agent uses only reinforcement learning to guide decisions. However, we find
that the animals have residual tendencies captured by choice kernel and therefore lie away from
optimal performance (***Figure 3I***). Collectively, the direct comparison across tasks illustrates the
utility of matching pennies for exploring a regime in reinforcement learning that is distinct from
the more widely used two-armed bandit paradigm.
520

Figure 3. Comparison between matching pennies and two-armed bandit: behavioral results, model fitting, and computer simulations.

(A) A schematic diagram of the two-armed bandit task. Top: Head-fixed mouse makes a left or right choice by licking the spouts. The trials are separated into different blocks based on the high (0.7) or low (0.1) reward probability assigned to each of the two choices. Middle: The assigned reward probabilities for the left (red) and right (blue) choices in an example session. Bottom: The choices and outcomes in the same session. The reward rate was 52.8%. Blue and red bars indicate right and left choices. Black bars indicate rewards. **(B)** Summary from 26 sessions. Top: the average trials performed each session is 702±26. Bottom: the average reward rate is 43.5%±1.1%. **(C)** Model comparison using BIC. **(D)** Learning parameters extracted from fitting the hybrid model to the matching pennies data. Left: the relative weight of choice kernel, $\beta_K/(\beta+\beta_K) = 0.75\pm0.04$. Middle: sum of inverse temperature, $\beta+\beta_K = 2.15\pm0.07$. Right: relative learning rate of the choice kernel. $\alpha_K/\alpha = 0.22\pm0.04$. **(E)** Psychometric curve based on the whole dataset. Black histograms indicate the distribution of trials according to the weighted sum of the difference of action values (ΔQ) and the difference of choice kernels (ΔK). Dashed purple line shows the predicted probability to choose left according to the softmax equation used by the hybrid model; Purple dots show the observed probability to choose left. **(F)** The performance of a computational agent playing the game, where $\beta_K/(\beta+\beta_K)$ was varied, while the learning rates and ($\beta+\beta_K$) were fixed and set to be the median of

The pupil response contained choice- and outcome-related signals during matching

pennies

While the mouse played matching pennies, a camera was positioned to capture a video of the

right eye (***Figure 4A***). We used the DeepLabCut toolbox (Mathis et al., 2018; Nath et al., 2019)

to extract pupil size from the videos (see Material and Methods). ***Figure 4B*** shows an example

frame with manually selected and computer-generated labels. To quantify the quality of the

automatic labeling, we calculated the deviations between the manually selected and

automatically estimated labels for the uppermost, lowermost, leftmost, rightmost, and central

points of the mouse's pupil (***Figure supplement 2A - B***). The mean values of the deviations

were close to zero, demonstrating that the estimates had little bias. To give an intuition into the

pupil size fluctuation observed, for one session, we plotted the time course of the pupil diameter

after z-score normalization (***Figure supplement 2C***). When aligned to select trial types, there

were obvious task-related transients in the pupil size (***Figure supplement 2D***). In this study, we

were interested in the relation between pupil fluctuations and decision-related variables on a

trial-by-trial basis, therefore we calculated the pupil response for each trial – which was defined

as the pupil size in z-score minus the pre-cue baseline z-score (***Figure 4C***).

To characterize the factors that drive pupil responses during matching pennies, we used

multiple linear regression. For each session, we fitted a regression model to determine the

relation between the pupil responses and the choices, outcomes, reinforcers (choice-outcome

interactions), the recent reward rate, and the cumulative reward (***Figure 4D***). Specifically, the

choices, outcomes, and interactions included terms for the next trial, the current trial, the last

trial, and the trial before last to capture the potential persistent effects of these variables on

neural correlates (Bari et al., 2019; Seo and Lee, 2007; Siniscalchi et al., 2019; Sul et al., 2010).

The analyses revealed that pupil responses were modulated by choices, outcomes, and

reinforcers during matching pennies (***Figure 4E – G***). For a significant fraction of sessions, we

detected a change in pupil size signaling the upcoming choice well before the trial would start

(c_{n+1}, ***Figure 4E***). The early choice-related signal suggested that the animal was planning and

preparing for the upcoming action prior to the cue. The choice-related signal ceased abruptly at

around the time of the cue onset for the next trial (c_{n-1}, ***Figure 4E***). Meanwhile, outcome- and

reinforcer-related signals in the pupil responses emerged after the potential reward would be

delivered and persisted for the next two trials (r_{n-1}, r_{n-2}, c_{n-1} * r_{n-1}, c_{n-2} * r_{n-2}, **Figure 4F, G**). The

pupil responses were also influenced by the cumulative reward ($r_n^{\text{Cum.}}$, **Figure 4H**), which related

to the number of trials performed, and therefore might reflect the motivational state of the

animal. Moreover, although choice consistently influenced the pupil responses, the mean

amplitude of the effect was more muted than outcome. Specifically, the presence of a reward

led a large phasic dilation of the pupil (r_n, **Figure 4I**).

Figure 4. Effects of choices and outcomes on pupil responses during matching pennies.

(A) A schematic illustration of the pupillometry set up. **(B)** An example still frame from a video showing both human labeling (dot) and DLC labeling (cross) for five labels. Scale bar, 50 pixels. **(C)** The pupil response at any time during a trial (-1 to 5 s from the cue) is the z-score at the corresponding time subtracted by the baseline, which is

the mean z-score between -2 and -1 s before the cue onset. **(D)** A schematic diagram of the multiple linear regression model, i.e., equation (9), that was fit to the pupil response in each 100 ms time bin. **(E)** The fraction of sessions with significant regression coefficient for choice in the next trial c_{n+1}, choice in the current trial c_n, choice in the previous trial c_{n-1}, and choice in the trial before the previous trial c_{n-2}. Red shading indicates the p-value from the chi-square test, without correcting for multiple comparison. **(F)** Same as (E) for trial outcomes. **(G)** Same as (E) for the interactions of choice and outcome. **(H)** Same as (E) for recent reward rate, calculated as a moving average over last 20 trials, and the cumulative reward from start of session to current trial. **(I)** The mean regression coefficients of several predictors: choice of the current trial (c_n), reward of the current trial (r_n). Shading indicates the 95% confidence interval estimated by bootstrap.

Pupil response was modulated by latent variables related to value updating, but not action selection

Previously we showed that the animals' behavior can be captured by the hybrid FQ_RPE_CK model, therefore we next asked whether pupil responses may accompany changes in select latent decision variables. To this end, we built additional multiple linear regression models using latent variables relevant for action selection or value updating. For action selection, we considered action-value difference, chosen value, choice-kernel difference, and chosen choice kernel (***Figure 5A***). Consistent with our prior observation, we found significant choice- and outcome-related signals (***Figure 5B - C***), however there was no reliable, sustained modulation of the pupil responses by the latent variables used for action selection ($Q_n^L - Q_n^R$, $K_n^L - K_n^R$, ***Figure 5D - E***). For value updating, we tested latent variables including reward prediction error (RPE) and choice kernel error (CKE) in addition to action-value difference and choice-kernel difference (***Figure 6A***). In a significant fraction of sessions, pupil responses were modulated by the RPE, and to a lesser extent CKE and choice-kernel difference (***Figure 6B – D***). Characteristically, mean coefficient was positive for both trials involving positive or negative RPE (***Figure 6E***). In other words, positive RPE led to phasic dilation of the pupil, whereas negative RPE was associated with transient reduction in pupil size. Overall, these analyses show that transient change in pupil diameter is modulated by latent variables used in value updating, namely the RPE.

Figure 5. Effects of decision variables for action selection on pupil responses during matching pennies. **(A)** A schematic diagram of the multiple linear regression model, i.e., equation (12). **(B)** The fraction of sessions with significant regression coefficient for the choice c_n, outcome r_n, and the interaction c_n x r_n in the current trial. Red shading indicates the p-value from the chi-square test, without correcting for multiple comparison. **(C)** Same as (B) for the choice, outcome, and interaction in the previous trial. **(D)** Same as (B) for the difference in action values ($Q_n^{\mathrm{L}} - Q_n^{\mathrm{R}}$), the action value of the chosen action (Q_n^{chosen}), and the difference in the choice kernel ($K_n^{\mathrm{L}} - K_n^{\mathrm{R}}$). **(E)** Same as (B) for choice kernel of the chosen action (K_n^{chosen}), moving-average reward rate ($\overline{r_n^{\mathrm{MA}}}$), and cumulative reward ($r_n^{\mathrm{Cum.}}$).

Figure 6. Effects of decision variables for value updating on pupil responses during matching pennies.
(A) A schematic diagram of the multiple linear regression model, i.e., equation (13). **(B)** The fraction of sessions with significant regression coefficient for choice in the current trial c_n, choice in the previous trial c_{n-1}, and outcome in the previous trial r_{n-1}. Red shading indicates the p-value from the chi-square test, without correcting for multiple comparison. **(C)** Same as (B) for difference in action values ($Q_n^L - Q_n^R$), the RPE, and the difference in choice kernels ($K_n^L - K_n^R$). **(D)** Same as (B) for the choice kernel error (CKE), moving-average reward rate ($\overline{r_n^{MA}}$), and cumulative reward ($r_n^{Cum.}$). **(E)** The mean regression coefficients for RPE (quantified separately for trials with positive or negative RPE) and CKE. Shading indicates the 95% confidence interval estimated by bootstrap.

Similar pupil correlates for decision-related variables during two-armed bandit task

The results presented so far indicated that for mice playing the matching pennies game, the transient pupil dilations were modulated by choice, outcome, and latent decision variables relevant for value updating. To determine if comparable pupil responses occur for two-armed bandit, we made recordings during the task and applied the same multiple linear regression analyses. We found that the choice- and outcome-dependent signals were present in a significant fraction of sessions (***Figure 7A***). The latent variables for action selection were largely absent (***Figure 7B***). The value updating variables, especially the RPE and again to a lesser degree the CKE, were associated with transient pupil responses (***Figure 7C***). Therefore, our results show that factors that influenced pupil responses in matching pennies – choice, outcome, and value updating variables – were also contributors to the pupil responses during the two-armed bandit task.

Figure 7. Multiple linear regression analyses of factors influencing pupil responses during two-armed bandit.

(A) The fraction of sessions with significant coefficient for choice in the next trial c_{n+1}, choice in the current trial c_n, choice in the previous trial c_{n-1}, outcome in the next trial r_{n+1}, outcome in the current trial r_n, and outcome in the previous trial r_{n-1},. The results were obtained by fitting equation (9) as we did in Figure 4 but onto pupil responses from two-armed bandit task. Red shading indicates the p-value from the chi-square test, without correcting for multiple comparison. (B) Same as (A) but for the difference in action values ($Q_n^{L} - Q_n^{R}$), the action value of the chosen action (Q_n^{chosen}), the difference in the choice kernel ($K_n^{L} - K_n^{R}$), and the choice kernel of the chosen action (K_n^{chosen}). The results were obtained by fitting equation (12) as we did in Figure 5 but onto pupil responses from two-armed bandit task. (C) same as (A) but for the RPE and the choice kernel error (CKE). The results were obtained by fitting equation (13) as we did in Figure 6 but onto pupil responses from two-armed bandit task.

Correlated fluctuations of left and right pupils during the two-armed bandit task

One intriguing result is that pupil response was influenced by choice, i.e., whether the animal

was choosing left or right. Is this a genuine choice-related signal? Some previous studies show

that pupil dilations can predict the upcoming choice of human subjects including the choice

timing and the selection of one out of five digits (Einhauser et al., 2010), and the decision of a

yes/no question (de Gee et al., 2014). However, another possibility is that when the animal

made a choice, the tongue lick movement could be associated with facial movements leading to

spurious detection of pupil size changes. To clarify the issue, we positioned two cameras to

record both eyes simultaneously during the two-armed bandit task (***Figure 8A***). For each eye,

we applied multiple linear regression (***Figure 4D***) to analyze the influences of choices and

outcomes on pupil responses. We reasoned that if the choice-related signal was a movement

artifact, then the aberrant signal should differ across eyes and across animals, and therefore the

coefficients extracted from left and right eye would be uncorrelated. By contrast, if the choice-

related signal was related to the animal's internal decision, we would expect consistent dilation

responses in both eyes. We analyzed the coefficients for the current choice between 3 – 5 s

from cue onset when the pupil responses were largest (***Figure 8B***). The choice-related signal

for the left pupil were correlated with that for the right pupil in every session (r = 0.83, *P* = 9 x 10^{-43}

). The positive correlation coefficient indicated that the pupil size changes are symmetric in the

two pupils. As a positive control, we plotted the coefficients of the current outcome in the same

time window, which was expected not to be lateralized and indeed showed a positive correlation

coefficient (r = 0.90, *P* = 0; ***Figure 8C***). Taken together, these results suggested that the effect

of choice on transient pupil response could not be explained by simple movement artifact.

Figure 8. Two-pupil recordings during the bandit task.

(A) Schematics of the two-pupil recordings setup. Two cameras were placed in front of the two pupils with the same angle while the mouse was performing the task. **(B)** Scatter plot of the linear regression coefficients of the current choice within the 3-5 s from the cue time. The linear regression is the same as shown in Figure 4. X-axis: coefficients of the left pupil; Y-axis: coefficients of the right pupil. Different colors represent different subjects. Each dot represents a 0.1-s interval within the 3-5 s period. The black line shows the diagonal when coefficients of the left pupil equal to that of the right pupil. **(C)** Same as (B) for current outcome.

DISCUSSION

The present study has two main findings. First, we demonstrated that head-fixed mice can play

a two-player competitive game against a computer opponent. Their tendencies in the matching

pennies game can be described by a computational model incorporating reinforcement learning

and choice kernels. Second, we showed that transient pupil responses of the animals were

associated with observable variables such as choices and outcomes, as well as latent variables

relevant for value updating, but not action selection.

Performance in the matching pennies game

Iterative matching pennies is a classic competitive game. Subjects playing the game tend to

deviate from the Nash Equilibrium. For example, human players attempting to generate random

choices would switch too often (Camerer, 2003). Macaque monkeys and chimpanzees also

showed deviation from the optimal strategy (Lee et al., 2004; Martin et al., 2014; Seo et al.,

2009; Seo and Lee, 2009; Soltani et al., 2006). Rats were shown to counter-predict the

opponent's choice first and switch to a more random behavior when facing a strong competitor
(Tervo et al., 2014). Moreover, pigeons playing the matching pennies game exhibit a similar
divergence from the optimal play as the humans do (Sanabria and Thrailkill, 2009). Here we
showed that head-fixed mouse can play matching pennies at a high level, albeit unsurprisingly
also gaining rewards at below optimal rates. Demonstrating that mice can be studied using
competitive game paradigms opens new avenues for studying neural circuitry for reward
learning in animal models of neuropsychiatric disorders (Barthas et al., 2020; Liao and Kwan,
2021).
644
Although initial characterizations of the tendencies for sub-optimal play have relied on standard
learning algorithms (Erev and Roth, 1998; Lee et al., 2004), recent studies have reported
deviations from the predictions of reinforcement learning (Hampton et al., 2008; Seo et al.,
2014; Tervo et al., 2014). In this study, we employed a hybrid model, which combines Q-
learning with choice kernels, also known as the choice-autocorrelation factor (Katahira, 2015;
Wilson and Collins, 2019). Specifically, choice kernels were included to capture serial choice
dependency, which is commonly observed in humans and animals performing various tasks
(Abrahamyan et al., 2016; Akaishi et al., 2014). The hybrid model indeed fit the behavior better
than variations of Q-learning algorithms (**Figure 2B**). We want to highlight the numerical
simulations where the reward rate was examined as a function of relative inverse temperature
(**Figure 3F**). The animal's performance lied at a regime where further increase in reliance on
choice kernel would deteriorate sharply the reward rate. The result hints at the possibility that
the animal may be maximizing a reward-effort trade-off, because repeating the same choice is
likely to be less effortful and indeed is the strategy taken by the animal often near the end of a
session.
660
Many studies of flexible decision-making in rodents have relied on two-armed bandit tasks with
a block-based design (Bari et al., 2019; Groman et al., 2019; Hattori et al., 2019; Ito and Doya,
2009; Sul et al., 2011; Sul et al., 2010; Tai et al., 2012). This paradigm has many merits, but
also a few shortcomings. First, the length of the blocks is a key parameter that defines the
volatility of the environment, but is typically manually set by the experimenter. By contrast,
matching pennies refers to a payoff matrix for gameplay, but contain no other experimenter-
defined parameters. Second, within a block, it is advantageous for the animals to continually
exploit the high-reward-probability option, therefore overtraining in the two-armed bandit task
may lead to strong serial choice dependencies. To the contrary, in matching pennies, the

computer opponent is designed to detect such dependencies and exert competitive pressure on

the animal, therefore the animal is encouraged to always diversify its choice patterns during the

session. Consequently, two-player games such as matching pennies are elegant and simple in

design, and allows for investigation of neural mechanism underlying flexible decision-making

under a regime that are quite different from multi-armed bandit tasks (*Figure 3D - I*).

Pupil responses and potential neuromodulatory mechanisms

Pupil fluctuation is an indicator of the arousal state of an animal, and likely associates with the

levels of various neuromodulators in the forebrain (McGinley et al., 2015). The relationship

between pupil size and NE is supported by prior results, which showed reliable tracking of pupil

fluctuations to activity of noradrenergic axons in the neocortex (Reimer et al., 2016).

Furthermore, studies of the locus coeruleus (LC), the main source of NE for the forebrain,

demonstrated a correlation between single unit firing in LC and pupil diameter (Aston-Jones and

Cohen, 2005; Yang et al., 2021), and pupil dilation triggered by electrical microstimulation of the

locus coeruleus (Joshi et al., 2016). Several studies have linked pupil dynamics and activity in

LC to choice behavior, such as in the consolidation of the previous choices (Clayton et al., 2004;

Einhauser et al., 2010) or the shaping of upcoming actions (de Gee et al., 2014). However,

these studies were based on visual perceptual tasks, which is different from our task design

where the cue is auditory and carries no relevant information except for trial timing. Our results

hint at a potential role for noradrenergic signaling in post-decisional value updating, because the

pupil response was correlated with the RPE and weakly associated with choice kernel error.

This would agree with work that have showed the importance for rewards in LC activity and

pupil dilation in various behavioral settings (Aston-Jones et al., 1997; Sara and Segal, 1991;

Varazzani et al., 2015). Furthermore, there is strong evidence linking pupil changes to errors

and adaptations in decision tasks involving trial- or block-based inference (Nassar et al., 2012;

Urai et al., 2017), highlighting the role of pupil-linked systems to control the influence of

incoming data to guide future decisions.

Overall, the current study lays the groundwork for studying reward-based learning in mice using

competitive games. The two-player matching pennies game, which we showed the mouse can

play against a computer opponent, may potentially be extended to a mouse competing against

another mouse in the future. The paradigm may therefore provide a quantitative framework for

evaluating social decision-making in mice. The findings of significant pupil correlates to the

major decision-related variables during matching pennies provide clues to the neuromodulatory

mechanisms in mice. The current results open avenues for future research into the role of

neuromodulators in mediating the adaptive and social aspects of decision-making in mice.

Acknowledgements

We thank Daeyeol Lee and Hyojung Seo for helping with programming the matching pennies

game, Michael Siniscalchi on behavioral training, and Matthew McGinley on the pupil recording

setup. This work was supported by NIH/NIMH grants R01MH112750 (A.C.K.), R01MH121848

(A.C.K.), R21MH118596 (A.C.K.), China Scholarship Council-Yale World Scholars Fellowship

(H.W.), Gruber Science Fellowship (H.K.O.), NIH training grant T32NS007224 (H.K.O.), and

Kavli Institute for Neuroscience Postdoctoral Fellowship (H.A.).

Author Contributions

H.W. and A.C.K. designed the research. H.W. performed the matching pennies experiments.

H.K.O. and C.E.M. performed the two-armed bandit experiments. H.W. analyzed the data. H.A.

assisted by developing the bandit task and providing code for analysis. H.W. and A.C.K. wrote

the paper with input from all other authors.

References

Abrahamyan, A., Silva, L.L., Dakin, S.C., Carandini, M., and Gardner, J.L. (2016). Adaptable
history biases in human perceptual decisions. Proceedings of the National Academy of
Sciences 113, E3548-E3557.
Akaishi, R., Umeda, K., Nagase, A., and Sakai, K. (2014). Autonomous mechanism of internal
choice estimate underlies decision inertia. Neuron 81, 195-206.
Aston-Jones, G., and Cohen, J.D. (2005). An integrative theory of locus coeruleus-
norepinephrine function: adaptive gain and optimal performance. Annu Rev Neurosci 28, 403-
450.
Aston-Jones, G., Rajkowski, J., and Kubiak, P. (1997). Conditioned responses of monkey locus
coeruleus neurons anticipate acquisition of discriminative behavior in a vigilance task.
Neuroscience 80, 697-715.
Bari, B.A., Grossman, C.D., Lubin, E.E., Rajagopalan, A.E., Cressy, J.I., and Cohen, J.Y.
(2019). Stable Representations of Decision Variables for Flexible Behavior. Neuron.
Barraclough, D.J., Conroy, M.L., and Lee, D. (2004). Prefrontal cortex and decision making in a
mixed-strategy game. Nat Neurosci 7, 404-410.
Barthas, F., Hu, M.Y., Siniscalchi, M.J., Ali, F., Mineur, Y.S., Picciotto, M.R., and Kwan, A.C.
(2020). Cumulative Effects of Social Stress on Reward-Guided Actions and Prefrontal Cortical
Activity. Biol Psychiatry 88, 541-553.
Bouret, S., and Sara, S.J. (2005). Network reset: a simplified overarching theory of locus
coeruleus noradrenaline function. Trends Neurosci 28, 574-582.
Camerer, C. (2003). Behavioral Game Theory: Experiments in Strategic Interaction (Princeton
University Press).
Caze, R.D., and van der Meer, M.A. (2013). Adaptive properties of differential learning rates for
positive and negative outcomes. Biol Cybern 107, 711-719.

Chang, S.W., Gariepy, J.F., and Platt, M.L. (2013). Neuronal reference frames for social
decisions in primate frontal cortex. Nat Neurosci 16, 243-250.
Clayton, E.C., Rajkowski, J., Cohen, J.D., and Aston-Jones, G. (2004). Phasic activation of
monkey locus ceruleus neurons by simple decisions in a forced-choice task. J Neurosci 24,
9914-9920.
Dal Monte, O., Chu, C.C.J., Fagan, N.A., and Chang, S.W.C. (2020). Specialized medial
prefrontal-amygdala coordination in other-regarding decision preference. Nat Neurosci 23, 565-
574.
de Gee, J.W., Knapen, T., and Donner, T.H. (2014). Decision-related pupil dilation reflects
upcoming choice and individual bias. Proc Natl Acad Sci U S A 111, E618-625.
Einhauser, W., Koch, C., and Carter, O.L. (2010). Pupil dilation betrays the timing of decisions.
Front Hum Neurosci 4, 18.
Erev, I., and Roth, A.E. (1998). Predicting how people play games: Reinforcement learning in
experimental games with unique, mixed strategy equilibria. American Economic Review 88,
848-881.
Gilzenrat, M.S., Nieuwenhuis, S., Jepma, M., and Cohen, J.D. (2010). Pupil diameter tracks
changes in control state predicted by the adaptive gain theory of locus coeruleus function. Cogn
Affect Behav Neurosci 10, 252-269.
Groman, S.M., Keistler, C., Keip, A.J., Hammarlund, E., DiLeone, R.J., Pittenger, C., Lee, D.,
and Taylor, J.R. (2019). Orbitofrontal Circuits Control Multiple Reinforcement-Learning
Processes. Neuron.
Hampton, A.N., Bossaerts, P., and O'Doherty, J.P. (2008). Neural correlates of mentalizing-
related computations during strategic interactions in humans. Proc Natl Acad Sci U S A 105,
6741-6746.
Haroush, K., and Williams, Z.M. (2015). Neuronal prediction of opponent's behavior during
cooperative social interchange in primates. Cell 160, 1233-1245.
Hattori, R., Danskin, B., Babic, Z., Mlynaryk, N., and Komiyama, T. (2019). Area-Specificity and
Plasticity of History-Dependent Value Coding During Learning. Cell 177, 1858-1872 e1815.
Hess, E.H., and Polt, J.M. (1960). Pupil size as related to interest value of visual stimuli.
Science (New York, NY) 132, 349-350.
Ito, M., and Doya, K. (2009). Validation of decision-making models and analysis of decision
variables in the rat basal ganglia. J Neurosci 29, 9861-9874.
Jepma, M., and Nieuwenhuis, S. (2011). Pupil diameter predicts changes in the exploration–
exploitation trade-off: Evidence for the adaptive gain theory. Journal of cognitive neuroscience
23, 1587-1596.
Joshi, S., Li, Y., Kalwani, R.M., and Gold, J.I. (2016). Relationships between Pupil Diameter and
Neuronal Activity in the Locus Coeruleus, Colliculi, and Cingulate Cortex. Neuron 89, 221-234.
Katahira, K. (2015). The relation between reinforcement learning parameters and the influence
of reinforcement history on choice behavior. Journal of Mathematical Psychology 66, 59-69.
Katahira, K. (2018). The statistical structures of reinforcement learning with asymmetric value
updates. Journal of Mathematical Psychology 87, 31-45.
Lee, D. (2008). Game theory and neural basis of social decision making. Nat Neurosci 11, 404-
409.
Lee, D., Conroy, M.L., McGreevy, B.P., and Barraclough, D.J. (2004). Reinforcement learning
and decision making in monkeys during a competitive game. Brain Res Cogn Brain Res 22, 45-
58.
Liao, C., and Kwan, A.C. (2021). Applying Reinforcement Learning to Rodent Stress Research.
Chronic Stress (Thousand Oaks) 5, 2470547020984732.
Martin, C.F., Bhui, R., Bossaerts, P., Matsuzawa, T., and Camerer, C. (2014). Chimpanzee
choice rates in competitive games match equilibrium game theory predictions. Sci Rep 4, 5182.

Mathis, A., Mamidanna, P., Cury, K.M., Abe, T., Murthy, V.N., Mathis, M.W., and Bethge, M. (2018). DeepLabCut: markerless pose estimation of user-defined body parts with deep learning. Nat Neurosci 21, 1281-1289.

McGinley, M.J., Vinck, M., Reimer, J., Batista-Brito, R., Zagha, E., Cadwell, C.R., Tolias, A.S., Cardin, J.A., and McCormick, D.A. (2015). Waking state: rapid variations modulate neural and behavioral responses. Neuron 87, 1143-1161.

Nassar, M.R., Rumsey, K.M., Wilson, R.C., Parikh, K., Heasly, B., and Gold, J.I. (2012). Rational regulation of learning dynamics by pupil-linked arousal systems. Nat Neurosci 15, 1040-1046.

Nath, T., Mathis, A., Chen, A.C., Patel, A., Bethge, M., and Mathis, M.W. (2019). Using DeepLabCut for 3D markerless pose estimation across species and behaviors. Nat Protoc 14, 2152-2176.

Pajkossy, P., Szőllősi, Á., Demeter, G., and Racsmány, M. (2017). Tonic noradrenergic activity modulates explorative behavior and attentional set shifting: Evidence from pupillometry and gaze pattern analysis. Psychophysiology 54, 1839-1854.

Qiyuan, J., Richer, F., Wagoner, B.L., and Beatty, J. (1985). The pupil and stimulus probability. Psychophysiology 22, 530-534.

Reimer, J., McGinley, M.J., Liu, Y., Rodenkirch, C., Wang, Q., McCormick, D.A., and Tolias, A.S. (2016). Pupil fluctuations track rapid changes in adrenergic and cholinergic activity in cortex. Nat Commun 7, 13289.

Sanabria, F., and Thrailkill, E. (2009). Pigeons (Columba livia) approach Nash equilibrium in experimental Matching Pennies competitions. J Exp Anal Behav 91, 169-183.

Sara, S.J., and Segal, M. (1991). Plasticity of sensory responses of locus coeruleus neurons in the behaving rat: implications for cognition. Progress in brain research 88, 571-585.

Seo, H., Barraclough, D.J., and Lee, D. (2007). Dynamic signals related to choices and outcomes in the dorsolateral prefrontal cortex. Cereb Cortex 17 Suppl 1, i110-117.

Seo, H., Barraclough, D.J., and Lee, D. (2009). Lateral intraparietal cortex and reinforcement learning during a mixed-strategy game. J Neurosci 29, 7278-7289.

Seo, H., Cai, X., Donahue, C.H., and Lee, D. (2014). Neural correlates of strategic reasoning during competitive games. Science (New York, NY) 346, 340-343.

Seo, H., and Lee, D. (2007). Temporal filtering of reward signals in the dorsal anterior cingulate cortex during a mixed-strategy game. J Neurosci 27, 8366-8377.

Seo, H., and Lee, D. (2009). Behavioral and neural changes after gains and losses of conditioned reinforcers. J Neurosci 29, 3627-3641.

Siniscalchi, M.J., Phoumthipphavong, V., Ali, F., Lozano, M., and Kwan, A.C. (2016). Fast and slow transitions in frontal ensemble activity during flexible sensorimotor behavior. Nat Neurosci 19, 1234-1242.

Siniscalchi, M.J., Wang, H., and Kwan, A.C. (2019). Enhanced Population Coding for Rewarded Choices in the Medial Frontal Cortex of the Mouse. Cereb Cortex 29, 4090-4106.

Soltani, A., Lee, D., and Wang, X.J. (2006). Neural mechanism for stochastic behaviour during a competitive game. Neural Netw 19, 1075-1090.

Sul, J.H., Jo, S., Lee, D., and Jung, M.W. (2011). Role of rodent secondary motor cortex in value-based action selection. Nat Neurosci 14, 1202-1208.

Sul, J.H., Kim, H., Huh, N., Lee, D., and Jung, M.W. (2010). Distinct roles of rodent orbitofrontal and medial prefrontal cortex in decision making. Neuron 66, 449-460.

Sutton, R.S., and Barto, A.G. (1998). Reinforcement learning: An introduction, Vol 1 (MIT press Cambridge).

Tai, L.H., Lee, A.M., Benavidez, N., Bonci, A., and Wilbrecht, L. (2012). Transient stimulation of distinct subpopulations of striatal neurons mimics changes in action value. Nat Neurosci 15, 1281-1289.

Tervo, D.G., Proskurin, M., Manakov, M., Kabra, M., Vollmer, A., Branson, K., and Karpova,
A.Y. (2014). Behavioral variability through stochastic choice and its gating by anterior cingulate
cortex. Cell 159, 21-32.
Urai, A.E., Braun, A., and Donner, T.H. (2017). Pupil-linked arousal is driven by decision
uncertainty and alters serial choice bias. Nat Commun 8, 14637.
Van Slooten, J.C., Jahfari, S., Knapen, T., and Theeuwes, J. (2018). How pupil responses track
value-based decision-making during and after reinforcement learning. PLoS Comput Biol 14,
e1006632.
Varazzani, C., San-Galli, A., Gilardeau, S., and Bouret, S. (2015). Noradrenaline and dopamine
neurons in the reward/effort trade-off: a direct electrophysiological comparison in behaving
monkeys. Journal of Neuroscience 35, 7866-7877.
Vickery, T.J., Chun, M.M., and Lee, D. (2011). Ubiquity and specificity of reinforcement signals
throughout the human brain. Neuron 72, 166-177.
Wilson, R.C., and Collins, A.G. (2019). Ten simple rules for the computational modeling of
behavioral data. Elife 8.
Wood, R.I., Kim, J.Y., and Li, G.R. (2016). Cooperation in rats playing the iterated Prisoner's
Dilemma game. Anim Behav 114, 27-35.
Yang, H., Bari, B.A., Cohen, J.Y., and O'Connor, D.H. (2021). Locus coeruleus spiking
differently correlates with S1 cortex activity and pupil diameter in a tactile detection task. Elife
10.

Supplementary figures

Figure supplement 1. Computational modeling of the animals' behavior during two-armed bandit.

(A) The switch of the reward probabilities of left (red) and right (blue) choices. **(B)** An example of the time course of the latent variables and predicted behavior in the same session as (A). Top: Long red and blue bars indicate rewarded left and right choices. Short red and blue bars indicate unrewarded left and right choices. Gray line shows the observed probability to choose left, smoothed by a gaussian kernel. Black line shows the probability to choose left predicted by the hybrid model. Middle: the action values of left (red) and right (blue) choices estimated by the hybrid model. Bottom: the choice kernels of left (red) and right (blue) choices estimated by the hybrid model.

Figure supplement 2. Extracting the pupil size using DLC.

(A) Deviation of DLC labels from manually selected labels in the x-axis (n = 324 frames, taken from different sessions of multiple animals). **(B)** Same as (A) for y-axis. **(C)** An example trace of the z-score of pupil diameter during a session of matching pennies. **(D)** Mean traces of z-score of pupil diameter for four different trial types: rewarded left choice, unrewarded left choice, rewarded right choice, unrewarded right choice. Shading indicates the standard deviation.