1   **Evidence Accumulates for Individual Attributes during Value-Based Decisions**

2   Douglas G. Lee [1]   Todd A. Hare [2,3]

3   [1] Institute of Cognitive Sciences and Technologies, National Research Council of Italy

4   [2] Zurich Center for Neuroeconomics, Department of Economics, University of Zurich

5   [3] Neuroscience Center Zurich, University of Zurich and ETH Zurich

12   Email for correspondence:

13   DouglasGLee@gmail.com

14   **Abstract**

When choosing between different options, we tend to consider specific attribute qualities rather

than deliberating over some general sense of the options' overall values. The importance of each

attribute together with its quality will determine our preference rankings over the available

alternatives. Here, we test the hypothesis that the most prominent class of model for simple

decisions – sequential sampling or evidence accumulation to bound – can be bolstered by explicitly

incorporating variables related to individual attributes in addition to the standard usage of overall

value estimates. We examine six datasets in which participants evaluated snack foods both in terms

of overall value and individual attributes, then chose between pairs of the same snacks, and show

that only models that explicitly incorporate information about the individual attributes are able to

reproduce fundamental patterns in the choice data, such as the influence of attribute disparity on

decisions, and such models provide quantitatively better fits to the choice outcomes, response

times, and confidence ratings compared to models based on overall value alone. Our results

provide important evidence that incorporating attribute-level information into computational

models helps us to better understand the cognitive processes involved in value-based decision-

making.

Keywords: multi-attribute choice, value-based choice, preferential choice, sequential sampling

model, drift-diffusion model

33   **Introduction**

34   Most decisions that we make are based on information about a variety of relevant features

of the available options. Theories and mathematical models of multi-attribute choice generally

agree that, *in principle*, the decision system in our brains should compare options based on how

well they score cumulatively across all relevant attribute dimensions (Bettman et al., 1998; E. J.

Johnson & Payne, 1985; Keeney et al., 1993; Levav et al., 2010; Payne et al., 1988, 1993; Russo

et al., 1996; Shah & Oppenheimer, 2008). These overall scores, be they based on subjective

valuations or more objective features, are typically thought to be calculated as the weighted sums

of sub-scores across all dimensions (Bettman et al., 1998; Bhatia & Stewart, 2018; E. J. Johnson

& Payne, 1985; Levav et al., 2010; Payne et al., 1988, 1993; Russo et al., 1996; Shah &

Oppenheimer, 2008). Specifically, each option will be assigned a score along each attribute

dimension, and each dimension will be given some weight according to how relevant or important

it is to the decision. Simplifications of this strategy that assign equal weights to all attributes

(Dawes, 1979; Dawes & Corrigan, 1974), reduce attribute scores to binary better/worse rankings

(Russo & Dosher, 1983), or only consider a subset of the attributes have also been proposed

(Fishburn, 1974; Tversky, 1972). How well these simpler strategies perform depends on the choice

context (Bettman et al., 1998; Gigerenzer & Gaissmaier, 2011; E. J. Johnson & Payne, 1985; Levav

et al., 2010; Payne et al., 1988, 1993; Russo et al., 1996; Shah & Oppenheimer, 2008). Regardless

of precisely how they are combined, almost every choice is determined by an assessment of

multiple attributes. Thus, it is important for both basic and applied researchers to better understand

how the attribute composition of choice options (and not just their overall values) influences the

decision-making process in the brain.

Recent work has investigated the question of whether value-based decisions are driven by

attribute-level comparison processes, and specifically whether such processes might lead to choice

behavior that systematically varies as a function of the disparity of the options' attribute

compositions (D. G. Lee & Holyoak, 2021b). A pair of options has high disparity if, for example,

one option scores high in the first attribute dimension but low in the second, while the other option

scores high in the second dimension but low in the first (Figure 1a, left panel). On the contrary, a

pair of options has low disparity if both options have similar scores along each attribute dimension

(Figure 1a, middle panel). Notably, two decisions could be equally difficult in the traditional sense

that the overall value ratings of the choice options are equally close together, yet have very

different levels of disparity (Figure 1a, right panel). In multiple independent experiments, Lee &

Holyoak (D. G. Lee & Holyoak, 2021b) found that choice behavior differs as a function of

disparity, such that higher disparity corresponds to higher choice consistency (i.e., a choice in favor

of the option that was previously rated as having the higher overall value), lower response time,

and higher choice confidence, even after accounting for differences in overall values. Here, we re-

examine the Lee & Holyoak (D. G. Lee & Holyoak, 2021b) data using computational modeling

and show that models of value comparison that assume an immutable combination of attributes

into the overall option value cannot account for this pattern of results.

Figure 1. Choice disparity. a) A schematic illustration of orthogonal components of choice difficulty: dV and disparity. *The left plot illustrates a "high disparity" choice, and the middle plot illustrates a "low disparity" choice. The orange and green dots represent the alternative options for each choice, each plotted according to its measurements on two attribute dimensions. The example assumes equal importance weights for each attribute, so the iso-value curves are represented by parallel lines with slope -1. The difference in overall value of the options, dV, is the distance between the iso-value curves on which the options lie. Disparity is the distance between the options in the dimension orthogonal to overall value (see Equation 1 below for a mathematical formulation). The right plot shows the location of each choice pair in the transformed dV-disparity space.* **b)** *An example illustration of two choice sets for snack foods, one high disparity (left plot), one low disparity (right plot). As shown by the dashed iso-value lines, all of the available snacks are of comparable overall value (and thus each choice pair is of comparable low dV). However, the two choice pairs are of very different disparity. In the high disparity pair (left), one option scores high on pleasure but low on nutrition, while the other option scores low on pleasure but high on nutrition. In the low disparity pair (right), both options score high on pleasure and low on nutrition.*

Instead, choices between naturalistic multi-attribute stimuli and subsequent confidence

reports for those choices are best explained by models in which individual attributes are actively

(re)weighted during the comparison process. In our tests, we focus on multi-attribute choices

between naturalistic unitary options with multiple inherent latent features, as opposed to bundled

or conjoint options made up of multiple components (e.g., probability + amount for risky choice;

delay + amount for inter-temporal choice; effort or pain + reward for cost-benefit tradeoffs;

different items for bundled choices). We believe that this type of naturalistic reward, which could

plausibly be treated as an integrated whole, provides a stronger test of whether items are compared

based on fixed weights that yield stable overall values or values constructed from flexible attribute

weights during decisions. We find that models that allow context-dependent attribute weights

during decisions best explain the outcome, response time, and confidence data. This demonstrates

not only that attributes are considered individually, but also that the manner in which attributes

contribute to value estimates (measured either explicitly through ratings or implicitly through

choices) might vary across context (rating versus choice). However, we also show that using a

subset of attribute-specific ratings together with overall value ratings can help to better explain the

choice data (e.g., when obtaining ratings for the full set of potentially relevant attributes is

impractical).

In the domain of risky choice, it has long been established that individuals' preferences

over options that combine monetary gains and losses with probabilities or time delays may reverse

when different methods are used to elicit those preferences. For example, preferences revealed

through choices have been shown to reverse compared to those elicited by matching, pricing, or

rating procedures (Alós-Ferrer et al., 2016; Alos-Ferrer et al., 2020; Alós-Ferrer et al., 2021;

Fischer et al., 1999; Grether & Plott, 1979; Lichtenstein & Slovic, 1971; Seidl, 2002; Tversky et

al., 1988, 1990; Weber & Johnson, 2009). A leading explanation for these preference reversals is

that the importance weights on the probability, time, and/or money dimensions differ across the

preference elicitation procedures (Seidl, 2002; Tversky et al., 1988). Eye-tracking experiments

have shown that changes in the proportion of visual fixations to the monetary amount of a lottery's

potential outcome relative to its probability across choice and pricing trials are associated with the

differences in the relative weights given to amounts versus probabilities when choosing versus

setting a price (Alós-Ferrer et al., 2021). This influence of visual attention on context-dependent

weighting is consistent with sequential sampling models that predict that the effects of overall

value and attribute differences on choices are determined in part by the amount of attention paid

to each option or attribute (Busemeyer & Townsend, 1993; Diederich, 1997; Krajbich et al., 2010;

Roe et al., 2001). Together, these theories and data form the basis of our hypothesis that decision

values in naturalistic multi-attribute choices will also be constructed at the time of choice from the

options' basic attributes in a context-dependent manner, rather than being compared as unitary

overall values aggregated across all attributes in a constant fashion. We aim to show that individual

attributes directly influence the valuation process in consumer choices over unitary goods whose

attributes must be recalled from memory rather than read off a screen. We propose that attribute-

level evidence accumulation is necessary and sufficient to explain the observed disparity effects

on choice (D. G. Lee & Holyoak, 2021b).

132   **Methods**

Data

We analyzed the data from six previously published experiments (Experiments 1-5 in (D.

G. Lee & Holyoak, 2021b), plus one unpublished pilot experiment that we label Experiment 0).

Experiments 1-5 recruited a total of 325 participants (186 female, mean age = 40, age range: 19-

50) and Experiment 0 recruited 55 participants (demographic data were not recorded for this

unpublished experiment). All participants were native English speakers from the United States or

Canada, recruited via Amazon Mechanical Turk. The total number of participants included in our

analyses was 307 (41 for Experiment 0, 50 for experiment 1, 48 for experiment 2, 54 for

experiment 3, 60 for experiment 4, and 54 for experiment 5), using the same exclusion criteria

from the original study: using Spearman correlation coefficients between first and last ratings

(within participant) in addition to slope parameters from logistic regression of choice on value

(separately using first and last ratings), participants with scores outside a cutoff (median +/−3 ×

median average deviation) were excluded.

In each experiment, participants completed several distinct phases. They first passively

observed images of individual snack foods (100 in Experiments 0 and 1, 60 in Experiments 2-5).

Second, they provided overall value ratings for each individual snack food. Next, they rated the

pleasure they expected to derive from each food and its nutritional value, in separate experimental

sections (the order of the pleasure and nutrition rating tasks was counterbalanced across

participants). In Experiments 2-5, participants then completed a "non-choice" task (e.g., stating

how similar paired options were to each other), followed by another series of rating tasks (overall

value, pleasure, and nutrition) identical in format to the initial rating tasks. In all experiments,

participants then completed a choice task in which they chose their preferred snack from pairs of

options (50 choice trials for Experiments 0 and 1, 30 choice trials for Experiments 2-5). During

the choice section, after each choice, participants also rated their confidence that the option they

chose was indeed their preferred option on that trial. Lastly, participants completed a final series

of rating tasks (overall value, pleasure, and nutrition) identical in format to the previous rating

tasks. For the purposes of our current study, we focus on those ratings that occurred immediately

prior to the choice task (i.e., the first series of ratings for Experiments 0-1 and the second series of

ratings for Experiments 2-5). We also examine the post-choice ratings, to rule out the possibility

that the reported results only hold for pre-choice ratings. We did not expect to find any differences

by rating timing, since the pre- and post-choice ratings were highly correlated (cross-participant

median Pearson correlation coefficient for overall value, pleasure, and nutrition, respectively: 0.90,

0.90, 0.95). The consistency of the pre- and post-choice ratings indicates that participants likely

reported their true opinions during each of the rating sessions. This is because random ratings

would not be as consistent, and maintaining intentionally altered ratings of attributes or overall

value relative to one another would require exerting substantial cognitive effort for no real benefit,

which is something that humans rarely do. See Figure 2 for an illustration of the different tasks.

Figure 2. Task illustration. *An example of what participants saw on the screen during each*
experimental section..
173

In addition to the aforementioned datasets, we also examined data from an unpublished

pilot auxiliary task that were originally collected along with the primary data reported in (D. G.

Lee & Daunizeau, 2021). The participants in this study were native French speakers, recruited via

the RISC platform at the Paris Brain Institute (demographic data not available). In this study, all

participants provided overall value ratings for 148 food options, then made 74 choices between

pairs of options, then again provided overall value ratings for the same 148 options. Out of the

main group of participants, 17 completed the auxiliary task (determined solely by which

participants had extra time remaining in their assigned testing time slot), in which they rated each

of the food options in terms of "taste", "health", "texture", and "appearance". The format of the

different tasks was similar to that described above, except that all text was presented in the French

language. We are thus able to compare versions of our models (described below) that incorporate

four attributes rather than two (the third and fourth attributes enter the models in the same way as

the first and second attributes).

Evidence accumulation models

In this study, we consider several ways in which attribute and overall value estimates might

influence the evidence accumulation process in a sequential sampling model (Bhatia, 2013;

Busemeyer et al., 2019; Pleskac & Busemeyer, 2010; Ratcliff, 1978; Ratcliff & McKoon, 2008;

Ratcliff & Rouder, 1998; Roe et al., 2001; Trueblood et al., 2014; Usher & Mcclelland, 2001). The

specifics of each model are detailed below. Within the evidence accumulation-to-bound class of

models, the values of the options (in simple two-alternative forced-choice tasks) are repeatedly

compared across time. The so-called evidence that arises in favor of one option over the other is

corrupted by processing (e.g., neural) noise, so repeated samples are accumulated to cancel out the

noise. Once a sufficient amount of evidence has been accrued (i.e., the response threshold is

reached), the process terminates and a choice is made. The various types of evidence accumulation

model that operate over differences in evidence for each option or allow inhibition between

separate accumulators all make qualitatively similar predictions about the relationship between the

evidence accumulation rate and choice probabilities, response times (RTs), and confidence ratings.

Specifically, greater evidence accumulation rates are associated with more correct or consistent

choices, faster RTs, and higher levels of confidence. We tested the fit of these generalized

predictions to data when the evidence accumulation rate is proportional to the difference in overall

value between the options (OV) or to a weighted linear combination of the differences in individual

attributes (IA) using six different empirical data sets. We demonstrate that the evidence

accumulation based on a weighted linear combination of the differences in individual attributes

provides a better account of choice probabilities, mean RTs, and the effects of attribute disparity

on choice outcomes and RT.

Evidence accumulation based on overall value (OV)

In this case, evidence about the overall value of each option is sampled at each time step,

the evidence for the two options is compared, and the relative evidence in favor of option 1 over

option 2 is aggregated by the evidence accumulator. For simplicity, we use a basic drift diffusion

model (DDM, (Ratcliff, 1978; Ratcliff & McKoon, 2008; Ratcliff & Rouder, 1998)) with

symmetric and constant boundaries to derive quantitative predictions about choices, response

times, and confidence levels. However, we note that the predictions of many types of evidence

accumulation model are qualitatively similar, and we make no concrete claims about the specific

mechanisms of the accumulation and decision process beyond the nature of the evidence being

accumulated. We assume that the cumulative evidence (x) evolves across deliberation time as

follows:

222
$$x_t = x_{t-1} + d(\mu_1 - \mu_2) + \varepsilon$$

223
$$\varepsilon \sim N(0, \sigma^2)$$

224
$$x_0 = 0$$

where d is an efficiency parameter for the evidence accumulation (the drift rate in a DDM), μ_i is

the reported overall value of option $i \in \{1, 2\}$, and σ^2 is the strength of the white noise ε in the

accumulation process. Evidence sampling and accumulation proceeds until x reaches a response

boundary $\in \{\theta, -\theta\}$, with the sign determining the chosen option (arbitrarily defined as positive for

option 1, negative for option 2). Response time (RT) is equal to t at the moment a boundary is

crossed. General predictions about the choice probability (p, choice of option 1) and mean RT can

be analytically derived (Alós-Ferrer, 2018) as a function of μ_1, μ_2, and σ^2, with θ being fixed (here,

to $\theta = 1$ for simplicity):

233
$$DV = \mu_1 - \mu_2$$

234
$$p = \frac{1}{1 + e^{\left(\frac{-2dDV}{\sigma^2}\right)}}$$

235
$$RT = \frac{2p - 1}{dDV}$$

where μ_1 and μ_2 are independent variables, and d and σ^2 are free parameters to be estimated to

capture the individual-specific mean rate of evidence accumulation (drift rate) and level of noise

in the accumulation process, respectively. We focus on mean response times because those are

more similar across the different flavors of evidence accumulation models than the entire response

time distribution, and our aim is to test general predictions independent of any specific model.

Evidence accumulation based on individual attributes (IA)

In this case, evidence about the individual attributes of each option is sampled at each time

step, the evidence for the two options is compared separately for each attribute, and the relative

evidence in favor of option 1 over option 2 for each attribute is aggregated by the evidence

accumulator. The IA model is of the same form as the OV model, except that the evidence

accumulator is driven by two evidence streams (one for each attribute dimension: a, b). The process

is otherwise identical, and it unfolds as follows:

249
$$x_t = x_{t-1} + d^a(\mu_1^a - \mu_2^a) + d^b(\mu_1^b - \mu_2^b) + \varepsilon$$

250
$$\varepsilon \sim N(0, \sigma^2)$$

251
$$x_0 = 0$$

252   where μ_i^j is the reported value of option $i \in \{1,2\}$ along attribute dimension $j \in \{a,b\}$, and σ^2 is

253   white noise common to the overall evidence accumulation process. Choice probability and mean

254   RT are derived as:

255
$$DV^a = \mu_1^a - \mu_2^a$$

256
$$DV^b = \mu_1^b - \mu_2^b$$

257
$$p = \frac{1}{1 + e^{\left[\frac{-2(d^a DV^a + d^b DV^b)}{\sigma^2}\right]}}$$

258
$$RT = \frac{2p - 1}{d^a DV^a + d^b DV^b}$$

where d^j are independent free parameters that allow for different rates of evidence accumulation

within each attribute dimension $j \in \{a,b\}$.

Evidence accumulation based on overall value and individual attributes (IA+)

In this case, evidence about both the overall value and the individual attributes of each

option is sampled at each time step, the evidence (for both OV and IA) for the two options is

compared, and the relative evidence in favor of option 1 over option 2 is aggregated by the

evidence accumulator. This IA+ model is of the same basic form as the OV and IA models.

However, the IA+ assumes that the drift rate is driven by the separate values of the individual

attributes that were explicitly evaluated (in these experiments, pleasure and nutrition), but that it

is also influenced by other attributes that were not explicitly evaluated. Thus, if the overall value

ratings contain information about the attributes that were rated individually as well as other

attributes that were not rated, including overall value should enhance the model fit. Therefore, in

this model, the evidence accumulator is driven by evidence streams for each explicit attribute

dimension as well as the aggregate overall value estimates. The process is otherwise identical to

that in the OV and IA models, and it unfolds as follows:

$$x_t = x_{t-1} + d^o(\mu_1^o - \mu_2^o) + d^a(\mu_1^a - \mu_2^a) + d^b(\mu_1^b - \mu_2^b) + \varepsilon$$

$$\varepsilon \sim N(0, \sigma^2)$$

$$x_0 = 0$$

where μ_i^o is the reported overall value for option $i \in \{1, 2\}$, μ_i^j is the reported value of option i $\in$

$\{1,2\}$ along attribute dimension j $\in$ $\{a,b\}$, and σ^2 is white noise common to the overall evidence

accumulation process. (Note that in cases where the individual attributes are highly correlated

and/or the attribute ratings jointly explain a large portion of the variance in overall values, it may

be necessary to employ orthogonalization or dimensionality reduction techniques, if the goal is to

make inferences about the relative weights or importance of attributes in determining the drift

rate.) Choice probability and mean RT are derived as:

285
$$DV^o = \mu_1^o - \mu_2^o$$

286
$$DV^a = \mu_1^a - \mu_2^a$$

287
$$DV^b = \mu_1^b - \mu_2^b$$

288
$$p = \frac{1}{1 + e^{\left[\frac{-2(d^o DV^o + d^a DV^a + d^b DV^b)}{\sigma^2}\right]}}$$

289
$$RT = \frac{2p - 1}{d^o DV^o + d^a DV^a + d^b DV^b}$$

where d^j are independent free parameters that allow for different rates of evidence accumulation

for overall value estimates and within each attribute dimension $j \in \{a,b\}$.

Model fitting procedure

We fit each of the three candidate models to the experimental data, then performed

Bayesian model comparison to determine which of the models (if any) performed significantly

better than the others across the population of participants. For this model fitting and comparison

exercise, we relied on the Variational Bayesian Analysis toolbox (VBA, available freely at

https://mbb-team.github.io/VBA-toolbox/; (Daunizeau et al., 2014)) with Matlab R2020a. Within

participant and across trials, we entered the experimental variables {ratings of overall value,

pleasure, and nutrition for each option} as input and {choice = 1 for left option, 0 for right option;

RT; choice confidence} as output. All ratings and reports of certainty and confidence were rescaled

to range from (0-1]. We also provided the model-specific mappings from input to output as

outlined in the analytical formulas above. As we fixed the threshold parameter θ to 1, the

parameters to be fitted were thus the drift rate *d* and diffusion noise σ^2 terms described above in

the model formulations. VBA requires prior estimates for the free parameters, for which we set

the mean equal to 1 and the variance equal to 10for each parameter. The theoretical drift rate and

noise parameters are always positive; we thus constrained the search space of our model fitting

algorithm to the positive domain by replacing these parameters with their exponential values. VBA

then recovers an approximation to both the posterior density on unknown variables and the model

evidence (which is used for model comparison). We used the VBA_NLStateSpaceModel function

to fit the data for each participant individually, followed by the VBA_groupBMC function to

compare the results of the model fitting across models for the full group of participants.

One benefit of using VBA to fit the data to our models is that it is computationally efficient,

as it relies on Variational Bayesian analysis under the Laplace approximation. This iterative

algorithm provides a free-energy approximation for the model evidence, which represents a natural

trade-off between model accuracy (goodness of fit, or log likelihood) and complexity (degrees of

freedom, or KL divergence between priors and fitted parameter estimates; see (Friston et al., 2007;

Penny, 2012)). This is a critical step for comparing models that differ in number of parameters.

Additionally, the algorithm provides an estimate of the posterior density over the model's free

parameters, estimated from our flat Gaussian priors. Individual log model evidence scores are then

provided as input to the group-level random-effect Bayesian model selection (BMS) procedure.

BMS provides an exceedance probability that measures how likely it is that a given model is more

frequently implemented, relative to all other models under consideration, in the population from

which participants were drawn (Rigoux et al., 2014; Stephan et al., 2009). This approach to fitting

and comparing variants of DDM has already been successfully demonstrated in previous studies

(Feltgen & Daunizeau, 2021; D. G. Lee & Usher, 2021; Lopez-Persem et al., 2016).

An additional benefit of fitting and comparing models within the VBA toolbox is that it

allows us to fit the formulas for choice probability and mean RT in a generic manner by

simultaneously optimizing parameters over a collection of analytical equations. Moreover, while

choice probability and RT are summarized by a set of two equations, we can just as easily perform

our model comparison while fitting additional equations alongside those for choices and response

times. Therefore we fit generalized predictions about the relationship between the evidence

accumulation rate and choice confidence in addition to choice probability and mean RT. We

estimated choice confidence as a linear function of either overall value difference (OV), individual

attribute differences (IA), or both (IA+). In each case, we assume that higher drift rates would be

associated with greater confidence. This is consistent with empirical data showing that confidence

decreases monotonically with choice difficulty (which determines the drift rate), as well as

previous studies investigating the relationship between evidence accumulation and confidence

(Pleskac & Busemeyer, 2010). The formulas that we used to estimate confidence under the

different models were thus:

$$(OV) \quad confidence = \beta_0 + \beta_1 * d^o DV^o$$

$$(IA) \quad confidence = \beta_0 + \beta_1 * (d^a DV^a + d^b DV^b)$$

$$(IA+) \quad confidence = \beta_0 + \beta_1 * (d^o DV^o + d^a DV^a + d^b DV^b)$$

Model recoverability

To verify that our model-fitting procedure is suitable for this specific analysis, we

performed a test of model recoverability. Specifically, we created a group of 1,000 synthetic

participants, each with 50 choice trials. For each trial, we generated a random number in the range:

(0-1) for each of the pleasure and nutrition ratings. For each synthetic participant, we generated a

random relative weight parameter (RW) for the importance of pleasure versus nutrition, in the

range: (0-10). We then generated the value of each option by sampling from a normal distribution

with mean equal to the weighted average of the pleasure and nutrition ratings and random standard

deviation in the range: (0,1). We assigned random parameters for each participant under each

model by sampling from normal distributions with the following means and standard deviations:

drift rates: (1, 0.3) for dV under OV, (0.2, 0.3) for dN under IA, (0.5, 0.3) for dV under IA+, (0.1,

0.2) for dN under the IA+; diffusion noise: (0.5, 0.1) under all models; confidence: (0.5, 0.2) for

both parameters under all models. For IA and IA+, the drift rate parameters for dP were set equal

to the drift rate for dN * RW. We then simulated the set of choice probabilities, mean RTs, and

confidence ratings for each participant, separately according to each of our models. Finally, we fit

all simulated data (per synthetic participant) to each of our models and performed the same formal

model comparison as with our real experimental data. The results of this procedure can be seen in

Figure 3A as a model confusion matrix. This matrix shows, for each true generative model, the

percentage of synthetic participants (under that model) that were attributed to each of the best fit

models by our model-fitting procedure. As shown in the matrix, model confusion was low and the

procedure attributed the true generating model as the best fitting model for the vast majority of the

simulated participants (recovery accuracy: 97% for OV, 81% for IA, 86% for IA+).

We then needed to determine if the model recoverability would remain high when using

the precise distributions of variables observed in our empirical data. We thus repeated the model

recovery analysis based on real data. Specifically, we took as the model input the actual data for

each participant in Studies 1-6 (ratings of overall value, pleasure, and nutrition for each option).

We then simulated the set of choice probabilities, mean RTs, and confidence ratings for each

participant, separately according to each of our models, using the actual participant-specific fitted

parameters for each model. Finally, we fit all simulated data (per participant) to each of our models

and performed the same formal model comparison as with our real experimental data. The results

of this procedure can be seen in Figure 3B. As shown in the matrix, model confusion remained

very low (recovery accuracy: 86% for OV, 66% for IA, 83% for IA+). There was still some

confusion between the IA+ and other specifications, which is expected because the IA+ is

essentially a combination of those other specifications.

Figure 3. Model recovery analysis using random input (A) and empirical input (B). *The cells*
in each "confusion matrix" summarize the percentage of simulated participants (under each true
model) for which our model-fitting procedure attributed each of the (best fit) models.
383

384   **Results**

385   ***Relationship between variables***

386   Our main analyses rely on some fundamental assumptions about how the different

variables (value, pleasure, and nutrition) relate to each other. First, it is necessary that the pleasure

and nutrition attributes explain a large portion of the variance in overall value ratings, i.e., that

those attributes are an adequate subset of the relevant attributes for these choices. We tested this

by running a linear regression of value on pleasure and nutrition, separately for each participant.

Across participants, the GLM beta weights for pleasure and nutrition were 0.736 and 0.192,

respectively ($p < .001$ for both, based on 2-sided t-tests of each beta versus zero), and the mean r-

squared value for the multiple regressions was 0.730. Second, it is necessary that pleasure and

nutrition are sufficiently orthogonal and explain unique variance in overall value ratings and

choices. We tested this by calculating the Pearson's correlation between pleasure and nutrition

ratings, separately for each participant. Across participants, there was no systematic correlation

between pleasure and nutrition (mean $\rho = -0.034$, $p = .137$, based on a 2-sided t-test versus zero).

There was heterogeneity across participants, but most correlation coefficients were within the [-

0.53, 0.52] range (80% of participants; see the Supplementary Material).

Qualitative Model Predictions

402   Many evidence accumulation models make distinguishable predictions regarding the

impact of two important features of binary choices: overall value difference and attribute disparity.

Lee and Holyoak (D. G. Lee & Holyoak, 2021b) introduced the term *disparity* as a secondary

characteristic of a decision, orthogonal to the primary characteristic most often used in the field:

overall value difference (often referred to as choice difficulty, where lower value difference

implies higher difficulty). The disparity between two options {i,j} with respect to two attribute

dimensions (here, P for pleasure and N for nutrition) is calculated as:

$$disparity_{i,j} \triangleq \left| \frac{[P_i \, N_i] * \begin{bmatrix} -b_P \\ b_N \end{bmatrix} - [P_j \, N_j] * \begin{bmatrix} -b_P \\ b_N \end{bmatrix}}{\left\| \begin{matrix} -b_P \\ b_N \end{matrix} \right\|} \right|, \text{ for options } i, j. \tag{1}$$

where b_P and b_N are the importance weights for the P and N attributes, respectively. Note that it

would be straightforward to extend this formula to incorporate more than two options or more than

two attributes. Disparity calculated in this way effectively transforms the variable space from

attribute dimensions to decision dimensions (see Figure 1 above).

We first show the qualitative predictions that each evidence accumulation process (OV,

IA, IA+, all simulated under their participant-specific best fitting parameters) makes with respect

to the effects of value difference (dV) and disparity (D) on choice consistency, RT, and choice

confidence, and how this compares to the empirical data (Figure 4). To generate the synthetic data,

we used the real trial-by-trial values faced by each individual participant (value of option 1, or v1;

value of option 2, or v2; pleasure of option 1, or p1; pleasure of option 2, or p2; nutrition of option

1, or n1; nutrition of option 2, or n2), along with each participant's best-fitting parameters for each

of the three evidence accumulation specifications. Note: we coded the data such that option 1

always had the higher overall value. Next, we performed mixed effects (MFX) regressions of

choice (binomial), of RT (linear), and of confidence (linear) on dV and D, pooling all simulations

together and including study and participant as random effect regressors. The IA+ specification is

the only one from the set we examined that is able to account for the relative magnitudes and

directionality of the associations dV and D show with choice consistency (whether or not the

higher-rated option was chosen), RT, and confidence (see Figure 4). Note that because the

simulated data are less noisy than the empirical data, those regression coefficients will be larger

(i.e., the regressors will explain more of the variance in the dependent variables). Regardless, what

is important here is the relative magnitudes of the coefficients for dV and D *within* each data

source, not the absolute magnitudes or comparisons across data sources.

Figure 4. Model predictions. *Qualitative predictions of the effects of value difference (dV = value of option 1 – value of option 2) and disparity (D; see equation 1) on choice consistency, log(RT), and confidence in the empirical (column 1) and simulated data (columns 2-4; shown for responses simulated using the best fitting parameters for each model); diamonds represent MFX fixed effects regression coefficients; error bars represent 95% confidence intervals.*

Quantitative model comparisons

To quantitatively evaluate the models, we performed formal quantitative model comparisons of the various diffusion decision model specifications. We compared the fit of the model based on overall value (OV) to a model based on individual attribute values (IA), to test our hypothesis that decision makers place different importance or decision weights on attributes during

choices than when rating the overall value of each option in isolation. If the attributes are weighted

and aggregated the same way during ratings and choices, then the OV model, which uses the

comprehensive overall value of the foods to estimate choices should outperform the IA model,

which only uses a subset of the foods' attributes (pleasure and nutrition) to estimate choice

outcomes, response times, and reported confidence levels. If instead attributes are weighted

differently during choices compared to ratings, then the flexibility to estimate attribute-specific

decision weights may give the IA model the advantage even though it is based on only two

attributes out of a larger set of potentially relevant attributes. We also compared a model in which

we tried to combine the advantages of the comprehensive overall value ratings together with the

flexibility to estimate choice-specific weights for a subset of the individual attributes. We thus fit

a third DDM model (IA+) that used the pleasure and nutrition ratings as well as information about

the foods' values beyond those two attributes, in the form of the reported overall value. This

provides a measure to quantify the benefit of including individual attribute ratings in the model in

addition to overall value ratings. Across all six datasets (studies 0-5 from (D. G. Lee & Holyoak,

2021b)), the winning model was the IA+, with an exceedance probability of 1 and an estimated

model frequency of 0.63. The OV model had an estimated frequency of 0.33, and the IA model

had an estimated frequency of 0.04 (Figure 5).

Figure 5. Model comparison results. *Simultaneous comparison of the OV, IA, and IA+ models. We show here the probability that each model best explains the data across the participant population, across all studies (n=307). The black dashed line indicates chance level if all models were equally probable a priori.*

As a robustness check, we repeated the above model comparisons using the final post-choice ratings from each experiment (i.e., Rating 2 for Experiments 0-1 and Rating 3 for Experiments 2-5). If somehow the initial ratings were too noisy or mis-calibrated, we might expect to find different results when using final ratings to drive the models. The model comparison results using final rather than initial ratings were very similar: IA+ won with an exceedance probability of 0.99 and an estimated frequency of 0.55, OV had an estimated frequency of 0.42, and IA had an estimated frequency of 0.03. The main difference was that OV gained some support (9%) when using post-choice ratings (consistent with the idea that the accuracy of overall value ratings was refined during choice deliberation; (D. G. Lee & Daunizeau, 2020, 2021)).

To test the influence of confidence ratings on the model comparison results reported above (which were based on choice probability, RT, and confidence), we repeated that analysis while excluding confidence data. The assumption that confidence is linearly related to the evidence accumulation rate is arguably the least supported of our three generalized predictions. The model comparison results without confidence were similar to those with confidence, although OV gained more support (exceedance probability: 0.35 for OV, 0.65 for IA+; estimated model frequency: 0.45 for OV, 0.08 for IA, 0.47 for IA+). This suggests that including confidence data helps to distinguish the models (see model recovery details in the Methods section).

The last model comparison analysis that we performed examined the dataset for which we had overall value ratings as well as four individual attribute ratings (taste, health, texture, appearance). Here, even though this additional dataset had attribute ratings covering a larger range

of potentially relevant attributes (4 versus 2), the IA+ version again dominated (exceedance

probability = 1; estimated model frequency for IA+ = 0.96, for OV and IA = 0.02 each; but note

the small sample size, n=17; Figure 6). To check whether adding additional attribute ratings would

always be useful, we compared versions of the IA specification that included only one attribute

(taste), two attributes (taste + health), three attributes (taste + health + texture), and four attributes

(taste + health + texture + appearance). The version with two attributes performed best (exceedance

probability = 0.98, estimated model frequency = 0.72), followed by the version with three

attributes (estimated model frequency = 0.25). However, when pitted against OV and the full IA+,

the results remained the same as reported above.

Figure 6. Model comparison results. *Simultaneous comparison of the OV, IA, and IA+ models.*
We show here the probability that each model best explains the data across the participant
population, for the four-attribute pilot study (n=17). The black dashed line indicates chance level
if all models were equally probable a priori.
501

In this paper, we do not examine the parameter estimates for the evidence accumulation

models for two reasons. First, we are testing predictions shared by a general class of evidence

accumulation models rather than a precise version of any specific model. Second, we know that

value is highly correlated with pleasure and nutrition (indeed, it is assumed to be composed of

them). This would make it complicated to accurately estimate the different parameters for each

rating under IA+.

509   **Discussion**

Most options that humans need to evaluate and choose from in daily life have multiple

attributes or dimensions, and we found that these attributes are combined in a context-dependent

manner to determine an option's value. Previous work on naturalistic multi-attribute decisions has

shown that people form option representations based on a large number of separate underlying

attributes (Bhatia & Stewart, 2018). Our results on both choice outcomes and post-decision

confidence ratings are consistent with these findings. Similar results have also been reported for

options where the attributes are objectively defined, such as intertemporal choice (monetary

amount and delay (Amasino et al., 2019)) and risky choice (monetary amount and probability (D.

G. Lee et al., 2022)). In addition, our model simulation and comparison results suggest that the

representations that determine an option's subjective value may differ between rating and binary

choice tasks. From the simulation analysis, it is clear that decision models based on a fixed, unitary

overall value equal to that given during the ratings sessions do not generate the influence of

disparity on choices, response times, or confidence ratings seen in the empirical data (D. G. Lee

& Holyoak, 2021b). A simple explanation for this result is that the influence of pleasure, nutrition,

or other attributes differs between the preference elicitation methods (ratings versus choices). In

terms of quantitative model comparisons, if the overall values of the foods in these six studies were

invariant across the rating and choice tasks, then models using only the overall values to determine

the drift rate (OV) would be preferred over models using either a subset of the food attributes (i.e.,

IA with pleasure and nutrition) or individual attributes plus the overall values (IA+). This is

because relative to the OV specification, IA adds complexity (one additional parameter) while at

the same time reducing the completeness of the information about the food items – assuming

overall value is determined by more than just pleasure and nutrition. Moreover, if overall value

representations were constant, then the IA+ specification would add redundant complexity

compared to OV and be penalized for that complexity without benefiting from greater explanatory

power in the comparisons. In fact, IA+ (overall value + pleasure + nutrition) dominated the other

models in the model comparison, as it is the best in terms of generating the observed effects of

attribute disparity and accounting for the observed pattern of choice outcomes, response times, and

confidence ratings.

The construction of a choice option's subjective value is an active, malleable process. We

have shown that when options are composed of multiple distinct attributes, the manner in which

these attributes are evaluated and potentially combined to determine the overall value of each

option relative to the other occurs in the moment (i.e., at the time of rating or choice solicitation).

Specifically, the contributions of inherent attributes such as pleasure and nutrition to the overall

value of food rewards may differ when the foods are evaluated in isolation compared to when

choices are made between pairs of foods, even though the goal of the valuation process should be

the same in both cases. These findings indicate that preferences over naturalistic multi-attribute

goods are labile, and that it might not always be reasonable to assume that previously-obtained

overall value ratings summarize the same value representations that guide current choice behavior.

Note that our results hold using either pre- or post-choice ratings of overall value, pleasure, and

nutrition and regardless of whether the overall value or attribute-specific ratings were given closest

to the choice phase, ruling out temporal proximity or item familiarity as potential explanations for

these results.

The superior ability of models including attribute-level information to explain the effects

of disparity on choices, RTs, and confidence ratings indicates that the importance of one or more

attributes reliably differs during binary choices relative to ratings. Specifications of the models

that use reports of overall value as the input to the evidence accumulation process implicitly hold

the relative importance of each attribute fixed, and thus cannot account for differences in value

computation between ratings of single options and choices over two or more options. In contrast,

a multi-attribute model specification directly estimates the importance weights for each attribute

within the choice context and is therefore better able to explain choice behavior. However, these

models are agnostic about how or why the importance of specific attributes differs when

individuals are computing the overall value of a single option compared to choosing between two

options.

Many sequential sampling models of decision-making posit that attention and salience play

an important role in value computation and comparison. Examples of such models are Decision

Field Theory (DFT; (Busemeyer & Townsend, 1993)), an extension of DFT known as the Multi-

Attribute Dynamic Decision (MADD) model (Diederich, 1997), and the attentional DDM (aDDM;

(Krajbich et al., 2010; Smith & Krajbich, 2019)). In the DFT model, the drift rate can vary across

deliberation time if, for example, one option is more salient but the other is truly more valuable.

The MADD model makes the multi-attribute nature explicit, and the drift rate fluctuates over time

as the decision maker shifts focus across the set of relevant attributes. Although the aDDM has

generally been applied to the overall values of options, or to distinct items within a bundle (Fisher,

2017, 2021b), it would be conceptually similar to the MADD if applied at the attribute level for

goods that are inherently multidimensional. Query theory is similar to these sequential sampling

models in that it holds that the order in which a decision maker considers different aspects (or

attributes) of an option alters its resultant valuation (E. Johnson et al., 2007; Weber et al., 2007).

In all these models, it is assumed that options or attributes that receive more attention will be

favored during the value comparison process. However, the relationship between value and

attention is most likely bidirectional to some extent (Anderson et al., 2011; Callaway et al., 2021;

Gluth et al., 2018; Jang et al., 2021; Towal et al., 2013; Westbrook et al., 2020).

Differences in the amount of attention directed to specific attributes during the evaluation

and decision contexts could explain changes in the manner in which the attributes aggregate into

overall value across those contexts. Consistent with this idea, changes in the proportions of visual

fixations to locations on a computer screen indicating the monetary amount versus the probability

of winning when pricing versus choosing between lotteries are associated with inconsistencies

between the two preference elicitation contexts (Alós-Ferrer et al., 2021; Kim et al., 2012).

Fixation patterns towards monetary amount versus delay affect temporal discounting rates (Fisher,

2021a), although whether this might vary in pricing versus choice contexts has not been tested.

Covert attention processes may have effects similar to visual attention for naturalistic multi-

attribute goods. The focus of covert attention is more difficult to measure than visual attention

(i.e., fixation locations), but studies combining decision tasks with neuroimaging or

electrophysiology and machine learning techniques may give us a window into these cognitive

processes (Aoi et al., 2020; Peixoto et al., 2021). Experimental manipulation of focus on a specific

attribute (Fisher, 2018; Hare et al., 2011) may also prove useful, if an appropriate method to

dynamically shift attention within each trial is developed.

In addition to providing further insight into the mechanistic nature of value-based

decisions, our current work has practical implications for future studies of decision-making. We

have shown that it is best to use as much attribute-level information as possible when modeling

decisions over multi-attribute stimuli. Most, if not all, naturalistic stimuli are composed of multiple

attributes, thus most studies of decision-making should incorporate attribute-level information. At

the same time, it will often be impractical to collect information on a large number of attributes,

especially if one needs subjective opinions about the attributes from each participant in an

experiment (but see the Supplementary Material regarding using population-level averages as

proxies for additional attribute ratings). Our results indicate that combining attribute-specific and

overall values may be a good compromise between attempting to include comprehensive attribute-

level information and conforming to practical constraints. Naturally, which attribute-level

information to obtain and how to best combine it with some type of overall value rating will depend

on the hypotheses and experimental design. Given the clear evidence that the value-comparison

process is based on context-dependent attribute assessments, experiments that use a well-designed

combination of attribute-specific and aggregate-level information should prove to be the most

useful in advancing our understanding of many important decision mechanisms. We believe that

the datasets we examined in this study may be the only ones currently available that include

subjective ratings of both overall value and individual attributes. It would be beneficial if future

studies also collected such comprehensive data, for without it, effects such as those we have shown

here might never be exposed.

616   **Data and Analysis Code Availability**

617   The raw data and primary analysis code for this study are available in the Open Science Forum at

618   http://doi.org/10.17605/OSF.IO/EDSH6.

References

Alós-Ferrer, C. (2018). A Dual-Process Diffusion Model. *Journal of Behavioral Decision Making*, *31*(2), 203–218. https://doi.org/10.1002/bdm.1960

Alos-Ferrer, C., Buckenmaier, J., & Garagnani, M. (2020). Stochastic Choice and Preference Reversals. *SSRN Electronic Journal*. https://doi.org/10.2139/ssrn.3748599

Alós-Ferrer, C., Granić, Đ.-G., Kern, J., & Wagner, A. K. (2016). Preference reversals: Time and again. *Journal of Risk and Uncertainty*, *52*(1), 65–97. https://doi.org/10.1007/s11166-016-9233-z

Alós-Ferrer, C., Jaudas, A., & Ritschel, A. (2021). Attentional shifts and preference reversals: An eye-tracking study. *Judgment and Decision Making*, *16*(1), 37.

Amasino, D. R., Sullivan, N. J., Kranton, R. E., & Huettel, S. A. (2019). Amount and Time Exert Independent Influences on Intertemporal Choice. *Nature Human Behaviour*, *3*(4), 383–392. https://doi.org/10.1038/s41562-019-0537-2

Anderson, B. A., Laurent, P. A., & Yantis, S. (2011). Value-Driven Attentional Capture. *Proceedings of the National Academy of Sciences*, *108*(25), 10367–10371. https://doi.org/10.1073/pnas.1104047108

Aoi, M. C., Mante, V., & Pillow, J. W. (2020). Prefrontal cortex exhibits multidimensional dynamic encoding during decision-making. *Nature Neuroscience*, *23*(11), 1410–1420. https://doi.org/10.1038/s41593-020-0696-5

Azen, R., & Budescu, D. V. (20030714). The dominance analysis approach for comparing predictors in multiple regression. *Psychological Methods*, *8*(2), 129. https://doi.org/10.1037/1082-989X.8.2.129

Azen, R., & Traxel, N. (2009). Using Dominance Analysis to Determine Predictor Importance in Logistic Regression. *Journal of Educational and Behavioral Statistics*, *34*(3), 319–347. https://doi.org/10.3102/1076998609332754

Bettman, J. R., Luce, M. F., & Payne, J. W. (1998). Constructive Consumer Choice Processes. *Journal of Consumer Research*, *25*(3), 187–217. https://doi.org/10.1086/209535

Bhatia, S. (2013). Associations and the accumulation of preference. *Psychological Review*, *120*(3), 522–543. https://doi.org/10.1037/a0032457

Bhatia, S., & Stewart, N. (2018). Naturalistic Multiattribute Choice. *Cognition*, *179*, 71–88. https://doi.org/10.1016/j.cognition.2018.05.025

Budescu, D. V. (1993). Dominance analysis: A new approach to the problem of relative importance of predictors in multiple regression. *Psychological Bulletin*, *114*(3), 542–551. https://doi.org/10.1037/0033-2909.114.3.542

Busemeyer, J. R., Gluth, S., Rieskamp, J., & Turner, B. M. (2019). Cognitive and Neural Bases of Multi-Attribute, Multi-Alternative, Value-Based Decisions. *Trends in Cognitive Sciences*, *23*(3), 251–263. https://doi.org/10.1016/j.tics.2018.12.003

Busemeyer, J. R., & Townsend, J. T. (1993). Decision field theory: A dynamic-cognitive approach
to decision making in an uncertain environment. *Psychological Review*, *100*(3), 432.
https://doi.org/10.1037/0033-295X.100.3.432

Callaway, F., Rangel, A., & Griffiths, T. L. (2021). Fixation Patterns in Simple Choice Reflect
Optimal Information Sampling. *PLOS Computational Biology*, *17*(3), e1008863.
https://doi.org/10.1371/journal.pcbi.1008863

Daunizeau, J., Adam, V., & Rigoux, L. (2014). VBA: A Probabilistic Treatment of Nonlinear Models
for Neurobiological and Behavioural Data. *PLOS Computational Biology*, *10*(1), e1003441.
https://doi.org/10.1371/journal.pcbi.1003441

Dawes, R. M. (1979). The robust beauty of improper linear models in decision making. *American
Psychologist*, *34*(7), 571–582. https://doi.org/10.1037/0003-066X.34.7.571

Dawes, R. M., & Corrigan, B. (1974). Linear models in decision making. *Psychological Bulletin*,
81(2), 95–106. https://doi.org/10.1037/h0037613

Diederich, A. (1997). Dynamic Stochastic Models for Decision Making under Time Constraints.
Journal of Mathematical Psychology, *41*(3), 260–274. https://doi.org/10.1006/jmps.1997.1167

Feltgen, Q., & Daunizeau, J. (2021). An Overcomplete Approach to Fitting Drift-Diffusion Decision
Models to Trial-By-Trial Data. *Frontiers in Artificial Intelligence*, *0*.
https://doi.org/10.3389/frai.2021.531316

Fischer, G. W., Carmon, Z., Ariely, D., & Zauberman, G. (1999). Goal-Based Construction of
Preferences: Task Goals and the Prominence Effect. *Management Science*, *45*(8), 1057–1075.
https://doi.org/10.1287/mnsc.45.8.1057

Fishburn, P. C. (1974). Exceptional Paper—Lexicographic Orders, Utilities and Decision Rules: A
Survey. *Management Science*, *20*(11), 1442–1471. https://doi.org/10.1287/mnsc.20.11.1442

Fisher, G. (2017). An Attentional Drift Diffusion Model over Binary-Attribute Choice. *Cognition*, *168*,
34–45. https://doi.org/10.1016/j.cognition.2017.06.007

Fisher, G. (2018). Nutrition labeling reduces valuations of food through multiple health and taste
channels. *Appetite*, *120*, 500–504. https://doi.org/10.1016/j.appet.2017.09.013

Fisher, G. (2021a). Intertemporal Choices Are Causally Influenced by Fluctuations in Visual
Attention. *Management Science*. https://doi.org/10.1287/mnsc.2020.3732

Fisher, G. (2021b). A Multiattribute Attentional Drift Diffusion Model. *Organizational Behavior and
Human Decision Processes*, *165*, 167–182. https://doi.org/10.1016/j.obhdp.2021.04.004

Friston, K., Mattout, J., Trujillo-Barreto, N., Ashburner, J., & Penny, W. (2007). Variational free
energy and the Laplace approximation. *NeuroImage*, *34*(1), 220–234.
https://doi.org/10.1016/j.neuroimage.2006.08.035

Gigerenzer, G., & Gaissmaier, W. (2011). Heuristic Decision Making. *Annual Review of
Psychology*, *62*(1), 451–482. https://doi.org/10.1146/annurev-psych-120709-145346

Gluth, S., Spektor, M. S., & Rieskamp, J. (2018). Value-Based Attentional Capture Affects Multi-
Alternative Decision Making. *ELife*, *7*, e39659. https://doi.org/10.7554/eLife.39659

Grether, D., & Plott, C. (1979). Economic Theory of Choice and the Preference Reversal Effect.
American Economic Review, *69*, 623–638.

Hare, T. A., Malmaud, J., & Rangel, A. (2011). Focusing Attention on the Health Aspects of Foods
Changes Value Signals in vmPFC and Improves Dietary Choice. *Journal of Neuroscience*,
31(30), 11077–11087. https://doi.org/10.1523/JNEUROSCI.6383-10.2011

Jang, A. I., Sharma, R., & Drugowitsch, J. (2021). Optimal Policy for Attention-Modulated Decisions
Explains Human Fixation Behavior. *ELife, 10*, e63436. https://doi.org/10.7554/eLife.63436

Johnson, E., Häubl, G., & Keinan, A. (2007). Aspects of Endowment: A Query Theory of Value
Construction. *Journal of Experimental Psychology. Learning, Memory, and Cognition*, *33*, 461–
474. https://doi.org/10.1037/0278-7393.33.3.461

Johnson, E. J., & Payne, J. W. (1985). Effort and Accuracy in Choice. *Management Science*, *31*(4),
395–414. https://doi.org/10.1287/mnsc.31.4.395

Keeney, R. L., Raiffa, H., L, K. R., & Meyer, R. F. (1993). *Decisions with Multiple Objectives:*
Preferences and Value Trade-Offs. Cambridge University Press.

Kim, B., Seligman, D., & Kable, J. W. (2012). Preference Reversals in Decision Making Under Risk
are Accompanied by Changes in Attention to Different Attributes. *Frontiers in Neuroscience*, *0*.
https://doi.org/10.3389/fnins.2012.00109

Krajbich, I., Armel, C., & Rangel, A. (2010). Visual Fixations and the Computation and Comparison
of Value in Simple Choice. *Nature Neuroscience, 13*(10), 1292–1298.
https://doi.org/10.1038/nn.2635

Lee, D. G., D'Alessandro, M., Iodice, P., Calluso, C., Rustichini, A., & Pezzulo, G. (2022). *Evidence*
Accumulates for Individual Attributes in Risky Choice. PsyArXiv.
https://doi.org/10.31234/osf.io/h3r6x

Lee, D. G., & Daunizeau, J. (2020). Choosing what we like vs liking what we choose: How choice-
induced preference change might actually be instrumental to decision-making. *PLOS ONE*,
15(5), e0231081. https://doi.org/10.1371/journal.pone.0231081

Lee, D. G., & Daunizeau, J. (2021). Trading mental effort for confidence in the metacognitive
control of value-based decision-making. *ELife*, *10*, e63282. https://doi.org/10.7554/eLife.63282

Lee, D. G., & Holyoak, K. (2021a). Transient Value Refinements during Deliberation Facilitate
Choice. *PsyArXiv*. https://doi.org/10.31234/osf.io/7pmgh

Lee, D. G., & Holyoak, K. J. (2021b). Coherence Shifts in Attribute Evaluations. *Decision*, No
Pagination Specified-No Pagination Specified. https://doi.org/10.1037/dec0000151

Lee, D. G., & Usher, M. (2021). Value certainty in drift-diffusion models of preferential choice.
Psychological Review, No Pagination Specified-No Pagination Specified.
https://doi.org/10.1037/rev0000329

Levav, J., Heitmann, M., Herrmann, A., & Iyengar, S. S. (2010). Order in Product Customization
Decisions: Evidence from Field Experiments. *Journal of Political Economy*, *118*(2), 274–299.
https://doi.org/10.1086/652463

Lichtenstein, S., & Slovic, P. (1971). Reversals of Preference between Bids and Choices in
Gambling Decisions. *Journal of Experimental Psychology*, *89*(1), 46–55.
https://doi.org/10.1037/h0031207

Lopez-Persem, A., Domenech, P., & Pessiglione, M. (2016). How prior preferences determine
decision-making frames and biases in the human brain. *ELife*, *5*, e20317.
https://doi.org/10.7554/eLife.20317

Payne, J. W., Bettman, J. R., & Johnson, E. J. (1988). Adaptive strategy selection in decision
making. *Journal of Experimental Psychology: Learning, Memory and Cognition*, *14*, 534–552.

Payne, J. W., Bettman, J. R., & Johnson, E. J. (1993). *The adaptive decision maker*. Cambridge
University Press. https://doi.org/10.1017/CBO9781139173933

Peixoto, D., Verhein, J. R., Kiani, R., Kao, J. C., Nuyujukian, P., Chandrasekaran, C., Brown, J.,
Fong, S., Ryu, S. I., Shenoy, K. V., & Newsome, W. T. (2021). Decoding and Perturbing
Decision States in Real Time. *Nature*, 1–6. https://doi.org/10.1038/s41586-020-03181-9

Penny, W. D. (2012). Comparing Dynamic Causal Models using AIC, BIC and Free Energy.
NeuroImage, *59*(1), 319–330. https://doi.org/10.1016/j.neuroimage.2011.07.039

Pleskac, T. J., & Busemeyer, J. R. (2010). Two-stage dynamic signal detection: A theory of choice,
decision time, and confidence. *Psychological Review*, *117*(3), 864–901.
https://doi.org/10.1037/a0019737

Ratcliff, R. (1978). A theory of memory retrieval. *Psychol. Rev*, *85*(2), 59–108.

Ratcliff, R., & McKoon, G. (2008). The Diffusion Decision Model: Theory and Data for Two-Choice
Decision Tasks. *Neural Computation*, *20*(4), 873–922. https://doi.org/10.1162/neco.2008.12-06-
420

Ratcliff, R., & Rouder, J. N. (1998). Modeling Response Times for Two-Choice Decisions.
Psychological Science, *9*(5), 347–356. https://doi.org/10.1111/1467-9280.00067

Rigoux, L., Stephan, K. E., Friston, K. J., & Daunizeau, J. (2014). Bayesian Model Selection for
Group Studies—Revisited. *NeuroImage*, *84*, 971–985.
https://doi.org/10.1016/j.neuroimage.2013.08.065

Roe, R. M., Busemeyer, J. R., & Townsend, J. T. (2001). Multialternative Decision Field Theory: A
Dynamic Connectionist Model of Decision Making. *Psychological Review*, *108*(2), 370–392.
https://doi.org/10.1037/0033-295X.108.2.370

Russo, J. E., & Dosher, B. A. (1983). Strategies for multiattribute binary choice. *Journal of
Experimental Psychology: Learning, Memory, and Cognition*, *9*(4), 676–696.
https://doi.org/10.1037/0278-7393.9.4.676

Russo, J. E., Medvec, V. H., & Meloy, M. G. (1996). The Distortion of Information during Decisions.
Organizational Behavior and Human Decision Processes, *66*(1), 102–110.
https://doi.org/10.1006/obhd.1996.0041

Seidl, C. (2002). Preference Reversal. *Journal of Economic Surveys*, *16*(5), 621–655.
https://doi.org/10.1111/1467-6419.00184

Shah, A. K., & Oppenheimer, D. M. (2008). Heuristics made easy: An effort-reduction framework.
Psychological Bulletin, *134*(2), 207–222. https://doi.org/10.1037/0033-2909.134.2.207

Smith, S. M., & Krajbich, I. (2019). Gaze Amplifies Value in Decision Making. *Psychological*
Science, *30*(1), 116–128. https://doi.org/10.1177/0956797618810521

Stephan, K. E., Penny, W. D., Daunizeau, J., Moran, R. J., & Friston, K. J. (2009). Bayesian model
selection for group studies. *NeuroImage*, *46*(4), 1004–1017.
https://doi.org/10.1016/j.neuroimage.2009.03.025

Towal, R. B., Mormann, M., & Koch, C. (2013). Simultaneous Modeling of Visual Saliency and
Value Computation Improves Predictions of Economic Choice. *Proceedings of the National*
Academy of Sciences, *110*(40), E3858–E3867. https://doi.org/10.1073/pnas.1304429110

Trueblood, J. S., Brown, S. D., & Heathcote, A. (2014). The multiattribute linear ballistic
accumulator model of context effects in multialternative choice. *Psychological Review*, *121*(2),
179–205. https://doi.org/10.1037/a0036137

Tversky, A. (1972). Elimination by aspects: A theory of choice. *Psychological Review*, *79*(4), 281–
299. https://doi.org/10.1037/h0032955

Tversky, A., Sattath, S., & Slovic, P. (1988). Contingent Weighting in Judgment and Choice.
Psychological Review, *95*(3), 371–384. https://doi.org/10.1037/0033-295X.95.3.371

Tversky, A., Slovic, P., & Kahneman, D. (1990). The Causes of Preference Reversal. *The*
American Economic Review, *80*(1), 204–217.

Usher, M., & Mcclelland, J. L. (2001). On the time course of perceptual choice: The leaky
competing accumulator model. *Psychological Review*, 550–592.

Weber, E. U., & Johnson, E. J. (2009). Mindful Judgment and Decision Making. *Annual Review of*
Psychology, *60*(1), 53–85. https://doi.org/10.1146/annurev.psych.60.110707.163633

Weber, E. U., Johnson, E. J., Milch, K. F., Chang, H., Brodscholl, J. C., & Goldstein, D. G. (2007).
Asymmetric Discounting in Intertemporal Choice: A Query-Theory Account. *Psychological*
Science, *18*(6), 516–523. https://doi.org/10.1111/j.1467-9280.2007.01932.x

Westbrook, A., van den Bosch, R., Määttä, J. I., Hofmans, L., Papadopetraki, D., Cools, R., &
Frank, M. J. (2020). Dopamine Promotes Cognitive Effort by Biasing the Benefits versus Costs
of Cognitive Work. *Science*, *367*(6484), 1362–1366. https://doi.org/10.1126/science.aaz5891

Supplementary Material

Correlation between pleasure and nutrition ratings

In this study, we examined the relative subjective importance of the pleasure (P) and

nutrition (N) attributes when people either rate individual snack foods or choose between pairs of

snack foods. It is thus beneficial if ratings along these two attribute dimensions are not highly

correlated, as that would make the regression analysis results less straightforward to interpret. In

the main text, we reported that the average Pearson correlation between P and N (across

participants) was not statistically different from zero. However, we did find a good deal of

heterogeneity across participants, such that some provided P and N ratings that were negatively

correlated, while others provided P and N ratings that were positively correlated. Figure S1

displays a histogram of the correlation between P and N for the entire participant pool. Note that

the majority of participants (about 80%) had correlation coefficients between -0.5 and 0.5.

Figure S1: Histogram of participants' coefficients of correlation between P and N.

Correlation between predicted and empirical variables

As an additional check that our models did a reasonable job of accounting for the empirical

data, we compared the predicted RT and confidence ratings (under each model formulation) with

the true empirical data. As shown in Figure S2, each model did a good job of accurately predicting

the data (all correlation levels are around 60%). Note that the correlations between data simulated

under the IA+ formulation show the highest correlation with the empirical data, which is to be

expected given that the IA+ outperformed the other formulations in the formal model comparison.

Figure S2: Correlations between data (RT and confidence) predicted under each model

formulation and empirical data. *The upper row shows the associations between the logarithms*

of empirical response times (x-axis) and response times simulated under each evidence

accumulation assumption (y-axis). The lower row shows the associations between empirical

confidence ratings (x-axis) and confidence ratings simulated under each evidence accumulation

assumption (y-axis). The green dotted lines show the identity line for all plots.

Consistency of attribute ratings across participants

In the main text, we demonstrated that it is beneficial to include ratings of multiple

individual attributes when modeling choice behavior, in addition to the traditional ratings of

overall value. However, it might not always be practical to collect ratings for many different

attributes (e.g., due to time constraints or participant boredom or fatigue). As a potential solution

for this dilemma, one might wonder whether individual subjective ratings could be replaced (as an

approximation) by population-level averages. If true, an experimenter could accumulate a database

of ratings of many attributes for many options, because each attribute could in principle be

evaluated by a different group of participants (and used to model the behavior of other participants

in future studies). In order for such a method to work, there would have to be a high degree of

similarity in the ratings for each option across participants. Whereas this might be unlikely for

ratings based largely on personal experience and personal preferences (e.g., value or pleasure), it

might be reasonable for ratings based more on learned information (e.g., nutrition), especially

when such learning is generally consistent across a specific culture (e.g., for the residents of the

US and Canada in this study). We thus calculated aggregate statistics (mean and standard

deviation) for the 100 items in Study 2 (Study 1 did not include an identical set of items across

participants) and for the 60 items in Studies 3-6 across all participants in those studies. As shown

in Figure S3, there is a lot of variability in the value and pleasure ratings, but much less variability

in the nutrition ratings.

Figure S3: Ratings across participant populations. *Population statistics for the ratings of value*

(panels A & D), pleasure (panels B & E), and nutrition (panels C & F) for participants in Study 2

(panels A-C) and Studies 3-6 (panels D-F). Circles indicate means, error bars indicate +/- one

standard deviation.