A general deep learning model for bird detection in high resolution airborne imagery

Ben G. Weinstein[1], Lindsey Garner[1], Vienna R. Saccomanno[2], Ashley Steinkraus[1], Andrew

Ortega[3], Kristen Brush[4], Glenda Yenni[1], Ann E. McKellar[5], Rowan Converse[7], Christopher D.

Lippitt[7], Alex Wegmann[2], Nick D. Holmes[2], Alice J. Edney[6], Tom Hart[6], Mark J. Jessopp[8],

Rohan H Clarke[9], Dominik Marchowski[10], Henry Senyondo[1], Ryan Dotson[11], Ethan P. White[1],

Peter Frederick[1], S.K. Morgan Ernest[1]

1 Department of Wildlife Ecology and Conservation, University of Florida, Gainesville, Florida, USA. Corresponding author.

ben.weinstein@weecology.org

2 California Oceans Program, The Nature Conservancy, Sacramento, CA USA

3 Geomatics Program, University of Florida, Gainesville, Florida, USA

4 Montana State University, Bozeman, Montana, USA

5 Environment and Climate Change Canada, Saskatoon, Saskatchewan, Canada

6 Department of Zoology, University of Oxford, Oxford, UK

7 Center for the Advancement of Spatial Informatics Research and Education, University of New Mexico, Albuquerque, New Mexico, USA

8 School of Biological, Earth and Environmental Sciences, University College Cork, Cork, Ireland.

9 School of Biological Sciences, Monash University, Melbourne, Australia

10 Ornithological Station, Museum and Institute of Zoology, Polish Academy of Sciences, Gdańsk, Poland.

11 Quantaero, Reno, Nevada, USA.

Open Research Statement

The data, code and imagery used in this work are all available as open-source resources with

permissive licenses. The code for recreating the analysis is noted in the manuscript

(https://github.com/weecology/BirdDetector) and is available through a previously published

python package (https://deepforest.readthedocs.io/). The data and models have been uploaded to

Zenodo (https://doi.org/10.5281/zenodo.5033174).

Abstract

Advances in artificial intelligence for computer vision hold great promise for increasing the

scales at which ecological systems can be studied. The distribution and behavior of individuals is

central to ecology, and computer vision using deep neural networks can learn to detect individual

objects in imagery. However, developing supervised models for ecological monitoring is

challenging because it needs large amounts of human-labeled training data, requires advanced

technical expertise and computational infrastructure, and is prone to overfitting. This limits

application across space and time. One solution is developing generalized models that can be

applied across species and ecosystems. Using over 250,000 annotations from 13 projects from

around the world, we develop a general bird detection model that achieves over 65% recall and

50% precision on novel aerial data without any local training despite differences in species,

habitat, and imaging methodology. Fine-tuning this model with only 1000 local annotations

increase these values to an average of 84% recall and 69% precision by building on the general

features learned from other data sources. Retraining from the general model improves local

predictions even when moderately large annotation sets are available and makes model training

faster and more stable. Our results demonstrate that general models for detecting broad classes of

organisms using airborne imagery are achievable. These models can reduce the effort, expertise,

and computational resources necessary for automating the detection of individual organisms

across large scales, helping to transform the scale of data collection in ecology and the questions

that can be addressed.

Keywords: airborne monitoring, bird detection, computer vision, deep learning, UAV

Introduction

Airborne image capture is revolutionizing data collection in ecology by providing information on

animal presence, abundance and behavior at unprecedented scales (Weissensteiner et al. 2015,

Bondi et al. 2018, Reintsma et al. 2018, Afán et al. 2018). A central challenge in airborne

monitoring is converting the large amount of sensor data into ecological information. Ecological

image annotation is laborious and the amount of imagery collected can quickly overwhelm

human annotators (Kellenberger et al. 2020). Automated tools for animal detection are therefore

critical to make image-based data collection feasible at large scales. Computer vision using deep

neural networks is a subfield of artificial intelligence that connects sensor data, such as image

pixels, to semantic concepts such as the category and location of individual objects within an

image. The rapid growth of computer vision for ecological monitoring has allowed surveys to

scale to unprecedented extents using ground-based (Berger-Wolf et al. 2017) and airborne

imaging systems (Moreland et al. 2015). There have been a number of recent studies

demonstrating that with sufficient quantities of human-annotated data, computer vision using

deep neural networks can accurately predict animal location, abundance and behavior (Crall et

al. 2013, Beijbom et al. 2015, Bowley et al. 2018, Weinstein 2018, Bondi et al. 2018,

Kellenberger et al. 2018, Torney et al. 2019, Willi et al. 2019, Beery et al. 2020, Ahumada et al.

2020). However, developing and deploying models for ecological monitoring can be challenging

because: 1) large amounts of human labeled training data are typically necessary for training

deep neural networks to convergence, 2) building neural networks requires technical expertise

and access to significant computational infrastructure that are often unavailable to ecological

teams, and 3) the large number of parameters in deep neural networks tend to overfit to available

data preventing application across space and time.

One solution to these challenges is the development of generalized models that can be

applied to a broad range of species and ecosystems. Generalized models attempt to produce a

single model that works effectively regardless of the details of image background and target

object (Kawaguchi et al. 2020). Due to shared evolutionary history, animals within broad

taxonomic groups, such as class (e.g *Aves*, *Mammalia*) and order (e.g. *Charadriiformes*,

Carnivora) share general visual characteristics that can be useful for detection in natural

landscapes. While there will be significant variation in appearance within these groups, the goal

is to combine annotations from many studies to produce the large data sets needed to train a

general detector. The majority of computer vision models developed in ecology focus on a single

species or ecosystem. As a result, it is not clear how accurately deep learning models predict

under truly novel ecological conditions, how effective fine-tuning is for producing improved

predictions for individual studies, and how these models compare to similar models developed

using only training data collected specifically for that study.

The detection of large birds in airborne imagery is an ideal scenario for developing and

evaluating the performance of generalized models. Birds are a major indicator of ecosystem

health and represent an important intersection of remote sensing and conservation (Gregory and

Strien 2010). Airborne monitoring of birds using unoccupied aerial vehicles (UAVs) and

airplanes is increasingly common due to the need to monitor birds over large scales (Groom et al.

2013, Dulava et al. 2015, Kim and Kim 2020, Pfeifer et al. 2021). Much of this work involves

hand counting birds in imagery using human annotators. When computer vision methods are

applied, they typically use between 10,000 and 40,000 local annotations developed for a single

species and ecosystem (Chabot et al. 2018, Liu et al. 2020). The widespread use of airborne

imagery for monitoring birds has created sufficient data for developing a general model, but

doing so is challenging because bird species vary dramatically in appearance and the airborne

imagery is not collected in a standardized manner, with each monitoring effort collecting data

using different airborne vehicles, sampling protocols, and sensors.

Here we develop and evaluate a deep learning object detection model that identifies large

birds in high resolution airborne imagery across species and ecosystems. We build from a well-

annotated image monitoring program of long-legged wading birds in the Everglades ecosystem

of South Florida and add data from projects around the world to train the model to detect birds

regardless of species and habitat (Table 1, Figure 1). To address variation resulting from

differences in sensors and survey methods, we used data from a range of acquisition platforms

and performed on-the-fly data augmentation changing the sizes of individual annotations to

represent variation in the height and resolution of image capture. We show that this model

performs well for detecting novel species in novel environments, that its performance can be

improved by fine-tuning with only small amounts of human-labeled data, and that these fine-

tuned models outperform models based only on local training data. This approach creates a

framework for general models covering common animal taxa and will lower the barrier to

automated monitoring using airborne imagery.

Materials and Methods

Data

Initial model development was conducted with a large dataset of wading bird imagery collected

in the Everglades. This data was collected using UAV surveys over wading bird nesting colonies

from January - June 2020 to capture roosting and nesting behavior of wading birds in the central

Everglades, Florida, United States. We used a DJI Inspire II quadcopter fitted with a Zenmuse

X7 RGB camera and 35mm equivalent fixed lens. Flight transects were created using the DJI

Ground Station Pro App® and included 80% front and 75% side overlap of imagery collected at

15° off-nadir for a ground resolution of approximately 1cm. Flights were conducted between 76

and 91 m above ground level (AGL) (dependent on disturbance and air space). Target species of

wading birds included White Ibis (*Eudocimus albus*), Roseate Spoonbill (*Platalea ajaja*), Great

Egret (*Ardea alba*), Snowy Egret (*Egretta thula*) and Wood Stork (*Mycteria americana*), but

images also included incidental detections of other species in the ecosystem. After data

acquisition and preprocessing, we divided the orthomosaic into small clips and annotated all

visible birds with a single x,y point. Points were then transformed into boxes using a fixed buffer

size of 0.25m. We annotated a total of 4,653 images yielding 57,000 individual bird annotations.

Prior to model training, orthomosaic image tiles were divided into 1500 x 1500 pixel crops and

the resulting crops were split into train and test samples. The training data sample for each

dataset was composed of randomly selected crops that represented as close to 90% of the

annotations as possible within that dataset given the structure of the annotations within the

images (range 50% - 90%).

To build a global dataset, we contacted ecologists and conservation biologists using

airborne monitoring to request datasets from airborne images with largely nadir camera position

and ground sampling distance of 1-3cm (Figure 1). We obtained 13 datasets covering over

250,000 annotations for model training and testing (Table 1). All datasets came from airborne

bird monitoring projects with the exception of Seabird Watch (Table 1, ID = 9), which uses

ground based remote time lapse cameras to view distant rocky cliffs. This dataset was judged

sufficiently similar to be included based on size and resolution. For each dataset we split into

training and test sets. Wherever possible test sets were selected to be separate in time or space

from training images. For example, if there were multiple flights in an area, each flight would

occur only in train or test sets. Or if multiple islands were surveyed, each island would occur

only in train or test sets. See Appendix S1 for information on each dataset, including camera

specifications, species lists and flight information. Code, processed images and annotations are

made available on Zenodo (Weinstein 2021). The final model

(https://github.com/weecology/BirdDetector) and evaluation procedures are made available

through the DeepForest python package allowing users to extend, train and evaluate models with

minimal difficulty (Weinstein et al. 2020).

Models and Analysis

A general model for bird detection should predict birds in novel environments, allow

customization to new datasets using local annotations, and perform better than solely local data.

To test these characteristics, we trained a suite of models for analysis (Table 2). All models

shared the same architecture and general workflow but differed in input data. The architecture

was initially developed for identifying trees in airborne imagery by Weinstein et al., (2020b,

2019). The model was a one-shot object retinanet detector with a convolutional neural network

backbone (Lin et al. 2017) implemented in the 'DeepForest' Python package (Weinstein et al.

2020a). The retinanet detector uses focal loss to increase the weight of difficult to predict

images, reducing the overfitting to easy-to-predict samples. The retinanet backbone was a resnet-

50 network pretrained on the ImageNet classification benchmark.

One of the major challenges with building generalized models for airborne bird detection

is that airborne data from different sources varies in the height of image capture and resolution of

the camera. This leads to differences in size, contrast and detail of birds among datasets. To

synthesize bird detections at different resolutions we performed on-the-fly-data augmentation

during training to change the sizes of individual annotations to represent variation in the height

and resolution of image capture (Zoph et al. 2019). During each batch, a random annotation was

selected, and then a randomly sized box was placed with this focal annotation at its center. To

avoid over zooming on the annotation and filling the entire image, we set a minimum size of

0.15 times the original image size. This technique reduces overfitting but cannot fully remedy

differences in image resolution since it is possible to downscale images, but difficult to

realistically upscale images. In addition to random zooming, each image was randomly flipped

over the x or y axis with a probability of 0.5.

To evaluate the ability of the general model to predict birds in novel locations, we

performed a leave-one-out cross-validation analysis. For each large dataset, we trained a 'cross-

validation' model using all other datasets and then predicted the test images of the withheld

dataset (Table 2). While the final 'general' model available to users is trained with every dataset,

this leave-one-out strategy is a conservative proxy for future use because it represents how well a

general model works when not trained on data for a new monitoring effort. Each of the cross-

validation models were trained with a batch size of 32 for 12 epochs. Training was performed

using stochastic gradient descent (SGD) with a momentum of 0.9 and an initial learning rate of

0.001. Learning rates were reduced by 50% when validation loss had not decreased by more than

0.001 over a period of 10 epochs with a minimum learning rate of 0.00001.

To determine whether starting from the general model improved performance for new

datasets, we fine-tuned each 'cross-validation model' using local data. For example, to test the

ability to customize to the Atlantic Seaduck dataset (ID = 8), we started from the 'cross-

validation' model trained on all other datasets and added in Atlantic Seaduck annotations. We

trained multiple versions of a fine-tuned model, each with a subset of local datasets with 1000,

5000, 10000 and 20000 annotations. We repeated the sub-sampling for the fine-tuned model 3

times to evaluate the effect of image sampling. Finally, to determine whether the fine-tuned

model benefited from the pretraining on all other datasets, we trained a 'local-only' model that

used the same annotations as the 'fine-tuned' model, but starting from standard ImageNet

weights. The same test dataset was used for the fine-tuned and local-only models. The zoom data

augmentation strategy was not used in these models since flight height and object size are largely

conserved within each dataset. The local-only models were more sensitive to initial conditions,

and given each dataset, we attempted to find the optimal number of epochs that led to model

convergence and highest performance.

For all analysis, we used precision and recall on held-out images for model evaluation.

The most common evaluation metric in object detection is intersection-over-union, defined as the

area of intersection between the true and predicted bounding box, divided by the area of union

between true and predicted bounding box. Using this metric, we assessed model recall, defined

as the proportion of ground truth boxes correctly overlapping with predicted boxes with an

intersection-over-union of greater than 0.2, and model precision, defined as the proportion of

predicted boxes which overlap with a ground truth box with an intersection-over-union of 0.2.

We selected this threshold because the vast majority of annotations were automatically created

from original points placed on individual birds. The exact outline of individuals is therefore

approximate and secondary to the goal of detection and enumeration. To rank models, we also

calculate the F1-score for each model, which is a combined score of precision and recall and is

calculated as F1 = 2 * (precision * recall) / (precision + recall).

Results and Discussion

General models for ecological object detection will be most useful if they can detect individuals

in novel environments, allow customization to new datasets using local annotations, and produce

better detections than models developed with limited local annotations alone. To test for these

characteristics, we trained a suite of local and general models for analysis (Table 2). All models

shared the same workflow and architecture, a one-shot object retinanet detector with a

convolutional neural network backbone (Lin et al. 2017), but differed in input data and

evaluation data. We performed on-the-fly-data augmentation during training, zooming in on

individual annotations to represent variation in the height and resolution of image capture (Zoph

et al. 2019).

To evaluate the ability of a general model to predict birds in novel locations, we

performed a leave-one-out cross-validation analysis. For each large dataset, we trained a 'cross-

validation' model using all other datasets and then predicted the test images of the withheld

dataset (Table 2). Each model was judged to have converged by visually assessing the validation

loss during training (Figure S3). The mean recall of the held-out dataset was 67.9% (range =

29.8, 95.4%), the mean precision was 52.9% (range = 18.8, 79.7%; Figure 2), and the mean F1

score was 54.5% (range = 30.4%, 81.5%; Table 3). In general, performance was better for

datasets with high resolution imagery, such as the West African Terns (ID = 4; recall = 87.7%;

resolution = <1cm), whereas lower resolution datasets like the Antarctic Chinstrap Penguins (ID

= 5; resolution = > 2cm)) had lower values (recall = 29.8%). Datasets with forested backgrounds

similar to the everglades dataset (ID = 1), which forms the backbone of the training annotations,

had higher precision, such as the South Pacific Seabirds (ID = 2, precision = 74.0%) whereas

datasets with complex aquatic backgrounds had lower precision (e.g Canadian Marshbirds, ID=7,

precision = 18.9%). These results suggest that there is the potential for a generalized model to

make accurate predictions for completely novel species and environments, but that its

performance will depend on having sufficiently diverse data to obtain highly accurate predictions

across all novel environments.

General models can be refined to local conditions to improve performance by fine-tuning

the model using small amounts of local human-labeled data. Using ~1000 annotated birds from

the local site improved the mean recall, precision, and F1-score to 84.3%, 66.0%, and 74.5%

respectively, driven by large improvements in the datasets with the lowest precision and recall

scores in the cross-validation models (Figure 2, Table 3). For example, the Atlantic Seaducks (ID

= 8) improved from 27% recall to 98% recall (Figure 2A, 2C). Visual inspection showed that

improvements often resulted from remedying issues with background objects (e.g, shadows,

rocks, leaves) being erroneously predicted as birds, as well as providing the model with

information on bird size, which varied due to differences in species, acquisition height, and

resolution (Figure 3). Recall and precision where high for all datasets, including those with no

clear analog in the general model training data like the SeabirdWatch dataset (where the imagery

is from land-based cameras not UAVs; Figure 2C; ID = 9) and the Atlantic Seaducks (where the

background is exclusively water; ID = 8). This suggests that general models can be used

effectively for most airborne monitoring of large birds using a small number of bird annotations,

allowing monitoring efforts to automate bird detection without developing their own deep

learning models or investing in time consuming and expensive annotation efforts for every

species and environment being studied. For an example of cross-validation prediction for each

dataset, see Appendix S1.

In addition to making effective predictions with little or no local training data, building

on general models may result in more straightforward model development and better predictions

for ecological studies even in cases with moderate amounts of training data (Figure 4). This is

due to their ability to learn robust general features, thus avoiding overfitting and producing more

accurate predictions on images that deviate from the training set, which is a common occurrence

when scaling up monitoring efforts. We evaluated the performance of 'local-only' models versus

the cross-validation models that had the same structure but were initially trained with the training

data from all other datasets. In 11 of the 13 test datasets, starting from global model weights

improved overall performance (F1-score), often by large margins (Table 3). While this difference

was largest when using small amounts of local data, it persisted for some datasets even when

using >10,000 local annotations, and the fine-tuned general model always performed at least as

well as the local-only model (Figure 4). Local-only models were also highly variable with large

changes in performance among runs, sensitive to learning rate and training hyperparameters, and

required more computationally intensive training. Fine-tuned models required only 20 epochs of

training, whereas local-only models needed to be trained for at least 70 epochs to produce

reasonable results (Table 2). Even among local-only models there was large variation in the

amount of training needed. For example, the West African Terns dataset (ID = 4) had 0% recall

and 0% precision after 70 epochs even when using 20,000 local annotations. Extending to 110

epochs resulted in a rapid increase to 84% recall and 87% precision, but the potential for good

predictions for datasets like this would often be missed given the consistently poor performance

at shorter training times. This idiosyncratic behavior was difficult to anticipate since the tern

dataset is similar to other datasets in terms of the density of birds, image resolution, and

background complexity.

Compared to local-only models, the fine-tuned models were more uniform, exhibiting

significantly less between-run variance (Figure S2), and achieved good prediction with less data

and less intensive computational training. This highlights that even when large numbers of

annotations are available for an ecological study, starting with a general model makes developing

models easier and provides more stable results. As a result, starting with a general model

requires less expertise, less time spent on model development, and fewer computational

resources. Our experience developing these models suggests that the difference is significant

enough that starting with a general model will allow more studies to successfully build

automated approaches to detect individual organisms in airborne imagery and thereby reduce the

number of efforts that are limited in the scale of research due to manually annotating all birds

being studied.

From a computer vision perspective, one of the major challenges for developing this type

of general model for ecological systems is the range of sizes and representations of objects in

images caused by differences in the altitude of image acquisition and the sensor resolution. Due

to differences in species behavior, UAV regulations, and research questions it is unlikely that

there will ever be a standard approach to the acquisition of airborne monitoring imagery in

ecology. Therefore, methods are needed that can help overcome this key source of variation. We

used a data augmentation strategy to synthesize datasets at different flight elevations and

resolutions by zooming in and out on each annotation during model training. This strategy

reduced the size-based errors of the dataset, but it did not eliminate them (Appendix S1: Figure

S10). Additional strategies to address this challenge going forward include synthesizing new data

by combining abundant background data in airborne datasets with bird images from high quality

benchmarks such as iNaturalist, which includes tens of thousands of zoomed in images of birds

taken by ground-based observers (Van Horn et al. 2018). Synthetic data has been effective in

animal detection in thermal airborne imagery and would allow greater control of the range of

image scales shown during the model training (Bondi et al. 2018).

While the datasets used in this study differed in capture altitudes, angle, and sensor

specifications, they were still broadly similar in using RGB data with resolutions <3 cm.

Generalizing to spatial resolutions >3 cm and using non-RGB remote sensing (e.g., hyperspectral

imagery) requires further study across sensors and data acquisition strategies. For example,

fixed-wing aircraft surveys covering hundreds of miles are unlikely to capture images at ultra-

high resolution due to storage and processing limitations. It is unknown how well the features

learned in 2 cm imagery will transfer to 10 cm airborne imagery or high-resolution satellite

imagery (~30cm). One approach to this type of generalization is to reduce the higher resolution

data and train a series of models to bridge the features learned from high resolution to low

resolution data. This is known as 'curriculum learning' ((Graves et al. 2017) and can be useful in

transferring information among spatial resolutions.

Conclusion

Aerial imagery is a powerful tool for studying species and ecosystems at temporal frequencies

and spatial extents that are difficult using traditional methods, but it comes with computational

and analysis challenges that have limited its widespread application. General computer vision

models provide a solution for simplifying the processing of aerial imagery to allow researchers to

more easily, efficiently, and accurately extract ecological data from large amounts of imagery.

We showed that general models can provide accurate predictions in novel ecosystems and with

novel species, with either no local training data or by retraining with very small numbers of

annotations. Even when large amounts of local-data are available, starting with general models

produces more stable results, with less computational expense, and often performs better than

local-only models because of the general features these models learn from other ecosystems and

taxa. The ability of general computer vision models to make accurate predictions in novel

circumstances will make them an essential tool for monitoring dynamic ecosystems, where

species and habitats may change over time or space. Because the need for local hand-annotations

is limited, general models can potentially be rapidly deployed in new environments and support

aerial monitoring of rare species which can be difficult to study and have limited annotations

available for local model development. By reducing the effort, expertise, and computational

resources necessary to develop computer vision models for image processing, general models

have the potential for revolutionizing the types of data ecology can collect.

328   Our approach to developing a general computer vision model for bird detection was

based on the concept of transfer learning, where a model trained for one task is applied to a

different task (Pan and Yang 2010). While we used transfer learning to generalize among bird

monitoring projects with new species, in new ecosystems, using images of differing resolutions

and image capture features, transfer learning can potentially be applied more broadly to create

general detectors across taxonomic groups, including birds, mammals, reptiles, or any other

organism visible in airborne images. Using the same general model structure, (Weinstein et al.

2020) developed detection models for individual trees in airborne imagery, suggesting that the

underlying architecture is suitable for a broad array of ecological objects. The increased use of

UAV-based monitoring, combined with developments in very high resolution satellite imagery

(LaRue et al. 2017), increases the potential for animal detection at broad scales with high

temporal frequency (Willi et al. 2019). We anticipate that a cross-taxon model of animal

detection is achievable with sufficient annotations and research into the most effective way of

overcoming the large differences in resolution, object appearance and scale. A general model for

automated airborne monitoring of many types of individual organisms would fundamentally

change the scales at which we can monitor ecological systems, allowing us to tackle critical

questions about the processes that determine population dynamics and biodiversity patterns

across scales.

Funding

This work was supported by a AI4Earth grant from Microsoft Azure to BW. This research was

supported by the Gordon and Betty Moore Foundation's Data-Driven Discovery Initiative

(GBMF4563) to E.P. White, by a grant from the Army Corps of Engineers (W912HZ-20-2-

0022/3) to S.K.M. Ernest and P. Frederick, and by grants from the South Florida Water

Management District (4500126520) to S.K.M. Ernest and P. Frederick.

Acknowledgements

We thank many researchers for contributing published data and images to modeling training

including John Neill, Christian Pfeifer, Kyle Landolt, Heather Lynch, Madeline Hayes, Rodrigo

Valle, Benjamin Kellenberger, Gary Andrew and Francie Cuthbert. Dan Morris was instrumental

in hosting data and organizing the AI4Earth community. Thanks to Mark Koneff and the Branch

of Migratory Bird Surveys for their assistance in gathering data and providing insight on model

application.

Works Cited

Afán, I., M. Máñez, and R. Díaz-Delgado. 2018. Drone Monitoring of Breeding Waterbird

Populations: The Case of the Glossy Ibis. Drones 2:42.

Ahumada, J. A., E. Fegraus, T. Birch, N. Flores, R. Kays, T. G. O'Brien, J. Palmer, S. Schuttler,

J. Y. Zhao, W. Jetz, M. Kinnaird, S. Kulkarni, A. Lyet, D. Thau, M. Duong, R. Oliver,

and A. Dancer. 2020. Wildlife Insights: A Platform to Maximize the Potential of Camera

Trap and Other Passive Sensor Wildlife Data for the Planet. Environmental Conservation

47:1–6.

Beery, S., G. Wu, V. Rathod, R. Votel, and J. Huang. 2020. Context R-CNN: Long Term

Temporal Context for Per-Camera Object Detection. Pages 13075–13085.

Beijbom, O., P. J. Edmunds, C. Roelfsema, J. Smith, D. I. Kline, B. P. Neal, M. J. Dunlap, V.

Moriarty, T.-Y. Fan, C.-J. Tan, S. Chan, T. Treibitz, A. Gamst, B. G. Mitchell, and D.

Kriegman. 2015. Towards Automated Annotation of Benthic Survey Images: Variability

of Human Experts and Operational Modes of Automation. PLOS ONE 10:e0130312.

Berger-Wolf, T. Y., D. I. Rubenstein, C. V. Stewart, J. A. Holmberg, J. Parham, S. Menon, J.

Crall, J. Van Oast, E. Kiciman, and L. Joppa. 2017. Wildbook: Crowdsourcing, computer

vision, and data science for conservation. arXiv:1710.08880 [cs].

Bondi, E., D. Dey, A. Kapoor, J. Piavis, S. Shah, F. Fang, B. Dilkina, R. Hannaford, A. Iyer, L.

Joppa, and M. Tambe. 2018. AirSim-W: A Simulation Environment for Wildlife

Conservation with UAVs. Pages 1–12 Proceedings of the 1st ACM SIGCAS Conference

on Computing and Sustainable Societies. Association for Computing Machinery, New

York, NY, USA.

Bowley, C., M. Mattingly, A. Barnas, S. Ellis-Felege, and T. Desell. 2018. Detecting Wildlife in

Unmanned Aerial Systems Imagery Using Convolutional Neural Networks Trained with

an Automated Feedback Loop. Pages 69–82 *in* Y. Shi, H. Fu, Y. Tian, V. V.

Krzhizhanovskaya, M. H. Lees, J. Dongarra, and P. M. A. Sloot, editors. Computational

Science – ICCS 2018. Springer International Publishing, Cham.

Chabot, D., C. Dillon, and C. Francis. 2018. An approach for using off-the-shelf object-based

image analysis software to detect and count birds in large volumes of aerial imagery.

Avian Conservation and Ecology 13.

Crall, J. P., C. V. Stewart, T. Y. Berger-Wolf, D. I. Rubenstein, and S. R. Sundaresan. 2013.

HotSpotter — Patterned species instance recognition. Pages 230–237 2013 IEEE

Workshop on Applications of Computer Vision (WACV).

Dulava, S., W. T. Bean, and O. M. W. Richmond. 2015. Environmental Reviews and Case

Studies: Applications of Unmanned Aircraft Systems (UAS) for Waterbird Surveys.

Environmental Practice 17:201–210.

Graves, A., M. G. Bellemare, J. Menick, R. Munos, and K. Kavukcuoglu. 2017. Automated

Curriculum Learning for Neural Networks. Proceedings of the 34th International

Conference on Machine Learning 70:10.

Gregory, R. D., and A. van Strien. 2010. Wild bird indicators: using composite population trends

of birds as measures of environmental health. Ornithological Science 9:3–22.

Groom, G., M. Stjernholm, R. D. Nielsen, A. Fleetwood, and I. K. Petersen. 2013. Remote

sensing image data and automated analysis to describe marine bird distributions and

abundances. Ecological Informatics 14:2–8.

Hayes, M. C., N. Chazal, D. W. Johnston, V. D. Crawford, P. C. Gray, W. C. Sedgwick, and G.

Harris. 2021. Data from: Drones and deep learning produce accurate and efficient

monitoring of large-scale seabird colonies.

Kawaguchi, K., L. P. Kaelbling, and Y. Bengio. 2020. Generalization in Deep Learning.

arXiv:1710.05468 [cs, stat].

Kellenberger, B., D. Marcos, and D. Tuia. 2018. Detecting mammals in UAV images: Best

practices to address a substantially imbalanced dataset with deep learning. Remote

Sensing of Environment 216:139–153.

Kellenberger, B., D. Tuia, and D. Morris. 2020. AIDE: Accelerating image-based ecological

surveys with interactive machine learning. Methods in Ecology and Evolution 11:1716–

1727.

Kim, S., and M. Kim. 2020. Learning of Counting Crowded Birds of Various Scales via Novel

Density Activation Maps. IEEE Access 8:155296–155305.

LaRue, M. A., S. Stapleton, and M. Anderson. 2017. Feasibility of using high-resolution satellite

imagery to assess vertebrate wildlife populations. Conservation Biology 31:213–220.

Lin, T.-Y., P. Goyal, R. Girshick, K. He, and P. Dollar. 2017. Focal Loss for Dense Object

Detection. Pages 2980–2988.

Liu, Y., V. Shah, A. Borowicz, M. Wethington, N. Strycker, S. Forrest, H. Lynch, and H. Singh.

2020. Towards Efficient Machine Learning Methods for Penguin Counting in Unmanned

Aerial System Imagery. Pages 1–7 2020 IEEE/OES Autonomous Underwater Vehicles

Symposium (AUV).

McKellar, A. E., N. G. Shephard, and D. Chabot. 2021. Dual visible-thermal camera approach

facilitates drone surveys of colonial marshbirds. Remote Sensing in Ecology and

Conservation n/a.

Moreland, E. E., M. F. Cameron, R. P. Angliss, and P. L. Boveng. 2015. Evaluation of a ship-

based unoccupied aircraft system (UAS) for surveys of spotted and ribbon seals in the

Bering Sea pack ice. Journal of Unmanned Vehicle Systems 3:114–122.

Pan, S. J., and Q. Yang. 2010. A Survey on Transfer Learning. IEEE Transactions on Knowledge

and Data Engineering 22:1345–1359.

Pfeifer, C., M.-C. Rümmler, and O. Mustafa. 2021. Assessing colonies of Antarctic shags by

unmanned aerial vehicle (UAV) at South Shetland Islands, Antarctica. Antarctic

Science:1–17.

Reintsma, K. M., P. C. McGowan, C. Callahan, T. Collier, D. Gray, J. D. Sullivan, and D. J.

Prosser. 2018. Preliminary Evaluation of Behavioral Response of Nesting Waterbirds to

Small Unmanned Aircraft Flight. Waterbirds 41:326–331.

Torney, C. J., D. J. Lloyd-Jones, M. Chevallier, D. C. Moyer, H. T. Maliti, M. Mwita, E. M.

Kohi, and G. C. Hopcraft. 2019. A comparison of deep learning and citizen science

techniques for counting wildlife in aerial survey images. Methods in Ecology and

Evolution 10:779–787.

Van Horn, G., O. Mac Aodha, Y. Song, Y. Cui, C. Sun, A. Shepard, H. Adam, P. Perona, and S.

Belongie. 2018. The iNaturalist Species Classification and Detection Dataset. Pages

8769–8778 2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition.

IEEE, Salt Lake City, UT.

Weinstein, B. 2021. A global model of bird detection in high resolution airborne images using

computer vision.

Weinstein, B. G. 2018. A computer vision for animal ecology. Journal of Animal Ecology

87:533–545.

Weinstein, B. G., S. Marconi, M. Aubry□Kientz, G. Vincent, H. Senyondo, and E. P. White.

2020. DeepForest: A Python package for RGB deep learning tree crown delineation.

Methods in Ecology and Evolution 11:1743–1751.

Weissensteiner, M. H., J. W. Poelstra, and J. B. W. Wolf. 2015. Low-budget ready-to-fly

unmanned aerial vehicles: an effective tool for evaluating the nesting status of canopy-

breeding bird species. Journal of Avian Biology 46:425–430.

Willi, M., R. T. Pitman, A. W. Cardoso, C. Locke, A. Swanson, A. Boyer, M. Veldthuis, and L.

Fortson. 2019. Identifying animal species in camera trap images using deep learning and

citizen science. Methods in Ecology and Evolution 10:80–91.

Zoph, B., E. D. Cubuk, G. Ghiasi, T.-Y. Lin, J. Shlens, and Q. V. Le. 2019. Learning Data

Augmentation Strategies for Object Detection. arXiv:1906.11172 [cs].

Table 1. Description of the datasets used to train and evaluate the general model. For more detail

on taxa, resolution and acquisition conditions, please see Appendix S1.

ID	Taxa	Location	Citation	Train Annotations	Test Annotations
1	Wading Birds	Florida, USA	-	50869	5647
2	Seabirds	Palmyra Atoll, South Pacific	-	1305	456
3	Penguins	Antarctic Peninsula	Liu et al. 2020	1744	1293
4	Terns	Guinea	(Kellenberger et al. 2020)	20790	2301
5	Penguins and Shags	South Shetland Islands, Antarctica	(Pfeifer et al. 2021)	25337	2528
6	Albatross and Penguin	Falkland Islands	(Hayes et al. 2021)	8408	930
7	Marsh Birds	Saskachawan, Canada	(McKellar et al. 2021)	1598	60

8	Ducks	Cape Cod, USA	-	26417	226
9	Seabirds	North Atlantic	-	61009	2363
10	Seabirds	Indian Ocean Seabirds	-	9846	327
11	Pelicans	Utah, USA	-	39623	5119
12	Ducks, Geese and Cranes	New Mexico, USA	-	2582	174
13	Gulls	Lake Michigan, USA	-	40233	6199
14	Waterbirds (Ducks, Swans, Herons, Terns and Gulls)	Poland		7584	-

Table 2. Model descriptions and terminology for the analysis of the general bird model. Global

annotations come from all datasets except for the dataset being evaluated. Local annotations

come from the dataset being evaluated. During zoom data augmentation, images are randomly

preprocessed to zoom in or out on a subset of birds within an image to mimic flights at different

heights. All models were trained using SGD optimization with learning rate of 0.001 and

momentum of 0.9 with a batch size of 32 on two NVIDIA DGX A100 GPUs

Model	Global Annotations	Local Annotations	Zoom Augmentation	Epochs	Description
Cross-validation	Yes	No	Yes	12	For each dataset we trained on all other datasets and then predicted a portion of the withheld dataset.
Local-only	No	Yes	No	70-110	Individual models using only local annotations for each dataset. This model was repeated for up to 1000, 5000, 10000 and 20000 local annotations.
Fine-tune	Yes	Yes	No	20	For each dataset we started from the cross-validation model using all other datasets and then fine-tuned using local annotations. This model was repeated for up to 1000, 5000, 10000 and 20000 local

					annotations.
General model	Yes	Yes	Yes	12	Final model trained with all training and test data for future use

Table 3. F1 scores for novel datasets. F1 is calculated as F1 = 2 * (precision * recall) / (precision

+ recall). The cross-validation model is trained on all other datasets and is used to predict the

test dataset. The local-only model uses only annotations from the test dataset. The finetune

model starts from the cross-validation model and trains on annotations from the test dataset. Two

local-only models are shown, one with 1000 annotations and one with 5,000 annotations.

Datasets that do not have 5,000 total annotations have NA values.

Dataset	F1 - Cross-validation	F1 - Local Only (1000)	F1 - Local Only (5000)	F1 - Finetune (1000)
2. Seabirds - South Pacific	0.80	0.20	NA	0.72
3. Penguins - Antarctica	0.68	0.20	NA	0.83
4. Terns - Guinea	0.81	0.0	0.0	0.79
5. Penguins and Shags - Antarctica	0.41	0.0	0.0	0.66
6. Albatross - Falklands	0.62	0.0	0.52	0.79
7. Marshbirds - Canada	0.3	0.59	NA	0.60
8. Ducks - Cape Cod	0.4	0.12	0.93	0.82
9. Seabirds - North	0.5	0.0	0.31	0.69

Atlantic				
10. Seabirds - Indian Ocean	0.49	0.21	0.76	0.72
11. Pelicans - Utah	0.43	0.0	0.70	0.79
12. Ducks - New Mexico	0.59	0.0	NA	0.76
13. Lake Michigan - USA	0.49	0.0	0.73	0.72

Figure 1: Example orthomosaics for A) the Everglades dataset (ID = 1 in Table 1), B) West

African Terns (ID = 4), C) Seabirds from the South Pacific (ID = 2), and D) Chinstrap Penguins

from Antarctica (ID = 3). The datasets differ in acquisition backgrounds, target species,

individual density and camera specifications.

Figure 2. Results of predictions on novel datasets with and without fine-tuning. Recall and

precision for each dataset for the cross-validation model with 0 local annotations and the fine-

tuned model with 1000 local bird annotations. Recall is defined as the proportion of ground truth

boxes that are correctly predicted. Precision is defined as the proportion of predicted that match a

ground truth box. The violin plots show the density of points along the Y-axis across all datasets.

Figure 3. Example images from cross-validation (top) models with no local training data and

fine-tuned models (bottom) with 1000 local bird annotations. From left to right, images are from

a) South Pacific Seabirds (ID = 2), b) Pelicans from Utah, USA (ID = 11), c) Terns from West

Africa (ID = 4), and d) Seabirds from the North Atlantic (ID = 9). Predicted birds are in blue,

ground truth birds are in orange.

Figure 4. Difference between models fit using only local annotations (the 'local-only' model)

and general models retrained with the same local data (the 'fine-tuned' model) for each dataset

using different numbers of local annotations for training. The fine-tuned model is pre-trained on

all other datasets, whereas the local-only model contains no annotations from other datasets.

Each dataset was run up to its available number of annotations.

502