1
2
The representational hierarchy in human and artificial visual systems in the presence of object-scene regularities

5
6
7   Stefania Bracci[12]*, Jakob Mraz[2], Astrid Zeman[2], Gaëlle Leys[2] and Hans Op de Beeck[2].

8
9
10   [1] Center for Mind/Brain Sciences - CIMeC, University of Trento, Rovereto (TN), Italy.
11   [2] KU Leuven, Leuven Brain Institute, Brain & Cognition Research Unit, Leuven, 3000, Belgium.

12
13
14
15
16 Corresponding author:
17 Stefania Bracci
18 Corso Bettini, 31 - 38068 Rovereto
19 tel. 0464 808718
20 stefania.bracci@unitn.it

21
22

26
27

28 **Keywords:**
29 Object recognition, scenes, context, DCCNs, visual cortex.

30
31
32
33 **Author Contributions:**
34 Designed research: S.B. and H.O.B;
35 Performed research: S.B., A.Z., and G.L.;
36 Analyzed data: S.B. and J.M.;
37 Wrote the paper: S.B., J.M., and H.O.B;
38
39
40

Abstract

Human vision is still largely unexplained. Computer vision made impressive progress on this front, but it is still unclear to which extent artificial neural networks approximate human object vision at the behavioral and neural levels. Here, we investigated whether machine object vision mimics the representational hierarchy of human object vision with an experimental design that allows testing within-domain representations for animals and scenes, as well as across-domain representations reflecting their real-world contextual regularities such as animal-scene pairs that often co-occur in the visual environment. We found that DCNNs trained in object recognition acquire representations, in their late processing stage, that closely capture human conceptual judgements about the co-occurrence of animals and their typical scenes. Likewise, the DCNNs representational hierarchy shows surprising similarities with the representational transformations emerging in domain-specific ventrotemporal areas up to domain-general frontoparietal areas. Despite these remarkable similarities, the underlying information processing differs. The ability of neural networks to learn a human-like high-level conceptual representation of object-scene co-occurrence depends upon the amount of object-scene co-occurrence present in the image set thus highlighting the fundamental role of training history. Further, although mid/high-level DCNN layers represent the category division for animals and scenes as observed in VTC, its information content shows reduced domain-specific representational richness. To conclude, by testing within- and between-domain selectivity while manipulating contextual regularities we reveal unknown similarities and differences in the information processing strategies employed by human and artificial visual systems.

Author Summary

Computational object vision represents the new frontier of brain models, but do current artificial visual systems known as deep convolutional neural networks (DCNNs) represent the world as humans do? Our results reveal that DCNNs are able to capture important representational aspects of human vision both at the behavioral and neural levels. At the behavioral level, DCNNs are able to pick up contextual regularities of objects and scenes thus mimicking human high-level semantic knowledge such as learning that a polar bear "lives" in ice landscapes. At the neural representational level, DCNNs capture the representational hierarchy observed in the visual cortex all the way up to frontoparietal areas. Despite these remarkable correspondences, the information processing strategies implemented differ. In order to aim for future DCNNs to perceive the world as humans do, we suggest the need to consider aspects of training and tasks that more closely match the wide computational role of human object vision over and above object recognition.

Introduction

We live in a structured world; as a consequence, sensory input is not a random collection of lines and patterns but can be organized into meaningful and identifiable wholes such as objects. These objects show particular relationships to their environment. Some objects are most likely to appear in specific contexts, such as penguins in ice landscapes or lions in the savannah. This set of rules, similarly to the grammar of our language, provides a structure to guide our behaviour [1]. Here we investigate how information about object domain and their cross-domain structure is represented through the visual processing in human and artificial neural systems.

While visual information is fully intertwined at the retina level, soon through the human hierarchical visual pathway, information pertaining to the different object domains is processed in largely separated brain networks [e.g., 2, 3] as confirmed by human neuroimaging revealing rich domain-specific object spaces characterizing the different processing channels. As an example, behaviourally relevant image dimensions are encoded in object and scene areas: animate features such as the eyes/mouth, useful for identifying living entities in the former [4-6], and spatial layout, informative for scene navigation in the latter [7-9]. At the same time, statistical regularities of the world influence perception [10-13] as shown by faciliatory effects of context observed during object recognition [14] and evidence for interaction between object and scene processing at the neural level [15-18]. While such studies indicate that the representation of objects might be influenced by whether they share similar context statistics, to our knowledge, none of them included a multivariate test pinpointing the representational similarity of neural patterns across objects and scenes. Is the frequent occurrence of a penguin in ice landscapes sufficient to modulate how penguins and ice landscapes are coded despite the separate processing channels? Or does interaction occur at a later stage of visual processing when information becomes relevant to support goal-directed behaviour?

Even less is known about how this across-domain segregation and integration happens in artificial vision models. In the past decade, artificial computer vision models have been developed that are able to classify visual patterns with human-level performance, such as deep convolutional neural networks [DCNNs; 19] and recent adaptations including residual, recurrent, and transformer networks [20]. These artificial models appear to develop representations similar to those in human visual cortex [21, 22]. Various avenues have been suggested to further improve this correspondence, such as the use of recurrent processing and changes in training regimes [20, 23]. But does the representational hierarchy learnt by DCNNs mimic the information transformation emerging through the human visual hierarchy? The presence of object-scene regularities potentially provides a critical test of this correspondence. Many DCNNs employed in computational vision are trained on object recognition which is considered the main computational goal of visual cortex [24] and employ large image sets in which each image is attached to a single label [25]. In such scenario, DCNNs trained in object recognition do not need to explicitly separate objects from background scene; short cuts are available and sufficient to solve the problem. In other words, visual information from image background might be equally useful to succeed at the task at hand, thus shaping the learnt object space. This suggests that DCNNs might very well mimic the ability of the human perceptual system to take advantage of image statistical and contextual regularities experienced during lifetime [11, 14, 26], but these

artificial models might find this solution in a different way without explicitly segregating object
and scene information.

Here, we compare "neural" representations in the human brain and in artificial DCNNs using an
original stimulus set that includes object images and background images with a variety of
object/scene domain specific properties, as well as a manipulation of object-background co-
occurrence in real-world images. The results show that DCNNs in a quite remarkable way, appear
capable of mimicking conceptual-like human knowledge of the world such as capturing the
conceptual similarity for a specific object-scene pair (gorilla and jungle forest) as well as the
hierarchical representations observed along the human visual pathway, all the way up to
frontoparietal areas. At the same time, results suggest difference in the underlying computational
strategy implemented by the two systems.

Results

To test how the biological or artificial brain represent object within-domain and cross-domain regularities through their computational hierarchy, we created a stimulus set which includes two category domains of contextually related pairs of images (Fig. 1). Each pair includes one animal (clownfish, ladybug, passerine bird, seagull, polar bear, and gorilla) and its associated background scene (anemone, leaves, tree branches, seashores, ice landscapes, and jungle forests). We carefully selected images of animals that have a neutral background (e.g., the polar bear and the gorilla have a similar grayish background) to avoid possible confounds where the object background might be informative for recognition.

Fig. 1 – Experimental design. *(A) The stimulus set includes 2 domains: animals and scenes, each including 6 different identity conditions (4 images for each condition). The pictures of animals were carefully selected to avoid that background information could be informative for object identification (e.g., the polar bear and the gorilla have a very similar neutral background). To control for shape, we further divided the animal categories in three subsets along the animacy continuum (2 mammals, 2 birds, and 2 small rounded animals). Within each subset, animals are matched for body shape (e.g., gorilla and polar bear) but each animal is paired with a different scene. As an example, the passerine bird and the seagull have similar body shape but are associated with two different backgrounds. As for the pictures of scenes, 3 of the backgrounds are characterized by rich navigational properties where there is no object in focus in the middle of the image: seashores, ice landscapes, and jungle forests. The other 3 backgrounds are object-like scenes with little navigational layout properties: anemones, leaves, and tree branches. Concurrently, animals and scenes conditions were selected based on their frequent co-occurrence in real-world images: polar bears live in ice landscapes and gorilla live in forest jungles, thus allowing the creation of 6 specific object-scene contextual pairs (B) The ROIs included in the brain RSA analysis included visual areas (for their relevance in object recognition) and frontoparietal areas (for their relevance in goal-directed behavior): BA17, posterior ventral-temporal cortex (VTC), anterior VTC, lateral VTC, occipital place area (OPA), parahippocampal area (PPA), retrosplenial cortex (RSC), intraparietal sulcus (IPS), and dorsal prefrontal cortex (DPFC). See Methods for details on the localization procedure. (C) Four models were tested: GIST, condition, domain, and co-occurrence.*

This unique stimulus set allows us to differentiate between alternative hypotheses about how objects and scenes might be represented (Fig. 2). The *domain model* predicts a separation between animals and scenes. On the contrary, the *co-occurrence model* predicts contextually related associations between each animal and its specific background scene. These two models are orthogonal to each other (r = -0.05). Two additional control models rule out the role of visual factors: (1) The *GIST model* [27], a good descriptor of scene statistics [13], well describes

166 responses in lower visual areas [28]; (2) the *condition model* captures within-category similarities
167 for each animal and scene condition. Representational similarity analysis [RSA; 29] allows to test
168 each model's ability to capture the object space in the brain and DCNNs.
169
170
171 **Object and scene information is processed in separate visual pathways, with**
172 **contextual effects emerging in frontoparietal areas.**
173
How does the human brain encode both object-scene separation and interaction? To test this, we
analyzed fMRI scans from participants (N=19; two long scan sessions per participant) while they
watched the stimuli from Fig. 1A in an event-related design. Participants were asked to indicate
to what extent each image would normally co-occur with the previous image. We investigated
the representational structure along the hierarchy of visual regions from the primary visual cortex
over regions involved in object and scene perception up to regions in the frontoparietal cortex
involved in goal-directed behavior [30] that are known to be connected to domain-specific
regions [31].
182
Results in visual cortex reveal a clear separation between animal and scene representations,
despite their co-occurrence in our visual experience. The domain model captures most variance
in many areas from posterior to anterior temporal cortex but, importantly, not in early visual
cortex BA17 where only the GIST model reached significance (z=0.14; p=0.0001, Fig. 2A). The
separation between animals and scenes is particularly evident in animal-selective areas (domain
model: z > 0.84; for all ROIs, p < 0.0001, Fig. 2A) with an additional minor contribution of the
GIST model in posterior VTC (z=0.17; p < 0.0001, Fig. 2A). This separation is also very obvious
when visually inspecting the dissimilarity matrices displayed in Fig. 2 (bottom). In scene-selective
areas, the domain model also best captures the representational structure in 2 out of 3 ROIs
(PPA: z= 0.46; OPA: z= 0.29; both p < 0.0001, Fig. 2A). The remaining models did not explain
any additional variance in these areas. The very same results were observed using single-subject
data (Fig. 2B).
195
The information comes together again when moving downstream, with a small but significant
effect of the co-occurrence model in frontoparietal areas (IPS: z= 0.18; DPFC: z = 0.16, both p <
0.0001, Fig. 2A), thus shifting the representational content in these ROIs from object-scene
separation to object-scene contextual association. When using individual subject data, the effect
for the co-occurrence model in these ROIs is relatively small but highly significant (DPFC and IPS:
z > 0.04, both p < 0.005, Fig 2B). It also reaches reliability boundaries (IPS: 0.09; DPFC: 0.04),
which indicates the highest expected correlation in a brain region after accounting for signal
noise [32]. In DPFC, the remaining models did not explain any significant variance in the
patterns, while in IPS there were significant correlations for the domain model (z= 0.18; p <
0.0001, Fig. 2A; z= 0.05; p < 0.0001, Fig. 2B) and condition model (z= 0.03; p = 0.001, Fig.
2B). Together, these results show that the overall representational content in visual cortex largely
distinguishes category information at domain level (object vs scene), with interaction of these
components emerging at a later processing stage in regions known to support goal-directed
behavior [30]. The whole-brain RSA confirmed these results revealing that the domain model
strongly activates regions in the ventral and dorsal visual pathways, whereas the co-occurrence
effect for animals and matching scenes is confined within frontoparietal areas (Fig. 2C).

Fig. 2. The representational hierarchy for separation and interaction of objects and scenes in the brain. The ROI-based (A, B) and whole-brain (C) RSA results for the 4 models (GIST, condition, domain, co-occurrence) are shown for brain data. Results reveal a strong separation for domain (scene and animal) representations in most ventral regions. The effect for animal-scene co-occurrence emerges in frontoparietal areas. (A) For group-averaged results, filled bars indicate significant values against baseline (p < 0.0001) computed with permutation tests (10,000 randomizations of stimulus labels). (B) For individual subject results, reliability boundaries (in gray) indicate the highest expected correlation considering signal noise (see Methods) and error bars indicate SEM. Filled bars indicate significant values against baseline (p <0.005, corrected for n. or ROIs) calculated with pairwise t-tests across subjects (n=19). For each ROI, the neural dissimilarity matrix (1 - r) is shown below. (C) The random-effects whole-brain RSA results corrected with Threshold-Free Cluster Enhancement [TFCE; 33] are displayed separately for each individual model against baseline [BrainNet Viewer; 34].

The representational hierarchy in DCNNs mimics representational transformations observed in the human brain.

DCNNs widely employed in image classification [35], are now considered a promising venue to explain biological object vision at the neural level, proving to match human object recognition abilities in several benchmarks [36-38]. Yet, it is unclear the extent to what machine vision learns brain-like representational hierarchy and computational strategies [39]. To test this, we use RSA to evaluate the predictive power of our models in four DCNNs: Alexnet, VGG16, GoogLeNet, and ResNet-50. All models are trained in object recognition (ImageNet) which is widely considered the main computational goal of ventral visual cortex [24] and are the most frequent benchmarks used in the literature that suggests similarities in representational structure between human and computational vision [40, 41].

Quite remarkably, results revealed high similarity between biological and artificial systems in their representational hierarchy (Fig 3A). At an early stage of computational processing, the GIST model best predicts representations in all neural networks (p < 0.001 relative to all models). At mid/high-level layers, when the GIST model drops in performance, the domain model increases and reaches significance relative to the remaining models (p < 0.001). Finally, the representational space at the latest processing stage shows a salient object-scene association. For all networks, the co-occurrence model peaks at the final processing stages (i.e., fully

connected layers) and, relative to the remaining models, explains significantly better the DCNNs'
representational space (p < 0.001 relative to all models; for summary statistics, see Fig. 3B). This
structure is also visible in the secondary diagonal emerging in the lower left and upper right
quadrant of the networks' representational dissimilarity matrices (Fig. 3A). The entangled animal-
scene representation emerges later through the network's hierarchy, ruling out the contribution
of low-level image properties best captured by low-level visual models such as the GIST (e.g.,
visual similarities between each animal category and its associated environment).

253
Fig. 3. Similar representational hierarchy in the brain and DCNNs. *(A) The DCNNs RSA results for the 4*
models (GIST, condition, domain, co-occurrence) are shown for 4 DCNNs (AlexNet, VGG16, GoogLeNet, ResNet-
50). The network's depth is shown on the x axis. For each graph and each model, color-coded lines indicate
significant effects relative to all remaining models (p < 0.001) computed with pairwise permutations tests (1000
randomizations of stimulus labels). For each DCNN, the representational dissimilarity (1 - r) is shown for the last
fully connected layer. (B) Correlational matrices show second-order relationships among representational patterns
in the brain's ROIs and individual DCNNs' layers. Color-coded line boxes highlight the ROIs and DCNNs' layers
where each model reaches significance. For brain areas, significance for each model is shown relative to baseline
(p <0.0001), calculated with permutation tests (10,000 randomizations of stimulus labels). For DCNNs' layers,
significance for each model is shown relative to all remaining models (p < 0.001), calculated with permutation
tests (1000 randomizations of stimulus labels). Both systems show similar transformations in the representational
space. Early on, the object space reflects image low-level visual properties (GIST model, yellow color-coded), it
then shifts towards animal-scene domain division (domain model, light-blue color-coded), to finally reveal animal-
scene co-occurrence effects (co-occurrence model, purple color-coded).

Overall, these results suggest that DCNNs are able to capture the way visual information is
transformed through the human brain visual hierarchy, from early visual cortex encoding low-
level visual properties, through VTC encoding domain specific information in separate channels,
all the way up to frontoparietal areas where information from the different domains is combined
to support goal-directed behavior focused upon object-scene regularities (Fig 3B). Based on

these results, we expect this effect to also emerge when directly comparing DCNNs and brain
representations. To test this, we correlated the hierarchical representational space for each
DCNNs with the representational space in the selected ROIs (Fig. 4A) as well as across the whole
brain (Fig. 4B). Results confirm this prediction showing that the correlation between DCNNs
representations and the ventral stream domain-specific areas (animal- and scene-selective areas)
increases up to mid-high layers but it then drops sharply. Conversely, representational
correspondence with frontoparietal areas increases and remains high till the final processing
layers. This effect was observed regardless of DCNNs architecture.
282
283

285
286 ***Fig. 4. VTC representations are best captured by mid-level DCNNs layers.*** *(A) For each DCNNs, the RSA*
287 *results show the degree of similarity between the representational space of individual layers in each brain area.*
288 *(B) The random-effects whole-brain RSA results corrected with Threshold-Free Cluster Enhancement [TFCE; 33]*
289 *are displayed separately for each layer of AlexNet against baseline [BrainNet Viewer; 34].*
290

291
292 **DCNNs capture humans' conceptual knowledge of object-scene co-occurrence**
293

An object code that incorporates statistical regularities of an object in its background might be
relevant to mimic human-like object recognition behavior, which indeed is influenced by the
object-scene interaction [10, 11]; context facilitates object recognition and vice versa [14]. Given
that DCNNs representations at their final layers appear to capture a degree of contextual
regularities between an object and its recurring background scene, we might expect similarities
with human behavior when humans judge image similarities in terms of co-occurrence (see
Methods).
301

302
Fig. 5. DCNNs acquire human-like conceptual biases. *(A) The correlational plot shows the degree of*
similarity between behavioral judgments and each of the four DCNN architectures. (B) MDS spaces (metric stress)
show consistent object-scene clusters in human behavioral judgments as well as DCNNs (last fully connected
layer). (C) The object-scene cluster analysis (right) for behavioral and DCNNs (last layer) data, show a consistent
significant effect of congruency (lower distance) for object-scene stimulus pairs. Dashed bars show the averaged
data for the 6 stimulus pairs.
309

Results confirm this prediction. The correlation between human co-occurrence judgments and
DCNNs' object space (Fig. 5A) increases throughout the DCNNs' processing hierarchy to reach its
peak at the final processing stages for all DCNNs (AlexNet: z = 0.46; VGG16: z = 0.59;
GoogLeNet: z = 0.65; ResNet-50: z = 0.56). The DCNNs' ability to capture human behavior is
also visible when inspecting the MDS's space (Fig. 5B). In a similar fashion as the object space
generated by behavioral judgments, the DCNNs object space in their final layer shows an orderly
structure: each animal sits close to its semantically associated scene, thus revealing a clear

contextual effect. To confirm this observation statistically, we tested similarities for congruent
pairs (polar bear and iceberg) versus the average of all remaining incongruent pairs (polar bear
and jungle). We observed significantly higher similarity for congruent relative to incongruent
pairs in behavioral ($p < 0.0001$; Fig. 5C) as well as DCNNs data (for all models, $p < 0.001$). Thus,
DCNNs' sensitivity to image statistical regularities of objects occurring in typical environments
results in the acquisition of a "representation of the world" that closely resembles humans'
conceptual judgments.
324
325   **Knowledge about object-scene co-occurrence is reached through different**
326   **computational strategies in DCNNs**
327
The ability of DCNNs to capture human high-level conceptual knowledge about the world is
striking, but does this prove that the artificial networks have a real understanding of objects and
scenes? One possibility is that object-background segregation might be less optimized in DCNNs
architectures trained with natural images (e.g., ImageNet) where regularities between objects
and backgrounds are common. For instance, a whale lives in open water, not on the street. As
such, any image feature (e.g., not necessarily object-specific) might become a useful piece of
information to recognize the object [42]. Here, we test this hypothesis by systematically
manipulating object/background co-occurrence during DCNNs training (see Methods): from 0%
co-occurrence (objects within the same category were no more likely to occur on the same
background type than objects from different categories) to 100% co-occurrence (objects within
the same category were always presented on the same background). Confirming the role of
image regularities in facilitating object recognition (Fig 6A), the model's validation test revealed
significantly higher model performance for the 100% co-occurrence condition (accuracy: 0.85)
relative to remaining conditions (accuracy < 0.72; $t(4)$ 3.95, $p < 0.02$, for all pairwise t-tests).
Furthermore, we predicted an increasing representational bias towards human-like conceptual
object-scene associations in accordance with increasing object-scene co-occurrence. We run an
RSA analysis with each of our predicting models and tested correlations for fully connected layer
7 in a 4x4 ANOVA within Co-occurrence (0%, 58%, 83%, 100%) and Model (GIST, condition,
domain, co-occurrence) as within-subject factors. Results revealed a significant Co-occurrence x
Model interaction ($F(9,36)$ 11.82, $p < 0.0001$; Fig. 6B) showing that different levels of object-
background regularities in the training set result in differences in DCNN's representational
content (fc7) as captured by our models.

Fig. 6. The effect of increasing levels of object-scene co-occurrence in DCNN object space. *We trained a DCNN multiple times (N=5) in 4 training conditions with increasing levels of object-background regularity from 0% to 100%. (A) Accuracy results for the model's validation test. (B) The RSA results for the 4 models (GIST, condition, domain, co-occurrence) are shown for AlexNet's fc7 that underwent different training regimes with increasing co-occurrence (0%, 58%, 87%, 100%) between objects and backgrounds (n=6). Error bars indicate SEM. In the dissimilarity matrices, red represents animal conditions and orange represents background conditions.*

Follow-up analyses revealed that the contextual-related effect is absent when the training is based on random object-scene associations (0% co-occurrence: z = 0.01) but emerges when regularities in the training set increase (58%: z = 0.20; 83%: z = 0.27; 100%: z = 0.32). This effect is already significantly higher for the 58% condition relative to 0% condition (t(4) 3.68, p= 0.02) and it increases for higher levels of object-scene co-occurrence (83%: t(4) 6.51, p= 0.003; 100%: t(4) 20.22, p < 0.0001; both relative to 0%). Interestingly, the effect of the condition model is significantly high when the network cannot rely on scene information (0%: z = 0.17), but strongly decreases when regularity increases (58%-100%: z < 0.06; t(4), > 6.24, p < 0.004, for all 3 comparisons). In the 100% co-occurrence condition, the correlation with the GIST model reaches significance (z = 0.18; t(4), > 5.78, p = 0.004), probably because in this condition there is an increase of lower-level background features that can be relied upon. This last condition shows that finding a representation of object-scene correspondences can be obtained through various processing strategies. This motivated us to take closer look at the processing stages right before the stage at which object-scene correspondences are represented.

Multiple object (domain-specific) spaces in the visual cortex but not in DCNNs

In visual cortex, the domain model captures most of the variance in animal as well as in scene areas, but the dissimilarity matrices (Fig. 2A) reveal a marked difference between the two sets of regions that likely reflect differential domain-specific object spaces [7-9, 43, 44]. DCNN's mid-layers do also show domain division for animals and scenes (Fig. 3A), but does this division embed rich domain-specific object spaces like those observed in the human visual cortex? We tested two domain-specific dimensions that well characterize the object space in animal and scene areas: the animacy continuum for the animal domain and navigational layout information

for the scene domain. These two dimensions were included in our stimulus set (Fig. 7A). The
animacy continuum model [43] captures the degree to which an animal is perceived as animate
(within the animate/inanimate division some animals are perceived more animate than others:
mammals > birds, birds > fish/bugs). Conversely, the *navigational layout model* captures the
degree to which scene layout provides relevant information for scene navigation. In addition, we
included two control models. First, the condition model is considered the default model for the
classification tasks employed in computational vision model which predicts classification at the
level of basic category (e.g., polar bears, beaches etc). Second, to control for low-level image
properties, we also include the GIST model. As above, these models were tested with RSA in
brain and DCNNs data. To account for the different domains we tested two instances of the same
DCNNs architecture (GoogLeNet), trained to classify the basic level category in the two domains:
objects (ImageNet) and scenes (Scene 365).
395
As expected, the RSA on the brain data (Fig 7B) confirms differential representational spaces
reflecting domain-specific object spaces in visual cortex. Whereas VTC areas show a significant
preference for the animacy continuum model (VTC post: z = 0.76; VTC lat: z = 0.84; VTC inf: z
= 0.70; all p < 0.001, relative to the remaining models), scene-selective PPA and OPA show a
significant preference for the navigational layout model (OPA: z=0.47; PPA: z= 0.38; both p <
0.001, relative to the remaining models). These results highlight the functional specialization of
the human brain for multiple domain-specific computations and it highlights a representational
richness that is exactly what one expects in a system with separate streams to process animal
and scene information relevant to support domain-specific computations.
405
Do DCNNs trained on category (objects or scenes) recogntion tasks learn representations that
mimic brain domain-specific object spaces? When comparing the same architecture (GoogLeNet)
on two different training tasks (object recogniton and scene recogniton) we note that only the
object recognion task revealed some effects similar to those obseved in visual cortex (Fig 7A,
GoogLeNet). The RSA for DCNN data trained on object recognition (GoogLeNet trained on
ImageNet) partially replicates results observed in VTC showing a significant effect for the
animacy relative to all remaining models in those same layers that revealed an domain-division
effect in the previous RSA analysis (Fig 7C, gray-shaded areas). Interestingly, at the latest
processing stage the representation was best predicted by the condition model which reflects the
representation expected when a network learn to distinguish the different conditions at the basic-
level. Overall, this result reveals higher sensitivity for the dimension DCNNs were trained on (note
that the Imagenet dataset contains a high % of animal images) and points to a potentially critical
role that training tasks play in developing domain-specific spaces in DCNNs. On the contrary, the
DCNN trained in scene recognition (GoogLeNet trained on Scene 365), throughout its layers, did
not reveal any similarity with the object space observed in scene-selective areas (Fig 7B). It did
not learn a representational space that reflects the amount of navigational layout features
present in the image. This result is not totally unexpected; scene recognition tasks require the
elaboration of information that substantially differs from the information necessary to support
scene navigation computations, thus questioning the role of purely recognition-based training
tasks in capturing the richness of object space observed in visual cortex. Finally, the different
training task did not influence the representations learnt in the early layers. In early layers, both
object and scene recognition DCNNs showed a representational space that was best captured by
the GIST model relative to the remaining models (Fig. 7C).

Fig. 7. Multiple domain-specific object spaces. *The RSA results for the 4 models (GIST, condition, animacy continuum, navigational layout) are shown for (B) group-averaged brain data and (C) DCNNs. (B) For the neural data, only ROIs where the domain model reached significance were included (see Fig. 2A). (C) The same DCNN architecture (GoogLeNet) was trained either on object recognition (ImageNet), or scene recognition (Scene 365). For comparison with the first RSA analysis (see Fig 3A), gray shaded areas indicate the network's layers in which the domain model significantly outperformed the remaining models. Color-coded lines on top of bar/graphs indicate the network's layers/ROIs where each model significantly outperformed the remaining models (p < 0.001) computed with pairwise permutations tests (1000 randomizations of stimulus labels).*

Discussion

We investigated how human and machine object vision represent within-domain and across-domain information of animals and scenes matched for contextual regularities and to what extent the latter mimics human object vision computations. We measured the representational similarity within domain (for animals and scenes) as well as across domains (animal-scene association), in a stimulus set that includes object-scene pairs that often co-occur in the visual environment. Results revealed that DCNNs employed in computational vision are able to capture conceptual representations humans have about object-scene correspondences. Not only DCNNs trained to perform object recognition are able to capture human judgments about contextual associations between and animal and its typical scene, but most importantly, they show a good hierarchical correspondence at the neural level. Nevertheless, our results do also show differences in terms of implemented computational strategies. In the visual cortex, object and scene information is processed in separated pathways, which reveal domain-specific representational contents for animal (animacy continuum) and scene (navigational layout) processing. Interaction between object and scene components was observed at a later processing stage in areas that contribute to goal-directed behavior. DCNNs' mid-layers showed a similar degree of object/scene separation, but its information content shows reduced domain-specificity even when DCCNs were trained on domain-specific recognition tasks (i.e., scene recognition). Further, the emergence of human-like high-level conceptual representation of object-scene co-occurrence in DCNNs depends upon the amount of object-scene co-occurrence present in the image-set thus highlighting the fundamental role of training history. In sum, despite the remarkable achievements shown by convolutional object recognition trained DNNs, when aiming to mimic the rich and multiple representational spaces observed in the human brain, future brain models should extent their focus beyond recognition tasks.

The primate brain is, at least in part, characterized by separated modules for domain-specific processing [45]. These modules are relatively independent such that confined lesions disrupt computations for one domain (e.g., animate entities) leaving unaffected other domains [e.g., inanimate objects; 46]. In visual cortex, domain-specific areas encode object dimensions tailored to support specific computations [31, 47, 48]. As an example, view-invariant features represented in face- [48, 49] and hand-selective regions [50, 51] reflect domain-specific computations: the former to support identity recognition [52], the latter to support action understanding [50]. In agreement, our results show that in addition to a large division between animal and scene representations, within each domain, representational content reflects the type of computations these networks support: animacy features in animal-selective areas [4, 5, 53] and layout navigational properties in scene-selective areas [7, 54]. We can show this representational diversity because in our study we included separate behavioral-relevant dimensions for objects (i.e., animacy continuum) and background scenes (i.e., navigational properties), while this was typically not done in previous studies. Furthermore, by including objects and backgrounds that co-occur in the environment, we also demonstrate that at the level of domain-specific representations there is not yet a strong effect of such statistical regularities. This is not to say that there is no interaction between object and scene representations in human object vision, which in fact, has been reported in previous studies [12, 15, 55, 56]. Nevertheless, the nature of such an interaction is still debated and it might occur on top of domain modularity for objects and scenes [57, 58]. Our study points in this direction, showing that, ultimately, all

such interaction effects ride on top of a fundamental division of labor for animal versus scene
properties.

In a quite remarkable fashion, DCNNs capture both human behavior as well as the hierarchical
representations observed in the human brain. When it comes to behavior, DCNNs pick up typical
object-background regularities reflecting conceptual knowledge we have about the world, thus
reaching the human-unique conceptual knowledge level. However, the information processing
strategy might be very different in DCNNs. Indeed, when we manipulated object-background
systematically in a smaller-scale training regime, even arbitrary object-background associations
resulted in strong effects of such associations upon the representations that these networks
develop (Fig. 6). This result highlights the critical role played by training on the resulting object
space. In the context of a one-image, one-label approach, any pixel in the image might contain
features useful to recognize objects. When such regularities are prevalent in a dataset, as it is for
natural image databases, shortcuts can be taken [59]. In these situations, background
information becomes as relevant (or even more relevant) as the object to be recognized [60].
This points to a substantial difference between human vision and feedforward DCNNs. Although,
faciliatory effects on object recognition have been observed when an object and its background
are congruent [14], thus highlighting the potential role of statistical regularities in the
environment in supporting human behavior [26], the ability to separate foreground objects from
background information is a prerequisite to object recognition, for which the VTC plays a critical
role. On the contrary, the DCNNs tested here, which are widely used in computational vision, do
integrate background information in their learnt object space when they have been trained in
image classification.

The effect of background on the object space in DCNN's fully connected layers raises the
question of how much of the previously reported domain-specific effects (e.g., animacy division)
observed in these same layers are due to the sensitivity of these layers to represent background
information in addition to objects [61-63]. Such questions arise because apparently DCNNs end
up with representations in which object and scene information is more entangled than what we
observe in the human visual system. One possibility is that DCNNs represent animals separated
from inanimate objects because the former is typically seen in specific backgrounds. Taking such
shortcuts can be advantageous such as the case shown here, where DCNNs acquired human-like
"knowledge" on which they were not trained. However, in general, studies show that relying too
much on background information can result in remarkable non-human-like errors. Examples have
been reported where DCNNs accuracy for animal recognition drops in unfamiliar backgrounds
[64], large animals go undetected in unlikely environments such as a living room [65], or more
simply, object classification might be primarily driven by object-irrelevant information present in
the image, which happen to correlate with categorization-relevant features [42].
527
Previous studies have shown that DCNNs learn a hierarchical representational space that mimics
the visual hierarchy observed in the ventral pathway, where the top DCNNs layers are those that
best fit with VTC representations [22, 66]. Our results go beyond previous observations and show
that VTC domain-specific representations are well captured by mid-level layers instead, because
final layers appear to even be able to predict high-level representations observed in downstream
frontoparietal areas, generally associated to goal-directed behavior [30]. How can we explain
these findings? We believe that the answer lies in the selection of the stimulus set. Previous

studies have mainly focused on independent category representations (e.g., animate-inanimate),
here instead we created a stimulus set that in addition to within-domain relations allows to test
similarities across domains that can be found in the co-occurrence of an object in its typical
scene.
539
Although DCNNs might implement different computational strategies they do still develop
interesting representations. Already in our study, the object space in mid-layers, revealed
evidence for a degree of animacy continuum on top of object-scene division. What these
representations lack, however, is the diversity and division of labor that we see in the human
brain (Fig 7). The representational diversity observed in visual cortex is likely to result from the
need of our brain to employ visual information to support diverse behavioral goals: from
recognizing the identity and mental states of people we constantly interact with, to the ability to
navigate in the surrounding environment. These computations are implemented in parallel brain
networks and the representations in domain-specific networks are optimized to support the
different computational goals our brain constantly deals with. Thus, for instance, in visual cortex,
scene-selective areas represent scene layout information relevant to support navigation which is
not captured by DCNNs trained on scene recognition tasks (Fig. 7). DCNNs can be trained in
separate domains though. Training a network on a specific object domain (e.g., faces and
objects) leads to diverging object spaces in late DCNNs' layers [67], which however, do not
generalize well to other domains [68-70]. Together, this highlights the advantages of domain-
specialized modules evolved by biological vision [45]. We suggest that future DCNNs that aim to
capture the rich and diverse representational space found in VTC need to employ tasks that go
beyond standard object recognition tasks and target the diverse computational goals our visual
system supports.
559
In sum, our study confirms and goes beyond previous studies showing a quite remarkable ability
of DCNNs to mimic human object vision at the behavioral and neural representational level in a
previously unexplored aspect: the representation of object-scene correspondences. At the same
time, it demonstrates the importance of a unique aspect of human information processing
relative to machine vision: human information processing represents rich and diverse object
spaces. Most likely, this is related to the fact that the human brain has evolved and has been
trained to implement a wide variety of tasks that require to extract different information type
from the different domains present in the visual scene: object information might be more
relevant for computations that pertain human-object interactions, whereas information from the
background is more relevant to spatial computations such as navigation in the environment. As a
consequence, humans understand that an object is not just a collection of features, which could
erroneously lead to the assumption that green leaves are inherently linked to ladybugs or to
adversarial errors such as classifying a set of yellow and black stripes as a school bus [71]. While
the human brain is definitely also prone to the use of shortcuts and heuristics [72], the presence
of multiple streams of processing and of a multitude of modular systems has the potential of
limiting the impact of such shortcuts. It is a major challenge for the future to develop neural
network models with a similar richness of representational content.
577
578
579
580

Methods and Materials

Participants

We recruited 21 participants (7 females, mean age 29). All participants took part in the behavioral test and in 2 functional neuroimaging sessions. Due to technical problems, 1 session from 2 participants and 2 sessions from 1 participant went lost. Additionally, due to excessive head motion, all data from 1 participant and 4 runs from an additional participant were excluded from the data analyses. The head motion exclusion criterion was set to 2 mm (equal to 1 voxel size) and defined before data collection. All participants signed the informed consent approved from the ethic committee at KU Leuven.

Stimuli

We constructed a stimulus set with contextual-related pairs of images (Fig 1A). For each contextual pair (1 background and 1 animal), we selected 6 conditions, each containing 4 examples. The animal conditions were depicted on a neutral background to avoid low-level associations between animals and their typical backgrounds. To balance the animals' shape information, we included 2 similarly colorful (red) rounded shaped and small size animals (clownfish and ladybug), 2 birds (passerine and seagull) and 2 mammals with similar body shape (polar bear and gorilla). Thus, conditions within each animal pair are matched in terms of taxonomic and visual information (the two birds have a similar shape, visual features, and both fly), but are specifically associated with a different background: one was associated with a watery background (polar bear and ice landscapes) and one with a greenery background (gorilla and jungle). Finally, each stimulus domain is characterized by a behaviorally relevant dimension: the animacy continuum for the animal conditions [fish/bug < birds < mammals; 43] and the degree of navigational properties [7, 8] for the background conditions (seashore, ice landscape, forest jungle versus anemones, leaves, tree branches).

fMRI data

The fMRI data was acquired in two separate sessions within 2 weeks. Each session comprised 8 runs for the main experiment and 2 runs for the functional localizer. For the main experiment, each run lasted 6 min and 52 sec (206 volumes). For each run, the 48 image trials and 16 fixation trials were presented twice in a random order. Each trial was presented for 1500 ms and followed by a fixation screen for 1500 ms. Each run started and ended with 14 s of fixation. During scanning participants performed a one-back task judging on a scale from 1 to 4 the degree of co-occurrence of each pair of stimuli ("How often do you see these images occurring together?"). The response order was counterbalanced across runs. Before the first scanner session, participants familiarized with the stimuli and performed a similarity judgments task [73] arranging the 48 images (Fig 1A) according to "the degree to which you see these images occurring together". The resulting behavioral dissimilarity matrices were averaged across participants.

Acquisition parameters. The fMRI scans were acquired on a 3T Philips scanner with a 32-channel
coil at the Department of Radiology of the University Hospitals Leuven. MRI volumes were
collected using echo planar (EPI) T2*-weighted scans. Acquisition parameters were as follows:
repetition time (TR) of 2 s, echo time (TE) of 30 ms, flip angle (FA) of 90°, field of view (FoV) of
224 mm, and matrix size of 112 x 109 and voxel size of 2 x 2 x 2 mm. Each volume comprised 60
axial slices (0.2 mm gap) acquired with a multi-band factor of 2, covering the whole brain. The
T1-weighted anatomical images were acquired with an MP-RAGE sequence, with 1 x 1 x 1 mm
resolution.
634
Preprocessing. Before statistical analysis, functional images underwent a standard preprocessing
procedure (SPM 12, Welcome Department of Cognitive Neurology) including three-dimensional
head-motion corrected (2nd degree spine interpolation), coregistration to the individual
anatomical images and normalization to an MNI (Montreal Neurological Institute) template.
Spatial smoothing by convolution of a Gaussian kernel of 4 mm full width at half-maximum was
applied to functional images [74]. For each participant, a general linear model (GLM) was created
to model the 48 conditions and the six motion correction parameters (x, y, z for translation and
for rotation). Each predictor's time course was modeled for 3 s (stimulus presentation + fixation)
by a boxcar function convolved with the canonical hemodynamic response function in SPM.
644
Regions of interest (ROIs). All ROIs were defined at the group level based on anatomical masks
defined with the Neuromorphometrics SPM toolbox, and functional masks defined with an
independent localizer. All visually active voxels (all 48 conditions vs baseline) exceeding the
uncorrected threshold p <0.0001 within the functional/anatomical masks were included. The
anatomical-based ROIs included 2 visual areas (V1, posterior VTC), and 2 frontoparietal areas,
intraparietal sulcus (IPS) and dorsal prefrontal cortex (DPFC). The functionally defined ROIs
included animal- and scene-selective areas defined with the contrast animals versus scenes and
scenes versus animals, respectively by means of an independent localizer. Animal-selective areas
were defined in lateral and ventral VTC. Scene-selective areas were defined in parahippocampal
gyrus (PPA), retrosplenial cortex (RSC), and transverse occipital sulcus (TOS).
655
656 **DCCN data**
657
We extracted the vector spaces for images in our stimulus set from 4 recent DCNNs with different
depth: Alexnet [75], VGG-19 [76], GoogLeNet [77] and ResNet 50 [78]. DCNNs consist of various
feedforward processing stages including (1) convolutional layers, (2) rectified linear unit
activation, (3) max pooling layers, and (4) fully connected layers (resembling a multilayer
perceptron). For each DCNNs and each convolutional and fully connected layer, we extracted the
vector space for all 48 stimuli by means of the Deep Learning Toolbox
(https://uk.mathworks.com/products/deep-learning.html) in MATLAB. All DCNNs were pre-trained
in object recognition on 1.2 million natural images belonging to 1000 classes for the ImageNet
dataset (http://www.image-net.org/). In addition, GoogLeNet was also pre-trained in scene
recognition on the Place365 dataset which contains 10 million images comprising more than 400
scene classes. Each scene contains between 5000 to 30,000 training images.
669
670

Statistical Analysis

We used representational similarity analysis [RSA; 29] to compare the neural activity patterns from the brain's ROIs and DCNNs' layers to our experimental models. CoSMoMVPA [79] was used to create the representational dissimilarity matrices (RDMs) for brain and DCNNs data. For neural data, for each voxel within a given ROI, GLM parameter estimates for each stimulus condition (relative to baseline) were extracted for each participant and each run and normalized by subtracting the mean response across all conditions. Similarly, for each DCNNs, the vector features for each stimulus condition within each layer were normalized by subtracting the mean feature activations across all conditions. Next, we computed Pearson's correlation across voxels (fMRI) or units (DCNNs) between all condition pairs and converted the resulting correlation matrix into a representational dissimilarity matrix (RDM; 1 minus Pearson's r) and used it as input for the RSA analysis. We performed two main analyses. To test our main experimental hypothesis, we run two RSAs for both brain and DCNNs data. The first analysis tested two main models: the domain model which assumed high similarity for stimuli within each domain (animals and scenes) and the co-occurrence model which assumed high similarity for each animal-scene contextual-related pair. These two models were derived from our two alternative hypotheses and were orthogonal to each other (r=-0.05). Two additional control models were included: the GIST model [27] to capture low-level image information and the condition model to account for within condition similarities. For the neural data the RSA was performed for group averaged data and for single subject data. For the latter one we calculated reliability of RDMs which indicates the highest expected correlation in a brain region given its signal-to-noise ratio. For each subject and each ROI, the RDM was correlated with the averaged RDM of the remaining participants. The resulting correlation values (averaged across participants) capture noise inherent to a single subject as well as noise caused by inter-subject variability. For the second RSA (Fig 7), in addition to the two control models, the following experimental models were included: the animacy continuum model which captures the well-known animacy continuum described in VTC and the navigational layout model which instead captures the degree to which a scene contains features useful for navigation. Before statistical analyses, results from the RSAs were Fisher transformed (0.5*log[(1r)/(1r)]) and tested with ANOVAs and pairwise t tests when individual-subject data were available, or permutation tests for DCNNs and fMRI group averaged data (1000 and 10000 iterations of permuting stimulus labels for DCNNs and brain data, respectively).

In addition to ROI-based RSAs we performed two whole-brain RSAs. The whole-brain RSA was implemented in CoSMo MVPA (Oosterhof et al., 2016) using the volume-based searching approach (Kriegeskorte et al., 2006). For each condition (relative to baseline), parameter estimates were extracted for each participant and each run and normalized by subtracting the mean response across all conditions. Resulting values were then averaged across all runs. For each brain voxel, a searchlight was defined using a spherical neighborhood with a variable radius, including the 100 voxels nearest to the center voxel. For each searchlight, the neural dissimilarity matrix was computed for the 48 stimuli. The neural dissimilarity matrix (upper triangle) was then correlated with the dissimilarity matrices derived from the 4 models (Fig 1C) and dissimilarity matrices derived from all layers of AlexNet (Fig 4). The output correlation values were Fisher transformed and assigned to the center voxel of the sphere. Resulting whole-brain correlation maps for each model and layer were tested against baseline using random effects whole-brain group analysis corrected with the threshold-free cluster enhancement (TFCE) method (Smith and

717 Nichols, 2009). Voxelwise-corrected statistical maps for each model/layer relative to baseline (z
718 1.96; p < 0.025, one-sided t test) are displayed on a brain template by means of BrainNet Viewer
719 (Xia et al., 2013).
720
721

DCNN experiment with congruency manipulation
723
Construction of the training datasets: Custom datasets were constructed by joining masked
images of objects with inverse-masked images of scenes obtained from two publicly available
datasets. Images of 6 object categories ('bus', 'clock', 'dog', 'giraffe', 'television', 'umbrella') were
obtained from the Microsoft COCO dataset that consists of over 300.000 images labelled with
more than 2 million object instances [80]. Each object instance is associated with a mask which
allows extraction of object-representing pixels. Objects of small size (ratio between object size
versus total image size smaller than 3%) were enlarged and objects of object-image ratio smaller
than 0.15% omitted in order to avoid unsatisfactory classification performance on images with
hardly any object-associated pixels [81]. Scene images of 6 categories ('church indoor', 'sand
desert', 'glacier', 'ocean underwater', 'broadleaf forest', 'landfill') were obtained from the Places
dataset that consists of more than 2 million images of 205 scene categories, most of them
containing several thousand unique images [82]. This allowed generation of a total of 10500
training images (1750 per object category) of 256 x 256 x 3 pixels per dataset, in which each
image showed an object of one of the 6 object categories embedded in a scene of one of the 6
scene categories.
739
Four different datasets of 0%, 58.3%, 83.3% and 100% of object-scene co-occurrence were
constructed by manipulating the likelihood of objects being joined with their adhering background
type. Each dataset was constructed out of the same set of object and background images that
were, however, joined in a different fashion. To illustrate this on the example of 83.3% object-
scene co-occurrence dataset, backgrounds of every 1st, 2nd, 3rd and 4th image were object-
specific (80%) and background of every 5th image was belonging to either one of the six
background categories (20%). Thus, there is an additional 1/6 chance that randomly chosen
backgrounds will come from the object-specific category (adding additional 3.3% to the total
object-scene specificity of the dataset). In the 0% object-scene co-occurrence, none of the 6
scene categories is more likely to be associated with a particular object category than the other
scene categories (all have a 16.7% chance).
751
Training of the models: Five individual DCNN models were trained on each of the constructed
datasets. The models followed the standard AlexNet architecture with five convolutional and
three fully-connected layers with one minor difference in input layer accepting images of size 256
x 256 x 3 instead of 224 x 224 x 3 pixels, as originally defined by Krizhevsky and colleagues
(2012)[75] to better fit the size of our image stimuli. All models were trained for 150 epochs in
batches of 75 training images, with the Adam optimizer and categorical cross-entropy loss
function. A dropout regularization rate of 0.5 was added to the first two fully-connected layers.
Additionally, image augmentation was employed to improve generalization of the trained models.
At the end of the training, only the weights of the best performing epoch (lowest validation loss
calculated on a total 750 validation images, 125 per object category) were stored. All models
were implemented in Python utilizing functions of the Keras library.

Representational similarity analysis with congruency manipulation: Additionally, representational
similarity analysis was performed to compare patterns of inner neural representations of the
trained networks with our experimental models. In order to do so, neural activations of each
networks' 7th layer (fully connected) were extracted by presenting them with 48 image stimuli,
each sprouting 4096 neural activations. This set of stimuli consisted of 24 images of objects on
neutralized backgrounds and 24 images of scenes without the object entities (4 for each object
category and 4 for each scene category). Neutralized backgrounds were obtained by averaging
pixels of 6 scene images randomly chosen from Places dataset [82], each of them belonging to
one of the above specified scene categories. This was done in order to provide objects with a
background that possessed no relevant scene information yet were not too
atypical/homogeneous and thus too different from training examples (usage of monotonous
backgrounds was found to be problematic as it significantly impacted internal representations of
the networks). Next, correlations between internal activations for each stimulus were obtained by
calculation of Pearson correlation coefficients. This sprouted a single RSA matrix for each model
which was in the end transformed into an RDM matrix by subtracting it from a unit matrix (with
all values equal one) of a matching dimension.
780
781

782 **Data and Code Availability**
783 All types of brain images are available from the authors upon request. The stimulus set and
784 statistics data will be made available through the Open Science Framework at xxx.
785

Acknowledgments

S.B. was funded by FWO (Fonds Wetenschappelijk Onderzoek) through a postdoctoral fellowship
(12S1317N) and a Research Grant (1505518N). J.M. was supported by the Ad futura Scholarship
of the Public Scholarship, Development, Disability and Maintenance Fund of the Republic of
Slovenia. H.O.B. was supported by the KU Leuven Research Council (C14/16/031) and
FWO/FNRS EOS (Excellence of Science) grant HumVisCat (nr. 30991544).

792
793
794
795

References

1.   Vo ML, Boettcher SE, Draschkow D. Reading scenes: how scene grammar guides attention and aids
perception in real-world environments. Curr Opin Psychol. 2019;29:205-10. Epub 2019/05/06. doi:
10.1016/j.copsyc.2019.03.009. PubMed PMID: 31051430.
2.   Epstein R, Kanwisher N. A cortical representation of the local visual environment. Nature.
1998;392(6676):598-601. Epub 1998/04/29. doi: 10.1038/33402. PubMed PMID: 9560155.
3.   Malach R, Reppas JB, Benson RR, Kwong KK, Jiang H, Kennedy WA, et al. Object-related activity
revealed by functional magnetic resonance imaging in human occipital cortex. Proceedings of the National
Academy of Sciences of the United States of America. 1995;92(18):8135-9. Epub 1995/08/29. PubMed
PMID: 7667258; PubMed Central PMCID: PMCPMC41110.
4.   Bracci S, Ritchie JB, Kalfas I, Op de Beeck HP. The Ventral Visual Pathway Represents Animal
Appearance over Animacy, Unlike Human Behavior and Deep Neural Networks. The Journal of neuroscience
: the official journal of the Society for Neuroscience. 2019;39(33):6513-25. Epub 2019/06/15. doi:
10.1523/JNEUROSCI.1714-18.2019. PubMed PMID: 31196934; PubMed Central PMCID:
PMCPMC6697402.
5.   Ritchie JB, Zeman AA, Bosmans J, Sun S, Verhaegen K, Op de Beeck HP. Untangling the animacy
organization of occipitotemporal cortex. BioRxiv. 2020;2020.07.17.206896.
6.   Wardle SG, Taubert J, Teichmann L, Baker CI. Rapid and dynamic processing of face pareidolia in
the human brain. Nature communications. 2020;11(1):4518. Epub 2020/09/11. doi: 10.1038/s41467-020-
18325-8. PubMed PMID: 32908146; PubMed Central PMCID: PMCPMC7481186.
7.   Kravitz DJ, Peng CS, Baker CI. Real-world scene representations in high-level visual cortex: it's the
spaces more than the places. The Journal of neuroscience : the official journal of the Society for
Neuroscience. 2011;31(20):7322-33. Epub 2011/05/20. doi: 10.1523/JNEUROSCI.4588-10.2011. PubMed
PMID: 21593316; PubMed Central PMCID: PMCPMC3115537.
8.   Park S, Brady TF, Greene MR, Oliva A. Disentangling scene content from spatial boundary:
complementary roles for the parahippocampal place area and lateral occipital complex in representing real-
world scenes. The Journal of neuroscience : the official journal of the Society for Neuroscience.
2011;31(4):1333-40. Epub 2011/01/29. doi: 10.1523/JNEUROSCI.3885-10.2011. PubMed PMID:
21273418; PubMed Central PMCID: PMCPMC6623596.
9.   Bonner MF, Epstein RA. Coding of navigational affordances in the human visual system.
Proceedings of the National Academy of Sciences of the United States of America. 2017;114(18):4793-8.
Epub 2017/04/19. doi: 10.1073/pnas.1618228114. PubMed PMID: 28416669; PubMed Central PMCID:
PMCPMC5422815.
10.   Biederman I. Perceiving real-world scenes. Science. 1972;177(4043):77-80. Epub 1972/07/07. doi:
10.1126/science.177.4043.77. PubMed PMID: 5041781.
11.   Palmer TE. The effects of contextual scenes on the identification of objects. Mem Cognit.
1975;3(5):519-26. Epub 1975/09/01. doi: 10.3758/BF03197524. PubMed PMID: 24203874.
12.   Bar M. Visual objects in context. Nature reviews Neuroscience. 2004;5(8):617-29. Epub
2004/07/21. doi: 10.1038/nrn1476. PubMed PMID: 15263892.
13.   Oliva A, Torralba A. The role of context in object recognition. Trends in cognitive sciences.
2007;11(12):520-7. Epub 2007/11/21. doi: 10.1016/j.tics.2007.09.009. PubMed PMID: 18024143.
14.   Davenport JL, Potter MC. Scene consistency in object and background perception. Psychol Sci.
2004;15(8):559-64. Epub 2004/07/24. doi: 10.1111/j.0956-7976.2004.00719.x. PubMed PMID: 15271002.
15.   Brandman T, Peelen MV. Interaction between Scene and Object Processing Revealed by Human
fMRI and MEG Decoding. The Journal of neuroscience : the official journal of the Society for Neuroscience.
2017;37(32):7700-10. Epub 2017/07/09. doi: 10.1523/JNEUROSCI.0582-17.2017. PubMed PMID:
28687603; PubMed Central PMCID: PMCPMC6596648.
16.   Bar M, Aminoff E, Schacter DL. Scenes unseen: the parahippocampal cortex intrinsically subserves
contextual associations, not scenes or places per se. The Journal of neuroscience : the official journal of the
Society for Neuroscience. 2008;28(34):8539-44. Epub 2008/08/22. doi: 10.1523/JNEUROSCI.0987-
08.2008. PubMed PMID: 18716212; PubMed Central PMCID: PMCPMC2707255.

17.   Oppermann F, Hassler U, Jescheniak JD, Gruber T. The rapid extraction of gist-early neural
correlates of high-level visual processing. Journal of cognitive neuroscience. 2012;24(2):521-9. Epub
2011/08/05. doi: 10.1162/jocn_a_00100. PubMed PMID: 21812567.
18.   Bonner MF, Epstein RA. Object representations in the human brain reflect the co-occurrence
statistics of vision and language. Nature communications. 2021;12(1):4081. Epub 2021/07/04. doi:
10.1038/s41467-021-24368-2. PubMed PMID: 34215754; PubMed Central PMCID: PMCPMC8253839.
19.   LeCun Y, Bengio Y, Hinton G. Deep learning. Nature. 2015;521(7553):436-44. doi:
10.1038/nature14539. PubMed PMID: 26017442.
20.   Zhuang C, Yan S, Nayebi A, Schrimpf M, Frank MC, DiCarlo JJ, et al. Unsupervised neural network
models of the ventral visual stream. Proceedings of the National Academy of Sciences of the United States
of America. 2021;118(3). Epub 2021/01/13. doi: 10.1073/pnas.2014196118. PubMed PMID: 33431673;
PubMed Central PMCID: PMCPMC7826371.
21.   Yamins DL, Hong H, Cadieu CF, Solomon EA, Seibert D, DiCarlo JJ. Performance-optimized
hierarchical models predict neural responses in higher visual cortex. Proceedings of the National Academy
of Sciences of the United States of America. 2014;111(23):8619-24. doi: 10.1073/pnas.1403112111. PubMed
PMID: 24812127; PubMed Central PMCID: PMC4060707.
22.   Khaligh-Razavi SM, Kriegeskorte N. Deep supervised, but not unsupervised, models may explain
IT   cortical   representation.   PLoS   computational   biology.   2014;10(11):e1003915.   doi:
10.1371/journal.pcbi.1003915. PubMed PMID: 25375136; PubMed Central PMCID: PMC4222664.
23.   Bakhtiari S, Mineault P, Lillicrap T, Pack CC, Richards BA. The functional specialization of visual
cortex emerges from training parallel pathways with self-supervised predictive learning. bioRxiv.
2021;https://doi.org/10.1101/2021.06.18.448989.
24.   Ullman S. High-Level Vision: Object Recognition and Visual Cognition. . Cambridge, MA: MIT
Press. 1996.
25.   Deng J, Dong W, Socher R, Li LJ, Li K, Fei-Fei L. Imagenet: A large-scale hierarchical image
database. . IEEE conference on computer vision and pattern recognition 2009;pp. 248-255.
26.   Kaiser D, Quek GL, Cichy RM, Peelen MV. Object Vision in a Structured World. Trends in
cognitive sciences. 2019;23(8):672-85. Epub 2019/05/31. doi: 10.1016/j.tics.2019.04.013. PubMed PMID:
31147151.
27.   Oliva A, Torralba A. Modeling the shape of the scene: A holistic representation of the spatial
envelope. Int J Comput Vis. 2001;42:145–75.
28.   Groen, II, Ghebreab S, Prins H, Lamme VA, Scholte HS. From image statistics to scene gist: evoked
neural activity reveals transition from low-level natural image structure to scene category. The Journal of
neuroscience : the official journal of the Society for Neuroscience. 2013;33(48):18814-24. Epub 2013/11/29.
doi: 10.1523/JNEUROSCI.3128-13.2013.   PubMed   PMID: 24285888;   PubMed   Central   PMCID:
PMCPMC6618700.
29.   Kriegeskorte N, Mur M, Bandettini P. Representational similarity analysis - connecting the branches
of systems neuroscience. Frontiers in systems neuroscience. 2008;2:4. doi: 10.3389/neuro.06.004.2008.
PubMed PMID: 19104670; PubMed Central PMCID: PMC2605405.
30.   Duncan J. The multiple-demand (MD) system of the primate brain: mental programs for intelligent
behaviour.   Trends   in   cognitive   sciences.   2010;14(4):172-9.   Epub   2010/02/23.   doi:
10.1016/j.tics.2010.01.004. PubMed PMID: 20171926.
31.   Epstein RA, Baker CI. Scene Perception in the Human Brain. Annual review of vision science.
2019;5:373-97. Epub 2019/06/22. doi: 10.1146/annurev-vision-091718-014809. PubMed PMID: 31226012;
PubMed Central PMCID: PMCPMC6989029.
32.   Ritchie JB, Bracci S, Op de Beeck H. Avoiding illusory effects in representational similarity
analysis: What   (not)   to   do   with   the   diagonal.   NeuroImage.   2017;148:197-200.   doi:
10.1016/j.neuroimage.2016.12.079. PubMed PMID: 28069538.
33.   Smith SM, Nichols TE. Threshold-free cluster enhancement: addressing problems of smoothing,
threshold dependence and localisation in cluster inference. NeuroImage. 2009;44(1):83-98. doi:
10.1016/j.neuroimage.2008.03.061. PubMed PMID: 18501637.
34.   Xia M, Wang J, He Y. BrainNet Viewer: a network visualization tool for human brain connectomics.
PloS one. 2013;8(7):e68910. doi: 10.1371/journal.pone.0068910. PubMed PMID: 23861951; PubMed
Central PMCID: PMC3701683.
35.   He K, Zhang X, Ren S, Sun J. Delving Deep into Rectifiers: Surpassing Human-Level Performance
on ImageNet Classification. arXiv. 2015;1502.01852v1.

36. Cichy RM, Kaiser D. Deep Neural Networks as Scientific Models. Trends in cognitive sciences.
2019;23(4):305-17. Epub 2019/02/24. doi: 10.1016/j.tics.2019.01.009. PubMed PMID: 30795896.
37. Lindsay GW. Convolutional Neural Networks as a Model of the Visual System: Past, Present, and
Future. Journal of cognitive neuroscience. 2020:1-15. Epub 2020/02/07. doi: 10.1162/jocn_a_01544.
PubMed PMID: 32027584.
38. Schrimpf M, Blank I, Tuckute G, Kauf C, Hosseini EA, Kanwisher N, et al. Artificial neural
networks accurately predict language processing in the brain. BioRxiv. 2020;10.1101/2020.06.26.174482.
39. Serre T. Deep Learning: The Good, the Bad, and the Ugly. Annual review of vision science.
2019;5:399-426. Epub 2019/08/09. doi: 10.1146/annurev-vision-091718-014951. PubMed PMID:
31394043.
40. Cichy RM, Khosla A, Pantazis D, Torralba A, Oliva A. Comparison of deep neural networks to
spatio-temporal cortical dynamics of human visual object recognition reveals hierarchical correspondence.
Scientific reports. 2016;6:27755. doi: 10.1038/srep27755. PubMed PMID: 27282108; PubMed Central
PMCID: PMC4901271.
41. Hong H, Yamins DL, Majaj NJ, DiCarlo JJ. Explicit information for category-orthogonal object
properties increases along the ventral stream. Nature neuroscience. 2016;19(4):613-22. Epub 2016/02/24.
doi: 10.1038/nn.4247. PubMed PMID: 26900926.
42. Zech JR, Badgeley MA, Liu M, Costa AB, Titano JJ, Oermann EK. Variable generalization
performance of a deep learning model to detect pneumonia in chest radiographs: A cross-sectional study.
PLoS Med. 2018;15(11):e1002683. Epub 2018/11/07. doi: 10.1371/journal.pmed.1002683. PubMed PMID:
30399157; PubMed Central PMCID: PMCPMC6219764 following competing interests: MAB and ML are
currently employees at Verily Life Sciences, which played no role in the research and has no commercial
interest in it. EKO and ABC receive funding from Intel for unrelated work.
43. Connolly AC, Guntupalli JS, Gors J, Hanke M, Halchenko YO, Wu YC, et al. The representation
of biological classes in the human brain. The Journal of neuroscience : the official journal of the Society for
Neuroscience. 2012;32(8):2608-18. Epub 2012/02/24. doi: 10.1523/JNEUROSCI.5547-11.2012. PubMed
PMID: 22357845; PubMed Central PMCID: PMCPMC3532035.
44. Sha L, Haxby JV, Abdi H, Guntupalli JS, Oosterhof NN, Halchenko YO, et al. The animacy
continuum in the human ventral vision pathway. Journal of cognitive neuroscience. 2015;27(4):665-78. doi:
10.1162/jocn_a_00733. PubMed PMID: 25269114.
45. Kanwisher N. Functional specificity in the human brain: a window into the functional architecture
of the mind. Proceedings of the National Academy of Sciences of the United States of America.
2010;107(25):11163-70. Epub 2010/05/21. doi: 10.1073/pnas.1005062107. PubMed PMID: 20484679;
PubMed Central PMCID: PMCPMC2895137.
46. Caramazza A, Shelton JR. Domain-specific knowledge systems in the brain the animate-inanimate
distinction. Journal of cognitive neuroscience. 1998;10(1):1-34. Epub 1998/05/02. PubMed PMID: 9526080.
47. Op de Beeck HP, Haushofer J, Kanwisher NG. Interpreting fMRI data: maps, modules and
dimensions. Nature reviews Neuroscience. 2008;9(2):123-35. Epub 2008/01/18. doi: 10.1038/nrn2314.
PubMed PMID: 18200027; PubMed Central PMCID: PMCPMC2731480.
48. Kanwisher N, McDermott J, Chun MM. The fusiform face area: a module in human extrastriate
cortex specialized for face perception. The Journal of neuroscience : the official journal of the Society for
Neuroscience. 1997;17(11):4302-11. PubMed PMID: 9151747.
49. Anzellotti S, Fairhall SL, Caramazza A. Decoding representations of face identity that are tolerant
to rotation. Cerebral cortex. 2014;24(8):1988-95. Epub 2013/03/07. doi: 10.1093/cercor/bht046. PubMed
PMID: 23463339.
50. Bracci S, Caramazza A, Peelen MV. View-invariant representation of hand postures in the human
lateral occipitotemporal cortex. NeuroImage. 2018;181:446-52. Epub 2018/07/24. doi:
10.1016/j.neuroimage.2018.07.001. PubMed PMID: 30033392.
51. Bracci S, Ietswaart M, Peelen MV, Cavina-Pratesi C. Dissociable neural responses to hands and
non-hand body parts in human left extrastriate visual cortex. Journal of neurophysiology. 2010;103(6):3389-
97. Epub 2010/04/16. doi: 10.1152/jn.00215.2010. PubMed PMID: 20393066; PubMed Central PMCID:
PMCPMC2888254.
52. Chang L, Tsao DY. The Code for Facial Identity in the Primate Brain. Cell. 2017;169(6):1013-28
e14. Epub 2017/06/03. doi: 10.1016/j.cell.2017.05.011. PubMed PMID: 28575666.
53. Proklova D, Goodale MA. The role of animal faces in the animate-inanimate distinction in the
ventral temporal cortex. bioRxiv. 2020;2020.10.08.330639.

54.   Dwivedi K, Cichy RM, Roig G. Unraveling Representations in Scene-selective Brain Regions Using Scene-Parsing Deep Neural Networks. Journal of cognitive neuroscience. 2020:1-12. Epub 2020/09/09. doi: 10.1162/jocn_a_01624. PubMed PMID: 32897121.

55.   Ganis G, Kutas M. An electrophysiological study of scene effects on object identification. Brain Res Cogn Brain Res. 2003;16(2):123-44. Epub 2003/04/02. doi: 10.1016/s0926-6410(02)00244-6. PubMed PMID: 12668221.

56.   Seijdel N, Jahfari S, Groen IIA, Scholte HS. Low-level image statistics in natural scenes influence perceptual decision-making. Scientific reports. 2020;10(1):10573. Epub 2020/07/01. doi: 10.1038/s41598-020-67661-8. PubMed PMID: 32601499; PubMed Central PMCID: PMCPMC7324621.

57.   Wischnewski M, Peelen MV. Causal Evidence for a Double Dissociation between Object- and Scene-Selective Regions of Visual Cortex: A Preregistered TMS Replication Study. The Journal of neuroscience : the official journal of the Society for Neuroscience. 2021;41(4):751-6. Epub 2020/12/03. doi: 10.1523/JNEUROSCI.2162-20.2020. PubMed PMID: 33262244; PubMed Central PMCID: PMCPMC7842759.

58.   Dilks DD, Julian JB, Paunov AM, Kanwisher N. The occipital place area is causally and selectively involved in scene perception. The Journal of neuroscience : the official journal of the Society for Neuroscience. 2013;33(4):1331-6a. Epub 2013/01/25. doi: 10.1523/JNEUROSCI.4081-12.2013. PubMed PMID: 23345209; PubMed Central PMCID: PMCPMC3711611.

59.   Geirhos R, Jacobsen JH, Michaelis C, Zemel R, Brendel W, Bethge M, et al. Shortcut learning in deep neural networks. Nat Mach Intell. 2020;2:665–73.

60.   Zhu Z, Xie L, Yuille A. Object Recognition with and without Objects. Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence. IJCAI 2017.

61.   Kubilius J, Bracci S, Op de Beeck HP. Deep Neural Networks as a Computational Model for Human Shape Sensitivity. PLoS computational biology. 2016;12(4):e1004896. doi: 10.1371/journal.pcbi.1004896. PubMed PMID: 27124699; PubMed Central PMCID: PMC4849740.

62.   Jozwik KM, Kriegeskorte N, Storrs KR, Mur M. Deep Convolutional Neural Networks Outperform Feature-Based But Not Categorical Models in Explaining Object Similarity Judgments. Frontiers in psychology. 2017;8:1726. Epub 2017/10/25. doi: 10.3389/fpsyg.2017.01726. PubMed PMID: 29062291; PubMed Central PMCID: PMCPMC5640771.

63.   Kalfas I, Kumar S, Vogels R. Shape Selectivity of Middle Superior Temporal Sulcus Body Patch Neurons. eNeuro. 2017;4(3). doi: 10.1523/ENEURO.0113-17.2017. PubMed PMID: 28660250; PubMed Central PMCID: PMC5485377.

64.   Beery S, Van Horn G, Perona P. Recognition in terra incognita. . In Proceedings of the European Conference on Computer Vision. 2018:456–73.

65.   Rosenfeld A, Zemel R, Tsotsos JK. The elephant in the room. . arXiv 2018;1808.03305

66.   Zeman AA, Ritchie JB, Bracci S, Op de Beeck H. Orthogonal Representations of Object Shape and Category in Deep Convolutional Neural Networks and Human Visual Cortex. Scientific reports. 2020;10(1):2453. Epub 2020/02/14. doi: 10.1038/s41598-020-59175-0. PubMed PMID: 32051467; PubMed Central PMCID: PMCPMC7016009.

67.   Kallmayer A, Prince J, Konkle T. Comparing representations that support object, scene, and face recognition using representational trajectory analysis. Journal of Vision. 2020.

68.   Dobs K, Kell A, Palmer I, Cohen MA, Kanwisher N. Why Are Face and Object Processing Segregated in the Human Brain? Testing Computational Hypotheses with Deep Convolutional Neural Networks. Cognitive Computational Neuroscience Conference, Berlin, Germany. 2019.

69.   Dobs K, Martinez J, Kell AJE, Kanwisher N. Brain-like functional specialization emerges spontaneously in deep neural networks. Sci Adv. 2022;8(11):eabl8913. Epub 2022/03/17. doi: 10.1126/sciadv.abl8913. PubMed PMID: 35294241; PubMed Central PMCID: PMCPMC8926347.

70.   Blauch NM, De Avila Belbute Peres F, Farooqui J, Zar AC, Plaut D, Behrmann M. Assessing the similarity of cortical object and scene representations through cross-validated voxel encoding models. Journal of Vision. 2019;Vol.19.

71.   Nguyen A, Yosinski J, Clune JD. Deep Neural Networks are Easily Fooled: High Confidence Predictions for Unrecognizable Images Computer Vision and Pattern Recognition (CVPR), IEEE. 2015.

72.   Tversky A, Kahneman D. Judgment under Uncertainty: Heuristics and Biases. Science. 1974;185(4157):1124-31. Epub 1974/09/27. doi: 10.1126/science.185.4157.1124. PubMed PMID: 17835457.

73.   Kriegeskorte N, Mur M. Inverse MDS: Inferring Dissimilarity Structure from Multiple Item
Arrangements. Frontiers in psychology. 2012;3:245. doi: 10.3389/fpsyg.2012.00245. PubMed PMID:
22848204; PubMed Central PMCID: PMC3404552.
74.   Op de Beeck HP. Against hyperacuity in brain reading: spatial smoothing does not hurt multivariate
fMRI analyses? NeuroImage. 2010;49(3):1943-8. doi: 10.1016/j.neuroimage.2009.02.047. PubMed PMID:
19285144.
75.   Krizhevsky A, Sutskever I, Hinton GE. ImageNet Classification with Deep Convolutional Neural
Networks. Advances in Neural Information Processing Systems 25. 2012.
76.   Simonyan K, Zisserman A. Very deep convolutional networks for large-scale image recognition.
arXiv. 2014;1409.1556.
77.   Szegedy C, Liu W, Jia Y, Sermanet P, Reed S, Anguelov D, et al. Going Deeper With Convolutions.
arXiv. 2015;1409.4842v1
78.   He K, Zhang X, Ren S, Sun J. Deep residual learning for image recognitio. IEEE Conference on
Computer Vision and Pattern Recognition (CVPR). 2016:770-8.
79.   Oosterhof NN, Connolly AC, Haxby JV. CoSMoMVPA: Multi-Modal Multivariate Pattern
Analysis of Neuroimaging Data in Matlab/GNU Octave. Frontiers in neuroinformatics. 2016;10:27. doi:
10.3389/fninf.2016.00027. PubMed PMID: 27499741; PubMed Central PMCID: PMC4956688.
80.   Lin T-Y, Maire M, Belongie S, Hays J, Perona P, Ramanan D, et al. Microsoft COCO: Common
Objects in Context. European Conference on Computer Vision (ECCV). 2014.
81.   Chen C, Liu MY, Tuzel O, Xiao J. R-CNN for Small Object Detection. Asian Conference on
Computer Vision. 2017.
82.   Zhou B, Lapedriza B, Khosla A, Oliva A, A. T. Places: A 10 million image database for scene
recognition.
. IEEE TPAM. 2017.
1041