1

Spatio-temporally efficient coding assigns functions to hierarchical structures of the visual system

Duho Sihn[1], Sung-Phil Kim[1]*

[1] Department of Biomedical Engineering, Ulsan National Institute of Science and Technology, Ulsan, 44919, Republic of Korea

* Corresponding author

E-mail: spkim@unist.ac.kr

Abstract

Hierarchical structures constitute a wide array of brain areas, including the visual system. One of the important questions regarding visual hierarchical structures is to identify computational principles for assigning functions that represent the external world to hierarchical structures of the visual system. Given that visual hierarchical structures contain both bottom-up and top-down pathways, the derived principles should encompass these bidirectional pathways. However, existing principles such as predictive coding do not provide an effective principle for bidirectional pathways. Therefore, we propose a novel computational principle for visual hierarchical structures as spatio-temporally efficient coding underscored by the efficient use of given resources in both neural activity space and processing time. This coding principle optimises bidirectional information transmissions over hierarchical structures by simultaneously minimising temporal differences in neural responses and maximising entropy in neural representations. Simulations demonstrated that the proposed spatio-temporally efficient coding was able to assign the function of appropriate neural representations of natural visual scenes to visual hierarchical structures. Furthermore, spatio-temporally efficient coding was able to predict well-known phenomena, including deviations in neural responses to unlearned inputs and bias in preferred orientations. Our proposed spatio-temporally efficient coding may facilitate deeper mechanistic understanding of the computational processes of hierarchical brain structures.

Keywords

Efficient coding, Hierarchical structure, Neural response, Neural representation, Receptive field,
Selectivity, Visual system.

1. Introduction

It is well-established that a wide array of brain areas has a hierarchical structure, including the visual
system (Felleman and Van Essen, 1991; Mesulam, 1998; Harris et al., 2019; Hilgetag and Goulas,
2020). Studies have identified a link between hierarchical structures and gene expression (Burt et
al., 2018; Hansen et al., 2021), suggesting that hierarchical structures are genetically determined *a*
priori. Given that one of the major functions of the brain is to represent the external world
(deCharms and Zador, 2000; Kriegeskorte and Diedrichsen, 2019), an ensuing question arises: How
do *a priori* hierarchical brain structures attain functions to represent the external world? This
question can be addressed by identifying a fundamental neural coding principle that assigns
representational functions to hierarchical structures.

The traditional view of the neural coding of visual hierarchical structures is bottom-up visual
information processing, whereby simple features are processed in a lower visual hierarchy and more
complex features created by integrating simple features are processed in a higher visual hierarchy
(Hubel and Wiesel, 1962; Hubel and Wiesel, 1968; Riesenhuber and Poggio, 1999; Riesenhuber and
Poggio, 2000; Serre et al., 2007; DiCarlo et al., 2012; Yamins et al., 2014). However, this view does
not consider the role of top-down pathways that are abundant even in the early visual system, such
as the lateral geniculate nucleus (Murphy and Sillito, 1987; Wang et al., 2006) and primary visual
cortex (Zhang et al., 2014; Muckli et al., 2015; Huh et al., 2018).

The role of top-down visual processing is especially prominent in predictive coding (Rao and Ballard,
1999; Spratling, 2017). According to predictive coding, a higher hierarchy performs top-down
predictions of neural responses in a lower hierarchy. Both inference and learning of predictive coding
are based on the minimisation of bottom-up prediction errors. Predictive coding has been used to
explain the neural responses corresponding to prediction errors (Friston, 2005) and extends from
the explanations of perception to action (Friston, 2010; Clark, 2013). A recent study combined
predictive coding with sparse coding (i.e., sparse deep predictive coding) and demonstrate that it
could enhance perceptual explanatory power (Boutin et al., 2021).

Nevertheless, predictive coding has several theoretical shortcomings. Since inference in predictive
coding aims to minimise prediction errors, the hierarchical structure would require an additional
information processing subsystem to perform this inference. In addition, because bottom-up

transmitted information contains only prediction errors, predictive coding requires the presence of error units (biological neurons) in the hierarchical structure to represent this prediction error, yet such error units remain as hypothetical entities and evidence for prediction error responses is limited in some conditions (Solomon et al., 2021).

In a hierarchical structure in which information is exchanged in both directions, if the information represented by the upper and lower hierarchies at the same time is different, it is difficult to obtain a stable neural response on time domain for an external input. The reason is that if the information represented by the upper and lower hierarchy are different, different information is exchanged, and thus the information represented next time may be also different. These inter-connected structures could also produce chaotic dynamics (Rubinov et al., 2009; Tomov et al., 2014). Nevertheless, neural responses in the early visual system can be decoded as external inputs. These decodable neural responses include both neuronal spikes (Berens et al., 2012; Zavitz et al., 2016) and blood-oxygen-level-dependent responses (Kamitani and Tong, 2005; Brouwer and Heeger 2009). Therefore, it is important to find neural coding principles that enable decodable stable neural representations in hierarchical structures on time domain.

Existing efficient coding (Attneave, 1954; Barlow, 1961; Laughlin, 1981) does not require additional information processing subsystems or virtual error units, which are shortcomings of predictive coding. Unfortunately, however, existing efficient coding does not consider hierarchical structures on the time domain. Many other ideas have been proposed for representation learning (Bengio et al., 2013). Properties of the visual cortex have been successfully studied using sparse coding (Olshausen and Field, 1996). Sparse coding has been successfully implemented using artificial neural networks such as restricted Boltzmann machines for representation learning (Goodfellow et al., 2011). However, these sparse coding studies have the disadvantage that they do not take into account the passage of time, which is an important aspect in the operation of the real brain. The hierarchical structure of the brain, which ascends to the upper hierarchy from the input by the bottom-up pathway and then descends to the input by the top-down pathway again, resembles the structure of autoencoders (Bourlard and Kamp, 1988; Hinton and Zemel, 1993) of artificial neural networks. A study to obtain slow representations change using temporal coherence was implemented using autoencoders (Zou et al., 2011). However, such studies using temporal coherence lack the aspect of dynamically reacting to changes in external input or neural responses of other hierarchies.

We, therefore, propose a novel computational principle for hierarchical structures as spatio-temporally efficient coding underscored by the efficient use of given resources in both neural activity space and processing time (Fig 1). By spatio-temporally efficient coding, neural responses change smoothly but dynamically. Spatio-temporally efficient coding in hierarchical structures can also be seen as an extension of efficient coding into hierarchical structures on time domain.

99   Spatio-temporally efficient coding enables rapid stabilization of neural responses and smooth
100   neural representations. Through simulations, these properties (smooth temporal trajectory of
101   neural responses, smooth neural representations, decodable stable neural responses; Fig 2, 3, and
102   4) and predictable phenomena (deviant neural response for unlearned inputs, orientation
103   preference bias; Fig 6, 7 and 8) were confirmed.

105   2. Materials and Methods

106   2.1. Spatio-temporally efficient coding

Predictive coding utilizes both bottom-up and top-down pathways to describe neural
representations in hierarchical structures in the brain. Nevertheless, predictive coding has several
theoretical shortcomings: 1) the hierarchical structure would require an additional information
processing subsystem to perform this inference to minimise the prediction error and 2) predictive
coding requires the presence of error units in the hierarchical structure to represent this prediction
error, yet such error units remain as hypothetical entities.

Existing efficient coding (Attneave, 1954; Barlow, 1961; Laughlin, 1981) does not require additional
information processing subsystems or virtual error units, which are shortcomings of predictive
coding. Unfortunately, however, existing efficient coding does not consider hierarchical structures.
We, therefore, propose a novel computational principle for visual hierarchical structures as spatio-
temporally efficient coding underscored by the efficient use of given resources in both neural activity
space and processing time. The derivation of spatio-temporally efficient coding is as follows.

A possible approach to overcome the shortcomings of both bottom-up processing and predictive
coding in visual hierarchical structures is to make bottom-up information transmissions similarly to
top-down information transmissions across hierarchies, instead of transmitting bottom-up
prediction errors. For example, context-independent bottom-up predictions and context-dependent
top-down predictions (Teufel and Fletcher, 2020). Such bidirectional information transmissions
eliminate the necessity for hypothetical error units, while presumably elucidating the neural
responses of hierarchical structures underlying bottom-up feature integration and top-down
predictive coding. A neural coding principle underlying bidirectional information transmissions of
hierarchical structures can be found in the theory of efficient coding that draws upon the efficient
use of given resources (Laughlin, 2001; Bullmore and Sporns, 2012), which crucially include limited
time resources related to processing speed (Griffiths et al., 2015; Lieder and Griffiths, 2020). A
possible solution to promote the most efficient use of limited time resources by the bidirectional
information transmission system is to render present neural responses similar to future ones before
the occurrence of future neural responses. This can be achieved by minimising the temporal

differences between present and future neural responses. Accordingly, we consider this temporal
difference minimisation as our *learning principle*, referred to as *temporally efficient coding*. Here,
inference simply refers to a bidirectional information transmission mediated by top-down and
bottom-up pathways. Unlike inference in predictive coding, which requires further error minimisation,
inference in temporally efficient coding involves simple single-step information transmission.

Temporally efficient coding involves a trivial solution: neural responses do not change to changes
in external events. This trivial solution is comparable to the dark-room problem of predictive coding
or free-energy principle, where an agent stays and is unchanged in a dark room with no surprise
or unpredicted parts (Friston et al., 2012; Clark, 2013). We circumvent this issue by adding a
complementary neural coding (learning) principle that maximises the informational entropy of
neural responses to alter neural responses to changing external events. It maximises the neural
response space available to represent the external world under the constraints of both the number
of neurons and maximum firing rates. Maximal entropy coding indicates that the system uses spatial
resources of neural responses efficiently (Attneave, 1954; Barlow, 1961; Laughlin, 1981), referred to
as *spatially efficient coding*. By combining spatially efficient coding and temporally efficient coding,
we propose a neural coding principle termed *spatio-temporally efficient coding* (Fig 1).

Spatially efficient coding has the same objective as existing efficient coding (Barlow, 1961; Laughlin,
1981), which minimizes informational redundancy because it increases the difference between neural
responses. Temporally efficient coding, on the other hand, can be regarded to increase informational
redundancy, as it reduces the difference between neural responses. Two seemingly opposing coding
objectives can be reconciled by isolating mechanisms that decrease the differences between
consecutive neural responses on time domain and those that increase the differences between
neural responses to the apparently different external world. In the real brain, it can be explained
that different mechanisms are applied depending on the degree of difference in neural response.
In the implementation of the present study, two coding objectives were applied in different ways.
As an implementation of temporally efficient coding, we minimize the difference between
consecutive neural responses on the time. In spatially efficient coding, the neural responses to the
apparently different external stimuli are implemented in a minibatch method that simultaneously
learns different images. We maximized the difference between neural responses to different images
within each time step (see, Implementation of spatio-temporally efficient coding).

Temporally efficient coding trains the present neural response to be similar to the future neural
response in order to efficiently use a given time resource. The temporal trajectory of the neural
response is smoothed as the difference between the present and future neural responses is
minimised. It thereby minimises the size of the space represented, when a single stimulus (stimulus
in the external world) is represented on the time domain. In other words, it reduces neuronal noise

(also see, Fig 2C) which is defined as the uncertainty of a neural response for given stimulus (Borst
and Theunissen, 1999). This is to decrease the conditional entropy of neural response given stimulus,
$H(X|S)$ where X indicates neural response and S indicates stimulus. Spatially efficient coding
increases $H(X)$. Spatio-temporally efficient coding, thus, increases the Shannon mutual information
$I(X;S) = H(X) - H(X|S)$ simultaneously in both terms: $H(X)$ and $-H(X|S)$. This is also the
definition of another existing efficient coding (Friston, 2010). Spatio-temporally efficient coding in
hierarchical structures, therefore, can also be seen as an extension of efficient coding into
hierarchical structures on time domain.

Neural system homeostasis is associated with maximisation of mutual information between neural
responses and external stimuli (Toyoizumi et al., 2005; Sullivan and de Sa, 2006). Since spatio-
temporally efficient coding increases the Shannon mutual information between neural responses
and external stimuli, it is related to homeostasis. In particular, temporal difference minimisation of
neural responses in temporally efficient coding is reminiscent of homeostasis of energy metabolism.
Smoothing the temporal trajectory of a neural responses reduces the variance of the neural response
distribution so that the neural response stays within a certain range. This is also a consequence of
the homeostatic plasticity (Turrigiano and Nelson, 2004) of the brain (also see, Fig 5).

As mentioned earlier, smoothing the temporal trajectories of neural responses reduces the spatial
extent of neural responses to static stimuli. This leads to a rapid stabilization of the neural response
to the static stimulus (also see, Fig 2C and 4). The rapid stabilization of neural responses shows the
characteristic of temporally efficient coding, which makes efficient use of given time resources.
Another effect of this smoothing the temporal trajectory of neural response is to render smooth
neural representations that locally preserves the structure of the external world. If a stimulus is static
or changes smoothly, making the temporal trajectory of the neural response smooth is to render a
similar neural response to the similar stimuli. This is smooth neural representations that locally
preserves the structure of the external world (also see, Fig 3).

Fig 1. Spatio-temporally efficient coding. (A) This illustration depicts a hierarchical structure of the brain. Open black circles indicate an ensemble of neuronal units in each hierarchy of the brain. Open black square indicates visual input. Back arrows indicate information transmissions of bottom-up (upward arrow), recurrent (loop arrow), and top-down (downward arrow). (B) This illustration depicts a hierarchical structure of the brain and learning objectives. The hierarchical structure learns to represent input from the external world, which is depicted as black squares (e.g., visual input). Open black circles indicate an ensemble of neuronal units in each hierarchy of the brain. Inference based on spatio-temporally efficient coding is made by neuronal units as bottom-up, recurrent, and top-down information transmissions over time (black arrows). Learning in spatio-temporally efficient coding consists of two objectives: minimising the temporal differences between present and future neural responses and maximising the informational entropy of neural responses. For example, information transmissions (purple arrows) are optimised to minimise the temporal differences between present neural responses at the corresponding hierarchy (red filled circle) and future neural responses (circle to the right of the red filed circle) while concurrently maximising the informational entropy of neural responses at the corresponding hierarchy (red filled circle).

2.2. Relation to other works

Existing efficient coding (Attneave, 1954; Barlow, 1961; Laughlin, 1981) is a widely accepted coding principle. However, existing efficient coding does not consider hierarchical structures. Spatio-temporally efficient coding started with a different kind of assumption from the existing efficient coding that given resources are used efficiently. However, spatio-temporally efficient coding can be seen as an extension of efficient coding to hierarchical structures. As mentioned previously, temporally efficient coding decreases the conditional entropy of neural response given stimulus, $H(X|S)$ where X indicates neural response and S indicates stimulus. Spatially efficient coding increases $H(X)$. Spatio-temporally efficient coding, thus, increases the Shannon mutual information $I(X;S) = H(X) - H(X|S)$ simultaneously in both terms: $H(X)$ and $-H(X|S)$. This is also the definition of another existing efficient coding (Friston, 2010). Since spatio-temporally efficient coding can be applied to a hierarchical structure, spatio-temporally efficient coding can be viewed as an extension of efficient coding to hierarchical structures on time domain.

It is noteworthy that minimising temporal differences in upper hierarchies may, at first glance, be reminiscent of the slow feature analysis (Wiskott and Sejnowski, 2002; Berkes and Wiskott, 2005; Creutzig and Sprekeler, 2008). However, the upper hierarchies of the proposed spatio-temporally efficient coding need to change dynamically to react rapidly changing visual inputs and neural responses of the lower hierarchies, whereas the upper hierarchies of the slow feature analysis need to change slowly. Minimising temporal differences in spatio-temporally efficient coding does

not aim at extracting slow features, but rather aim at the smooth representation of rapidly

changing visual inputs with stabilizing neural responses as quickly as possible.

The hierarchical structure of the brain, which ascends to the upper hierarchy from the input by the

bottom-up pathway and then descends to the input by the top-down pathway again, resembles

the structure of autoencoders (Bourlard and Kamp, 1988; Hinton and Zemel, 1993) of artificial neural

networks. Objective functions of spatio-temporally efficient coding applied to the hierarchical

structure for neural representations can be viewed as a kind of objective function applied to

autoencoders. Many autoencoders have also been used for representation learning (Bengio et al.,

2013). Typical examples include sparse autoencoders (Ranzato et al., 2006), denoising autoencoders

(Vincent et al., 2008), and contractive autoencoders (Rifai et al., 2011). However, these examples do

not take into account the passage of time like spatio-temporally efficient coding. Similar to slow

feature analysis, there have been studies on the properties of cells in the visual cortex using temporal

coherence to obtain slow representations (Hurri and Hyvärinen, 2002; Zou et al., 2011). In particular,

one of these studies has been conducted using models that partially include autoencoders (Zou et

al., 2011). However it is different from spatio-temporally efficient coding in that it lacks an aspect

of dynamically reacting to changes in external input or neural responses of other hierarchies, and

only partially includes autoencoders.

248   2.3. Implementation of spatio-temporally efficient coding

In the present study, visual information processing in hierarchical structures was established as

biologically inspired temporal processing. Specifically, visual information processing is described as

a function f_t for both image X_{image} and neural responses X_h in each hierarchy h such that it

maps from X_{image} and X_h at time $t-1$ to those at time t:

$f_t: X_{image,t-1} \times X_{h=1,t-1} \times \dots \times X_{h=H,t-1} \to X_{image,t} \times X_{h=1,t} \times \dots \times X_{h=H,t}$ (1)

where $X_{h,t-1}$ and $X_{h,t}$ are the neural responses X_h at time $t-1$ and t, respectively, at hierarchy

h. For convenience, $X_{h=0}$ denotes X_{image}, in particular $X_{h=0,t}$ denotes the image presented at time

t. The details of the visual information processing f_t are as follows: If $h > 0$, then

$f_t|_{X_{h,t}} = \sigma\left(W_{h+1,h}^T X_{h+1,t-1} + W_{h,h}^T X_{h,t-1} + W_{h-1,h}^T X_{h-1,t-1} + b_h\right)$ (2)

where $X_{h,t}$ is an X_h value vector at time t, $f_t(\cdot)|_{X_{h,t}}$ indicates restricting the range of the function

value $f_t(\cdot)$ to $X_{h,t}$, $W_{h+1,h}$ is a synaptic weight matrix from hierarchy $h+1$ to h, T is the transpose

of a matrix, b_h is a bias vector at hierarchy h, and $\sigma(\cdot)$ is a sigmoid function. The terms of

$W_{h+1,h}^T X_{h+1,t-1}$, $W_{h,h}^T X_{h,t-1}$, and $W_{h-1,h}^T X_{h-1,t-1}$ indicate top-down, recurrent, and bottom-up

information transmissions, respectively. In case of $h+1 > H$ the $W_{h+1,h}^T X_{h+1,t-1}$ term would be

omitted. If $h = 0$, then

$$f_t|_{X_{h,t}} = \sigma\big(W_{h+1,h}^T X_{h+1,t-1} + b_h\big). \tag{3}$$

If $h > 0$, $X_{h,t} = f_t|_{X_{h,t}}$. On the other hand, when $h = 0$, $X_{h,t}$ is the image presented at time t, not

$f_t|_{X_{h,t}}$. This function f_t makes *inferences* using spatio-temporally efficient coding. Unlike inference

in predictive coding (Rao and Ballard, 1999; Spratling, 2017) that requires additional processes such

as minimisation of prediction errors, inference in spatio-temporally efficient coding is a function

value f_t itself.

Learning in spatio-temporally efficient coding minimises the ensuing objectives of both temporally

and spatially efficient coding. The objective of temporally efficient coding is given by:

$$L_{Temporal} = \sum_{n=1}^{N} \Big(f_t \circ f_{t-1}\big(x_{h=0,\tilde{t},\text{image}=n}\big) - f_{t+1} \circ f_t \circ f_{t-1}\big(x_{h=0,\tilde{t},\text{image}=n}\big)\Big)^2 \tag{4}$$

where $\circ$ is the function composition, $x_{h=0,\tilde{t},\text{image}=n}$ indicates that the image is fixed to the nth

sample throughout the temporal processing (i.e., $X_{h=0,t-2} = X_{h=0,t-1} = X_{h=0,t}$ is nth image sample),

squaring is operated component-wise. In case of $h = 0$, $f_{t+1} \circ f_t \circ f_{t-1}\big(X_{h=0,\tilde{t},\text{image}=n}\big)|_{X_{h=0}} := X_{h=0,t+1}$

which is the image presented at time $t + 1$ while $f_t \circ f_{t-1}\big(x_{h=0,\tilde{t},\text{image}=n}\big)|_{X_{h=0}}$ is the function value

as inference. The function composition $f_t \circ f_{t-1}$ of two functions (inferences) in the $L_{Temporal}$ allows

the simultaneous learning of all information transmissions across all hierarchies because the depth

of hierarchy is $H = 2$ in the present study (bottom-up, recurrent, and top-down information

transmission across the hierarchy of depth $H = 2$). The minimisation of the given objective

minimises the temporal differences between present and future neural responses. The objective of

temporally efficient coding is to render present neural responses similar to future neural responses

that has not yet arrived. By doing so, it uses the given time resources efficiently. This minimisation

of temporal difference creates a learning effect in which the temporal trajectory of the neural

response becomes smooth. The expected effect of this learning effect is to quickly stabilize neural

responses when a static external stimulus is given (also see, Fig 2C and 4). In that aspect, it is also

to use the given time resources efficiently.

The objective of spatially efficient coding is given by

$$L_{Spatial} = \sum_{n=1}^{N} \log P\big(f_t\big(x_{h=0,\tilde{t},\text{image}=n}\big)|_{X_h}\big) \tag{5}$$

Where $h > 0$ in X_h (so, $f_t\big(X_{h=0,\tilde{t},\text{image}=n}\big)|_{X_h} = X_{h,t}$) and $P(\cdot)$ is a probability. Because the term

$L_{Spatial}$ is an estimation of negative informational entropy, minimising the objective maximises the

informational entropy of f_t. This objective increases the entropy of each neuron, and it can be seen

that an increase in marginal entropy in each neuron will increase the joint entropy of the entire

system. Therefore, spatially efficient coding maximises the entropy of individual neurons as in

Laughlin's study (Laughlin, 1981) and consequently the entropy of the entire system. The objective

of spatially efficient coding is to render different neural responses to different inputs from the

external world. We, therefore, can overcome the trivial solution of temporally efficient coding, where

there is no change in neural response despite changes in the external world. This thereby does not

conflict with the learning of temporally efficient coding, which decreases differences in consecutive

neural responses in the time domain to inputs of one stream.

To minimise $L_{Spatial}$, which is the objective of spatially efficient coding, it is necessary to calculate

the probability $P(\cdot)$ in $L_{Spatial}$ (equation 5). Instead of calculating the exact probabilities, we

obtained pre-normalised densities in the sense of probabilities without a partition function. As the

value of the partition function is fixed, it does not affect the minimisation process. Note that, when

$h > 0$, $X_{h,t}$ is the space of all possible neural responses, i.e., $X_{h,t} = [0,1]^{\dim X_{h,t}}$. Let $x \in X_{h,t}$ be a

value of $f_t(x_{h=0,\tilde{t},\text{image}=n})|_{X_h}$. Kernel density estimation was used to obtain $P(x)$. Using a Gaussian

kernel with width $0.1(\dim X_{h,t})^{1/2}$, the neural response density $Q(x)$ and compensation density

$Q'(x)$ at $x \in X_{h,t}$ were obtained. Then, the pre-normalised density of interest is

$$P(x) = \frac{Q(x)}{Q'(x)}. \tag{6}$$

The neural response density $Q(x)$ is obtained by kernel density estimation of neural responses on

$X_{h,t}$. The compensation density $Q'(x)$ is obtained using pseudo-uniformly generated samples on

$X_{h,t}$ instead of the neural responses. (For sparseness constraint, i.e., sparse neural responses, $Q'(x)$

is obtained using pseudo-uniformly generated samples on $[-1,1]^{\dim X_{h,t}}$ instead of $X_{h,t} =$

$[0,1]^{\dim X_{h,t}}$, so that $Q'(x)$ has a fat distribution around zero. See, Fig 6) The compensation density

is necessary to compensate for the non-uniform intrinsic expectation of $Q(\cdot)$ resulting from the fact

that $X_{h,t}$ is bounded. At the boundary of $X_{h,t}$, the density of neural responses, $Q(x)$, measured by

kernel density estimation is decrease. This intrinsic decrease corresponds to $Q'(x)$. We compensated

for the decrease by dividing $Q(x)$ by $Q'(x)$.

Finally, the objective of spatio-temporally efficient coding is a linear combination of those two

objectives:

$$L = L_{Temporal} + \lambda L_{Spatial} \tag{7}$$

where λ is a regularisation parameter. A smaller λ indicates a greater emphasis on the temporally

efficient coding objective, whereas a larger λ indicates the opposite. As mentioned previously,

temporally efficient coding decreases the conditional entropy of neural response given stimulus,

$H(X|S)$ where X indicates neural response and S indicates stimulus. Spatially efficient coding

increases $H(X)$. Hence, the regularisation parameter λ can be seen as controlling the balance

between $H(X)$ and $-H(X|S)$. It is a modification of fixed balance of Shannon mutual information

$I(X;S) = H(X) - H(X|S)$ of the existing efficient coding (Friston, 2010).

Temporal trajectories of neural responses are smoothed by temporally efficient coding, but this does
not mean just slow neural representations. By spatially efficient coding, different neural responses
to different inputs from the external world should be exhibited. Therefore, it should show rapid
changes in neural responses to sudden changes in the external world (fast representation). This is
the difference from slow feature analysis (Wiskott and Sejnowski, 2002; Berkes and Wiskott, 2005;
Creutzig and Sprekeler, 2008) or temporal coherence (Hurri and Hyvärinen, 2002; Zou et al., 2011),
which targets slow neural representations. On the one hand, with temporally efficient coding,
changes in neural responses should be smoothed out quickly when the external input is not
changing (fast stabilization).

Suppose that Gaussian noise is added to a series of temporally correlated external inputs (e.g., static
images or smoothly moved images + Gaussian noise). If these noisy external inputs are still
temporally correlated, then smoothing the temporal trajectory of neural responses (by temporally
efficient coding objective $L_{Temporal}$) is rendering temporally similar neural responses to temporally
similar inputs. It is also smooth neural representations that locally preserves the structure of the
external world. Moreover, if the noise is provided independently of the input, the effect of the noise
on neural representations will be dispelled by multiple independent trials. Therefore, temporally
efficient coding objective $L_{Temporal}$ increases the fidelity of the neural representation with respect
to a Gaussian noise.

Smooth neural representation also means making different neural responses to different inputs. In
other words, it increases discriminability for different inputs. This is achieved by spatially efficient
coding objective $L_{Spatial}$ that maximises the entropy of neural responses. Assumed that Gaussian
noise is added to external inputs. Let D_{true} be a binary-valued random variable for the
discrimination between two actually different inputs such that $D_{\text{true}} = 1$ means the discrimination
that two noised inputs differ and $D_{\text{true}} = 0$ means the discrimination that two noised inputs are
same. D_{true} is probabilistic because of the Gaussian noise mentioned earlier. Let D_{response} be a
binary-valued random variable for the discrimination between two neural responses for inputs such
that $D_{\text{response}} = 1$ means the discrimination that two neural responses differ and $D_{\text{response}} = 0$
means the discrimination that two neural responses are same. Let P_{true} and P_{response} be the
probability mass functions of D_{true} and D_{response}, respectively. Spatially efficient coding objective
$L_{Spatial}$ decreases the Kullback–Leibler divergence from P_{response} to P_{true}, i.e., $D_{\text{KL}}(P_{\text{true}}||P_{\text{response}})$.
Hence it also decreases the binary cross entropy $H(P_{\text{true}}) + D_{\text{KL}}(P_{\text{true}}||P_{\text{response}})$ where $H(\cdot)$ is an
informational entropy.

In the present study, the depth H of hierarchies was set to 2, the minimum depth to realise both
bottom-up and top-down pathways in the same hierarchy. Images with 64×96 size were divided
into four overlapping 38×58 patches. Each patch was connected to 16 of 64 lower hierarchy units.

Further, 64 lower hierarchy units were fully connected to 64 upper hierarchy units. All units in each
hierarchy are fully connected to each other (Fig 2A).

Because $L = L_{Temporal} + \lambda L_{Spatial}$ is differentiable, the minimisation of the objective in spatio-
temporally efficient coding was performed with a gradient descent. The Adam optimiser (Kingma
and Ba, 2015) was used to perform the stochastic gradient descent with momentum. The parameters
of the Adam optimiser used in this study were $\alpha = 0.001$, $\beta_1 = 0.9$, $\beta_2 = 0.999$, and $\epsilon = 10^{-8}$. The
optimisation lasted 10^4 iterations for each repetition and restarted with five repetitions. For each
iteration, the duration of temporal processing f_t was five (i.e., $t \in [1,5]$), and the minibatch size was
40. For a given image, the duration of temporal processing of f_t was given as five (i.e., $t \in [1,5]$) in
both learning and inference, because four time steps are required for the image information to
reach the top hierarchy and return over $H = 2$ hierarchies, in addition to one time step to obtain
future neural responses. In learning, after temporal processing of five durations was finished, new
temporal processing begins, and the initial values of neural responses of new temporal processing
were the last neural responses values of the previous temporal processing.In our simulations, we
repeatedly exposed the hierarchical structure to natural scene images, which enabled it to learn the
bidirectional information transmissions between top-down and bottom-up hierarchies using spatio-
temporally efficient coding with a range of the balancing parameter λ. Successful learning was
confirmed by minimising or stabilising L during learning. Further, we verified that the learned
hierarchical structure could successfully reconstruct an input image, as shown in Fig 2C.

Simulation codes for spatio-temporally efficient coding are available from
https://github.com/DuhoSihn/Spatio-temporally-efficient-coding (Sihn, 2021).

2.4. Datasets

For the simulations, van Hateren's natural scene image dataset (van Hateren and van der Schaaf,
1998) was used. The dataset was downloaded from http://bethgelab.org/datasets/vanhateren/. The
images were downsized to 64×96 pixels. For the comparison tests, the MNIST handwritten digit
dataset (Lecun et al., 1998) was used. The dataset was downloaded from
http://yann.lecun.com/exdb/mnist/. The images were resized to 64×96 pixels to fit the images
used in the simulations. All image data were rescaled between 0 and 1.

2.5. Computation of receptive fields

Images of 64×96 size with randomly selected 16×16 subregions were created to compute the
receptive field. These 64×96 images had a value of one in the 16×16 subregions and zero

otherwise. Receptive fields were calculated based on the average neural response when the visual
hierarchy $(X_{h=1} \times \dots \times X_{h=H})$ was exposed to these images. Specifically, the value of the receptive
field at a pixel was defined as the average neural response to an image with a value of one at this
pixel. This averaging method was inspired by the previous study in case of binary neural responses
(firing or not) (Ohzawa et al., 1996). The difference is that the previous study was for image averaging
and the present study was for neural response averaging.

3. Results

3.1. Balancing between temporally and spatially efficient coding

The temporally efficient coding objective that minimises the temporal difference between present
and future neural responses smooths the temporal trajectory of neural responses. The spatially
efficient coding objective that maximises the informational entropy of neural responses renders
different neural responses to different inputs. We can predict that when the temporally efficient
coding objective and the spatially efficient coding objective are properly balanced, different neural
responses to different stimuli and temporally smooth neural responses to the same stimuli can be
expected. This means that when the external input changes, the neural response changes quickly,
and when the external input does not change, the neural response quickly stabilizes. If the
temporally efficient coding objective is overweighted, it can be predicted to arrive at a trivial solution
in which the neural response does not change despite changes in external input. Conversely, if the
spatially efficient coding objective is overweighted, it can be predicted that the temporal trajectory
of the neural response is not smooth, resulting in neuronal noise. Three regularisation parameters
$\lambda \in \{0, 10, 1000\}$ were used to confirm these predictions through simulations. $\lambda = 10$ represents a
balanced condition between the temporally efficient coding objective and the spatially efficient
coding objective (STEC condition). $\lambda = 0$ represents an overweighted condition for the temporally
efficient coding objective (TEC condition). $\lambda = 1000$ represents an overweighted condition for the
spatially efficient coding objective (SEC condition). This control condition (SEC condition) is a
condition in which only the spatially efficient coding objective is considered, and represents the
existing efficient coding (Barlow, 1961; Laughlin, 1981). Sparse coding (Olshausen and Field, 1996;
Olshausen and Field, 1997) was chosen to compare with other neural coding principles where
temporal factors were not considered. The sparseness constraint (see, Implementation of spatio-
temporally efficient coding) is applied to $\lambda = 1000$ to implement sparse coding (Sparse condition).

Based on the simulation, we confirmed this phenomenon by observing that, under STEC condition
($\lambda = 10$), when the external input changes, the neural response changes rapidly, and when the
external input does not change, the neural response quickly stabilizes. In addition, we confirmed

that under TEC condition ($\lambda = 0$, control), we arrive at the trivial solution in which the neural response
does not change even when the external input changes. We also confirmed that under SEC condition
($\lambda = 1000$) and Sparse condition ($\lambda = 1000$ + sparseness constraint), the temporal trajectory of the
neural response is not smooth, resulting in neuronal noise (Fig 2C). This also shows the problem of
applying existing efficient coding (Barlow, 1961; Laughlin, 1981) and sparse coding (Olshausen and
Field, 1996; Olshausen and Field, 1997) directly to the hierarchical structure on time domain.

A change in balance between the two objectives also altered the relative strengths between bottom-
up and top-down synaptic connections. Simulation results demonstrated that top-down synaptic
strengths from upper to lower hierarchy were increased compared to bottom-up synaptic strengths
from images to lower hierarchy as λ increased, with an emphasis on spatially efficient coding (Fig
2B, see Materials and Methods section for details on the computation of synaptic strength). This
finding suggests that the balance between spatially and temporally efficient coding could be related
to the balance between bottom-up and top-down synaptic strengths in the brain.

Fig 2. A simulation of spatio-temporally efficient coding. (A) Architecture of the simulation model. An input image is divided into four subspaces with overlaps, denoted by different colours. A subset of neuronal units in lower hierarchy receive corresponding parts of the image (matching colours). There is no spatial correspondence between lower and upper hierarchies. Pink, magenta, and purple arrows indicate bottom-up, recurrent, and top-down information transmissions, respectively. (B) The magnitude of synaptic weights on lower hierarchy units is compared for different conditions, where STEC: the balanced condition between temporally and spatially efficient coding objectives, TEC: temporally efficient coding alone, SEC: spatially efficient coding alone which is existing efficient coding, Sparse: sparse coding. Each cross indicates the L2 norm of synaptic weights for each unit. Black squares indicate the mean. (C) Left: Four different original input images and their

reconstructions from the neuronal responses of lower hierarchy. Right: Representative neural responses for different conditions. The neural response is the output of the sigmoid function and is therefore normalised to a range between 0 and 1.

3.2. Smooth neural representations of the external world

As a major function of the brain is to represent the external world (deCharms and Zador, 2000; Kriegeskorte and Diedrichsen, 2019), we investigated whether spatio-temporally efficient coding creates appropriate neural representations of the external world. Spatio-temporally efficient coding smooths the temporal trajectory of neural responses while having different neural responses to different external inputs. This effect renders smooth neural representations that locally preserves the structure of the external world. We quantified the smoothness of neural representations by examining the correlations between a natural scene image space and a neural response space. Specifically, we first measured the global feature based distance (Di Gesù and Starovoitov, 1999) from a natural scene image (i.e., reference image) to other natural scene images in the image space and the Euclidean distances from the neural responses for the reference image to those for other compared images in the neural response space (Fig 3A). It has been proven that global feature based distance reflects differences in images in a way that humans actually perceive (Di Gesù and Starovoitov, 1999). When calculating the distances between neural responses, we used the neural responses at five time steps after receiving a given image based on the assumption that the neural responses became temporally steady after five steps of temporal processing (see Fig 1B). We then measured the Pearson's linear correlation between the distances in the image space and those in the neural response space. A high correlation indicates that neural responses tend to be similar when the visual system perceives natural scenes close to each other (in the sense of global feature based distance). We set each image sample as a reference and repeated the calculations for the correlation across all image samples. We defined local similarity as the average correlation obtained by using the distances from one image to its neighbouring images only (1% of all images). We also measured discriminability as the proportion of dissimilar neural responses among dissimilar images. This dissimilarity was defined as 99% of all, based on certain distances (the global feature based distance for images, the Euclidean distance for neural responses). A high discriminability indicates that if the image is different, the neural response will also be different.

If the learned neural representations are smooth, i.e. locally preserving the structure of the external world, both local similarity and discriminability will be high. We can predict that when the temporally efficient coding objective and spatially efficient coding objective are balanced (STEC condition), neural representations are smooth, so that local similarity and discriminability are high. From the simulations, we confirmed that local similarity and discriminability do not lower in STEC condition

490   than SEC or Sparse condition (Fig 3B and 3C).

Fig 3. Smooth neural representations of visual images by spatio-temporally efficient coding.
(A) Examples of relative Euclidean distances from the reference image (Ref. left) to other images in
the natural scene image space are depicted on the horizontal axis. Relative Euclidean distances from
the neural representations of the reference image at hierarchy 1 to those of corresponding other
images are depicted on the vertical axis. (B) Local similarity based on correlations of distances
between overall natural scene images (N = 42 out of 4212; 1%) (global feature based distance) with
those of corresponding neural responses (Euclidean distance). Error bars indicate standard deviations.
(C) Discriminability of neural responses for images (N = 4170 out of 4212; 99%). Three horizontal
lines in each box indicates 25 %, 50 %, and 75 % levels of data, respectively.

3.3. Decodable stable neural representations

In a hierarchical structure in which information is exchanged in both directions, if the information
represented by the upper and lower hierarchies at the same time is different, it is difficult to obtain
a stable neural response on time domain for an external input. The reason is that if the information
represented by the upper and lower hierarchy are different, different information is exchanged, and
thus the information represented next time may be also different. These inter-connected structures
could also produce chaotic dynamics (Rubinov et al., 2009; Tomov et al., 2014).

The objective of temporally efficient coding is to render present neural responses similar to future
neural responses that has not yet arrived. This minimisation of temporal difference creates a learning
effect in which the temporal trajectory of the neural response becomes smooth. It thereby minimises
the size of the space represented, when a single stimulus is represented on the time domain. In
other words, it reduces neuronal noise which is defined as the uncertainty of a neural response for
given stimulus (Borst and Theunissen, 1999). The expected effect of this learning effect is to quickly
stabilize neural responses when a static external stimulus is given. The objective of spatially efficient
coding is to render different neural responses to different stimuli. The expected effect of spatio-
temporally efficient coding is to render decodable stable neural representations which is an
appropriate function to hierarchical brain structures on the time domain.

As a result of the simulation, different neural responses to different stimuli were shown in the STEC
condition, and these neural responses were rapidly stabilized. On the other hand, neural responses
were less stabilized under SEC and sparse conditions (Fig 4A). The factor affecting the stabilization
of the neural response was the amount of neuronal noise. To quantify the amount of neural noise,
conditional entropy of neural responses given stimulus was measured. Conditional entropy was
measured by collecting neural responses at every five time step. Probability was estimated by kernel
density estimation without a partition function, and thus shifted conditional entropy was measured.
The STEC condition showed lower neuronal noise than the SEC and Sparse conditions (Fig 4B).

We measured how much this neuronal noise makes to confuse the neural response to one stimulus
with the neural response to another similar stimulus. This is represented by the confusion index.
Here, we set the time step to 10 and measured the variability in neural responses from time step 1
(i.e., when receiving an input image) to time step 9 until convergence. Temporal variations were
computed using the Euclidean distance from the neural responses at each time step (1, …, 9) to
neural responses at time step 10. We also computed the Euclidean distance from the neural
responses at time step 10 and those for an image that was the nearest to the given image in the
image space. We compared the temporal variations above with this distance to the nearest
neighbouring image by calculating the ratio of the temporal variations over the distance to the
nearest neighbouring image. This ratio was called the confusion index. The confusion index exceeds

1 indicates that the noise could significantly interfere with neural representations to be confused

with nearby images. Under STEC condition, the confusion index was kept below 1 on average for

the majority of time steps at each hierarchy (Fig 4C). This means that the neural representations are

rapidly stabilized in STEC condition. On the other hand, the confusion index was not sufficiently

reduced in SEC and Sparse condition (Fig 4C). This means that sufficient stabilization of neural

representations is difficult with only existing efficient coding or sparse coding.

To measure how decodable the neural response is, the neural responses of time steps 1, …, 9 were

decoded using the neural responses of time steps 10 and 11 as a training set. The naïve Bayes

classifier (Hastie et al., 2009) was selected as the decoder, and each of the 4212 natural scene

images was defined as one class. In the STEC condition, the decoding accuracy gradually increased

over time, suggesting decodable stable neural representations. On the other hand, the decoding

accuracy was low in SEC and Sparse conditions.

Fig 4. Decodable stable neural representations via spatio-temporally efficient coding. (A) Examples of neural responses in the lower hierarchy. These were neural responses of 3rd units in Fig 2C. Dotted vertical black lines indicate the presentations of new external input. (B) Neuronal noise that measured as shifted conditional entropy of neural responses given stimulus. Conditional entropy was measured by collecting neural responses at every five time step. (C) Confusion index that a measure of how much it confuses neural responses to one stimulus with neural responses to another similar stimulus. The dotted lines denote the confusion index of 1 which indicates the confusion. Error bars indicate standard deviations. (D) Decoding accuracy via the naïve Bayes classifier. The upper dotted line denotes the maximum decoding accuracy, 1. The lower dotted line denotes the chance level, 1/4212. Error bars indicate standard deviations.

3.4. Relation to homeostasis

Neural system homeostasis is associated with maximisation of mutual information between neural responses and external stimuli (Toyoizumi et al., 2005; Sullivan and de Sa, 2006). Since spatio-temporally efficient coding increases the Shannon mutual information between neural responses and external stimuli, it is related to homeostasis. In particular, temporal difference minimisation of neural responses in temporally efficient coding is reminiscent of homeostasis of energy metabolism. Smoothing the temporal trajectory of a neural responses reduces the variance of the neural response distribution so that the neural response stays within a certain range. We confirmed this through simulation. In STEC condition emphasizing temporally efficient coding objective, neural responses were concentrated at the middle value than in SEC condition (Fig 5). This is also a consequence of the homeostatic plasticity (Turrigiano and Nelson, 2004) of the brain.

Fig 5. Neural response distributions. (A) Examples of natural scene images. (B) Examples of neural

577   response distributions of lower hierarchy units for each of the five time steps of bidirectional

578   information transmissions, corresponding to images in (A). The colour scale indicates the proportion.

579   (C) Overall neural response distributions in response to all input images (either STEC or SEC) at

580   lower and upper hierarchies, respectively.

582   3.5. Deviant neural responses to unlearned inputs

The visual system often responds selectively to sensory inputs (Margoliash, 1983; Waydo et al., 2006).

Even for the type of sensory inputs to which the visual system is responsive, unfamiliar inputs induce

larger neural responses compared to familiar inputs (Huang et al., 2018; Issa et al., 2018). These

large neural responses to unfamiliar inputs are thought to be due to prediction errors (Issa et al.,

2018). On the one hand, spatio-temporally efficient coding renders smooth neural representations,

i.e., locally preserving the structure of the external world. Because unlearned inputs differ from

learned inputs, if their neural representations are smooth, their neural representations will also differ.

These are deviant neural responses to unlearned inputs. Accordingly, we can expect that spatio-

temporally efficient coding could predict the phenomenon of deviant neural responses to unlearned

inputs without the introduction of prediction error responses mediated by error units.

In the simulations, the visual hierarchical structure learned to be learned with natural scene images,

and novel handwritten digit images were used as unlearned visual inputs (Fig 6A). The simulation

results revealed that neural responses were distributed over middle values for learned images and

over smaller or larger values for unlearned inputs (Fig 6B and 6C), suggesting that spatio-temporally

efficient coding could predict the phenomenon of deviant neural responses to unlearned inputs.

The same conclusion could also be reached if the learned images were handwritten digit images

and the unlearned images were natural scene images (Fig 6D, 6E, and 6F).

Simulations in the present study demonstrated that neural responses were distributed around

smaller or larger extremes for unlearned inputs and around intermediate values for learned inputs

(Fig 6B and 6C). In a separate analysis, we allowed the neural responses to learned inputs be

distributed only around lower values (see, Implementation of spatio-temporally efficient coding, $\lambda =$

5), similar to sparse coding (Olshausen and Field, 1996; Olshausen and Field, 1997), and observed

that neural responses of the lower hierarchy to unlearned inputs exhibited higher values (Fig 7).

Under this sparseness constraint, when an external stimulus was first given, the neural response

surged from zero to a large value and then stabilized again (Fig 7C and 7D).

Fig 6. Neural response distributions for learned and unlearned inputs. (A) Natural scene images are used as learned inputs (for learning in the visual hierarchical structure) and handwritten digit images are used as unlearned inputs (not used in learning). (B) Examples of neural response distributions of lower hierarchy units for each of the five time steps of bidirectional information transmissions, corresponding to images in (A). The colour scale indicates the proportion. (C) Overall neural response distributions in response to all input images (either learned or unlearned) at lower and upper hierarchies, respectively. (D), (E), (F) are similar to (A), (B), (C), but handwritten digit images are used as learned inputs and natural scene images are used as unlearned inputs.

Fig 7. Neural response distributions for learned and unlearned inputs under sparseness constraint. (A) Natural scene images are used as learned inputs (for learning in the visual hierarchical structure) and handwritten digit images are used as unlearned inputs (not used in learning). (B) Lower hierarchy neural responses for consecutive external inputs in (A). The neural response is the output of the sigmoid function and is therefore normalised to a range between 0 and 1. (C) Examples of neural response distributions of lower hierarchy units for each of the five time steps of bidirectional information transmissions, corresponding to images in (A). Unlike (B), it is a neural response when images are presented separately rather than consecutively. The colour scale indicates the proportion. (D) Overall neural response distributions in response to all input images (either learned or unlearned) at lower and upper hierarchies, respectively.

3.6. Preferred orientation biases of receptive fields

Neurons in the visual system prefer horizontal and vertical orientations over oblique orientations
(Furmanski and Engel, 2000; Li et al., 2003). Indeed, orientation discrimination is more sensitive to
horizontal and vertical orientations than to oblique orientations (Girshick et al., 2011). This is a bias
towards cardinals (Girshick et al., 2011). Since smooth neural representations of spatio-temporally
efficient coding reflects the structure of the external world well, we predicted that it would also
reflect the environmental statistics of natural scenes. We investigated whether units in the visual
hierarchical structure that learned by spatio-temporally efficient coding of natural scene images
exhibited such biases. Units in the lower hierarchy had the Gabor-like visual receptive fields, while
units in the upper hierarchy had more complex visual receptive fields (Fig 8A) (also see, Computation
of receptive fields in Materials and Methods section). Because the units had an oriented Gabor-like
receptive field, we used oriented bar stimuli to measure the unit's preferred orientation. We
presented a static bar oriented in one of eight angles that moved in the direction perpendicular to
the orientation angle (Fig 8B) and defined the response of each unit to that orientation by the
largest response during presentation. We then defined the preferred orientation of each unit as the
orientation that elicited the largest response. Example neural responses were shown in Fig 8C.
Simulation results revealed that units clearly prefer horizontal and vertical orientations over oblique
orientations (Fig 8D), consistent with the orientation bias of visual cortical neurons and in
accordance with context-independent bottom-up prediction (Teufel and Fletcher, 2020). This means
that smooth neural representations when well-balanced between temporally efficient coding
objective and spatially efficient coding objective reflect the environmental statistics of natural scenes.

Fig 8. Orientation preference. (A) Examples of visual receptive fields of lower and upper hierarchy

units. (B) Orientation images used to test the visual orientation preference of neuronal units at hierarchy 1 in the visual hierarchical structure that learned by the spatio-temporally efficient coding of natural scene images. White bars in each of the eight orientations are moved in the perpendicular directions denoted by blue dotted arrows. (C) Examples of lower hierarchy neural responses for bar stimuli. Each colour indicates each orientation. The neural responses of each orientation were obtained from the bar positions with the largest neural responses at time step 5. These four example units correspond to 1st, 3rd, 5th, and 7th units in (A). (D) Histograms of the orientation preference at time step.

4. Discussion

The present study aimed to find computational principles that enables visual hierarchical structures to attain the function to represent external visual information. To address the lack of neural coding principles to encompass both bottom-up and top-down pathways, we propose spatio-temporally efficient coding as a novel computational model. As a principled way of efficiently using given resources in both neural activity space and processing time, this coding principle optimises bidirectional information transmissions over hierarchical structures by simultaneously minimising temporally differences in neural responses and maximising entropy in neural representations. Simulation results showed that the proposed spatio-temporally efficient coding assigned the function of appropriate neural representations of natural scenes to a visual hierarchical structure on time domain and that it could predict deviations in neural responses to unlearned inputs and a bias in preferred orientations, which are well known characteristics of the visual system.

Appropriate neural representations in the present study were decodable stable neural representations which is an appropriate function to hierarchical brain structures on the time domain. To demonstrate this, we compared spatio-temporally efficient coding (STEC condition) with existing efficient coding (SEC condition) and sparse coding (Sparse condition) as shown in Fig 4. Only spatio-temporally efficient coding showed decodable stable neural representations. Existing predictive coding is conceptually problematic to apply to such real-time information processing (Hogendoorn and Burkitt, 2019). It would be interesting to compare the results with the conceptually improved predictive coding as well. Temporal coherence (Hurri and Hyvärinen, 2002; Zou et al., 2011) or slow feature analysis (Wiskott and Sejnowski, 2002; Berkes and Wiskott, 2005; Creutzig and Sprekeler, 2008) elicits smooth changes in neural responses, similar to temporally efficient coding in the present study. However, they were not used as comparative models because they are not intended to elicit different neural responses to different external inputs and are not suitable for direct application to the bidirectional multiple hierarchical structure of in the present study. Nevertheless, they can be substituted to the role of temporally efficient coding in the present study.

Since its initial proposal (Attneave, 1954; Barlow, 1961), spatially efficient coding has been validated
experimentally (Laughlin, 1981). However, observed correlations between neurons, which maximise
entropy to a lesser extent compared to mere spatially efficient coding assuming no inter-neuronal
correlations, have yet to be incorporated into the principle of spatially efficient coding. Empirically
observed neuronal correlations may drive computational processes of the brain away from strict
spatially efficient coding. Recent studies suggest that biological visual systems are intermediate
between strict spatially efficient coding and correlated neural responses (Stringer et al., 2019).
Therefore, to create biologically plausible computational models, it is necessary to mitigate the
spatially efficient coding objective by combining firing-rate-dependent correlations (de la Rocha et
al., 2007). This enables more accurate information transmissions of visual perception mediated by
visual hierarchical structures. As we focused on integrating spatially efficient coding with temporally
efficient coding for computation in hierarchical structures, this study did not incorporate the
correlations between neurons in spatially efficient coding, which will be pursued in follow-up studies.

Based on our simulations, we observed that the learning of bidirectional information transmission
networks with spatio-temporally efficient coding was hindered when the balancing parameter λ
was too small or too large (Fig 2C). Therefore, it was necessary to confine λ within a certain range,
in which the magnitude of λ affected neural responses such that a larger λ rendered responses
more variable (Fig 2C). Such increased variability is likely to originate from recurrent responses via
higher hierarchies. This was confirmed by the observation that top-down synaptic weights become
larger than bottom-up synaptic weights when λ increased (Fig 2B). Although a large λ attenuated
the appropriateness of neural representations (Fig 3), it rendered stronger top-down synaptic
connections in lower hierarchy (Fig 2B), which is consistent with the previous finding that top-down
synaptic connections are stronger than bottom-up connections in the lateral geniculate nucleus
(Sillito et al., 2006). As to why top-down synaptic weights increase with a larger λ value (Fig 2B),
we speculate that learning via spatio-temporally efficient coding may increase the range of neural
responses to maximise entropy through top-down pathways. While the bottom-up pathways
originating from external inputs are invariant during learning, the top-down pathways originating
from higher hierarchy neural responses are more flexible to adjustment to maximise entropy during
learning. An increase in these top-down synaptic weights predicts impairment of eye movement
tracking partially occluded visual targets in schizophrenic patients (Adams et al., 2012). This may be
due to an increased higher hierarchy's influence in patients with schizophrenia. The increased higher
hierarchy's influence in our simulations is that they do not stabilize neural responses sufficiently to
distinguish a given input from other inputs (Fig 4C).

The deviant neural responses to unlearned inputs observed in this study (Fig 6) arise from smooth
neural representations for learned inputs (distributed over the middle value). As such, neural
representations for learned inputs extrude neural responses to unlearned inputs into a range of

deviant neural responses. We conjecture that the visual system may generate deviant neural
responses via a similar mechanism.

Spatio-temporally efficient coding predicted a bias in preferred orientations (Fig 8). In this regard,
spatially efficient coding alone has been reported to predict bias in preferred orientations (Ganguli
and Simoncelli, 2014). Notably, spatio-temporally efficient coding was able to predict this bias well,
even when λ was low, that is, when the spatially efficient coding objective was less weighted (Fig
8D). Therefore, this bias prediction should be viewed as a result of spatio-temporally efficient coding,
not as a result of spatially efficient coding alone.

The present study has several limitations. First, for simplicity, our simulation model contained only
two hierarchies. However, it is necessary to explore how spatio-temporally efficient coding operates
in models with more hierarchies. We also modelled 64 neuronal units at each hierarchy, as we
assumed that this would be sufficient to represent the natural scene images used in this study.
Nevertheless, the interactions between the number of neuronal units, levels of hierarchy, and spatio-
temporally efficient coding require further investigation. Second, we demonstrated that the visual
hierarchical structure could learn to represent static natural scene images with spatio-temporally
efficient coding, but future follow-up studies will investigate whether the visual hierarchical structure
learns to represent moving scenes using the same coding principle. Finally, the scope of the present
study was limited to the visual system given that its hierarchical structure is well documented, but
spatio-temporally efficient coding may be applied to other systems (e.g., somatosensory system) or
to movements and planning.

4.1. Conclusions

In the present study, we proposed spatio-temporally efficient coding, inspired by the efficient use
of given resources in neural systems, as a neural coding mechanism to assign representational
functions to the hierarchical structures of the visual system. Simulations demonstrated that the visual
hierarchical structure could represent the external world (i.e., natural scenes) appropriately using
bidirectional information transmissions (Fig 2, 3, and 4). Furthermore, spatio-temporally efficient
coding predicted the well-known properties of visual cortical neurons, including deviations in neural
responses to unlearned images (Fig 6 and 7) and bias in preferred orientations (Fig 8). Our proposed
spatio-temporally efficient coding may facilitate deeper mechanistic understanding of the
computational processes of hierarchical brain structures.

Data availability statement

All simulation and analysis codes are available at: https://github.com/DuhoSihn/Spatio-temporally-efficient-coding and on Zenodo (doi: 10.5281/zenodo.5298182)

CRediT authorship contribution statement

Duho Sihn: Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Resources, Data Curation, Writing - Original Draft, Writing - Review & Editing, Visualization, Supervision, Project administration. **Sung-Phil Kim**: Writing - Original Draft, Writing - Review & Editing, Visualization, Supervision, Project administration, Funding acquisition.

Declaration of Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have influenced the work reported in this paper.

Acknowledgments

This research was supported by the Brain Convergence Research Programs of the National Research Foundation (NRF) funded by the Korean government (MSIT) (NRF-2019M3E5D2A01058328 and No. 2021M3E5D2A01019542).

References

1. Adams RA, Perrinet LU, Friston K. Smooth pursuit and visual occlusion: Active inference and oculomotor control in schizophrenia. PLOS ONE 2012 Oct 26; 7(10):e47502. doi: 10.1371/journal.pone.0047502

2. Attneave F. Some informational aspects of visual perception. Psychological Review 1954; 61(3):183–193. doi: 10.1037/h0054663

3. Barlow HB. Possible principles underlying the transformations of sensory messages. In: Rosenblith WA editor. Sensory Communication, MIT Press; 1961. p 217-234. doi:

10.7551/mitpress/9780262518420.003.0013

4. Bengio Y, Courville A, Vincent P. Representation learning: A review and new perspectives.
IEEE Transactions on Pattern Analysis and Machine Intelligence 2013 Aug; 35(8):1798-1828.
doi: 10.1109/TPAMI.2013.50

5. Berens P, Ecker AS, Cotton RJ, Ma WJ, Bethge M, Tolias AS. A fast and simple population
code for orientation in primate V1. J. Neurosci. 2012 Aug 01; 32(31):10618-10626. doi:
10.1523/JNEUROSCI.1335-12.2012

6. Berkes P, Wiskott L. Slow feature analysis yields a rich repertoire of complex cell properties.
Journal of Vision 2005 Jul 20; 5(6):579-602. doi: 10.1167/5.6.9

7. Borst A, Theunissen FE. Information theory and neural coding. Nature Neuroscience 1999
Nov 01; 2(11):947-957. doi: 10.1038/14731

8. Bourlard H, Kamp Y. Auto-association by multilayer perceptrons and singular value
decomposition.   Biological   Cybernetics   1988   Sep   01;   59(4):291-294.   doi:
10.1007/BF00332918

9. Boutin V, Franciosini A, Chavane F, Ruffier F, Perrinet L, Sparse deep predictive coding
captures contour integration capabilities of the early visual system. PLoS Comput Biol 2021
Jan 26; 17(1): e1008629. doi: 10.1371/journal.pcbi.1008629

10. Brouwer GJ, Heeger DJ. Decoding and reconstructing color from responses in human visual
cortex. J. Neurosci. 2009 Nov 04; 29(44):13992-14003. doi: 10.1523/JNEUROSCI.3577-
09.2009

11. Bullmore E, Sporns O. The economy of brain network organization. Nat Rev Neurosci 2012
May 01; 13(5)336–349. doi: 10.1038/nrn3214

12. Burt JB, Demirtaş M, Eckner WJ, Navejar NM, Ji JL, Martin WJ, Bernacchia A, Anticevic A,
Murray JD. Hierarchy of transcriptomic specialization across human cortex captured by
structural neuroimaging topography. Nat Neurosci 2018 Sep 01; 21(9):1251–1259. doi:
10.1038/s41593-018-0195-0

13. Clark A. Whatever next? Predictive brains, situated agents, and the future of cognitive
science.   Behavioral   and   Brain   Sciences   2013   May   10;   36(3):181-204.   doi:
10.1017/S0140525X12000477

14. Creutzig F, Sprekeler H. Predictive coding and the slowness principle: An information-
theoretic   approach.   Neural   Computation   2008   Apr;   20(4):1026-1041.   doi:
10.1162/neco.2008.01-07-455

15. de la Rocha J, Doiron B, Shea-Brown E, Josic K, Reyes A. Correlation between neural spike
trains increases with firing rate. Nature 2007 Aug 01; 448(7155):802–806. doi:
10.1038/nature06028

16. deCharms RC, Zador A. Neural representation and the cortical code. Annu. Rev. Neurosci.
2000 May 01; 23(1):613-647. doi: 10.1146/annurev.neuro.23.1.613

17. DiCarlo JJ, Zoccolan D, Rust NC. How does the brain solve visual object recognition? Neuron
2012 Feb 09; 73(3):415-434. doi: 10.1016/j.neuron.2012.01.010

18. Di Gesù V, Starovoitov V. Distance-based functions for image comparison. Pattern
Recognition Letters 1999 Feb 01; 20(2):207-214. doi: 10.1016/S0167-8655(98)00115-9

19. Felleman DJ, Van Essen DC. Distributed hierarchical processing in the primate cerebral
cortex. Cereb Cortex, 1991 Jan 01; 1(1):1-47. doi: 10.1093/cercor/1.1.1

20. Friston K. A theory of cortical responses. Phil. Trans. R. Soc. B 2005 Apr 29; 360(1456):815-
836. doi: 10.1098/rstb.2005.1622

21. Friston K. The free-energy principle: a unified brain theory? Nat Rev Neurosci 2010 Feb 01;
11(2):127–138. doi: 10.1038/nrn2787

22. Friston K, Thornton C, Clark A. Free-energy minimization and the dark-room problem. Front.
Psychol. 2012 May 08; 3:130. doi: 10.3389/fpsyg.2012.00130

23. Furmanski CS, Engel SA. An oblique effect in human primary visual cortex. Nat Neurosci
2000 Jun 01; 3(6):535–536. doi: 10.1038/75702

24. Ganguli D, Simoncelli EP. Efficient sensory encoding and bayesian inference with
heterogeneous neural populations. Neural Comput 2014 Oct 01; 26(10):2103–2134. doi:
10.1162/NECO_a_00638

25. Girshick AR, Landy MS, Simoncelli EP. Cardinal rules: visual orientation perception reflects
knowledge of environmental statistics. Nat Neurosci 2011 Jul 01; 14(7):926–932. doi:
10.1038/nn.2831

26. Griffiths TL, Lieder F, Goodman ND. Rational use of cognitive resources: Levels of analysis
between the computational and the algorithmic. Top Cogn Sci 2015 Apr 01; 7(2):217-229.
doi: 10.1111/tops.12142

27. Goodfellow IJ, Courville A, Bengio Y. Spike-and-slab sparse coding for unsupervised feature
discovery. Proceedings of the Conference on Neural Information Processing Systems; 2011
Dec 12-17; Granada, Spain.

28. Hansen JY, Markello RD, Vogel JW, Seidlitz J, Bzdok D, Misic B. Mapping gene transcription
and neurocognition across human neocortex. Nat Hum Behav 2021 Mar 25. doi:
10.1038/s41562-021-01082-z

29. Harris JA, Mihalas S, Hirokawa KE, Whitesell JD, Choi H, Bernard A, Bohn P, Caldejon S, Casal
L, Cho A, Feiner A, Feng D, Gaudreault N, Gerfen CR, Graddis N, Groblewski PA, Henry AM,
Ho A, Howard R, Knox JE, Kuan L, Kuang X, Lecoq J, Lesnar P, Li Y, Luviano J, McConoughey
S, Mortrud MT, Naeemi M, Ng L, Oh SW, Ouellette B, Shen E, Sorensen SA, Wakeman W,
Wang Q, Wang Y, Williford A, Phillips JW, Jones AR, Koch C, Zeng H. Hierarchical
organization of cortical and thalamic connectivity. Nature 2019 Nov 01; 575(7781):195–202.
doi: 10.1038/s41586-019-1716-z

30. Hastie T, Tibshirani R, Friedman J. The elements of statistical learning: Data mining, inference,
and prediction. 2nd ed. Springer; 2009. doi: 10.1007/978-0-387-84858-7

31. Hinton GE, Zemel RS. Autoencoders, minimum description length and Helmholtz free
energy. Proceedings of the Conference on Neural Information Processing Systems; 1993;
Denver, Colorado, United States.

32. Hurri J, Hyvärinen A. Temporal coherence, natural image sequences, and the visual cortex.
Proceedings of the Conference on Neural Information Processing Systems; 2002 Dec 9-12;
Vancouver, British Columbia, Canada.

33. Hilgetag CC, Goulas A. 'Hierarchy' in the organization of brain networks. Phil. Trans. R. Soc.
B 2020 Apr 13; 375(1796):20190319. doi: 10.1098/rstb.2019.0319

34. Hogendoorn H, Burkitt AN. Predictive coding with neural transmission delays: a real-time
temporal alignment hypothesis. eNeuro 2019 Mar 28; 6(2). doi: 10.1523/ENEURO.0412-
18.2019

35. Huang G, Ramachandran S, Lee TS, Olson CR. Neural correlate of visual familiarity in
macaque   area   V2.   J.   Neurosci.   2018   Oct   17;   38(42):8967-8975.   doi:
10.1523/JNEUROSCI.0664-18.2018

36. Hubel DH, Wiesel TN. Receptive fields, binocular interaction and functional architecture in
the cat's visual cortex. The Journal of Physiology 1962 Jan 01; 160(1):106-154. doi:
10.1113/jphysiol.1962.sp006837

37. Hubel DH, Wiesel TN. Receptive fields and functional architecture of monkey striate cortex.
The   Journal   of   Physiology   1968   Mar   01;   195(1):215-243.   doi:
10.1113/jphysiol.1968.sp008455

38. Huh CYL, Peach JP, Bennett C, Vega RM, Hestrin S. Feature-Specific Organization of
Feedback Pathways in Mouse Visual Cortex. Current Biology 2018 Jan 08; 28(1):114-120.e5.
doi: 10.1016/j.cub.2017.11.056

39. Issa EB, Cadieu CF, DiCarlo JJ. Neural dynamics at successive stages of the ventral visual
stream are consistent with hierarchical error signals. eLife 2018 Nov 28; 7:e42870. doi:
10.7554/eLife.42870

40. Kamitani Y, Tong F, Decoding the visual and subjective contents of the human brain. Nature
Neuroscience 2005 May 01; 8(5):679-685. doi: 10.1038/nn1444

41. Kingma DP, Ba J. Adam: A method for stochastic optimization. Proceedings of the 3th
International Conference on Learning Representations; 2015 May 7-9; San Diego, California,
United States.

42. Kriegeskorte N, Diedrichsen J. Peeling the onion of brain representations. Annu. Rev.
Neurosci. 2019 Jul 08; 42(1):407-432. doi: 10.1146/annurev-neuro-080317-061906

43. Laughlin SB. A simple coding procedure enhances a neuron's information capacity. Z.
Naturforsch. 1981; 36(9-10):910-912 doi: 10.1515/znc-1981-9-1040

44. Laughlin SB. Energy as a constraint on the coding and processing of sensory information.
Current Opinion in Neurobiology 2001 Aug 01; 11(4):475-480. doi: 10.1016/S0959-
4388(00)00237-3

45. Lecun Y, Bottou L, Bengio Y, Haffner P. Gradient-based learning applied to document
recognition. Proceedings of the IEEE 1998 Nov; 86(11):2278-2324. doi: 10.1109/5.726791

46. Li B, Peterson MR, Freeman RD. Oblique Effect: A neural basis in the visual cortex. J.
Neurophysiol. 2003 Jul 01; 90(1):204-217. doi: 10.1152/jn.00954.2002

47. Lieder F, Griffiths TL. Resource-rational analysis: Understanding human cognition as the
optimal use of limited computational resources. Behavioral and Brain Sciences 2020; 43:E1.
doi: 10.1017/S0140525X1900061X

48. Margoliash D. Acoustic parameters underlying the responses of song-specific neurons in
the white-crowned sparrow. J. Neurosci. 1983 May 01; 3(5):1039-1057. doi:
10.1523/JNEUROSCI.03-05-01039.1983

49. Mesulam MM, From sensation to cognition. Brain, 1998 Jun 01; 121(6):1013–1052. doi:
10.1093/brain/121.6.1013

50. Muckli L, De Martino F, Vizioli L, Petro LS, Smith FW, Ugurbil K, Goebel R, Yacoub E.

Contextual feedback to superficial layers of V1. Current Biology 2015 Oct 19, 25(20):2690-2695. doi: 10.1016/j.cub.2015.08.057

51. Murphy PC, Sillito AM. Corticofugal feedback influences the generation of length tuning in the visual pathway. Nature 1987 Oct 01; 392(6141):727-729. doi: 10.1038/329727a0

52. Olshausen BA, Field DJ. Emergence of simple-cell receptive field properties by learning a sparse code for natural images. Nature 1996 Jun 01; 381(6583):607–609. doi: 10.1038/381607a0

53. Olshausen BA, Field DJ. Sparse coding with an overcomplete basis set: A strategy employed by V1? Vision Research 1997 Dec 01; 37(23):3311-3325. doi: 10.1016/S0042-6989(97)00169-7

54. Ohzawa I, DeAngelis GC, Freeman RD. Encoding of binocular disparity by simple cells in the cat's visual cortex. Journal of Neurophysiology 1996 May 01; 75(5):1779-1805. doi: 10.1152/jn.1996.75.5.1779

55. Ranzato M, Poultney CS, Chopra S, LeCun Y. Efficient learning of sparse representations with an energy-based model. Proceedings of the Conference on Neural Information Processing Systems; 2006 Dec 4-7; Vancouver, British Columbia, Canada.

56. Rao RPN, Ballard DH. Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. Nat Neurosci 1999 Jan 01; 2(1):79-87. doi: 10.1038/4580

57. Riesenhuber M, Poggio T. Hierarchical models of object recognition in cortex. Nat Neurosci 1999 Nov 01; 2(11):1019-1025. doi: 10.1038/14819

58. Riesenhuber M, Poggio T. Models of object recognition. Nat Neurosci 2000 Nov 01; 3(11):1199-1204. doi: 10.1038/81479

59. Rifai S, Vincent P, Muller X, Glorot X, Bengio Y. Contractive auto-encoders: Explicit invariance during feature extraction. Proceedings of the International Conference on Machine Learning; 2011 Jun 28-Jul 2; Bellevue, Washington, United States.

60. Rubinov M, Sporns O, van Leeuwen C, Breakspear M. Symbiotic relationship between brain structure and dynamics. BMC Neuroscience 2009 Jun 02; 10(1):55. doi: 10.1186/1471-2202-10-55

61. Sederberg AJ, MacLean JN, Palmer SE. Learning to make external sensory stimulus predictions using internal correlations in populations of neurons. Proc Natl Acad Sci USA 2018 Jan 30; 115(5):1105-1110. doi: 10.1073/pnas.1710779115

62. Serre T, Oliva A, Poggio T. A feedforward architecture accounts for rapid categorization.
Proc Natl Acad Sci USA 2007 Apr 10; 104(15):6424-6429. doi: 10.1073/pnas.0700622104

63. Sihn D. Simulation codes for spatio-temporally efficient coding. 2021. Available from:
https://github.com/DuhoSihn/Spatio-temporally-efficient-coding   doi:
10.5281/zenodo.5298182

64. Sillito AM, Cudeiro J, J HE. Always returning: feedback and sensory processing in visual
cortex and thalamus. Trends Neurosci. 2006 Jun 01; 29(6):307-316. doi:
10.1016/j.tins.2006.05.001

65. Solomon SS, Tang H, Sussman E, Kohn A. Limited evidence for sensory prediction error
responses in visual cortex of macaques and humans. Cereb Cortex 2021 Jun 01; 31(6):3136-
3152. doi: 10.1093/cercor/bhab014

66. Spratling MW. A review of predictive coding algorithms. Brain and Cognition 2017 Mar 01;
112:92-97. doi: 10.1016/j.bandc.2015.11.003

67. Stringer C, Pachitariu M, Steinmetz N, Carandini M, Harris KD. High-dimensional geometry
of population responses in visual cortex. Nature 2019 Jul 01; 571(7765)361–365. doi:
10.1038/s41586-019-1346-5

68. Sullivan TJ, de Sa VR. Homeostatic synaptic scaling in self-organizing maps. Neural
Networks 2006 Jul 01; 19(6):734-743. doi: 10.1016/j.neunet.2006.05.006

69. Teufel C, Fletcher PC. Forms of prediction in the nervous system. Nat Rev Neurosci 2020
Apr 01; 21(4):231–242. doi: 10.1038/s41583-020-0275-5

70. Tomov P, Pena RFO, Zaks MA, Roque AC. Sustained oscillations, irregular firing, and chaotic
dynamics in hierarchical modular networks with mixtures of electrophysiological cell types.
Front. Comput. Neurosci. 2014 Sep 02; 8:103 doi: 10.3389/fncom.2014.00103

71. Toyoizumi T, Pfister J-P, Aihara K, Gerstner W. Generalized Bienenstock–Cooper–Munro rule
for spiking neurons that maximizes information transmission. Proc Natl Acad Sci U S A
2005 Apr 05; 102(14):5239-5244. doi: 10.1073/pnas.0500495102

72. Turrigiano GG, Nelson SB. Homeostatic plasticity in the developing nervous system. Nature
Reviews Neuroscience 2004 Feb 01; 5(2):97-107. doi: 10.1038/nrn1327

73. van Hateren JH, van der Schaaf A. Independent component filters of natural images
compared with simple cells in primary visual cortex. Proc. Royal Soc. B 1998 Mar 07;
265(1394):359-366. doi: 10.1098/rspb.1998.0303

74. Vincent P, Larochelle H, Bengio Y, Manzagol P-A. Extracting and composing robust features
with denoising autoencoders. Proceedings of the International Conference on Machine
Learning; 2008 Jul 5-8; Helsinki, Finland.

75. Wang W, Jones HE, Andolina IM, Salt TE, Sillito AM. Functional alignment of feedback
effects from visual cortex to thalamus. Nat Neurosci 2006 Oct 01; 9(10):1330-1336. doi:
10.1038/nn1768

76. Waydo S, Kraskov A, Quian Quiroga R, Fried I, Koch C. Sparse representation in the human
medial temporal lobe. J. Neurosci. 2006 Oct 04; 26(40):10232-10234. doi:
10.1523/JNEUROSCI.2101-06.2006

77. Wiskott L, Sejnowski TJ. Slow feature analysis: Unsupervised learning of invariances. Neural
Computation 2002 Apr 01; 14(4):715-770. doi: 10.1162/089976602317318938

78. Yamins DLK, Hong H, Cadieu CF, Solomon EA, Seibert D, DiCarlo JJ. Performance-optimized
hierarchical models predict neural responses in higher visual cortex. Proc Natl Acad Sci
USA 2014 Jun 10; 111(23):8619-8624. doi: 10.1073/pnas.1403112111

79. Zavitz E, Yu H-H, Rowe EG, Rosa MGP, Price NSC. Rapid adaptation induces persistent biases
in population codes for visual motion. J. Neurosci. 2016 Apr 20; 36(16):4579-4590. doi:
10.1523/JNEUROSCI.4563-15.2016

80. Zhang S, Xu M, Kamigaki T, Hoang Do JP, Chang W, Jenvay S, Miyamichi K, Luo L, Dan Y.
Long-range and local circuits for top-down modulation of visual cortex processing. Science
2014 Aug 08; 345(6197):660-665. doi: 10.1126/science.1254126

81. Zou WY, Ng AY, Yu K. Unsupervised learning of visual invariance with temporal coherence.
Proceedings of the Conference on Neural Information Processing Systems; 2011 Dec 12-
17; Granada, Spain.

A

Ref.

(STEC)

Relative distance from ref. on lower hierarchy

Relative distance from ref. on image

B Local similarity

Correlation over distances

1
0.8
0.6
0.4
0.2
0

STEC   SEC   Sparse

Lower hierarchy
Upper hierarchy

C Discriminability

Performance

0.994
0.992
0.990
0.988

STEC   SEC   Sparse   Random

Lower hierarchy
Upper hierarchy

A

B

STEC; Lower hierarchy | SEC; Lower hierarchy

C

Lower hierarchy STEC | Lower hierarchy SEC

Upper hierarchy STEC | Upper hierarchy SEC

A **Learned** | **Unlearned**

B **Learned, Lower hierarchy** | **Unlearned, Lower hierarchy**

C **Learned** | **Unlearned**

D **Lower hierarchy Learned** | **Lower hierarchy Unlearned** | **Upper hierarchy Learned** | **Upper hierarchy Unlearned**

(STEC)