TopoRoot: A method for computing hierarchy and fine-grained

traits of maize roots from X-ray CT images

Dan Zeng[1]*, Mao Li[2], Ni Jiang[2], Yiwen Ju[1], Hannah Schreiber[3], Erin Chambers[3], David

Letscher[3], Tao Ju[1], Christopher N. Topp[2]

1: Department of Computer Science and Engineering, Washington University in St. Louis, Saint

Louis, Missouri, 63130, USA

2: Donald Danforth Plant Science Center, Saint Louis, Missouri, 63132, USA

3: Department of Computer Science, Saint Louis University, Saint Louis, Missouri, 63103, USA

*author to whom correspondence should be addressed: danzeng@wustl.edu

Abstract

Background:

3D imaging, such as X-ray CT and MRI, has been widely deployed to study plant root structures. Many computational tools exist to extract coarse-grained features from 3D root images, such as total volume, root number and total root length. However, methods that can accurately and efficiently compute fine-grained root traits, such as root number and geometry at each hierarchy level, are still lacking. These traits would allow biologists to gain deeper insights into the root system architecture (RSA).

Results:

We present TopoRoot, a high-throughput computational method that computes fine-grained architectural traits from 3D X-ray CT images of field-excavated maize root crowns. These traits include the number, length, thickness, angle, tortuosity, and number of children for the roots at each level of the hierarchy. TopoRoot combines state-of-the-art algorithms in computer graphics, such as topological simplification and geometric skeletonization, with customized heuristics for robustly obtaining the branching structure and hierarchical information. TopoRoot is validated on both real and simulated root images, and in both cases it was shown to improve the accuracy of traits over existing methods. We also demonstrate TopoRoot in differentiating a maize root mutant from its wild type segregant using fine-grained traits. TopoRoot runs within a few minutes on a desktop workstation for volumes at the resolution range of 400^3, without need for human intervention.

Conclusions:

TopoRoot improves the state-of-the-art methods in obtaining more accurate and comprehensive fine-grained traits of maize roots from 3D CT images. The automation and efficiency makes

56 TopoRoot suitable for batch processing on a large number of root images. Our method is thus

57 useful for phenomic studies aimed at finding the genetic basis behind root system architecture

58 and the subsequent development of more productive crops.

59 Keywords

60 Root system architecture, Phenotyping, 3D Imaging, Topology, Computer Graphics

61 Introduction

Roots are the primary means by which the plant absorbs water and nutrients, and they provide

anchorage to the plant. These functions are largely determined by the root system architecture

(RSA) [10, 2, 8], which describes both the geometry of individual roots and their hierarchical

relationships. Quantifying RSA enables efforts to discover the genetic control of root traits,

which can lead to improved crop productivity while minimizing adverse environmental effects

[8]. However, RSA is difficult to study owing to roots' poor accessibility as the "hidden" half of

the plant. Traditionally, roots are excavated from the soil, washed, and then measured by hand

using devices such as rulers, calipers, and protractors. This process is not only labor-intensive

but also prone to human errors. More importantly, many aspects of RSA, particularly those

pertaining to lateral roots of higher order, are almost impossible to measure by hand.

Advances in 3D imaging, including X-ray CT, MRI, and optical imaging [20, 27, 15], have

allowed root shapes to be captured digitally either after excavation or *in situ*. The availability of

such imaging data has paved the way for recent efforts towards computational quantification of

root system architecture [23, 19, 28]. However, most image-based root phenotyping methods

only compute overall traits such as the volume, depth, convex hull volume, total root length, and

root number [33, 6, 14, 5]. Though useful, these traits which are aggregated over the whole root

system do not capture the branching structure or the hierarchical organization of individual roots,

which provide a much more comprehensive description of RSA. Recently, a system for multi-

view scanning and subsequent computational analysis, known as DIRT/3D [12], was proposed to

measure detailed traits of maize root crowns. The system can report 18 traits that concern the

geometry of the stem (e.g., diameter and depth), the upper whorls (e.g., inter-whorl distance) and

their individual nodal roots (e.g., length, angle and diameter). An inherent challenge for multi-

view reconstruction, due to occlusion, is resolving densely packed roots. As a result, DIRT/3D

does not provide a full root hierarchy of the root crown beyond the nodal roots.

To our knowledge, DynamicRoots [32] is the only published and validated root phenotyping

method that produces a full branching hierarchy and root traits associated with each hierarchy

level in 3-dimensions. DynamicRoots is designed for a time-series of root systems grown in

transparent gel [17]. These seedling-stage root systems tend to have a relatively simple geometry

and structure, which makes it possible to obtain high quality 3D reconstructions using multi-view

imaging [39]. DynamicRoots first employs graph analysis on the voxelized root system at each

time-point to identify the root branches. Hierarchical relations among the branches are first

determined by the length of the branches and then refined by the time function obtained by

aligning root architectures across time. However, DynamicRoots makes two assumptions that

limit its application to other types of root images. First, the input shapes can only have a mild

amount of topological errors, including disconnected root components (e.g. due to limits in

resolution), root branches forming loops due to touchings (e.g. due to limits in resolution and

noise), and voids of space surrounded by the surface of the root (e.g. due to high optical density

of the root). Second, the time series must be dense enough to observe the correct root hierarchy.

Neither assumption may hold for other imaging setups, such as X-ray CT or MRI scans of

complex roots, which may lead to numerous topological errors after image segmentation and

have few, and often a single, time point available.

In this work, we present TopoRoot, a method for obtaining the complete root hierarchy and

computing the associated traits from a single 3D X-ray CT scan of excavated maize root crowns.

TopoRoot adopts a multi-step approach to treat the topological errors in the input image, and it

computes the hierarchy and traits using a high-fidelity skeleton representation of the root system

architecture. Our method builds on state-of-the-art algorithms from computer graphics and

introduces customized heuristics tailored to the image features and the maize root structure.

On a set of X-ray CT scans of 45 excavated maize root crowns where manual measurements of

nodal root counts were made, TopoRoot shows dramatic improvements in accuracy compared to

DynamicRoots. As a demonstration of the utility of TopoRoot, several of TopoRoot's fine-

grained traits showed an ability to differentiate between two groups of genetically differentiated

species within this data set. On another set of 495 maize root images simulated by

OpenSimRoot [24] with varying age, complexity, and noise level, TopoRoot exhibits improved

accuracy in a variety of coarse-grained and fine-grained traits over GiaRoots [33] and

DynamicRoots.

TopoRoot is completely automated and has only a few parameters to set. On a standard desktop

computer, TopoRoot runs within a few minutes for images at the resolution range of 400^3. This

makes TopoRoot suited for batch processing a large set of images in a high-throughput analysis

pipeline. The software package is freely distributed on GitHub with our test dataset.

Material and Methods

Data preparation

128   **Fig. 1**

(A) (B)

Picture of the X-ray setup. (A) Each maize root crown was clamped and placed on a turntable,
which was rotated for 3 minutes while radiographs were collected at a rate of 10 frames per

second. (B) efX-CT software was used to reconstruct the scan into a 3D grayscale volume

(pictured).

The main data set used for validation consists of 59 maize roots which were planted in June 2020

at Planthaven Farms in O'Fallon, Missouri (latitude 38.84871204483824, longitude -

90.68711352048403) in silt loam soil. Fields received fertilization with ammonium nitrate. Seeds

were planted using jabtype planters into 3.65-m long rows (~25.4-cm within row spacing) on

0.9144-meter row-to-row spacing. The maize plants (Rt1-2.4 MUT) that had mutation on the

Rootless1 gene are known to have decreased nodal root counts [16] compared to their wild-type

counterparts (Rt1-2.4 WT). After 54-57 days of growth, the roots were excavated using the

Shovelomics protocol [34] in September 2020 and washed to remove soil. We used an X5000 X-

ray imaging system and efX-DR software (NSI, Rogers, MN) to collect X-ray computed

tomography (XRT) data (pictured in Figure 1). The X-ray source was set to a voltage of 70kV,

current of 1700µA, and focal spot length of 119µm. Samples were clamped and placed on a

turntable for imaging at a magnification of 1.17X and 10 frames per second (fps), collecting

1800 16-bit digital radiographs over a 3 minute scan time. efX-CT software was used to

reconstruct the scan into a 3D volume at 109µm voxel resolution. This volume was exported as a

16-bit RAW volume. Following imaging, manual counts were collected for the nodal roots. Each

sample was dissected starting at the highest node (stalk end) moving downward to the root tips.

Only attached roots were counted towards the total number of developed roots at each node.

Finally, 14 scans were removed from the analysis due to excessive soil present in the imaging

and missing whorls. The remaining 45 scans and their manual nodal root counts provide

validation for TopoRoot's computed values.

It is generally difficult to obtain manual measurement of fine-grained root traits beyond counting

the nodal roots. To validate other fine-grained traits produced by our method, we supplement the

156 real data set with a systematically created set of simulated root images. We adopt OpenSimRoot

157 [24], a highly customizable 3D root growth simulation software that has been widely used in

158 modeling and visualizing root growth [11, 31, 7]. We used OpenSimRoot to create 55 maize

159 roots ranging in days of growth from 30 to 40 days, numbers of nodal roots ranging from 31 to

160 69, number of whorls from 5 to 6, and lateral root branching frequency from 0.3 to 0.7 cm /

161 branch. The diameter of the stem was set to be 2 cm, starting diameter for nodal roots is 0.3 cm

162 (gradually decreasing to 0.1 cm after 10 days of growth), lateral roots is 0.04 cm, and fine lateral

163 roots is 0.02 cm. OpenSimRoot provides a detailed hierarchy for each of the simulated roots,

164 from which we obtain the ground-truth traits.

165 **Fig. 2**

167 Iso-surfaces (at level 0) of simulated maize root images with increasing amounts of noise (e)**.**
168 The example is at 40 days of growth. The closeups show fine lateral roots. With increased noise,
169 the roots exhibit less regular geometry and more topological errors (e.g., disconnections and
170 loops).

For each simulated root, we create a 512^3 image by computing the signed distance field from

the surface of the root using the method of [35] with the inside of the surface having positive

values and the outside having negative values. To simulate various levels of image noise, we

randomly perturb the distance value at each voxel, with the amount of perturbation ranging from

0 to 0.08 cm in 0.01 increments. This results in 9 images at increasing noise levels for each of the

55 roots, and thus 495 images in total. Figure 2 shows images of one simulated root (at day 40)

at different noise levels. Note that the amount of geometric irregularity and topological noise

(e.g., disconnected components and loops) increase with the noise level.

Thresholding

Although the X-ray images have good contrast between roots and air, due to the spatial variation

in the contrast, limited resolution and noise, there is typically no common threshold that can

accurately capture both thicker (e.g., nodal) and thinner (e.g., lateral) roots. To obtain the best

result, our method therefore asks the user to provide three thresholds, visualized in Figure 3. The

shape threshold provides the best balance between capturing thick and thin roots, but it may

contain many topological errors (e.g., disconnected thin roots and merged thick roots). We

additionally ask for a kernel threshold (the lowest value that avoids merging of thick roots) and a

neighborhood threshold (the highest value that avoids disconnecting thin roots), such that the

increasing ordering of the three thresholds are neighborhood, shape, and kernel. Our method will

attempt to fix topological errors at the shape threshold guided by the neighborhood and kernel

thresholds. For this data set, we set the shape threshold to be 0, kernel threshold to be 0.03 and

neighborhood threshold to be -0.15.

Fig. 3

Neighborhood (*n*)   Shape (*s*)   Kernel (*k*)

Iso-surfaces *n*, *s*, and *k*, as visualized for an X-ray image of a maize root. The red closeup shows a fine lateral root which is connected in *n*, but disconnected in *s* and which has disappeared in *k*. The light blue closeup shows two nodal roots which are merged together in *n* and *s*, but separated in *k*.

Overview

Our pipeline takes as input a 3D grayscale image with three thresholds (shape, kernel and neighborhood) and produces a hierarchy and associated traits in four steps (Figure 4):

1. Topological simplification: Most topological errors on the iso-surface at the shape threshold are removed by combining a global optimization algorithm [38] and a heuristic that fills in the hollow space inside the stem and other thick roots.

2. Skeletonization: A geometric skeleton capturing the branching structure is computed by first running an existing skeletonization algorithm [36, 37] and then removing cycles on the skeleton using a minimum-spanning tree.

3. Inferring hierarchy: Each skeleton branch is associated with a hierarchy level using a heuristic that favors a shallow hierarchy while encouraging longer branches at lower levels.

4. Computing traits: A suite of root traits, such as the count, lengths, angles, thickness, and tortuosity, are computed from the skeleton at each level of the hierarchy.

212   These steps are detailed in the next sections.

213   **Fig. 4**

Input: 3D Grayscale Image   Topologically simplified iso-surface   Skeleton representing branching structure   Hierarchy

(A)   (B)   (C)   (D)

214
The pipeline of TopoRoot for computing fine-grained traits from a 3D X-ray image. Beginning
from a 3D grayscale image (A), TopoRoot first simplifies the topological complexity of the iso-
surface (B), then it creates a geometric skeleton capturing the branching structure (C), from
which a hierarchy is obtained (D) and the traits are subsequently computed.

<u>Topological simplification</u>

As shown in Figures 1 and 2, iso-surfaces of input images often contain numerous topological

errors, including disconnections, loops, and voids. These errors make it challenging to infer the

branching structure of the root system. We use a recent algorithm [38] to maximally remove

topological errors. Given the iso-surfaces at three thresholds (shape, kernel and neighborhood),

the algorithm attempts to remove all topological features on the iso-surface at the shape threshold

that are not present on either of the other two iso-surfaces. The algorithm allows both addition

and removal of contents to the shape's iso-surface, and it tries to minimize these geometric

changes to achieve topological simplification. This algorithm can effectively connect broken

branches (if they are contiguous at the neighborhood threshold) and split merged branches (if

they are separate at the kernel threshold), as shown in Figure 5A and 5B.

A common issue in XRT scans of dried roots is that the interior space of the stem and some thick

root branches often appears to be hollow. Since our subsequent analysis of the hierarchy relies on

a skeleton representation of the root architecture, we need to fill in such hollow space so that the

resulting skeleton captures the solid cylindrical shape of the roots (instead of only the walls).

However, identifying such interior space is not straight-forward. In the ideal scenario, at the

shape threshold, the wall of the stem or root branch completely separates the interior space from

the outside space, making the interior space a topological void and hence easy to detect. But

oftentimes the iso-surface at the shape threshold exhibits "tunnels" on the wall of the stem or

branch (see Figure 5A, top-left purple box), which connect the interior space with the outside

and making it impossible to identify as a topological feature. Applying the algorithm of [38] does

not fill in the hollow space. On the contrary, it may merge nearby small tunnels into larger

tunnels to reduce the number of topological loops (see Figure 5B, top-left).

Fig. 5

(A) (B) (C)

Topological simplification applied to a root image. (A): The input iso-surface at the shape
threshold contains numerous topological errors such as disconnections (red box) and loops (cyan
box), and tunnels exist on the stem wall (highlighted in the purple box) that connect the hollow
interior space to the outside. (B): Applying the algorithm of [38] resolves the disconnections and
loops (red and cyan boxes), but the hollow space inside the stem remains connected to the
outside through tunnels (highlighted in the purple box). (C): By applying the filling heuristic
prior to calling [38], the stem's interior is filled in without introducing new topological errors.

We develop a simple heuristic to identify and fill the hollow interior spaces. Our assumption,

based on observation of our data, is that such spaces usually become topological voids at the

lower, *neighborhood* threshold (see Figure 6A). These voids, however, are usually smaller than

the hollow space at the shape threshold, and hence need to be expanded before filling in. To do

so, we first erode the set of all voxels above the neighborhood threshold, noted as   , onto the set

of voxels above the shape threshold, noted as   , while preserving the topology of   . The

erosion is prioritized by the intensity, such that voxels having lower intensity are eroded earlier.

The eroded voxel set, denoted as ', consists of   and a minimal set of voxels needed to achieve

the topology of   , denoted as   (colored red in Figure 6B). We then fill each void of ', as

well as those voxels in   adjacent to these voids (see Figure 6C). Since filling may introduce

additional topological errors, such as loops or new voids, we call the heuristic prior to applying

the algorithm of [38]. This produces a topologically simple root shape with filled stems and

branches (see Figure 6C).

Fig. 6

265
Filling the hollow space inside the stem and thick branches. (A) A cross section of a stem,
showing voxels at or above the shape threshold (white, denoted by   ) and voxels at or above the
neighborhood threshold (gray, denoted by   ). Note that the hollow interior of the stem is
connected to the outside space in   , but it forms a void disconnected from the outside in   . (B)

The result of a topology-preserving erosion of V_n onto V_s, denoted by V_n', which consists of V_s

(white) and additional voxels (red) needed to retain the topology of V_n. (C) The voids of V_n', as

well as any voxels that are in V_n' but not in V_s (denoted V_f) are filled in.

Not all topological errors will be removed at the end of this step. In particular, the algorithm of

[38] will retain those topological features (e.g., loops) that exist on all three thresholds (shape,

kernel, and neighborhood). Removing these larger-scale errors often requires more careful

analysis of the root architecture, for example, to prevent breaking a root in the middle. We shall

address these remaining issues in the next step of our pipeline and with the help of a geometric

skeleton.

<u>Skeletonization</u>

To obtain the root hierarchy and associated traits, our method relies on a representation of the

root system as a curve skeleton - a connected set of curves lying in the center of the root

branches and capturing the branching structure. While there are many algorithms for computing

skeletons of 3D shapes, we adopt the methods of [36, 37] because of their scalability to high-

resolution iso-surfaces, robustness to noise, and the final representation as an embedded graph

(with vertices and edges) which is more convenient for connectivity analysis than voxel-based

skeletons. These methods have been previously adopted in skeleton-based phenotyping of

sorghum panicles [9]. Specifically, given the topologically simplified iso-surface produced by

the previous step, [37] computes a 2-dimensional centered structure known as the medial axis,

and [36] further reduces the medial axis to 1c-dimensional curves. The resulting skeleton is also

associated with shape attributes, including the thickness and the width of the tubular cross-

sections, which are useful in our subsequent analysis. An example is shown in Figure 4C (also in

Figure 7A).

Fig. 7

(A) (B) (C)

294
Removing cycles on the curve skeleton. (A) A curve skeleton computed by the methods of [36,
37], where color indicates the thickness of the roots (redder curves lie in thicker roots). (B) A
skeleton junction (in the boxed region in (A)) caused by merging between two roots in the iso-
surface, which leads to a cycle in the skeleton. (C) The cycle is removed by detaching a skeleton
segment from the junction.

As mentioned earlier, some topological errors remain after topological simplification. These

errors manifest as disconnected components and cycles (a path of edges which begin and end at

the same vertex) on the curve skeleton. To reduce the number of components to one, we simply

take the largest connected component on the skeleton. To remove cycles in that component, we

observe that cycles are usually caused by merging of distinct roots, which take place at junctions

(vertices with degree three or higher) on the skeletons (Figure 7B). Our goal is to identify

junctions that correspond to merging between roots, as opposed to natural branching of roots,

and resolve the cycles by detaching skeleton segments from such junctions (Figure 7C). This is

achieved by computing the minimum spanning tree (MST) on a weighted graph, as described

below.

As we are primarily concerned with the junctions of the skeleton, we construct an abstract graph

where each node represents either a junction vertex or a continuous skeleton segment between

junctions (Figure 8A, 8B). A graph edge connects a node representing a skeleton junction with

another node representing a skeleton segment incident to the junction. Removing a graph edge

corresponds to detaching a skeleton segment from a junction (Figure 8C, 8D).

Fig. 8

(A)   (B)   (C)   (D)

Illustration of our cycle-breaking algorithm. (A) A curve skeleton (red) of a synthetic root
system (blue) that contains a cycle. (B) A graph that represents each skeleton junction or
segment by a node (yellow circle) and connects two nodes representing a junction and an
incident segment by an edge (black line).   is a graph edge,   is the node   that represents a
skeleton junction,   the other node of   which represents a skeleton segment, and is the unit
vector of the tangent direction of the skeleton segment represented by node   towards the
junction node   . (C) The MST of the graph removes the cycle by excluding an edge (green
box). (D) The corresponding skeleton segment is detached from the skeleton junction.

The MST is the subset of edges such that all graph nodes remain connected and the sum of edge

weights is minimal. An MST is always free of cycles. We define the edge weights such that a

lower weight implies a higher likelihood that a skeleton segment should be attached to a

junction. Our weight definition is motivated by the observation that a merging between two

distinct roots often results in a "T" junction on the skeleton where, among all skeleton segments

incident to the junction, one segment (which should be detached) is close to being orthogonal to

the other segments (see Figure 8B). In contrast, a typical branching of the root usually results in

a "Y" junction on the skeleton where each skeleton segment at the junction forms an obtuse

angle with at least one other segment. However, branching close to the stem of the root could be

more like "T" than "Y", due to the large difference in thickness between the main and offspring

roots. Our weight encourages "Y" junctions while preventing detachment close to the stem.

Specifically, let e be a graph edge, v_e the node of the edge e that represents a skeleton junction,

u_e the other node of e which represents a skeleton segment, and $E(v)$ the set of edges incident to

node v. We denote by $\bar{e}$ the unit vector of the tangent direction of the skeleton segment

represented by node u_e *towards* the junction node v_e. We first define the angle deviation term

w_{angle} as:

$$w_{angle}(e) = \min_{e' \in E(v_e), e' \neq e} \left(2 - \left(1 + \bar{e} \cdot \bar{e'}\right)\right).$$

This term reaches the minimal value of 0 when there is some edge e' incident to v_e that has the

same direction as e, and it attains the maximal value of 2 when all other edges incident to v_e

have the opposite direction as e. Next, we define $w_{dis}(e)$ as the shortest distance along the

skeleton between the skeleton junction represented by v_e and any skeleton vertex in the stem.

Here, we extract the stem from the skeleton using the heuristic reported in [9]. The heuristic

starts from a subset of the skeleton whose thickness measure is above a threshold (since the stem

is usually the thickest portion of the maize root system) and extracts the longest simple path from

the subset. Finally, the edge weight is defined as:

$$w(e) = \lambda w_{dis}(e) + w_{angle}(e).$$

Here λ is a balancing parameter, which is set to 0.05 in our experiments.

Inferring hierarchy

Fig. 9

(A) (B) (C)

354
Heuristic for inferring hierarchy on a cycle-free skeleton. (A) The input skeleton with only the
stem region labelled (blue). (B) The first stage associates each parent segment with one of its
children segments (indicated by arrows). The numbers are the depth stored at each segment, an
intermediate quantity used to determine the parent-child association. (C) The second stage
assigns hierarchy levels to each skeleton segment based on the parent-child association.

A key feature of TopoRoot is computing the hierarchy of the maize root system consisting of the

stem, nodal roots, and lateral roots at different levels. Given the cycle-free skeleton computed

from the previous steps, we next label each vertex of the skeleton as either part of the stem path,

the stem region, a nodal root, or a lateral root at a specific level. As described in the previous

step, the stem path is identified using the thickness-based heuristic of [9]. The stem region is then

defined as the set of skeleton edges within a cylindrical region around the skeleton path, where

the radius of the cylinder varies along the stem path and is set to be 1.6 times the thickness

measure stored on the path vertices. In Figure 4D, the stem path and stem region are colored dark

blue.

To label the remaining skeleton edges by the root hierarchy (e.g., nodal roots, 1st-order lateral

roots, 2nd-order lateral roots, etc.), we make the following two assumptions. First, as assumed in

previous works including DynamicRoots, roots at lower levels of the hierarchy are generally

longer. For example, nodal roots are generally longer than lateral roots, and 1st-order lateral

roots are generally longer than 2nd-order lateral roots, and so on. Second, the maximum number

of hierarchy levels in a root system is generally kept low. With these assumptions, we developed

a labelling heuristic that minimizes the maximal level of hierarchy in the root system while

encouraging longer roots to be at lower levels.

Our heuristic proceeds in two stages, a bottom-up traversal of the skeleton and then a top-down

traversal. They are illustrated in Figure 9 using a cartoon example. We start with a skeleton

labelled only by the stem region (Figure 9A). Since the skeleton has no cycles, it is a "tree". We

consider the stem region as the "root" of this tree, and this induces a partial ordering of the

skeleton segments such that each skeleton junction (outside the stem region) is incident to

exactly one *parent* segment and zero or more *children* segments. The first stage of the heuristic

computes, at each skeleton junction, the association between the parent skeleton segment with

one of the children segments as the continuation of the same root (see arrows in Figure 9B). The

association is computed by visiting the skeleton segments from the leaves of the skeleton

towards the stem and updating a depth *d(b)* (numbers in Figure 9B) and a distance *l(b)* at each

visited segment b, as follows. First, for each segment b incident to a leaf vertex of the skeleton,

we set *d(b)=0* and *l(b)* as the length of the segment b. We then iteratively visit parent segments

whose children segments have already been visited. For a parent segment b whose children are

$b_1, \ldots, b_n$, we associate b with the child b_i that has the maximal depth $d(b_i)$. If multiple children

have the same maximal depth, b is associated with the b_i with maximal length $l(b_i)$. We then set

d(b)=d(b_i)+1 and *l(b)* to be *l(b_i)* plus the length of segment b. In the second stage, we visit all

segments from the stem to the leaves and assign the hierarchy levels. We assign each segment

attached to the stem region a hierarchy level of 1 (i.e., nodal roots). For each parent segment

assigned with level k, we assign level k to the child segment associated with the parent

(computed from the first stage) and level $k + 1$ to all other children segments. The resulting

hierarchy labelling is shown in Figure 9C both as numbers and the heat color (warmer colors

have higher levels).

<u>Computing traits</u>

Given the skeleton and the hierarchy labelling, TopoRoot computes a suite of coarse-grained and

fine-grained traits of the root system. Like existing works (e.g. [33]), we compute global traits

which are aggregated over all the hierarchy levels, including the total root length, number of

roots, and average root length. For fine-grained traits, for each hierarchy level (e.g., nodal roots,

1st-order lateral roots, 2nd-order lateral roots, etc.), we compute the root count, average and total

root length, average root tortuosity, average root thickness, average number of children, and the

average emergence, midpoint, and tip angle. We also report the length and thickness of the stem.

Some of these traits, such as stem length and per-level angle traits, have not been previously

reported by existing tools (including DynamicRoots [32]). Details on how each of these traits is

computed can be found in supplementary table 1.

Results

We validated TopoRoot on the aforementioned dataset and compared it with some previous

tools, including DynamicRoots [32] (for both global and fine-grained traits) and a 3D version of

GiaRoots [4] first published in [33] (for global traits only). We used default parameters for both

DynamicRoots and GiaRoots. DynamicRoots requires a "seed" voxel, which we set as a random

voxel from the top slice. We ran DynamicRoots and GiaRoots on the thresholded images at the

shape threshold. To illustrate the effect of topological errors on these tools, we extend each tool

by first performing the topological simplification step of TopoRoot. We call the extended tools

DynamicRoots+ and GiaRoots+ respectively. TopoRoot is implemented in C++, and all

experiments were run on a Windows 10 machine with an Intel(R) Core(TM) i9-10900X

Processor @ 3.70 GHz and 64.0 GB of memory (RAM).

<u>Excavated root crowns</u>

First, we visually compare the root hierarchies computed by TopoRoot, DynamicRoots, and

DynamicRoots+ for a randomly picked root crown (Figure 10). DynamicRoots produces a point

cloud where each point represents an input voxel and is labelled by its hierarchy level (0, 1, 2,

etc.). As explained in [32], the hierarchy levels produced by DynamicRoots reflect the geometric

branching structure and may not map well to the biological hierarchy (e.g., stem, nodal roots,

lateral roots, etc.). For this reason, as well as the inaccuracy in determining hierarchy without a

dense time series and the different morphology of mature root crowns in our dataset from those

of seedlings grown in a gel environment (for which DynamicRoots was designed),

DynamicRoots tends to produce significant mis-classifications of root branches in our dataset.

For example, the level-0 roots obtained by DynamicRoots include not only the stem but quite a

few nodal roots (black boxes). These errors propagate to higher-level roots, which fork from

lower-level roots. In addition, since the thresholded root image at the shape threshold contains

many disconnected components, and because DynamicRoots only considered one connected

component, a significant portion of the root is missing in the analysis of DynamicRoots (red

box). Although performing the topological simplification step in TopoRoot allows

DynamicRoots+ to recover a more complete root system, mis-labelling of hierarchy levels

remains (black boxes). In contrast, TopoRoot produces a more visually plausible hierarchy

separating the stem (region), nodal roots, and lateral roots.

Fig. 10

TopoRoot   DynamicRoots   DynamicRoots+

Visual comparison of root hierarchies computed by TopoRoot, DynamicRoots and
DynamicRoots+ from the X-ray CT scan of an excavated maize root crown. Hierarchy levels are
colored as follows: 0 (stem): dark blue, 1 (nodal roots): light blue, 2 (1st-order lateral roots):
green, 3 (2nd-order lateral roots): orange, 4 (3rd-order lateral roots): red, ≥ 5: dark red. Black
boxes highlight incorrect levels obtained by DynamicRoots and DynamicRoots+, and the red box
highlights a missing component in DynamicRoots.

Next, we quantitatively validate the nodal root counts computed by various tools against the

hand measurements. Figure 11 plots the correlation between the hand-measured nodal root

counts and those computed by TopoRoot (A), DynamicRoots (B) and DynamicRoots+ (C) for all

45 samples. Based on visual inspection (Figure 10), we consider the level 1 branches as nodal

roots for DynamicRoots+. For each sample we computed the relative error by taking the absolute

difference of TopoRoot's nodal root count and the hand measurement, and finding the

percentage of this difference relative to the hand measurements. We compute the mean and

standard deviation ( ) of this relative error for TopoRoot, DynamicRoots, and DynamicRoots+.

TopoRoot exhibits a much lower relative error (mean=8.3%,   5.6%) and higher correlation

(Pearson's coefficient=0.951) than either DynamicRoots (159.5% mean error with   190.0%,

Pearson's coefficient=-0.0452) or DynamicRoots+ (235.4% mean error with   244.4%,

Pearson's coefficient=-0.160). The significant over-counting of DynamicRoots+ is mostly

caused by the mislabeling of nodal roots as level-0 roots, as explained above, which leads to

many lateral roots being labelled as level-1 roots. The over-counting also increases with the size

of the root system. Furthermore, both the nodal root counts computed by TopoRoot and the hand

measurements exhibited a significant difference between the mutant and wild type samples, as

measured by the independent two-sided Wilcoxon rank sum test (p=0.000130 for TopoRoot,

p=0.00349 for hand measurements). Neither DynamicRoots (p=0.126) nor DynamicRoots+

(p=0.0199) showed a significant difference between the mutant and wild-type, and both had

negative Pearson coefficients. This shows that TopoRoot can perform better for differentiating

the root system architecture between these two varieties than can DynamicRoots.

Fig. 11

470
Correlation of nodal root count between hand and computational measurements. (A) Correlation

between TopoRoot and hand measurement. (B) Correlation between DynamicRoots and hand
measurement. (C) Correlation between DynamicRoots+ and hand measurement. Each dot in the
graph represents one of the 45 samples. Blue and red dots indicate wild type and mutant samples,
respectively. The regression line is in red, while the dashed green line indicates the ideal
correspondence between the hand and computational measurements. The correlation coefficient
ρ is indicated in each plot.

Since we do not have hand measurements of other fine-grained traits for this data set, we

perform an indirect evaluation by assessing the ability of each trait computed by TopoRoot in

differentiating the mutant and wild type samples. As shown in Figure 12, 12 out of the 23 fine-

grained traits computed by TopoRoot (reported up to the hierarchy level of the first-order lateral

roots) exhibit a significant difference between the two genotypes ($p<0.01$). Compared to the wild

type, the mutants generally have fewer and shorter thinner roots at each hierarchy, whereas the

various angle measures are greater. These fine-grained trait differences offer a more

comprehensive analysis of phenotypic differences caused by the mutation which better

characterizes gene function and may lead to novel biological investigations.

Fig. 12

Fine-grained traits computed by TopoRoot for wild type and mutant samples. Each boxplot
shows distribution bars for one trait over all 27 wild type samples and 18 mutants. Traits with
p<0.01, as measured by the independent two-sided Wilcoxon rank sum test, are highlighted in
red boxes.

Simulated Roots

We start with a visual comparison of the results of TopoRoot, DynamicRoots+ and GiaRoots+

on one of the simulated root systems. This root system is simulated to be 34 days old, with five

whorls, 34 nodal roots, and a lateral root branching frequency between 0.3 - 0.7 cm / branch.

Figure 13 visualizes the root hierarchies produced by TopoRoots and DynamicRoots+ as well as

the voxelized skeletons produced by GiaRoots+ at three different noise levels (0, 0.04cm,

0.08cm). As the noise level increases, the thresholded image at the shape threshold becomes

more disconnected and contaminated by topological errors (see Figure 13). Accordingly,

DynamicRoots and GiaRoots miss more root parts, whereas TopoRoot as well as the extended

tools, DynamicRoots+ and GiaRoots+, retain much of the root shape. Observe that, similar to the

real roots dataset, the hierarchies produced by DynamicRoots+ incorrectly label many nodal

roots as level 0 (black boxes). In contrast, the hierarchies produced by TopoRoot are more

visually plausible.

524 **Fig. 13**

525
Comparing hierarchies and skeletons computed by different tools from images of a simulated
maize root. Three different noise levels are shown. Hierarchy levels 0, 1, 2, 3 and 4 produced by
TopoRoot and DynamicRoots+ are colored dark blue, light blue, green, orange, and red. The
voxelized skeletons produced by GiaRoots+ are colored brown. Black boxes highlight
mislabeling of nodal roots as level 0 roots by DynamicRoots and DynamicRoots+.

We performed a thorough quantitative validation of all traits computed by TopoRoot against the

ground truth provided by OpenSimRoot. The relative error for each trait over the entire

simulated dataset, as well as the errors of DynamicRoots+ and GiaRoots+ (for global traits only),

are reported in Tables 1-4 for noise levels ≤ 0.04 cm and 0.08 cm. In supplementary Figures S1-

S4, we take a closer look at the accuracy of TopoRoot and the other tools as a function of the

noise level of the input images. These figures plot the relative errors of the five tools in

computing the stem traits (Figure S1), the nodal root traits (Figure S2), the lateral root traits

(Figure S3), and the global traits (Figure S4) as the noise level increases. Roots less than one

voxel long in the ground truth model were ignored in our analysis. We compare and analyze the

accuracy of TopoRoot across each category of traits below. In general, we observe that higher

image noise leads to larger mean errors and/or greater variance by TopoRoot. For most of the

traits, TopoRoot maintains a lower error than other tools across all noise levels.

As the base of the hierarchy, the stem traits are among the most accurate. As the noise increases,

portions of the stem region are lost, resulting in a thinner stem (Figure S1). Increased noise also

causes the stem to wiggle more in the direction perpendicular to its main path, resulting in an

increased stem length.

The nodal root traits (Table 2) are the most accurate for the root count (8.3% up to $e=0.04$,

10.3% up to $e=0.08$) and emergence and midpoint angles (5.7/7.1% up to $e=0.04$, 9.1/9.5% up to

$e=0.08$). The lowest accuracy is seen for the number of children (40.0% up to $e=0.04$, 48.6% up

to $e=0.08$) and thickness (39.2% up to $e=0.04$, and 38.2% up to $e=0.08$). These errors are due to

misclassifications when the nodal root becomes entangled with higher-order lateral roots.

TopoRoot slightly underestimates the average and total length due to faulty cycle breaking and

misclassification errors in portions of nodal roots further away from the stem. TopoRoot's error

in nodal root tortuosity is higher than that of DynamicRoots for two reasons. First, the ground

truth tortuosity is close to 1 (only for the simulated data, but not for the real maize roots), and

DynamicRoots coincidentally produces values close to this because it mistakes many shorter

lateral roots as nodal roots, as evidenced by its much shorter average nodal root length and the

black boxes of Figure 13. Second, nodal roots sometimes are misclassified by TopoRoot closer

to their tips due to the large number of intersections between roots of different hierarchy levels,

resulting in excessive winding. TopoRoot slightly overestimates angle measurements due to

misclassification errors further away from the stem which bend the detected paths sideways;

these explain the errors in the tip angle measurements.

563 The errors for the lateral root traits (Table 3) are generally larger than nodal root traits, primarily

564 since the imaging noise has a greater impact on the thinner roots more than the thicker ones.

565 There is a greater underestimation of both the total first-order lateral roots and their total length

566 (Figure S3), due to both the misclassification of the hierarchy levels and the loss of many thin

567 roots in the distance field. On the other hand, the misclassified first-order lateral roots are

568 counted as lateral roots of higher orders, and hence less errors lie in the total lateral root count

569 (22.2% up to e=0.04 and 37.0% up to e=0.08) and lengths (24.3% up to e=0.04 and 24.4% up to

570 e=0.08) over all orders. All methods significantly overestimate the first-order lateral root

571 thickness due to limits in the resolution, but TopoRoot produces the lowest error. The lowest

572 errors are seen in the first-order lateral emergence/midpoint/tip angles (3.4%/4.1%/5.4% up to

573 e=0.04 and 3.0%/4.0%/5.9% up to e=0.08) and tortuosity (4.6% up to e=0.04 and 4.5% up to

574 e=0.08).

576 Finally, combining nodal and lateral roots, TopoRoot produces on average 35.4% error (21.5%

577 up to e=0.04) in the total root count and 25.4% error (25.0% up to e=0.04) in the total root

578 length, which are much lower than DynamicRoots and GiaRoots (Table 4). Note that both

579 DynamicRoots and GiaRoots significantly underestimate the root count and total length, even

580 after topological simplification, and the amount of underestimation generally increases with the

581 level of noise (Figure S4). The only global trait that TopoRoot does not have the lowest error is

582 the average length, due to a combination of DynamicRoots being coincidentally closer due to its

583 underestimation of both the total length and number of roots, and TopoRoot having an excessive

584 number of roots at higher noise levels. These are the same reasons why the two methods have

585 similar lateral root average length errors.

586 **Table 1: Reporting the accuracy of TopoRoot for stem traits.**

Trait	≤ *e*	TopoRoot (%)
Stem length	0.04	6.9 (σ=6.9)
	0.08	7.7 (σ=7.3)
Stem thickness	0.04	11.9 (σ=4.3)
	0.08	15.3 (σ=5.8)

587 Each entry gives the average error (and standard deviation σ) for our method across all simulated
588 models and across all noise levels up to *e*=0.04 cm and 0.08 cm.
589
590 **Table 2: Comparing TopoRoot to DynamicRoots and DynamicRoots+ for nodal root traits.**

Trait	≤ *e*	TopoRoot (%)	DynamicRoots (%)	DynamicRoots+ (%)
Nodal root count	0.04	**8.3** (σ=8.2)	392.9 (σ=423.5)	486.2 (σ=426.6)
	0.08	**10.3** (σ=10.9)	263.9 (σ=367.0)	455.2 (σ=400.0)
Nodal root total length	0.04	**22.4** (σ=13.1)	46.4 (σ=17.7)	38.3 (σ=14.3)
	0.08	**23.9** (σ=13.7)	56.9 (σ=19.7)	40.7 (σ=14.6)
Nodal root average length	0.04	**17.8** (σ=11.2)	76.6 (σ=18.8)	80.9 (σ=16.1)
	0.08	**19.9** (σ=13.1)	74.0 (σ=17.4)	81.0 (σ=15.4)
Nodal root thickness	0.04	39.2 (σ=27.6)	**36.6** (σ=33.8)	46.2 (σ=115.0)
	0.08	**38.2** (σ=26.8)	50.1 (σ=150.3)	48.2 (σ=109.6)
Nodal root number of children	0.04	**36.4** (σ=21.6)	87.7 (σ=13.7)	89.4.5 (σ=12.5)
	0.08	**45.6** (σ=41.0)	87.0 (σ=13.1)	89.2 (σ=12.4)
Nodal root tortuosity	0.04	32.6 (σ=13.0)	2.3 (σ=2.5)	**2.0** (σ=1.8)
	0.08	37.3 (σ=13.8)	4.5 (σ=4.4)	**2.9** (σ=2.3)

Nodal root emergence angle	0.04	**5.7** (σ=11.9)	N/A	N/A
	0.08	**7.3** (σ=11.9)	N/A	N/A
Nodal root midpoint angle	0.04	**7.1** (σ=14.0)	N/A	N/A
	0.08	**9.1** (σ=13.8)	N/A	N/A
Nodal root tip angle	0.04	**18.3** (σ=17.7)	N/A	N/A
	0.08	**22.7** (σ=22.8)	N/A	N/A

591 Each entry gives the average error (and standard deviation *s*) for a method across all simulated
592 models and across all noise levels up to *e*=0.04 cm and 0.08 cm. For each trait, the method with
593 the lowest error is bold-faced.
594
595 **Table 3: Comparing TopoRoot to DynamicRoots and DynamicRoots+ for lateral root**
596 **traits.**
597

Trait	≤ *e*	TopoRoot (%)	DynamicRoots (%)	DynamicRoots+ (%)
1st-order lateral root count	0.04	**41.4** (σ=23.4)	75.6 (σ=11.3)	71.5 (σ=10.7)
	0.08	**49.0** (σ=41.5)	80.7 (σ=11.2)	71.9 (σ=10.3)
1st-order lateral root total length	0.04	**44.5** (σ=15.0)	71.9 (σ=13.9)	66.9 (σ=15.4)
	0.08	**47.0** (σ=15.9)	76.7 (σ=14.9)	67.4 (σ=14.9)
1st-order lateral root avg. length	0.04	**20.4** (σ=15.0)	38.1 (σ=74.6)	26.5 (σ=54.0)
	0.08	**25.6** (σ=19.2)	53.2 (σ=98.2)	26.0 (σ=52.3)
1st-order lateral root thickness	0.04	**355.0** (σ=85.8)	424.6 (σ=101.7)	439.2 (σ=104.2)
	0.08	**342.8** (σ=85.3)	427.7 (σ=112.0)	450.1 (σ=102.2)
1st-order lateral root	0.04	**68.3** (σ=34.7)	152.9 (σ=301.1)	115.6 (σ=192.7)

number of children	0.08	**80.7 (σ=50.0)**	180.9 (σ=319.7)	115.6 (σ=182.6)
1st-order lateral root tortuosity	0.04	**4.6 (σ=3.2)**	11.9 (σ=2.1)	12.1 (σ=1.8)
	0.08	**4.5 (σ=3.2)**	10.2 (σ=3.0)	11.3 (σ=2.0)
1st-order lateral root emergence angle	0.04	**3.4 (σ=2.4)**	N/A	N/A
	0.08	**3.0 (σ=2.2)**	N/A	N/A
1st-order lateral root midpoint angle	0.04	**4.1 (σ=2.7)**	N/A	N/A
	0.08	**4.0 (σ=2.7)**	N/A	N/A
1st-order lateral root tip angle	0.04	**5.4 (σ=6.4)**	N/A	N/A
	0.08	**5.9 (σ=7.3)**	N/A	N/A
Lateral root count	0.04	**22.2 (σ=19.5)**	60.6 (σ=13.0)	58.0 (σ=14.8)
	0.08	**37.0 (σ=56.1)**	66.8 (σ=12.4)	58.1 (σ=14.4)
Total lateral root length	0.04	**24.3 (σ=9.3)**	52.3 (σ=19.6)	50.9 (σ=19.0)
	0.08	**24.4 (σ=11.4)**	59.1 (σ=18.8)	56.0 (σ=17.8)
Average lateral root length	0.04	**20.2 (σ=14.8)**	21.2 (σ=22.4)	22.0 (σ=21.6)
	0.08	25.9 (σ=19.0)	21.4 (σ=22.9)	**20.6 (σ=20.2)**

598 Each entry gives the average error (and standard deviation *s*) for a method across all simulated
599 models and across all noise levels up to *e*=0.04 cm and 0.08 cm. For each trait, the method with
600 the lowest error is bold-faced.
601
602 **Table 4: Comparing TopoRoot to DynamicRoots, DynamicRoots+, GiaRoots, and**
603 **GiaRoots+ for global traits.**

Trait	≤ *e*	TopoRoot (%)	DynamicRoots (%)	DynamicRoots + (%)	GiARoots (%)	GiARoots+ (%)
Total root count	0.04	**21.5 (σ=18.4)**	53.7 (σ=11.1)	49.3 (σ=11.3)	57.9 (σ=13.7)	56.8 (σ=13.7)

	0.08	**35.4** (σ=51.8)	60.8 (σ=12.7)	49.7 (σ=11.3)	45.7 (σ=21.1)	57.5 (σ=13.2
Average root length	0.04	18.4 (σ=13.5)	9.1 (σ=11.8)	**9.7** (σ=9.8)	42.6 (σ=33.5)	50.2 (σ=35.3)
	0.08	24.7(σ=18.8)	**9.9** (σ=12.5)	13.3 (σ=12.2)	40.8 (σ=27.4)	55.6 (σ=34.2)
Total length	0.04	**25.0** (σ=8.5)	52.2 (σ=13.9)	48.7 (σ=13.1)	46.0 (σ=12.1)	40.1 (σ=12.1)
	0.08	**25.4** (σ=9.7)	59.6 (σ=14.5)	52.8 (σ=12.4)	45.7 (σ=19.6)	38.2 (σ=13.1)

604 Each entry gives the average error (and standard deviation *s*) for a method across all simulated
605 models and across all noise levels up to *e*=0.04 cm and 0.08 cm. For each trait, the method with
606 the lowest error is bold-faced.

Discussion

A gap exists in the phenotypic measure of root system architecture between fine-grained

analyses that can be conducted on entire seedling root systems in laboratory settings, and much

coarser global analyses available to field researchers. Since root systems are an emergent

property of their many hundreds, thousands, or tens of thousands of constituent roots, this gap is

a major hindrance to a comprehensive understanding of root system development, environmental

interaction, and the genetics that influence these processes. In previous work, we showed that

when global 3D analysis of field excavated maize root crowns was compared to 3D seedling

analysis in gellan gum, genetically encoded differences were consistent despite major differences

in developmental stage and the growth environment [17]. Whereas DynamicRoots was

previously developed for fine scale measurements of 3D seedling root systems containing dozens

to hundreds of roots, no similar tool existed for more complex mature root crowns, containing

hundreds to thousands of roots. The orders of magnitude of increased complexity motivated

unique solutions using both state-of-the-art techniques in computer graphics [38, 36, 37] and

novel algorithms which eventually led to the development of TopoRoot. While we consider this

first version as the foundation of several future planned advancements, discussed below, we were

able to present here unprecedented fine-grained analysis of complex 3D root systems (on average

943 total roots [maximum of 2514]), 78 nodal roots (maximum of 126), 865 lateral roots (all

classes combined; maximum of 2414) for the excavated maize roots, as computed by TopoRoot)

that facilitates "apples to apples" comparisons with existing seedling phenotyping pipelines.

Error analysis

The steps of our pipeline which are most prone to errors are topological simplification and

skeletonization. The amount and quality of the topological repairs depends on the choices of the

iso-values k, s, and n. If k and n are too close to s, then very little topological simplification will

occur. On the other hand, if k and n are too far away from s, then such an aggressive setting may

result in some topological features being removed in a geometrically suboptimal fashion. This is

because we use a setting of [38] which uses the image intensity as guidance to determine where

contents are added and removed from the iso-surface s, but these changes may not be smooth if

the image values are not reliable. For example, cycles may be cut in the middle of branches,

resulting in improper tracing of branches and potential double counting of the same root.

Another step of our pipeline which is prone to errors is the cycle breaking portion of

skeletonization. Decisions on where to break cycles rely on local angle continuity information

near junctions, as well as the distance from the stem. However, if a root continues across many

junctions where cycles pass through, then the root may accidentally be cut off early at one of

these junctions. Our pipeline is sensitive to the amount of soil remaining in the sample, because

soil often has a similar or higher intensity as the roots. If a large clump of soil is stuck onto the

root, it may result in a thick region which is mistakenly identified as part of the stem. This

problem can be avoided by thorough cleaning of samples prior to scanning, and by basic image

thresholding prior to TopoRoot analysis. The final contrast will affect the ideal choices for k and

n with respect to s; the greater the contrast, the smaller the gap between k and n need to be to

incur the same amount of topological simplification.

The quality of the topological repairs may be improved by considering not only the image

intensity when computing additions and removals of contents, but also incorporating geometric

criteria such as the tubularity of a region to identify it as part of a root. This will allow for a

greater amount of topological simplification without sacrificing geometric optimality. The

suboptimal local decisions of cycle-breaking may be potentially improved by grouping cutting

decisions together to produce a collective score. These groups can gradually be built from the

bottom-up to produce a more globally optimal solution.

<u>Running time</u>

On average, TopoRoot completes in 7 minutes and 13 seconds for each sample in the CT scan

dataset (downsampled by a factor of 4 to the resolution of 369 x 369 x 465). Since this is much

shorter than the time spent imaging and reconstructing one sample, TopoRoot is well suited for

high-throughput analysis. The computation time is dominated by the first two steps, topological

simplification (3 minutes and 6 seconds) and skeletonization (3 minutes and 44 seconds). The

time complexity of both these steps may increase quickly with the image resolution. For

example, running TopoRoot on the original CT volumes downsampled by a factor of 2 (instead

of 4 as used in our validation), which results in volumes of resolution 737 x 737 x 931, would

take 63 minutes and 39 seconds, with 32 minutes and 25 seconds spent on topological

simplification and 29 minutes and 9 seconds on skeletonization. On the other hand, we have not

observed a notable improvement in the accuracy of the nodal root count for this data set by

reducing the downsampling factor from 4 to 2.

Extensions

Fig. 14

672   (A)   (B)   (C)

Hierarchies of sorghum roots computed by TopoRoot. The examples have (A) one tiller (B) two
tillers and (C) four tillers. Hierarchy levels 0, 1, 2, 3 and 4 are colored dark blue, light blue,
green, orange, and red.

In addition to the per-level traits reported in this work, the hierarchy obtained by TopoRoots

potentially enables computation of other fine-grained traits. For example, we are currently

exploring the use of the hierarchy for computing whorls and the soil plane, which would in turn

enable computation of traits such as inter-whorl distances, per-whorl measurements, and the

numbers of nodal roots above and below the soil. Preliminary experiments show promising

results of whorl detection by clustering the nodal roots along the stem. The soil plane can be

potentially identified where a large cluster of 1st-order lateral roots appear along the direction of

the stem.

While TopoRoot is designed for and validated on X-ray CT scans of excavated maize root

crowns, the tool can be potentially adapted to other types of root systems and imaging

modalities. For root crowns with multiple tillers (e.g., sorghum), we offer a mode of TopoRoot

which extends the stem-detection heuristic (during the skeletonization step) by producing a stem

path within each region of the skeleton above a given thickness threshold. Preliminary visual

experiments show that TopoRoot's multiple-tiller mode produces plausible hierarchies at a

quality similar to that seen in the single-tiller mode (Figure 14). Further expanding the stem-

detection heuristic to identify the primary root would make the pipeline applicable to taprooted

systems as well. TopoRoot should work equally well for fine-grained analysis of 3D root system

architecture reconstructions derived from in situ imaging methods such as X-ray CT, MRI, and

optical imaging, provided they are first segmented from background (primarily soil and pot).

Segmentation can be done using a variety of methods such as region-growing [1], tracking

tubular features [26; 22], deep learning [29, 30], and semi-automatic annotation [3, 6]. Note that

some of these methods produce a binary volume (e.g., region-growing) whereas others produce a

probability density field (e.g., deep learning). Since TopoRoot requires a gray-scale intensity

volume with three thresholds (shape, kernel and neighborhood), a binary segmentation will first

need to be converted into a Euclidean distance field.

Software availability

TopoRoot is available for free at: https://github.com/danzeng8/TopoRoot

Included in the page are instructions to run the software, and details on the formats of the input

and output. Currently, the accepted inputs are either image slices (suffixed with .png) or .raw

files, with a .dat accompanying the .raw file to specify the dimensions. TopoRoot is currently

configured to build and run on Windows 10 machines, and has not been tested on other

platforms. We plan on releasing a Linux build of TopoRoot in the future. A graphical user

interface is also available on the page for visualizing the output hierarchy.

Conclusions

We introduced TopoRoot, a high-throughput method for computing the root hierarchy and fine-

grained root traits from a 3D image. TopoRoot specifically addresses topological errors, which

are common in 3D imaging and segmentation and are barriers for obtaining accurate root

hierarchies. Our method combines state-of-the-art methods developed in computer graphics with

customized heuristics to compute a wide variety of traits at each level of the root hierarchy.

When tested on both 3D scans of excavated maize root crowns and simulated root systems with

artificially added noise, TopoRoot exhibits higher accuracy than existing tools (DynamicRoots

and GiaRoots) in both coarse-grained and fine-grained traits. Furthermore, the efficiency and

automation of TopoRoot makes it ideal for a high-throughput analysis pipeline, and the results

are readily compatible with the Root System Markup Language (RSML;[13]), and major plant

structural-functional modelling frameworks such as CRootBox [25] and OpenSimRoot [24].

List of Abbreviations

722 **RSA:** Root system architecture

723 **CT:** Computed Tomography

Declarations

<u>Ethics approval and consent to participate</u>

Not applicable

<u>Consent for publication</u>

Not applicable

<u>Availability of data and materials</u>

The datasets generated and analysed during the current study are available in the TopoRoot

Github repository: https://github.com/danzeng8/TopoRoot

<u>Competing interests</u>

The authors declare that they have no competing interests.

<u>Funding</u>

This material is based upon work supported by the National Science Foundation under award

numbers DBI-1759836, DBI-1759807, DBI-1759796, EF-1971728, CCF-1907612, CCF-

2106672, and IOS-1638507. DZ is funded in part by an Imaging Sciences Pathway Fellowship

from Washington University in St. Louis.

<u>Authors' Contributions</u>

DZ was the primary developer and coder of TopoRoot. DZ wrote the manuscript with

contributions from TJ, CNT, NJ, ML, EC, DL, YJ, and HS. DZ, TJ, and CNT designed the study

and experiments. DZ performed experiments and analyzed the data. YJ developed the graphical

user interface with contributions from DZ. All authors have read and approved the final

manuscript.

<u>Acknowledgements</u>

We would like to thank Tiffany Hopkins, Dhineshkumar Thiruppathi, Elisa Morales, Mitchell

Sellers, Shayla Gunn, August (Gus) Thies, Keith Duncan, and Tim Parker (Donald Danforth

Plant Science Center) for the planting, harvesting, imaging, and collection of hand measurements

on maize roots, and Gustavo Gratacos (Washington University) and Yajie Yan (Facebook) for

their valuable insights on the cycle breaking algorithm and geometric skeleton computation. We

thank Mon-Ray Shao (Donald Danforth Plant Science Center) for the discussion on future

applications to sorghum and other species.

<u>Authors' information</u>

Affiliations

Department of Computer Science and Engineering, Washington University in St. Louis, St.

Louis, USA

Dan Zeng, Tao Ju, Yiwen Ju

Donald Danforth Plant Science Center, St. Louis, USA

Christopher Topp, Mao Li, Ni Jiang

Department of Computer Science, Saint Louis University, St. Louis, USA

Erin Chambers, David Letscher, Hannah Schreiber

<u>References</u>

1. Blaser S, Schluter S, Vetterlein D. How much is too much? - Influence of X-ray dose

on root growth of faba bean (Vicia faba) and barley (Hordeum vulgare). PLoS ONE.

2018;13(3).

2. Dorlodot SD, Forster B, Pages L, Price A, Tuberosa R, Draye X. Root system

architecture: opportunities and constraints for genetic improvement of crops. Trends in

plant science. 2007;12(10):474-81.

3. Flavel RJ, Guppy CN, Rabbi SMR, Young IM (2017) An image processing and analysis

tool for identifying and analysing complex plant root systems in 3D soil using non-

destructive analysis: Root1. PLoS ONE 12(5).

4. Galkovskyi T, Mileyko Y, Bucksch A, Moore B, Symonova O, Price CA, et al. GiA

Roots: software for the high throughput analysis of plant root system architecture.

BMC Plant Biology. 2012;69:237-43.

5. Gao W, Schluter S, Blaser SRGA, Shen J, Vetterlein D. A shape-based method for

automatic and rapid segmentation of roots in soil from X-ray computed tomography

images. Plant and Soil. 2019;441:643-655.

6. Gerth S, Clauben J, Eggert A, Wörlein N, Waininger M, Wittenberg T, Uhlmann N.

Semiautomated 3D Root Segmentation and Evaluation Based on X-Ray CT Imagery.

Plant Phenomics. 2021.

7. Gonzalez D, Postma J, Wissuwa M. Cost-Benefit Analysis of the Upland-Rice Root

Architecture in Relation to Phosphate: 3D Simulations Highlight the Importance of S-

Type Lateral Roots for Reducing the Pay-Off Time. Frontiers in Plant Science.

2021;12(359).

8. Koevoets IT, Venema JH, Elzenga JTM, Testerink C. Roots withstanding their

environment:

exploiting root system architecture responses to abiotic stress to improve crop

tolerance. Trends in plant science. 2016;7:1335.

9. Li M, Shao MR, Zeng D, Ju T, Kellogg EA, Topp CN. Comprehensive 3D phenotyping reveals

continuous morphological variation across genetically diverse sorghum inflorescences. New

Phytologist. 2020;226:1873-85.

10. Lynch J. Root architecture and plant productivity. Plant physiology. 1995; 109(1):7-13.

11. Lynch J. Rightsizing root phenotypes for drought resistance. Journal of Experimental

Botany. 2018;69(13):3279-3292.

12. Liu S., Barrow CS, Hanlon, M, Lynch JP, Buksch A. DIRT/3D: 3D root phenotyping for

field-grown maize (Zea mays). Plant Physiology. 2021.

13. Lobet, G, Pound, MP, Diener, J, Pradal, C, Draye, X, Godin, C, Javaux, M, Leitner, D,

Meunier, F, Nacry, P, Pridmore, TP, and Schnepf, A. (2015). Root system markup

language: toward a unified root architecture description language. Plant Physiol.

167:617–627.

14. Mairhofer S, Zappala S, Tracy SR, Sturrock C, Bennett M, Mooney SJ, et al.

RooTrak:Automated Recovery of Three-Dimensional Plant Root Architecture in Soil

from X-Ray Microcomputed Tomography Images Using Visual Tracking. Plant

Physiology. 2012;158(2):561-9.

15. Mooney SJ, Pridmore TP, Helliwell J. Developing X-ray Computed Tomography to non-

invasively image 3-D root systems architecture in soil. Plant Soil. 2012;352:1-22.

16. Jenkins, MT. Heritable Characters of Maize XXXIV—Rootless. J. Hered. 1930.21:79–

80.

17. Jiang N, Floro E, Bray AL, Laws B, Duncan KE, Topp CN, Three-Dimensional Time-

Lapse Analysis Reveals Multiscale Relationships in Maize Root Systems with

Contrasting Architectures. The Plant Cell. 2019 Aug;31(8):1708–1722.

18. Oswald SE, Totzke C, Haber-Pohlmeier S, Pohlmeier A, Kaestner AP, Lehmann E.

Combining Neutron and Magnetic Resonance Imaging to Study the Interaction of Plant

Roots and Soil. Physics Procedia. 2015;69:237-43.

19. Paez-Garcia A, Motes CM, Scheible WR, Chen R, Blancaflor EB, Monteros MJ. Root

Traits and Phenotyping Strategies for Plant Improvement. Plants. 2015;4(2):334-55.

20. Perret JS, Al-Belushi ME, Deadman M. Non-destructive visualization and quantification

of roots using computed tomography. Soil Biology and Biochemistry. 2007;39(2):391-9.

21. Pfeifer J, Kirchgessner N, Colombi T, Walter A. Rapid phenotyping of crop root systems

in undisturbed eld soils using X-ray computed tomography. Plant Methods. 2015;11(41).

22. Phalempin, M., Lippold, E., Vetterlein, D., and Schlüter, S. (2021). An improved method

for the segmentation of roots from X-ray computed tomography 3D images: Rootine v.2.

Plant Methods. 17(39).

23. Piñeros MA, Larson BG, Shaff JE, Schneider DJ, Falcão AX, Yuan L, Clark RT, Craft

EJ, Davis TW, Pradier PL, Shaw NM, Assaranurak I, McCouch SR, Sturrock C, Bennett

M, Kochian LV. Evolving technologies for growing, imaging and analyzing 3D root

system architecture of crop plants. J Integr Plant Biol. 2016 Mar;58(3):230-41.

24. Postma JA, Kuppe C, Owen MR, Mellor N, Griffiths M, Bennett MJ, Lynch JP, Watt M.

OpenSimRoot: widening the scope and application of root architectural models. New

Phytologist. 2017;215:1274–1286.

25. Schnepf, A, Leitner, D, Landl, M, Lobet, G, Mai, TH, Morandage, S, Sheng, C, Zörner,

M, Vanderborght, J, and Vereecken, H CRootBox: a structural-functional modelling

framework for root systems. Ann. Bot. 2018.

26. Schulz, H, Postma JA, van Dusschoten D, Scharr H, Behnke S. 3D reconstruction of

plant roots from MRI images. In Proc. Internat. Conf. Comput. Vision Theory and

Applications (VISAPP) 2012.

27. Schulz H, Postma JA, van Dusschoten D, Scharr H, Behnke S. Plant Root System

Analysis from MRI Images. In: Csurka G, Kraus M, Laramee RS, Richard P, Braz J,

editors. Computer Vision, Imaging and Computer Graphics. Theory and Application.

Berlin, Heidelberg: Springer Berlin Heidelberg; 2013;411-25.

28. Shao MR, Jiang N, Li M, Howard A, Lehner K, Mullen JL, Gunn SL, McKay JK, Topp

CN. Complementary Phenotyping of Maize Root Architecture by Root Pulling Force and

X-Ray Computed Tomography. bioRxiv 2021. doi: 10.1101/2021.03.03.433776

29. Smith, A.G., Petersen, J., Selvan, R. et al. Segmentation of roots in soil with U-Net. Plant

Methods. 2020;16(13).

30. Soltaninejad, M, Sturrock, CJ, Griffiths, M, Pridmore, TP, and Pound, MP. Three

Dimensional Root CT Segmentation using Multi-Resolution Encoder-Decoder Networks.

IEEE Trans. Image Process. 2020.

31. Strock CF, Burridge J, Massas ASF, Beaver J, Beebe S, Camilo SA, et al. Seedling root

architecture and its relationship with seed yield across diverse environments in Phaseolus

vulgaris. Field Crops Research. 2019;237:53-64.

32. Symonova O, Topp CN, Edelsbrunner H. DynamicRoots: A Software Platform for the

Reconstruction and Analysis of Growing Plant Roots. PLoS ONE. 2015;10(6).

33. Topp, CN et al. 2013. 3D phenotyping and quantitative trait locus mapping identify core

regions of the rice genome controlling root architecture. Proc. Natl. Acad. Sci. U. S. A.

110:E1695–E1704.

34. Trachsel, S, Kaeppler, SM, Brown, KM, Lynch JP. Shovelomics: high throughput

phenotyping of maize (Zea mays L.) root architecture in the field. Plant Soil.

2011;341;75–87.

35. Xu J, Barbič J. Signed Distance Fields for Polygon Soup Meshes. In Proceedings of

Graphics Interface 2014.

36. Yan Y, Sykes K, Chambers E, Letscher D, Ju T. Erosion Thickness on Medial Axes of

3D Shapes. ACM Trans Graph. 2016; 35(4).

37. Yan Y, Letscher D, Ju T. Voxel Cores: Efficient, Robust, and Provably Good

Approximation of 3D Medial Axes. ACM Trans Graph. 2018 Jul;37(4).

38. Zeng D, Chambers E, Letscher D, Ju T. To cut or to fill: a global optimization approach

to topological simplification. ACM transactions on graphics; 39(6).

39. Zheng Y, Gu S, Edelsbrunner H, Tomasi C, Benfey P. Detailed reconstruction of 3D

plant root shape. In Proc. 13th Internat. Conf. Comput. Vision 2011;2026–2033.

Supplementary Information

Supplementary Table 1: TopoRoot's computed traits

Groups	Trait	Description
Global traits	Total length	Sum of the lengths of stem, nodal roots, and lateral roots.
	Number of roots	Total number of roots across all hierarchy levels.
	Average length	Total length divided by number of roots.
Stem traits	Average stem thickness	Average thickness of the vertices along the stem path.
	Stem length	Length of the stem path.
Per-level traits	Level n root count	The number of level n roots.
	Total level n root length	Sum of the lengths of level n roots. The length is the skeleton distance from the beginning of the root to its tip.
	Average level n root length	Total level n root length divided by level n root count.
	Level n root tortuosity	Length of a root (skeleton distance) divided by the Euclidean distance from the beginning to the tip, averaged across all level n roots.
	Level n root thickness	Thickness associated with the skeleton vertices in the root, averaged across all level n roots.
	Number of level n root children	Number of level 2 roots divided by number of level 1 roots.
	Level n root tip angle	Angle between the stem direction and the vector from the beginning to the tip of a root, averaged across all level n roots.
	Level n root emergence angle	Angle between the stem direction and the vector from the beginning to 30 vertices along the skeleton of a root, averaged across all level n roots.

	Level n root midpoint angle	Angle between the stem direction and the vector from the beginning of a root to the halfway point of the root, averaged across all level n roots.
Aggregated lateral root traits	Total lateral length	Sum of the lengths of lateral roots whose hierarchy level is greater than or equal to 2.
	Number of lateral roots	Number of lateral roots whose hierarchy level is greater than or equal to 2.
	Average lateral root length	Average length of lateral roots whose hierarchy level is greater than or equal to 2.

872   **Supplementary Fig. S1**

873   (a)   (b)
874   Evaluating the accuracy of computing stem traits by TopoRoot. The tan line represents the
875   ground truth, and the result of TopoRoot is computed as a percentage of the ground truth.
876

887 **Supplementary Fig. S2**

(a) (b) (c)

(d) (e) (f)

(g) (h) (i)

888 ■ TopoRoot ■ DynamicRoots ■ DynamicRoots+

889 Comparing the accuracy of computing nodal root traits between TopoRoot, DynamicRoots, and
890 DynamicRoots+ across 55 models. The tan line represents the ground truth, and the results of all
891 methods are computed as a percentage of the ground truth.

903 **Supplementary Fig. S3**

Comparing the accuracy of computing lateral root traits between TopoRoot, DynamicRoots, and DynamicRoots+ across 55 models. The tan line represents the ground truth, and the results of all methods are computed as a percentage of the ground truth.

Supplementary Fig. S4

910
911   Comparing the accuracy of computing global traits between TopoRoot, DynamicRoots,
912   DynamicRoots+, GiaRoots, and GiaRoots+ across 55 models. The tan line represents the ground
913   truth, and the results of all methods are computed as a percentage of the ground truth.

(A)   (B)

No Noise (e = 0 cm)   e = 0.04 cm   e = 0.08 cm

Neighborhood (*n*)　　　　　Shape (*s*)　　　　　Kernel (*k*)

Input: 3D Grayscale Image

(A)

Topologically simplified
iso-surface

(B)

Skeleton representing
branching structure

(C)

Hierarchy

(D)

(A)   (B)   (C)

(A)   (B)   (C)

(A)   (B)   (C)   (D)

TopoRoot   DynamicRoots   DynamicRoots+

Noise level (cm): TopoRoot | DynamicRoots | DynamicRoots+ | GiaRoots | GiaRoots+

0.04

0.08

(A)   (B)   (C)