Invariant neural dynamics drive commands to control different movements

Vivek R. Athalye[1]†, Preeya Khanna[2]†, Suraj Gowda[4], Amy L. Orsborn[3], Rui M. Costa[1]*‡, and Jose M. Carmena[4,5,6]*‡

[1] Zuckerman Mind Brain Behavior Institute, Departments of Neuroscience and Neurology, Columbia University; New York, NY, USA

[2] Department of Neurology, University of California, San Francisco; San Francisco, CA, USA

[3] Departments of Bioengineering, Electrical and Computer Engineering, University of Washington, Seattle; Seattle, WA, USA

[4] Department of Electrical Engineering and Computer Sciences, University of California, Berkeley; Berkeley, CA, USA

[5] Helen Wills Neuroscience Institute, University of California, Berkeley; Berkeley, CA, USA

[6] UC Berkeley-UCSF Joint Graduate Program in Bioengineering, University of California, Berkeley; Berkeley, CA, USA

†These authors contributed equally to this work.

‡Senior author

*Corresponding author. Email: rc3031@columbia.edu (RMC); jcarmena@berkeley.edu (JMC)

Summary: It has been proposed that the nervous system has the capacity to generate a wide variety of movements because it re-uses some invariant code. Previous work has identified that dynamics of neural population activity are similar during different movements, where dynamics refer to how the instantaneous spatial pattern of population activity changes in time. Here we test whether invariant dynamics of neural populations are actually used to issue the commands that direct movement. Using a brain-machine interface that transformed rhesus macaques' motor cortex activity into commands for a neuroprosthetic cursor, we discovered that the same command is issued with different neural activity patterns in different movements. However, these different patterns were predictable, as we found that the transitions between activity patterns are governed by the same dynamics across movements. These invariant dynamics are low-dimensional, and critically, they align with the brain-machine interface, so that they predict the specific component of neural activity that actually issues the next command. We introduce a model of optimal feedback control that shows that invariant dynamics can help transform movement feedback into commands, reducing the input that the neural population needs to control movement. Altogether our results demonstrate that invariant dynamics drive commands to control a variety of movements, and show how feedback can be integrated with invariant dynamics to issue generalizable commands.

39 **Keywords:** neural population dynamics, motor cortex, motor control, brain-machine interfaces,
40 neuroprosthetics, optimal feedback control, motor commands, movement representations,
41 dynamical systems

Introduction

Our brain can generate a vast variety of movements. It is believed that the brain would not have such capacity if it used separate populations of neurons to control each movement. Thus, it has been proposed that the brain's capacity to produce different movements relies on re-using the dynamics of a specific neural population's activity [1–3]. While theoretical work shows how dynamics emerge from neural activity transmitted through recurrent connectivity[1,4–6], it has been elusive to identify whether the brain re-uses dynamics to actually control movements.

Recent work on the motor cortex, a region that controls movement through direct projections to the spinal cord [7] and other motor centers [8–10], has found that population dynamics are similar across different movements. Specifically, the spatial pattern of population activity at a given time point (i.e. the instantaneous firing rate of each neuron in the population) systematically influences what spatial pattern occurs next. Models of dynamics h that are invariant across movements[3] can predict the transition from the current population activity pattern x_t to the subsequent pattern x_{t+1}:

$$x_{t+1} = h(x_t) + \text{input}_t + \text{noise}_t \tag{1}$$

where external input input_t and noise noise_t are typically unmeasured. Recent work[11] has provided the intuition that invariant dynamics bias neural activity to avoid "tangling" – which is when the same activity pattern undergoes different transitions in different movements. These dynamics models have explained features of neural activity that were unexpected from behavior [11–14] such as oscillations[12], and have predicted neural activity during different movements on single trials [15–18], for single neurons' spiking [15], for local field potential features [19,20], and over many days [18,21]. These models also help predict behavior [16,18,19,22].

While past work characterized the statistical relationship between invariant dynamics and

behavior, it remains untested if invariant dynamics are actually used to issue commands for

movement. This test requires identifying the causal transformation from neural activity to

command, where the "command" is the instantaneous influence of the nervous system on

movement. This is a long-standing challenge in motor control. While past work has modeled this

transformation[23–25], ongoing research reveals its complexity[8–10,26–28].

We addressed this challenge with a brain-machine interface (BMI) [29–32] in which the

transformation from neural activity to command was known exactly and determined by the

experimenter. We trained rhesus monkeys to use motor cortex population activity to move a two-

dimensional computer cursor on a screen through a BMI. The BMI transformed neural activity

into a force-like command to update the cursor's velocity, analogous to muscular force on the

skeleton. Thus, an individual movement was produced by a series of commands, where each

command acted on the cursor at an instant in time.

We discovered that the same exact command is issued with different neural activity

patterns in different movements. Critically, these different patterns transition according to low-

dimensional, invariant dynamics to patterns that issue the next command, even when the next

command differs across movements. Thus, our results demonstrate that invariant dynamics drive

commands to control different movements.

While past work has presented a view of how dynamics operate in a feedforward manner,

propagating an initial state of activity [23,33,34] to produce movement, it has been unclear how

feedback[24,35–37] integrates with invariant dynamics. Given that motor cortex is interconnected to

larger motor control circuits including cortical[38–41] and cortico-basal ganglia-thalamic

circuits[8,9,42,43], we introduce a hierarchical model[44] of optimal feedback control (OFC) in which

the brain (i.e. larger motor control circuitry) uses feedback to control the motor cortex population

which controls movement[45,46]. Our model reveals that invariant dynamics can help transform

feedback into commands, as they reduce the input that a population needs to issue commands.

Altogether, our results demonstrate that invariant neural dynamics are both used and useful for

issuing commands across different movements.

Results

BMI to study neural population control of movement

We used a BMI[47–49] to study the dynamics of population activity as it issued commands

for movement of a two-dimensional computer cursor (Fig. 1A). Population activity (20-151

units) was recorded using chronically implanted microwire electrode arrays spanning bilateral

dorsal premotor cortex and primary motor cortex. Each unit's spiking rate at time t (computed as

the number of spikes in a temporal bin) was stacked into a vector of population activity x_t, and

the BMI used a "decoder" given by matrix K to linearly transform population activity into a two-

dimensional command:

$$\text{command}_t = Kx_t \tag{2}$$

The command linearly updated the two-dimensional velocity vector of the computer cursor:

$$\text{velocity}_t = \text{command}_t + \alpha^*\text{velocity}_{t-1} + \text{offset} \tag{3}$$

We note that the BMI was not identical across the two subjects, as neural activity was modeled

with different statistical distributions (Gaussian for Monkey G and a Point Processs[47,48] for

Monkey J, see STAR methods – "Neuroprosthetic decoding").

The decoder was initialized as subjects passively watched cursor movement, calibrated as

subjects used the BMI in closed-loop[49] without performing trained overt movement, and then

fixed for the experiment (Fig. 1B). Critically, the decoder was not fit during trained overt

movement, as was done previously[16], so it did not demand neural dynamics associated with overt

movement.

To study control of diverse movements, we trained monkeys to perform two different

tasks (Fig. 1CD). Monkeys performed a center-out task in which they moved the cursor from the

center of the workspace to one of eight radial targets, and they performed an obstacle-avoidance

task in which they avoided an obstacle blocking the straight path to the target. Our tasks elicited

up to 24 conditions of movement (with an average of 16-17 conditions per session), where each

condition is defined as the task performed ("co" = center-out task, "cw" / "ccw" =

clockwise/counterclockwise movement around the obstacle in the obstacle-avoidance task) and

the target achieved (numbered 0 through 7).

Importantly, the BMI enabled us to identify when neural activity issued the same exact

command in different conditions (Fig. 1EF, Fig. S1). We considered two-dimensional,

continuous-valued commands as the same if they fell within the same discrete bin for analysis.

We categorized commands into 32 bins (8 angular x 4 magnitude) based on percentiles of the

continuous-valued distribution (Fig. S1A; see STAR methods - "Command discretization for

analysis"). On each session, a command (of the 32 discretized bins) was analyzed if it was used

in a condition 15 or more times (Fig. S1B), for more than one condition. Each individual

command was used with regularity during multiple conditions (on average ~7 conditions, Fig.

S1B), within distinct local "subtrajectories" (Fig. 1F, Fig. S1, STAR methods – "Cursor and

command trajectory visualization").

Using the BMI to test whether invariant dynamics are used to control different movements

The BMI enabled us to test whether the pattern of neural activity systematically

influences the subsequent pattern and command. We can visualize an activity pattern x_t as a

point in high-dimensional activity space, where each neuron's activity is one dimension, and

visualize the transition between two patterns x_t and x_{t+1} as an arrow (Fig. 2A). Then,

dynamics can be visualized as a flow field in activity space. This flow field is invariant because

the predicted transition for a given neural activity pattern (i.e. its arrow) does not change,

regardless of the current command or condition. Because there are more neurons than

dimensions of the command, different activity patterns can issue the same command[24,50] (Fig.

2B), as is believed to be true in the natural motor system[23,24,50]. The BMI decoder defined the

"decoder space" as the dimensions of neural activity that determine the command and the

"decoder null space" as the orthogonal dimensions which have no consequence on the decoder.

The BMI allowed us to observe the precise temporal order of commands (Fig. 2C) and test

whether activity trajectories followed the flow of invariant dynamics to issue these commands

for movements (Fig. 2D).

The same command is issued by different neural activity patterns in different movements

First, we tested whether the same command is issued by different neural activity patterns

in different movements, as would be expected if the current pattern influences the subsequent

pattern and command (Fig. 3A). We calculated the distance between the average neural activity

for a given command and condition and the average neural activity for the given command

pooled over conditions. We then tested if this distance is larger than expected simply due to the

variability of noisy neural activity. To emulate the scenario in which neural activity for a given

command has the same distribution across conditions, we constructed shuffled datasets where we

identified all observations of neural activity issuing a given command and shuffled their

condition-labels, for all commands (see STAR methods – "Behavior-preserving shuffle of

activity"). In this scenario, the distance is expected to be greater than zero simply because

average activity is estimated from limited samples and thus is subject to variability.

Overall, neural activity issuing a given command significantly deviated across conditions

relative to the shuffle distribution (Fig. 3B-E). Distances averaged within-session ranged from

10% to 200% larger than shuffle distance (Fig. 3D, S2 for additional distributions). Distances

were significantly larger than shuffle distances for a large fraction of individual (command,

condition) tuples (~30% for Monkey G, ~70% for Monkey J), individual commands (~65% for

G, ~90% for J) when aggregating over conditions, and individual neurons (~40% for G, ~80%

for J) when aggregating over all (command, condition) tuples (Fig. 3E). Further, these deviations

reflected the behavior; the distance between two patterns issuing the same command correlated

with the distance between the command subtrajectories (Fig. S6E-H).

Invariant dynamics predict the different neural activity patterns used to issue the same

command

Given that a command was not issued with the same activity pattern across conditions,

we next constructed a model of invariant dynamics. We used single-trial neural activity x_t from

all conditions to estimate dynamics with a linear model (Fig. 4A):

$$x_{t+1} = Ax_t + b \qquad (4)$$

We found that the dynamics A were low-dimensional (~4 dimensions, Fig. 5D, S3B) and

decaying to a fixed point (Fig. S3A,C), contrasting with rotational dynamics observed during

natural motor control [12,13,16,22,51]. See Fig. S3D for an illustration of how decaying invariant

dynamics can control different movements. Notably, a non-linear dynamics model (a recurrent

switching linear dynamical system[52]) did not out-perform these simple linear dynamics (Fig.

S5C-F).

We asked whether invariant dynamics predict the different activity patterns observed to

issue the same command. Concretely, we predicted the activity pattern given the command it

issued and its previous activity (Fig. 4A, see STAR methods – "Invariant dynamics model

predictions"), combining the dynamics model (Equation 4) with the decoder (Equation 2). This

analyzed whether the model could predict the component of the activity pattern that can vary

when a given command is issued, i.e. the component in the decoder null space. For comparison,

we also computed the prediction of neural activity when only given the command it issued (in

the absence of a dynamics model). Further, we tested whether the invariant dynamics model

generalized to new commands and conditions. Dynamics models were fit on neural activity

specifically excluding individual commands or conditions, and these models were used to predict

the neural activity for the left-out commands or conditions (Fig. 4B, Fig. S4, see STAR methods

– "Invariant dynamics models").

We tested whether the dynamics model's accuracy exceeded a dynamics model fit on the

shuffled datasets that preserved the temporal order of commands while shuffling the neural

activity issuing the commands (see STAR methods – "Behavior-preserving shuffle of activity").

The shuffle dynamics model captured the expected predictability in neural activity due to the

predictability of commands in the performed movements.

On the level of single time points in individual trials, we found that the dynamics model

significantly exceeded shuffle dynamics in predicting the activity pattern issuing a given

command based on the previous pattern. Importantly, it generalized across left-out commands

and conditions (Fig. 4C) and even when much larger subsets of commands and conditions were

left-out (Fig. S4). We confirmed that the result was not driven by neural activity simply

representing behavioral variables (cursor kinematics, target location, and condition) in addition

to the command (Fig. S5AB), consistent with previous work [53].

The invariant dynamics model also predicted the different average activity patterns for

each command and condition (Fig. 4D-G) significantly better than shuffle dynamics. It predicted

20-40% of the condition-specific component of neural activity (i.e. the difference between

average activity for a (command, condition) and the prediction of that activity based on the

command alone) (Fig. 4F, see STAR methods – "Invariant dynamics model predictions"). The

model predicted neural activity for the vast majority of commands, conditions, and neurons (Fig.

4G), revealing that dynamics were indeed invariant.

Finally, the dynamics model preserved structure of neural activity across pairs of

conditions (Fig. S6A-D) and predicted that the distance between two activity patterns issuing the

same command would be correlated with the distance between the corresponding command

subtrajectories (Fig. S6E-I). Altogether, these results show that invariant dynamics contribute to

what activity pattern was used to issue a command, generalizing across commands and

conditions.

Invariant dynamics align with the decoder, propagating neural activity to issue the next

command

We next asked whether invariant dynamics were actually used to transition between

commands. Concretely, we used the dynamics model to predict the transition from the current

activity pattern to the next pattern, and then we applied the BMI decoder to this prediction of

next pattern in order to predict the next command (i.e. its continuous value) (Fig. 5A). This tests

whether invariant dynamics predict the component of neural activity in the decoder space, which

actually drives the BMI. The BMI enabled this analysis as it defines the transformation from

neural activity to command which has not been measurable during natural motor control.

We emphasize that invariant dynamics do not have to predict the command, i.e. the

decoder space (Fig. 5B). Low-dimensional dynamics could be misaligned with the decoder such

that they only predict the component of neural activity in the decoder null space. To assess this

possibility, we fit an invariant dynamics model on the component of neural activity in the

decoder null space ("decoder-null dynamics", see STAR methods – "Invariant dynamics

models"). While this model was restricted to the decoder-null space, it maintained similar

dimensionality and eigenvalues to the full dynamics model (Fig. S3BC).

Both the full dynamics and the decoder-null dynamics model predicted next neural

activity significantly better than shuffle dynamics (Fig. 5C) on the level of single time points in

individual trials. This reveals that invariant dynamics occupied decoder-null dimensions. Given

that the full dynamics model was low-dimensional (Fig. S3B) and predicted ~4 dimensions more

accurately than the rest of neural activity (Fig. 5D), we next tested whether the dynamics aligned

with the decoder. Critically, the full dynamics model predicted the next command (Fig. 5E)

better than shuffle dynamics, while decoder-null dynamics provided absolutely no prediction for

the next command, as expected by construction. The dynamics were invariant, as the full

dynamics model generalized across commands and conditions that were left-out from model

fitting (Fig. 5E) and predicted the next command for the majority of (command, condition) tuples

(Fig. 5F). These predictions preserved structure across pairs of conditions, such that invariant

dynamics indicated how similar the next command would be across pairs of conditions (Fig. S6I-

K).

Notably, invariant dynamics could predict the turn that the next command would take

following a given command in a specific condition relative to the average next command

(averaged across conditions for the given current command) (Fig. 5GH). Specifically, the

dynamics model predicted whether the turn would be clockwise or counter clockwise (Fig. 5H

left) and the angle of turn (Fig 5H *right*) better than shuffle dynamics. Altogether, these results

show that invariant dynamics align with the decoder and are used to transition between

commands.

An OFC model reveals that invariant dynamics reduce the input that a neural population

needs to issue commands based on feedback

We observe that the invariant dynamics model did not perfectly predict transitions

between commands. Throughout movement there were substantial residuals (Fig. S3E-G),

consistent with ongoing movement feedback driving neural activity in addition to invariant

dynamics. However, it has been unclear how the brain can integrate feedback with invariant

dynamics to control movement. Thus, we constructed a model of optimal feedback control

(OFC) that incorporates invariant neural dynamics.

We introduce a hierarchical model in which the brain controls the neural population

which controls movement of the BMI cursor (Fig. 6A, Equation 5). Population activity x_t issues

commands for movement and is driven by three terms: invariant dynamics (which we

hypothesize are intrinsic to some connectivity of the neural population), input, and noise. The

brain transforms ongoing cursor state and population activity into the input to the population that

is necessary to achieve successful movement. Concretely, the brain acts as an optimal linear

feedback controller with knowledge of the neural population's invariant dynamics, the BMI

decoder, and the condition of movement. In this formulation, the brain's objective was to achieve

the target while using the smallest possible input to the population, which minimizes the

communication from the brain to the population. Importantly, this incentivized the OFC model to

optimize input in order to use invariant dynamics to control movement, rather than relying solely

on input to issue commands. Consistent with this formulation, experiments show that thalamic

input into motor cortex is optimized during motor learning[54].

$$x_{t+1} = Ax_t + b + \text{input}_t + \text{noise}_t \qquad (5)$$
$$\text{input}_t = f_t^{\text{LQR}}(x_t, \text{cursor}_t, \text{condition})$$
$$\text{cursor}_{t+1} = \text{BMI}(\text{cursor}_t, x_t)$$

We simulated the model performing center-out and obstacle-avoidance movements with

the decoders that were used in BMI experiments (see STAR methods – "Optimal feedback

control model and simulation"). In the Full Dynamics Model, the brain computed the minimal

input to a population that followed the invariant dynamics we observed experimentally. In the

No Dynamics Model, the minimal input was computed to a neural population that had no

invariant dynamics (i.e. the A matrix was set to zero). To facilitate comparison, we designed the

models to receive the same noise magnitude and to produce behavior with equal success and

target acquisition time (Fig. 6B).

These simulations revealed that the population required significantly less input in the Full

Dynamics Model than in the No Dynamics Model (Fig. 6C). This effect was erased in the

Decoder-Null Dynamics Model (Fig 6D), in which the OFC model's invariant dynamics were

restricted to the decoder-null space. These results show that invariant dynamics that specifically

align with the decoder, as experimentally-observed, can help the brain perform feedback control,

reducing the input that the population needs to issue commands based on feedback.

Finally, we confirmed the principle that feedback control with invariant dynamics makes

use of distinct activity patterns to issue a particular command. As in Fig. 3, we compared the

OFC models' neural activity against shuffled activity that preserved the temporal order of

commands. The population activity distances for (command, condition) tuples were significantly

larger than shuffle in the Full Dynamics Model but not in the No Dynamics Model (Fig. 6FG).

Further, this effect depended on alignment between invariant dynamics and the decoder, as we

detected no difference between the Decoder-Null Dynamics Model and shuffle (Fig. 6H). Thus,

the OFC model used different neural activity patterns to issue the same command only when the

invariant dynamics were useful for feedback control.

Discussion

Theoretical work shows that recurrent connectivity can give rise to neural population

dynamics for motor control[1,4,5] and endow the brain with the capacity to generate diverse

physical movement[3]. Experimental work has found that population activity in the motor cortex

follows similar and predictable dynamics across different movements[11,12,16]. But it has been

untested whether dynamics that are invariant across movements are used to actually control

movement, as the transformation from neural activity to motor command has been challenging to

measure[26,27] and model[23–25]. Here, we use a BMI to perform that test.

We discovered that different neural activity patterns are used to issue the same command

in different movements. The activity patterns issuing the same command vary systemically

depending on the past pattern, and critically, they transition according to low-dimensional,

invariant dynamics towards activity patterns that causally drive the subsequent command. Our

results' focus on the command provides a conceptual advance beyond previous work that

characterized properties of dynamics during behavior [12,13,15,16], revealing that invariant dynamics

are actually used to control movement.

Further, it has been unclear how the brain could integrate invariant dynamics with

feedback [24,35–37] to control movement. We introduce a hierarchical model[44] of optimal feedback

control, in which the brain uses feedback to control a neural population that controls movement.

Optimal control theory reveals that invariant dynamics that are aligned to the decoder can help

the brain perform feedback control of movement, reducing the input that a population needs to

issue the appropriate commands. The model verified that when invariant dynamics are used for

feedback control, the same command is issued with different neural activity patterns across

movements. Altogether, these findings form a basis for future studies on what connectivity and

neural populations throughout the brain give rise to invariant dynamics, whether the brain sends

inputs to a neural population to take advantage of invariant dynamics, and whether invariant

dynamics actually drive muscles during physical movement.

These results provide strong evidence against one traditional view that the brain reuses

the same neural population activity patterns to issue a particular command. This perspective is

present in classic studies that describe neurons as representing movement parameters[55,56]. It is

still debated what movement parameters are updated by motor cortex neurons [28,57–59], as

population activity encodes movement position [60–62], distance [63], velocity [61,62], speed [64],

acceleration [65], and direction of movement [64,66–68] , as well as muscle-related parameters such as

force/torque [55,68–70], muscle synergies [71,72], muscle activation [73–75], and even activation of motor

units[27]. Regardless of how commands from motor cortex update physical movement, our

findings using a BMI strongly suggest that the motor cortex does not use the same neural activity

pattern to issue a specific motor command. Our findings instead support the recent proposal that

neural activity in motor cortex avoids "tangling"[11] while issuing commands.

We found that invariant dynamics do not perfectly determine the neural population's next

command. We propose that as the brain sends input to the neural population, it performs

feedback control on the state of the neural population's invariant dynamics in order to produce

movement. This proposal expands the number of behaviors for which invariant dynamics are

useful. This is because invariant dynamics do not need to define the precise neural

trajectories[12,34] that produce movement; they only need to provide useful transitions of neural

activity that inputs can harness to control movement. In our data, simple dynamics (decaying

dynamics with different time constants) in a low-dimensional activity space (~4 dimensions)

were used to control many conditions of movement (~20 conditions). We find that invariant

dynamics constrain neural activity in dimensions which do not directly matter for issuing current

commands[50], so that inputs in these dimensions can produce future commands (Fig. 6C). This

mechanism refutes a simplistic interpretation of the minimal intervention principle[76] in which

neural activity should only be controlled in the few dimensions which directly drive commands.

This also accords with the finding that motor cortex responses to feedback are initially in the

decoder null space before transitioning to neural activity that issues corrective commands [24].

There is almost surely a limitation to the behaviors that particular invariant dynamics are

useful for. Motor cortex activity occupies orthogonal dimensions and shows a different influence

on muscle activation during walking and trained forelimb movement [26], and follows different

dynamics for reach and grasp movements [77]. Notably, our finding of decaying dynamics for BMI

control contrasts with rotational dynamics observed during natural arm movement [12,13,16,22]. We

speculate this could be because controlling the BMI relied more on feedback control than a well-

trained physical movement, because controlling the BMI did not require the temporal structure of

commands needed to control muscles for movement[2], and/or because controlling the BMI did not

involve proprioceptive feedback of physical movement[35]. Recent theoretical work shows that cortico-basal ganglia-thalamic loops can switch between different cortical dynamics useful for different temporal patterns of commands [46].

The use of invariant dynamics to issue commands has implications for how the brain learns new behavior [78,79], enabling the brain to leverage pre-existing dynamics for initial learning [25,80,81] and to develop new dynamics through gradual reinforcement [82,83]. This learning that modifies dynamics relies on plasticity in cortico-basal ganglia circuits [83–85] and permits the brain to reliably access a particular neural activity pattern for a given command and movement [32], even if the same neural activity pattern is not used to issue the same command across different movements.

Modeling invariant dynamics can inform the design of new neuroprosthetics that can generalize commands to new behaviors [16] and classify entire movement trajectories [86]. We expect that as new behaviors are performed, distinct neural activity patterns will be used to issue the same command, but that invariant dynamics can predict and thus recognize these distinct neural patterns as signal for the BMI rather than noise. In addition, our results inform the design of rehabilitative therapies to restore dynamics following brain injury or stroke to recover movement [87,88].

Overall, this study put the output of a neural population into focus, revealing how rules for neural dynamics are used to issue commands and produce different movements. This was achieved by studying the brain as it controlled the very neural activity we recorded. BMI [78,89–92], especially combined with technical advances in measuring, modeling, and manipulating activity from defined populations, provides a powerful technique to test emerging hypotheses about how neural circuits generate activity to control behavior.

Acknowledgements

We thank I. Rodrigues-Vaz, D. Peterka, the Theory Center at the Zuckerman Institute, and I.

Papusha for helpful discussions, and the Costa and Carmena labs for their support.

Funding
NIH NINDS Pathway to Independence Award
1K99NS128250-01 (VRA)

BRAIN Initiative National Institute of Mental Health postdoctoral fellowship
1F32MH118714-01 (VRA)

NIH Pathway to Independence Award
1K99NS124748-01 (PK)

BRAIN Initiative National Institute of Mental Health postdoctoral fellowship
1F32MH120891-01 (PK)

NINDS/NIH BRAIN Initiative U19
NS104649 (RMC)

Simons-Emory International Consortium on Motor Control
#717104 (RMC)

NINDS/NIH R01
NS106094 (JMC)

Author contributions

V.R.A., P.K., R.M.C., and J.M.C. conceived and designed this study. P.K., S.G., and A.L.O.

performed the experiments. P.K. and V.R.A. analyzed the data. All authors contributed materials

and analysis tools. V.R.A., P.K., R.M.C, and J.M.C. wrote the manuscript. All authors reviewed

the manuscript.

Declaration of interests

Authors declare that they have no competing interests.

Figures and legends

Figure 1. BMI to study neural population control of movement.

(A) Schematic of the BMI system.

(B) Schematic of decoder calibration.

(C) Single trials of BMI control.

(D) Average target acquisition time per session.

412   (E) Example of the same command (black arrow) being issued during single trials of different

413   conditions. The example command was in the -45 degree direction and the smallest magnitude

414   bin of analysis.

415   (F) *Left:* The average command subtrajectory from -500ms to 500ms. *Right:* The average

416   position subtrajectory from -500ms to 500ms. See Fig. S1 for analysis of subtrajectories.

Figure 2. Using the BMI to test whether invariant dynamics are used to control different movements.

(A) Illustration of invariant dynamics.

(B) Multiple neural activity patterns (e.g. white and black square) issue the same command. An illustrative decoder defines the command at time t as the difference between two neurons' instantaneous activity $x_2(t) - x_1(t)$, symbolized with orange arrows (top right) indicating the command's magnitude and sign.

(C) A trajectory of commands (orange arrows) produces one whole movement. Movement 1 (blue) and 2 (green) are driven by the same commands in different temporal orders.

427   (D) Neural activity that follows invariant dynamics h in order to issue the commands for

428   movement. See Fig. S3D for another example of invariant dynamics (decaying dynamics).

Figure 3. The same command is issued by different neural activity patterns in different

movements.

(A) The same command (orange upward arrow) is issued in different conditions with different

activity patterns (blue, green dots). These patterns deviate from the condition-pooled average

activity pattern for the command (black dot).

(B) *Left:* An example neuron's average firing rate (colored dots) for the example command and

conditions from Fig. 1F (position subtrajectories plotted at right legend), as well as the condition-

pooled average activity (dashed black line labeled "condition-pool"). The condition-shuffled

distributions of average activity are shown with gray boxplots indicating the 2.5th, 25th, 50th, 75th,

and 97.5th percentiles. Asterisk indicates the distance for the (command, condition, neuron)

exceeded the shuffle distance ($p<0.05$). 5/9 or 62.5% of the examples were significant. Distance

was significantly greater than shuffle distance aggregating over all (command, condition,

neuron) tuples: Monkey G [J]: p-value < 0.001 for 9/9 [4/4] sessions, p-value < 0.001 pooled

over sessions. *Right:* Population distance normalized to the shuffle mean (colored dots). 7/9 or

78% of examples were significant. Fig. S2A shows population distances for all (command,

condition) tuples in this session.

(C) The distribution of normalized population distances across (command, condition) tuples.

Colored ticks indicate distances in (B) *right*. See Fig. S2BC for additional distance distributions.

(D) Normalized population distance averaged across (command, condition) tuples (Monkey G

[J]: n=9 [4] sessions). Bars indicate the average across sessions. Population distance was

significantly greater than shuffle distances, aggregating over all (command, condition) tuples:

Monkey G [J]: p-value < 0.001 for 9/9 [4/4] sessions, p-value < 0.001 for pooled over sessions.

(E) *Left:* Fraction of (command, condition) tuples with distance significantly greater than shuffle

distance. *Middle:* Fraction of commands with distance significantly greater than shuffle distance,

aggregating over conditions. *Right:* Fraction of neurons with distance significantly greater than

shuffle distance, calculated for each (command, condition) separately and aggregating over all

(command, condition) tuples for statistics. Throughout (E): dashed line indicates chance level

(fraction equal to 0.05 significantly deviating from shuffle distance) and datapoints are each of 9

[4] sessions for monkey G [J]. See Fig. S6E-H for the relationship between population distance

and command subtrajectories across pairs of conditions. See Table S1 for statistics details.

Figure 4. Invariant dynamics predict the different neural activity patterns used to issue the

same command.

(A) A linear dynamics model predicts the different activity patterns (cyan-outlined dots) that

issue a given command (orange arrow) based on previous activity. See Fig. S6 for predictions of

the relationship between activity patterns across pairs of conditions.

(B) Models were tested on neural activity for a command (*Left*, magenta) or condition (*Right*,

purple) left-out of training the model. See Fig. S4 for elaboration on invariant dynamics

generalization.

(C) The coefficient of determination (R^2) of models predicting neural activity given the

command it issues and previous activity, evaluated on test data not used for model fitting

(Monkey G [J]: n=9 [4] sessions). See Fig. S3 for properties of the models. Inset shows raw R^2,

where "shuffle" is the 95[th] percentile of the shuffle distribution of R^2. Main panel shows R^2

normalized to shuffle. Full dynamics, command left-out dynamics, and condition left-out

dynamics all predicted neural activity significantly better than shuffle dynamics. For each model:

Monkey G [J]: p-value < 0.001 for 9/9 [4/4] sessions, p-value < 0.001 for sessions pooled. Fig.

S5 shows models with behavior variables and non-linear dynamics.

(D) *Left.* Average activity for the example neuron, command, and conditions from Fig. 3B, left.

Right. Prediction of the activity in *Left* by the full dynamics model (stars), the shuffle dynamics

model (black boxplot distribution), and the model predicting neural activity only using the

command (gray triangle). 8/9 or 88.9% of these examples were predicted significantly better than

shuffle dynamics. The full dynamics model predicted individual neuron activity better than

shuffle dynamics, aggregating over all (command, condition, neuron) tuples (Monkey G [J]: p-

value < 0.001 for 9/9 [4/4] sessions, p-value < 0.001 for pooled sessions).

(E) *Left.* Average population activity for the example command and conditions from Fig. 3B

right, visualized along the activity dimension that captured the most variance (the first principal

component, labeled "PC1", of condition-specific average population activity). *Right.* Prediction

of activity in *Left* by the full dynamics model (stars), the shuffle dynamics model (black boxplot

distribution), and the model predicting neural activity only using the command (gray triangle).

9/9 or 100.0% of these examples were predicted with significantly lower error than shuffle

dynamics (prediction was calculated using full population activity, not just PC1). The full

dynamics model predicted population activity with lower error than shuffle dynamics,

aggregating over all (command, condition, neuron) tuples (Monkey G [J]: p-value < 0.001 for

9/9 [4/4] sessions, p-value < 0.001 for pooled sessions).

(F) Model R^2 from predicting the component of average neural activity for a given command that

is specific to a condition, comparing the full dynamics model (dark gray bar and filled dots) with

the mean of the shuffle dynamics model (light bar and empty dots) (Monkey G [J]: n=9 [4]

sessions). The full dynamics model predicted significantly more variance than shuffle dynamics

(Monkey G [J]: p-value < 0.001 for 9/9 [4/4] sessions, p-value < 0.001 for pooled sessions).

(G) *Left.* Fraction of (command, condition) tuples where full dynamics predicts average

population activity significantly better than shuffle dynamics. *Center.* Fraction of commands

where full dynamics predicts average population activity significantly better than shuffle

dynamics, calculated for each condition separately and then aggregated over all conditions for

statistics. *Right.* Fraction of neurons where full dynamics predicts the neuron's average activity

significantly better than shuffle dynamics, calculated for each (command, condition) separately

and then aggregated over all (command, condition) tuples for statistics. Throughout E: datapoints

are each of 9[4] sessions for Monkey G[J].

509   See Table S1 for statistics details.

Figure 5. Invariant dynamics align with the decoder, propagating neural activity to issue the next command.

(A) A linear dynamics model predicts the transition from current neural activity (colored rings)

to next neural activity (cyan-outlined dots) and next commands (orange symbols) (i.e. the

component of neural activity in the decoder space).

(B) If invariant dynamics are low-dimensional and only occupy the decoder null space (pink

plane), then they do not predict the next command (i.e. the component of neural activity in the

decoder space).

(C) The coefficient of determination (R^2) of models predicting next neural activity given current

neural activity, evaluated on test data not used for model fitting (Monkey G [J]: n=9 [4]

sessions). Inset shows raw R^2, where "shuffle" is the 95[th] percentile of the shuffle distribution of

R^2. Main panel shows R^2 normalized to shuffle. All models predicted next neural activity

significantly better than shuffle dynamics. For each model, Monkey G [J]: p-value < 0.001 for

9/9 [4/4] sessions, p-value < 0.001 for sessions pooled.

(D) R^2 of full model for each neural activity dimension (dynamics eigenvector), sorted by R^2.

(E) Same as (C), except prediction of next command given current neural activity (Monkey G

[J]: n=9 [4] sessions). All models except decoder-null dynamics predicted next command

significantly better than shuffle dynamics. For condition left-out dynamics (purple), Monkey

G[J]: p-value < 0.001 for 9/9 [2/4] session, p-value < 0.05 for 9/9 [3/4] session, p-value n.s. for

0/0 [1/4] sessions, p-value < 0.001 for sessions pooled. For full dynamics and command left-out

dynamics, Monkey G [J]: p-value < 0.001 for 9/9 [4/4] sessions, p-value < 0.001 for sessions

pooled.

(F) Analyses of how well the next command is predicted for individual (command, condition)

tuples. The full dynamics model predicted condition-specific next command better than shuffle

dynamics, aggregating over all (command, condition) tuples (Monkey G [J]: p-value < 0.001 for

9/9 [4/4] sessions, p-value < 0.001 for pooled sessions). *Left.* Fraction of (command, condition)

tuples where full dynamics predicts the next command significantly better than shuffle dynamics

(Monkey G [J]: n=9 [4] sessions). *Right.* Fraction of commands where full dynamics predicts the

next command significantly better than shuffle dynamics, calculated for each condition

separately and then aggregated over all conditions for statistics (Monkey G [J]: n=9 [4] sessions).

(G) Visualization of the command angle (*left*) (i.e. the direction that the command points) for the

example command and conditions (*right*) from Fig. 3B. For each condition (each row),

visualization shows the average current command angle (first column), the average next

command angle (second column), and the prediction of the average next command angle by the

full dynamics model (third column).

(H) For each (command, condition) tuple, prediction of the angle between the next command and

the condition-pooled average next command. *Left.* Fraction of (command, condition) tuples for

which the sign of the angle is accurately predicted (positive=turn counterclockwise,

negative=turn clockwise). Full dynamics predictions are significantly more accurate than shuffle

dynamics (Monkey G [J]: p-value < 0.001 for 9/9 [4/4] sessions, p-value < 0.001 for pooled

sessions. *Right.* Error in predicted angle. Full dynamics predictions are significantly more

accurate than shuffle dynamics (Monkey G [J]: p-value < 0.001 for 9/9 [4/4] sessions, p-value <

0.001 for pooled sessions).

See Table S1 for statistics details.

Figure 6. An OFC model reveals that invariant dynamics reduce the input that a neural population needs to issue commands based on feedback.

(A) A model of optimal feedback control for movement that incorporates invariant neural dynamics.

(B) Three simulated trials for each condition (center-out (co), counter-clockwise (ccw), and clockwise (cw) movements to 8 targets resulting in 24 conditions). *Top:* Full Dynamics Model that uses invariant dynamics fit on experimental data. *Bottom:* No Dynamics Model that uses dynamics matrix A set to 0.

(C) Input magnitude as a percentage of the No Dynamics Model (Monkey G [J]: n=9 [4] sessions). The population required significantly less input to control movement under the Full Dynamics Model (cyan 'D') as compared to the No Dynamics Model (black 'ND'). Un-normalized data were pooled across sessions and compared with a linear mixed effect (LME) model between input magnitude and model category with session modeled as random effect

(Monkey G [J]: p-value < 0.001). Individual sessions were analyzed with a Wilcoxon signed-

rank test that paired condition across the models (Monkey G [J]: p-value<0.05 for 9/9 [4/4]

sessions).

(D) Same as (C) but for Decoder-null Dynamics. There was no significant difference in input

magnitude between Decoder-null Dynamics (pink 'D') and No Dynamics (black 'ND') when

pooling across sessions (Monkey G [J] p-value > 0.05) and on individual sessions (Monkey G

[J]: p-value<0.05 for 0/9 [0/4] sessions).

(E) The same command is issued across conditions in both the Full Dynamics Model and No

Dynamics Model. Average position subtrajectories are shown locked to an example command

across conditions.

(F) Distance between average population activity for a (command, condition) and the average

activity for the command pooling across conditions, normalized by the mean distance of the

shuffle distribution (gray boxplots showing mean, 0^{th} percentile, 25^{th}, 75^{th}, and 95^{th} percentile).

Left: data from Full Dynamics Model. *Right:* data from the No Dynamics Model. Asterisk

indicates distance is greater than shuffle (p-value<0.05).

(G) Same as (F), but each point is an individual session pooling over (command, condition)

tuples (Monkey G [J]: n=9 [4] sessions). Population distances for the Full Dynamics Model were

greater than shuffle. Data was pooled over sessions using a LME with session modeled as

random effect (Monkey G [J]: p-value < 0.001), and individual sessions were analyzed with a

Mann-Whitney U test (p-value<0.05 for Monkey G [J] on 9/9 [4/4] sessions). No difference was

detected in population distances between the No Dynamics Model and shuffle when pooling

across sessions (Monkey G [J]: p-value > 0.05) and on individual sessions (p-value<0.05 for

Monkey G (J) on 0/9 (0/4) sessions).

592 (H) Same as (G), but for the Decoder-null Dynamics Model (pink 'D'). No difference was

593 detected in population distances between the Decoder-null Dynamics Model and shuffle when

594 pooling across sessions (Monkey G [J]: p-value > 0.05) and on individual sessions (p-value<0.05

595 for Monkey G (J) on 0/9 (0/4) sessions). Also, no difference was detected in population distances

596 between the No Dynamics Model and shuffle when pooling across sessions (Monkey G [J]: p-

597 value > 0.05) and on individual sessions (p-value<0.05 for Monkey G(J) on 0/9 (0/4) sessions).

598 See Table S2 for statistics details.

STAR Methods

RESOURCE AVAILABILITY

Lead contact

Further information and requests for resources and reagents should be directed to and will be

fulfilled by the lead contacts, Rui M. Costa (rc3031@columbia.edu) and Jose M. Carmena

(jcarmena@berkeley.edu).

Materials availability

This study did not generate new unique reagents.

Data and code availability

• Monkey BMI data (binned spike counts, cursor trajectories, condition parameters,

decoder parameters, and task parameters) has been deposited the DANDI Archive at

http://dandiarchive.org/dandiset/000404/draft and is publicly available as of the date of

publication. Accession numbers / DOIs are listed in the key resources table.

• All original code has been deposited at

https://github.com/pkhanna104/bmi_dynamics_code and is publicly available as of the

date of publication. DOIs are listed in the key resources table.

• Any additional information required to reanalyze the data reported in this paper is

available from the lead contact upon request.

EXPERIMENTAL MODEL AND SUBJECT DETAILS

All training, surgery, and experimental procedures were conducted in accordance with the NIH

Guide for the Care and Use of Laboratory Animals and were approved by the University of

California, Berkeley Institutional Animal Care and Use Committee (IACUC). Two adult male

rhesus macaque monkeys (7 years old, monkey G and 10 years old, monkey J) (Macaca mulatta,

RRID: NCBITaxon:9544) were used as subjects in this study. Prior to this study, Monkeys G and

J were trained at arm reaching tasks and spike-based 2D neuroprosthetic cursor tasks for 1.5

years. All animals were housed in pairs.

METHOD DETAILS

Electrophysiology and experimental setup

Two male rhesus macaques were bilaterally, chronically implanted with 16 x 8 arrays of

Teflon-coated tungsten microwire electrodes (35 mm in diameter, 500 mm separation between

microwires, 6.5 mm length, Innovative Neurophysiology, Durham, NC) in the upper arm area of

primary motor cortex (M1) and posterior dorsal premotor cortex (PMd). Localization of target

areas was performed using stereotactic coordinates from a neuroanatomical atlas of the rhesus

brain [93]. Implant depth was chosen to target layer 5 pyramidal tract neurons and was typically 2.5

- 3 mm, guided by stereotactic coordinates.

During behavioral sessions, neural activity was recorded, filtered, and thresholded using the

128-channel Multichannel Acquisition Processor (Plexon, Inc., Dallas, TX) (Monkey J) or the

256-channel Omniplex D Neural Acquisition System (Plexon, Inc.) (Monkey G). Channel

thresholds were manually set at the beginning of each session based on 1–2 min of neural

activity recorded as the animal sat quietly (i.e. not performing a behavioral task). Single-unit and

multi-unit activity were sorted online after setting channel thresholds. Decoder units were

manually selected based on a combination of waveform amplitude, variance, and stability over

time.

Neuroprosthetic decoding

Subjects' neural activity controlled a two-dimensional (2D) neuroprosthetic cursor in real-

time to perform center-out and obstacle-avoidance tasks. The neuroprosthetic decoder consists of

two   models:

1) A cursor dynamics model capturing the physics of the cursor's position and velocity.

2) A neural observation model capturing the statistical relationship between neural activity and the

cursor.

The neuroprosthetic decoder combines the models optimally to estimate the subjects' intent for the

cursor and to correspondingly update the cursor.

Decoder algorithm and calibration -- Monkey G

Monkey G used a velocity Kalman filter (KF) [94,95] that uses the following models for cursor

state c_t and observed neural activity x_t :

$$c_t = Ac_{t-1} + w_t, w_t \sim N(0, W)$$

$$x_t = Cc_t + q_t, q_t \sim N(0, Q)$$

In the cursor dynamics model, the cursor state $c_t \in R^5$ was a 5-by-1 vector

$[pos_x, pox_y vel_x, vel_y, 1]^T$, $A \in R^{5x5}$ captures the physics of cursor position and velocity, and w_t

is additive Gaussian noise with covariance $W \in R^{5x5}$ capturing cursor state variance that is not

explained by A.

In the neural observation model, neural observation $x_t \in R^N$ was a vector corresponding

to spike counts from N units binned at 10 Hz, or 100ms bins. C models a linear relationship

between the subjects' neural activity and intended cursor state. The decoder only modeled the

statistical relationship between neural activity and intended cursor velocity, so only the columns

corresponding to cursor state velocity and the offset (columns 3-5) in C were non-zero. Q is

additive Gaussian noise capturing variation in neural activity that is not explained by Cc_t. For

Monkey G, 35-151 units were used in the decoder (median 48 units).

In summary, the KF is parameterized by matrices $\{A \in R^{5x5}, W \in R^{5x5}, C \in R^{Nx5}, Q \in$

$R^{NxN}\}$. The KF equations used to update the cursor based on observations of neural activity are

defined as in [95].

The KF parameters were defined as follows. For the cursor dynamics model, the A and W

matrices were fixed as in previous studies [96]. Specifically, they were:

$$A = \begin{bmatrix} 1 & 0 & 0.1 & 0 & 0 \\ 0 & 1 & 0 & 0.1 & 0 \\ 0 & 0 & 0.8 & 0 & 0 \\ 0 & 0 & 0 & 0.8 & 0 \\ 0 & 0 & 0 & 0 & 1 \end{bmatrix}, \quad W = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 7 & 0 & 0 \\ 0 & 0 & 0 & 7 & 0 \\ 0 & 0 & 0 & 0 & 0 \end{bmatrix}$$

where units of cursor position were in cm and cursor velocity in cm/sec.

For the neural observation model, the C and Q matrices were initialized from neural and

cursor kinematic data collected at the beginning of each experimental session while Monkey G

observed 2D cursor movements that moved through either a center-out task or obstacle avoidance

task. Maximum likelihood methods were used to fit C and Q.

Next, Monkey G performed a "calibration block" where he performed the center-out or

obstacle-avoidance task movements as the newly initialized decoder parameters were continuously

calibrated/adapted online ("closed-loop decoder adaptation", or CLDA). This calibration block

was performed in order to arrive at parameters that would enable excellent neuroprosthetic

performance. Every 100ms, decoder matrices C and Q were adapted using the recursive maximum

likelihood CLDA algorithm [49]. Half-life values, defining how quickly C and Q could adapt, were

typically 300 sec, and adaptation blocks were performed with a weak, linearly decreasing "assist"

(re-defining c_t as a weighted linear combination of user-generated c_t and optimal c_t to drive the

cursor to the target). Typical assist values at the start of the block were 90% user-generated, 10%

optimal and decayed to 100% user-generated, 0% optimal over the course of the block. Following

CLDA, decoder parameters were fixed. Then the experiment proceeded with Monkey G

performing the center-out and obstacle-avoidance tasks.

Decoder algorithm -- Monkey J

Monkey J used a velocity Point Process Filter (PPF) [47,48]. The PPF uses the same cursor

dynamics model for cursor state c_t as the KF above, but uses a different neural observations model

(a Point Process model rather than a Gaussian model) for the spiking $S_t^{1:N}$ of each of N neurons:

$$c_t = Ac_{t-1} + w_t, w_t \sim N(0, W)$$

$$p(S_t^{1:N}|v_t) = \prod_{j=1}^{N} (\lambda_j(t\,|v_t, \phi^j)\Delta)^{S_t^j} \exp(-\lambda_j(t|v_t, \phi^j)\,\Delta)$$

In the neural observations model, neural observation S_t^j is the jth neuron's spiking activity,

equal to 1 or 0 depending on whether the jth neuron spikes in the interval $(t, t + \Delta)$. We used Δt

= 5ms bins since consecutive spikes rarely occurred within 5ms of each other. For Monkey J, 20

or 21 units were used in the decoder (median 20 units). The probability distribution over spiking

$p(S_t^{1:N}|v_t)$ was a point process with $\lambda_j(t\,|v_t, \phi^j)$ as the jth neuron's instantaneous firing rate at

time t. $\lambda_j(t\,|v_t, \phi^j)$ depended on the intended cursor velocity $v_t \in R^2$ in the two dimensional

workspace and the parameters ϕ^j for how neuron j encodes velocity. $\lambda_j(t\,|v_t, \phi^j)$ was modeled

as a log-linear function of velocity:

$$\lambda_j(t\,|v_t, \phi^j) = \exp(\beta_j + \alpha_j^T v_t)$$

where ϕ^j parameters consist of $\alpha_j \in R^2, \beta_j \in R^1$.

In summary, the PPF is parameterized by $\{A \in R^{5x5}, W \in R^{5x5}, \phi^{1:N}\}$. The PPF equations

used to update the cursor based on observations of neural activity are defined as in [48].

The PPF parameters were defined as follows. For the cursor dynamics model, the A and

W matrices are defined as:

$$A = \begin{bmatrix} 1 & 0 & 0.005 & 0 & 0 \\ 0 & 1 & 0 & 0.005 & 0 \\ 0 & 0 & 0.989 & 0 & 0 \\ 0 & 0 & 0 & 0.989 & 0 \\ 0 & 0 & 0 & 0 & 1 \end{bmatrix}, \quad W = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 3.7 \times 10^{-5} & 0 & 0 \\ 0 & 0 & 0 & 3.7 \times 10^{-5} & 0 \\ 0 & 0 & 0 & 0 & 0 \end{bmatrix}$$

where units of cursor position were in m and cursor velocity in m/sec.

For the neural observations model, parameters $\phi^{1:N}$ were initialized from neural and cursor

kinematic data collected at the beginning of each experimental session while Monkey J observed

2D cursor movements that moved through a center-out task. Decoder parameters were adapted

using CLDA and optimal feedback control intention estimation as outlined in [47]. Following CLDA,

decoder parameters were fixed. Then the experiment proceeded with Monkey J performing the

center-out and obstacle-avoidance tasks.

<u>Definition of the command for the BMI</u>

We defined the "command" for the BMI as the direct influence of subjects' neural activity

x_t (binned at 100ms) on the cursor. Concretely, in both decoders, the command was a linear

transformation of neural activity that we write as Kx_t which updated the cursor velocity.

Command definition -- Monkey G

For Monkey G, the update to the cursor state c_t due to cursor dynamics and neural observation

x_t can be written as:

$$c_t = F_t c_{t-1} + K_t x_t$$

where $F_t c_{t-1}$ is the update in cursor state due to the cursor dynamics process and $K_t x_t$ is what we

have defined as the command: the update in cursor state due to the current neural observation.

$K_t \in R^{5xn}$ is the Kalman Gain matrix and $F_t = (I - K_t C)A$. In practice K_t converges to its steady-

state form K within a matter of seconds [97], and thus F_t converges to $F = (I - KC)A$, so we can

write the above expression in its steady state form:

740
$$c_t = Fc_{t-1} + Kx_t$$

In our implementation, the structure of K is such that neural activity x_t directly updates cursor

velocity, and velocity integrates to update position. The following technical note explains the

structure of K. Due to the form of the A, W matrices, $Rank(K) = 2$. In addition, decoder

adaptation imposed the constraint that the intermediate matrix $C^T Q^{-1} C$ was of the form aI,

where $a = mean(diag(C^T Q^{-1} C))$. Due to this constraint, the rows of K that update the position

of the cursor are equal to the rows of K that update the velocity multiplied by the update

timestep: $K(1:2,:) = K(3:4,:) * dt$ [98] (see independent velocity control in the reference). Given

this structure of K, neural activity's contribution to cursor position is the simple integration of

neural activity's contribution to velocity over one timestep.

In summary, since Kx_t reflects the direct effect of the motor cortex units on the velocity of

the cursor, we term the velocity components of Kx_t the "command". We analyzed the neural spike

counts binned at 100ms that were used online to drive cursor movements with no additional pre-

processing.

Command definition -- Monkey J

For Monkey J the cursor state updates in time as:

747
$$c_t = f_t(c_{t-1}) + K_t x_t$$

748   where

749
$$f_t(c_{t-1}) = (Ac_{t-1} - K_t e^{CAc_{t-1}} \Delta), \quad K_t = P_t C$$

Here $f_t(c_{t-1})$ is the cursor dynamics process and $K_t x_t$ is the neural command. $P_t \in R^{5x5}$ is the

estimate of cursor state covariance, and $C \in R^{5xN}$ captures how neural activity encodes velocity

as a matrix where each column is composed of $[0, 0, \alpha_j^{xvel}, \alpha_j^{yvel}, \beta_j]^T$ for the jth unit.

We define the command for analysis in this study as $K_{est}x_t$, where K_{est} is a time-invariant

matrix that almost perfectly approximates K_t. While the PPF's K_t does not necessarily converge

in the same way it does in the KF, for all four analyzed sessions, neural activity mapped through

$K_{est} \in R^{2xN}$ could account for 99.6, 99.6, 99.5, and 99.8 percent of the variance of the command

respectively $(K_tx_t \cong K_{est}x_t)$. In addition, due to the accuracy of this linear approximation, we also

match Monkey J's timescale of neural activity and commands to that of Monkey G. In order to

match timescales across the two animals (Monkey G: 100 ms updates, Monkey J: 5ms updates),

Monkey J's commands were aggregated into 100 ms bins by summing $K_{est}x_t$ over 20 consecutive

5ms bins to yield the aggregated command over 100ms. Correspondingly, Monkey J's neural

activity was also summed into 100ms bins by summing x_t over 20 consecutive 5ms bins.

<u>Neuroprosthetic tasks</u>

Subjects performed movements in a two-dimensional workspace (Monkey J: 24cm x 24cm,

Monkey G: 50cm x 28cm) for two neuroprosthetic tasks: a center-out task and an obstacle-

avoidance task. We define the movement "condition" as the task performed ("co" = center-out

task, "cw" / "ccw" = clockwise/counterclockwise movement around the obstacle in the obstacle-

avoidance task) and the target achieved (numbered 0 through 7). Thus, there were up to 24 different

conditions possible (8 center-out conditions, 8 clockwise obstacle-avoidance conditions, 8

counterclockwise obstacle-avoidance conditions). In practice, subjects mostly circumvented the

obstacles for a given target location consistently in a clockwise or counterclockwise manner (as

illustrated in Fig. 1C right) resulting in an average of 16-17 conditions per session.

Center-out task:

The center-out task required subjects to hold their cursor within a center target (Monkey J:

radius = 1.2 cm, Monkey G: radius = 1.7 cm) for a specified period of time (Monkey J: hold = 0.25

sec, Monkey G: hold = 0.2 sec) before a go cue signaled the subjects to move their cursor to one

of eight peripheral targets uniformly spaced around a circle. Each target was equidistant from the

center starting target (Monkey J: distance = 6.5cm, Monkey G: distance = 10cm). Subjects then

had to position their cursor within the peripheral target (Monkey J: target radius = 1.2cm, Monkey

G: target radius = 1.7cm) for a specified period to time (Monkey J: hold = 0.25, Monkey G: hold

= 0.2sec). Failure to acquire the target within a specified window (Monkey J: 3-10 sec, Monkey

G: 10 sec) or to hold the cursor within the target for the duration of the hold period resulted in an

error. Following successful completion of a target, a juice reward was delivered. Monkey J was

required to move his cursor back to the center target to initiate a new trial, and Monkey G's cursor

was automatically reset to the center target to initiate a new trial.

Obstacle-avoidance task:

Monkey G performed an obstacle-avoidance task with a very similar structure to the center-

out task. The only difference was that a square obstacle (side length 2 or 3 cm) would appear in

the workspace centered exactly in the middle of the straight line connecting the center target

position and peripheral target position. If the cursor entered the obstacle, the trial would end in an

error, and the trial was repeated.

Monkey J's obstacle-avoidance task required a point-to-point movement between an initial

(not necessarily center) target and another target. On arrival at the initial target, an ellipsoid

obstacle appeared on the screen. If the cursor entered the obstacle at any time during the movement

to the peripheral target, an error resulted, and the trial was repeated. Target positions and obstacle

sizes and positions were selected to vary the amount of obstruction, radius of curvature around the

obstacles, and spatial locations of targets. Trials were constructed to include the following

conditions: no obstruction, partial obstruction with low-curvature, full obstruction with a long

distance between targets, and full obstruction with a short distance between targets thus requiring

a high curvature. See [48] for further details. In this study, only trials that included partial obstruction

or full obstruction were analyzed as "obstacle-avoidance" trials.

Number of sessions

We analyzed 9 sessions of data from Monkey G and 4 sessions of data from Monkey J where

on each session, monkeys performed both the center-out and obstacle-avoidance tasks with the

same decoder. Only successful trials were analyzed.

<u>Optimal feedback control model and simulation</u>

We introduce a model based on optimal feedback control (OFC) for how the brain can use

invariant neural population dynamics to control movement based on feedback. From the

perspective of the brain trying to control the BMI, we used the model to ask how invariant neural

population dynamics affect the brain's control of movement.

Thus, we performed and analyzed simulations of a model in which the brain acts as an

optimal linear feedback controller (finite horizon linear quadratic regulator), sending inputs to a

neural population so that it performs the center-out and obstacle-avoidance tasks (Fig. 6). The

feedback controller computed optimal inputs to the neural population based on the current cursor

state and current neural population activity. Specifically, the inputs were computed as the solution

of an optimization problem that used knowledge of the target and task, decoder, and the neural

population's invariant dynamics. We simulated 20 trials for each of 24 conditions: 8 center-out

conditions, 8 clockwise obstacle-avoidance conditions, and 8 counterclockwise obstacle-

avoidance conditions. The neural and cursor dynamics processes in the simulation are summarized

below:

Neural population dynamics with input

In our simulation, the neural activity of N neurons $x_t \in R^N$ is driven by invariant dynamics

$A \in R^{N \times N}$ that act on previous activity x_{t-1}, an activity offset $b \in R^N$, inputs from the feedback

controller $u_{t-1} \in R^N$ that are transformed by input matrix $B \in R^{N \times N}$, and noise $\sigma_{t-1} \in R^N$:

825
$$x_t = Ax_{t-1} + b + Bu_{t-1} + \sigma_{t-1}$$

826   The input matrix B was set to be the identity matrix such that each neuron has its own

827   independent input. Each neuron also had its own independent, time-invariant noise (see *Noise*

828   section below for how the noise level was set).

829   For notational convenience, an offset term was appended to x_t: $\begin{bmatrix} x_t \\ 1 \end{bmatrix} \in R^{N+1}$. This enabled

830   incorporating the offset b into the neural dynamics matrix:

831
$$\begin{bmatrix} x_t \\ 1 \end{bmatrix} = \begin{bmatrix} A & b \\ 0 & 1 \end{bmatrix} \begin{bmatrix} x_{t-1} \\ 1 \end{bmatrix} + \begin{bmatrix} B \\ 0 \end{bmatrix} u_{t-1} + \begin{bmatrix} \sigma_{t-1} \\ 0 \end{bmatrix}$$

832   *BMI cursor dynamics*

833   The cursor update equations for the simulation matched the steady state cursor update equations

834   in the online BMI experiment (see "<u>Definition of the command for the BMI</u>" above):

835
$$c_t = Fc_{t-1} + Kx_{t-1}$$

As in the experiment, cursor state $c_t \in R^{N_c}$ where $N_c = 5$ was a vector consisting of two-

dimensional position, velocity, and an offset: $[pos_x, pox_y vel_x, vel_y, 1]^T$. $K \in R^{N_c \times N}$ was the

decoder's steady-state Kalman gain (Monkey G) or estimated equivalent K_{est} (Monkey J). $F \in$

$R^{N_c \times N_c}$ was set to the decoder's steady-state cursor dynamics matrix (Monkey G). For Monkey J,

F was estimated using the expression for calculating the steady-state cursor dynamics matrix:

$F_{est} = (I - K_{est}C_{est}) * A_{100ms}$, where $I \in R^{N_c \times N_c}, C_{est} \in R^{N \times N_c}$ was set using the α, β velocity

encoding parameters from the point process filter (see above): $C_{est}(j,:) = \begin{bmatrix} 0 & 0 & 0.01 * \end{bmatrix}$

$\alpha_j(1) \quad 0.01 * \alpha_j(2) \quad 0.01 * \beta_j]$. Values in C_{est} were multiplied by 0.01 to adjust for velocities

expressed in units of cm/sec (in the simulation) instead of m/sec (as in PPF). A_{100ms} was set to the

same A used by Monkey G so that the cursor dynamics would be appropriate for 100ms timesteps:

846
$$A_{100ms} = \begin{bmatrix} 1 & 0 & 0.1 & 0 & 0 \\ 0 & 1 & 0 & 0.1 & 0 \\ 0 & 0 & 0.8 & 0 & 0 \\ 0 & 0 & 0 & 0.8 & 0 \\ 0 & 0 & 0 & 0 & 1 \end{bmatrix}$$

Joint dynamics of neural activity and cursor

The feedback controller sent inputs to the neural population which were optimal considering

the task goal, the cursor's current state, the neural population's invariant dynamics, and the neural

population's current activity. To solve for the optimal input given all the listed quantities, first, the

neural and cursor states are jointly defined. We append the cursor state c_t to the neural activity

state $\begin{bmatrix} x_t \\ 1 \end{bmatrix}$ to form $z_t \in R^{N+1+N_c}$:

853
$$z_t = \begin{bmatrix} x_t \\ 1 \\ c_t \end{bmatrix} = \begin{bmatrix} A & b & 0 \\ 0 & 1 & 0 \\ K & 0 & F \end{bmatrix} \begin{bmatrix} x_{t-1} \\ 1 \\ c_{t-1} \end{bmatrix} + \begin{bmatrix} B \\ 0 \\ 0 \end{bmatrix} u_{t-1} + \begin{bmatrix} \sigma_{t-1} \\ 0 \\ 0 \end{bmatrix}$$

In words, this expression defines a linear dynamical system where input u_{t-1} influences only

the neural activity x_t, x_t evolves by invariant dynamics A with offset vector b, and x_t drives cursor

c_t through the BMI decoder K. Finally, noise σ_{t-1} only influences neural activity x_t (see *Noise*

section below for how the noise level was set).

OFC to reach a target

Our OFC model computes input u_t to the neural population such that the activity of the neural

population x_t drives the cursor to achieve the desired final cursor state (i.e. the target) with minimal

magnitude of input u_t. Concretely, in the finite horizon LQR model, the optimal control sequence

$(u_t, t = 0, 1, \dots T - 1)$ is computed by minimizing the following cost function:

$$J(u_{0:T-1}) = (\sum_{t=0}^{T-1} ((z_t - z_{targ})^T Q(z_t - z_{targ}) + u_t^T R u_t)) + (z_T - z_{targ})^T Q_T(z_T - z_{targ})$$

In   our   model, $Q = 0 \in R^{(N+1+N_c)\times(N+1+N_c)}, R = I \in R^{N\times N}$, and $Q_T =$

$\begin{bmatrix} 0 \in R^{N\times N} & 0 & 0 \\ 0 & 0 \in R^1 & 0 \\ 0 & 0 & I * 10^2 \in R^{N_c\times N_c} \end{bmatrix} \in R^{(N+1+N_c)\times(N+1+N_c)}$. Thus, the final cursor state

error is penalized, and the magnitude of the input to the neural population u_t is penalized (with

setting R as non-zero). Because the magnitude of the input to neural activity is penalized, the

controller sends the minimal input to the neural population to produce task behavior. We defined

our cost function so that the cursor state during movement before the final cursor state is not

penalized, and the neural state is never penalized.

The optimal control sequence $(u_t, t = 0, 1, \dots T - 1)$ is given by $u_t = K_t^{lqr}(z_t - z_{targ})$

where feedback gain matrices $(K_t^{lqr}, t = 0, 1, \dots T - 1)$ are computed iteratively solving the

dynamic Ricatti equation backwards in time. We note that we computed the LQR solution for u_t

using the dynamics of state error $z_t - z_{targ}$, and that the dynamics of state error for non-zero target

states are affine rather than strictly linear.

OFC for center-out task

Center-out task simulations were run with the initial cursor position in the center of the

workspace at $c_0 = [0, 0, 0, 0, 1]$ and the target cursor state at $[target_x, target_y, vel_x = 0, vel_y =$

$0, 1]^T$. Targets were positioned 10cm away from the origin (same target arrangement as Monkey

G). Target cursor velocity was set to zero to enforce that the cursor should stop at the desired target

location.

Exact decoder parameters from Monkey G and linearized decoder parameters from Monkey

J were used (F, K) in simulations. The invariant neural dynamics model parameters (A, b) were

varied depending on the simulated experiment (see below). The horizon for each trial to hit its

target state was set to be $T = 40$ (corresponding to 4 seconds based on the BMI's timebin of

100ms). Constraining each trial to be equal length facilitated comparison of performance across

different simulation experiments. We verified that all of our simulated trials completed their tasks

successfully.

OFC for obstacle-avoidance using a heuristic

Obstacle-avoidance task simulations were performed with the same initial and target cursor

states as the center-out task, except that the cursor circumvented the obstacle to reach the target in

both clockwise and counterclockwise movements. We used a heuristic strategy to direct cursor

movements around the obstacle; we defined a waypoint as an intermediate state the cursor had to

reach enroute to the final target. The heuristic solution performs optimal control from the start

position to the waypoint, and then optimal control from the waypoint to the final target.

Importantly, this solution minimizes the amount of input needed to accomplish these goals. We

used a heuristic solution because the linear control problem of going from the initial cursor state

to the final target cursor state with the constraint of avoiding an obstacle is not a convex

optimization problem.

Concretely, for the first segment of the movement, a controller with a horizon T=20 directed

the cursor to the waypoint, and then a controller with horizon T=20 directed the cursor from the

waypoint to the final target (such that the trial length was matched to the center-out task simulation

with T=40).

The waypoint was defined relative to the obstacle position as follows. First the vector between

the center target and the obstacle position was determined ($v_{obs,center}$). The $v_{obs,center}$ was then

rotated either +90 degrees or -90 degrees corresponding to clockwise and counterclockwise

movements. The waypoint position was a 6cm distance in the direction of the rotated vector, from

the obstacle center. Finally, the desired velocity vector of the intermediate target was set to be in

the direction of $v_{obs,center}$, with a magnitude of 10 cm/s, so that the cursor would be moving in a

direction consistent with reaching its final target in the second segment of the movement after the

waypoint was reached.

To compute the input u_t to execute these movements, we defined the state error at each time

t as $z_{error} = z_{targ} - z_t$, where z_{targ} was the waypoint for the first half of the movement, and

z_{targ} was the final target for the second half of the movement. The linear quadratic regulator

feedback gain K_t^{lqr} matrices were computed on the appropriate state error dynamics with the

shortened horizon T=20.

"Full Dynamics Model" Simulation

Simulations of the "Full Dynamics Model" consisted of OFC with the invariant dynamics

parameters (A, b) that were fit on experimentally-recorded neural activity from each subject and

session (see "Invariant dynamics models" below, under "Quantification and Statistical Analysis").

K_t^{lqr} was computed using these experimentally-observed (A, b) parameters. The initial state of

neural activity (i.e. x_t at t=0) was set to the fixed point of the dynamics.

"No Dynamics Model" Simulation

Simulations of the "No Dynamics Model" consisted of OFC with invariant dynamics

parameter A set to zero ($A = 0$). The experimentally-observed offset b was still used from each

subject and session. K_t^{lqr} was computed using $A = 0$ and the experimentally-observed b, and thus

it was different than in the "Full Dynamics Model." The initial state of neural activity (i.e. x_t at

t=0) was set to offset b, the fixed point of dynamics with $A = 0$.

"Decoder-null Dynamics Model" Simulation

Simulations of the "Decoder-null Dynamics Model" consisted of OFC with the

experimentally-observed invariant dynamics parameters (A, b) that were restricted to the decoder-

null space, i.e. each invariant dynamics model was fit only on the projection of neural activity into

the decoder-null space (see "Invariant dynamics models" under "Quantification and Statistical

Analysis"). K_t^{lqr} was computed using these experimentally-observed decoder-null (A, b)

parameters, and thus it was different than in the "Full Dynamics Model." The initial state of neural

activity (i.e. x_t at t=0) was set to the fixed point of the decoder-null invariant dynamics.

The "Decoder-null Dynamics Model" was compared to its own "No Dynamics Model",

which consisted of OFC with K_t^{lqr} computed using $A = 0$ and the experimentally-observed

decoder-null offset b for each subject and session, and thus it was different than in the previously

defined models. The initial state of neural activity (i.e. x_t at t=0) was set to the decoder-null offset

b, the fixed point of dynamics with $A = 0$.

Noise

In our OFC model, movement errors arise due to noise in the neural activity, and

subsequent neural activity issues commands based on feedback to correct these errors. We used

two considerations to choose the noise level for neural activity. First, we sought to add a level of

neural noise that was comparable to the neural "signal" needed to perform control in the absence

of noise. Second, we wanted to add the same level of noise to the dynamics model (either "Full

Dynamics Model" or "Decoder-null Dynamics Model") and the corresponding "No Dynamics

Model," in order to facilitate comparison.

Thus, we first simulated the "No Dynamics Model" without noise for a single trial for each

of 24 conditions, and we calculated a, the average variance of a neuron across time and trials.

Then for our noisy simulations of the "No Dynamics Model" and the corresponding

dynamics models, Gaussian noise with zero mean and fixed variance a was added to each neuron

at each timestep: $x_t = Ax_{t-1} + Bu_{t-1} + \sigma_{t-1}$, where $\sigma_t \sim N(0, aI)$. Thus, the overall level of

added noise (the sum of noise variance over neurons) matched the overall level of signal in the

noiseless No Dynamics Model simulation (sum of activity variance over neurons).

We note that our main findings (Fig. 6CD, 6GH) held even with different noise levels.

QUANTIFICATION AND STATISTICAL ANALYSIS

<u>Command discretization for analysis</u>

We sought to analyze the occurrence of the same command across different movements.

Commands on individual time points were analyzed as the same command if they fell within the

same discretized bin of continuous-valued, two-dimensional command space. All commands from

rewarded trials in a given experimental session (including both tasks) were aggregated and

discretized into 32 bins. Individual commands were assigned to one of 8 angular bins (bin edges

were 22.5, 67.5, 112.5, 157.5, 202.5, 247.5, 292.5, and 337.5 degrees) and one of four magnitude

bins. Angular bins were selected such that the straight line from the center to each of the center-

out targets bisected each of the angular bins as has been done in previous work[50] (Fig. S1A).

Magnitude bin edges were selected as the 23.75^{th}, 47.5^{th}, 71.25^{th}, and 95^{th} percentile of the

distribution of command magnitudes for that experimental session. Commands falling between the

95^{th} and 100^{th} percentile of magnitude were not analyzed to prevent very infrequent noisy

observations from skewing the bin edges for command magnitude.

Conditions that used a command regularly

For each session, the number of times each of the 32 (discretized) commands was used in a

given condition was tabulated. If the command was used >= 15 times for that condition within a

given session pooling across trials, that condition was counted as using the command regularly

and was used in all analyses involving (command, condition) tuples. Commands that were used <

15 times were not used in analysis involving (command, condition) tuples. We note that the main

results of the study were not affected by this particular selection. Typically, an individual

command is used regularly in 5-10 conditions (distribution shown in Fig. S1A).

<u>Cursor and command trajectory visualization</u>

Cursor position subtrajectories

To visualize the cursor position trajectories locally around the occurrence of a given

command for each condition, we computed the average position "subtrajectory," which we define

as the average trajectory in a window locked to the occurrence of the given command. For each

condition, cursor positions from successful trials were aggregated. Cursor position subtrajectories

shown in Fig. 1F are from representative session 0 from Monkey G. A matrix of x-axis and y-axis

position trajectories was formed by extracting a window of -500ms to 500ms (5 previous samples

plus 5 proceeding samples) around each occurrence of the given command in a given condition

(total of $N_{com\text{-}cond}$ occurrences, yielding a 2 x 11 x $N_{com\text{-}cond}$ matrix). Averaging over the $N_{com\text{-}cond}$

observations yielded a condition-specific command-locked average position subtrajectory (size: 2

x 11) for each condition. If a command fell in the first 500ms or last 500ms of a trial, its occurrence

was not included in the subtrajectory calculation. The position subtrajectories were translated such

that the occurrence of the given command was set to (0, 0) in the 2D workspace (Fig. 1F *right*,

Fig. S1C *middle*).

Command subtrajectories

To visualize trajectories of commands around the occurrence of a given command for each

condition (Fig. 1G, *right*), we followed the same procedure as described above for cursor position

subtrajectories to tabulate a 2 x 11 x N$_{com\text{-}cond}$ matrix but with x-axis and y-axis commands instead

of positions. We note that this matrix consisted of the continuous, two-dimensional velocity values

of the commands. Averaging over the N$_{com\text{-}cond}$ observations yielded the average condition-specific

command subtrajectory (size: 2 x 11 array), as shown in Fig. 1F *left* for example conditions.

<u>Matching the condition-pooled distribution</u>

In many analyses, data (e.g. neural activity or a command-locked cursor trajectory) associated

with a command and a specific condition is compared to data that pools across conditions for that

same command (Figs. 3-5). The distribution of the precise continuous value of the command

within the command's bin may systematically differ between condition-specific and condition-

pooled datasets, which we refer to as 'within-command-bin differences.' To ensure within-

command-bin differences are not the source of significant differences between condition-specific

and condition-pooled data associated with a command, we developed a procedure to subselect

observations of condition-pooled commands so that the mean of the condition-pooled command

distribution is matched to the mean of the condition-specific command distribution. This procedure

ensures that any differences between the condition-specific quantity and condition-pooled quantity

are not due to 'within-command-bin differences'. This procedure is performed on all analyses

comparing condition-specific data to a condition-pooled distribution of data. The matching

procedure is as follows:

1. From the condition-specific distribution, compute the command mean $\mu_{com-cond}$ (size:

2x1) and standard deviation $\sigma_{com-cond}$ (size: 2x1).

2. Compute the deviation of each continuous-valued command observation in the condition-

pooled distribution from the condition-specific distribution.

a.   Use the condition-specific distribution's parameters to z-score the condition-pooled

distribution's continuous-valued command observations by subtracting $\mu_{com-cond}$ and

dividing by $\sigma_{com-cond}$.

b.   Compute the deviation of condition-pooled observations from the condition-specific

distribution as the L2-norm of the z-scored value

c.   For indices in the condition-pooled distribution that correspond to data in the condition-

specific distribution, over-write the L2-norm of the z-scored values with zeros. This step

prevents the condition-pooled distribution from dropping datapoints that are in the

condition-specific data, thereby ensuring the condition-pooled distribution contains the

condition-specific data.

3. Remove the 5% of condition-pooled observations with the largest deviations

4. Use a Student's t-test to assess if the remaining observations in the condition-pooled

distribution are significantly different than the condition-specific distribution for the first and

second dimension of the command (two p-values)

5. If both p-values are > 0.05, then the procedure is complete and the remaining observations

in the condition-pooled distribution are considered the "command-matched condition-pooled

distribution" for a specific command and condition.

6. If either or both p-values are < 0.05, return to step 3 and repeat.

If the condition-pooled distribution cannot be matched to the condition-specific distribution such

that the size of the condition-pooled distribution is larger than the condition-specific distribution,

the particular (command, condition) will not be included in the analysis.

<u>Comparing command subtrajectories</u>

To assess whether a command is used within significantly different command subtrajectories

in different conditions (Fig. S1 DE), the following analysis is performed for conditions that have

sufficient occurrences of the command (>=15):

1. The condition-specific average command subtrajectory is computed by averaging over

$N_{com\text{-}cond}$ single-trial command subtrajectories for the condition, as defined above in "*Visualization*

of command subtrajectories".

2. The condition-pooled average command subtrajectory is computed: all the single-trial

command subtrajectories (N_{com}) are pooled across trials from all conditions that use the given

command regularly (command occurs >= 15 times in a session) to create a condition-pooled

distribution of single-trial command subtrajectories (a 2 x 11 x N_{com} matrix), which is then

averaged to yield the condition-pooled average command subtrajectory (a 2 x 11 matrix).

3. In order to test whether condition-specific average command subtrajectories were

significantly different from the condition-pooled average command subtrajectory, a distribution of

subtrajectories was created by subsampling the condition-pooled distribution to assess expected

variation in subtrajectories due to limited data. Specifically, $N_{com\text{-}cond}$ single-trial command

subtrajectories were sampled from a condition-pooled distribution of command subtrajectories that

was command-matched to the specific condition (see above, "Matching the condition-pooled

distribution"). These $N_{com\text{-}cond}$ samples were then averaged to create a single subtrajectory,

representing a plausible condition-specific average subtrajectory under the view that the condition-

specific subtrajectories are just subsamples of the condition-pooled subtrajectories. This procedure

was repeated 1000 times and used to construct a bootstrapped distribution of 1000 command

subtrajectories.

4. This distribution was then used to test whether condition-specific subtrajectories deviated

from the condition-pooled subtrajectory more than would be expected by subsampling and

averaging the condition-pooled subtrajectory distribution. Specifically, the true condition-specific

command subtrajectory distance from the condition-pooled command subtrajectory was computed

(L2-norm between condition-specific 2x11 subtrajectory and condition-pooled 2x11 subtrajectory)

and compared to the bootstrapped distribution of distances: (L2-norm between each of the 1000

subsampled averaged 2x11 command subtrajectories and the condition-pooled 2x11 command

subtrajectory). A p-value for each condition-specific command subtrajectory distance was then

derived.

The same analysis is also performed using only the next command following a given command

(Fig. S1 E).

<u>Behavior-preserving shuffle of activity</u>

We shuffled neural activity in a manner that preserved behavior as a control for comparison

against the hypothesis that neural activity follows invariant dynamics beyond the structure of

behavior. Shuffled datasets preserved the timeseries of discretized commands but shuffled the

neural activity that issues these commands. In order to create a shuffle for each animal on each

session, all timebins from all trials from all conditions were collated. The continuous-valued

command at each timebin was labeled with its discretized command bin. For each of the 32

discretized command bins, all timebins corresponding to a particular discretized command bin

were identified. The neural activity in these identified timebins was then randomly permuted. A

complete shuffled dataset was constructed by performing this random permutation for all

discretized command bins. This full procedure was repeated 1000 times to yield 1000 shuffled

datasets.

<u>Analysis of activity issuing a given command</u>

Condition-specific neural activity distances

For each session, (command, condition) tuples with >= 15 observations were analyzed. For

each of these (command, condition) tuples, we analyzed the distance between condition-specific

average activity and condition-pooled average activity, both for individual neurons and for the

population's   activity   vector   (Fig.   3B-E).

Analysis of individual neurons for a given (command, condition) tuple, given N neurons:

1. Compute the condition-specific average neural activity ($\mu_{com-cond} \in R^N$) as the average

neural activity over all observations of the command in the condition.

2. Compute the condition-pooled average activity ($\mu_{com-pool} \in R^N$) as the average neural

activity over observations of the command pooling across conditions. The command-matching

procedure is used to form the condition-pooled dataset to account for within-command-bin

differences (see "Matching the condition-pooled distribution" above).

3. Compute the absolute value of the difference between the condition-specific and condition-

pooled averages: $d\mu_{com-cond} = abs(\mu_{com-cond} - \mu_{com-pool}) \in R^N$.

4. Repeat steps 1-3 for each shuffled dataset i, yielding $d\mu_{shuff-i-com-cond}$ for $i = 1:1000$.

5. For   each   neuron   *j*,   compare $d\mu_{com-cond}(j)$ to   the   distribution   of

$d\mu_{shuff-i-com-cond}(j)$ for i = 1:1000. Distances greater than the 95th percentile of the shuffled

distribution are deemed to have significantly different neuron *j* activity for a command-condition.

Analysis of population activity for a given (command, condition) tuple:

To compute population distances, one extra step was performed. We sought to ensure that the

distances we calculated were not trivially due to "within-bin differences" between the condition-

specific and condition-pooled distributions. The first step to ensure this was described above in

"Matching the condition-pooled distribution". The second step was to only compute distances in

the dimensions of neural activity that are null to the decoder and do not affect the composition of

the command. Thus, any subtle remaining differences in the distribution of commands would not

influence population distances.

To compute distances in the dimensions of neural activity null to the decoder, we computed

an orthonormal basis of the null space of decoder matrix $K \in R^{2xN}$ using scipy.linalg.null_space,

yielding $V_{null} \in R^{NxN-2}$. The columns of V correspond to basis vectors spanning the $N-2$

dimensional null space. Using V_{null} we computed: $\mu_{com-cond-null} = V_{null}' * \mu_{com-cond}$ and

$\mu_{com-pool-null} = V_{null}' * \mu_{com-pool}$. We then calculated the population distance metric (L2-

norm), normalized by the square-root of the number of neurons: $d\mu_{pop-com-cond} = /\sqrt[2]{N}$,

$d\mu_{pop-com-cond} \in R^1$. In step 5, the single value $d\mu_{pop-com-cond}$ is compared to the distribution

of $d\mu_{shuff-i-pop-com-cond}$ for i = 1:1000 to derive a p-value for each (command, condition)

tuple. The fraction of (command, condition) tuples with population activity distances greater than

the 95th percentile of the shuffle data (i.e. significant) is reported in Fig. 3E.

For visualization of distances relative to the shuffle distribution (Fig. 3B-D), we divided the

observed population distance for each (command, condition) tuple by the mean of the

corresponding shuffle distribution. With this normalization, we can visualize the spread of the

shuffle distribution (Fig. 3B, *right*) and we can interpret a normalized distance of 1 as the expected

distance according to the shuffle distribution.

Activity distances pooling over conditions

To test whether condition-specific neural activity significantly deviated from condition-

pooled neural activity for a given command (Fig. 3E, *middle*), we aggregated the distance between

condition-specific and condition-pooled average activity over all *Ncond* conditions in which the

command was used ($>= 15$ occurrences of the command in a condition) . An aggregate command

distance is computed: $d\mu_{pop-com} = \frac{1}{Ncond}\sum_{j=1}^{Ncond} d\mu_{pop-com-j}$, and an aggregate shuffle

distribution is computed: $d\mu_{shuff-i-pop-com} = \frac{1}{Ncond}\sum_{j=1}^{Ncond} d\mu_{shuff-i-pop-com-j}$. Then,

$d\mu_{pop-com}$ is compared to the distribution of $d\mu_{shuff-i-pop-com}$ for $i = 1:1000$ to derive a p-

value for each command. The fraction of commands with significant population activity distances

is reported in Fig. 3E, *middle*.

Single neuron distances

To test whether an individual neuron's condition-specific activity deviated from condition-

pooled activity (Fig. 3E *right*), we aggregated the distances between condition-specific and

condition-pooled average activity over the C (command, condition) tuples with at least 15

observations. The aggregated distance for neuron n was computed: $d\mu(n) = \frac{1}{C}\sum_{c=1}^{C} d\mu_c(n)$

where $d\mu_c(n)$ is the condition-specific absolute difference for the nth neuron and cth (command,

condition) tuple. Then $d\mu(n)$ was compared to the distribution of the aggregated shuffle:

$d\mu_{shuff-i}(n) = \frac{1}{C}\sum_{c=1}^{C} d\mu_{shuff-i-c}(n)$ for $i = 1:1000$ to derive a p-value for each neuron. The

fraction of neurons with significant activity distances (p-value<0.05) is reported in Fig. 3E *right*.

Neural activity distances summary

Single neuron activity distances reported in Fig. S2B *(left)* are for all (command, condition,

neuron) tuples that had at least 15 observations. We report distances as a z-score of shuffle

distribution: $z_{com-cond}(n) = \frac{\left(d\mu_{com-cond}(n) - mean\left(d\mu_{shuff-i},(n)\, i=1:1000\right)\right)}{std\left(d\mu_{shuff-i}(n), i=1:1000\right)}$.

Single neuron activity distances reported in (Fig. S2B *center, right*) are for (command,

condition, neuron) tuples that significantly deviated from shuffle. We report raw distances in

neuron activity as $d\mu_{com-cond}(n)$ (Fig. S2B, *center*), and fraction distances as $\frac{d\mu_{com-cond}(n)}{\mu_{com-pool}(n)}$ (Fig.

S2B, *right*).

Population activity distances reported in Fig. 3BCD and Fig. S2C *left* are for all (command,

condition) tuples. We report distances in population activity as a fraction of shuffle mean:

$d\mu_{pop-com-cond}/mean(d\mu_{shuff-i}, i = 1:1000)$ (Fig. 3BCD), and as a z-score of shuffle

distribution: $z_{pop-com-cond} = \frac{\left(\mu_{pop-com-cond} - mean(d\mu_{shuff-i}, i=1:1000)\right)}{std(d\mu_{shuff-i}, i=1:1000)}$ (Fig. S2C *left*).

Population activity distances reported in Fig. S2C (*center, right*) are for (command,

condition) tuples that significantly deviated from shuffle. We report distances in population

activity as a fraction of shuffle mean $d\mu_{pop-com-cond}/mean(d\mu_{shuff-i}, i = 1:1000)$ (Fig. S2C,

center) and fraction of condition-pooled activity as $\frac{d\mu_{pop-out-cond}}{\|\mu_{com-pool}\|_2}$ (Fig. S2C, *right*).

<u>Invariant dynamics models</u>

In order to test whether invariant dynamics predicts the different neural activity patterns

issuing the same command for different conditions, a linear model was fit for each experimental

session on training data of neural activity from all conditions and assessed on held-out test data.

Neural activity at time t, x_t, was modeled as a linear function of x_{t-1}:

$$x_t = Ax_{t-1} + b$$

Here $A \in R^{NxN}$ modeled invariant dynamics and $b \in R^N$ was an offset vector that allowed the

model to identify non-zero fixed points of neural dynamics. Ridge regression was used to estimate

the A and b parameters. Prior to any training or testing, data was collated such that all neural

activity in bins from t=2:T_{trl} in all rewarded trials were paired with neural activity from t=1:(T_{trl}-

1), where T_{trl} is the number of time samples in a trial.

Estimation of Ridge Parameter

For each experimental session, data collated from all conditions was randomly split into 5

sections, and a Ridge model (sklearn.linear_model.Ridge) with a ridge parameter varying from

2.5×10^{-5} to 10^6 was trained using 4 of the 5 sections and tested on the remaining test section. Test

sections were rotated, yielding five estimates of the coefficient of determination (R^2) for each ridge

parameter. The ridge parameter yielding the highest cross-validated mean R^2 was selected for each

experimental session. Ridge regression was used primarily due to a subset of sessions with a very

high number of units (148 and 151 units), thus a high number of parameters needed to be estimated

for the A matrix. Without regularization, these parameters tended to extreme values, and the model

generalized poorly.

Invariant dynamics model: fitting and testing

Once a ridge parameter for a given experimental session was identified, A, b were again

trained using 4/5 of the data. The remaining test data was predicted using the fit A, b. This

procedure was repeated, rotating the training and testing data such that after five iterations, all data

points in the experimental session had been in the test data section for one iteration of model-

fitting. The predictions made on the held-out test data were collated together into a full dataset.

Predictions were then analyzed in subsequent analyses.

Generalization of invariant dynamics

We assessed how well invariant dynamics generalized when certain categories of neural

activity were not included in the training data. Invariant dynamics models were estimated after

excluding neural activity in the following categories (Fig. 4C, Fig. S4, Fig 5CD):

1. Left-out Command: For each command (total of 32 command bins), training data sets were

constructed leaving out neural activity that issued the command (Fig. 4C, Fig. S4, Fig. 5CE).

2. Left-out Condition: For each condition (consisting of target, task, and clockwise or

counterclockwise movement for obstacle avoidance), training data sets were constructed leaving

out neural activity for the given condition (Fig. 4C, Fig. S4, Fig. 5CE).

3. Left-out Command Angle: For each command angular bin (total of 8 angular bins), training

data sets were constructed leaving out neural activity that issued commands in the given angular

bin. This corresponds to leaving out neural activity for the 4 command bins that have the given

angular bin but different magnitude bins (Fig. S4B, middle).

4. Left-out Command Magnitude: For each command magnitude bin (total of 4 magnitude

bins), training data sets were constructed leaving out neural activity that issued commands of the

given command magnitude. This corresponds to leaving out neural activity for the 8 command

bins that have the given magnitude bin but different angle bins (Fig. S4B, right).

5. Left-out Classes of Conditions (Fig. S4G):

a.   vertical condition class consisting of conditions with targets located at 90 and 270

1211   degrees for both tasks,

1212   b.   horizontal condition class consisting of conditions with targets located at 0 and 180

1213   degrees for both tasks,

1214   c.   diagonal 1 condition class consisting of conditions with targets located at 45 and

1215   215 degrees for both tasks, and

1216   d.   diagonal 2 condition class consisting of conditions with targets located at 135 and

1217   315 degrees for both tasks.

For each of the listed categories above, many dynamics models were computed – each one

corresponding to the exclusion of one element of the category (i.e. one model per: command left-

out, condition left-out, command angle left-out, command magnitude left-out, and class of

conditions left-out). Each of the trained models was then used to predict the left-out data.

Predictions were aggregated across all dynamics models resulting in a full dataset of predictions.

The coefficient of determination (R^2) of this predicted dataset reflected how well dynamics models

could generalize to types of neural activity that were not observed during training. We note that

Monkey J did not perform all conditions in the "diagonal 2" class, and so was not used in the

analysis predicting excluded "diagonal 2" conditions.

Decoder-null dynamics model

As an additional comparison, we modeled invariant dynamics that lie only within the

decoder-null space (the neural activity subspace that was orthogonal to the decoder such that

variation of neural activity in this space has no effect on the decoder's output, i.e. commands for

movement).

Our approach was to project spiking activity into the decoder null space, and then fit

invariant dynamics on the projected, decoder-null spiking activity. We first computed an

orthonormal basis of the null space of decoder matrix $K \in R^{2xN}$ using scipy.linalg.null_space,

yielding $V_{null} \in R^{NxN-2}$. The columns of V correspond to basis vectors spanning the $N - 2$

dimensional null space. We then computed the projection matrix $P_{null} \in R^{NxN}$ where $P_{null} =$

$V_{null}V_{null}^T$. Spiking activity was then projected into the null space $x_t^{null} = P_{null}x_t$, where $x_t^{null} \in$

R^{Nx1}.

Following the above procedure (see "*Estimation of Ridge Parameter*"), a ridge regression

parameter was selected using projected data x_t^{null}. Decoder-null dynamics model parameters A_{null},

b_{null} were then fit on 4/5 of the dataset and then tested on the remaining 1/5 of the x_t^{null} dataset.

As before, the training/testing procedure was repeated 5 times such that all data points fell into the

test dataset once. Predictions of test data from all five repetitions were collated into one full dataset

of predictions. We note that the average of the decoder-space activity across the entire session

$\hat{x}^{decoder} = \frac{1}{T}\sum_{t=1}^{T} x_t^{decoder}$, where T is the number of bins in an entire session, was added to all

predictions of decoder-null dynamics ($x_{t+1} = A_{null}x_t + b_{null} + \hat{x}^{decoder}$).

Shuffle dynamics model

The invariant dynamics model was compared to a shuffle dynamics model fit on shuffled

data (see "Behavior-preserving shuffle of activity" above). Following the above procedure (see

"*Estimation of Ridge Parameter*"), a ridge parameter was selected using shuffled data. Shuffle

dynamics model parameters $A_{shuffle}$, $b_{shuffle}$ were then fit on 4/5 of the dataset using shuffled data

and then tested on the remaining 1/5 of the dataset using original, unshuffled data.

Invariant dynamics model characterization

Dimensionality and eigenvalues

Once the linear invariant dynamics model's parameters A, b were estimated, A was analyzed

to assess which modes of dynamics[16] were present (Fig. S3). The eigenvalues of A were computed.

From each eigenvalue, an oscillation frequency and time decay value were computed using the

following equations:

Frequency = $\angle\lambda/(2\pi\Delta t)$ Hz if λ is complex, else frequency = 0 Hz

Time Decay = $\frac{-1}{\ln(|\lambda|)}\Delta t$ sec

Modes of dynamics contributing substantially to predicting future neural variance will have

time decays greater than the BMI decoder's binsize (here, 100ms). 2-4 such dimensions of

dynamics were found across sessions and subjects (Fig. S3).

Invariant dynamics model predictions

Predicting next neural activity: $x_{t+1}| x_t, A, b$

In Fig. 5C, we predict next activity x_{t+1} based on current activity x_t by taking the expected

value according to our model: $E(x_{t+1}|x_t, A, b) = Ax_t + b$.

In Fig. 5D, we evaluated this prediction for individual dimensions of neural activity.

We projected the prediction of x_{t+1} onto each eigenvector of the dynamics model A matrix and

evaluated how well that dimension was predicted (via coefficient of determination).

In Fig. S3E, G, we evaluated this prediction across time from the start of trial. The magnitude

(i.e. L2 norm) of the model residual $\|x_{t+1} - Ax_t + b\|_2$ (Fig. S3E) and the coefficient of

determination (R^2) (Fig. S3G) are plotted for each time point from trial start, evaluated on held-

out test data pooling across trials.

Predicting next command: $\text{command}_{t+1}| \, x_t, A, b, K$

In Fig. 5E-H, we predict the next command command_{t+1} based on current neural activity x_t

by taking its expected value according to our model: $E(\text{command}_{t+1} \, | \, x_t, A, b, K) = K(Ax_t +$

$b)$, where the decoder matrix K maps between neural activity and the command. This amounts to

first predicting next activity based on current activity as above $E(x_{t+1}|x_t, A, b) = Ax_t + b$ and

then applying decoder K.

Predicting activity issuing a given command

In Fig. 4C-G, we predict current activity x_t not only with knowledge of previous activity

x_{t-1}, but also with knowledge of the current command command_t ($x_t| \, x_{t-1}, A, b, K, \text{command}_t$).

We modeled x_t and x_{t-1} as jointly Gaussian with our dynamics model, and command_t is jointly

Gaussian with them since $\text{command}_t = Kx_t$. We modify our prediction of x_t based on knowledge

of command_t: $E(x_t|x_{t-1}, A, b, K, \text{command}_t)$. Explicitly we conditioned on command_t, thereby

ensuring that $K * E(x_t|x_{t-1}, A, b, K, \text{command}_t) = \text{command}_t$. To do this we wrote the joint

distribution of x_t and command_t:

1289
$$\begin{matrix} x_t \\ Kx_t \end{matrix} \sim N\left(\begin{pmatrix} \mu \\ K\mu \end{pmatrix}, \begin{pmatrix} \Sigma & (K\Sigma)^T \\ K\Sigma & K\Sigma K^T \end{pmatrix}\right)$$

where $\mu = E(x_t|x_{t-1}, A, b) = Ax_{t-1} + b$, and $\Sigma = cov[x_t - (Ax_{t-1} + b)]$ is the covariance of

the noise in the dynamics model. Then, the multivariate Gaussian conditional distribution provides

the solution to conditioning on command$_t$:

$E(x_t|x_{t-1}, A, b, \mathrm{K}, \mathrm{command}_t) = Ax_{t-1}+b + \Sigma^T K^T (K\Sigma K^T)^{-1}(\mathrm{command}_t - K(Ax_{t-1} + b))$

This prediction constrains the prediction of x_t to produce the given command command$_t$.

For these predictions, Σ is estimated following dynamics model fitting and set to the empirical

error covariance between estimates of $E(x_t) = Ax_{t-1} + b$ and true x_t in the training data.

Predicting current activity only with command

In Fig. 4C-E, as a comparison to the dynamics prediction $(x_t| x_{t-1}, A, b, K, \mathrm{command}_t)$, we

predict x_t as its expected value $(x_t| K, \mathrm{command}_t)$ based only on the command command$_t =$

Kx_t it issues and the decoder matrix K. The same approach was used as above, except with

empirical estimates of μ, Σ corresponding to the mean and covariance of the neural data instead of

using the neural dynamics model and x_{t-1} to compute μ, Σ.

1303
$$\begin{matrix} x_t \\ Kx_t \end{matrix} \sim N\left(\begin{pmatrix} \mu \\ K\mu \end{pmatrix}, \begin{pmatrix} \Sigma & (K\Sigma)^T \\ K\Sigma & K\Sigma K^T \end{pmatrix}\right)$$

This formulation makes the prediction:

$E(x_t|\mathrm{K}, \mathrm{command}_t) = \mu + \Sigma^T K^T (K\Sigma K^T)^{-1}(\mathrm{command}_t - K\mu)$

Comparing invariant dynamics to shuffle

For the above predictions, we evaluated if invariant dynamics models were more accurate

than shuffle dynamics. A distribution of shuffle dynamics R^2 values (coefficient of determination)

was generated by computing one R^2 value per shuffled dataset (see "Behavior-preserving shuffle

of activity" above), where $R^2_{shuffle,i,j}$ corresponds to the R^2 for shuffle dataset i on session j. For

each session j, each invariant dynamics model was considered significant if its R^2 was greater than

95% of shuffle R^2 values. To aggregate over S sessions, the R^2 values for all S sessions were

averaged yielding one R^2_{avg} value. This averaged value was compared to a distribution of averaged

shuffle R^2 values. Specifically, for each shuffle i (i=1:1000 shuffled dataset) an averaged R^2 value

was computed across all S sessions: $R^2_{avg,shuffle,i} = \frac{1}{S}\sum_{j=1}^{S} R^2_{shuffle,i,j}$, yielding a distribution of

averaged shuffle R^2 values.

Predicting condition-specific activity

The invariant dynamics model was used to predict the condition-specific average activity

for a given command ($\mu_{com-cond}$, i.e. the average neural activity over all observations of the

command in the condition, see "Analysis of activity issuing a given command" above) (Fig. 4D-

G). The invariant dynamics model prediction ($\widehat{\mu_{com-cond}}$) was computed as

$E(x_t|x_{t-1}, A, b, K, \text{command}_t)$ (see "*Predicting activity issuing a given command*" above)

averaged over all observations of neural activity for the given command and condition.

To test if the invariant dynamics prediction was significantly more accurate than the shuffle

dynamics model (i.e. the dynamics model fit on shuffled data, see "Shuffle dynamics model"

above) prediction, we computed the error as the distance between true ($\mu_{com-cond}$) and predicted

($\widehat{\mu_{com-cond}}$) condition-specific average activity (single neuron error and population distance).

Note that population distances for true and predicted activity were taken only in the dimensions

null to the decoder (see "*Condition-specific neural activity deviation*"). The invariant dynamics

model was deemed significantly more accurate than shuffle dynamics if the error was less than the

5th percentile of the distribution of the errors from shuffle dynamics models. We reported the

fraction of (command, condition) tuples that were individually significant relative to shuffle (Fig.

4G, left). We determined whether commands were individually significant relative to shuffle by

analyzing the average population activity error across conditions (Fig 4G, middle). We determined

whether neurons were individually significant relative to shuffle by analyzing the average single-

neuron error over (command, condition) tuples (Fig 4G, right).

Predicting condition-specific component

The component of neural activity for a given command that was specific to a condition was

calculated as $\mu_{com-cond} - E(x^t_{com-cond}|K, \text{command}_t)$, where $\mu_{com-cond}$ is neural activity

averaged over observations for the given command and condition, and

$E(x^t_{com-cond}|K, \text{command}_t)$ is the prediction of neural activity only given the command it issued,

averaged over observations for the (command, condition) tuple (see "*Predicting current activity*

only with command" above). Thus, $\mu_{com-cond} - E(x^t_{com-cond}|K, \text{command}_t)$ estimates the

portion of neural activity that cannot be explained by just knowing the command issued.

We analyzed how well this condition-specific component could be predicted with invariant

dynamics as: $\widehat{\mu_{com-cond}} - E(x^t_{com-cond}|K, \text{command}_t)$ (see "*Predicting condition-specific*

activity" above for calculation of $\widehat{\mu_{com-cond}}$). The variance of $\mu_{com-cond} -$

$E(x^t_{com-cond}|K, \text{command}_t)$ explained by $\widehat{\mu_{com-cond}} - E(x^t_{com-cond}|K, \text{command}_t)$ is reported

in Fig. 4F.

Predicting condition-specific next command

For each (command, condition) tuple, the average "next command" $\text{command}_{com-cond}$

was calculated. For every observation of the given command in the given condition, we took the

command at the time step immediately following the given command and averaged over

observations. We then analyzed how well invariant dynamics predicted this average "next

command" $\widehat{\text{command}_{com-cond}}$, calculated as $E(\text{command}_{t+1} \mid x_t, A, b, K)$ averaged over all

observations of neural activity x_t for the given command and condition. The L2-norm of the

difference $\text{command}_{com-cond} - \widehat{\text{command}}_{com-cond}$ was computed and compared to the errors

obtained from the shuffled-dynamics predictions. For each (command, condition) tuple, the

dynamics-predicted "next command" was deemed significantly more accurate than shuffle

dynamics if the error was less than the 5^{th} percentile of the distribution of the errors of the shuffled-

dynamics predictions (Fig. 5F, *left*). Commands were determined to be individually significant if

the error averaged over conditions was significantly less than the shuffled-dynamics error averaged

over conditions (Fig. 5F, *right*).

Analysis of predicted command angle

We sought to further analyze whether invariant dynamics predicted the transition from a

given command to different "next commands" in different movements. Thus, we calculated two

additional metrics on the direction of the predicted "next command", i.e. the angle of the predicted

"next command" $\widehat{\text{command}}_{com-cond}$ with respect to the condition-pooled "next command"

$\text{command}_{com-pool}$ (the average "next command" following a given command when pooling over

conditions).

First, we predicted whether a condition's "next command" would rotate clockwise or

counterclockwise relative to the condition-pooled "next command." Specifically, we calculated

whether the sign of the cross-product between $\widehat{\text{command}}_{com-cond}$ and $\text{command}_{com-pool}$

matched the sign of the cross-product between $\text{command}_{com-cond}$ and $\text{command}_{com-pool}$. The

fraction of (command, conditions) that were correctly predicted (clockwise vs counterclockwise)

was compared to the fraction of (command, condition) tuples correctly predicted in the shuffle

distribution (Fig. 5H, *left*).

Second, we calculated the absolute error of the angle between the predicted "next

command" and the condition-pooled "next command" for each (command, condition) tuple:

$$\text{abs}(\angle (\widehat{\text{command}}_{com-cond}, \text{command}_{com-pool})$$

$$- \angle (\text{command}_{com-cond}, \text{command}_{com-pool}))$$

Explicitly, for each (command, condition) tuple, we calculated the absolute difference between

two angles: 1) the angle between the predicted "next command" and the condition-pooled "next

command" and 2) the angle between the true "next command" and the condition-pooled "next

command". These errors were then compared to the shuffle distribution (Fig. 5H, *right*).

<u>Estimation of behavior-encoding models</u>

To compare invariant dynamics models to models in which neural activity encodes behavioral

variables in addition to the command, we fit a series of behavior-encoding models (Fig. S5).

Regressors included cursor state (position, velocity), target position (x,y postion in cursor

workspace), and a categorical variable encoding target number (0-7) and task ("center-out",

"clockwise obstacle-avoidance", or "counter-clockwise obstacle-avoidance").

Models were fit using Ridge regression following the same procedure described above (see

"*Estimation of Ridge Parameter*") was followed with one additional step: prior to estimating the

ridge parameter or fitting the regression, variables were z-scored. Without z-scoring, ridge

regression may favor giving explanatory power to the variables with larger variances, since they

would require smaller weights which ridge regression prefers. Then, as above, models were fit

using 4/5 of the data and then used to predict the held-out 1/5 of data. After 5 rotations of training

and testing data, a full predicted dataset was collated.

We then tested whether invariant neural dynamics improved the prediction of neural activity

beyond behavior-encoding. The coefficient of determination (R^2) of the model containing all

regressors except previous neural activity was compared to the R^2 of the model containing all

regressors plus previous neural activity (Fig. S5B) using a paired Student's t-test where session

was paired. One test was done for each monkey.

<u>Analysis between pairs of conditions</u>

We sought to assess whether the invariant dynamics model predicted the relationship between

pairs of conditions for neural activity and behavior (Fig. S6).

Average neural activity for a given command

The invariant dynamics model was used to predict the distance between average neural

activity patterns for the same command across pairs of conditions. Concretely, the predicted

distance was simply the distance between the predicted neural activity pattern for condition 1 and

for condition 2. The correlation between the true distance and the predicted distance was reported

for individual neurons (Fig. S6AC) and population activity (Fig. S6BD). The Wald test

(implemented in scipy.stats.linregress) was used to assess the significance of the correlations on

single sessions. To assess significance pooled over sessions, data points (true distances vs.

dynamics model predicted distances) were aggregated across sessions and assessed for

significance.

Average next command

The invariant dynamics model was used to predict the distance between "next commands"

for the same given command across pairs of conditions. Concretely, the predicted distance was

simply the distance between the predicted "next command" for condition 1 and for condition 2.

The correlation between the true distance and the predicted distance was reported (Fig. S6JK). As

above, the Wald test was used to assess significance of correlations on single sessions and over

pooled sessions.

Correlating neural distance with behavior

We asked whether neural activity for a given command was more similar across conditions

with more similar command subtrajectories (see *"Command subtrajectories"*) (Fig. S6E), and

whether invariant dynamics predict this. Specifically, we analyzed whether the distance between

average neural activity across two conditions for a given command correlated to the distance

between command subtrajectories for the same two conditions (Fig. S6, F *top,* GH *left*). Further,

we analyzed whether invariant dynamics predicted this correlation (Fig. S6, F *bottom,* GH *right*).

For every command (that was used in more than five conditions) and pair of conditions that used

the command ($>=15$ observations in each condition in the pair), 1) the distances between condition-

specific average activity were computed and 2) distances between command subtrajectories were

computed. The neural activity distances were correlated with the command subtrajectory distances

(Fig. S6, F *top,* GH *left*) . To assess whether invariant dynamics made predictions that maintained

this structure, we performed that same analysis with distances between dynamics-predicted

condition-specific average activity across pairs of conditions (Fig. S6, F *bottom,* GH *right*).

We assessed the significance of the relationship using a linear mixed effects (LME) model

(statsmodels.formula.api.mixedlm). The LME modeled command as a random effect because the

exact parameters of the increasing linear relationship between command subtrajectories and

population activity may vary depending on command. Individual sessions were assessed for

significance. To assess significance across sessions, data points were aggregated over sessions,

and the LME model used command and session ID as random effects.

<u>Analysis of Optimal Feedback Control Models</u>

Input magnitude

For each simulated trial, we computed the magnitude of input to the neural population as

the L2 norm of the input matrix $u_t \in R^{N \times T}$ (where N is the number of neurons and $T = 40$ was

the horizon and thus movement length). For each of the 24 conditions, we calculated the average

input magnitude over the 20 trials. We compared the magnitude of input used by the Invariant

Dynamics Model and the No Dynamics Model, where the Invariant Dynamics Model was either

the Full Dynamics Model (Fig. 6C) or the Decoder-Null Dynamics Model (Fig. 6D). We analyzed

each individual session with a paired Wilcoxon signed-rank test, where each pair within a session

consisted of one condition (24 conditions total). We aggregated across sessions for each subject

using a linear mixed effect (LME) model between input magnitude and model category (Invariant

Dynamics Model or No Dynamics Model), with session modeled as a random effect.

Simulated activity issuing a given command

In the OFC simulations, we sought to verify if different neural activity patterns were used

to issue the same command across different conditions, applying analyses that we used on

experimental neural data to the OFC simulations. As above, we defined discretized command bins

(see "Command discretization for analysis") and calculated the average neural activity for each

(command, condition) tuple. For (command, condition) tuples with $>=15$ observations (example

shown in Fig. 6E), we computed the distance between condition-specific average activity and

condition-pooled average activity by subtracting the activity, projecting into the decoder-null

space, taking the L2 norm, and normalizing by the square root of the number of neurons, as in the

experimental data analysis (see "Analysis of activity issuing a given command").

We analyzed the distance between condition-specific average activity and condition-

pooled average activity for a given command, comparing each model to its own shuffle distribution

(see "Behavior-preserving shuffle of activity") (Fig. 6GH). Concretely, for each simulated session,

we calculated the mean of the shuffle distribution of distances for each (command, condition) tuple

and compared these shuffle means (one per (command, condition) tuple) to the observed distances

from the simulations. We analyzed individual sessions with a Mann-Whitney U test. We

aggregated across sessions for each subject with a LME model between activity distance and data

source (OFC Simulation vs shuffle), with session modeled as a random effect. For visualization of

distances relative to the shuffle distribution (Fig. 6F-H), we divided the observed distance for each

(command, condition) tuple by the mean of the corresponding shuffle distribution (same as in Fig.

3B-D).

<u>Statistics Summary</u>

In many analyses, we assessed whether a quantity calculated for a specific condition was

significantly larger than expected from the distribution of the quantity due to subsampling the

condition-pooled distribution. A p-value was computed by comparing the condition-specific

quantity to the distribution of the quantity computed from subsampling the condition-pooled

distribution. The "<u>behavior-preserving shuffle of activity</u>" and "<u>matching the condition-pooled</u>

<u>distribution</u>" (see above) were used to construct the condition-pooled distribution.

The following is a summary of these analyses:

•   Fig. S1D, Quantity: distance between condition-specific average command

subtrajectory and condition-pooled average command subtrajectory, P-value: computed using

behavior-preserving shuffle.

•   Fig. S1E, Quantity: distance between condition-specific average next command

and the condition-pooled average next command, P-value: computed using behavior-

preserving shuffle.

•   Fig. 3B *left*, 3E *right*: Quantity: for a given command, distance between condition-

specific average activity for a neuron and condition-pooled average activity for a neuron, P-

value: behavior-preserving shuffle.

- Fig. 3B *right*, 3D, 3E *left, middle*: Quantity: for a given command, distance between condition-specific average population activity and condition-pooled average population activity, P-value: behavior-preserving shuffle.

- Fig. 4G *right:* Quantity: for a given command, error between the invariant dynamics' prediction of condition-specific average activity for a neuron and the true condition-specific average activity for the neuron. P-value: distribution of prediction errors from shuffle dynamics (models fit on behavior-preserving shuffle and that made predictions using unshuffled data).

- Fig. 4G *left, middle:* Quantity: for a given command, error between the invariant dynamics' prediction of condition-specific average population activity and the true condition-specific average population activity. P-value: distribution of prediction errors from shuffle dynamics (models fit on behavior-preserving shuffle and that made predictions using unshuffled data).

- Fig. 5F: Quantity: for a given command, error between the invariant dynamics' prediction of condition-specific average next command and true condition-specific average next command. P-value: distribution of prediction errors from shuffle dynamics (models fit on behavior-preserving shuffle and that made predictions using unshuffled data).

In the above analyses, we also assessed the fraction of condition-specific quantities that were significantly different from the condition-pooled quantities or significantly predicted compared to a shuffled distribution (Fig. S1DE, Fig. 3E, Fig. 4G, Fig. 5F, Fig. S4DI, Fig. S6G). In order to aggregate over all data to determine whether condition-specific quantities were significantly different from shuffle or significantly predicted within a session relative to shuffle dynamics, we averaged the condition-specific quantity over the relevant dimensions (command,

condition, and/or neuron) to yield a single aggregated value for a session. For example in Fig. 3E

right, we take the distance between average activity for a (command, condition, neuron) tuple and

condition-pooled average activity for a (command, neuron) tuple, and we average this distance

over (command, condition) tuples to yield an aggregated value that is used to assess if individual

neurons are significant. We correspondingly averaged the shuffle distribution across all relevant

dimensions (command, condition, and/or neuron). Together this procedure yielded a single

aggregated value that could be compared to a single aggregated distribution to determine session

significance. Finally, when we sought to aggregate over sessions, we took the condition-specific

quantity that was aggregated within a session and averaged it across sessions and again compared

it to a shuffle distribution of this value aggregated over sessions.

When R^2 was the metric assessed (Fig. 4CF, Fig. 5C-E, Fig. S4BFG), a single R^2 metric was

computed for each session and compared to the R^2 distribution from shuffle models. This R^2 metric

is known as the "coefficient of determination," and we note that it assesses how well the dynamics-

predicted values (e.g. spike counts) account for the variance of the true values.

In some cases, a linear regression was fit between two quantities (Fig. S6CDGJK) on both

individual sessions and on data pooled over all sessions, and the significance of the fit and

correlation coefficient were both reported. In other cases where random effects such as session or

analyzed command may have influenced the linear regression parameters (Fig. S6FG), a Linear

Mixed Effect (LME) model was used with session and/or command modeled as random effects on

intercept.

In Fig. S5, a paired Student's t-test was used to compare two models' R^2 metric across

sessions.Fig. 6 analyzed simulations of OFC models, not experimentally-recorded data. Fig. 6CD

used a paired Wilcoxon test and a LME to compare input magnitude between a pair of OFC

models. Fig. 6GH used a Mann-Whitney U test and a LME to compare population distance

between an OFC model and its shuffle distribution.

References

1. Rokni, U., and Sompolinsky, H. (2012). How the brain generates movement. Neural Comput. *24*, 289–331.

2. Churchland, M.M., and Cunningham, J.P. (2014). A Dynamical Basis Set for Generating Reaches. Cold Spring Harb. Symp. Quant. Biol. *79*, 67–80.

3. Shenoy, K. V, Sahani, M., and Churchland, M.M. (2013). Cortical Control of Arm Movements: A Dynamical Systems Perspective. Annu. Rev. Neurosci. *36*, 337–359.

4. Hennequin, G., Vogels, T.P., and Gerstner, W. (2014). Optimal control of transient dynamics in balanced networks supports generation of complex movements. Neuron *82*, 1394–1406.

5. Sussillo, D., Churchland, M.M., Kaufman, M.T., and Shenoy, K. V (2015). A neural network that finds a naturalistic solution for the production of muscle activity. Nat. Neurosci. *18*, 1025–33.

6. Mastrogiuseppe, F., and Ostojic, S. (2018). Linking Connectivity, Dynamics, and Computations in Low-Rank Recurrent Neural Networks. Neuron *99*, 609-623.e29.

7. Porter, R., and Lemon, R. (1995). Corticospinal Function and Voluntary Movement (Oxford University Press).

8. Nelson, A., Abdelmesih, B., and Costa, R.M. (2021). Corticospinal populations broadcast complex motor signals to coordinated spinal and striatal circuits. Nat. Neurosci. *24*, 1721–1732.

9. Arber, S., and Costa, R.M. (2018). Connecting neuronal circuits for movement. Science (80-.). *360*, 1403–1404.

10. Arber, S., and Costa, R.M. (2022). Networking brainstem and basal ganglia circuits for movement. Nat. Rev. Neurosci.

11. Russo, A.A., Bittner, S.R., Perkins, S.M., Seely, J.S., London, B.M., Lara, A.H., Miri, A., Marshall, N.J., Kohn, A., Jessell, T.M., et al. (2018). Motor Cortex Embeds Muscle-like Commands in an Untangled Population Response. Neuron *97*, 953-966.e8.

12. Churchland, M.M., Cunningham, J.P., Kaufman, M.T., Foster, J.D., Nuyujukian, P., Ryu, S.I., and Shenoy, K. V (2012). Neural population dynamics during reaching. Nature *487*, 51–56.

13. Michaels, J.A., Dann, B., and Scherberger, H. (2016). Neural Population Dynamics during Reaching Are Better Explained by a Dynamical System than Representational Tuning. PLoS Comput. Biol. *12*.

14. Liang, K.-F., and Kao, J.C. (2020). Deep Learning Neural Encoders for Motor Cortex. IEEE Trans. Biomed. Eng. *67*, 2145–2158.

15. Truccolo, W., Hochberg, L.R., and Donoghue, J.P. (2010). Collective dynamics in human and monkey sensorimotor cortex: Predicting single neuron spikes. Nat. Neurosci. *13*, 105–111.

16. Kao, J.C., Nuyujukian, P., Ryu, S.I., Churchland, M.M., Cunningham, J.P., and Shenoy, K. V. (2015). Single-trial dynamics of motor cortex and their applications to brain-machine interfaces. Nat. Commun. *6*, 7759.

17. Kao, J.C., Ryu, S.I., and Shenoy, K. V. (2017). Leveraging neural dynamics to extend functional lifetime of brain-machine interfaces. Sci. Rep. *7*, 7395.

18. Pandarinath, C., O'Shea, D.J., Collins, J., Jozefowicz, R., Stavisky, S.D., Kao, J.C., Trautmann, E.M., Kaufman, M.T., Ryu, S.I., Hochberg, L.R., et al. (2018). Inferring single-trial neural population dynamics using sequential auto-encoders. Nat. Methods *15*,

805–815.

19. Abbaspourazad, H., Choudhury, M., Wong, Y.T., Pesaran, B., and Shanechi, M.M.
(2021). Multiscale low-dimensional motor cortical state dynamics predict naturalistic
reach-and-grasp behavior. Nat. Commun. *12*, 607.

20. Gallego-Carracedo, C., Perich, M.G., Chowdhury, R.H., Miller, L.E., and Gallego, J.Á.
(2022). Local field potentials reflect cortical population dynamics in a region-specific and
frequency-dependent manner. Elife *11*, e73155.

21. Gallego, J.A., Perich, M.G., Chowdhury, R.H., Solla, S.A., and Miller, L.E. (2020). Long-
term stability of cortical population dynamics underlying consistent behavior. Nat.
Neurosci. *23*, 260–270.

22. Sani, O.G., Abbaspourazad, H., Wong, Y.T., Pesaran, B., and Shanechi, M.M. (2021).
Modeling behaviorally relevant neural dynamics enabled by preferential subspace
identification. Nat. Neurosci. *24*, 140–149.

23. Kaufman, M.T., Churchland, M.M., Ryu, S.I., and Shenoy, K. V (2014). Cortical activity
in the null space: permitting preparation without movement. Nat. Neurosci. *17*, 440–8.

24. Stavisky, S.D., Kao, J.C., Ryu, S.I., and Shenoy, K. V. (2017). Motor Cortical Visuomotor
Feedback Activity Is Initially Isolated from Downstream Targets in Output-Null Neural
State Space Dimensions. Neuron, 1–14.

25. Perich, M.G., Gallego, J.A., and Miller, L.E. (2018). A Neural Population Mechanism for
Rapid Learning. Neuron *100*, 964-976.e7.

26. Miri, A., Warriner, C.L., Seely, J.S., Elsayed, G.F., Cunningham, J.P., Churchland, M.M.,
and Jessell, T.M. (2017). Behaviorally Selective Engagement of Short-Latency Effector
Pathways by Motor Cortex. Neuron *95*, 683-696.e11.

27. Marshall, N.J., Glaser, J.I., Trautmann, E.M., Amematsro, E.A., Perkins, S.M., Shadlen,
M.N., Abbott, L.F., Cunningham, J.P., and Churchland, M.M. (2022). Flexible neural
control of motor units. Nat. Neurosci. *25*, 1492–1504.

28. Schieber, M.H. (2004). Motor Control: Basic Units of Cortical Output? Curr. Biol. *14*,
R353–R354.

29. Taylor, D.M., Tillery, S.I.H., and Schwartz, A.B. (2002). Direct cortical control of 3D
neuroprosthetic devices. Science (80-.). *296*, 1829–1832.

30. Serruya, M.D., Hatsopoulos, N.G., Paninski, L., Fellows, M.R., and Donoghue, J.P.
(2002). Instant neural control of a movement signal. Nature *416*, 141–2.

31. Carmena, J.M., Lebedev, M.A., Crist, R.E., O'Doherty, J.E., Santucci, D.M., Dimitrov,
D.F., Patil, P.G., Henriquez, C.S., and Nicolelis, M.A.L. (2003). Learning to control a
brain-machine interface for reaching and grasping by primates. PLoS Biol. *1*, 193–208.

32. Ganguly, K., and Carmena, J.M. (2009). Emergence of a stable cortical map for
neuroprosthetic control. PLoS Biol. *7*.

33. Elsayed, G.F., Lara, A.H., Kaufman, M.T., Churchland, M.M., and Cunningham, J.P.
(2016). Reorganization between preparatory and movement population responses in motor
cortex. Nat. Commun., 13239.

34. Churchland, M.M., Cunningham, J.P., Kaufman, M.T., Ryu, S.I., and Shenoy, K. V.
(2010). Cortical Preparatory Activity: Representation of Movement or First Cog in a
Dynamical Machine? Neuron *68*, 387–400.

35. Kalidindi, H.T., Cross, K.P., Lillicrap, T.P., Omrani, M., Falotico, E., Sabes, P.N., and
Scott, S.H. (2021). Rotational dynamics in motor cortex are consistent with a feedback
controller. Elife *10*, e67256.

36.   Pruszynski, J.A., Kurtzer, I., Nashed, J.Y., Omrani, M., Brouwer, B., and Scott, S.H.
1635   (2011). Primary motor cortex underlies multi-joint integration for fast feedback control.
1636   Nature *478*, 387–390.

1637   37.   Bollu, T., Ito, B.S., Whitehead, S.C., Kardon, B., Redd, J., Liu, M.H., and Goldberg, J.H.
1638   (2021). Cortex-dependent corrections as the tongue reaches for and misses targets. Nature
1639   *594*, 82–87.

1640   38.   Veuthey, T.L., Derosier, K., Kondapavulur, S., and Ganguly, K. (2020). Single-trial cross-
1641   area neural population dynamics during long-term skill learning. Nat. Commun. *11*, 4057.

1642   39.   Rizzolatti, G., and Luppino, G. (2001). The cortical motor system. Neuron *31*, 889–901.

1643   40.   Dum, R.P., and Strick, P.L. (2005). Frontal Lobe Inputs to the Digit Representations of the
1644   Motor Areas on the Lateral Surface of the Hemisphere. J. Neurosci. *25*, 1375–1386.

1645   41.   Harris, J.A., Mihalas, S., Hirokawa, K.E., Whitesell, J.D., Choi, H., Bernard, A., Bohn, P.,
1646   Caldejon, S., Casal, L., Cho, A., et al. (2019). Hierarchical organization of cortical and
1647   thalamic connectivity. Nature *575*, 195–202.

1648   42.   Athalye, V.R., Carmena, J.M., and Costa, R.M. (2020). Neural reinforcement: re-entering
1649   and refining neural dynamics leading to desirable outcomes. Curr. Opin. Neurobiol. *60*.

1650   43.   Sauerbrei, B.A., Guo, J.-Z., Cohen, J.D., Mischiati, M., Guo, W., Kabra, M., Verma, N.,
1651   Mensh, B., Branson, K., and Hantman, A.W. (2020). Cortical pattern generation during
1652   dexterous movement is input-driven. Nature *577*, 386–391.

1653   44.   Merel, J., Botvinick, M., and Wayne, G. (2019). Hierarchical motor control in mammals
1654   and machines. Nat. Commun. *10*, 5489.

1655   45.   Kao, T.-C., Sadabadi, M.S., and Hennequin, G. (2021). Optimal anticipatory control as a
1656   theory of motor preparation: A thalamo-cortical circuit model. Neuron *109*, 1567-
1657   1581.e12.

1658   46.   Logiaco, L., Abbott, L.F., and Escola, S. (2021). Thalamic control of cortical dynamics in
1659   a model of flexible motor sequencing. Cell Rep. *35*, 109090.

1660   47.   Shanechi, M.M., Orsborn, A.L., and Carmena, J.M. (2016). Robust Brain-Machine
1661   Interface Design Using Optimal Feedback Control Modeling and Adaptive Point Process
1662   Filtering. PLoS Comput. Biol. *12*, e1004730.

1663   48.   Shanechi, M.M., Orsborn, A.L., Moorman, H.G., Gowda, S., Dangi, S., Carmena, J.M.,
1664   Chapin, J.K., Moxon, K.A., Markowitz, R.S., Nicolelis, M.A.L., et al. (2017). Rapid
1665   control and feedback rates enhance neuroprosthetic control. Nat. Commun. *8*, 13825.

1666   49.   Dangi, S., Gowda, S., Moorman, H.G., Orsborn, A.L., So, K., Shanechi, M.M., and
1667   Carmena, J.M. (2014). Continuous closed-loop decoder adaptation with a recursive
1668   maximum likelihood algorithm allows for rapid performance acquisition in brain-machine
1669   interfaces. Neural Comput. *26*, 1811–1839.

1670   50.   Hennig, J.A., Golub, M.D., Lund, P.J., Sadtler, P.T., Oby, E.R., Quick, K.M., Ryu, S.I.,
1671   Tyler-Kabara, E.C., Batista, A.P., Yu, B.M., et al. (2018). Constraints on neural
1672   redundancy. Elife *7*, 1–34.

1673   51.   Elsayed, G.F., and Cunningham, J.P. (2017). Structure in neural population recordings:
1674   An expected byproduct of simpler phenomena? Nat. Neurosci. *20*, 1310–1318.

1675   52.   Linderman, S., Johnson, M., Miller, A., Adams, R., Blei, D., and Paninski, L. (2017).
1676   Bayesian Learning and Inference in Recurrent Switching Linear Dynamical Systems. In
1677   Proceedings of the 20th International Conference on Artificial Intelligence and Statistics
1678   Proceedings of Machine Learning Research., A. Singh and J. Zhu, eds. (PMLR), pp. 914–
1679   922.

53.   Stavisky, S.D., Kao, J.C., Nuyujukian, P., Pandarinath, C., Blabe, C., Ryu, S.I., Hochberg,
L.R., Henderson, J.M., and Shenoy, K. V. (2018). Brain-machine interface cursor position
only weakly affects monkey and human motor cortical activity in the absence of arm
movements. Sci. Rep. *8*, 1–19.

54.   Biane, J.S., Takashima, Y., Scanziani, M., Conner, J.M., and Tuszynski, M.H. (2016).
Thalamocortical Projections onto Behaviorally Relevant Neurons Exhibit Plasticity during
Adult Motor Learning. Neuron *89*, 1173–1179.

55.   Evarts, E. V (1968). Relation of pyramidal tract activity to force exerted during voluntary
movement. J. Neurophysiol. *31*, 14–27.

56.   Kalaska, J.F. (2009). From intention to action: motor cortex and the control of reaching
movements. Adv. Exp. Med. Biol. *629*, 139–178.

57.   Fetz, E.E. (1992). Are movement parameters recognizably coded in the activity of single
neurons? Behav. Brain Sci. *15*, 679–690.

58.   Reimer, J., and Hatsopoulos, N.G. (2009). The problem of parametric neural coding in the
motor system. Adv. Exp. Med. Biol. *629*, 243–259.

59.   Omrani, M., Kaufman, M.T., Hatsopoulos, N.G., and Cheney, P.D. (2017). Perspectives
on classical controversies about the motor cortex. J. Neurophysiol. *118*, 1828–1848.

60.   Georgopoulos, A.P., Caminiti, R., and Kalaska, J.F. (1984). Static spatial effects in motor
cortex and area 5: Quantitative relations in a two-dimensional space. Exp. Brain Res. *54*,
446–454.

61.   Wang, W., Chan, S.S., Heldman, D.A., and Moran, D.W. (2007). Motor cortical
representation of position and velocity during reaching. J. Neurophysiol. *97*, 4258–4270.

62.   Paninski, L., Fellows, M.R., Hatsopoulos, N.G., and Donoghue, J.P. (2004).
Spatiotemporal Tuning of Motor Cortical Neurons for Hand Position and Velocity. J.
Neurophysiol. *91*, 515–532.

63.   Fu, Q.-G., Suarez, J.I., and Ebner, T.J. (1993). Neuronal Specification of Direction and
Distance During Reaching Movements in the Superior Precentral Premotor Area and
Primary Motor Cortex of Monkeys. J. Neurophysiol. *70*.

64.   Moran, D.W., and Schwartz, A.B. (1999). Motor cortical representation of speed and
direction during reaching. J. Neurophysiol. *82*, 2676–2692.

65.   Flament, D., and Hore, J. (1988). Relations of motor cortex neural discharge to kinematics
of passive and active elbow movements in the monkey. J. Neurophysiol. *60*, 1268–1284.

66.   Georgopoulos, A.P., Kalaska, J.F., Caminiti, R., and Massey, J.T. (1982). On the relations
between the direction of two-dimensional arm movements and cell discharge in primate
motor cortex. J. Neurosci. *2*, 1527–1537.

67.   Georgopoulos, A.P., Schwartz, A.B., and Kettner, R.E. (1986). Neuronal population
coding of movement direction. Science (80-.). *233*, 1416–9.

68.   Sergio, L.E., Hamel-pâquet, C., and Kalaska, J.F. (2005). Motor Cortex Neural Correlates
of Output Kinematics and Kinetics During Isometric-Force and Arm-Reaching Tasks
Motor Cortex Neural Correlates of Output Kinematics and Kinetics During Isometric-
Force and Arm-Reaching Tasks. J. Neurophysiol. *94*, 2353–2378.

69.   Cheney, P.D., and Fetz, E.E. (1980). Functional classes of primate corticomotoneuronal
cells and their relation to active force. J. Neurophysiol. *44*, 773–791.

70.   Ajemian, R., Green, A., Bullock, D., Sergio, L., Kalaska, J., and Grossberg, S. (2008).
Assessing the Function of Motor Cortex: Single-Neuron Models of How Neural Response
Is Modulated by Limb Biomechanics. Neuron *58*, 414–428.

71.   Overduin, S.A., d'Avella, A., Roh, J., Carmena, J.M., and Bizzi, E. (2015). Representation
of muscle synergies in the primate brain. J. Neurosci. *35*, 12615–12624.
72.   Holdefer, R.N., and Miller, L.E. (2002). Primary motor cortical neurons encode functional
muscle synergies. Exp. Brain Res. *146*, 233–243.
73.   Fetz, E.E., and Cheney, P.D. (1980). Postspike facilitation of forelimb muscle activity by
primate corticomotoneuronal cells. J. Neurophysiol. *44*, 751–772.
74.   Schieber, M.H., and Rivlis, G. (2007). Partial reconstruction of muscle activity from a
pruned network of diverse motor cortex neurons. J. Neurophysiol. *97*, 70–82.
75.   Morrow, M.M., and Miller, L.E. (2003). Prediction of muscle activity by populations of
sequentially recorded primary motor cortex neurons. J. Neurophysiol. *89*, 2279–2288.
76.   Todorov, E., and Jordan, M.I. (2002). Optimal feedback control as a theory of motor
coordination. Nat Neurosci *5*, 1226–35.
77.   Suresh, A.K., Goodman, J.M., Okorokova, E. V, Kaufman, M., Hatsopoulos, N.G., and
Bensmaia, S.J. (2020). Neural population dynamics in motor cortex are different for reach
and grasp. Elife *9*.
78.   Athalye, V.R., Carmena, J.M., and Costa, R.M. (2020). Neural reinforcement: re-entering
and refining neural dynamics leading to desirable outcomes. Curr. Opin. Neurobiol. *60*,
145–154.
79.   Mannella, F., and Baldassarre, G. (2015). Selection of cortical dynamics for motor
behaviour by the basal ganglia. Biol. Cybern. *109*, 575–595.
80.   Vyas, S., Even-Chen, N., Stavisky, S.D., Ryu, S.I., Nuyujukian, P., and Shenoy, K. V.
(2018). Neural Population Dynamics Underlying Motor Learning Transfer. Neuron *97*,
1177-1186.e3.
81.   Sadtler, P.T., Quick, K.M., Golub, M.D., Chase, S.M., Ryu, S.I., Tyler-Kabara, E.C., Yu,
B.M., and Batista, A.P. (2014). Neural constraints on learning. Nature *512*, 423–426.
82.   Athalye, V.R., Ganguly, K., Costa, R.M., and Carmena, J.M. (2017). Emergence of
Coordinated Neural Dynamics Underlies Neuroprosthetic Learning and Skillful Control.
Neuron *93*, 955–970.
83.   Athalye, V.R., Santos, F.J., Carmena, J.M., and Costa, R.M. (2018). Evidence for a neural
law of effect. Science (80-.). *359*, 1024–1029.
84.   Koralek, A.C., Jin, X., Long II, J.D., Costa, R.M., and Carmena, J.M. (2012).
Corticostriatal plasticity is necessary for learning intentional neuroprosthetic skills. Nature
483, 331–335.
85.   Neely, R.M., Koralek, A.C., Athalye, V.R., Costa, R.M., and Carmena, J.M. (2018).
Volitional Modulation of Primary Visual Cortex Activity Requires the Basal Ganglia.
Neuron *97*, 1356–1368.
86.   Willett, F.R., Avansino, D.T., Hochberg, L.R., Henderson, J.M., and Shenoy, K. V (2021).
High-performance brain-to-text communication via handwriting. Nature *593*, 249–254.
87.   Khanna, P., Totten, D., Novik, L., Roberts, J., Morecraft, R.J., and Ganguly, K. (2021).
Low-frequency stimulation enhances ensemble co-firing and dexterity after stroke. Cell
184, 912-930.e20.
88.   Ramanathan, D.S., Guo, L., Gulati, T., Davidson, G., Hishinuma, A.K., Won, S.-J.,
Knight, R.T., Chang, E.F., Swanson, R.A., and Ganguly, K. (2018). Low-frequency
cortical activity is a neuromodulatory target that tracks recovery after stroke. Nat. Med.
24, 1257–1267.
89.   Shenoy, K., and Carmena, J. (2014). Combining decoder design and neural adaptation in

brain-machine interfaces. Neuron *84*, 665–680.

90.   Golub, M.D., Chase, S.M., Batista, A.P., and Yu, B.M. (2016). Brain-computer interfaces
for dissecting cognitive processes underlying sensorimotor control. Curr. Opin. Neurobiol.
37, 53–58.

91.   Orsborn, A.L., and Pesaran, B. (2017). Parsing learning in networks using brain-machine
interfaces. Curr. Opin. Neurobiol. *46*, 76–83.

92.   Moxon, K.A., and Foffani, G. (2015). Brain-Machine Interfaces beyond Neuroprosthetics.
Neuron *86*, 55–67.

93.   Paxinos, G., Huang, X.-F., and Toga, A.W. (2013). The Rhesus Monkey Brain in
Stereotaxic Coordinates.

94.   Gilja, V., Nuyujukian, P., Chestek, C.A., Cunningham, J.P., Yu, B.M., Fan, J.M.,
Churchland, M.M., Kaufman, M.T., Kao, J.C., Ryu, S.I., et al. (2012). A high-
performance neural prosthesis enabled by control algorithm design. Nat. Neurosci. *15*,
1752–1757.

95.   Wu, W., Gao, Y., Bienenstock, E., Donoghue, J.P., and Black, M.J. (2006). Bayesian
Population Decoding of Motor Cortical Activity Using a Kalman Filter. Neural Comput.
18, 80–118.

96.   Dangi, S., Orsborn, A.L., Moorman, H.G., and Carmena, J.M. (2013). Design and
Analysis of Closed-Loop Decoder Adaptation Algorithms for Brain-Machine Interfaces.
Neural Comput. *25*, 1693–1731.

97.   Malik, W.Q., Truccolo, W., Brown, E.N., and Hochberg, L.R. (2011). Efficient decoding
with steady-state kalman filter in neural interface systems. IEEE Trans. Neural Syst.
Rehabil. Eng. *19*, 25–34.

98.   Gowda, S., Orsborn, A.L., Overduin, S.A., Moorman, H.G., and Carmena, J.M. (2014).
Designing dynamical properties of brain-machine interfaces to optimize task-specific
performance. IEEE Trans. Neural Syst. Rehabil. Eng. *22*, 911–920.

1798