1 **What do we gain when tolerating loss? The information bottleneck, lossy compression, and**
2 **detecting horizontal gene transfer**
3

4 Apurva Narechania[1]*, Rob DeSalle[1], Barun Mathema[2], Barry Kreiswirth, and Paul J. Planet[1,4,5]*
5
[1]Institute for Comparative Genomics, American Museum of Natural History, New York, NY
[2]Department of Epidemiology, Mailman School of Public Health, Columbia University, New
York, NY
[3]Center for Discovery and Innovation, Hackensack Meridien Health, Nutley, NJ
[4] Division of Infectious Diseases, Children's Hospital of Philadelphia, Philadelphia, PA
[5] Perelman School of Medicine, University of Pennsylvania, Philadelphia, Pennsylvania, United
States of America
13
14 *Correspondence to: Apurva Narechania (anarechania@amnh.org) & Paul J. Planet
15 (planetp@email.chop.edu)

16
17 **Word Count**
18 Abstract: 263
19 Body: 4824
20
21 Running Title: Information bottleneck for detecting recombination
22

Abstract

Most microbes have the capacity to acquire genetic material from their environment.

Recombination of foreign DNA yields genomes that are, at least in part, incongruent with the

vertical history of their species. Dominant approaches for detecting such horizontal gene

transfer (HGT) and recombination are phylogenetic, requiring a painstaking series of analyses

including sequence-based clustering, alignment, and phylogenetic tree reconstruction. Given

the breakneck pace of genome sequencing, these traditional pan-genomic methods do not

scale. Here we propose an alignment-free and tree-free technique based on the sequential

information bottleneck (SIB), an optimization procedure designed to extract some portion of

relevant information from one random variable conditioned on another. In our case, this joint

probability distribution tabulates occurrence counts of k-mers with respect to their genomes of

origin (the relevance information) with the expectation that HGT and recombination will create

a strong signal that distinguishes certain sets of co-occuring k-mers. The technique is

conceptualized as a rate-distortion problem. We measure distortion in the relevance

information as k-mers are compressed into clusters based on their co-occurrence in the source

genomes. This approach is similar to topic mining in the Natural Language Processing (NLP)

literature. The result is model-free, unsupervised compression of k-mers into genomic topics

that trace tracts of shared genome sequence whether vertically or horizontally acquired. We

examine the performance of SIB on simulated data and on the known large-scale

recombination event that formed the *Staphylococcus aureus* ST239 clade. We use this

technique to detect recombined regions and recover the vertically inherited core genome with

a fraction of the computing power required of current phylogenetic methods.

Introduction

Introduction

Whole microbial genomes are being sequenced at an unprecedented rate.[1] Focused

sequencing of key organisms and broad sequencing of microbial environments have expanded

our knowledge of evolution and the microbiosphere[234]. However, the production of data is

outstripping our ability to analyze it[5]. Most work in molecular evolution is grounded in

sequence alignment and phylogenetic tree reconstruction. However, whole genome alignment

breaks down with increasing diversity, and tree-based techniques suffer from an exponential

increase in compute time with broader taxon sampling. The evolution of microbes is particularly

challenging because horizontally transferred elements contribute historical signal that is

unrelated to vertical descent. Most dominant techniques for capturing horizontal gene transfer

(HGT) and recombination require either alignment of reads across a reference genome (eg.,

single nucleotide polymorphism (SNP) based analysis or whole genome alignment[67]. Where

global alignment is impossible, phylogenomic tools require all-against-all analyses designed to

fix genes into aligned orthologous groups[8910]. All of these approaches require careful curation,

tree-building, HGT/Recombination detection analysis, and deliberate sampling to limit data to

reasonable scales. For larger, unbiased datasets that include as much natural variation as

possible, these approaches are not sustainable. To handle the onslaught of genomes, we need

tools that can tolerate information loss without sacrificing knowledge of key evolutionary

events.

Lossy compression, where an individual or algorithm makes decisions about which data

are important (or relevant) from a large body of information[11], may offer a solution. To do this

in a principled way, the relevance of a given dataset can be measured as information retained

about some other correlated variable. For example, in unsupervised natural language

processing (NLP) large corpora of texts are distilled to a few topics that reflect overall themes

by comparing patterns of co-occurring words in the source texts. In topic modeling of this sort,

the texts themselves are the relevance variable. The goal is to cluster the overall word

distribution with respect to the documents from which they arise. If X is the original data

distribution, T its compressed representation, and Y the relevance variable, the challenge is to

pack X into as few clusters, T, as possible without sacrificing too much information, Y. This idea

was first described by Tishby, Pereira and Bialek as the information bottleneck (IB)[12]. It was

premised on rate distortion, Shannon's original theory of lossy compression which yoked signal

distortion to the rate at which that signal can be encoded[13]. Distortion is severe if the signal is

forced through a small communication channel and gets cleaner as the channel widens. The IB's

primary innovation was the use of a relevance variable to quantify this distortion. Topic

modeling was one of this technique's first applications.

Topic modeling has become an important part of the NLP literature with a number of

wider applications to unsupervised machine learning. The dominant technique in the field is

Latent Dirchilet Allocation (LDA)[14], a probabilistic method, that like the IB, considers each

document as a mixture of topics. Some groups have applied this idea to whole genomes[151617],

and since the publication of STRUCTURE, LDA has become foundational in the genetics

literature where populations are inferred by the distribution of alleles at measured loci[18].

Despite LDA's popularity and success, a number of authors have shown that unbalanced

sampling can lead to erroneous or missed population assignments[19]. LDA also makes a number

of statistical assumptions including the assignment of hyperparameters and a Dirchilet prior[20].

In contrast, the IB is model free and less likely to suffer from size sample bias. The distortion

measure emerges from the analysis of the relevance variable, revealing underlying topics

without having to set any distributional parameters other than the number of clusters

expected.

Because it is model free, the IB is a powerful approach for microbial genomics where

very little is known about the diversity of the organisms in nature or their distribution.

Genomes are living documents that can be sliced into words of arbitrary size. This metaphor is

straightforward and has been explored with respect to other NLP techniques elsewhere[212223]. In

a genomic context, where words are k-mers (X) and documents (Y) are their genomes of origin

we hypothesized that IB derived topics (T) may represent co-occurring groups of k-mers that

highlight shared ancestry. These topics might include k-mers arranged in co-linear blocks

corresponding to a single element, or k-mers distributed across the genome that were inherited

in concert. In either case, compression of these k-mers into topics is guided by how often they

co-occur with respect to their genomes of origin. This mechanism will tend to group adjacent k-

mers in a recombined region because the recombination event is likely restricted to just a

subset of taxa. Additionally, shared tracts of co-occuring k-mers common to all genomes, offer

a simple, operational definition of a genomic "core".[76] For microbial genomes where HGT is

rampant[2425] we can therefore use the technique to learn which portions of the genome form

the vertically inherited core, and which portions have been recombined, or inherited

horizontally. In the NLP topic modeling analogy, the core genome of a species could be

considered the set of meaningful words across every book in a specialized library, while

recombined regions are like themes or ideas restricted to only certain shelves.

Here we apply the IB to microbial genomes. Remarkably, our approach identifies

recombination tracts without making any attempt to model evolution, annotate genes,

reconstruct trees, or build alignments. In addition, the IB treats genic and intergenic portions of

the genome equally, obviating the need for gene-based pangenomic analysis[26]. Applying the

information bottleneck to a k-mer occurrence matrix identifies genome segments with shared

vertical or horizontal evolutionary history in a fraction of the time used by other approaches.

Theory and Implementation

Consider a set of genomes each of which is chopped into overlapping k-mers. One way

to measure the overall relatedness of two of these genomes is to compare their k-mer

conditional distributions. To do this we can define

125
$$p(x|y) = \frac{n(x|y)}{\sum_y n(x|y)}$$

where X is the set of all k-mers, Y the set of all genomes, and *n(x|y)* is the occurrence count of

the k-mer, x, in genome y. The exercise would then be to group genomes with similar k-mer

distributions across all k-mers. In the natural language processing literature, this idea was

formalized as distributional clustering[27].

However, finding the right distance or distortion measure between these distributions is

non-trivial. It is especially difficult when the important features of the signal are unknown.

Imagine compressing music into MP3s without data on which frequencies are most important

for human perception, or determining themes from a body of literature if words were

decoupled from their books. Even when important components of the signals are known, most

clustering algorithms will resort to domain specific, pairwise distances or quantization to find a

compressed set of classes with either high levels of internal connectivity or low levels of

internal distortion. However, domain specific distortions reduce the usefulness of these

clustering techniques. For example, in bioinformatics, clustering based on sequence alignment

is subject to all the vagaries of the alignment procedure and parameters therein.

An antidote to these narrow clustering applications is to operate in an information

theoretic space where the primary measurement is relevant quantization[12]. The IB extends

Shannon's rate distortion theory by guiding it with an additional, orienting variable. Tishby et

al[12] enriched a theory about transmission efficiency with the concept of relevance (Y), or the

value of the information transmitted. The choice of Y defines relevant features in the signal. If X

and Y are tabulated as a joint probability distribution, the information that X provides about Y is

squeezed through a simpler representation, T. For the technique to work, the two variables in

our joint distribution *p(x,y)* must be non-independent, or more precisely, must have positive

mutual information, *I(X,Y)*:

151
$$I(X,Y) = \sum_x \sum_y p(x)p(y|x) \log \frac{p(y|x)}{p(y)}$$

T is now a meaningful compression of the data, maximizing the mutual information between

the clusters and documents, I(T;Y), while minimizing the mutual information between the

words and the clusters, I(T;X). The IB is a classic optimization problem.

With the distribution in hand and implemented as a k-mer occurrence matrix, we can

quantize the set of all k-mers directly by minimizing information lost about their source

genomes. If X is compressed into T then we can find the optimal assignments for X by

minimizing the following Lagranian with respect to Y:

$$\mathcal{L}[p(t|x)] = I(X;T) - \beta I(X;Y)$$

This formulation balances the compactness of X, with the erosion of information about Y. β is a

multiplier that slides through the optimization landscape. As beta approaches 0, k-mers are

clumped into fewer and fewer clusters, emphasizing compression. As beta approaches infinity,

every k-mer is its own cluster, preserving all relevant information. Of course, collapsing all k-

mers into one cluster is overly reductive, and assigning each k-mer to its own cluster is

meaningless. The IB negotiates these two extremes (Figure 1). In NLP, the result is a set of

clusters that coalesce into topics over a body of literature[28]. In genomics, these same clusters

might yield co-occurring and/or spatially co-located k-mers with distinct biological and/or

evolutionary meaning.

Remarkably, minimizing the Lagranian above has an exact, optimal solution[12]. The most

surprising outcome of this solution is that the relative entropy, or Kullback Liebler divergence[29],

emerges as the distortion measure for the information bottleneck. The relative entropy is a

fundamental quantity in information theory, and in the IB context, it measures the distortion

between the points, x (k-mers), as they are quantized into their clusters, t, with respect to the

relevance variable, y (genomes):

$$D_{KL} = \sum_y p(y|x) \log \frac{P(y|x)}{P(y|t)}$$

Calculation of the optimal solution requires soft clustering, that is, any given k-mer can exist in

more than one cluster. But soft clustering can be slow and difficult to devise. Early

implementations of the information bottleneck therefore settled on hard clustering

approximations. In hard or deterministic clustering, each k-mer is assigned to only one cluster,

an assumption that eases computational burden but does not generally arrive at globally

optimal solutions.

The most obvious hard clustering algorithm is agglomerative, or bottom-up[30]. Consider

again the set of all genomes, X, and their compressed representation, T. If we start with a

scenario where every k-mer in X occupies its own singleton cluster, we can systematically

reduce the dimensionality by merging clusters that minimize some distortion score. This greedy

merging procedure produces a tree. But agglomerative clustering does not yield stable cluster

membership. The tree varies every time the process is reinitialized. Worse, its computation is

expensive, requiring cubic time complexity and quadratic memory complexity. In a genomic

context where we routinely deal with billions of k-mers, this approach is a nonstarter.

Instead, we implemented a sequential clustering procedure where the number of

clusters is defined at the outset and remains consistent throughout the calculation. From an

initial random distribution of all k-mers across this set of clusters, we draw one k-mer out, and

represent it as a singleton. Now using greedy optimization, we merge this singleton into one of

the existing bulk clusters. Slonim's sequential information bottleneck (SIB)[31] employs the

Jensen-Shannon divergence[3221] in the cost of merging a k-mer, x, into a cluster, t:

$$d(x,t) = (p(x) + p(t)) * D_{JS}(p(y|x), p(y|t))$$

A k-mer will join a new cluster only if its new address reduces the total distortion. Otherwise it

will remain in its existing cluster. With respect to our initial random conditions, this algorithm is

guaranteed to converge to a local optimum. We mitigate the risk of getting trapped in local

optima by testing several random initializations.

208   Once the clusters stabilize, we quantify the information captured by calculating the

209   normalized mutual information, *NMI = I(T;X) / I(X;Y).* Trivially, NMI = 1 when each k-mer

210   occupies its own cluster. The curve traced between T = 1 (NMI = 0) and T = *x* is called the

211   relevance compression curve[33]. This is analogous to the optimization of β in the Lagranian

212   above, but for the deterministic case involving hard clustering. As with β, the shape of this

213   curve describes the compressibility of the data.

214   The most important aspect of the SIB, and the reason we chose it for this work, is that it

makes the concept of the information bottleneck accessible to modern genomics. The time

complexity is linear in the number of k-mers and the number of clusters. This improvement

makes information theoretic NLP a useful tool to discover genomic topics encoded as clusters

of co-occurring k-mers.

Results and Discussion

The bottleneck in test: one large, simulated HGT event

The simple example in Figure 2 illustrates how the bottleneck works in practice. In

SimBac[34], we simulated four 1 megabase genomes with a single 200 kilobase recombination

event. The event is common to genomes 0, 2 and 3, but is not found in strain 1. We initialized

the simulation with a random distribution of 19-mers across five clusters. To learn the true

distribution, we leveraged information in our relevance variable, the source genomes. The inset

table shows how this distribution evolves as we iterate through the sequential information

bottleneck (SIB). Since the relevance variable is expected to drive the unsupervised

compression of these k-mers, we also included the genomes in this table. Counts across each

row therefore reflect how many times a k-mer in that cluster is found in a particular genome.

The SIB starts by randomly distributing the k-mers, destroying all information available

in the original occurrence matrix. At the outset, the normalized mutual information is therefore

zero. With each SIB loop, we attempt to reclaim as much of this information as possible given

the number of clusters we choose to model. Because the technique is inherently lossy, the SIB

will never recover all of the information originally encoded, but aims to extract the most salient

themes, or topics.

In the example shown here, after the first loop, cluster 3 (the cluster designations are

arbitrary) has attracted the most k-mers in roughly even proportion across the genomes. The

normalized mutual information has also jumped to 0.69, indicating that just one pass of sorting

k-mers into five bins effectively captures 70% of the information available in the original

occurrence matrix. The second and third loops refine the other clusters into mutually exclusive

sets and add to cluster 3, which strengthens into a genomic "core" defined here as the cluster

of k-mers with the highest average representation across all genomes and the lowest index of

dispersion.

By the third pass through the k-mers, the SIB reaches a plateau in the normalized

mutual information, and the counts of k-mers across clusters and genomes have stabilized. For

this particular set of starting conditions, the SIB reclaims nearly 91% of the information in the

original matrix. To put this in perspective, we have effectively reduced the outsized,

uninterpretable dimensions of our original data – 1.25 million unique k-mers – into the 5

clusters we set out to model, while sacrificing only 9% of the original information present in the

relevance variable.

In a genomic context, we hypothesized that the spatial organization of k-mer clusters

would correspond to areas of common ancestry. In Figure 2, we mapped k-mers from various

clusters to the genome backbones of strain 1 and strain 2. Cluster 3 occupies the outer tracks of

both strains. This cluster emerges as a dense block of shared genome sequence and

corresponds to our definition of a bottleneck-defined core. But the block is interrupted by our

simulated recombination event. Since this event is restricted to only genomes 0, 2 and 3, the

region is absent from the core. Its k-mers are instead captured by cluster 4 while cluster 1

serves as a counterpoint, containing the ancestral state prior to the simulated event.

Several smaller, simulated HGT events

Though large hybridization events like the one we simulated here do occur (see our

analysis of ST239 *S. aureus* below), smaller and more abundant events typify most microbial

evolution[35]. To see how the bottleneck performs in this more challenging case, we simulated

ten 1 megabase genomes with a background mutation rate of 0.01 and a recombination rate of

0.0001, resulting in 57 discrete events averaging 500 basepairs in size (from 6 to 2884 bases). In

Figure 3, the innermost track marks the locations of these events.

The ability to detect horizontally transferred sequence is strongly dependent on its

evolutionary distance from the genome background[7]. To visualize this dependence, we

modulated the divergence of our 57 recombination events (an arbitrary number derived from

the first simulation) and measured the effect on the core cluster, one of 60 modeled for this

simulation. The innermost histogram in Figure 3 shows the core pattern with an external

(between species) divergence rate of 0.1, an order of magnitude higher than the background.

We observe clear "valleys" in the k-mer distribution of the core that are coincident with the

positions of our 57 events. But this pattern steadily disappears as we sweep through lower

rates of divergence (0.05, 0.03, and 0.01). The outermost track models the same mutation rate

as the background, resulting in dulled or partially filled valleys in the core genome. Plots of core

k-mers function almost as a photographic negative, highlighting blank spaces as regions of

potential evolutionary interest.

The k-mers that would otherwise occupy these gaps, are sorted into other clusters

because they are unique to only a subset of the genomes, and carry the recombination signal.

As we have shown in our first simulation, k-mers corresponding to the ancestral state should

fall into a different cluster. Note that this does not necessarily mean that each side (donor and

recipient) of an HGT event has its *own* cluster. Recall that compression is driven by genome

origin. If a single common ancestor sustains multiple transfer events, all k-mers from those

events will merge into a single cluster because they are shared by the same subset of

descendants.

The accounting becomes increasingly complicated when events overlap. Overlapping

events might mix across clusters depending on their arrangement and how frequently they

have been overwritten. When detection becomes difficult, we instead rely on an evolutionary

event's imprint on the core cluster. This approach exploits the idea of the core as a

photographic negative or a clonal frame. The pattern of HGT events in this negative is evident

by eye, but if the number of input genomes and the number of modeled clusters is large, visual

inspection is a burden, and subject to error in interpretation. Instead we introduce a method

based in change point detection to automatically detect changes in k-mer frequency[36]. We

specifically employ Bayesian change point detection[37] to model probabilities of change in the k-

mer frequency stream. As shown in Figure 4 change point probabilities spike at the start and

end of HGT events.

In addition to change point detection, we note that if counts of k-mers in an HGT region

are significantly lower than the rest of the core's background (Wilcoxon, $p < 0.05$), these

depletions can qualify as a simple signal marking some combination of HGT events. With these

criteria, at a divergence rate of 0.1, the bottleneck captures 56 of the 57 simulated events,

missing only the smallest.

The k-mer skim

Accounting for every overlapping k-mer in each strain is an unnecessarily close reading

of our genomic text. We can save on both memory and computation by selecting fewer k-mers

(skimming) from our source genomes with some set space between each sample. In Figure 5 we

show that even when sampling every 25[th] 19-mer in our ten 1 Mbase simulated genomes, we

still detect 55 of our 57 recombination events. Because the bottleneck relies on the signal

inherent in k-mer co-occurrence, as we reduce the density of our k-mer sampling, we lose

detection of the smallest events first. However, the compute time savings more than

compensate for this loss in sensitivity. While analyzing every 19-mer requires nearly 12

minutes, skimming every 25[th] reduces the runtime to 30 seconds. This compares favorably with

the efficiency of both ClonalFrameML[7] and Gubbins[6], the two dominant HGT detection

methods in the literature. ClonalFrameML requires 110 seconds and captures only 47 of our 57

events. Gubbins finds 54 in 21 seconds. However, both ClonalFrameML and Gubbins require

alignment and phylogenetic tree reconstruction, which both add massive prior computational

cost and time.

Because the IB is alignment-free and tree-free, it is theoretically capable of handling

larger datasets than any existing technology in reasonable amounts of time. To test this, we

simulated 1000 1 Mb genomes with the same parameters as the smaller dataset shown in

Figure 3. The simulation generated 620 unique recombination events. ClonalFrameML detected

564 (91%). Including time required to build a guide tree, this calculation consumed 32.5 CPU

hours. Gubbins was slightly more accurate and significantly faster: 583 (95%) events over 16.3

CPU hours. Using Figure 5 as a guide, we ran the 1000 genome dataset through the SIB using a

25 base-pair skim. We detected an HGT imprint at 92% of sites in 1.5 CPU hours.

How well does the IB hold up under extreme evolutionary pressure?

To evaluate the performance of our technique with respect to recombination size and

divergence rate, we simulated sets of ten 1 megabase (Mb) genomes for each variable. We set

default parameters to 0.01 for background rate, 0.001 for recombination rate, 0.1 for HGT

divergence rate, and 500 base pairs for average recombination tract size. We performed 100

replicates at each size and rate, and measured the imprint of the simulated events on the core

cluster without the skim feature. Figure 6A shows this sweep for recombination tract length,

and Figure 6B, for recombination tract divergence. In both cases, we observe saturating

behavior. We see recombination imprints at 90% accuracy when events are larger than 100

base pairs with divergence rates of at least 0.02. Notably, our procedure can detect HGT in at

least half of events that diverge at the very low rate of 0.005, well below the background. And

only the very smallest recombination events (less than 7 basepairs) elude our technique

completely.

Recombination tract length and divergence have direct and measureable effects on the

efficacy of detection. As long as the total length of all recombination events is less than half the

size of the genome, the core remains intact, and we can easily isolate HGT events of sufficient

size and divergence. But recombination and background mutation rates are problematic

because they redefine the core. For example, at high rates of recombination, every base of a 1

Mb genome is likely scrambled. Under such flux, some sites recombine several times. A high

background mutation rate also disrupts stretches of common sequence that mark the core. As

these rates increase, the core genome itself erodes. To measure this phenomenon, we again

simulated 100 sets of ten 1 Mb genomes across a variety of recombination and background

mutation rates. All three curves in Figure 7 show a steep decline in the size of the core with

increasing recombination rate. At rates of 0.01 and 0.1, we see no shared core at all. Each

genome has essentially rewritten itself into something distinct from all others. Core genome

signal grows stronger with lower background mutation, but even with background mutation set

to essentially zero, a high recombination rate destroys the core.

The bottleneck in action: one large, real world hybridization event

We used genomes from ST239 *Staphylococcus aureus* to illustrate that our method can

corroborate known, large scale recombination events found in nature. The ST239 strain is a

hybrid: a segment from a CC30 (clonal complex 30) donor replaced nearly 20% of the

homologous region in a CC8 strain[38]. The evolutionary histories of genes across these segments

are incongruent. Previous studies compared the histories of thousands of genes to reach this

conclusion[39]. Here, we attempt to localize this same phenomenon using the co-occurrence

pattern of k-mers alone. We chose 10 genomes (GCA_000146385.1, GCA_000012045.1,

GCA_000011505.1, GCA_000011265.1, GCA_000013425.1, GCA_000204665.1,

GCA_000159535.2, GCA_000027045.1, GCA_000017085.1, and SA21300), sampled from both

the donor clade (CC30), the recipient clade (CC8), and genomes outside of the evolutionary

event. When cut into overlapping 19-mers (no skim), these 10 genomes dissolve into 28.8

million k-mers, 4.72 million of which are unique.

Figure 8 highlights two of these 10 genomes, and three of the 60 clusters we modeled

for this analysis. Both *S. aureus* COL (CC8) and *S. aureus* T0131 (ST239) share a large, congruent

core. The gap in this core characterizes the dimensions of the recombination event, whose k-

mers are split into two other clusters, shown here as the second and third tracks. Like subtopics

in a vast library, the bottleneck learns the complete structural evolution of the clade as tracts,

or topics, of co-occurring sequence. The clusters themselves comprise an evolutionary model

for the structural event and the core genome. This evolutionary model is derived not from

traditional character-based phylogenetic analysis, but from the presence/absence pattern of k-

mers squeezed into a predefined number of groups. Genome origin guides the k-mer sort by

forming the basis of the distortion measure. We lose information in a controlled and

quantitative way, and we short circuit the long and arduous tasks phylogenomic analyses

require[39] with an information theoretic procedure that runs for 2 hours on 1 CPU.

By definition, this sort of lossy compression is not perfect. In Figure 8, seemingly

unrelated contaminants pollute the recombined region's clusters. This is equivalent to channel

noise. It recalls Shannon's original formulation of the rate distortion problem[13]. When we force

all the signal in our k-mer occurrence matrix through a narrow five cluster channel, portions of

the original message emerge garbled. In this case, modeling more clusters increases the rate of

transmission, and reduces the distortion of the message received.

With respect to the information bottleneck, we can quantify this effect using a

relevance-compression curve[28]. Figure 9 shows curves for the ST239 genomes alongside 10

genomes of *Mycobacterium tuberculosis* and *Helicobacter pylori.* In all three cases, as the

number of clusters modeled increases, we capture more normalized mutual information. The

theoretical extremes for this curve are intuitive. At the origin, all the relevant information is

destroyed. At the other end, we retain too much relevant information to interpret. The curve

traced between these two extremes is a fingerprint of the data. A convex shape suggests

natural structure easily modeled with just a few clusters. We see this in *M. tuberculosis*, a

species thought to be largely clonal with little recombination. On the other hand, data that

resists compression flattens this curve. Highly recombinogenic species like *H. pylori* suffer this

sort of steep information loss. Theoretically, the space above the curve for each species is

unachievable by any process, forming an upper bound. The relevance-compression curve

therefore defines absolute limits on the quantity and quality of information communicated as

we sweep through a dilating channel. This approach introduces a new type of comparative

genomics based not on alignments and trees, but on compression. We interpret the shape of

the relevance compression curve as a proxy for evolutionary mode. A convex curve implies

fewer recombination events and more vertical signal, whereas a flattened curve may signal a

species with a more open pangenome.

In the case of ST239, asking for just two clusters – a very narrow channel – captures

more than 40% of the relevant information. Remarkably, these two clusters separate the core

from the recombined region. Even the simplest model learns the most prominent evolutionary

process. Further along the curve, fifteen clusters capture almost all of the information. Beyond

fifteen, the curve elbows, and modeling gains are slight. In this way, the relevance-compression

curve defines the optimal number of clusters.[33,40] But in the light of evolution this bend may

have a deeper meaning. Fifteen clusters are enough to adequately capture the complete set of

k-mer aggregation patterns across our chosen genomes. This point of diminishing returns may

signify an opportunity for interpretive balance: not so many clusters that we drown dominant

evolutionary events, and not so few that we neglect to model subtle k-mer co-occurrence

patterns. This particular use of the well-known elbow method in our information theoretic

context puts a crude limit on the dominant evolutionary paths taken by the genomic elements

that comprise our species.

420
Conclusion (words=149)

The information bottleneck, a lossy compression technique borrowed from the information

theoretic and Natural Langauge Processing literature, is well suited to detecting evolutionary

patterns in sets of co-occuring k-mers. Here we have shown that we can detect simulated and

real recombination events while highlighting a core set of k-mers that comprise the vertically

inherited portion of any set of genomes. Moreover, the compressibility of any given set of

genomes, as embodied in their relevance compression curves, offers a new way to compare the

pangenomes of very different clades in the microbial tree of life. In our application, the

bottleneck is informed by genome origin, our relevance variable. But the technique is general.

The information bottleneck can be used for any biological contingency matrix where the goal is

to cluster a variable into interpretable groups by preserving as much information as possible in

the variable to which it is linked.

433
434   Software implementation: NECK (https://github.com/narechan/neck)
435
436
Figure Legends

Figure 1. The information bottleneck. In the information bottleneck a distribution, *X*, is

compressed into *T* while retaining as much information as possible about a correlated relevance

variable, *Y*. The joint distribution, *p(x,y)*, has positive mutual information and the goal of the

information bottleneck is to capture as much of that information as possible at interpretive

scale. The technique is a classic optimization problem wherein the mutual information between

T and *X* is minimized, while the mutual information between *T* and *Y* is maximized. At

optimality, *T* is presumed to be a lossy but adequate model of *X*.

Figure 2. One simulated HGT event. A simple set of four simulated genomes with a single large

transfer event is shown. The transfer occurs in the common ancestor to genomes 0, 2, and 3.

The inset chart clearly shows that the k-mers corresponding to this event are captured by

cluster 4, while the ancestral state is captured by cluster 1. K-mers from these clusters map to

the location of the simulated event in genomes 0, 2 and 3 and genomes 1, respectively. Cluster

3 is the core and contains only one gap corresponding to the HGT region.

Figure 3. Several simulated HGT events. The innermost ring of this circos plot shows the

locations of 57 simulated HGT events across 10 1 Mbase genomes. The remaining concentric

tracks plot the core set of k-mers as calculated by the information bottleneck. In the outermost

frequency plot, the 57 HGT events diverge at the same mutation rate as the background, 0.01.

Going in towards the center, we increase the HGT divergence rate of the events to 0.03, 0.05,

and 0.1. Gaps in the core correspond with the simulated HGT events whose k-mers are sorted

into other clusters.

Figure 4. Bayesian change point detection. The two innermost rings mirror those in Figure 3.

The outermost ring plots the posterior probabilities of change in the k-mer frequencies.

Figure 5. The k-mer skim. Here we show the decrease in HGT detection sensitivity as a function

of the density of k-mers sampled. The higher the k-mer skim factor (defined as the number of

positions skipped before the next k-mer is sampled), the lower the density of k-mers subject to

the information bottleneck. The inset shows the plateau behavior near the origin for k-mer

skim factors of 1, 5, 10, 25, and 50.

Figure 6. Varying HGT length and divergence. HGT detection rates are shown with respect to

increasing HGT length and divergence.

Figure 7. Varying recombination and background mutation rates. We measure the fraction of

unique k-mers in each simulation captured by the core genome cluster as a function of

recombination rate and background mutation rate. The core genome signal is strongest at low

rates of recombination and background mutation. At higher recombination rates, there is no

evidence for a core genome of any kind regardless of the background mutation rate.

Figure 8. Modelling ST239's hybridization event. We selected 10 *S. aureus* genomes to track the

ST239 hybridization event with the information bottleneck. COL was chosen to represent the

CC30 donor strain, and T0131 the CC8 acceptor. Of the 60 clusters we calculated, we show the

three that capture the hybridization event. The innermost track is a frequency plot of k-mers

that define the core. The second and third tracks are flipsides of the HGT event that created

ST239.

Figure 9. Relevance compression curves. In an information bottleneck experiment, the

relevance compression curve traces the increase in normalized mutual information with the

number of clusters modeled. The curves quantify the amount of information lost at a given

modeling threshold. We show how this type of relationship can function as a marker for

evolutionary strategy by calculating curves for three very different groups of microbes: *M.*

tuberculosis, a species thought to demonstrate little if any HGT; *S. aureus*, a species considered

largely clonal with occasional HGT; and H. pylori, a species known to employ HGT as an engine

for diversity.

References

1. GenBank and WGS Statistics. https://www.ncbi.nlm.nih.gov/genbank/statistics/.

2. Hug, L. A. *et al.* A new view of the tree of life. *Nat. Microbiol.* **1**, (2016).

3. Rinke, C. *et al.* Insights into the phylogeny and coding potential of microbial dark matter.

Nature **499**, 431–437 (2013).

4. Sogin, M. L. *et al.* Microbial diversity in the deep sea and the underexplored "rare biosphere".

Proc. Natl. Acad. Sci. **103**, 12115–12120 (2006).

5. Stephens, Z. D. *et al.* Big Data: Astronomical or Genomical? *PLOS Biol.* **13**, e1002195

(2015).

6. Croucher, N. J. *et al.* Rapid phylogenetic analysis of large samples of recombinant bacterial

whole genome sequences using Gubbins. *Nucleic Acids Res.* **43**, e15–e15 (2015).

7. Didelot, X. & Wilson, D. J. ClonalFrameML: Efficient Inference of Recombination in Whole

Bacterial Genomes. *PLOS Comput. Biol.* **11**, e1004041 (2015).

8. Chiu, J. C. *et al.* OrthologID: automation of genome-scale ortholog identification within a

parsimony framework. *Bioinformatics* **22**, 699–707 (2006).

9. Page, A. J. *et al.* Roary: rapid large-scale prokaryote pan genome analysis. *Bioinformatics* **31**,

3691–3693 (2015).

10.   Zhao, Y. *et al.* PGAP: pan-genomes analysis pipeline. *Bioinformatics* **28**, 416–418

(2012).

11.   Marzen Sarah E. & DeDeo Simon. The evolution of lossy compression. *J. R. Soc.*

Interface **14**, 20170166 (2017).

12.   Tishby, N., Pereira, F. C. & Bialek, W. The information bottleneck method.

arXiv:physics/0004057 (2000).

13.   Shannon, C. E. A Mathematical Theory of Communication. *Bell Syst. Tech. J.* **27**, 379–

423 (1948).

14.   Blei, D. M., Ng, A. Y. & Jordan, M. I. Latent Dirichlet Allocation. *J. Mach. Learn. Res.*

3, 993–1022 (2003).

15.   Liu, L., Tang, L., Dong, W., Yao, S. & Zhou, W. An overview of topic modeling and its

current applications in bioinformatics. *SpringerPlus* **5**, 1608 (2016).

16.   La Rosa, M., Fiannaca, A., Rizzo, R. & Urso, A. Probabilistic topic modeling for the

analysis and classification of genomic sequences. *BMC Bioinformatics* **16**, S2 (2015).

17.   Chen, X., Hu, X., Shen, X. & Rosen, G. Probabilistic topic modeling for genomic data

interpretation. in *2010 IEEE International Conference on Bioinformatics and Biomedicine*

(BIBM) 149–152 (2010). doi:10.1109/BIBM.2010.5706554.

18.   Pritchard, J. K., Stephens, M. & Donnelly, P. Inference of Population Structure Using

Multilocus Genotype Data. *Genetics* **155**, 945–959 (2000).

19.   Wang, J. The computer program structure for assigning individuals to populations: easy

to use but easier to misuse. *Mol. Ecol. Resour.* **17**, 981–990 (2017).

20.   Wallach, H. M., Mimno, D. M. & McCallum, A. Rethinking LDA: Why Priors Matter. in

Advances in Neural Information Processing Systems 22 (eds. Bengio, Y., Schuurmans, D.,

Lafferty, J. D., Williams, C. K. I. & Culotta, A.) 1973–1981 (Curran Associates, Inc., 2009).

21.   Sims, G. E., Jun, S.-R., Wu, G. A. & Kim, S.-H. Alignment-free genome comparison

with feature frequency profiles (FFP) and optimal resolutions. *Proc. Natl. Acad. Sci.* **106**,

2677–2682 (2009).

22.   Cong, Y., Chan, Y. & Ragan, M. A. A novel alignment-free method for detection of

lateral genetic transfer based on TF-IDF. *Sci. Rep.* **6**, 30308 (2016).

23. Cong, Y., Chan, Y. & Ragan, M. A. Exploring lateral genetic transfer among microbial

genomes using TF-IDF. *Sci. Rep.* **6**, 29319 (2016).

24. Polz, M. F., Alm, E. J. & Hanage, W. P. Horizontal gene transfer and the evolution of

bacterial and archaeal population structure. *Trends Genet.* **29**, 170–175 (2013).

25. Planet, P. J. Reexamining microbial evolution through the lens of horizontal transfer. *EXS*

247–303 (2002).

26. Tettelin, H. *et al.* Genome analysis of multiple pathogenic isolates of Streptococcus

agalactiae: Implications for the microbial "pan-genome". *Proc. Natl. Acad. Sci.* **102**, 13950–

13955 (2005).

27. Pereira, F., Tishby, N. & Lee, L. Distributional Clustering of English Words. in

Proceedings of the 31st Annual Meeting on Association for Computational Linguistics 183–

190 (Association for Computational Linguistics, 1993). doi:10.3115/981574.981598.

28. Slonim, N. The Information Bottleneck: Theory and Applications. *Dr. Diss. Hebr. Univ.*

Jerus. Isr. 2003 157.

29. Kullback, S. & Leibler, R. A. On Information and Sufficiency. *Ann. Math. Stat.* **22**, 79–

86 (1951).

30. Slonim, N. & Tishby, N. Agglomerative Information Bottleneck. in *Proceedings of the*

12th International Conference on Neural Information Processing Systems 617–623 (MIT

Press, 1999).

31. Slonim, N., Friedman, N. & Tishby, N. Unsupervised Document Classification Using

Sequential Information Maximization. in *Proceedings of the 25th Annual International ACM*

SIGIR Conference on Research and Development in Information Retrieval 129–136 (ACM,

2002). doi:10.1145/564376.564401.

32.   Lin, J. Divergence measures based on the Shannon entropy. *IEEE Trans. Inf. Theory* **37**,

145–151 (1991).

33.   Still, S. & Bialek, W. How Many Clusters? An Information-Theoretic Perspective.

Neural Comput **16**, 2483–2506 (2004).

34.   Brown, T., Didelot, X., Wilson, D. J. & Maio, N. D. SimBac: simulation of whole

bacterial genomes with homologous recombination. *Microb. Genomics* **2**, (2016).

35.   Didelot, X. & Maiden, M. C. J. Impact of recombination on bacterial evolution. *Trends*

Microbiol. **18**, 315–322 (2010).

36.   Truong, C., Oudre, L. & Vayatis, N. Selective review of offline change point detection

methods. *Signal Process.* **167**, 107299 (2020).

37.   Barry, D. & Hartigan, J. A. A Bayesian Analysis for Change Point Problems. *J. Am. Stat.*

Assoc. **88**, 309 (1993).

38.   Robinson, D. A. & Enright, M. C. Evolution of Staphylococcus aureus by Large

Chromosomal Replacements. *J. Bacteriol.* **186**, 1060–1064 (2004).

39.   Narechania, A. *et al.* Clusterflock: a flocking algorithm for isolating congruent

phylogenomic datasets. *GigaScience* **5**, (2016).

40.   Slonim, N., Atwal, G. S., Tkačik, G. & Bialek, W. Information-based clustering. *Proc.*

Natl. Acad. Sci. **102**, 18297–18302 (2005).

585
586
587
588

Figure 1

Initialize	genome0	genome1	genome2	genome3
CLUST0	199366	199350	199437	199282
CLUST1	200184	200439	200134	200194
CLUST2	199693	199696	199591	199808
CLUST3	200765	200718	200857	200785
CLUST4	199974	199779	199963	199913
NMI = 0				
loop 1				
CLUST0	3270	3954	4079	0
CLUST1	15808	237766	19369	15327
CLUST2	9348	10535	1175	10552
CLUST3	746003	747727	747728	747728
CLUST4	225553	0	227631	226375
NMI = 0.69				
loop 2				
CLUST0	7093	19812	50361	0
CLUST1	0	206335	0	0
CLUST2	28277	21421	0	37257
CLUST3	746103	752414	752413	752314
CLUST4	218509	0	197208	210411
NMI = 0.89				
loop 3				
CLUST0	0	12719	43268	0
CLUST1	0	206335	0	0
CLUST2	48715	21421	0	51754
CLUST3	753196	759507	759506	752314
CLUST4	198071	0	197208	195914
NMI = 0.91				

Figure 2

Figure 3

query.1

Figure 4

Figure 5

Figure 6

Figure 7

SaCOL   SaT0131

Figure 8

Figure 9