SampleQC: robust multivariate, multi-celltype, multi-sample quality control for single cell data

Will Macnair[1,2,*] and Mark D. Robinson[1]

[1]Department of Molecular Life Sciences and SIB Swiss Institute of Bioinformatics, University of Zurich, Winterthurerstrasse 190, 8057 Zurich, Switzerland.

[2]Current address: F. Hoffmann-La Roche Ltd., Pharma Research and Early Development, Neuroscience, Ophthalmology and Rare Diseases, Roche Innovation Center Basel, Grenzacherstrasse 124, 4070 Basel, Switzerland.

[*] to whom correspondence should be addressed: will.macnair@roche.com

Abstract

Quality control (QC) is a critical component of single cell RNA-seq processing pipelines. Many single cell methods assume that scRNA-seq data comprises multiple celltypes that are distinct in terms of gene expression, however this is not reflected in current approaches to QC. We show that the current widely-used methods for QC may have a bias towards exclusion of rarer celltypes, especially those whose QC metrics are more extreme, e.g. those with naturally high mitochondrial proportions. We introduce `SampleQC`, which improves sensitivity and reduces bias relative to current industry standard approaches, via a robust Gaussian mixture model fit across multiple samples simultaneously. We show via simulations that `SampleQC` is less susceptible than other methods to exclusion of rarer celltypes. We also demonstrate `SampleQC` on complex real data, comprising up to 867k cells over 172 samples. The framework for `SampleQC` is general, and has applications as an outlier detection method for data beyond single cell RNA-seq. `SampleQC` is parallelized and implemented in `Rcpp`, and is available as an `R` package.

Background

Developments in single cell RNA-seq (scRNAseq) technology have enabled experimenters to quantify transcriptional profiles for ever larger and more complex experiments (1; 2; 3). The transformational nature of single cell RNA-seq is its ability to measure transcriptional expression from nanolitre volumes. However, these tiny volumes result in noisy measurement, and the cells themselves can be strongly affected by the process of measurement. Quality control (QC) is therefore a critical element of pre-processing scRNAseq data: experimenters wish to carefully remove 'bad' cells, while minimising both loss of healthy cell datapoints and any bias in the types of cells retained (4). Cells can be 'bad' due to either technical issues such as droplets with unsuccessful reactions, or biological perturbations such as apoptosis. As the size and complexity of experiments increases, doing this for each sample individually becomes more challenging, and researchers require computational assistance to make the task feasible.

A fundamental issue with methods aiming to exclude poor quality cells is adequately defining 'poor quality'. This is both challenging in itself and context-dependent. One approach to defining quality is in terms of the quantity of information provided by a cell, i.e. the number of reads or features. We might then seek to exclude all cells with too few reads. However, if there are sufficiently many of these cells, the total information provided could be enough to perform useful tasks (e.g. using 'pseudobulk' approaches to identify genes with differential expression between conditions (5; 6)). Similarly, high proportions of mitochondrial reads are associated with stressed and apoptotic cells (7), and excluding cells on the basis of high mitochondrial proportion (e.g. cells with greater than 5% mitochondrial reads in mice, or greater than 10% in human cells; (8)) is a common and recommended approach to QC (4). However, analysis of healthy tissue shows that the proportion of

mitochondrial reads shows strong variation across both species and tissue type (8), suggesting that this fixed-threshold strategy may exclude healthy cells and fail to exclude relatively stressed cells. Users may prefer more sensitive approaches that do not give hard assessments of cell quality, but give them the power to decide which are the unwanted cells.

The current industry standards for QC are `scater` (9) and `Seurat` (10), both of which are data-driven rather than based on a fixed threshold. In addition, a probabilistic method `miQC` was recently introduced (11). All three of these are unimodal (`scater` and `Seurat` are also univariate in typical use). `scater` and `Seurat` function by calculating robust measures of centre and scale (such as median and median absolute deviation, or MAD) for each QC metric, then discarding cells that are a specified number of deviations away from the centres. They are typically applied individually to each sample, which we find may introduce bias. Most importantly, where samples are composed of multiple celltypes whose QC metric distributions differ (e.g. they have lower counts, or higher mitochondrial proportions), such filtering will preferentially exclude cells from the celltypes with more extreme values, leading to a bias towards excluding cells from particular celltypes. This was noted by Germain *et al.*, who found that stringent filtering on all cells simultaneously led to exclusion of cells that have extreme QC metrics, but not poor quality cells (12). `miQC` is multivariate, assuming that the relationship between features detected and mitochondrial proportion is different in healthy cells and in 'compromised' cells. This approach is also unimodal, and may therefore also suffer from a bias against extreme celltypes. Germain *et al.* also found that filtering was necessary, as lenient filtering led to poorer downstream performance (as measured by clustering). Taken together, these findings motivate the need for a QC filtering tool that allows for the presence of multiple celltypes.

As the size of scRNAseq experiments increases, so does their complexity, resulting in ever-higher numbers of conditions and samples measured per experiment (13). This increases the challenge of doing sensitive QC, e.g. by manually deciding a threshold for each sample. In addition, it is important to measure experimental quality at a *sample* and not just a cell level. An experimenter may wish to make comparisons between samples deriving from multiple experimental conditions; this requires establishing that there are sufficient high quality samples of each desired condition.

To address these problems, we have developed `SampleQC`, a computational method designed for QC of large scRNAseq experiments with complex designs. `SampleQC` is implemented as an `R` package based on a robust multivariate Gaussian mixture model (GMM). By fitting a mixture model in which each of the mixture components corresponds to one 'QC celltype', `SampleQC` identifies the QC distributions for multiple celltypes simultaneously, removing the bias towards excluding healthy celltypes with extreme QC metric values. We use a fitting procedure that is statistically robust, in the sense that it expects outliers to be present and inference is not distorted by them. By allowing each sample to have its own 'sample shift' term, `SampleQC` fits simultaneously across multiple samples, which both increases statistical power and automates an otherwise tedious process. This addresses not only problems with sensitivity of outlier detection, but also provides sample-level QC outputs. Finally, `SampleQC` provides a comprehensive, automatically-generated report on cell and sample quality.

Results

SampleQC overview

Examining the distributions of QC metrics across many single-cell experiments, we observed that the values for a given sample would typically follow a multivariate Gaussian mixture distribution, i.e. groups of cells concentrated around distinct mean values, with distances from these mean values following approximately ellipsoid densities (Figure S1). We also observed that multiple samples often showed approximately the same

distribution, subject to a sample-level shift in values, i.e. the individual values might be on average higher or lower than other samples, but the shapes of the ellipsoids and the relative distances between their means remained approximately the same (Figure S1). This motivated the following model to describe the metrics: for a cell i from sample j, which is a member of QC celltype k (k is not known), $X_i \sim N(\alpha_0 + \alpha_j + \beta_k, \Sigma_k)$, where X_i is the vector of QC metrics, α_0 is the global mean, α_j is the mean shift of sample j relative to the global mean, and (β_k, Σ_k) describe mean and variance-covariance of mixture component k. Finally, we observed that across large experiments, not all samples would follow the same mixture distribution, but that the samples could be grouped into 'sample groups' with similar distributions of QC metrics.

For the metrics to follow a Gaussian mixture model, it is important that the marginal distributions of unimodal data are approximately Gaussian. This is dependent on appropriate transformations of the data, that allow non-Gaussian metrics to be transformed into spaces where they are approximately Gaussian. Applying `log` transformations to library sizes and genes detected is common practice; in addition, we have found that applying the `logit` (inverse logistic) transform to mitochondrial proportions often results in approximately Gaussian distributions (Figure S2). These observations suggest that, after appropriate transformations, a Gaussian mixture model may be a reasonable description of the data.

Figure 1: **SampleQC methodology. A** Cartoon of cells and samples with varying quality, and their corresponding QC metrics. **B** SampleQC estimates distributional distances between samples, and uses this to identify groups of samples. **C** SampleQC fits a robust GMM to each group of samples. **D** Low likelihood is used to exclude poor quality cells. **E** SampleQC generates report of outliers and overall sample quality.

We assumed that the components of the mixture model represent 'QC celltypes', where cells at the centres of the distributions are good quality, and cells that are unusually distant from these centres are cells with

extreme QC metric values that should be discarded. In addition, we sought to identify entire samples that were very different from most samples, to flag these to the user for possible exclusion. This motivated an outlier detection algorithm based on the following two steps: (1) identifying groups of samples whose multivariate QC values approximately follow the same distributions; and (2) within each of these, fitting a multivariate GMM to identify cell-level outliers. These steps are outlined in Figure 1.

To identify groups of samples with similar distributions, `SampleQC` uses a non-parametric statistical measure of dissimilarity between multivariate samples, maximum mean discrepancy (MMD: (14)), to estimate 'distances' between samples. MMD takes two samples as input, which must have the same dimensions but may have different numbers of observations, and calculates a measure of distance/dissimilarity that summarizes differences in means, (co)variances and higher moments. We then use pairwise distances to construct a nearest neighbour graph that allows the identification of 'sample groups', i.e. groups of samples following approximately the same QC metric distributions. We use Louvain clustering to identify the groups (15). The distances are also used as input to dimensionality reduction techniques, such as multidimensional scaling (MDS: (16)) and UMAP (17). This gives low-dimensional embeddings where each point corresponds to a sample, and permit users to check for batch effects or other issues with the data. For example, users can check the extent to which samples from the same batch are clustered together, potentially indicating sample quality problems with a batch.

The second step identifies cell outliers, i.e. cells with very different QC metric values to most other cells. Additionally, this step checks for outlier samples by estimating the mean shift in QC statistics for each sample. After `SampleQC` has identified sample groups, the user then determines how many components are present in each sample group by inspecting the QC distributions within each group, i.e. how many components the GMM should have. `SampleQC` then fits a robust GMM to the cells in each sample group.

Our GMM makes two main assumptions: (1) the configuration of QC celltypes (i.e. their covariance matrices and relative means) is constant across the samples in a sample group; and (2) each sample has a uniform shift in (transformed) QC metrics. Our justification for these assumptions is the observations on distributions of QC metrics discussed above, and the empirical performance of the method, although reasonable biological arguments can also be made for them. The model allows the proportions of QC celltypes (i.e. mixture components) to vary by sample; details of the mathematical model are discussed in Methods (see `SampleQC` model). This model structure, in which the same QC celltypes are assumed to be present in every sample, has benefits when identifying outlier cells. The model learns the parameters for the QC celltype components across the *whole* sample group, so that even when a sample has only a small proportion of a given QC celltype, these cells are not regarded as outliers. These cells may in fact be of particular interest, being from a celltype with reduced proportion relative to other samples.

We fit this model to identify poor quality cells, namely those that are outliers with respect to the distribution of the bulk of cells. While the presence of outliers is known to affect the estimation of statistics, especially higher order moments such as covariance (18), accurate estimation of the covariance matrices is essential precisely for identifying those outliers. We therefore use a *robust* estimation of the mean and covariance matrices (19): robust estimators (like the MAD) give good but slightly less than optimal results when the data do follow an assumed distribution, but are also guaranteed to give good results when the data is contaminated and MLEs may fail (18). We explicitly assume that outliers may be present, making this approach necessary.

Once we have fit models to each sample group, `SampleQC` is able to describe all cells in the included samples in terms of mixture components, which we assume to represent good quality cells. We can then identify outlier cells by calculating a statistical measure of distance from the centre of each QC celltype (Mahalanobis distance, which indicates how unlikely a particular observation is under a χ^2 distribution), and exclude cells that are unlikely to be a member of any component.

Simulating QC data for a large experiment

With single cell data, there is no ground truth regarding which cells or samples are poor quality, making assessment of the performance of QC methods challenging. To evaluate `SampleQC` against other approaches, we therefore developed a simulation framework that replicates the distributions of QC metrics observed in biological datasets (pseudocode provided in Methods; see Simulations). The framework and parameters are derived from large and complex experimental designs, including outliers, and are based on a hierarchical model.

At the experiment level, we make the following assumptions: (1) the experiment is composed of a number of sample groups with similar QC distributions; (2) there are a small number of 'QC celltypes' present in the experiment. By 'QC celltype', we mean a cluster of cells that is distinct within 'QC space', i.e. the selected QC metrics. We expect that multiple true celltypes, i.e. clusters that are distinct in terms of expression, may have the same distribution in QC terms. These QC celltypes are assumed to be common across all groups of samples, with a different subset present in each sample group. For each group, we randomly sample samples and cells, and which celltypes are present. We also sample the means and covariances for the QC celltypes, $\{\beta_k, \Sigma_k\}$.

Within each sample group, we then model outliers and sample shifts at the level of samples. We assume that for each sample j, there is a uniform shift in the (transformed) QC metrics, α_j. This affects all cells in a sample equally. We also assume that each sample has different proportions of the QC celltypes, sampled from a Dirichlet distribution. Each sample has a different proportion of outliers, modeled as a beta distribution, which gives all samples from the same group outlier proportions that vary around a common mean value. Outliers are assumed to differ from 'good' cells by having lower non-mitochondrial reads and numbers of features, and correspondingly higher mitochondrial proportions; we model this by a sample-level parameter corresponding to the proportion of non-mitochondrial reads lost (modelled as a logistic normal).

For every cell, we have annotations of sample group (g), sample (j) and QC celltype (k), with corresponding values of global mean (μ_g), sample shift (α_j) and QC celltype mean and covariance (β_k and Σ_k). We draw a healthy QC metric vector for a given cell via a multivariate normal with mean $\mu_g + \alpha_j + \beta_k$, and covariance Σ_k. We then determine whether this cell is an outlier via a Bernoulli distribution, and if it is, we perturb this value by downsampling the non-mitochondrial reads and the QC metrics are updated accordingly.

This approach follows the model assumed by the GMM (`SampleQC` model), with two additional points to make the simulations more challenging. Firstly, the GMM does not include any outliers. To model these, we assume that each sample has a given proportion of outlier cells, selected at random. For each of these cells, the non-mitochondrial reads and the number of features are decreased by a given proportion, according to a beta distribution. This results in both a reduction in total counts and features, and an increase in mitochondrial proportion, consistent with outliers observed in real data. Secondly, we assume that the relative positions of the components, $\{\beta_k\}$, are not identical in each sample, and vary by a small amount, δ_{jk}.

This results in simulated QC metrics for tens of thousands of cells across tens of samples, where the distributions of these metrics vary coherently across different groups of samples. The simulations provide two matrices of QC metrics: one that mimics the QC values we might see from experiments, and one for the QC values of the cells 'before' they became low quality (such a matrix would never be observed in real life).

Benchmarking `SampleQC` against `scater` and `miQC` on simulated data

We generated simulated data for an experiment with 100,000 cells across multiple samples, resulting in 64 samples with a median of 1,300 cells per sample, including outliers. We then ran `SampleQC`, `scater` and `miQC` to compare performance: both in terms of excluding outliers, and retaining 'good' cells. Inspecting the distributions of the outliers identified by the different methods, we observe that where multiple QC celltypes are present, `SampleQC` identifies outliers correctly, while both `scater` and `miQC` may preferentially exclude cells

from one QC celltype as outliers (Figure 2). Where only one QC celltype is present, `SampleQC`, `scater` and `miQC` show similar results (Figure S3), as expected.

Figure 2: **QC method comparisons on multimodal simulated data. A** True simulated outliers (red). **B** Multivariate density plot of simulated data, showing `SampleQC` fits. **C** Mahalanobis distance to nearest cluster under fitted `SampleQC` model. **D**, **E**, **F** Outliers detected by `SampleQC`, `scater` and `miQC` respectively.

When we assess performance in identifying good cells across the entire simulated dataset, we find that `SampleQC` has equal or better performance than both `scater` and `miQC` for both precision and recall (Figure 3A, Figure S4). The relative performance on individual samples is affected by how many celltypes are present in the sample. Where the data is multimodal, the multimodal model in `SampleQC` gives it equal or better performance than `scater` and `miQC` for both precision and recall (Figure S4, Figure S5). Where the data is unimodal (i.e. has one mixture component), `scater` and `SampleQC` show similar performance (Figure 3B). In this case, performance of `miQC` is slightly worse, potentially because it assumes that a reasonable quantity of 'compromised' cells must be present; when there are only few such cells, this may result in 'good' cells reported as outliers.

Importantly, `SampleQC` also shows better performance than the compared methods in terms of celltype bias. As above, when one QC celltype is present in a sample, `SampleQC` and `scater` have very similar biases in excluding good cells at default settings. However, when multiple QC celltypes are present in a sample, `SampleQC` excludes similar numbers of good cells, and shows low bias towards any particular QC celltype. In this setting, the good cells mistakenly excluded by both `miQC` and `scater` are almost entirely comprised of one celltype, while `SampleQC`'s more flexible model better preserves rare QC celltype proportions. We note that these results are dependent on the choices made in developing the simulation, and that alternative reasonable choices may give different results.

Figure 3:   **Performance comparison of `SampleQC` and `scater` on simulated data.** Results from one simulated experiment of 100k cells with 3 QC celltypes. **A** Precision-recall curve of identification of 'good' cells. Solid lines show curve calculated over all cells. Transparent lines show curves for individual samples. Dots show default cutoffs for each method ($< 1\%$ Chi-squared tail for `SampleQC`; > 2.5 MADs for `scater`; > 0.75 posterior probability of compromised cell for `miQC`). **B** Bias in number of cells reported by sample, samples split by whether > 1 QC celltype observed in sample. y-axis is bias in reporting of good cells.

Number of QC clusters

Determining the appropriate number of distinct clusters in a dataset is a well-studied problem in statistics that remains challenging (20). To avoid this problem, `SampleQC` requires users to specify the number of mixture components for each group of samples. We simulated experiments to test the sensitivity of our results to mismatches between the selected and true k. We simulated data with different true numbers of QC celltypes, varying over 1, 2 and 3 QC celltypes (our observation over many studies has been that many samples have

between 1 and 4 mixture components). For each value of `k_true`, we simulated data for 20,000 cells divided into samples, with an average of 2000 cells per sample. We then fit `SampleQC` to each dataset, with the assumed number of clusters `k_fit` varying between 1 and 4. We found that a mismatch between `k_true` and `k_fit` could result in a reduction in performance (while `SampleQC` performed well when `k_fit` was correctly specified) (Figure S7). However, for multiple of the combinations where `k_fit` was misspecified, `SampleQC` was not able to fit; this provides some protection in itself. These results indicate that review of the diagnostic plots rendered by `SampleQC` is an important part of the QC process, allowing users to determine plausible values of k from the empirical distributions.

Figure 4: **Sample-to-sample distance embedding (UMAP). A** Sample group, as derived from `SampleQC` clustering **B** Sequencing batch **C** Mitochondrial proportion (categorized) **D** Number of cells (categorized). **E** Median counts per cell **F** Median log2 splice ratio per cell.

Applying `SampleQC` to complex biological datasets

We applied `SampleQC` to a large single-nuclei RNA-seq dataset comprising 867k cells over 172 samples (see Data availability), taken from human brain tissue, including samples from patients with neurodegenerative conditions. This illustrates an intended use case for `SampleQC`: a dataset with sufficiently many samples to make it challenging to adjust outlier thresholds for each sample individually, and where complex batch effects could be present. Here, we use log library size, logistic transform of mitochondrial proportion; and log2(spliced reads / unspliced reads) as QC metrics. The motivation for using log splice ratio in single nuclei data comes from the difference in abundance of unspliced reads between the nucleus and the cytoplasm (21). In principle, unspliced reads should only be present in the nucleus; high ratios of spliced to unspliced read counts therefore allow us to identify nuclei that were not successfully stripped of their cytoplasm, and are likely to be contaminated. In addition, this demonstrates the flexibility of `SampleQC`, which only assumes that multiple QC celltypes are present, and does not require specific metrics to be used.

Figure 5: **QC method comparisons on complex biological data. A** Multivariate density plot of single nuclei data, showing one selected sample, with `SampleQC` model fits. **B** Mahalanobis distance to nearest cluster under fitted `SampleQC` model. **C**, **D**, **E** Outliers detected by `SampleQC`, `scater` and `miQC` respectively. `SampleQC` outliers include user specification that QC celltypes with mean splice ratio > 3 should be excluded.

`SampleQC` first identifies samples with similar QC distributions, by calculating pairwise MMD distances between the samples. The principle reason for this is to allow `SampleQC` to fit separate models to each group of individual samples. Low dimensional projections of the resulting dissimilarities are shown in Figure 4 (UMAP) and Figure S8 (MDS), showing the groups identified by `SampleQC` (Figure 4A), allowing investigators to assess

whether sample source, sequencing run or other covariates might have influenced sample quality (Figure 4B). Investigators can also check whether there are groups of samples that should be excluded entirely due to poor quality.

Applying `SampleQC` to this dataset shows similar results to those for the simulation: where a cell population is present in the whole dataset but only makes up a small proportion of a sample, `SampleQC` is better able to preserve these cells than `scater` and `miQC` (Figure 5). The Mahalanobis distances calculated under the `SampleQC` model also follow the expected distribution, i.e. most points follow a Chi-squared distribution with degrees of freedom equal to the number of dimensions, plus an outlier component with larger distances (Figure S9).

Although `SampleQC` is a more complex model than other approaches to QC, this does not substantially decrease speed. As an illustration, we timed `SampleQC` on the simulated dataset in Figure 3, comprising 100k cells over 64 samples. The three steps of `SampleQC` took the following times: 44s to calculate pairwise MMDs; 70s to fit the `SampleQC` models; and 104s to render the report.

The methodology underlying `SampleQC` is general, and not specific to scRNAseq. The example above demonstrates its application to single nuclei RNAseq, and in principle it can identify outliers in any dataset comprising a small set of mixture components described by a small set of variables. This includes other single cell technologies, such as CITE-seq, which is similar to scRNAseq but also quantifies protein expression via oligo-tagged antibodies (22), and scATACseq, which quantifies chromatin accessibility in single cells (23). To demonstrate this, we ran `SampleQC` on CITE-seq data from PBMCs (24), using similar QC metrics to scRNAseq: log RNA counts; log RNA features; logistic transform of mitochondrial proportion; log ADT (protein) counts; log ADT features. The models fit by `SampleQC` successfully converged to the modes of the data, and could be used for outlier detection (Figure S10).

Discussion

We introduced `SampleQC`, an approach for quality control of scRNAseq experiments that improves on the current industry standard, and is designed for large and complex experimental designs. We show that our model simultaneously allows flexibility and sensitivity, and reduces bias. Grouping samples by similarity of QC metric distributions allows a different model to be used for each sample group, which then increases sensitivity by borrowing strength across samples.

Our method is based on empirical observations of real data, and is motivated by known biological mechanisms. Many single cell techniques assume that scRNAseq data comprises multiple celltypes that are distinct in terms of gene expression, however this is not reflected in current approaches to QC. Metrics used for quality control are functions of the full expression vector of counts. When multiple celltypes are present in the full expression data, our observations over multiple datasets are that at least some separation into 'QC celltypes' is typically preserved in the restricted 'QC space'. Our motivations regarding outliers, i.e. that they form a small proportion of the dataset with lower read counts and higher mitochondrial proportions, are also consistent with this observation. New measurements of quality, not currently considered, may come into use. `SampleQC` allows users to choose any metric for input, and if the selected metrics approximately follow a GMM, the approach should produce sensible outputs. A GMM is a reasonable model given that single cell data is known to often form clusters, and we have shown that the individual metrics (after appropriate transformations) typically follow Gaussian distributions. Non-Gaussian and non-parametric approaches to outlier detection could also be considered, such as estimating cell densities in QC space and then excluding cells in sparsely populated regions. However, this would risk excluding cells that were only rare in that sample, and our observations suggest that a GMM is reasonable for various experiments.

`SampleQC` improves over simpler approaches to outlier detection in a number of ways. By fitting one model

across multiple samples, `SampleQC` is able to preserve celltypes that are abundant in some samples, but have low abundance in others and are therefore discarded by methods that operate only at the sample level. We have demonstrated `SampleQC` on standard measures of cell quality. However, the model is flexible, and can be applied to any set of metrics specified by the user that approximately follow a Gaussian mixture distribution. We also note transformations that allow non-Gaussian metrics to be transformed into spaces where they are more likely to be Gaussian. For example, `SampleQC` transforms mitochondrial proportions via the `logit` function, and spliced:unspliced ratios via `log`. `SampleQC` is effectively a general outlier detection technique for GMMs, and this should allow `SampleQC` to be applied to datasets with other or multiple modalities. We have applied `SampleQC` to CITEseq (Figure S10), but in principle it should also apply to data from scATACseq (23), scCATseq (25), single cell techniques based on combined modalities, and spatial transcriptomics.

It is worth noting that our performance results depend on the choices made in implementing the simulation, largely because we are not aware of other frameworks to simulate scRNA-seq QC summaries. While we tried to represent parameters and phenomena observed based on our experience in large scRNA-seq datasets, further development of the simulation framework would be desirable. We note that as the underlying models for both `scater` and `miQC` are unimodal, any circumstance where there are multiple distinct healthy cell populations may result in a performance advantage for `SampleQC`.

We do not provide any statistical guarantees that `SampleQC` converges to the optimal solution. However, `SampleQC` does provide automatically generated and comprehensive reports that show the fitted model over the empirical density. The models defined are conceptually simple, and the reports should therefore allow users to check both the validity of the fits and the appropriate number of clusters for each group.

We also do not attempt to solve the problem of selecting the appropriate value of k; this is a challenging and extensively-discussed problem in statistics (20). As noted above, the automatic reports allow users to inspect whether the model has fit appropriately. In addition, using robust estimators makes the procedure less sensitive to misspecification of the number of components: robust methods expect some of the data to be outliers, and therefore do not attempt to 'explain' all data; non-robust methods attempt to explain the whole dataset, and where the number of components is misspecified, the estimated means may lie between components.

As experiments increase in size and complexity, the task of removing unwanted cells becomes correspondingly more challenging, especially if users would like to preserve rarer populations. `SampleQC` attempts to solve this problem, by first identifying groups of samples with similar QC distributions, then fitting an empirically motivated statistical model to the QC metric data for each group. The model is simple, meaning that it is fast to fit and easy to check. This allows users to obtain an overview of data quality for their entire experiment, and to accurately identify cells for exclusion without having to make decisions regarding every sample individually. Our intention is to provide a fast, flexible and easy-to-use method that allows investigators to do quality control with minimal loss of their valuable data.

Methods

`SampleQC` model

`SampleQC` is based on standard approaches to identifying GMMs, with two important changes. Firstly, the model includes terms that are sample-specific: each sample has a sample shift term, i.e. a uniform change in values applying to all cells in a given sample. In addition, while we assume that each sample has the same mixture components (= QC celltypes), the *proportion* of these components may vary within each sample. For cell i, which comes from sample j in QC celltype k, this gives us the following model for the QC values X_i:

$$X_i \sim N(\alpha_0 + \alpha_j + \beta_k, \Sigma_k) \quad \text{and} \tag{1}$$

$$P(Z_i = k | s_i = j) = p_{jk} \tag{2}$$

where

$$s_i = j, \quad \text{cell } i \text{ is from sample } j$$
$$Z_i = k, \quad \text{cell } i \text{ is in mixture component } k$$
$$\alpha_j \quad \text{sample shift for sample } j$$
$$\beta_j \quad \text{mean for mixture component } k$$
$$\Sigma_j \quad \text{covariance matrix for mixture component } k$$
$$p_{jk} \quad \text{mixing proportions in sample } j$$

Secondly, the fit is robust, in the sense that it is less sensitive to outliers. The standard approach to fitting GMMs is via expectation-maximization, where the method alternates between fixing the means and covariance matrices then identifying the expected values for the latent cluster variables ('expectation'), and fixing the latent cluster variables then calculating the maximum likelihood estimators (MLEs) for the means and covariances ('maximization'). This approach assumes that all observations come from the GMM distribution. If the data is contaminated by a small proportion of observations that do not come from the assumed distribution (outliers), then this procedure may fail, especially regarding estimation of covariance matrices, in turn affecting cluster membership identification (18). To mitigate this problem, we use a robust method to estimate the means and covariance matrices, based on using the points nearest the centre of the component (19). Robust estimators are designed to return good results even in the presence of outliers, which is especially important when the principle assumption of our task is that outliers may be present.

In addition to identifying outlier cells, fitting the GMM gives in estimated statistics as outputs, namely: the QC metric shift for each sample ($\hat{\alpha}_j$), the location and shape of each mixture component (($\hat{\beta}_k, \hat{\Sigma}_k$)), and the proportions of the components in each sample (p_{jk}). These can be used to identify samples with markedly different statistics to others in their sample group, both in terms of mean QC values, and in terms of the split of cells across QC celltypes. These samples are therefore flagged to experimenters for detailed checking and potential exclusion.

Software

The input to `SampleQC` is a `data.frame` where each row corresponds to a cell; the columns must contain the chosen QC metrics and sample labels, and can optionally also include additional sample annotations such as batch or experimental condition.

Prior to running `SampleQC`, we recommend excluding empty droplets, for example by running `emptyDrops` with either the default or a more generous cutoff, to ensure that all genuine cells are included. This may result in some empty droplets being used as input to `SampleQC`, but they should be identified as outlier cells and later excluded.

We then recommend removing multiplets *before* running `SampleQC` for two principal reasons. Firstly, excluding low quality cells first assumes that all doublets are composed of two good quality cells; by excluding low quality cells first, it is then more difficult to detect doublets comprising one good quality and one low quality cell. Secondly, just as the count vectors for doublets are linear combinations of two true cells, their QC metric values are also functions of combinations of two true cells. The practical impact of this is that doublets introduce a small amount of noise to the QC metric distributions; excluding them results in cleaner

distributions that are slightly easier for `SampleQC` to fit. (In addition, the number of cells used in the run is needed to accurately estimate the expected number of doublets. Excluding low quality cells first would distort this calculation; although this can be addressed by recording the initial number of cells.)

To run `SampleQC`, the user first runs the function `calculate_pairwise_mmds`, which estimates MMD values for each pair of samples, identifies groups of samples with similar QC metric distributions, and calculates embeddings in lower-dimensional spaces (both MDS and UMAP). The user can then plot the samples and check for evidence of batch effects, e.g. if all samples from a given well, run or experimental condition are grouped together. Users can also check whether any sample group has consistently low quality cells (e.g. high mitochondrial proportions) and consider excluding all samples in that group.

To run the cell outlier section of `SampleQC`, the user then selects `qc_names`, the QC metrics to use, and k, a vector corresponding to the number of mixture components for each sample group, and calls the function `fit_sampleqc`. `SampleQC` then fits a GMM to each sample group, and uses cell likelihoods to identify outlier cells. Users would typically start by using $k = 1$ for all sample groups; as the simplest model, this is extremely fast. The report includes biaxial plots of the QC metrics for all samples, which allow users to judge what value of k is most appropriate for each sample group, then rerun `SampleQC`. Users can inspect the cells identified as outliers by generating an html report with the function `make_sampleqc_report`. The user can also specify `alpha`, the χ^2 distribution threshold determining the how stringent outlier exclusion should be, however this is less critical and the default value (`alpha` = 0.01) is generally appropriate. `alpha` specifies the distance away from the centre of the nearest GMM component that should be considered as an outlier. Under a robust model, the distribution is assumed to be a GMM plus a contamination component that does not follow the GMM, and is therefore by definition very unlikely under the GMM distribution, so as long as `alpha` is set reasonably low (e.g. 1%, 0.1%), this will only have marginal effects on results.

If a large proportion of a sample is of poor quality, `SampleQC` may identify these cells as one sample cluster, and one of the mixture model components may therefore be centred on them (e.g. the cells with high splice ratio in Figure 5). Without intervention, these would be reported as good cells rather than outliers. `SampleQC` therefore includes functionality allowing users to specify that any component whose mean meets a certain criteria should be regarded as outliers. For example, a component whose mean mitochondrial percentage is greater than a given percentage can be labelled as outliers.

Simulations

We developed a framework for simulating samples of QC data that reflects the complexity observed in real datasets, following the model given in Equation 1, but additionally modelling outliers; in the `SampleQC` R package, users can access this functionality from the `simulate_qcs` function. For the simulations, we assume that there are three QC metrics: log library sizes, log feature counts and `logit` mitochondrial proportion. The simulations are hierarchical: firstly, parameters for group size and GMM components are drawn at the whole-experiment level; then, we draw parameters for sample quality at the sample group level, capturing variability that is coherent across groups of samples; then we draw parameters for each individual sample and QC metrics for each individual cell. To model the QC metrics, we assume that most cells are healthy, i.e. they derive from the experiment-level GMM, while a small number are 'bad', i.e. their values are perturbed away from the means of the GMM. These steps are set out in Algorithm 1.

At the experiment level, we simulate the covariance matrices and relative means of the mixture components (QC celltypes) that are present in the experiment (Algorithm 2). We then simulate parameters reflecting coherent behaviour across different groups of samples. First, we partition the cells between the groups according to a multinomial distribution, simulate how many samples are present in each group, and randomly assign QC celltypes to each group. We assign the QC celltypes such that each group has at least one QC celltype present,

and that no two groups have identical sets of QC celltypes. To simulate coherent differences in outliers between each group, we simulate parameters from a beta distribution that determines how the proportion of outliers varies across samples (`p_out_0`, `theta_0`), and how perturbed these outliers will be relative to healthy cells (`p_loss_0`, the mean proportion of non-mitochondrial reads that is lost).

We then simulate samples and cells within each sample group (Algorithm 4). Within each sample, we first simulate the sample shift from a multivariate Gaussian, and simulate the proportions of the different QC celltypes via a Dirichlet distribution (`p_jk`). We also simulate what proportion of cells in this sample are outliers, `p_out_j`, from a beta distribution with parameters (`p_loss_0`, `theta_0`), and the extent of perturbation in unhealthy cells, `p_loss_j`, from a logit-normal distribution.

We can then simulate each healthy cell, by first drawing its QC celltype from a multinomial with $\mathbf{p} = \{$`p_jk`$\}$, then drawing from multivariate normal (`beta_k`, `Sigma_k`) for the appropriate k. Adding this to the relevant `mu_0` gives us the QC metrics for a healthy cell. We then decide whether this cell is healthy or not by drawing from a binomial distribution (with probability `p_out_j`. If the cell is healthy, its QC metrics are left unchanged. If not, its non-mitochondrial reads are randomly decreased by a proportion `p_loss_j`. This results in both a reduction in total counts, and an increase in mitochondrial proportion. We apply the same random reduction to the number of features.

The outputs from the simulations show similar distributions of QC metrics to real data (Figure 5).

Algorithm 1: `simulate_qcs`: Overview of simulations (* indicates variables that would be known and used as input for real data)

Input: `n_groups`, number of sample groups

Input: `n_cells`, number of cells in experiment

Input: `n_p_sample`, average number of cells per sample

Input: `D`, number of QC dimensions

Input: `K`, number of QC celltypes

Output: `cell_ids*`, labels for each cell

Output: `sample_ids*`, sample ID for each cell

Output: `qc_out*`, matrix of QC metrics including outliers for simulated experiment

Output: `qc_ok`, matrix of healthy QC metrics for simulated experiment

Output: `groups`, sample group for each sample

Output: `z`, QC celltype for each cell

Output: `outliers`, whether each cell is an outlier

draw experiment-level hyper-parameters:

  `beta_k, Sigma_k = draw_expt_level(D, K);`

draw sample group-level hyper-parameters:

  `Ns, Js, mu_0s, sel_ks, p_out_0s, theta_0s, p_loss_0s =`

    `draw_group_level(n_groups, n_cells, n_p_sample, D, K);`

simulate cells for each sample group:

for $g \leftarrow 1$ **to** *n_groups* **do**

    `qc_oks[g], qc_outs[g], zs[g], outliers[g] = draw_sample_level(Ns[g], Js[g], mu_0s[g], sel_ks[g], p_out_0s[g],`

      `theta_0s[g], p_loss_0s[g]);`

end

concatenate `qc_oks[g]`, `qc_outs[g]`, `zs[g]`, `outliers[g]` to `qc_ok`, `qc_out`, `z`, `outliers`;

Algorithm 2: `draw_expt_level`: Pseudocode for drawing experiment-level parameters

---

Input: `D`, number of QC dimensions

Input: `K`, number of QC celltypes

Output: `beta_k`, means of GMM components

Output: `Sigma_k`, covariance matrices of GMM components

for $k \leftarrow 1$ **to** K **do**

    draw β_k from multivariate distribution with mean 0, correlation matrix with off-diagonal elements $[0.999, -0.4, -0.4]$, and standard deviations $[0.3, 0.2, 0.1]$;

    draw Σ_k from a Wishart distribution with 10 degrees of freedom, and Sigma defined by a correlation matrix with off-diagonal elements $[0.99, -0.4, -0.4]$ multiplied by a vector of standard deviations $[0.15, 0.13, 0.54]$ (these values are derived from the MS dataset);

end

Algorithm 3: `draw_group_level`: Pseudocode for drawing sample group-level parameters

---

Input: `n_groups`, number of sample groups

Input: `n_cells`, number of cells in experiment

Input: `n_p_sample`, average number of cells per sample

Input: `D`, number of QC dimensions

Input: `K`, number of QC celltypes

Output: `Ns`, number of cells in each sample group

Output: `Js`, number of samples in each sample group

Output: `mu_0s`, global mean of each sample group

Output: `sel_ks`, which mixture components are present in each group

Output: `p_out_0s`, mean outlier proportion in each group

Output: `theta_0s`, size parameter for beta distribution of sample outlier proportions

Output: `p_loss_0s`, mean proportion of non-mitochondrial reads lost in each outlier group

draw number of cells per sample group, `Ns`, with Dirichlet-multinomial ($\alpha = 10$, $n = $ `n_cells`);

while *any rows of* `sel_ks` *identical OR any row of* `sel_ks` *all 0s* **do**

    for $g \leftarrow 1$ ***to*** `n_groups` **do**

        draw `sel_ks[g]` with binomial distribution ($n = K, p = 0.5$);

    end

end

for $g \leftarrow 1$ ***to*** `n_groups` **do**

    draw `Js[g]` from $\text{Pois}($`Ns[g]`$/$`cells_p_sample`$) + 1$;

    draw `mu_0s[g]` from multivariate normal with mean $[$`log10`$(3000),$ `log10`$(1500),$ `logit`$(0.03)]$, correlation matrix with off-diagonal elements $[0.98, -0.7, -0.8]$ and standard deviations $[0.3, 0.4, 1.5]$;

    draw `p_out_0[g]` from logistic normal with mean `logit`(0.08) and standard deviation 0.3 (on logistic scale);

    draw `theta_0[g]` from log-normal with mean 4 and standard deviation 0.5 (on log scale);

    draw `p_loss_0[g]` from logistic normal, with sample group mean `logit`(0.5) and standard deviation 0.5 (on logistic scale);

end

Algorithm 4: `draw_cell_level`: Pseudocode for drawing cell-level parameters

Input: `N_g`, number of cells in group

Input: `J_g`, number of samples in group

Input: `mu0_g`, global mean in group

Input: `sel_ks_g`, QC celltypes observed in group

Input: `beta_k, Sigma_k`, distributions of GMM components

Input: `p_out_0_g`, mean outlier proportion

Input: `theta_0_g`, size parameter of beta distribution for sample outlier proportions

Input: `p_loss_0_g`, mean proportion of non-mitochondrial reads lost in group

Output: `qc_ok`, matrix of unperturbed QC metrics for sample group

Output: `qc_out`, matrix of observed QC metrics for sample group

Output: `z`, QC celltype for each cell in group

Output: `outliers`, outlier status for each cell in group

assign `N_g` cells to `J_g` groups via multinomial distribution;

for $j \leftarrow 1$ **to** `J_g` **do**

    draw sample shift `alpha_j` from multivariate normal (mean 0, correlation matrix off-diagonal elements

      $[0.9, -0.4, -0.6]$, standard deviations $[0.25, 0.25, 0.6]$);

    draw probability of each QC celltype p_{jk} from Dirichlet ($\alpha = 5, K = $ `n_types`);

    draw outlier probability of each sample, `p_out_j` from Beta distribution

      $(a = theta_{0_}g * $ `p_out_0_g`$, b = theta_{0_}g * (1 - $ `p_out_0_g`$))$;

    draw proportion of reads lost in each sample, `p_loss_j` from logistic normal distribution (mean `p_loss_0_g`, sd 0.5);

    for $n \leftarrow 1$ **to** `N_g` **do**

        draw celltype, `z[n]`, from categorical ($\mathbf{p} = \{p_{jk}\}$);

        simulate healthy QC metrics, `qc_ok` multivariate normal with mean and covariance

          (`mu0_g` $+$ `alpha_j` $+$ `beta_k[z]`, `Sigma_k[z]`);

        draw outlier status: `outliers[n]` $=$ Bernoulli(`p_out_j`);

        if *outlier[n] is TRUE* **then**

            `qc_out[n]` $=$ downsample non-mitochondrial reads, Binomial($p = $ `p_loss_j`);

            downsample number of features, Binomial($p = $ `p_loss_j`);

            update mitochondrial proportion;

        else

            `qc_out[n]` $=$ `qc_ok[n]`

        end

    end

end

Datasets

The datasets listed in Table were used in this paper, obtained via the `scRNAseq` package (26).

Competing interests

The authors declare that they have no competing interests.

Author's contributions

We use the CRediT taxonomy to define author contributions:

- WM: Conceptualization, Methodology, Software, Formal analysis, Investigation, Visualization, Data curation, Writing - Original Draft, Writing - Review & Editing

- MDR: Supervision, Methodology, Writing - Review & Editing, Funding acquisition

Acknowledgements

We thank Helena Crowell, Pierre-Luc Germain and Simone Tiberi for their valuable feedback on the manuscript and software. We thank Dheeraj Malhotra and Roche for the large experimental dataset (see Data availability below).

Funding

This work was supported by the Swiss National Science Foundation (grant numbers 310030_175841, CR-SII5_177208). MDR acknowledges support from the University Research Priority Program Evolution in Action at the University of Zurich. The funder played no role in the design of this study or in its execution.

Data availability

The data in Figures Figure 4 and Figure 5 is QC data taken from human brain tissue, including samples from patients with neurodegenerative conditions. The data derives from a not-yet published study, and the experimental labels have therefore been anonymized. Although we have made the anonymized QC metric data available (see DOI: 10.5281/zenodo.5258847), the full expression data is not yet public. as part of a research collaboration agreement with the University of Zürich.

Code availability

The `SampleQC` software package is accessible at `https://github.com/wmacnair/SampleQC`; a code snapshot of the software package at time of submission is available here: DOI: 10.5281/zenodo.5258609). A repo for reproducing the analyses in the paper is accessible at `https://github.com/wmacnair/SampleQC_paper_analyses` and the corresponding HTML reports are available from `https://htmlpreview.github.io/?https://github.com/wmacnair/SampleQC_paper_analyses/blob/main/docs/index.html`; a code snapshot of the analysis repository at time of submission is available here: (see DOI: 10.5281/zenodo.5258847)

References

[1] Tang, F., Barbacioru, C., Wang, Y., Nordman, E., Lee, C., Xu, N., Wang, X., Bodeau, J., Tuch, B.B., Siddiqui, A., Lao, K., Surani, M.A.: mRNA-Seq whole-transcriptome analysis of a single cell. Nat. Methods **6**(5), 377–382 (2009)

[2] Macosko, E.Z., Basu, A., Satija, R., Nemesh, J., Shekhar, K., Goldman, M., Tirosh, I., Bialas, A.R., Kamitaki, N., Martersteck, E.M., Trombetta, J.J., Weitz, D.A., Sanes, J.R., Shalek, A.K., Regev, A., Mc-Carroll, S.A.: Highly parallel genome-wide expression profiling of individual cells using nanoliter droplets. Cell **161**(5), 1202–1214 (2015)

[3] Klein, A.M., Mazutis, L., Akartuna, I., Tallapragada, N., Veres, A., Li, V., Peshkin, L., Weitz, D.A., Kirschner, M.W.: Droplet barcoding for Single-Cell transcriptomics applied to embryonic stem cells. Cell **161**(5), 1187–1201 (2015)

[4] Luecken, M.D., Theis, F.J.: Current best practices in single-cell RNA-seq analysis: a tutorial. Mol. Syst. Biol. **15**(6) (2019)

[5] Crowell, H.L., Soneson, C., Germain, P.-L., Calini, D., Collin, L., Raposo, C., Malhotra, D., Robinson, M.D.: On the discovery of population-specific state transitions from multi-sample multi-condition single-cell RNA sequencing data (2019)

[6] Squair, J.W., Gautier, M., Kathe, C., Anderson, M.A., James, N.D., Hutson, T.H., Hudelle, R., Qaiser, T., Matson, K.J.E., Barraud, Q., Levine, A.J., La Manno, G., Skinnider, M.A., Courtine, G.: Confronting false discoveries in single-cell differential expression (2021)

[7] Márquez-Jurado, S., Díaz-Colunga, J., das Neves, R.P., Martinez-Lorente, A., Almazán, F., Guantes, R., Iborra, F.J.: Mitochondrial levels determine variability in cell death by modulating apoptotic gene expression. Nat. Commun. **9**(1), 389 (2018)

[8] Osorio, D., Cai, J.J.: Systematic determination of the mitochondrial proportion in human and mice tissues for single-cell RNA sequencing data quality control (2020)

[9] McCarthy, D.J., Campbell, K.R., Lun, A.T.L., Wills, Q.F.: Scater: pre-processing, quality control, normalization and visualization of single-cell RNA-seq data in R. Bioinformatics **33**(8), 1179–1186 (2017)

[10] Stuart, T., Butler, A., Hoffman, P., Hafemeister, C., Papalexi, E., Mauck, W.M. 3rd, Hao, Y., Stoeckius, M., Smibert, P., Satija, R.: Comprehensive integration of Single-Cell data. Cell **177**(7), 1888–190221 (2019)

[11] Hippen, A.A., Falco, M.M., Weber, L.M., Erkan, E.P., Zhang, K., Doherty, J.A., Vähärautio, A., Greene, C.S., Hicks, S.C.: miQC: An adaptive probabilistic framework for quality control of single-cell RNA-sequencing data (2021)

[12] Germain, P.-L., Sonrel, A., Robinson, M.D.: pipecomp, a general framework for the evaluation of computational pipelines, reveals performant single cell RNA-seq preprocessing tools. Genome Biol. **21**(1), 227 (2020)

[13] Svensson, V., da Veiga Beltrame, E.: A curated database reveals trends in single cell transcriptomics (2019)

[14] Gretton, A., Borgwardt, K.M., Rasch, M.J., Schölkopf, B., Smola, A.: A kernel Two-Sample test. J. Mach. Learn. Res. **13**(Mar), 723–773 (2012)

[15] Blondel, V.D., Guillaume, J.L.: Fast unfolding of communities in large networks. Journal of Statistical Mechanics: Theory and Experiment, 1–12 (2008)

[16] Torgerson, W.S.: Multidimensional scaling: I. theory and method. Psychometrika **17**(4), 401–419 (1952)

[17] McInnes, L., Healy, J.: UMAP: Uniform manifold approximation and projection for dimension reduction (2018). 1802.03426

[18] Huber, P.J.: Robust Statistics. John Wiley & Sons, ??? (2004)

[19] Rousseeuw, P.J., Van Driessen, K.: A fast algorithm for the minimum covariance determinant estimator. Technometrics **41**(3), 212–223 (1999)

[20] McLachlan, G.J., Lee, S.X., Rathnayake, S.I.: Finite mixture models. Annual review of statistics and its application (2019)

[21] Alvarez, M., Rahmani, E., Jew, B., Garske, K.M., Miao, Z., Benhammou, J.N., Ye, C.J., Pisegna, J.R., Pietiläinen, K.H., Halperin, E., Pajukanta, P.: Enhancing droplet-based single-nucleus RNA-seq resolution using the semi-supervised machine learning classifier DIEM. Sci. Rep. **10**(1), 11019 (2020)

[22] Stoeckius, M., Hafemeister, C., Stephenson, W., Houck-Loomis, B., Chattopadhyay, P.K., Swerdlow, H., Satija, R., Smibert, P.: Simultaneous epitope and transcriptome measurement in single cells. Nat. Methods **14**(9), 865–868 (2017)

[23] Buenrostro, J.D., Wu, B., Litzenburger, U.M., Ruff, D., Gonzales, M.L., Snyder, M.P., Chang, H.Y., Greenleaf, W.J.: Single-cell chromatin accessibility reveals principles of regulatory variation. Nature **523**(7561), 486–490 (2015)

[24] Kotliarov, Y., Sparks, R., Martins, A.J., Mulè, M.P., Lu, Y., Goswami, M., Kardava, L., Banchereau, R., Pascual, V., Biancotto, A., Chen, J., Schwartzberg, P.L., Bansal, N., Liu, C.C., Cheung, F., Moir, S., Tsang, J.S.: Broad immune activation underlies shared set point signatures for vaccine responsiveness in healthy individuals and disease activity in patients with lupus. Nat. Med. **26**(4), 618–629 (2020)

[25] Liu, L., Liu, C., Quintero, A., Wu, L., Yuan, Y., Wang, M., Cheng, M., Leng, L., Xu, L., Dong, G., Li, R., Liu, Y., Wei, X., Xu, J., Chen, X., Lu, H., Chen, D., Wang, Q., Zhou, Q., Lin, X., Li, G., Liu, S., Wang, Q., Wang, H., Fink, J.L., Gao, Z., Liu, X., Hou, Y., Zhu, S., Yang, H., Ye, Y., Lin, G., Chen, F., Herrmann, C., Eils, R., Shang, Z., Xu, X.: Deconvolution of single-cell multi-omics layers reveals regulatory heterogeneity. Nat. Commun. **10**(1), 470 (2019)

[26] Risso, D., Cole, M.: scRNAseq: Collection of Public Single-Cell RNA-Seq Datasets. (2020). R package version 2.4.0

[27] Campbell, J.N., Macosko, E.Z., Fenselau, H., Pers, T.H., Lyubetskaya, A., Tenen, D., Goldman, M., Verstegen, A.M.J., Resch, J.M., McCarroll, S.A., Rosen, E.D., Lowell, B.B., Tsai, L.T.: A molecular census of arcuate hypothalamus and median eminence cell types. Nat. Neurosci. **20**(3), 484–496 (2017)

[28] Weber, L.M., Hippen, A.A., Hickey, P.F., Berrett, K.C., Gertz, J., Doherty, J.A., Greene, C.S., Hicks, S.C.: Genetic demultiplexing of pooled single-cell RNA-sequencing samples in cancer facilitates effective experimental design (2021)

[29] Shekhar, K., Lapan, S.W., Whitney, I.E., Tran, N.M., Macosko, E.Z., Kowalczyk, M., Adiconis, X., Levin, J.Z., Nemesh, J., Goldman, M., McCarroll, S.A., Cepko, C.L., Regev, A., Sanes, J.R.: Comprehensive classification of retinal bipolar neurons by Single-Cell transcriptomics. Cell **166**(5), 1308–132330 (2016)

[30] Wang, W., Vilella, F., Alama, P., Moreno, I., Mignardi, M., Isakova, A., Pan, W., Simon, C., Quake, S.R.: Single-cell transcriptomic atlas of the human endometrium during the menstrual cycle. Nat. Med. **26**(10), 1644–1653 (2020)

[31] Zeisel, A., Muñoz-Manchado, A.B., Codeluppi, S., Lönnerberg, P., La Manno, G., Juréus, A., Marques, S., Munguba, H., He, L., Betsholtz, C., Rolny, C., Castelo-Branco, G., Hjerling-Leffler, J., Linnarsson, S.: Cell types in the mouse cortex and hippocampus revealed by single-cell RNA-seq. Science **347**(6226), 1138–1142 (2015)

Tables

Table 1: List of datasets used in paper. All datasets are single cell RNA-seq unless otherwise stated.

Short name	Tissue	Reference
Campbell	Mouse brain	(27)
CITEseq	Human PBMC (CITE-seq)	(24)
HGSOC	Human ovarian cancer	(28)
Macosko	Mouse retina	(2)
Roche	Human brain (single nuclei RNA-seq)	(29)
Shekhar	Mouse retina	(29)
Wang	Human endometrium	(30)
Zeisel	Mouse brain	(31)

Supplementary Figures

Figure S1: **Biaxial plots of QC metrics from selected samples and datasets.** *log_counts* indicates `log10` of library sizes, *log_feats* indicates `log10` of number of detected genes, *logit_mito* indicates `qlogis` i.e. inverse logistic function of mitochondrial proportion. For list of datasets, see Table .

Figure S2: **QQ plots of QC metrics from selected samples and datasets.** *counts_k* indicates library sizes in thousands, *feats_k* indicates number of detected genes in thousands, *mito_pct* indicates percent of mitochondrial reads, *log_counts* indicates `log10` of total reads per cell, *log_feats* indicates `log10` of number of detected genes, *logit_mito* indicates `qlogis` i.e. inverse logistic function of mitochondrial proportion, *log_mito_prop* indicates `log10` of proportion of mitochondrial reads. z-score calculated using median of QC metric as mean, MAD of QC metric as standard deviation; line shows expected z-scores under a Gaussian distribution with these parameters. For list of datasets, see Table .

Figure S3: **QC method comparisons on unimodal simulated data. A** True simulated outliers (red). **B** Multivariate density plot of simulated data, showing `SampleQC` fits. **C** Mahalanobis distance to nearest cluster under fitted `SampleQC` model. **D**, **E**, **F** Outliers detected by `SampleQC`, `scater` and `miQC` respectively.

Figure S4: **PR curves for individual samples.** PR curves for 20 randomly selected samples from simulated experiment. Precision is proportion of cells reported as 'good' that are actually 'good'; recall is proportion of all 'good' cells that are reported as 'good'. Samples in first row are unimodal, i.e. they are composed of one celltype; other samples have either 2 or 3 celltypes.

Figure S5: **Precision-recall curves split by number of celltypes present.** Modality indicates number of modes present in the distribution, i.e. the number of celltypes.

Figure S6: **Split of misreported good cells by celltype.**

Figure S7: **Robustness to choice of k. A** `SampleQC` fits to simulated data, for combinations of `k_fit` and `k_sim`; columns are `k_fit`, rows are `k_sim`. Each fit illustrated by randomly selected sample for each combination. Note that for some combinations of `k_fit` and `k_sim`, `SampleQC` was not able to fit the data; these are blank. **B** Precision-recall curves of identification of 'good' cells. Solid lines show curve where `k_fit` = `k_sim`. Dots show default cutoff ($< 1\%$ Chi-squared tail).

Figure S8: **Sample-to-sample distance embedding (MDS). A** Sample group, as derived from `SampleQC` clustering **B** Sequencing batch **C** Mitochondrial proportion (categorized) **D** Number of cells (categorized). **E** Median counts per cell **F** Median log2 splice ratio per cell.

Figure S9: **Supplementary: Comparison of Mahalanobis distances under `SampleQC` model and distances under expected Chi-squared distribution.** Mahalanobis distances for Roche data and model fit in Figure 5, samples selected at random.

Figure S10:   **Supplementary: `SampleQC` outputs for selected CITE-seq sample.** Biaxial distributions of CITE-seq QC metrics for PBMCs (24), annotated with fitted models fitted by `SampleQC`. Selected sample *H1B2ln2* from batch 2; distributions and fits for other samples are similar.