Riemannian geometry of functional connectivity matrices for multi-site attention-deficit/hyperactivity disorder data harmonization

Guillem Simeon [1], **Gemma Piella** [2], **Oscar Camara** [3] **and Deborah Pareto** [4]

[1] *Computational Science Laboratory, Universitat Pompeu Fabra, Barcelona Biomedical Research Park (PRBB), C/ Doctor Aiguader 88, 08003, Barcelona, Spain*
[2] *SimBioSys group, BCN MedTech, Department of Information and Communication Technologies, Universitat Pompeu Fabra, 08018 Barcelona, Spain*
[3] *PhySense group, BCN MedTech, Department of Information and Communication Technologies, Universitat Pompeu Fabra, 08018 Barcelona, Spain*
[4] *Neuroradiology Section, Department of Radiology (Institut de Diagnòstic per la Imatge), Vall d'Hebron Hospital Universitari, Pg Vall d'Hebron 119-129, 08035, Barcelona, Spain*

Correspondence*:
Guillem Simeon
guillem.simeon@upf.edu

ABSTRACT

The use of multi-site datasets in neuroimaging provides neuroscientists with more statistical power to perform their analyses. However, it has been shown that imaging-site introduces a variability in the data that cannot be attributed to biological sources. In this work, we show that functional connectivity matrices derived from resting-state multi-site data contain a significant imaging-site bias. To this aim, we exploited the fact that functional connectivity matrices belong to the manifold of symmetric positive-definite matrices, making possible to operate on them with Riemannian geometry. We hereby propose a geometry-aware harmonization approach, Rigid Log-Euclidean Translation, that accounts for this site bias. Moreover, we adapted other Riemannian-geometric methods designed for other domain adaptation tasks, and compared them to our proposal. Based on our results, Rigid Log-Euclidean Translation of multi-site functional connectivity matrices seems to be among the studied methods the most suitable one in a clinical setting. This represents an advance with respect to previous functional connectivity data harmonization approaches, which do not respect the geometric constraints imposed by the underlying structure of the manifold. In particular, when applying our proposed method on data from the ADHD-200 dataset, a multi-site dataset built for the study of attention-deficit/hyperactivity disorder, we obtained results that display a remarkable correlation with established pathophysiological findings and, therefore, represent a substantial improvement when compared to the non-harmonization analysis. Thus, we present evidence supporting that harmonization should be extended to other functional neuroimaging datasets, and provide a simple geometric method to address it.

22 **Keywords: Multi-site dataset, Resting-state, Functional connectivity, Harmonization, Riemannian geometry, Attention-**
23 **deficit/hyperactivity disorder**

1 INTRODUCTION

Functional magnetic resonance imaging (fMRI) has become one of the leading methods to conduct research
on human brain mapping. fMRI acquisitions allow the discovery of brain activation patterns, which help to
understand the brain processes behind cognition or task performance. A relevant paradigm of acquisition
is called resting-state fMRI, where the subject's brain is studied without performing any specific task.
Resting-state fMRI made possible to identify intrinsic functional connectivity and resting-state networks in
the brain (van den Heuvel and Pol, 2010; Smitha et al., 2017), that is, distant brain regions that exhibit a
temporal correlation in their blood-oxygen-level-dependent (BOLD) signals, and are thought to activate
in a synchronous way. Moreover, resting-state functional connectomics has provided new insights into
brain organization in disease states, since specific changes in connectivity patterns have been directly
correlated to multiple disorders (Greicius, 2008; Du et al., 2018). These alterations in connectivity are
useful to identify biomarkers or to gain more knowledge on these neurological or psychiatric disorders. A
very informative approach summarizing whole-brain functional connectivity consists on the construction
of functional connectivity matrices. It is based on the parcellation of the brain into some predefined regions
of interest (ROIs) and the comparison of the BOLD time-series associated to these ROIs. Usually, this
comparison is made in terms of a pair-wise Pearson's correlation coefficient between ROI signals (even
though partial correlations can also be used (Kim et al., 2015)). After the construction of functional
connectivity matrices from a collection of subjects, one can identify entry-wise statistically significant
differences between subsamples of these subjects (for example, patients and healthy controls), usually by
performing univariate statistical tests on each entry separately. Therefore, one is able to spot key functional
connections that display differences according to the condition of the subject and, hopefully, playing an
important role in the disease state.

The fact that functional connectivity matrices are constructed using correlation coefficients makes them
belong to a particular subset of matrices called symmetric positive-definite (SPD) matrices, which are
symmetric matrices with all eigenvalues strictly greater than zero. This set of matrices does not form
a vector space. This property implies that some conventional Euclidean operations on SPD matrices,
such as subtraction of two SPD matrices, do not yield another element of the set of SPD matrices. Even
though one can perform Euclidean operations with them, resulting matrices do not take into account the
underlying geometry of the space of SPD matrices. Mathematically, the space of SPD is what is known
as a manifold. Roughly speaking, a manifold is a curved space that locally looks like flat (Euclidean)
space. Although one cannot perform Euclidean operations with elements (points) of the space, there
exists an extremely powerful mathematical formalism, known as Riemannian geometry, that deals with
manifolds and allows computations respecting their underlying geometry. Since functional connectivity
matrices are SPD matrices, it is preferable to perform operations on them that take into account their
underlying geometry, rather than applying standard Euclidean methods (You and Park, 2021). Geometry-
aware approaches allow, for example, substantial increases in classification performance of functional
connectivity matrices and accurate comparison of connectomes (Ng et al., 2014; Dodero et al., 2015;
Varoquaux et al., 2010; Slavakis et al., 2017). Nevertheless, the potential of Riemannian geometric methods
has not been fully recognized yet, though their consideration in functional studies is increasing. One
remarkable contribution for the spread of these methods has been recently made by You and Park (You and
Park, 2021), where they introduced SPDtoolbox, a MATLAB-based toolbox that offers the possibility of

exploiting the geometry of functional connectivity matrices in a straightforward manner. One very relevant contribution put forward in (You and Park, 2021) is the proposal of a geometry-aware permutation testing framework that allows the identification of statistically significant differences in functional connectivity between groups.

Given the need for large cohorts to carry out statistical studies, together with the advent of big data and machine learning, neuroimaging datasets have increased their size usually by collecting data acquired at different sites. It is known that the use of different scanners, acquisition protocols or processing pipelines introduces a variability in the data that cannot be attributed to the biological variability of the subjects. To overcome this issue, the standardization of acquisition and processing protocols plays a key role. Nevertheless, it has been shown that some imaging-site bias remains in the data even when standardizing protocols and pipelines (David et al., 2013). Furthermore, from a machine learning perspective, classification might be more difficult because unwanted variability prevents the algorithm from learning the adequate hypothesis function, and also because the learned biased hypothesis might not have the necessary generalization power to unseen examples, affecting classification performance (Brain and Webb, 2002). One well-known approach to harmonize neuroimaging data is ComBat (Johnson et al., 2006). Essentially, ComBat involves subtracting batch variability by modelling it as a deviation from the estimated influence of known covariates of the model. By taking into account the effect of covariates, one can control for the other sources of variability other than the batch (site) effect. In the field of neuroimaging, the ComBat method was shown to remove imaging-site effects in diffusion tensor imaging acquisitions and cortical thickness studies (Fortin et al., 2017, 2018; Beer et al., 2020). Later, ComBat was adapted to functional acquisitions and their derived functional connectivity matrices (Yu et al., 2018).

Nevertheless, this approach does not take into account the geometry of the space of SPD matrices and, therefore, it cannot be considered to be operating in a geometry-constrained manner. In fact, the proposed adaptation of ComBat to functional connectivity matrices (Yu et al., 2018) only considers that resulting harmonized matrices need to be symmetric. Nevertheless, positive-definiteness is not enforced and, therefore, resulting matrices do not belong in general to the original space of SPD matrices. Positive-definiteness is a geometric constraint and precisely defines the manifold of SPD matrices as a subspace of the space of symmetric matrices. Any method that operates on SPD matrices and respects their symmetry and positive-definiteness can be regarded as a geometry-constrained method. Although site harmonization using Riemannian methods has not been directly addressed, some proposals have been put forward to deal with related procedures. In particular, there have been previous works on the use of manifold-constrained operations to develop domain adaptation procedures specifically for functional data (Ng et al., 2014; Yair et al., 2019). However, in their case, domain adaptation was performed targeting inter-session variability (that is, differences arising from acquiring data from the same subject in different sessions, possibly with intervention in-between).

Our intention in this work is to use the rich formalism of Riemannian geometry to geometrically characterize imaging-site bias and to propose methods to remove it (at least partially) from multi-site functional connectivity matrices. To this aim, we will adapt two previous contributions to domain adaptation of functional data and we will also propose a method from our own, called Rigid Log-Euclidean Translation. These operations will be particularized to ADHD-200 (ADHD-200 Consortium, 2017), a multi-site dataset of resting-state acquisitions from attention-deficit/hyperactivity (ADHD) patients and healthy controls (HC). Furthermore, using the geometry-aware permutation testing algorithm proposed in (You and Park, 2021), implemented in SPDtoolbox, we will analyse the impact of imaging-site bias on the results that can be distilled from functional connectivity matrices, and we will correlate them with

108 established pathophysiological findings in ADHD. In short, we intend to provide a simple but powerful
109 geometrically-grounded framework for multi-site functional connectivity matrices harmonization.

2 MATERIAL AND METHODS

2.1 Functional connectivity matrices from ADHD-200

The ADHD-200 sample (ADHD-200 Consortium, 2017) is the result of a joint international effort that
provides researchers worldwide with openly-shared resting-state and structural acquisitions from 8 different
sites, comprising 362 children and adolescents diagnosed with ADHD and 585 typically developing
controls, along with their phenotypic data (ADHD subtype, ADHD score, IQ, medication status, etc). In
an effort to standardize the analyses carried out with ADHD-200, three different preprocessing pipelines
for resting-state acquisitions were proposed, being also preprocessed data made publicly available (Bellec
et al., 2017). One of this preprocessing strategies, the Athena pipeline, was performed by Craddock
(Craddock, 2011). The relevant derived data for our present work are the extracted ROI time-courses from
resting-state acquisitions. As previously mentioned, the computation of the Pearson's correlation coefficient
between time-courses allows the construction of functional connectivity matrices. Craddock provided
researchers with time-series extracted using different parcellation schemes. In particular, Craddock derived
specific functional parcellations for ADHD-200 data from their resting-state acquisitions, giving rise to a
parcellation into 190 ROIs (CC200).

For our present work, we have used a subset of functional connectivity matrices constructed using the
CC200 parcellation scheme. Specifically, our dataset has consisted of functional connectivity matrices
from 80 ADHD patients and 80 HC. Their acquisitions have been randomly pooled (avoiding any kind of
matching in order to maximize intrinsic variability) from four different sources: 20 ADHD/20 HC from
Kennedy Krieger Institute (KKI) (Johns Hopkins University), 20 ADHD/20 HC from the NeuroIMAGE
sample (NIM), 20 ADHD/20 HC from New York University Child Study Center (NYU), and again 20
ADHD/20 HC from Peking University (PKG). Therefore, we have worked in total with 160 functional
connectivity matrices, with dimensions of 190×190.

2.2 Riemannian geometry of SPD matrices

Symmetric positive definite (SPD) matrices are the set of symmetric matrices with all eigenvalues strictly
greater than zero. This property is equivalent to the requirement that, for a $n \times n$ symmetric matrix Σ to
be positive definite, $x^T \Sigma x > 0$ for all non-zero $x \in \mathbb{R}^n$. The set of SPD matrices forms a manifold, a
topological space that locally looks like Euclidean space. At each point p of some manifold $\mathcal{M}$, one can
construct a tangent space $\mathcal{T}_p\mathcal{M}$, generated by the tangent vectors of curves crossing p, which is a vector
space and approximates the manifold in the neighbourhood of p. In our present case, $\mathcal{M}$ is the manifold of
$n \times n$ SPD matrices, which we will denote by Sym_n^+, where each point is a SPD matrix, and one can show
that at every point $p \in Sym_n^+$, $\mathcal{T}_p Sym_n^+$ is the space of symmetric $n \times n$ matrices, Sym_n.

Riemannian geometry provides a framework that allows one to regard the manifold as a metric space.
Specifically, a Riemannian manifold is a smooth manifold equipped with a symmetric, positive-definite
tensor field called metric tensor. The metric tensor g at every point $p \in \mathcal{M}$ is a map

$$g_p : \mathcal{T}_p\mathcal{M} \times \mathcal{T}_p\mathcal{M} \to \mathbb{R}, \tag{1}$$

144 constructed as a generalization of the canonical dot product in Euclidean space, and that can be used to
145 characterize the geometry of the manifold. Two other important maps in Riemannian geometry are the
146 exponential map $\exp_p$ and the logarithmic map $\log_p$ at some point $p \in \mathcal{M}$,

$$\exp_p : \mathcal{T}_p\mathcal{M} \to \mathcal{M}, \quad \log_p : \mathcal{M} \to \mathcal{T}_p\mathcal{M}. \tag{2}$$

Given a tangent vector $v \in \mathcal{T}_p\mathcal{M}$, $\exp_p(v)$ results in a projection of v onto the neighbourhood of p in the
manifold $\mathcal{M}$ by defining a geodesic (i.e., a shortest length curve on the manifold) in the direction of v. The
logarithmic map performs the inverse operation, mapping points in the manifold to vectors in the tangent
space of p.

Particularizing previous notions to our case, Pennec et al. (Pennec et al., 2006) introduced one of the
most used geometric Riemannian structures on the manifold of SPD matrices, Sym_n^+, the affine-invariant
Riemannian metric (AIRM). They proposed the following metric tensor at some point $\Sigma \in Sym_n^+$ (a SPD
matrix) applied on two tangent vectors $X, Y \in Sym_n$ (two symmetric matrices):

$$g_\Sigma(X, Y) := \mathrm{Tr}(\Sigma^{-1}X\Sigma^{-1}Y), \tag{3}$$

155 where Σ^{-1} is the matrix inverse and $\mathrm{Tr}(\cdot)$ is the usual trace operator. Associated to this metric, the
156 exponential map at Σ acting on a tangent vector $V \in Sym_n$ and the logarithmic map at Σ acting on a point
157 $\Pi \in Sym_n^+$ read

$$\exp_\Sigma(V) = \Sigma^{\frac{1}{2}} \mathrm{Exp}(\Sigma^{-\frac{1}{2}}V\Sigma^{-\frac{1}{2}})\Sigma^{\frac{1}{2}} \in Sym_n^+, \tag{4}$$

$$\log_\Sigma(\Pi) = \Sigma^{\frac{1}{2}} \mathrm{Log}(\Sigma^{-\frac{1}{2}}\Pi\Sigma^{-\frac{1}{2}})\Sigma^{\frac{1}{2}} \in Sym_n, \tag{5}$$

being $\mathrm{Exp}(A)$ and $\mathrm{Log}(A)$ the exponential and logarithm of matrix A, respectively, which can be computed
after eigenvalue decomposition $A = UDU^T$ as $\mathrm{Exp}(A) = U \exp(D) U^T, \mathrm{Log}(A) = U \log(D) U^T$,
where U is the eigenvector matrix and D the diagonal eigenvalue matrix, and $\exp(D)$ $(\log(D))$ denotes
the application of the exponential (logarithmic) function to the eigenvalues. $A^{\frac{1}{2}} = \mathrm{Exp}(\frac{1}{2}\mathrm{Log}(A))$ is the
unique SPD square root of the SPD matrix A. Finally, under the AIRM framework, the geodesic distance
between two SPD matrices Σ and Π is

$$d^2(\Sigma, \Pi) = ||\mathrm{Log}(\Sigma^{-1/2}\,\Pi\,\Sigma^{-1/2})||_F^2 \tag{6}$$

with $||A||_F^2 = \sum_i \sum_j |A_{ij}|^2$, the (squared) Frobenius norm of a matrix A. Arsigny et al. (Arsigny et al.,
2005) proposed another framework to account for the Riemannian structure of the manifold of SPD
matrices. This framework, known as Log-Euclidean Riemannian Metric (LERM), consists basically on
embedding points of the manifold in an Euclidean space by using the matrix logarithm $\mathrm{Log}(\cdot)$. Standard
Euclidean computations can be performed on SPD matrices' logarithms, since they have been mapped to
Euclidean space. Under LERM, the geodesic distance between two SPD matrices Σ, Π is simply

$$d^2(\Sigma, \Pi) = ||\mathrm{Log}(\Sigma) - \mathrm{Log}(\Pi)||_F^2, \tag{7}$$

that is, the Euclidean distance of matrix logarithms. The computation of these distances is directly
implemented in SPDtoolbox.

A useful object in the manifold that can be constructed given a collection of SPD matrices $\Sigma_1, \Sigma_2, ..., \Sigma_N$
is their Fréchet mean. The Fréchet mean is the generalization of the concept of centroid or center of

mass to more general metric spaces other than Euclidean space, giving a sense of centrality measure.
Mathematically, the Fréchet mean of the previous set of matrices is defined as

$$\overline{\Sigma} = \operatorname*{argmin}_{\Sigma \in \mathcal{M}} \sum_{i=1}^{N} d^2(\Sigma, \Sigma_i), \tag{8}$$

that is, the SPD matrix $\overline{\Sigma}$ that minimizes the sum of the squared distances from itself to the collection of
matrices. The Fréchet mean depends on the chosen distance function in the manifold and, therefore, the
Fréchet means under LERM and AIRM in general do not coincide. When considering AIRM, the Fréchet
mean has to be computed by an optimization procedure. In (Pennec, 2006), the author proposed a Newton
gradient descent algorithm which, after some mean initialization, consists on iterating the following update
rule to get successive estimates $\overline{\Sigma}_t \to \overline{\Sigma}_{t+1}$ until convergence:

$$\overline{\Sigma}_{t+1} = \exp_{\overline{\Sigma}_t}\left(\frac{1}{N} \sum_{i=1}^{N} \log_{\overline{\Sigma}_t}(\Sigma_i)\right). \tag{9}$$

183 The algorithm involves the computation of several matrix logarithms, square roots, inverses and exponentials
184 at each iteration, resulting in a computationally expensive process, especially when dealing with a large
185 number of samples. On the contrary, under LERM, the Fréchet mean has a closed form that enables a very
186 fast computation:

$$\overline{\Sigma} = \operatorname{Exp}\left(\frac{1}{N} \sum_{i=1}^{N} \operatorname{Log}(\Sigma_i)\right), \tag{10}$$

187 which reduces to the obtention of the Euclidean mean of the matrices' logarithms (vectors) and its projection
188 back to the manifold via exponential map. Again, both Fréchet mean computation methods are directly
189 implemented in SPDtoolbox.

2.3 Geometry-aware permutation testing

Permutation tests are non-parametric statistical tests that rely on the randomization of the observed data
to assess the statistical significance of group differences (Nichols and Holmes, 2001). In our case, we have
collected two sets of functional connectivity matrices, one with N_+ ADHD patients $\{\Sigma_i^+ \,|\, i = 1, ..., N_+\}$
and the other one with N_- healthy controls $\{\Sigma_i^- \,|\, i = 1, ..., N_-\}$. The philosophy behind permutation
testing is to make a very large number of random permutations of the N subjects into the two subgroups and
to sample the distribution of values of some statistic under the null hypothesis, that is, under the assumption
that the allocation of a subject into one of the two groups is arbitrary. This procedure allows the obtention
of the approximate null distribution of the statistic and the assessment of how extreme this observation is
with respect to the null distribution of values. Specifically, one can use the definition of p-value to reject
the null hypothesis, i.e., the probability to obtain a value for the statistic as or more extreme than the one
observed, under the assumption that the null hypothesis is correct. Therefore, under the permutation testing
approach, the p-value is the proportion of sampled permutations where the statistic is greater than or equal
to the originally observed statistic.

The geometry-aware algorithm proposed in (You and Park, 2021) and implemented in SPDtoolbox has
the following steps:

1. Compute Fréchet means $\overline{\Sigma}^{+}$ and $\overline{\Sigma}^{-}$ for ADHD patients and healthy controls, respectively, and take $|\overline{\Sigma}^{+} - \overline{\Sigma}^{-}| \equiv |\overline{\Sigma}^{+} - \overline{\Sigma}^{-}|_{obs}$ (the entry-wise absolute value of the difference matrix, the observed statistic of the $n \times n$ entries).

2. For T iterations, perform permutations of the subjects of sizes N_{+} and N_{-} as previously described, recompute group Fréchet means, and record the value of the statistic at iteration t, $|\overline{\Sigma}^{+} - \overline{\Sigma}^{-}|_{t}$.

3. For each entry ij, compute its corresponding p-value by taking the ratio between the number of iterations giving a statistic greater than or equal to $(|\overline{\Sigma}^{+} - \overline{\Sigma}^{-}|_{obs})_{ij}$ and the total number of iterations T.

At this point, assuming some confidence level α, one can reject the null hypothesis for entries with p-values lower than α. It is worth noting that the algorithm tests for statistical significance in absolute difference, and therefore cannot provide information on the positive or negative character of the difference. The output of the algorithm in our case will be a 190×190 matrix with p-values as entries. Nevertheless, we will not rely on a single permutation test on the 80 ADHD/80 HC subjects to perform our analyses. Instead, we have decided to perform 100 separate permutation tests on 10 ADHD/10 HC randomly sampled subjects in each experiment. The reasons for following this approach are: first, taking into account the philosophy behind permutation testing, performing a reliable permutation test on 80 ADHD and 80 HC is not computationally tractable, since the number of ways of dividing 160 subjects into two separate groups of 80 is $160!/(80! \, 80!) \sim 10^{47}$ and, therefore, by no means one can sample a large enough fraction of permutations to rely on the obtained distribution of statistic values; second, by randomly pooling 10 ADHD/10 HC 100 times, regardless of imaging site, one can probe different combinations of site members and site influence on the variability of the results; and third, one can assess the relevance of salient connections and nodes by checking for coincidences between independent permutation tests. Taken together, this treatment allows evaluating the power of harmonization methods, in the sense that when data is harmonized, one expects more sensitivity (coherence, coincidences) in statistically significant results when using randomly sampled subjects from different sites. Given these aforementioned points, we have operated in the following manner: we have performed 100 separate permutation tests, each one of 1000 iterations, on 10 ADHD/10 HC randomly sampled subjects; after each test, we have identified the entries with $p < 0.001$ and declared them as significant; at this point, we have been left with 100 binary matrices of dimensions 190×190 (one for each separate test) with ones in the location of significant entries and zeros elsewhere; and, finally, we have summed these binary matrices to obtain a symmetric 190×190 matrix, which we call F, with F_{ij} being the number of times the connection ij has been declared significant, that could be regarded as a 2-dimensional histogram.

When working at a significance level $\alpha = 0.001$ for each individual permutation test, we are assuming that, at most, the probability of mistakenly declaring an entry as statistically significant by chance is 0.001 (incorrect rejection of the null hypothesis). However, when performing 100 separate experiments and considering jointly their results (as in the frequency histograms), this effect can be accumulated. As a simplification, we can model each separate experiment as a random Bernoulli experiment: the probability of mistakenly declaring each entry as significant by chance in a separate experiment is 0.001. The concatenation of several independent Bernoulli experiments follows the binomial distribution. Therefore, we can use the binomial distribution to compute the probabilities for each separate entry to be declared significant by chance once, twice, 3 times, etc. In our case, considering a probability of 0.001 and 100 trials, the binomial distribution predicts that in the final frequency matrix, the probability for each entry to appear once is 0.09. That is, each entry has a probability of 9% of appearing once in the frequency histogram by chance, what indeed means that at this frequency level ($F_{ij} = 1$), significance is compromised. However,

for entries $F_{ij} \geq 2$, the (complementary cumulative) probability is ≈ 0.005, and for entries $F_{ij} \geq 3$ the
resulting (complementary cumulative) probability is ≈ 0.00015. As a consequence, one can threshold the
histogram matrix F_{ij} at different frequencies depending on the confidence that wants to assume.

Finally, using these notions and taking into account that the previously described procedure will be
applied to different imaging-site harmonization methods introduced in subsection 2.4, we define a simple
quantity that measures the power of a method to specifically point to some entries by accumulating counts
across the 100 separate experiments. We call this measure the sensitivity of the method. At a given
frequency n, the sensitivity $S(n)$ was defined as the ratio between the number of entries such that $F_{ij} \geq n$
and the number of entries such that $F_{ij} \geq 1$.

2.4 Geometry-aware site harmonization

As mentioned in the Introduction, imaging site has an impact on the acquisition of functional data and
their analyses. We show that this is indeed the case for ADHD-200, even when using the same preprocessing
pipeline (Wang et al., 2017). We also prove that, in our case, the principal difference stems from the biased
and site-clustered distribution of connectivity matrices in the SPD manifold. Some geometry-aware domain
adaptation approaches have been proposed, even though not targeting imaging-site variability. We can
distinguish two different harmonization methods that will be analysed separately: matrix whitening at
identity and parallel transport. When being described, they will be adapted to our dataset of ADHD patients
$\{\Sigma_i^+ \,|\, i = 1, ..., N_+\}$ and healthy controls $\{\Sigma_i^- \,|\, i = 1, ..., N_-\}$ and to our imaging-site harmonization aim.

2.4.1 Matrix whitening at identity

269 Suppose our dataset can also be divided into collections of matrices $\{\Sigma_i^{(k)}\}$, with k labeling the imaging
270 site where resting-state data from subject i was acquired. If we denote by $\overline{\Sigma}^{(k)}$ the AIRM Fréchet mean
271 of matrices obtained from site k, the matrix whitening approach reduces to applying the following
272 transformation to all $\Sigma_i^{(k)}$ (Ng et al., 2014; Yair et al., 2019):

$$\Sigma_i^{(k)} \to (\overline{\Sigma}^{(k)})^{-\frac{1}{2}} \Sigma_i^{(k)} (\overline{\Sigma}^{(k)})^{-\frac{1}{2}}. \tag{11}$$

One can show that this transformation is equivalent to a displacement of the matrices such that their Fréchet
mean is the identity matrix. To this aim, consider $C \in GL(n)$, that is, an invertible $n \times n$ matrix. The
following properties hold when considering the AIRM framework (Yair et al., 2019):

1. The geodesic distance (6) between two SPD matrices Σ and Π is invariant under $\Sigma \to C \Sigma C^T$ and
$\Pi \to C \Pi C^T$, i.e., $d(C \Sigma C^T, C \Pi C^T) = d(\Sigma, \Pi)$.

2. Given some Fréchet mean $\overline{\Sigma}(\Sigma_1, ..., \Sigma_N)$, then $\overline{\Sigma}(C \Sigma_1 C^T, ..., C \Sigma_N C^T)$ is equivalent to
$C \overline{\Sigma}(\Sigma_1, ..., \Sigma_N) C^T$.

Transformation (11) can be expressed as $\Sigma_i^{(k)} \to C \Sigma_i^{(k)} C^T$ with $C = (\overline{\Sigma}^{(k)})^{-\frac{1}{2}} = C^T$, following the last
equality from the fact that, if $\overline{\Sigma}^{(k)}$ is SPD, $(\overline{\Sigma}^{(k)})^{-\frac{1}{2}}$ is also SPD and, therefore, $\left((\overline{\Sigma}^{(k)})^{-\frac{1}{2}}\right)^T = (\overline{\Sigma}^{(k)})^{-\frac{1}{2}}$.
By virtue of the first property, intra-site geodesic distances are preserved, and the Fréchet mean becomes
$\overline{\Sigma}^{(k)} \to (\overline{\Sigma}^{(k)})^{-\frac{1}{2}} \overline{\Sigma}^{(k)} (\overline{\Sigma}^{(k)})^{-\frac{1}{2}} = I$, following from the second property.

In (Ng et al., 2014), authors followed this approach and applied the logarithmic map $\text{Log}(\cdot)$ to project
transformed SPD matrices to the common tangent space at identity before performing classification. To
our understanding, invariance of intra-site distances is a desirable property for harmonization since it is

essential to preserve intra-site variability, presumably coming from biological sources (that is, disease, age,
gender, medication status, etc). However, we think that, in our setting, it might be a priori more cautious
not to remove information about the original location of matrices in the manifold by displacing them to the
neighbourhood of the identity matrix, since it could also remove relevant clinical information.

One could also consider the use of two different $\overline{\Sigma}^{(k)}$, one for patients and another one for healthy
controls, since one expects their Fréchet means to be different. However, the use of a single site Fréchet
mean to perform the transformation is based on two considerations. On the one hand, the use of different
transformations for ADHD patients and HC would violate the preservation of all pair-wise distances within
the site, since the matrix C would be different depending on the condition of the subjects. Distances
among HC on one side and distances among ADHD patients on the other side would be preserved, while
distances between HC and ADHD patients would not. This fact could be regarded as the introduction of an
uncontrolled source of variability between conditions. On the other hand, it would be desirable to have a
harmonization approach that does not depend on the availability of knowledge about subjects' conditions,
which would be required when using different transformations. For example, as stated in the Introduction,
domain adaptation has been proven useful when training classifiers. Ideally, when the classifier is reliable
enough, one would like to assign the condition to a subject without knowing it a priori. Therefore, the use
of a single transformation would allow the harmonization of the data prior to the use of the classifier.

304   2.4.2   Parallel transport

Elements from two different tangent spaces cannot be directly compared. To compare them in an
appropriate manner, one needs to perform what is called parallel transport. In short, parallel transport refers
to transporting a tangent space at a point along a geodesic distorting vectors of this tangent space as less
as possible. In (Yair et al., 2019), authors provide an excellent and rigorous mathematical description of
parallel transport in the manifold of SPD matrices. For harmonization and comparison of SPD matrices,
we are interested in transporting and projecting them to a common tangent space.

The main line of reasoning applied to our case is as follows:

1. Project matrices from a given site k to the tangent space of their site Fréchet mean $\overline{\Sigma}^{(k)}$ via logarithmic
map $\log_{\overline{\Sigma}^{(k)}}(\Sigma_i^{(k)})$.
2. Parallel transport them to the tangent space of a common reference point Σ_0.
3. Reproject the parallel transported matrices back to the manifold via exponential map $\exp_{\Sigma_0}(\cdot)$.

One of the main results of (Yair et al., 2019), is that all this process can be performed by the transformation
$\Sigma_i^{(k)} \rightarrow C\,\Sigma_i^{(k)}C^T$ with $C = \left(\Sigma_0(\overline{\Sigma}^{(k)})^{-1}\right)^{1/2}$. Therefore, properties 1 and 2 presented in the case
of matrix whitening also hold here: intra-site distances are preserved and the Fréchet mean becomes
$C\,\overline{\Sigma}^{(k)}C^T$.

Then, one has to decide which is the appropriate reference point Σ_0. Ng et al. (Ng et al., 2014) used
$\Sigma_0 = I$ to compare the classification performance between the present method and matrix whitening at
identity, although they performed parallel transport numerically (Schild's ladder). In this case, $C = C^T = $
$(\overline{\Sigma}^{(k)})^{-1/2}$ and the Fréchet mean reduces to I (notice that the transformation is exactly equivalent to matrix
whitening), arising the same previously mentioned concerns about original location in the manifold. On the
other hand, Yair et al. (Yair et al., 2019) suggest using as the reference point $\Sigma_0 = \overline{\Sigma}$, the Fréchet mean of
site means $\{\overline{\Sigma}^{(k)}\}$. This approach takes into account the original location of SPD matrices in the manifold

through the global mean $\overline{\Sigma}$. Right after this step, Yair et al. perform matrix whitening using $\overline{\Sigma}$. We will
refer to this whole process proposed by Yair et al. as simply parallel transport (even though proper parallel
transport is the step performed after projecting to the site mean's tangent space and before reprojecting
back to the manifold at the reference point). Notice that the use of a single reference point Σ_0 in our setting,
both for ADHD patients and HC, can be justified by taking into account the same considerations from the
previous subsection.

A priori, matrix whitening and parallel transport are different transformations. Nevertheless, one can
show that under the condition $\left[\overline{\Sigma}, \overline{\Sigma}^{(k)}\right] \equiv \overline{\Sigma}\,\overline{\Sigma}^{(k)} - \overline{\Sigma}^{(k)}\,\overline{\Sigma} = 0, \forall k$, that is, when site means commute
with the global mean, parallel transport and matrix whitening are equivalent frameworks. This property is
proven in the Annex, and it will have an impact on the results we obtain.

2.4.3 Rigid Log-Euclidean Translation

We hereby propose a method for site harmonization, which we call Rigid Log-Euclidean Translation
(RLET), that has the two a priori desirable properties stated above: preservation of intra-site geodesic
distances, thus retaining biological variability, and consideration of the original location of correlation
matrices in the manifold. Site bias could also impact the distribution of matrices around site mean, but
this would require modelling site effects on the distribution of matrices around their mean. The proposed
method is therefore a geometrically-motivated first order approximation. We will work under the LERM
framework, which allows a purely Euclidean treatment of the logarithm of the matrices. The steps of Rigid
Log-Euclidean Translation are the following ones:

1. Compute the logarithm of site Fréchet mean for all k

$$\text{Log}(\overline{\Sigma}^{(k)}) = \frac{1}{N^{(k)}} \sum_{i \in (k)} \text{Log}(\Sigma_i^{(k)}), \tag{12}$$

347 where the sum runs through all subjects in site k, and $N^{(k)}$ is the total number of subjects in site k.
348 2. Compute the logarithm of the global mean $\overline{\Sigma}$ defined as

$$\text{Log}(\overline{\Sigma}) = \frac{1}{K} \sum_{(k)} \text{Log}(\overline{\Sigma}^{(k)}), \tag{13}$$

349 with K being the number of sites.
350 3. Apply the following transformation to the entire collection of matrices $\{\Sigma_i^{(k)}\}$ given their k

$$\text{Log}(\Sigma_i^{(k)}) \rightarrow \text{Log}(\tilde{\Sigma}_i^{(k)}) = \text{Log}(\overline{\Sigma}) + \left(\text{Log}(\Sigma_i^{(k)}) - \text{Log}(\overline{\Sigma}^{(k)})\right). \tag{14}$$

4. Use the exponential map to obtain the modified (site-harmonized) SPD matrices $\text{Exp}\left(\text{Log}(\tilde{\Sigma}_i^{(k)})\right) =$
$\tilde{\Sigma}_i^{(k)}$.

When taking into account that after applying the logarithmic map to the original matrices we obtain vectors
of the Euclidean space $\mathbb{R}^{n \times n}$, the above transformation is merely a translation of the original matrices
such that transformed site means $\overline{\tilde{\Sigma}}^{(k)}$ are identically the global mean $\overline{\Sigma}$. In fact, it is a rigid translation of

matrices logarithms, representing an isometry of the Euclidean metric, and therefore preserving Euclidean
distances in the Euclidean space $\mathbb{R}^{n \times n}$. These properties are formally proven in the Annex.

Since geodesic distances under the LERM framework are these Euclidean distances, intra-site geodesic
distances are invariant under the proposed transformation, and the Rigid Log-Euclidean Translation
approach preserves intra-site variability. The transformation also allows retaining information about the
original location in the manifold through the global mean. On the other hand, one can straightforwardly
modify this approach to rigidly transport matrices to I, by removing the term $\mathrm{Log}(\overline{\Sigma})$ from the
transformation rule. In this case $\mathrm{Log}(\widetilde{\overline{\Sigma}}^{(k)}) = 0 = \mathrm{Log}(I), \forall\, k$, (see Annex) and resulting relative positions
between all matrices in Euclidean space are the same as when translated to $\overline{\Sigma}$. We will refer to these
two approaches as $\mathrm{RLET}(\overline{\Sigma})$ and $\mathrm{RLET}(I)$. $\mathrm{RLET}(I)$ can be useful to compare different harmonization
strategies at identity, and to probe differences coming uniquely from manifold location.

2.5 Pair-wise distances and low-dimensional embedding

Even though all the concepts presented above are geometrically motivated, the major difficulty for bias
characterization stems from the fact that we are dealing with a very high-dimensional space (in our case,
$d = n(n + 1)/2 = 190(190 + 1)/2 = 18145$). Therefore, the extraction of insights from this space is
a challenging task. However, since our manifold is equipped with a metric and a distance measure (i.e.,
the manifold is Riemannian), we can construct a useful object that can summarize important geometric
information: the pair-wise distance matrix $D_{ij} = d(\Sigma_i, \Sigma_j)$ between functional connectivity matrices
(subjects). In fact, this approach of using pair-wise distances or pair-wise similarities is common in
unsupervised techniques of dimensionality reduction for visualization purposes, such as multidimensional
scaling (MDS) or t-distributed stochastic neighbour embedding (tSNE).

We will focus on t-distributed stochastic neighbour embedding (tSNE), since it was the method of choice
in the previous works we have adapted for site harmonization. tSNE (van der Maaten and Hinton, 2008) is
a nonlinear dimensionality reduction technique that maps a data point in a high-dimensional space to a
point in 2-dimensional or 3-dimensional Euclidean space. Differently from other nonlinear dimensionality
reduction approaches, tSNE has a probabilistic nature. Originally, the similarity metric of the algorithm was
taken to be the pair-wise Euclidean distance between high-dimensional points, although currently different
metrics can be used depending on the task at hand. However, the usual Euclidean distance is a good choice
in our case: by using as high-dimensional inputs the logarithms of the matrices, the similarity measure
between two different matrices will turn out to be the LERM geodesic distance. As a consequence, the
low-dimensional embedding and its visualization will display similarity given by the pair-wise distribution
of matrices in the manifold (under the LERM framework) with very high probability. At this point, one is
able to assess the distribution of matrices in the manifold and, therefore, to characterize original geometric
imaging-site bias and evaluate the effect of harmonization methods.

2.6 Functional analysis

One can perform comparative functional analyses between methods in terms of resting-state networks
instead of specific ROI-to-ROI connections. To this aim, we will use the Yeo 17-networks atlas (Yeo et al.,
2011), where the brain is parcellated into 17 different resting-state networks. We have further reduced the
number of networks by using the following proposed correspondence: 1 and 2 correspond to the visual
network (VIS); 3, 4 and 14 to the sensorimotor network (MOT); 5 and 6 to dorsal attention (DA); 7 to
ventral attention (VA); 8, 11, 12 and 13 to frontoparietal network (FP); 9 and 10 to limbic (LIM); and
15, 16 and 17 to default mode network (DMN). However, Yeo's parcellation does not include important

subcortical regions that are included in our ROIs (CC200 parcellation, see Introduction). Therefore, and
taking into account the results we have obtained, we have introduced the brain-stem (BS), the cerebellum
(CRB) and basal ganglia (BG). In total, we are left with 10 different functional components.

Once we have the functional parcellation of the brain, we will assign each ROI to its corresponding
functional component by using the ROI's coordinates. This will allow us to initially focus our attention
on inter-network and intra-network interactions, since the individual study of salient connections would
be intractable when the number of detected significant differences in ADHD and HC connectomes is
large. When thresholding frequency matrices F_{ij} at higher frequency levels, the number of samples will be
reduced and an individual treatment of these differences will be possible.

3 RESULTS

3.1 Pair-wise distances and distribution of matrices

We have constructed the aforementioned pair-wise distance matrices $D_{ij} = d(\Sigma_i, \Sigma_j)$ that retain
information of the high-dimensional distribution of the matrices in the manifold. Specifically, we
have computed pair-wise distances for: original (non-modified) matrices $D_{ij}^{(0)}$ both using AIRM and
LERM distances, harmonized matrices under Rigid Log-Euclidean Translation (RLET($\overline{\Sigma}$) and RLET(I)),
$D_{ij}^{(\mathrm{RLET}(\overline{\Sigma}))}$ and $D_{ij}^{(\mathrm{RLET}(I))}$, using LERM distance, and matrix-whitening-harmonized (MW) and
parallel-transport-harmonized matrices (PT), $D_{ij}^{(\mathrm{MW})}$ and $D_{ij}^{(\mathrm{PT})}$, employing AIRM distance (Figure 1).

$D_{ij}^{(\mathrm{MW})}$ and $D_{ij}^{(\mathrm{PT})}$ look identical (Figure 1C and Figure 1F). This approximate equivalence can be
explained by nearly vanishing commutators $\left[\overline{\Sigma}, \overline{\Sigma}^{(k)}\right]$, as previously proved. We have checked the values
of these commutators and, indeed, they almost vanish, as can be seen in Figure 2. The consequence is that,
in practical terms, in the following we can regard PT and MW as two equivalent frameworks.

On the other hand, we have applied tSNE to the logarithms of: original (non-harmonized) matrices,
RLET($\overline{\Sigma}$)-harmonized matrices and MW-harmonized matrices, with results shown in Figure 3 and Figure 4.
Therefore, we have obtained a low-dimensional representation of $D_{ij}^{(0)}$, $D_{ij}^{(\mathrm{RLET}(\overline{\Sigma}))}$ and $D_{ij}^{(\mathrm{MW})}$, all of
them computed by means of LERM distances. RLET(I)-harmonized matrices have not been used since, by
construction, their pair-wise distances are identical to the ones for RLET($\overline{\Sigma}$), and, regarding PT-harmonized
matrices, they are almost exactly equivalent to the ones obtained using MW. The differences that could
be displayed in the visualization of RLET(I) matrices compared to RLET($\overline{\Sigma}$)-harmonized ones and PT
compared to MW would be due to the stochastic nature of the tSNE algorithm.

3.2 Numerical assessment of harmonization properties

Two harmonization properties were required from the beginning: preservation of intra-site geodesic
distances, thus preserving biological variability (and some residual site bias), and the imposition of a
common Fréchet mean. In the case of RLET($\overline{\Sigma}$), this Fréchet mean is the global mean $\overline{\Sigma}$, and in the case of
RLET(I) and MW, the identity matrix I. To check that the first property is fulfilled, we have computed
pair-wise distance difference matrices $D_{ij}^{(\mathrm{RLET}(\overline{\Sigma}))} - D_{ij}^{(0)}$ (with RLET(I) giving the same results by
construction) and $D_{ij}^{(\mathrm{MW})} - D_{ij}^{(0)}$ (in this latter case, using $D_{ij}^{(\mathrm{PT})}$ would give visually the same result,
since $D_{ij}^{(\mathrm{PT})} \approx D_{ij}^{(\mathrm{MW})}$, as proved before). We have found that diagonal blocks (differences in intra-site
distances) vanish identically (Figure 5A and 5B). Regarding the second property, we have computed: on
one side, pair-wise LERM distances between site means and between the global mean and these site means,
before RLET(I) and RLET($\overline{\Sigma}$), and after RLET($\overline{\Sigma}$) harmonization; and on the other side, pair-wise AIRM

distances between site means and global mean before MW harmonization, pair-wise AIRM distances
between site means and the identity matrix after MW harmonization, and pair-wise LERM distances
between site means and the identity matrix after RLET(I) (Figures 5C, 5D, 5E, 5F). After harmonization
these pair-wise distances vanish identically.

3.3 Entry-wise ADHD/HC differences

The process of performing 100 separate experiments, described in subsection 2.3, to detect entry-
wise differences, has been applied, with the same randomly pooled subjects, to original, RLET($\overline{\Sigma}$)-
harmonized, RLET(I)-harmonized and MW-harmonized matrices (PT has been disregarded because
of its approximate equivalence to MW). Therefore, we have obtained four frequency matrices $F_{ij}{}^{(0)}$,
$F_{ij}{}^{(\mathrm{RLET}(\overline{\Sigma}))}$, $F_{ij}{}^{(\mathrm{RLET}(I))}$ and $F_{ij}{}^{(\mathrm{MW})}$, respectively, which are shown in Figure 6. Results on the
sensitivity (defined also in subsection 2.3) we have obtained for $F_{ij}{}^{(0)}$, $F_{ij}{}^{(\mathrm{RLET}(\overline{\Sigma}))}$, $F_{ij}{}^{(\mathrm{RLET}(I))}$ and
$F_{ij}{}^{(\mathrm{MW})}$ are shown in Table 1 between parentheses, together with the number of detected significant
differences depending on their frequency of appearance in the frequency matrices.

3.4 Intra-network and inter-network anomalies distribution

In the following, we will refer to significant differences in connection strength between ADHD and
HC subjects as 'anomalies'. To have a global view of the distribution of anomalies in terms of inter- and
intra-network interaction, we have constructed a 2-dimensional plot that reflects the relative involvement of
the different resting-state networks in these interactions.

This 2-dimensional plot is a 10×10 matrix (one row and one column per functional component)
constructed as follows: first, we have filled the matrix by assigning to each entry ij the number of
anomalies connecting functional component i with functional component j (therefore, diagonal elements
represent intra-network anomalies), with the matrix being symmetric since we do not have a sense of
directed connection; afterwards, we have normalized each row (say, for example, DMN), excluding
diagonal elements, by using the total number of inter-network anomalies that involve the component
represented by that row (DMN); finally, in the last step, we have normalized the diagonal by dividing each
diagonal entry by the sum of all diagonal entries (that is, the total number of intra-network anomalies).
At this point, we are left with a matrix where each row, excluding diagonal entries, adds up to 1, and
in turn, diagonal entries add up to 1. One has to interpret this matrix in the following manner: when
taking, for example, the row corresponding to DMN, the entry DMN-FP is the percentage of inter-network
anomalies involving DMN that end up connected to FP; when considering DMN-DMN, it is the percentage
of intra-network anomalies that are found within DMN. Therefore, we have summarized in a plot the
relative contribution of every functional component to the inter-network anomalies involving another
specific functional component. One has to bear in mind that DMN-FP (row-column) does not have the
same interpretation as FP-DMN and, indeed, their values are different in general (after normalizing per
row, the matrix is no longer symmetric): the number of anomalous connections between DMN and FP is
fixed, but their relative contribution to the total number of inter-network anomalies involving DMN and to
the total number of inter-network anomalies involving FP need not be the same.

We have plotted these matrices for the anomalies obtained using the original, the RLET($\overline{\Sigma}$)-harmonized,
the RLET(I)-harmonized and the MW-harmonized functional connectomes (Figure 7). They have been
computed with the anomalous connections identified by thresholding their corresponding frequency
matrices at $F_{ij} \geq 2$ to have a large enough number of samples (Table 1). Furthermore, we have computed
differences between the plots corresponding to original and RLET($\overline{\Sigma}$), between RLET(I) and MW, and

between RLET($\overline{\overline{\Sigma}}$) and RLET($I$); afterwards, we have binarized the resulting difference plots at an absolute
entry-wise difference $\geq 15\%$, thus allowing the detection of important changes in the distributions and
assessing harmonization and manifold location effects. These results are shown in Figure 8.

Even though a more involved interpretation of these results will be made in the Discussion section,
we highlight that discrepancies between RLET($\overline{\overline{\Sigma}}$) and RLET($I$) signal distortions induced by relocating
matrices to the neighbourhood of I, since relative positions between matrices in Log-Euclidean space are
exactly the same by construction. Therefore, in the following, we will focus on the comparison between
non-harmonized and RLET($\overline{\overline{\Sigma}}$)-harmonized matrices.

3.5 RLET($\overline{\overline{\Sigma}}$)-harmonization results

At this point, we focus on results at a frequency $F_{ij} \geq 3$ to allow a more precise comparison between the
results obtained from non-harmonized and RLET($\overline{\overline{\Sigma}}$)-harmonized matrices. In this case, we have obtained
21 significant inter-network connections using non-harmonized matrices; and 32 inter-network and 1
intra-network anomalies after transforming original matrices under the RLET($\overline{\overline{\Sigma}}$) framework. We have
represented the resulting anomalous connectomes in Figures 9,10.

Moreover, we have plotted two histograms, one for non-harmonized and the other for RLET($\overline{\overline{\Sigma}}$)-
harmonized matrices, displaying how the distribution of abnormal connections involving particular
functional components varies according to the frequency threshold (Figure 11). When looking at the
histograms, one can see that the distribution of anomalies according to the involved functional component
is better preserved when changing the considered frequency level in the case of RLET($\overline{\overline{\Sigma}}$) than in the
non-harmonization approach.

4 DISCUSSION

4.1 Imaging-site bias

Results from pair-wise distances computation (Figure 1) and low-dimensional embedding (Figures 3
and 4) of functional connectivity matrices show that there is an imaging-site-biased distribution of these
matrices in the manifold. In particular, one can distinguish between an intra-site bias effect and an inter-site
bias effect. Intra-site bias is clearly visible when looking at diagonal blocks of pair-wise distances plots:
intra-site distances are significantly different between KKI and NIM matrices (interestingly, the NIM
sample comes in its turn from 3 different imaging sites (ADHD-200 Consortium, 2017), what could
explain its large intra-site variability). Instead, one would expect the intrinsic biological variability to be
approximately the same across sites when the number of subjects is large enough. Inter-site bias is reflected
in the clustered distribution of matrices in the manifold that makes possible to clearly identify visually
the imaging site in the tSNE low-dimensional embedding (recall that this low-dimensional embedding is,
with high probability, displaying LERM distance similarities). When harmonizing using the three different
methods, inter-site distances were generally reduced (Figure 1), which is the expected effect of removing
site-clustering behaviour.

The clustered distribution in the manifold (Figure 3) points directly to the fact that entry-wise statistical
comparisons could not be completely reliable unless the site effect is previously subtracted (Figure 4),
since what are usually targeted in these statistical tests are entry-wise differences. Because of the nature of
the permutation testing approach targeting these differences, large entry-wise differences coming from the
original clustered and distant distribution of the matrices might be masking true and more subtle biological
differences, or even giving rise to wrong salient entries. Geometry-grounded frameworks transform the

matrices' entries in such a way that they can still be regarded as covariances (resulting matrices belong
to the SPD manifold, as opposed to ComBat outputs, for example), that removes (partially) multi-site
effects on entry-wise differences, and therefore that allows a more unbiased study of significance of these
individual differences or anomalies.

Regarding the detection of significant differences, in terms of sensitivity RLET(I) is the harmonization
method that performs the worst (Table 1) at all frequency thresholds. Nevertheless, only by using
harmonization approaches have we reached the $F_{ij} = 5$ level. On the other hand, site means transform
as expected, becoming the identity matrix I for RLET(I) and MW, and the global mean $\overline{\Sigma}$ in the case
of RLET($\overline{\Sigma}$), since pair-wise distances vanish. Intra-site distances are also preserved as intended but,
as a consequence, intra-site bias is also retained. However, as a first approximation to imaging-site
harmonization, our aim was to operate in the least distortive manner. One cannot know to which extent
true biological variability would be artificially altered by modifying intra-site distances, even though it
is clear that there is an imaging-site contribution to the observed dispersion. Notice however that when
looking at Figure 4A, it seems that MW has been able to correct differences in dispersions, as opposed to
RLET (Figure 4B). This impression is an artifact coming from the fact that the low-dimensional embedding
has been obtained by using LERM distances, both for MW and for RLET. MW is based on the AIRM
framework and, therefore, the low-dimensional embedding, using LERM distances as the metric, has
not been able to capture the expected intra-site AIRM distance preservation behavior. In fact, if one
considers Figure 1, one can see that different dispersions around the site mean have not been corrected for
MW (Figure 1C), since diagonal blocks exhibit different average intra-site distances in the same way as
RLET-transformed ones (Figure 1D).

Figure 8 provides evidence favouring harmonization, but also evidence for rejecting harmonization at the
identity matrix. Testing for the difference between these distribution matrices and requiring entry-wise
coincidence within $\pm 15\%$ is strict, bearing in mind that we are dealing with relative contributions of
connections among and within 10 different components, and the number of samples is considerably small.
Therefore, at this point, looking at the differences between RLET(I) and MW (only 3/100 entries display
absolute differences larger than 15%), we can claim that harmonization is indeed working in its task
of homogenizing results. However, taking into account that the only difference between RLET(I) and
RLET($\overline{\Sigma}$) is the location of the Fréchet mean (relative positions between functional connectivity matrices
in the Log-Euclidean space are exactly preserved by construction), and considering the dissimilarities
between distributions, we can affirm that: location in the manifold is important (as we had presumed in
the Methods section, and motivating our construction of RLET($\overline{\Sigma}$)) and that transporting matrices to the
identity matrix is too distortive in our setting. As a consequence, and given that discrepancies in anomaly
distributions between original and RLET($\overline{\Sigma}$) are three-fold (9/100) the ones observed by harmonizing with
two different approaches at identity (3/100), we have focused our attention in the following subsection on
the effect of RLET($\overline{\Sigma}$)-harmonization on the original functional connectivity matrices, since these (possibly
biologically relevant) discrepancies are, at least partially, due to harmonization.

Finally, given the results pointing to a considerably large intra-site bias, we can propose a modification to
RLET($\overline{\Sigma}$):

$$\text{Log}(\Sigma_i^{(k)}) \rightarrow \text{Log}(\tilde{\Sigma}_i^{(k)}) = \text{Log}(\overline{\Sigma}) + \lambda^{(k)}\big(\text{Log}(\Sigma_i^{(k)}) - \text{Log}(\overline{\Sigma}^{(k)})\big), \tag{15}$$

558 consisting on the introduction of a site-dependent rescaling parameter $\lambda^{(k)} > 0$, which has the effect of
559 rescaling intra-site distances by a factor of $\lambda^{(k)}$ while still enforcing all site Fréchet means to be the global
560 mean $\overline{\Sigma}$. Tuning $\lambda^{(k)}$ would allow, for example, to empirically adjust mean intra-site distances (and, thus,

561 intra-site variability), so that different sites display approximately the same dispersion around $\overline{\Sigma}$. A first
562 approximation choice for $\lambda^{(k)}$ could be therefore:

$$\lambda^{(k)} = \frac{\frac{1}{K} \sum_{(k')} \frac{1}{2N^{(k')}} \sum_{i \in (k')} \sum_{j \in (k')} d(\Sigma_i, \Sigma_j)}{\frac{1}{2N^{(k)}} \sum_{i \in (k)} \sum_{j \in (k)} d(\Sigma_i, \Sigma_j)}, \tag{16}$$

563 that is, the ratio between the mean of all intra-site pair-wise distances (regardless of k) and the mean of
564 intra-site-k distances.

4.2 Abnormal functional connectivity findings

4.2.1 Large-scale networks in ADHD

By thresholding frequency matrices at $F_{ij} \geq 2$ one can obtain a large enough number of anomalies to
construct the distributions shown in Figure 7. This approach enables to obtain a coarse-grained picture of
anomalous interactions and, therefore, to take into account anomalous engagement between large-scale
resting-state networks.

Although there is a large amount of pair-wise interactions, the most descriptive findings are obtained by
considering relevant functional components that do not have anomalous inter- or intra-network interactions.
Using non-harmonized matrices, we have found that at $F_{ij} \geq 2$ there is an absence of intra-DA and intra-VA
anomalous connections. In the case of RLET($\overline{\Sigma}$)-harmonized matrices, we see an absence of intra-VIS
and intra-VA anomalies, and an absence of DA-VA and VIS-VA inter-network abnormal interaction. In
both cases, BG engage abnormally selectively with DMN, FP and VIS networks. In resting-state functional
connectivity, in general, findings do not support an involvement of VA in ADHD, even though authors do
not find this evidence to be conclusive (Castellanos and Proal, 2012). On the contrary, DA involvement in
ADHD is well-established (Dickstein et al., 2006; Rubia, 2011). Absence of intra-DA alterations under
the non-harmonization framework could be therefore interpreted as a deficit of the framework. Intra-VIS
alterations, both hyper- and hypoactivations, have been found in task-based settings, depending on the task
(Dillo et al., 2010; Schneider et al., 2010; Vance et al., 2007). One study found altered intra-VIS resting-
state functional connectivity by using ADHD-200 resting-state data (Kessler et al., 2014) (correlating with
results from the analysis of non-harmonized matrices, where intra-VIS contributions are found). Authors
highlight the importance of examining carefully the impact of the visual component in ADHD and, in
particular, its relation to attention (Castellanos and Proal, 2012). To our opinion, given the importance (in
terms of contribution to anomalies) that RLET($\overline{\Sigma}$)-harmonization gives to VIS, the absence of intra-network
findings is descriptive, in the sense that it is difficult to understand that the algorithm did not discover
intra-network anomalies because of sensitivity regarding the visual component.

4.2.2 Pathophysiology of ADHD

Although there is a growing consensus that large-scale brain networks are involved in ADHD, the
number of anomalous connections that remain as significant when thresholding their frequency at $F_{ij} \geq 3$
does not allow an interpretation in terms of network interactions, but rather an interpretation in terms of
pathways, (parts of) circuits or pair-wise relevant connections. This interpretation makes possible to probe
the fine-grained pathophysiology of ADHD from a functional point of view, and to correlate our findings
with established results.

4.2.2.1 Prefrontal cortex

It has been hypothesized for a long time that ADHD is a disorder of the prefrontal cortex (PFC). The motivation underlying the hypothesis of involvement of PFC is that one of its most important functions is behavioural control, the principal impairment presented by ADHD patients. The circuitry that has been found to be critical in the neurobiology of ADHD are the cortico-striatal-thalamo-cortical (CSTC) loops. These closed loops transmit cortical inputs to the thalamus via the striatum, to be reprojected back to the cortical region. Two of these loops play a key role in ADHD: the dorsolateral prefrontal circuit, with the dorsolateral prefrontal cortex (DLPFC) and the (dorsolateral) caudate nucleus forming the cortico-striatal pathway, and the orbitofrontal circuit, composed of the orbitofrontal cortex (OFC) and the (ventromedial) caudate nucleus pathway. The dorsolateral prefrontal circuit is a central element in cognitive control, and the orbitofrontal circuit is heavily implicated in reward processing, whose impairment is thought to provoke impulsive behaviour in ADHD. On top of these ones, another component that has been added more recently to ADHD PFC anomalous connections is the fronto-cerebellar circuitry. The cerebellum is thought to be involved in diverse functional impairments of ADHD patients, such as working memory, attention, or the construction of temporal expectations. For a detailed description of the involvement of these circuits in ADHD, we refer the reader to (Durston et al., 2011) and references therein.

Remarkably, the analysis of RLET($\overline{\Sigma}$)-harmonized matrices points directly to these circuits: we have found anomalous connectivity between the right caudate nucleus and the left OFC; between right cerebellum (VIIb) and the right frontal pole; together with a connected chain comprising the left caudate nucleus, the right inferior frontal gyrus pars opercularis, left cerebellum (VIIb) and the right angular gyrus, with both right inferior frontal gyrus pars opercularis and right angular gyrus lying on DLPFC. Therefore, we have found evidence for: 1) anomalies in frontostriatal paths, both in the OFC and DLPFC circuits; 2) an abnormal connectivity in a fronto-cerebellar path (right cerebellum - right frontal pole); 3) a simultaneous anomalous engagement of fronto-cerebellar and frontostriatal circuits with the same cortical region, DLPFC (left cerebellum - right angular gyrus, right inferior frontal gyrus pars opercularis - left caudate nucleus); and 4) more specifically, a simultaneous anomalous engagement of a fronto-cerebellar circuit and a frontostriatal circuit involving exactly the same cortical node (right inferior frontal gyrus pars opercularis, DLPFC), and, thus, a precise anomalous overlap of different circuitry components. Results of non-harmonized matrices also feature the anomalous connection between the left caudate nucleus and the right inferior frontal gyrus pars opercularis. In this case, we would only have evidence for the involvement of the DLPFC circuit. Furthermore, it is important to mention that non-harmonized matrices have not signaled any anomaly involving cerebellar nodes, which is undesirable given the pervasive evidence of their implication in ADHD. In contrast, RLET($\overline{\Sigma}$)-harmonization provides evidence of abnormal functional connectivity of the cerebellum with somatomotor, default mode network and visual nodes, apart from the PFC ones, pointing to the multi-dimensional association to ADHD pathophysiology.

4.2.2.2 Visual nodes

It has been established that ADHD patients have worse performances when tested for visual processing speed and visual short-term memory in comparison to matched healthy controls (Low et al., 2018). These abnormal performances signal a perceptual deficit and, more concretely, impairments in early visual information processing (Alqahtani et al., 2019; Papp et al., 2020).

One of the most remarkable differences between the anomalies spotted using the original matrices and the RLET($\overline{\Sigma}$)-harmonized ones is the importance that the analysis of the latter matrices gives to visual network nodes, in terms of contribution to the total number of detected anomalies. Specifically, there is

an interesting and insisting presence of anomalous connections between visual network nodes and nodes
found in the posterior parietal cortex (PPC), belonging to the dorsal attention network (DA). Precisely,
these connections fill the void found in Figure 9. It has been found that the interaction between the occipital
cortex and DA is involved in maintaining attention and suppressing attention to irrelevant stimuli (Shulman
et al., 2009; Capotosto et al., 2009). Our findings signal specifically the anomalous connection of nodes
lying on the most posterior part of DA and nodes of the visual cortex. One important pathway for visual
information processing connects these brain regions: the dorsal stream. The dorsal stream and the ventral
stream were proposed as two routes with differentiated functions in early processing of visual information
(Goodale and Milner, 1992): the dorsal stream, running from the visual cortex to PPC, is typically thought
to be involved in the construction of a detailed map of the visual field, spatial awareness, the detection and
analysis of motion and the guidance of actions and coordination in space; on the other hand, the ventral
stream, originating in the visual cortex and leading to the temporal lobe, is proposed to be related to visual
identification and recognition.

The dorsal stream, which is tentatively being featured in our findings, has been demonstrated with clinical
and experimental evidence to play an essential role in the ability of shifting spatial attention, that is, to
disengage attention from a location and to engage attention to another location (Sciberras-Lim and Lambert,
2017). Although in ADHD patients there is a disregulation in attentional resources allocation, it is still not
clear which dimensions of attention are affected by the disorder. The affectation of visuospatial attention is
a controversial topic (Roberts et al., 2017), with findings pointing to opposite ways. Many authors point to
the fact that given the wide spectrum of impairments that patients exhibit, their phenotyping by a particular
dimension of attention might not be possible (Roberts et al., 2017). Nevertheless, what is widely accepted is
that ADHD patients display a deficit in visuospatial working memory (van Ewijk et al., 2013), the capacity
to maintain a representation of visuospatial information for a brief period of time (Vecera and Rizzo, 2003).
In particular, visuospatial working memory is involved, for example, in retrieval and manipulation of recent
images for orientation in space and for keeping track of moving objects. As we have explained, the dorsal
stream plays a critical role in the integration of visual information to produce the egocentric spatial map on
which the subject relies to detect motion or to guide his/her actions in space. Therefore, there is coherence
between the impairment of visuospatial working memory in ADHD and the tentative appearance of the
dorsal stream in our findings.

4.2.2.3   *Other relevant anomalies*

Given the coherence between the results obtained after RLET($\overline{\Sigma}$)-harmonization and established ADHD
pathophysiology, we have reasons to think that default mode network (DMN), sensorimotor (MOT), visual
(VIS), dorsal attention (DA) and frontoparietal (FP) nodes play very important roles in the disorder, and
that the right lateral occipital cortex is a region that needs to be examined more carefully in subsequent
analyses. When thresholding the frequency matrix at $F_{ij} \geq 4$, we are left with 8 anomalous connections.
Within these 8 anomalies, we can find the aforementioned OFC-striatum and fronto-cerebellar pathways,
and 5 of them involve DMN. If we take the maximum threshold $F_{ij} = 5$, 4 of these previous 8 anomalies
remain: left superior frontal gyrus (MOT) with right superior frontal gyrus (DMN), right postcentral gyrus
(MOT) with right lateral occipital cortex superior division (DMN), right occipital pole (VIS) with right
lateral occipital cortex superior division (FP), and right lateral occipital cortex superior division (DMN)
with right supramarginal gyrus anterior division (DA). Interestingly, 3 out of 4 feature the same brain
region, the right lateral occipital cortex superior division, being associated to DMN and FP functional
networks, depending on the particular node of the region.

4.3 Conclusions

In conclusion, we have collected evidence that supports further research on multi-site dataset harmonization when using functional connectivity matrices. Specifically, we have shown that the distribution of matrices in the symmetric positive-definite matrices manifold is site-biased. Moreover, we have been able to discard two adapted domain adaptation approaches and to prove that our proposal ($\mathrm{RLET}(\overline{\Sigma})$) is the most reliable one in a clinical setting. Remarkably, functional analyses of ADHD-200 data after $\mathrm{RLET}(\overline{\Sigma})$-harmonization present a high correlation with neurobiological findings in ADHD. However, intra-site bias was not removed and, to our point of view, this issue needs to be addressed, possibly by using our modification of RLET as a first approximation. It would also be valuable to use a more extended dataset for further research, and to rely on more permutations in each permutation test to increase statistical power. Nevertheless, given our results, we think there are reasons for reanalyzing functional data from multi-site datasets corresponding to other disorders, given their pervasive use in functional neuroscience.

CONFLICT OF INTEREST STATEMENT

The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

AUTHOR CONTRIBUTIONS

GS performed the study conception and design, as well as data analysis, code implementation and material and figures preparation. The first draft of the manuscript was written by GS. DP, GP and OC provided methodological guidance according to their role of master thesis' supervisors and senior authorship, and revised the manuscript.

FUNDING

This research has not been supported by any kind of funding.

ACKNOWLEDGMENTS

We thank the reviewers for their useful and constructive comments and suggestions. We also thank the publisher Frontiers for the partial publication fee waiver.

DATA AVAILABILITY STATEMENT

The code and the functional connectivity matrices used in this work, along with the p-value and frequency matrices generated after statistical experiments are available at Simeon (2021). The conversion from ROI number to anatomical location can be found along with the CC200 parcellation at Craddock (2011).

REFERENCES

[Dataset] ADHD-200 Consortium (2017). The adhd-200 sample. `https://fcon_1000.projects.nitrc.org/indi/adhd200/`, Last accessed on 2021-06-17

Alqahtani, Y., McGuire, M., Chakraborty, J., and Feng, J. H. (2019). Understanding how ADHD affects visual information processing. In *Universal Access in Human-Computer Interaction. Multimodality and Assistive Environments* (Springer International Publishing). 23–31. doi:10.1007/978-3-030-23563-5_3

Arsigny, V., Fillard, P., Pennec, X., and Ayache, N. (2005). Fast and simple calculus on tensors in the log-euclidean framework. In *Lecture Notes in Computer Science* (Springer Berlin Heidelberg). 115–122. doi:10.1007/11566465_15

Beer, J. C., Tustison, N. J., Cook, P. A., Davatzikos, C., Sheline, Y. I., Shinohara, R. T., et al. (2020). Longitudinal ComBat: A method for harmonizing longitudinal multi-scanner imaging data. *NeuroImage* 220, 117129. doi:10.1016/j.neuroimage.2020.117129

Bellec, P., Chu, C., Chouinard-Decorte, F., Benhajali, Y., Margulies, D. S., and Craddock, R. C. (2017). The neuro bureau ADHD-200 preprocessed repository. *NeuroImage* 144, 275–286. doi:10.1016/j.neuroimage.2016.06.034

Brain, D. and Webb, G. I. (2002). The need for low bias algorithms in classification learning from large data sets. In *Principles of Data Mining and Knowledge Discovery*, eds. T. Elomaa, H. Mannila, and H. Toivonen

Capotosto, P., Babiloni, C., Romani, G. L., and Corbetta, M. (2009). Frontoparietal cortex controls spatial attention through modulation of anticipatory alpha rhythms. *Journal of Neuroscience* 29, 5863–5872. doi:10.1523/jneurosci.0539-09.2009

Castellanos, F. X. and Proal, E. (2012). Large-scale brain systems in ADHD: beyond the prefrontal–striatal model. *Trends in Cognitive Sciences* 16, 17–26. doi:10.1016/j.tics.2011.11.007

[Dataset] Craddock, R. C. (2011). Athena pipeline. `https://www.nitrc.org/plugins/mwiki/index.php/neurobureau:AthenaPipeline`, Last accessed on 2021-06-20

David, S. P., Ware, J. J., Chu, I. M., Loftus, P. D., Fusar-Poli, P., Radua, J., et al. (2013). Potential reporting bias in fMRI studies of the brain. *PLoS ONE* 8, e70104. doi:10.1371/journal.pone.0070104

Dickstein, S. G., Bannon, K., Castellanos, F. X., and Milham, M. P. (2006). The neural correlates of attention deficit hyperactivity disorder: an ALE meta-analysis. *Journal of Child Psychology and Psychiatry* 47, 1051–1062. doi:10.1111/j.1469-7610.2006.01671.x

Dillo, W., Göke, A., Prox-Vagedes, V., Szycik, G. R., Roy, M., Donnerstag, F., et al. (2010). Neuronal correlates of adhd in adults with evidence for compensation strategies – a functional mri study with a go/no-go paradigm. *GMS German Medical Science; 8:Doc09; ISSN 1612-3174* doi:10.3205/000098

Dodero, L., Minh, H. Q., Biagio, M. S., Murino, V., and Sona, D. (2015). Kernel-based classification for brain connectivity graphs on the riemannian manifold of positive definite matrices. In *2015 IEEE 12th International Symposium on Biomedical Imaging (ISBI)* (IEEE). doi:10.1109/isbi.2015.7163812

Du, Y., Fu, Z., and Calhoun, V. D. (2018). Classification and prediction of brain disorders using functional connectivity: Promising but challenging. *Frontiers in Neuroscience* 12. doi:10.3389/fnins.2018.00525

Durston, S., van Belle, J., and de Zeeuw, P. (2011). Differentiating frontostriatal and fronto-cerebellar circuits in attention-deficit/hyperactivity disorder. *Biological Psychiatry* 69, 1178–1184. doi:10.1016/j.biopsych.2010.07.037

Fortin, J.-P., Cullen, N., Sheline, Y. I., Taylor, W. D., Aselcioglu, I., Cook, P. A., et al. (2018). Harmonization of cortical thickness measurements across scanners and sites. *NeuroImage* 167, 104–120. doi:10.1016/j.neuroimage.2017.11.024

Fortin, J.-P., Parker, D., Tunç, B., Watanabe, T., Elliott, M. A., Ruparel, K., et al. (2017). Harmonization of multi-site diffusion tensor imaging data. *NeuroImage* 161, 149–170. doi:10.1016/j.neuroimage.2017.08.047

Goodale, M. A. and Milner, A. (1992). Separate visual pathways for perception and action. *Trends in*
Neurosciences 15, 20–25. doi:10.1016/0166-2236(92)90344-8

Greicius, M. (2008). Resting-state functional connectivity in neuropsychiatric disorders. *Current Opinion*
in Neurology 21, 424–430. doi:10.1097/wco.0b013e328306f2c5

Johnson, W. E., Li, C., and Rabinovic, A. (2006). Adjusting batch effects in microarray expression data
using empirical bayes methods. *Biostatistics* 8, 118–127. doi:10.1093/biostatistics/kxj037

Kessler, D., Angstadt, M., Welsh, R. C., and Sripada, C. (2014). Modality-spanning deficits in attention-
deficit/hyperactivity disorder in functional networks, gray matter, and white matter. *Journal of*
Neuroscience 34, 16555–16566. doi:10.1523/jneurosci.3156-14.2014

Kim, J., Wozniak, J. R., Mueller, B. A., and Pan, W. (2015). Testing group differences in brain functional
connectivity: Using correlations or partial correlations? *Brain Connectivity* 5, 214–231. doi:10.1089/
brain.2014.0319

Low, A.-M., Vangkilde, S., le Sommer, J., Fagerlund, B., Glenthøj, B., Jepsen, J. R. M., et al. (2018).
Visual attention in adults with attention-deficit/hyperactivity disorder before and after stimulant treatment.
Psychological Medicine 49, 2617–2625. doi:10.1017/s0033291718003628

Ng, B., Dressler, M., Varoquaux, G., Poline, J. B., Greicius, M., and Thirion, B. (2014). Transport on
riemannian manifold for functional connectivity-based classification. In *Medical Image Computing*
and Computer-Assisted Intervention – MICCAI 2014 (Springer International Publishing). 405–412.
doi:10.1007/978-3-319-10470-6_51

Nichols, T. E. and Holmes, A. P. (2001). Nonparametric permutation tests for functional neuroimaging: A
primer with examples. *Human Brain Mapping* 15, 1–25. doi:10.1002/hbm.1058

Papp, S., Tombor, L., Kakuszi, B., Balogh, L., Réthelyi, J. M., Bitter, I., et al. (2020). Impaired early
information processing in adult ADHD: a high-density ERP study. *BMC Psychiatry* 20. doi:10.1186/
s12888-020-02706-w

Pennec, X. (2006). Intrinsic statistics on riemannian manifolds: Basic tools for geometric measurements.
Journal of Mathematical Imaging and Vision 25, 127–154. doi:10.1007/s10851-006-6228-4

Pennec, X., Fillard, P., and Ayache, N. (2006). A riemannian framework for tensor computing. *International*
Journal of Computer Vision 66, 41–66. doi:10.1007/s11263-005-3222-z

Roberts, M., Ashinoff, B. K., Castellanos, F. X., and Carrasco, M. (2017). When attention is intact in
adults with ADHD. *Psychonomic Bulletin & Review* 25, 1423–1434. doi:10.3758/s13423-017-1407-4

Rubia, K. (2011). "cool" inferior frontostriatal dysfunction in attention-deficit/hyperactivity disorder versus
"hot" ventromedial orbitofrontal-limbic dysfunction in conduct disorder: A review. *Biological Psychiatry*
69, e69–e87. doi:10.1016/j.biopsych.2010.09.023

Schneider, M. F., Krick, C. M., Retz, W., Hengesch, G., Retz-Junginger, P., Reith, W., et al. (2010).
Impairment of fronto-striatal and parietal cerebral networks correlates with attention deficit hyperactivity
disorder (ADHD) psychopathology in adults — a functional magnetic resonance imaging (fMRI) study.
Psychiatry Research: Neuroimaging 183, 75–84. doi:10.1016/j.pscychresns.2010.04.005

Sciberras-Lim, E. T. and Lambert, A. J. (2017). Attentional orienting and dorsal visual stream decline:
Review of behavioral and EEG studies. *Frontiers in Aging Neuroscience* 9. doi:10.3389/fnagi.2017.
00246

Shulman, G. L., Astafiev, S. V., Franke, D., Pope, D. L. W., Snyder, A. Z., McAvoy, M. P., et al. (2009).
Interaction of stimulus-driven reorienting and expectation in ventral and dorsal frontoparietal and basal
ganglia-cortical networks. *Journal of Neuroscience* 29, 4392–4407. doi:10.1523/jneurosci.5609-08.2009

Simeon, G. (2021).   Riemannian geometry of functional connectivity matrices for attention-
deficit/hyperactivity disorder data harmonization. ADHD200-derived functional connectivity matrices
for subjects in the study, results and code.
Slavakis, K., Salsabilian, S., Wack, D., Muldoon, S., Baidoo-Williams, H., Vettel, J., et al. (2017).
Riemannian-geometry-based modeling and clustering of network-wide non-stationary time series: The
brain-network case. *ArXiv [preprint]* abs/1701.07767
Smitha, K., Raja, K. A., Arun, K., Rajesh, P., Thomas, B., Kapilamoorthy, T., et al. (2017). Resting
state fMRI: A review on methods in resting state connectivity analysis and resting state networks. *The
Neuroradiology Journal* 30, 305–317. doi:10.1177/1971400917697342
van den Heuvel, M. P. and Pol, H. E. H. (2010). Exploring the brain network: A review on resting-
state fMRI functional connectivity. *European Neuropsychopharmacology* 20, 519–534. doi:10.1016/j.
euroneuro.2010.03.008
van der Maaten, L. and Hinton, G. (2008). Visualizing data using t-sne. *Journal of Machine Learning
Research* 9, 2579–2605
van Ewijk, H., Heslenfeld, D. J., Luman, M., Rommelse, N. N., Hartman, C. A., Hoekstra, P., et al. (2013).
Visuospatial working memory in ADHD patients, unaffected siblings, and healthy controls. *Journal of
Attention Disorders* 18, 369–378. doi:10.1177/1087054713482582
Vance, A., Silk, T. J., Casey, M., Rinehart, N. J., Bradshaw, J. L., Bellgrove, M. A., et al. (2007). Right
parietal dysfunction in children with attention deficit hyperactivity disorder, combined type: a functional
MRI study. *Molecular Psychiatry* 12, 826–832. doi:10.1038/sj.mp.4001999
Varoquaux, G., Baronnet, F., Kleinschmidt, A., Fillard, P., and Thirion, B. (2010). Detection of brain
functional-connectivity difference in post-stroke patients using group-level covariance modeling. In
Medical Image Computing and Computer-Assisted Intervention – MICCAI 2010 (Springer Berlin
Heidelberg). 200–208. doi:10.1007/978-3-642-15705-9_25
Vecera, S. P. and Rizzo, M. (2003). Spatial attention: normal processes and their breakdown. *Neurologic
Clinics* 21, 575–607. doi:10.1016/s0733-8619(02)00103-2
Wang, J.-B., Zheng, L.-J., Cao, Q.-J., Wang, Y.-F., Sun, L., Zang, Y.-F., et al. (2017). Inconsistency in
abnormal brain activity across cohorts of ADHD-200 in children with attention deficit hyperactivity
disorder. *Frontiers in Neuroscience* 11. doi:10.3389/fnins.2017.00320
Yair, O., Ben-Chen, M., and Talmon, R. (2019). Parallel transport on the cone manifold of SPD matrices
for domain adaptation. *IEEE Transactions on Signal Processing* 67, 1797–1811. doi:10.1109/tsp.2019.
2894801
Yeo, B. T. T., Krienen, F. M., Sepulcre, J., Sabuncu, M. R., Lashkari, D., Hollinshead, M., et al. (2011).
The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *Journal of
Neurophysiology* 106, 1125–1165. doi:10.1152/jn.00338.2011
You, K. and Park, H.-J. (2021). Re-visiting riemannian geometry of symmetric positive definite matrices
for the analysis of functional connectivity. *NeuroImage* 225, 117464. doi:10.1016/j.neuroimage.2020.
117464
Yu, M., Linn, K. A., Cook, P. A., Phillips, M. L., McInnis, M., Fava, M., et al. (2018). Statistical
harmonization corrects site effects in functional connectivity measurements from multi-site fMRI data.
Human Brain Mapping 39, 4213–4227. doi:10.1002/hbm.24241

ANNEX

Equivalence between parallel transport and matrix whitening

In general, matrix whitening and parallel transport using $\overline{\Sigma}$ as the reference point are different transformations. However, we show here that under the condition $\left[\overline{\Sigma}, \overline{\Sigma}^{(k)}\right] = 0$, $\forall k$, both frameworks are equivalent. To this aim, consider the following property regarding the unique positive-definite square root of the product of two $n \times n$ SPD matrices:

Property: Let A and B be two $n \times n$ SPD matrices that commute, i.e., $[A, B] \equiv AB - BA = 0$. Then $(AB)^{\frac{1}{2}} = A^{\frac{1}{2}}B^{\frac{1}{2}}$.

Proof: Considering that the unique SPD square root of some SPD matrix X can be computed as $X^{\frac{1}{2}} = \mathrm{Exp}(\frac{1}{2}\mathrm{Log}(X))$, and taking into account that, given two SPD matrices A and B such that $[A, B] = 0$, $\mathrm{Exp}(A + B) = \mathrm{Exp}(A)\mathrm{Exp}(B)$ and $\mathrm{Log}(AB) = \mathrm{Log}(A) + \mathrm{Log}(B)$:

$$
\begin{aligned}
(AB)^{\frac{1}{2}} &= \mathrm{Exp}(\frac{1}{2}\mathrm{Log}(AB)) = \mathrm{Exp}(\frac{1}{2}(\mathrm{Log}(A) + \mathrm{Log}(B))) = \\
&= \mathrm{Exp}(\frac{1}{2}\mathrm{Log}(A))\mathrm{Exp}(\frac{1}{2}\mathrm{Log}(B)) = A^{\frac{1}{2}}B^{\frac{1}{2}} \quad \square
\end{aligned}
\tag{17}
$$

Now, recall that the overall parallel transport transformation (including the last matrix whitening step) when using as the reference point Σ_0 the global mean $\overline{\Sigma}$ (Yair et al., 2019) is (subsection 2.4.2):

$$
\Sigma_i^{(k)} \to \overline{\Sigma}^{-1/2} \left(\overline{\Sigma}\left(\overline{\Sigma}^{(k)}\right)^{-1}\right)^{1/2} \Sigma_i^{(k)} \left(\left(\overline{\Sigma}\left(\overline{\Sigma}^{(k)}\right)^{-1}\right)^{1/2}\right)^T \overline{\Sigma}^{-1/2}.
\tag{18}
$$

Supposing that $\overline{\Sigma}$ and $\left(\overline{\Sigma}^{(k)}\right)^{-1}$ commute, by virtue of the previously stated property and taking into account that given two matrices A and B, $(AB)^T = B^T A^T$:

$$
\begin{aligned}
\Sigma_i^{(k)} \to{}& \overline{\Sigma}^{-1/2} \left(\overline{\Sigma}\left(\overline{\Sigma}^{(k)}\right)^{-1}\right)^{1/2} \Sigma_i^{(k)} \left(\left(\overline{\Sigma}\left(\overline{\Sigma}^{(k)}\right)^{-1}\right)^{1/2}\right)^T \overline{\Sigma}^{-1/2} = \\
={}& \overline{\Sigma}^{-1/2}\,\overline{\Sigma}^{1/2} \left(\left(\overline{\Sigma}^{(k)}\right)^{-1}\right)^{1/2} \Sigma_i^{(k)} \left(\left(\left(\overline{\Sigma}^{(k)}\right)^{-1}\right)^{1/2}\right)^T \left(\overline{\Sigma}^{1/2}\right)^T \overline{\Sigma}^{-1/2} = \\
={}& \overline{\Sigma}^{-1/2}\,\overline{\Sigma}^{1/2} \left(\overline{\Sigma}^{(k)}\right)^{-1/2} \Sigma_i^{(k)} \left(\overline{\Sigma}^{(k)}\right)^{-1/2} \overline{\Sigma}^{1/2}\,\overline{\Sigma}^{-1/2} = \\
={}& \left(\overline{\Sigma}^{(k)}\right)^{-1/2} \Sigma_i^{(k)} \left(\overline{\Sigma}^{(k)}\right)^{-1/2},
\end{aligned}
\tag{19}
$$

where in the second step we have used the facts that for a SPD matrix A, we take $A^{1/2}$ to be also SPD and thus satisfies $\left(A^{1/2}\right)^T = A^{1/2}$, along with $\left((A)^{-1}\right)^{1/2} = (A)^{-1/2}$, with $(A)^{-1/2}$ also SPD, and then, $\left((A)^{-1/2}\right)^T = (A)^{-1/2}$. One can conclude that under vanishing commutators $\left[\overline{\Sigma}, \left(\overline{\Sigma}^{(k)}\right)^{-1}\right]$, the transformation reduces to matrix whitening. Since $\overline{\Sigma}$ and $\left(\overline{\Sigma}^{(k)}\right)^{-1}$ belong to $GL(n)$, the requirement $\left[\overline{\Sigma}, \left(\overline{\Sigma}^{(k)}\right)^{-1}\right] = 0$ is equivalent to $\left[\overline{\Sigma}, \overline{\Sigma}^{(k)}\right] = 0$. Therefore, when site means $\overline{\Sigma}^{(k)}$ commute with the global mean $\overline{\Sigma}$, parallel transport and matrix whitening represent equivalent frameworks.

Properties of Rigid Log-Euclidean Translation

859   As mentioned in the description of Rigid Log-Euclidean Translation in subsection 2.4.3, the
860   transformation preserves intra-site geodesic distances under the LERM framework and displaces the
861   matrices in such a way that their transformed site mean $\tilde{\overline{\Sigma}}^{(k)}$ is the global mean $\overline{\Sigma}$, for all sites k.

862   By using the definition of LERM geodesic distance (7) for matrices belonging to the same site k and
863   modified according to RLET($\overline{\Sigma}$) transformation (14) one finds

$$
\begin{aligned}
d(\tilde{\Sigma}_i^{(k)}, \tilde{\Sigma}_j^{(k)}) &= \\
&= ||\mathrm{Log}(\tilde{\Sigma}_i^{(k)}) - \mathrm{Log}(\tilde{\Sigma}_j^{(k)})||_F = \\
&= ||\mathrm{Log}(\overline{\Sigma}) + \mathrm{Log}(\Sigma_i^{(k)}) - \mathrm{Log}(\overline{\Sigma}^{(k)}) - \mathrm{Log}(\overline{\Sigma}) - \mathrm{Log}(\Sigma_j^{(k)}) + \mathrm{Log}(\overline{\Sigma}^{(k)})||_F = \\
&= ||\mathrm{Log}(\Sigma_i^{(k)}) - \mathrm{Log}(\Sigma_j^{(k)})||_F = d(\Sigma_i^{(k)}, \Sigma_j^{(k)}),
\end{aligned}
\tag{20}
$$

864   meaning that intra-site geodesic distances are preserved as expected.

865   It is also straightforward to prove that $\tilde{\overline{\Sigma}}^{(k)} = \overline{\Sigma}, \, \forall \, k$. Considering the definition of site mean (12) for
866   matrices transformed according to (14):

$$
\begin{aligned}
\mathrm{Log}(\tilde{\overline{\Sigma}}^{(k)}) &= \frac{1}{N^{(k)}} \sum_{i \in (k)} \mathrm{Log}(\tilde{\Sigma}_i^{(k)}) = \\
&= \frac{1}{N^{(k)}} \left(\sum_{i \in (k)} \left(\mathrm{Log}(\overline{\Sigma}) + \mathrm{Log}(\Sigma_i^{(k)}) - \mathrm{Log}(\overline{\Sigma}^{(k)}) \right) \right) = \\
&= \frac{1}{N^{(k)}} \left(N^{(k)} \mathrm{Log}(\overline{\Sigma}) - N^{(k)} \mathrm{Log}(\overline{\Sigma}^{(k)}) \right) + \frac{1}{N^{(k)}} \sum_{i \in (k)} \mathrm{Log}(\Sigma_i^{(k)}) = \\
&= \mathrm{Log}(\overline{\Sigma}) - \mathrm{Log}(\overline{\Sigma}^{(k)}) + \mathrm{Log}(\overline{\Sigma}^{(k)}) = \mathrm{Log}(\overline{\Sigma}),
\end{aligned}
\tag{21}
$$

867   and therefore site means become the global mean $\overline{\Sigma}$. In the case where the term $\mathrm{Log}(\overline{\Sigma})$ is removed from
868   the transformation rule (14), one gets $\mathrm{Log}(\tilde{\overline{\Sigma}}^{(k)}) = 0 = \mathrm{Log}(I)$, and site means become the identity matrix
869   I.

TABLES

Table 1. Number of detected anomalies using original matrices, harmonized matrices under Rigid Log-Euclidean Translation (RLET) to the global mean $\overline{\Sigma}$, harmonized matrices under RLET to the identity matrix I, and harmonized matrices under matrix whitening, according to the chosen frequency threshold. Sensitivities are found between parentheses.

Threshold	Original	RLET($\overline{\Sigma}$)	RLET(I)	MW
$F_{ij} \geq 1$	2019	2125	1753	2274
$F_{ij} \geq 2$	188 (9.31%)	213 (10.02%)	154 (8.78%)	262 (11.52%)
$F_{ij} \geq 3$	21 (1.04%)	33 (1.55%)	14 (0.80%)	52 (2.3%)
$F_{ij} \geq 4$	2 (0.10%)	8 (0.38%)	1 (0.06%)	9 (0.40%)
$F_{ij} \geq 5$	0 (0%)	4 (0.19%)	1 (0.06%)	1 (0.04%)

FIGURES

Figure 1. Pair-wise distances between functional connectivity matrices from different sites (KKI: Kennedy Krieger Institute, Johns Hopkins University; NYU: New York University Child Study Center; PKG: Peking University; NIM: NeuroIMAGE sample). **(A)** Pair-wise affine-invariant Riemannian metric (AIRM) distances for non-transformed matrices. **(B)** Pair-wise Log-Euclidean Riemannian metric (LERM) distances for non-transformed matrices. **(C)** Pair-wise AIRM distances after matrix whitening. **(D)** Pair-wise LERM distances after Rigid Log-Euclidean Translation (RLET) to the global mean $\overline{\Sigma}$. **(E)** Pair-wise AIRM distances after parallel transport. **(F)** Pair-wise LERM distances after RLET to the identity matrix.

Figure 2. Commutators of the global mean $\overline{\overline{\Sigma}}$ and original site Fréchet means $\{\overline{\Sigma}^{(k)}\}$. **(A)** $\left[\overline{\overline{\Sigma}}, \overline{\Sigma}^{(\text{KKI})}\right]$; **(B)** $\left[\overline{\overline{\Sigma}}, \overline{\Sigma}^{(\text{NYU})}\right]$; **(C)** $\left[\overline{\overline{\Sigma}}, \overline{\Sigma}^{(\text{PKG})}\right]$; **(D)** $\left[\overline{\overline{\Sigma}}, \overline{\Sigma}^{(\text{NIM})}\right]$. (KKI: Kennedy Krieger Institute, Johns Hopkins University; NYU: New York University Child Study Center; PKG: Peking University; NIM: NeuroIMAGE sample).

Figure 3. Two-dimensional embedding obtained after applying t-stochastic neighbour embedding to the logarithms of non-harmonized matrices. (KKI: Kennedy Krieger Institute, Johns Hopkins University; NYU: New York University Child Study Center; PKG: Peking University; NIM: NeuroIMAGE sample).

Figure 4. **(A)** Two-dimensional embedding obtained after applying t-stochastic neighbour embedding to the logarithms of matrices transformed under matrix whitening. **(B)** Two-dimensional embedding obtained after applying t-stochastic neighbour embedding to the logarithms of matrices transformed under Rigid Log-Euclidean Translation to the global mean $\overline{\Sigma}$. (KKI: Kennedy Krieger Institute, Johns Hopkins University; NYU: New York University Child Study Center; PKG: Peking University; NIM: NeuroIMAGE sample).

Figure 5. **(A)** Difference in pair-wise AIRM distances between original matrices and matrices transformed under matrix whitening. **(B)** Difference in pair-wise LERM distances between original matrices and matrices transformed under Rigid Log-Euclidean Translation (RLET). **(C)** Pair-wise AIRM distances between site Fréchet means $\{\overline{\overline{\Sigma}}^{(k)}\}$ and the global mean $\overline{\overline{\Sigma}}$. **(D)** Pair-wise LERM distances between site Fréchet means $\overline{\overline{\Sigma}}^{(k)}$ and the global mean $\overline{\overline{\Sigma}}$. **(E)** Pair-wise AIRM distances between site Fréchet means computed after matrix whitening and the identity matrix I. **(F)** Pair-wise LERM distances between site Fréchet means computed after RLET($\overline{\overline{\Sigma}}$) and the global mean $\overline{\overline{\Sigma}}$. (KKI: Kennedy Krieger Institute, Johns Hopkins University; NYU: New York University Child Study Center; PKG: Peking University; NIM: NeuroIMAGE sample).

Figure 6. Frequency matrices F_{ij} obtained by performing 100 permutation experiments with the same randomly pooled subjects, binarizing each experiment's p-value matrix at $p < 0.001$, and summing these resulting matrices for: **(A)** original functional connectivity (FC) matrices; **(B)** FC matrices transformed under matrix whitening; **(C)** FC matrices transformed under Rigid Log-Euclidean Translation (RLET) to the global mean $\overline{\Sigma}$; **(D)** FC matrices transformed under RLET to the identity matrix.

Figure 7. Anomaly distribution plots according to the involved functional components obtained as described in subsection 3.4 using: **(A)** original matrices; **(B)** matrices transformed under Rigid Log-Euclidean Translation (RLET) to the global mean $\overline{\Sigma}$; **(C)** matrices transformed under matrix whitening; **(D)** matrices transformed under RLET to the identity matrix. (VIS: visual network; MOT: sensorimotor network; DA: dorsal attention network; VA: ventral attention network; FP: frontoparietal network; LIM: limbic network; DMN: default mode network; BS: brain stem; CRB: cerebellum; BG: basal ganglia).

Figure 8. Binarized entry-wise absolute differences greater than 15% between plots in Figure 6 for: **(A)** original (non-harmonized) matrices and matrices harmonized under Rigid Log-Euclidean Translation (RLET) to the global mean $\overline{\Sigma}$; **(B)** RLET to $\overline{\Sigma}$ and RLET to the identity matrix I harmonization approaches; **(C)** matrix whitening and RLET to I harmonized matrices. (VIS: visual network; MOT: sensorimotor network; DA: dorsal attention network; VA: ventral attention network; FP: frontoparietal network; LIM: limbic network; DMN: default mode network; BS: brain stem; CRB: cerebellum; BG: basal ganglia).

Figure 9. Anomalous connections obtained by thresholding the frequency matrix for non-harmonized matrices at $F_{ij} \geq 3$. In total, the 21 anomalous connections are displayed. Notice the lack of anomalies involving the posterior parietal cortex and the cerebellum.

Figure 10. Anomalous connections obtained by thresholding the frequency matrix for matrices harmonized under Rigid Log-Euclidean Translation to the global mean $\overline{\Sigma}$ at $F_{ij} \geq 3$. The 33 detected anomalies are displayed.

Figure 11. Relative contribution of functional components to the total number of detected anomalies by thresholding frequency matrices at $F_{ij} \geq 2$ and $F_{ij} \geq 3$ corresponding to: **(A)** the non-harmonization approach; **(B)** harmonization under Rigid Log-Euclidean Translation to the global mean $\overline{\Sigma}$. (VIS: visual network; MOT: sensorimotor network; DA: dorsal attention network; VA: ventral attention network; FP: frontoparietal network; LIM: limbic network; DMN: default mode network; BS: brain stem; CRB: cerebellum; BG: basal ganglia).