Main Manuscript for

Ear pinnae in a neotropical katydid (Orthoptera: Tettigoniidae) function as ultrasound

guides for bat detection

Christian Pulver[a], Emine Celiker[a,1], Charlie Woodrow[a], Inga Geipel[b,c,d], Carl Soulsbury[a], Darron A.
Cullen[a], Stephen M Rogers[a], Daniel Veitch[a] & Fernando Montealegre-Z[a,1]

[a]University of Lincoln, School of Life Sciences, Joseph Banks Laboratories, Green Lane, Lincoln,
UK, LN6 7DL

[b]Smithsonian Tropical Research Institute, Apartado 0843-03092, Balboa, Panama

[c]CoSys Lab, Faculty of Applied Engineering, University of Antwerp, 2020 Antwerpen, Belgium

[d]Flanders Make Strategic Research Centre, 3920 Lommel, Belgium

[1]Fernando Montealegre-Z, Emine Celiker

Email: fmontealegrez@lincoln.ac.uk, eceliker@lincoln.ac.uk

Author Contributions: All authors were involved in writing and revision of the manuscript. CP
and FM-Z performed acoustic experiments on live specimens. CP and CW designed and
performed all 3D print model experiments. CP constructed the speaker mount, automated the
controls in the arena, collected and analysed data. CS designed the statistical model and
completed statistical analyses. EC developed and performed all numerical models and
simulations. CW illustrated figures, conducted μ-CT scans, performed all post-image
segmentation for numerical analyses, and conducted 3D printing. IG and FM-Z recorded insect
and bat acoustic signals. FM-Z and DAC performed behavioural audiograms. DAC, CW and SMR
performed and analysed neurophysiological audiograms. FM-Z and CP conceived the idea for
the project. FM-Z led the lab, assisted with idea development, and provided equipment training.

Competing Interest Statement: No competing interests declared.

Classification: Biological Sciences: Biophysics and Computational Biology

Keywords: bushcricket, bioacoustics, ultrasound hearing, 3D printing, bat predation

This PDF file includes:

Main Text
Figures 1 to 6

Abstract

Early predator detection is a key component of the predator-prey arms race, and has driven the

evolution of multiple animal hearing systems. Katydids (Insecta) have sophisticated ears, each

consisting of paired tympana on each foreleg that receive sound directly externally, and internally

via a narrowing ear canal through the acoustic spiracle on the prothorax. These ears are

pressure-time difference receivers capable of sensitive and accurate directional hearing across a

wide frequency range, despite the small size of katydids. Many katydid species have cuticular

pinnae which form cavities around the outer tympanal surfaces, but their function is unknown. We

investigated pinnal function in the katydid *Copiphora gorgonensis* by combining experimental

biophysics and numerical modelling using 3D ear geometries. Results show that the pinnae in *C.*

gorgonensis do not assist in directional hearing for specific call frequencies, but instead pinnae

act as ultrasound detector devices, that complement the limited broadband-filtering range

achieved by the ear canal (< 60 kHz). Pinnae induced large sound pressure gains that enhanced

sound detection at high ultrasonic frequencies (> 60 kHz), matching the echolocation range of co-

occurring insectivorous bats. Comparing pinnal mechanics of sympatric katydid species (of other

subfamilies) supports these findings, and suggests that pinnae evolved in katydids primarily for

enhanced predator detection. Audiograms (both behavioural and neural) and tympanal cavity

resonances obtained from living specimens corroborate our findings. The complementary results

demonstrate the feasibility of multimodal approaches to investigate complex and difficult to

access hearing systems.

Significance Statement
Ear pinnae in mammals usually function in the first step of hearing – sound capture – and funnel

vibrations through the ear canal (EC) to the tympanum. Unlike mammals, katydid ears are located

in the legs and exhibit two tympanal membranes per ear, which receive sound externally and

internally via an EC. In many species, tympana are covered with cuticular flaps (pinnae), but their

function are unknown. We show that while the EC processes frequencies below 60 kHz, the

pinnae induce pressure gains at frequencies of the call of their common bat predators > 60 kHz,

providing additional breadth for frequency range. Directionality and the unusual broad frequency

response make these ears unique models for bioinspired sensors.

62
63   **Main Text**
64
65   **Introduction**
66
Throughout the animal kingdom, the need to localize sound signals, both to detect conspecifics

and to avoid predation, is a major selection pressure. As a result, vastly different species have

convergently evolved mechanisms of hearing to fulfil similar functions (1–3), and hearing organs

have evolved in closely related taxonomic groups many times independently (1, 4). To determine

the location of a sound source, an animal with two ears will utilize interaural time and amplitude

differences. Such binaural auditory systems must satisfy three requirements to function: 1) the

distance between each ear must be sufficient to produce recognisable differences in sound arrival

time, 2) the ears must be separated by a body which is large enough to attenuate sound between

them, 3) the ears must be neurologically coupled in order to calculate time and amplitude

differences (5, 6). However, small animals, such as insects, are too small to exploit diffractive

effects of sound on their bodies to perceive minute differences in sound delays and intensities (7).

Katydids (Orthoptera: Tettigoniidae), a family with ~8,000 species (8) , have overcome this

problem by evolving independently functioning ears in their forelegs (9), thereby increasing the

interaural distance. Many species have also evolved the ability to produce and detect ultrasonic

frequencies (10), meaning that the resulting distance between the ears provides sufficient spatial

separation to exceed the shorter wavelengths of incoming conspecific sounds (2). Each ear

receives sound directly at the external tympanal surface, but also internally in a process similar to

that of the mammalian ear. In this internal process, sound enters an air-filled ear canal (EC, also

called the acoustic trachea) through a specialised opening in the prothorax known as the acoustic

spiracle (11). The EC's narrowing, exponential horn shape amplifies the sound signals (12–14)

and reduces propagation velocity (12, 14, 15), and leads this decelerated sound signal through

the thorax and foreleg to the internal tympanal surface. The combined internal and external inputs

means that the tettigoniid ear functions as a pressure – time difference receiver (2, 7, 12), unlike

the mammalian ear which functions as a single input pressure receiver via the EC.

At the external auditory input, some tettigoniids possess cuticular pinnae (also referred to as

folds, flaps or tympanal covers) partially enclosing their tympana (Fig. 1*A-C*). The role(s) of these

pinnae are unclear. Early observations by Autrum suggested that pinnae aid the insect to

determine the direction of sound, effectively acting as a sound guide (16, 17). The prominence of

cuticular pinnae present in a variety of Pseudophyllinae and Conocephalinae species (see

examples in the *SI Appendix*, Fig. S1*A* and S1*C-K*) generated more interest in these

observations. Morphologies of cuticular pinnae vary greatly between species, and were originally

categorized in a phylogenetic context (9). A dual functioning auditory system in the tettigoniid

Mygalopsis marki was proposed to explain differences in the auditory morphologies in spiracle

size and tympanal pinnae in which the external tympanal ports appear to function as

omnidirectional receivers and the EC combined with the spiracle operate as a highly sensitive

non-directional receiver (18). These findings were corroborated in *Hemisaga* sp. where an

increased acoustic sensitivity at the external tympanal port (through blocking the entrances or

slits) was demonstrated (19). A dual channel system consisting of the EC and spiracle serve for

the detection of predators, whilst the external tympanal ports are used for detecting conspecific

communication signals (19). Studies of ultrasonic rainforest Pseudophyllinae provided more

evidence of principal sound reception for conspecific communication using the external tympanal

port as a consequence of exceptionally small spiracle sizes (20). It was reported that diffraction of

very short wavelengths along the tympanal slits contributed to directional orientation in rainforest

katydids (20).

Before experimental evidence of the dual port system in katydids was published (14, 15),

attention was given to the EC as the main port for sound capture (21–25). Moreover, it has been

argued that the size of the ear is considerably smaller than the wavelengths of most carrier

frequencies of described insects known at the time, and therefore the sound pressure field

around the ear would be constant and yield no directional cues (23). In other words, sound

accessing the external tympanal port is not related to the direction of incidence, and tympanal

pinnae are merely protective features sheltering the fragile tympanum. However, recent research

showed that quieter, low amplitude sound waves acting on the external tympanal membrane

(without gain from the EC) of the katydid *Copiphora gorgonensis* (Tettigoniidae: Copiphorini) do

cause vibrations of significant amplitude in the inner ear (26). Therefore, even these very weak

vibrations are mechanically transduced. The external sound arrives 60-80 µs before its amplified

form of self on the internal tympanal surface via the EC, and this significant phase delay forms

the basis of the pressure – time difference receiver definition (12, 15). In katydids with cuticular

pinnae surrounding the tympana, evidence suggests that the insect can use both ports, but how

the external port contributes to directionality remains unknown (27).

Here, we investigate the role of cuticular pinnae using the neotropical katydid *Copiphora*

gorgonensis, a species endemic to Gorgona, an island in the Pacific Ocean off the western coast

of Colombia (28). Males of this species produce a pure-tone song a 23 kHz to attract females.

Copiphora gorgonensis has become a model species for hearing studies due to the transparency

of the cuticle which facilitates non-invasive, real-time measurements of the inner ear (26, 29). We

integrated experimental biophysical measurements based on micro–scanning laser Doppler

vibrometry (LDV) and micro-computed tomography (µ-CT) to simulate the function of the cuticular

pinnae and how they contribute to auditory orientation in this katydid. The pairing of these

approaches were applied to 3-dimensional (3D) print models of the ear, and scaled experiments

were performed to validate the simulations. We investigated if: 1) the direction of incidence of the

sound stimulus, presented by a loudspeaker, is a function of the sound wave directly accessing

the tympana through the slits; 2) the tympanal cavities produce sound pressure gains that act

externally on the tympana; 3) tuning properties of the pinnal cavities are a result of pinnal

geometry and can be predicted by the volume and/or entrance size of the cavity.

Based on Autrum's original observations, we hypothesized that tympanal pinnae function as

ultrasonic guides by pinnae forming exceptionally small resonant cavities. Further, we

hypothesized that these cavities act as Helmholtz-like resonators able to capture and amplify

diminishing ultra-high frequency sound waves.

148
149
150 **Results**
151
We investigated the role of tympanal pinnae in sound capture by testing how the direction of

incidence of the sound stimulus presented by the loudspeaker induced tympanal displacements

at three frequencies (23, 40 and 60 kHz) with the cuticular pinnae intact and later ablated.

Frequencies above 60 kHz were not tested provided the acoustic limitations of the experimental

platform and the poor performance of the probe speaker at high ultrasounds (see *Materials and*

Methods). A total of 2,736 measurements were performed on 13 ears (1,512 measurements for

four male specimens; 1,224 for three female specimens). For time of sound arrival, we found a

significant interaction between the presence of cuticular pinnae with angle of incidence (21°

azimuth frontal to ear; Fig. 2*A*) and with frequency (*SI Appendix*, Table S1). Post hoc analysis

showed that the presence of pinnae significantly delayed the time of arrival to ipsilateral tympana

at 23 kHz (t-ratio = -11.15, $P < 0.001$) and 40 kHz (t-ratio = -7.43, $P < 0.001$), but not at 60 kHz (t-

ratio = -1.86, $P = 0.063$). The effect of tympanum (anterior or posterior) on time of arrival and

displacement amplitudes was found to be significant with the PTM exhibiting slightly longer arrival

times (~ 2 µs) but a 21.5% lower mean displacement amplitude (and 2*B* ; *SI Appendix*, Table S1).

For displacement amplitude, there was a significant interaction between the presence of pinnae

and frequency (*SI Appendix*, Table S1). Post hoc analysis showed greatest displacement

amplitudes at 23 kHz with the pinnae ablated (t-ratio = 3.20, $P < 0.001$; Fig. 2*B*). This

demonstrates that pinnae do not enhance auditory perception of the carrier frequency in *C.*

gorgonensis, and that the tympanum achieves this displacement by resonance (see (15, 29)).

There were no differences in displacement at either 40 kHz (t-ratio = 0.84, $P = 0.399$; Fig. 2*B*)

and 60 kHz (t-ratio = -0.61, $P=0.540$; Fig. 2*B*) regardless of pinnal condition. We also found a

significant interaction between the presence of cuticular pinnae with angle of incidence, showing

the impact of pinnae in increasing arrival time as the sound source rotates opposite the ear (*SI*

Appendix, Table S1). Responses were strongest for sound presented perpendicular to each

respective slit cavity (average 3.08 ± 2.91 nm at 10°, average 2.90 ± 2.98 nm at -9°) with the

lowest displacement amplitudes occurring when sound was directed at the region of the dorsal

cuticle bifurcating the cavities, also referred as "point zero", showing (average 1.99 ± 1.90 nm at -

1°) with the pinnae intact due to cuticle obstructing the response of the tympanal membrane. In

contrast, point zero and adjacent angles showed the greatest displacement amplitude with the

pinnae ablated (average 3.04 ± 3.42 nm at -1°) with incident angles on either side of point zero

showing a gradual subdued response to the stimulus (average 2.73 ± 3.27 nm at 10°, average

2.54 ± 2.57 nm at -10°).

Phase angle (φ°) was calculated from the absolute value of the difference between the vibrations

of the ATM and PTM per recording (1,532 in total). Pinnae maintained mean $\Delta\,\varphi$° at 80.9° for 23

kHz, 88.8° for 40 kHz, and 84.1° for 60 kHz, but with the pinnae ablated, phase differences were

smaller particularly at 60 kHz ($\Delta\,\varphi$° at 62.7° for 23 kHz, 78.7° for 40 kHz, and 49° for 60 kHz).

Anatomical measurements of the external tympanal port

The anatomical features of the ear were measured to predict resonance and compare

intraspecific variation in pinnal size (*SI Appendix*, Table S2). 2D measurements of the area of the

pinnal opening (slit), distance between the centre of the ear (septum) and edge of the pinna

(pinnal protrusion), and distance between slits (septum width) were studied using an Alicona

Infinite Focus microscope. 3D measurements of the cavities and cross section of the ears were

performed with the µ-CT scanner using the software Amira-Aviso 6.7 (n = 8 ears; 3 females and 2

males). We found that the average size of the slits (0.16 ± 0.01 mm^2) and cavities (0.14 ± 0.01

mm^3) were nearly identical between the ATM and PTM. The pinnal protrusion length showed that

the PTM pinnae (0.44 ± 0.03 mm) were wider than the ATM (0.39 ± 0.02 mm). The mean cross-

sectional width of the ear was 1.14 ± 0.35 mm.

Tympanal cavity resonance calculations

We used the 2D (slit area) and 3D measurements (cavity volume) to estimate resonance of the

tympanal cavities (*SI Appendix*, Table S2). This was calculated with the assumption that the slit

openings are a perfect circle (to determine radius) and the cavity acts as a cylindrical tube using a

neckless Helmholtz resonance equation. Here, c is speed of sound in air (343 m s^{-1}), cross-

sectional area of the opening with radius r, 1.85 is the correction length of the neck and V

denotes the volume of the resonator/cavity (30).

$$f(h) = \frac{c}{2\pi}\sqrt{\frac{1.85r}{V}}$$

210   The pinnal cavities (n = 8) showed a neckless Helmholtz resonance of 94.28 ± 3.53 kHz for the

211   ATM and 91.69 ± 3.93 kHz for the PTM. These calculations suggest that the pinnae cavity does

212   not resonate at the specific calling song frequency of *C. gorgonensis*.

3D printed model time and frequency domain measurements of pinnal cavities

3D printed model time and frequency domain measurements of pinnal cavities

3D printed scaled models of the ear were used to measure sound pressure gains and

resonances, to overcome the problem of experimental limitations imposed by the small size of the

specimens and ears. 3D ears ($n = 8$; 1 male and 1 female ± pinnae) were printed at a scale of

1:11.43 and the acoustic stimuli was scaled by the same factor for pure tones (2.01 kHz for 23

kHz, 3.50 kHz for 40 kHz, 5.25 kHz for 60 kHz, and 9.63 kHz for 110 kHz) and for broadband (2

to 15 kHz for 11.5 to 170 kHz). The interaction between pinnae and frequency significantly

affected sound pressure (dB), whilst tympanum (ATM or PTM) did not (*SI Appendix*, Table S1).

Across all frequencies, the presence of pinnae increased sound pressure, but differences were

greatest at higher frequencies (23 kHz: t-ratio = -2.54, $P = 0.014$; 40 kHz: t-ratio = -8.69, $P <$

0.001; 60 kHz t-ratio = -15.66, $P < 0.001$; 110 kHz t-ratio = 41.70, $P < 0.001$; Fig. 3*A*), the

greatest pressure gains were detected at 101.47± 3.43 kHz for both the ATM (26.33 ± 4.06 dB)

and PTM (30.04 ± 1.34 dB) with the pinnae intact. With the pinnae ablated, the greatest pressure

gain was found to be at 101.41 ± 0.86 kHz for both the ATM (9.69 ± 0.87 dB) and PTM (9.83 ±

0.97 dB).

229
Numerical results

Numerical results

Using real 3D geometries of each experimental ear ($n = 17$ ears; 8 with pinnae, 9 with pinnae

ablated), we used Finite Element Analysis (FEA) to simulate sound pressure gains and the effect

of incident angle at frequencies exceeding the experimental limitations on living specimens (see

Materials and Methods). For sound pressure measurements there was a significant interaction

between the presence of pinnae and frequency (*SI Appendix*, Table S1). At 23 kHz ears without

pinnae had significantly higher sound pressures (t-ratio = 3.45, $P < 0.001$), but the effect was

reversed at 40 kHz (t-ratio = -5.94, $P < 0.001$) and 60 kHz (t-ratio = -28.52, $P < 0.001$), with

differences increasing as frequency increased (Fig. 2*C*). There was no effect of angle of sound

incidence (-10°, -5°, 0°, 5°, 10°) or tympanum on sound pressures (*SI Appendix*, Table S1).

Simulated sound pressure gains (Figs. 4*C* and 4*D*), and their distribution maps (Fig. 4*A* and 4*B*)

showed the greatest sound pressure gain at a mean value of 118 kHz (ATM 121 kHz, PTM 115

kHz), and such gains were reduced or lost entirely when the pinnae were removed (*SI Appendix*,

Table S1; Fig. 4*D*).

The effects of angle, pinnae, tympanum, interaction of angle and pinnae, and the interaction of

pinnae and frequency were not significant on arrival times. However, frequency was a significant

factor on arrival times (23 vs. 40 kHz: t-ratio = 30.739, $P < 0.001$; 23 vs. 60 kHz: t-ratio = 45.857,

$P < 0.001$; 40 vs. 60 kHz: t-ratio = 15.117, $P < 0.001$).

250
Tympanal and behavioral response to broadband stimulation
For broad tympanal responses, we exposed seven specimens with intact pinnae to broadband
periodic chirp stimulation in the range 20 to 120 kHz in a free sound field and recorded the
vibration of both ATM and PTM, of the two ears using a micro-scanning laser Doppler vibrometer.
There was a relatively stable response (measured as velocity per sound pressure) of the
tympanal membranes between 20 to 70 kHz. However, above 80 kHz the tympana response
increased dramatically with resonant peaks at 107.84 ± 3.74 kHz for the PTM and 111.13 ± 4.24
kHz for the ATM (Fig. 5*A*).
259
260 Behavioural audiograms of startle behaviour were obtained from nine tethered females walking
261 on a treadmill. Audiograms were obtained with stimuli in the range 20 to 120 kHz. Audiograms
262 show that the startle response of females decline sharply for stimuli between 20 kHz and 35 kHz,
263 however, response remains essentially constant at higher frequencies over the entire tested
264 frequency range (*SI Appendix*, Table S3; Fig. 5*B*).
265
Neural audiograms
Auditory stimulation (the coloured mesh Fig. 5*C*) produced significantly greater responses in the
neural audiogram recordings compared to neuronal activity during silent periods (grey mesh Fig.
5*C*) for most combinations of sound frequency and intensity (white symbol Fig. 5*C*). Only a small
number of the stimuli failed to produce a significant difference in neuronal response, which
occurred when frequency was high and sound pressures low (Fig. 5*C* black symbols). Within this
region, responses to 100 kHz pulses were resolvable against background activity even for the
quietest sound pressures (46 dB SPL).
274
Amplitudes of response increased almost linearly with sound pressure intensity across the
frequency range. The largest responses were seen at the calling song frequency (23 kHz) across
the sound pressure intensity range: at 46 dB the response was 51.4 ± 21.8 µVs, 35.6% greater
than the activity during silence. At 70 dB SPL the response rose to 62.7 ± 15.8 µVs during
stimulation, which was 86.1% higher than the equivalent off response, and rose further to 65.8 ±
14 µVs, (132.2% greater than the off response) at 94 dB SPL.
281
There was generally a gradual falling away of responsiveness as stimulus frequency increased
above 23 kHz: at 70 dB SPL, the response to 40 kHz stimulation was 51.8 ± 12.2 µVs; the
response to 60 kHz 49.1 ± 14.1 and to 80 kHz stimulation 44.5 ± 12.3 µVs, but measured
responses to sound were still substantially above background activity. For example, at 100 kHz,

the response of 47.5 ± 12.7 µVs was 43% greater than background activity. The weakest set of

responses was to 120 kHz, which were not statistically distinguishable from the background until

above 70 dB SPL, but nevertheless demonstrated that very high ultrasonic frequencies can be

detected in *C. gorgonensis.*

291
292 **Discussion**
293
To understand the function of cuticular pinnae of katydid ears, we conducted acoustic

experiments on living specimens, combined with µ-CT to produce domains for numerical

modelling using accurate ear geometries and to print 3D scaled ears for additional acoustic

experiments. In all our experiments, pinnae had a significant effect on the sound reception at the

tympana. Pinnae significantly enhanced cavity-induced pressure gains in live specimens at 60

kHz (the maximum frequency achieved with the experimental platform for living specimens).

Further, the extent of the pinnal contribution to tympanal displacement amplitude depended on

the incident angle of the sound source at tested frequencies ≤ 60 kHz. The tympana of *C.*

gorgonensis naturally resonates at ca. 23 kHz, which shows high sensitivity to the dominant

frequency of the male calling song (28, 31). This was also observed in our experimental results,

irrespective of pinnal presence or absence. At ultrasonic frequencies (> 60 kHz), the pinnae-

enclosed tympanal membrane of *C. gorgonensis* show strong mechanical vibrations induced by

the resonances of the tympanal cavities (Fig. 5*A*). This suggests that tympanal pinnae enhance

sound pressure and sensitivity to high frequencies. It was previously demonstrated that even

minuscule tympanal displacements in *C. gorgonensis* create large displacement of the *crista*

acustica (CA) (26). Tympanal displacements are magnified in the CA as the effect of the lever

action imposed by the vibration of the tympanum (29). Comparable findings can be inferred from

LDV experiments in the katydid *Mecopoda elongata,* in which the CA was exposed by

microdissection (32). Insect mechanosensory auditory neurons are capable of detecting

exquisitely small mechanical displacements, down to 100 pm (33), close to the theoretical limits

of sensitivity (34). Therefore, the sound pressure gain induced by the tympanal pinnae at

ultrasonic frequencies (> 60 kHz; Fig. 3*A* and Fig. 5*A*) should produce sufficient tympanal

displacement without EC amplification to induce a response in the auditory receptors.

Electrophysiological recording of the auditory nerve from our experiments demonstrated a

significant neural response to a broad range of frequencies (23–120 kHz) and sound pressures

(46–94 dB SPL) (Fig. 5*C*; see *SI Appendix* Materials and Methods Section 1 for further details),

demonstrating that *C. gorgonensis* can detect very high ultrasonic frequencies. Recordings from

the T-cell in several katydids with pinnae (35, 36) and phaneropterines (36) without pinnae show

a broad sensitivity in the range 5 to 85 kHz (see *Discussion*).

As a result of probe-speaker frequency range limitations and reflections from the specialised

platform in our live time domain experiments, we were unable to test frequencies above 60 kHz.

We compensated by performing numerical simulations on 3D computer geometries of

experimental ears to predict pressure gains, 3D printing ear models to confirm resonance and

pressure gain, and recording free field vibrating tympana in living experimental specimens. Our

numerical simulations, considered in the frequency range 2-150 kHz, predicted sound pressure

gains in the interval 50 to 150 kHz with resonant frequencies of 115 kHz and 121 kHz in the PTM

and ATM cavities, respectively (Fig. 4*C*). Between 50 to 60 kHz, detectable pressure gains inside

the cavity started to act along the external surface of the tympanal membrane. We did not

compare the tympanal response between the experimental and numerical data directly, due to

the simplifying assumption in the numerical models that the tympana are composed of

homogeneous material. In reality, the tympana are composed of materially different layers where

the external surface has more chitinous, sclerotized layers extending from the tympanal plate to

the membrane, while the internal membrane is composed of elastic, tracheal derived material. To

overcome this, we measured tympanal vibrations to extreme ultrasound in free field conditions to

validate both the numerical and 3D print model results.

To test the influence of pinnal geometry alone on these ultrasonic gains, we printed 3D-scaled

ears and scaled the sound stimuli to match the ear size. The mean resonance of the 3D printed

models was found to be 101.47± 3.43 kHz for both the ATM and PTM (Fig. 4*E*). Differences

between the numerical and 3D print models results can be attributed to the material properties

(Young's modulus of printing resin) and tympanal thickness incorporated for the tympana in the

models. When we incorporated the material properties of the 3D ears into the mathematical

models, the resonant frequencies dropped from 118 to 111 kHz (ATM 112.5 kHz, PTM 109.5

kHz; *SI Appendix*, Fig. S2) which is close to the high frequency resonance of the tympana when

the pinnae are intact (107.84 ± 3.74 kHz for the PTM and 111.13 ± 4.24 kHz for the ATM; Fig.

5*A*). Without the pinnae, pressure gains were dramatically reduced in the simulations.

Additionally, a slight resonance was found in both the numerical simulations and 3D print models

caused by the incomplete ablation of the pinnal structures (Fig. 3 *D* and *F*).

Ultrasound guides in insects

Pinnae-covered tympanal ears are also found in some prominent moths (Notodontidae), with

eardrums mechanically tuned to detect the high frequencies used by hunting bats (37) which

range from as low as 35 to above 135 kHz (38). Cup-like pinnae from the metathorax are thought

to enhance the reflection of sounds onto the tympanic membrane. With the pinnae ablated, these

moths entirely lose the ability to localise sound at all frequencies (39). Therefore, katydids and

certain moths have independently evolved pinnal structures for detecting ultrasounds.

High frequency singers of the katydid subfamily Pseudophyllinae generally have very small

spiracles, long but narrow ECs, and tympana covered with various forms of cuticular pinnae (40).

Pseudophyllines with song frequencies greater than 50 kHz have been shown to depend more on

external than internal sound reception for communicating with conspecifics (18–20, 41). The

dominant port for hearing relies on the tympanal slit to spiracle size area ratio where the larger

input opening dictates principal auditory input in ultrasonic hearing rainforest pseudophyllines

(20). In *C. gorgonensis*, the spiracle area is large, naturally open on average three times larger

than the total area of the tympanal slits (1 mm^2:0.3 mm^2) which is inversely related to the general

scale of pseudophyllines. Reflectance and power transmittance inside the tympanal pinnal

cavities differ from the acoustic dynamics in the EC. Power transmittance of ultrasonic

frequencies suffers significant attenuation as a result of high reflectance of sound waves along

the narrowing EC in *C. gorgonensis* (13), limiting the EC response to frequencies <60 kHz.

By concentrating or funnelling ultrasonic sound into the tympanal cavity, the pinnae enhance

ultrasonic reception of incidental sounds. The cavity induced pressure gains are the consequence

of geometry of the tympanal slit in relation to the geometry and volume of the cavity (*SI Appendix*,

Table S2). These imparted forces are magnified by the motion of the tympanum. The resonances

afforded by the pinnal structures are evident as both the numerical and 3D print models do not

include a vibrating tympanum. In *C. gorgonensis*, irrespective of incident sound pressure

magnitude, the cavities provide a consistent pressure gain of at least 23 dB within the frequency

range 100 to 120 kHz (Fig. 4*C*). This is in contrast to tympanate moths that depend on the

incident sound intensity for mechanical tuning of high frequency bat calls (37, 39, 42) to produce

gains up to 16 dB (39).

Though the slit openings to both cavities are perceptively indistinguishable from each other, the

ATM slit opening is slightly larger than that of the PTM, but the PTM has a larger cavity volume.

These minuscule discrepancies cause differences in pressure gains, resonances, and phase

between vibrations of the ATM and PTM. In *C. gorgonensis*, the PTM pinna is approximately 13%

wider than the ATM. This increases the micro-acoustical diffraction of ultrasonic frequencies

entering the PTM cavity and potentially contributes to the broad turning of the PTM (Fig. 5*A*).

Similar pinnal asymmetries were observed in the katydid *Oxyecous lesnei* but the ATM structure

was much larger than the PTM which suggests that each tympanum is differentially tuned (for

other examples see Fig. 1 (43); *SI Appendix*, Fig. S3) (44). Here, we showed that the tympanal

cavities and their asymmetric openings act as Helmholtz resonators at frequencies of 94.13 ±

3.53 kHz for the ATM and 91.69 ± 3.93 kHz for the PTM in *C. gorgonensis*. Though the numerical

simulations show an average peak of 118 kHz (ATM 121, PTM 115 kHz), the Helmholtz

calculation assumes the slit opening is a circle and the cavity is a solid walled sphere. Pressure

distribution maps from the numerical models suggest that at 110 kHz (see Fig. 4*A*) the

resonances of the pinnae may function in a piston motion, whereby fluctuating air movements are

present at the opening of each independent cavity: an observation characteristic of Helmholtz

resonance. Quantitative imaging of scaled stimuli 9.63 kHz (110 kHz) using refracto-vibrometry

in the area around the 3D printed ear (1:11.4) demonstrated such piston behaviour (*SI Appendix*,

Supplementary Materials and Methods Section 2: Video 3). Sound pressure gains inside the 3D

printed model tympanal cavities and resonances closely matched the simulated numerical models

(Fig. 4*C* and *E*), showing an average sound pressure gain of 26.33 ± 4.06 dB for the ATM and

30.04 ± 1.34 dB for the PTM in the 3D printed ears at 101.47 kHz compared to 20.40 ± 2.82 dB

for the ATM at 121 kHz and 22.92 ± 1.03 dB for the PTM at 115 kHz in the numerical models.

When tympanal thickness and the material properties of the 3D print models were incorporated in

the simulations, the average sound pressure for the ATM was 20.37 ± 3.52 dB at 112.5 kHz and

21.40 ± 2.57 dB at 109.5 kHz for the PTM (*SI Appendix*, Fig. S2).

The asymmetry of the tympanal cavities has an acoustic function. Our results show that pinnae

cause intra-aural time differences and oscillation phase shifts at ultrasonic frequencies between

vibrations in the ATM and PTM (Fig. 2*A*). This contributes to differences of intensity and arrival of

sound that induce pressure gains of ultrasonic frequencies (Fig. 4*C* and Fig. 5*A*). Differential

tympanal mechanical responses have also been found in the pinnae possessing paleotropical

katydid *Onomarchus uninotatus* where the ATM exhibits tuning to the conspecific call and the

PTM's response is tuned to higher frequencies suggesting a possible use in predator detection

(45). The ATM and PTM of *C. gorgonensis* show differential responses to ultrasonic frequencies

(Fig. 4*C* and 5*A*), but how these two signals are transduced in the same auditory sensilla for

potential directional hearing remains unknown, as both membranes share the same CA.

Antiphasic motion of ipsilateral tympana in *Mecopoda elongata* has been suggested to drive

transduction by imparting mechanical stresses on the CA thereby stretching the sensory

dendrites of mechanoreceptors (46). If true, our findings from living specimens show that pinnae

cause consistently longer phase delays of ~0.25 cycle (= 90°) between vibrations of the ATM and

PTM at all tested frequencies than with the pinnae ablated. Not only do pinnal structures provide

a long diffractive edge for sound waves, but the dorso-ventral asymmetry between the ATM and

PTM pinnae increase phase differences that tune the ear (46). We argue that it is also possible

for asymmetries within a single ear to function in the same way, including at frequencies emitted

by hunting bats. However, our data do not support the idea of a single ear being directional at
least in the range 20 to 60 kHz (which includes the katydid's calling frequency at 23 kHz and first
harmonic at 46 kHz; *SI Appendix*, Fig. S8). Considering that the tettigoniid ear is capable of
resolving such small differences in time and intensity between the two ears (9, 44), four external
inputs could resolve the direction of an approaching bat and evoke ultrasound-triggered defensive
behaviour (35). The behavioural and ecological relevance of potential directional hearing using a
single ear constitutes an outstanding question and will be the subject of future studies.
438
In *C. gorgonensis*, the dual inputs of the spiracle and the four external ports (the pinnae) function
as a sound pressure gain compensation system. As previously shown for *C. gorgonensis* (13),
and in other species (14, 40), the EC with its exponential horn geometry acts as a bandpass filter
limited in providing pressure gains to high ultrasonic frequencies (> 60 kHz, for *C. gorgonensis*)
(12, 47) and is designed to enhance detection of the specific carrier frequency and associated
harmonic contents (46 kHz for *C. gorgonensis*). The effect of the EC geometry in reducing sound
velocity is as much as ~20% or ca. 60 µs, coupled with the contralateral EC, collectively a total of
eight inputs are possible with each causing a vibration with variable delays in four internal and
four external tympanal surfaces to the same stimulus (12). Though the reduction in velocity
contributes exceptional binaural directional cues, the external port provides real-time sensitivity to
exploit fading bat ultrasounds. Ear pinnae act as extreme ultrasonic guides that can resonate at
the high frequency components at the start of the echolocation calls of bats. Hence the EC might
be a less efficient method of bat detection as the angle of incidence accompanied by time delays
could shorten reaction times and obfuscate the localisation of the predator. This suggests that the
EC in katydids without ear pinnae should exhibit broadband responses (see last section of
discussion).
455

Bat detection by resonance
It has been shown that katydids form a key part of the diet of many insectivorous bat species in
various regions of world (48–55). However, such ecological interactions have been more
intensively studied in the Neotropical regions. Gorgona Island, Colombia, is home to over 33 bat
species with many still undescribed and underrepresented in wildlife inventories, including at least
three substrate gleaning bats of the neotropical leaf-nosed bat family Phyllostomidae (56).
Neotropical katydids have evolved sophisticated auditory features as strategies for survival
against substrate gleaning bats (36, 57–60). The habitat of *C. gorgonensis* is in cluttered
vegetation of the tropical forest understory (61). In this environment, acoustic signals are heavily
attenuated which leads to significant transmission loss (62, 63). However, insects have evolved a
variety of sophisticated receivers to perform call discrimination in these acoustically challenging

environments (64). Acoustic adaptations by katydids to evade bat predation include the use of

narrow bandwidths, high carrier frequencies, and sporadic calling in order to diminish signal

proliferation in the environment (57, 65–67), and ergo evade eavesdropping by bats (68). Certain

adaptations are a trade-off as the katydid becomes more conspicuous and vulnerable to other

predators as the communication method changes. For example, katydids that perform vibrotaxis,

even tremulations can likely attract spiders, scorpions (69) and primates, as well as bats (70).

Likewise, bats foraging at this level also face similar acoustic shortcomings, affecting their

echolocation abilities (71). Thus, several phyllostomid substrate gleaning bats are very well

adapted to listen to prey-produced sounds like rustling noises or mating calls of, e.g., male

katydids (38, 57, 72). At least one common gleaning bat species, *Micronycteris microtis*

(Phyllostomidae), uses a sophisticated echolocation strategy to detect katydids concealed in

vegetation (73, 74). Despite their passive acoustic defences, calling from restrictive locations and

being equipped with very large mandibles and sharp fastigia, katydids like *C. gorgonensis* are

predated by phyllostomid bats (60).

Here we argue that the pinnal structures of the external tympanal ports of katydid ears act as

sound guides providing acute ultrasonic hearing allowing the detection of echolocation calls of

hunting bats and thus an additional sensory based defence in the predatory-prey arms race. The

presented numerical and experimental evidence suggests that the greatest ultrasonic gain of the

pinnae is at frequencies matching those falling into the frequency range of the echolocation calls

of native, insect gleaning bat species (Fig. 6). As neotropical gleaning bats approach their target,

they emit short, broadband, multi-harmonic sweeps, demodulate the frequency from higher

frequencies above 135 kHz to as low 35 kHz (38, 75). In terms of predator detection, a katydid

like *C. gorgonensis* has an excellent chance of detecting the calls of a hunting bat even at the

start of the sweep. Responses to these high frequencies are supported by LDV recordings of

tympanal motion in intact ears of free-field specimens, and audiograms that show a broad

mechanical, behavioural, and neural response to ultrasonic frequencies (*SI Appendix*, Table S3,

Fig. 5*A-C*). These broad responses to ultrasound are common in several pinnal bearing katydids

subfamilies of Tettigoniidae (76, 77), as shown in the Tettigoniinae with *Tettigonia viridissima*

(62), in Pseudophyllinae with *Acanhodis curvidens* (36), *Balboa tibialis* (36), *Docidocercus*

gigliotosi (36) *Ischnomela gracilis* (36), and in Conocephalinae for example *Bucrates capitalus*

(36), *Neoconocephalus ensiger* (35) and *Neoconocephalis affinis* (36). A gain of 16 to 20 dB at

the start of the bat call provides essential awareness time (≤ 0.86 ms in terms of duration of the

complete sweep (38)) to *C. gorgonensis* as a result of the tympanal pinnae. Other katydid species

living in sympatry with *C. gorgonensis* like *Supersonus aequoreus* (the most ultrasonic katydid

found in nature to date (78)), *Ischnomela gracilis*, and *Eubliastes aethiops* exhibit similar cavity

induced pressure gains in the range of phyllostomid echolocation calls (*SI Appendix*, Fig. S4).

The pressure – time difference receiver of *C. gorgonensis* is a unique system that can capture

different ranges of frequencies between the multiple entry ports that can obviate the limitations of

each but is also capable of compensating for limitations in auditory orientation (12). For katydids,

incident sounds from elevation are difficult to perceive (27). The ability of the external port to be

positioned and rotated in accordance with the movement of the foretibial knee and foretibial leg

joints permits for the ear to be more vertically oriented. The μ-CT imaging presented here of the

tympanal cavities supports the theory for vertical orientation as the sub-slit cavity is

asymmetrically recessed to the distal end, which is likely to enhance mechanical responses to

vertical stimuli (Fig. 1*D*). For ultrasonic reception, a total of four asymmetrical external ports (left

and right ATMs and PTMs) may be behaviourally articulated in a manner to enhance the

detection of bats calling from elevated positions towards the katydids, and the physical separation

between the external ports of each ear yields sufficient binaural cues.

Katydid ear pinnae and the fossil record

The presence of ear pinnae in katydids is unknown in the fossil record. Katydid ancestors (e.g.,

Haglidae and Prophalangopsidae from upper Jurassic (79)) and early katydids (Tettigoniidae)

from the middle Paleogene (Eocene, ~55 mya (80, 81)) all show naked tympana (without pinnae).

The earliest echolocating bats are from the Eocene (82), therefore katydids with tympanal pinnae

may have initially evolved such sophisticated hearing devices to survive nocturnal predators while

they sing under the cover of darkness. Although katydid ear pinnae have never been mapped in

the most recent molecular phylogenies (83, 84), we observe a potential unique origin of ear

pinnae in the family Tettigoniidae, with multiple losses or retrogressions in modern species,

including the large subfamily Phaneropterinae (predominantly known to have naked tympana).

Comparative analyses using large phylogenies are needed to solve this working hypothesis.

Analogous ear pinnae adaptations are observed in some Eneopterinae crickets (tribe Lebinthini)

(85), which differ from field crickets in their use of high frequencies for specific communication (12

to 28 kHz). These crickets emerged also in the Eocene (86) and while their ancestors exhibit only

one functional tympanum (PTM), the extant forms show two functional asymmetric tympana, with

the ATM covered by pinnae (85). Such adaptation suggests a new paradigm of the dual role of

the ears, in detecting conspecific and bat echolocation calls.

Several katydid species (e.g., Phaneropterinae, Mecopodiae) exhibit naked tympana (*SI*

Appendix, Fig. S1*B*). While little is known about the ecology of many species, katydids have

developed diverse hearing structure morphologies to respond to predation pressure (87). Ears

evolve very rapidly (87, 88) and it would not be surprising that, without pinnal structures, some

nocturnal Phaneropterinae evolved sophisticated ECs with exceptional broadband response (i.e.,

broader than that of *C. gorgonensis*) (14, 21, 36, 40). A study from Barro Colorado Island,

Panamá, reported 31 Phaneropterinae katydids, of which about 42% use calling songs in the low

ultrasonic range while 74% showing a spectral bandwidth of >10 kHz (89). It might also be

possible that some Phaneropterinae have a unique ear function via the EC which is capable of

detecting conspecific calls as well as bats. This configuration of a single ear function is also

potentially exhibited by *Supersonus aequoreous* (*SI Appendix*, Fig. S3) which show atrophied EC,

and their outer ear components (tympana and pinnae) specialised in identifying the direction of

their own calls while at the same time detecting bats. Other adaptations of katydids without

tympanal pinnae for bat detection might involve activity during the daytime (87, 89), or dwell in

dense vegetation that challenges hunting bats (90). For example, *Phlugis poecila* and

Speculophlugis hishquten species are diurnal visual predators that need day light to hunt (91).

Owing to their transparent camouflage, males are able to sing below Araceae leaves during the

day and avoid visual detection by diurnal avian predators. Other katydids like *Conocephalus* sp.

with tympanal pinnae are also active during the daytime, although a few species are nocturnal or

crepuscular, but a majority dwell in dense grass vegetation. Their calling songs are of unusual

broadband energy, in many species expanding above 60 kHz (92). In this case, the retention of

the pinnal condition might be associated with specific directional hearing like acoustic ranging

(93) in such dense grass environments (62, 94).

While the diversity of form and function of pinnae in katydids requires a deeper comparative

analysis, the presented findings suggest that in the assessed species, pinnae act as ultrasonic

resonators for the early detection of echolocating bats. As a working hypothesis, we propose that

the ear pinnae have a unique origin across the ca. 8000 living species of Tettigoniidae (8) in

response to the emergence of bats during the early Eocene, and that it was subsequently lost or

modified several times.

566
567
568 **Materials and Methods**

569
Specimens

Copiphora gorgonensis (Tettigoniidae: Copiphorini) is endemic to Gorgona National Natural Park,

Colombia (02°58′03″N 78°10′49″W). The original generation of the species were imported to the

UK under the research permit granted by the Colombian Authority (DTS0-G-090 14/08/2014) in

2015. The specimens were ninth generation, captive bred colonies and maintained at 25°C, 70%

RH, light: day 11 h: 23 h. They were fed *ad libitum* diet of bee pollen (Sevenhills, Wakefield, UK),

fresh apple, dog food (Pedigree Schmackos, UK) and had access to water. Live experiments
were conducted on seven adults of *C. gorgonensis* from our laboratory breeding colonies at the
University of Lincoln (Lincoln, UK). Following experimentation, these specimens plus an
additional four females already stored in ethanol were μ-CT scanned for finite element modelling;
totalling 17 ears (10 female, 7 male). Live specimens were subsequently preserved in
100%ethanol -filled jars and stored in a freezer at -22°C at the University of Lincoln (Lincoln, UK).
582
Simultaneous recordings of tympanal vibrations using laser Doppler Vibrometry
Insects were chemically anesthetized using triethylamine-based agent FlyNap (Carolina
Biological Supply, USA) for 15 min prior to the mounting process, and remained awake
throughout the duration of the experiment. The animals were dorsally mounted using a
specialized platform to isolate the external and internal sound inputs and also mimic their natural
stance (*SI Appendix*, Fig. S5). A rosin-beeswax mix was used to fix the pronotum, and the mid
and hind legs, to the mount. This specialized platform (15) consists of two Perspex panels (1.61
mm thick) that are joined by latex and suspended in the air by a 12 x 12 mm metal frame
attached to a micromanipulator (World Precision Instruments, Inc., USA) (see (29)). At the
Perspex junction, the forelegs of the insect were extended through arm holes cut in the Perspex
and attached on a rubber block with metal clasps. A metal clasp was placed on each foretibia and
forefemur (total of 4) to arrest foreleg motion. The arm holes and frame borders were sealed with
latex to deny sound propagation to the spiracle.
596
The laser Doppler vibrometry system consisted of a the OFV-2520 Dual Channel Vibrometer -
range velocity controller for operating two single point laser sensor heads, (OFV-534, Polytec,
Germany) each with VIB-A–534 CAP camera video feed and laser filters. Each sensor head was
mounted on a two-axis pivoting stage (XYZ, Thorlabs Inc., USA) anchored to an articulating
platform (AP180, Thorlabs Inc., USA) and manually focused at 10.5 cm above a vibration
isolation table (Pneumatic Vibration Isolation Table with a B120150B - Nexus Breadboard, 1200
mm x 1500 mm x 110 mm, M6 x 1.0 Mounting Holes, Thorlabs Inc., USA) supported by an anti-
vibration frame (PFA52507 - 800 mm Active Isolation Frame 900 mm x 1200 mm, Thorlabs Inc.,
USA) in an anechoically isolated chamber (AC Acoustics, Series 120a, internal dimensions of 2.8
m x 2.7 m x 2 71 m). The sensor heads were outfitted with magnification microscopic lenses
(Mitutoyo M Plan 10x objective for Polytec PSV-500 single laser head OFV 534, Japan) and
positioned about 35 to 40 mm away from the insect foreleg at 45° angles towards the Perspex
surface (*SI Appendix*, Fig. S5). The narrow entrance to the tympanal cavities restricted the use of
LDV to measure tympanal responses across the entire tympanal membrane. Therefore, the
placement of the sensor heads was limited to positions where the sensor heads were

perpendicular to the tympanic membrane of interest. The sensor speeds were maintained at

0.005 (m/s)/V and recorded using an OFV-2520 internal data acquisition board (PCI-4451;

National Instruments, USA).

Tympanal vibrations were induced by a four-cycle sinusoidal wave at 23, 40 and 60 kHz. The

closed-field configuration of the loudspeaker restricted the delivery of high ultrasonic stimuli to 60

kHz. A rotating automated stage (PRM1Z8 rotation mount, Thorlabs Inc., USA) with a KDC101 K-

Cube™ DC Servo Motor Controller (Thorlabs Inc., USA) positioned a multi-field magnetic

loudspeaker (MF1, Tucker Davis, USA) with a parabolic nozzle (see Supplementary Materials

from (12)) and plastic probe tip (3.5 cm L x internal diameter 1.8 mm W) about 3.5 mm away from

the mounted insect and 10.2 cm above the breadboard table. The speaker was moved across a

12 cm semi-circle radius in 1° steps (0.56 mm). The probe tip was positioned at "point zero" and

20 single shot recordings at 1°intervals, totalling 10° at either side (*SI Appendix*, Fig. S6). A high

quality 500 band pass filter was applied at 10 to 30 kHz for the 23 kHz recordings, 30 to 50 kHz

for the 40 kHz recordings, and 50 to 70 kHz for the 60 kHz recordings. All acoustic signals were

generated by a waveform generator (SDG 1020, Siglent, China), synchronized with the LDV,

amplified (ZB1PS, Tucker Davis, USA) and measured by a 1/8⬚ (3.2 mm) omnidirectional

microphone (Type 4138, Brüel & Kjaer, Nærum Denmark) located about 3 mm from tympanum.

The microphone, with built in preamplifier (B&K 2670, Brüel & Kjær, Nærum, Denmark), was

calibrated using a sound-level calibrator (Type 4237, Brüel & Kjaer, Nærum, Denmark) and set to

316 mV/Pa output via a conditioning amplifier (Nexus 2690-OS1, Brüel & Kjær, Nærum,

Denmark). A reference measurement was performed by placing the microphone 3 mm from the

probe tip to the loudspeaker before each experiment. Using a micro-manipulator, the microphone

was positioned approximately 3 to 3.5 mm from the ear to monitor the acoustic isolation of the

platform.

Experimental procedures

The sensor heads were manually focused on the external tympanal surface using the 2-axis

pivoting stage and manual wheel with the aid of the sensor head camera output displayed on an

LED screen. For the time measurements, the point zero was found for each leg and for each test

frequency. The point zero was the point where the displacements from the anterior tympanic

membrane (ATM) and posterior tympanic membrane (PTM) matched the oscillation phase of the

generated 4-cycle sinusoidal waves. This ensured that the vibrations of the tympanic membranes

were synchronous relative to the speaker position. Displacement amplitudes from the same cycle

order number were measured from each sensor head reference, and approximately 252 data

points were measured per ear.

After recording the vibrations for both ears of the tested individual, the cuticular pinnae were

carefully excised using a razor blade (taking care not to damage the tympanal organs or the fine

layer of tissue ventrally connected to the tympanic membranes). The measurements were

repeated for each ear following the same protocol.

Time and displacement measurements were analysed by identifying the second oscillation of the

4-cycle tone generated waves in each software window (PSV 9.4 Presentation software, Polytec,

Germany). Phase calculations were obtained using the equation $\varphi\,° = 360°\,x\,f\,x\,\Delta t$ where f is

frequency (kHz) and Δt (ms) the difference in arrival times between the ATM and PTM.

Morphological studies of the ear

To produce 3D data for modelling, 17 ears of *C. gorgonensis* were scanned using a SkyScan

1172 X-ray µ-CT scanner (Bruker Corporation, Billerica, MA, USA) with a resolution between 1.3

and 2.9 µm (55 kV source voltage, 180 µA source current, 300 ms exposure and 0.1° rotation

steps). As experimental procedures required removal of the cuticular pinnae, eight additional

specimens with intact pinnae were scanned. The µ-CT projection images were reconstructed with

NRecon (v.1.6.9.18, Bruker Corporation, Billerica, MA, USA) to produce a series of orthogonal

slices. The 3D segmentation of the ear, measurements of the ear cross section and width, and

volumetric measurements of the cavities formed by the pinnae were performed with the software

Amira-Aviso 6.7 (Thermo Fisher Scientific, Waltham, Massachusetts, USA). µ-CT

stereolithography files (STL) were generated for numerical modelling using established protocols

(12, 15) and to 3D print ear models.

For 2D measurements of the cavity slit area, pinnal protrusion, and the distance between the

pinnal cavities, an Alicona InfiniteFocus microscope (G5, Bruker Alicona Imaging, Graz, Austria)

at x5 objective magnification was used to capture images of collection specimens with intact

pinnae, with a resolution of about 100 nm ($n = 8$ ears).

Bat and insect call recordings

The echolocation calls of phyllostomid bats (Chiroptera: Phyllostomidae) native to Gorgona Island

(*Gardnerycteris crenulatum*, *Tonatia saurophila* and *Micronycteris microtis*) were recorded in a

small indoor flight cage (1.4 x 1.0 x 0.8 m) in which they were allowed to fly, via an ultrasound

condenser microphone (2-200 kHz frequency range, ±3 dB frequency response between 25-140

kHz; CM16, CMPA preamplifier unit, Avisoft Bioacoustics, Glienicke, Germany) and real time

ultrasound acquisition board (6 dB gain, 500 kHz sampling rate, 16 bit resolution; UltraSoundGate

116Hm, Avisoft Bioacoustics, Glienicke, Germany) connected to a laptop (Think Pad X220,

Lenovo, Beijing, China), with a corresponding recording software (Avisoft RECORDER USGH,

Avisoft Bioacoustics, Glienicke, Germany). These are the most common insectivorous gleaning

species in the habitat of *C. gorgonensis*. Single calls of each species are presented in Fig. 6 and

SI Appendix Fig. S7.

SI Appendix, Section 1 (see *SI Appendix*, Fig. S8) has details of male *C. gorgonensis* calling

song recording.

Acoustics measurements of synthetic 3D-printed scaled ear models

For time domain measurements, 3D models of the ears were placed on a micromanipulator arm

with blu-tac (Bostik Ltd, Stafford, UK) and positioned frontally 30 cm from a MF1 loudspeaker at

the same elevation. A 25 mm tipped B&K Type 4182 probe microphone (Brüel & Kjær, Nærum,

Denmark) with a 1 × 25 mm (0.99″) probe tube length and 1.24 mm (0.05″) interior diameter,

calibrated using a B&K Type 4237 sound pressure calibrator was placed ventral to the ear. The

ear moved on the microphone using an electronic micromanipulator (TR10/MP-245, Sutter

Instrument, Novato, California, USA), to a position 1 cm from the back of the cavity. Stimuli

delivered were individually scaled to match the wavelength of a real-size ear (e.g., for a 1:10

scale printed model, the frequency delivered to simulate 120 kHz would be 120/10 = 12 kHz) to

account for variation in printed model scaling. 3D printed models were scaled 1:11.43 (male

1:11.33; female 1:11.53) with the corresponding average scaled stimuli of 2.01 kHz for 23 kHz,

3.50 kHz for 40 kHz, 5.25 kHz for 60 kHz, and 9.63 kHz for 110 kHz. Four cycle pure tones were

produced using the aforementioned function generator, and the amplitude set to deliver 1 Pa to

the microphone at each frequency. Received signals were amplified using a B&K 1708

conditioning amplifier (Brüel & Kjær, Nærum, Denmark), and acquired using a PSV-500 internal

data acquisition board at a sampling frequency of 512 kHz. The microphone remained stationary

during the experiments, nor was its direct path to the speaker obstructed. Instead, the

microphone entered the ear via a drilled hole, allowing the pinnae to surround the tip of the

microphone. Thus, the reported sound pressure gains result solely from the cavities of the 3D

model, and not the motion of the microphone. When the microphone was positioned inside the

cavities, the gap between the drilled hole and microphone probe was sealed with blu-tac (Bostik

Ltd, Stafford, UK) to mimic the real cavity and avoid acoustic leaking (refer to *SI Appendix*,

Supplementary Materials and Methods Section 2: Video 1; Video 2).

To calculate the frequency that produced the best gain, the MF1 loudspeaker was replaced with a

RAAL 140-15D Flatfoil loudspeaker (RAAL, Serbia), with a different amplifier (A-400, Pioneer,

Kawasaki, Japan). This speaker was able to deliver a broadband stimulus of periodic chirps,

generated within Polytec 9.4 software, with a simulated frequency range of 2 to 150 kHz.

Recording in the frequency domain, at a sampling frequency of 512 kHz, the amplitude of the

broadband stimulus was mathematically corrected within the software to deliver 60 dB at all

frequencies. The reference frequency spectrum with no ear present could be subtracted from the

frequency spectrum reported within the cavities to calculate frequency-specific gain and thus

cavity resonance. Gain was calculated by subtracting the probe microphone sound pressure (dB)

measured 1 cm outside of the cavity from inside the tympanal cavity measurements (Fig. 3*B* and

3*C*; see also *SI Appendix*, Supplementary Materials and Methods Section 2: Video 1).

For comparative purposes, the ears of the following sympatric and pinnae bearing katydid

species from Gorgona Island were also 3D printed and subjected to experiments according to the

aforementioned protocol: *Ischnomela gracilis*, *Supersonus aequoreus* and *Eubliastes aethiops*

(see *SI Appendix*, Fig. S3).

Frequency domain recordings of the cavity resonance, and time domain recordings of pure tone

gains were then exported as .txt files for analysis. Methods for printing 3D ear models are

provided in the Supplementary Materials and Methods Section 1 of the *SI Appendix*.

Mathematical models and numerical simulations

The mathematical models have been constructed as a scattering acoustic – structure interaction

problem and simulate the acoustic response of the tympanal cavities to an incident plane acoustic

wave in an air domain. Hence, the 3D model considers the interaction of the sound wave with the

ear, for which realistic material properties have been incorporated. The air acoustic domain is

truncated as a sphere with a 3 mm radius that is centered around the ear (*SI Appendix*, Fig. S9).

Two different geometries of the ears were taken as part of the mathematical model domain:

pinnae intact and pinnae removed (*SI Appendix*, Fig. S10).

The models were considered both in the frequency and the time domains, and were solved using

the acoustic-shell interaction module of the software Comsol Multiphysics, v5.6 (95). For the

frequency domain models, the incident wave was taken to be a chirp with an amplitude of 1 Pa

and frequency 2 to 150 kHz, directed at "point zero" as defined in the in the section *vibrational*

measurements. For the time domain models, three different incident waves were used, with

amplitudes 1 Pa and frequencies 23, 40, 60 kHz. The direction of the waves was taken as -10°, -

5°, 0°, 5° and 10° on a fixed plane perpendicular to the ear, with 0° corresponding to "point zero".

The details of the solved system of equations can be found in the *SI Appendix* Supplementary

Materials and Methods Section 1.

The numerical solution to the problem was obtained using the finite element method for the

spatial variables in both the time and frequency domain simulations. For forming the finite-

element mesh, the maximum diameter used for the tetrahedral elements in the sphere was

$h_{max} = \frac{c}{6 \times f_0}$, where $c = 343 \text{ m/s}$ and $f_0 = 150 \text{ kHz}$ (*SI Appendix*, Fig. S11 and S12). Hence, even

at the largest frequency considered, there were six tetrahedral elements per wavelength.

Quadratic Lagrange elements were applied for the solution.

For the time domain solution, the time variable was solved for using the Generalized alpha

method, with a constant time step of $\Delta t = \frac{1}{60 \times 150} \text{s}$, so that the Courant-Friedrichs-Lewy (CFL)

condition (96), defined as $CFL = \frac{c \times h_{max}}{\Delta t}$ was 0.1, which gives a reliable approximation of the

solution.

Behavioral and tympanal response to broadband stimulation

Behavioral audiograms were measured from nine tethered female ($n = 9$) *C. gorgonensis* to test

behavioral response thresholds to controlled auditory stimuli (20 to 120 kHz). Methods are

provided in the *SI Appendix* Supplementary Materials and Methods Section 1.

For the tympanal tuning measurements, we exposed seven specimens(4 males, 3 females) to

free field broadband (periodic chirp 20 to 120 kHz) stimulation presented by an ipsilaterally

positioned SS-TW100ED Super-Tweeter (Sony, Tokyo, Japan) with a 20 kHz built-in high-pass

filter using an Avisoft Bioacoustics Ultrasonics Power Amplifier (Avisoft Bioacoustics,

Glienicke/Nordbahn, Germany). A rosin-beeswax mix was used to fix the pronotum, and the mid

and hind legs, to the mount (see (29)) after the insects were chemically anesthetized using

FlyNap. Insects were then elevated to the same level as the LDV and positioned 15 cm from the

loudspeaker. A 1/8" B&K Type 4138 microphone was placed about 3 mm in front of the ear of

interest and recorded the stimulus. Mechanical responses were acquired using a PSV-500

internal data acquisition board at a sampling frequency of 512 kHz. The amplitude was corrected

to maintain 60 dB SPL at all frequencies. Data was collected as magnitude (velocity/sound

pressure).

Neural audiograms

Extracellular recordings of whole auditory nerve activity in response to sound were obtained from

five animals, using a suction electrode positioned on the nerve in the distal femur. Recordings

were digitized using a Micro1401 mk II (Cambridge Electronic Design (CED), Cambridge, UK) for

observation and storage for later analysis on a PC using Spike2 (CED) software. Stimuli

consisted of 10 repeats of 500 ms sound pulses followed by 500 ms silent periods. Frequency
(11 pure tones ranging from 23–120 kHz) and SPL (9 levels ranging from 46–94 dB in 6 dB
increments) were systematically altered for a total of 99 combinations. Recordings for each train
of 10 stimuli were root-mean-square transformed (time constant 0.66 ms) to convert the neuronal
traces into positive displacements from zero and averaged. The mean areas of response (in
microvolt s, µVs) during the presentation of each different sound stimulus was compared to the
mean response during the subsequent silent period in each animal (n = 5) using paired t-tests.
Detailed methods for neural audiograms are provided in the *SI Appendix* Supplementary
Materials and Methods Section 1.
800
Statistical analyses
Using empirical data we tested the effect of cuticular pinnae on tympanal responses [in
displacement amplitude (natural log transformed) and arrival time] to incident sound, we fitted
linear mixed models (LMM) with angle (-10° to 10°, quadratic polynomial continuous variable) as
a covariate and presence of pinnae (y/n), frequency (23, 40 and 60 kHz, categorical variable),
tympanum (ATM or PTM) as fixed factors. We included the interactions between angle and
pinnae presence and between pinnae presence and frequency. To model the curvature in the
response surface of the pinnal enclosed tympanum, angle was fitted as a quadratic polynomial
with 0^o at point zero. The interaction of angle and pinnae was fitted as such to show the restriction
of pinnal structures in both time and displacement to the response surface. To account for
repeated measures of the same specimen, we nested leg (left or right) within individual
specimens as a random factor. We carried out post hoc tests between pinnae (y/n) at each
frequency using estimated marginal means from the package *emmeans* (97).
814
Using the same initial LMM model, we tested how sound pressure estimated from numerical
models was related to angle (-10° to 10°, polynomial continuous variable), presence of pinnae
(y/n), frequency (23, 40 and 60 kHz, categorical variable), tympanum (ATM or PTM) as fixed
factors. Again, we include the interactions between angle and pinnae and between pinnae and
frequency. We finally tested sound pressure based on 3D models with the presence of pinnae
(y/n), frequency (23, 40 and 60 kHz, categorical variable), tympanum (ATM or PTM) as fixed
factors, and with the inclusion of the interaction between pinnae and frequency. For both
numerical and 3D models, we carried out post hoc tests between pinnae (y/n) at each frequency
using estimated marginal means from the package *emmeans*.
824
825   Statistical tests and graphs were performed in R 4.0.0 (98) and all LMMs were run using the
826   package lmerTest (99).

Data availability

Experimental data (LDV recordings), numerical simulations, Comsol model files, and µ-CT
stereolithography files (in .stl format) are available in Dryad
(https://doi.org/10.5061/dryad.k0p2ngf8x; deposited 9 September 2021).

Acknowledgments

This research is part of the project "The Insect Cochlea" funded by the European Research
Council, Grant ERCCoG-2017-773067 to FM-Z; and was also funded by the Natural Environment
Research Council (NERC), grant DEB-1937815 to FM-Z. We thank the Orthopterists' Society for
aiding in funding the µ-CT work of CW, for which some data has been used in this study, and to
the University of Lincoln's School of Life Sciences for CW's PhD studentship.

References

1. M. C. Göpfert, R. M. Hennig, Hearing in Insects. *Annu. Rev. Entomol.* **61**, 257–276 (2016).

2. D. Robert, "Directional Hearing in Insects" in *Sound Source Localization*, A. N. Popper, R. R. Fay, Eds. (Springer New York, 2005), pp. 6–35.

3. B. Warren, M. Nowotny, Bridging the gap between mammal and insect ears – A comparative and evolutionary view of sound-reception. *Front. Ecol. Evol.* **9**, 504 (2021).

4. J. E. Yack, The structure and function of auditory chordotonal organs in insects. *Microsc. Res. Tech.* **63**, 315–337 (2004).

5. R. Lakes-Harlan, J. Scherberich, Position-dependent hearing in three species of bushcrickets (Tettigoniidae, Orthoptera). *R. Soc. Open Sci.* **2**, 140473 (2015).

6. N. Suga, Principles of auditory information-processing derived from neuroethology. *J. Exp. Biol.* **146**, 277–286 (1989).

7. A. Michelsen, O. N. Larsen, Pressure difference receiving ears. *Bioinspiration and Biomimetics* **3**, 011001 (2008).

8. M. M. Cigliano, H. Braun, D. C. Eades, D. Otte, Orthoptera Species file v.5.0. *Orthoptera Species File* (2021).

9. W. J. Bailey, "The ear of the bushcricket" in *The Tettigoniidae. Biology, Systematics and Evolution*, W. J. Bailey, D. Rentz, Eds. (Crawford House Press, 1990), pp. 217–247.

10. J. Strauß, A. W. Lehmann, G. U. C. Lehmann, Sensory evolution of hearing in tettigoniids

865   with differing communication systems. *J. Evol. Biol.* **27**, 200–213 (2014).

866 11. K. Kalmring, *et al.*, "The Auditory-Vibratory Sensory System in Bushcrickets (Tettigoniidae,
867   Ensifera, Orthoptera) I Comparison of Morphology, Development and Physiology" in
868   *Environmental Signal Processing and Adaptation*, G. Heldmaier, D. Werner, Eds.
869   (Springer Berlin Heidelberg, 2003), pp. 169–207.

870 12. D. Veitch, *et al.*, A narrow ear canal reduces sound velocity to create additional acoustic
871   inputs in a microscale insect ear. *Proc. Natl. Acad. Sci. U. S. A.* **118**, e2017281118
872   (2021).

873 13. E. Celiker, T. Jonsson, F. Montealegre-Z, The auditory mechanics of the outer ear of the
874   bush cricket: a numerical approach. *Biophys. J.* **118**, 464–475 (2020).

875 14. A. Michelsen, K. Rohrseitz, K. G. Heller, A. Stumpner, A new biophysical method to
876   determine the gain of the acoustic trachea in bushcrickets. *J. Comp. Physiol. A* **175**, 145–
877   151 (1994).

878 15. T. Jonsson, F. Montealegre-Z, C. D. Soulsbury, K. A. Robson Brown, D. Robert, Auditory
879   mechanics in a bush-cricket: Direct evidence of dual sound inputs in the pressure
880   difference receiver. *J. R. Soc. Interface* **13**, 20160560 (2016).

881 16. H. Autrum, Über Lautäusserungen und Schallwahrnehmung bei Arthropoden II. *Z. Vgl.*
882   *Physiol.* **28**, 326–352 (1940).

883 17. H. Autrum, Anatomy and physiology of sound receptors in invertebrates. *Acoust. Behav.*
884   *Anim.*, 412–433 (1963).

885 18. W. J. Bailey, R. O. Stephen, Directionality and auditory slit function: A theory of hearing in
886   bushcrickets. *Science.* **201**, 633–634 (1978).

887 19. R. O. Stephen, W. J. Bailey, Bioacoustics of the ear of the bushcricket *Hemisaga*
888   (Sagenae). *J. Acoust. Soc. Am.* **72**, 13–25 (1982).

889 20. A. C. Mason, G. K. Morris, P. Wall, High ultrasonic hearing and tympanal slit function in
890   rainforest katydids. *Naturwissenschaften* **78**, 365–367 (1991).

891 21. E. Hoffmann, M. Jatho, The acoustic trachea of Tettigoniids as an exponential horn:
892   Theoretical calculations and bioacoustical measurements. *J. Acoust. Soc. Am.* **98**, 1845–
893   1851 (1995).

894 22. J. Shen, A peripheral mechanism for auditory directionality in the bushcricket *Gampsocleis*
895   *gratiosa*: Acoustic tracheal system. *J. Acoust. Soc. Am.* **94**, 1211–1217 (1993).

896 23. A. Michelsen, H. Nocke, Biophysical Aspects of Sound Communication in Insects. *Adv. In*
897   *Insect Phys.* **10**, 247–296 (1974).

898 24. N. Eisner, A. V. Popov, "Neuroethology of Acoustic Communication" in *Advances in Insect*
899   *Physiology*, 13th Ed., J. E. Treherne, M. J. Berridge, V. B. Wigglesworth, Eds. (1978), pp.
900   229–355.

901 25. K. G. Hill, B. P. Oldfield, Auditory function in tettigoniidae (Orthoptera:Ensifera). *J. Comp.*
902   *Physiol. A* **142**, 169–180 (1981).

903   26.   F. Montealegre-Z, D. Robert, Biomechanics of hearing in katydids. *J. Comp. Physiol. A*
904   **201**, 5–18 (2015).

905   27.   H. Römer, Directional hearing in insects: biophysical, physiological and ecological
906   challenges. *J. Exp. Biol.* **223**, Pt 14 (2020).

907   28.   F. Montealegre-Z, M. Postles, Resonant sound production in *Copiphora gorgonensis*
908   (Tettigoniidae: Copiphorini), an endemic species from Parque Nacional Natural Gorgona,
909   Colombia. *J. Orthoptera Res.* **19**, 347–355 (2010).

910   29.   F. Montealegre-Z, T. Jonsson, K. A. Robson Brown, M. Postles, D. Robert, Convergent
911   evolution between insect and mammalian audition. *Science.* **338**, 968–97 (2012).

912   30.   T. D. Rossing, N. H. Fletcher, *Principles of Vibration and Sound*, 2nd Ed. (Springer New
913   York, 2004) https:/doi.org/10.1007/978-1-4757-3822-3.

914   31.   E. Celiker, T. Jonsson, F. Montealegre-Z, On the tympanic membrane impedance of the
915   katydid *Copiphora gorgonensis* (Insecta: Orthoptera: Tettigoniidae) . *J. Acoust. Soc. Am.*
916   **148**, 1952–1960 (2020).

917   32.   J. Hummel, K. Wolf, M. Kössl, M. Nowotny, Processing of simple and complex acoustic
918   signals in a tonotopically organized ear. *Proc. R. Soc. B Biol. Sci.* **281**, 20141872 (2014).

919   33.   J. F. C. Windmill, J. H. Fullard, D. Robert, Mechanics of a `simple' ear: tympanal vibrations
920   in noctuid moths. *J. Exp. Biol.* **210**, 2637–2648 (2007).

921   34.   W. Bialek, Physical limits to sensation and perception. *Annu. Rev. Biophys. Biophys.*
922   *Chem.* **16**, 455–478 (1987).

923   35.   P. A. Faure, R. R. Hoy, The sounds of silence: cessation of singing and song pausing are
924   ultrasound-induced acoustic startle behaviors in the katydid *Neoconocephalus ensiger*
925   (Orthoptera; Tettigoniidae). *J. Comp. Physiol. A* **186**, 129–142 (2000).

926   36.   H. ter Hofstede, E. K. V Kalko, J. H. Fullard, Auditory-based defence against gleaning bats
927   in neotropical katydids (Orthoptera: Tettigoniidae). *J. Comp. Physiol. A* **196**, 349–358
928   (2010).

929   37.   J. F. C. Windmill, J. C. Jackson, E. J. Tuck, D. Robert, Keeping up with bats: dynamic
930   auditory tuning in a moth. *Curr. Biol.* **16**, 2418–2423 (2006).

931   38.   I. Geipel, E. Z. Lattenkamp, M. M. Dixon, L. Wiegrebe, R. A. Page, Hearing sensitivity: An
932   underlying mechanism for niche differentiation in gleaning bats. *Proc. Natl. Acad. Sci. U.*
933   *S. A.* **118** (2021).

934   39.   J. H. Fullard, External auditory structures in two species of neotropical notodontid moths.
935   *J. Comp. Physiol. A* **155**, 625–632 (1984).

936   40.   R. Heinrich, M. Jatho, K. Kalmring, Acoustic transmission characteristics of the tympanal
937   tracheae of bushcrickets (Tettigoniidae). II: Comparative studies of the tracheae of seven
938   species. *J. Acoust. Soc. Am.* **93**, 3481–3489 (1993).

939   41.   W. J. Bailey, R. O. Stephen, P. Yeoh, Signal transmission in noisy environments: Auditory
940   masking in the tympanic nerve of the bushcricket *Metaballus litus* (Orthoptera:

941   Tettigoniinae). *J. Acoust. Soc. Am.* **83**, 1828–1832 (1988).

942   42.   J. H. Fullard, Acoustic relationships between tympanate moths and the Hawaiian hoary
943   bat (*Lasiurus cinereus semotus*). *J. Comp. Physiol. A* **155**, 795–801 (1984).

944   43.   F. A. Sarria-S, B. D. Chivers, C. D. Soulsbury, F. Montealegre-Z, Non-invasive biophysical
945   measurement of travelling waves in the insect inner ear. *R. Soc. Open Sci.* **4**, 1–11
946   (2017).

947   44.   W. J. Bailey, The tettigoniid (Orthoptera□: Tettigoniidae) ear: Multiple functions and
948   structural diversity. *Int. J. Insect Morphol. Embryol.* **22**, 185–205 (1993).

949   45.   K. Rajaraman, *et al.*, Low-pass filters and differential tympanal tuning in a paleotropical
950   bushcricket with an unusually low frequency call. *J. Exp. Biol.* **216**, 777–787 (2013).

951   46.   A. Vavakou, J. Scherberich, M. Nowotny, M. van der Heijden, Tuned vibration modes in a
952   miniature hearing organ: Insights from the bushcricket. *Proc. Natl. Acad. Sci. U. S. A.* **118**,
953   e2105234118 (2021).

954   47.   B. Lewis, The physiology of the Tettigoniid ear. *Methods*, 861–869 (1974).

955   48.   R. Arlettaz, M. Ruedi, J. Hausser, Ecologie trophique de deux espèces jumelles et
956   sympatriques de chauves-souris: *Myotis myotis* et *Myotis blythi* (Chiroptera□:
957   Vespertilionidae). Premiers résultats: **57**, 519–532 (1993).

958   49.   R. K. LaVal, M. L. LaVal, Prey selection by the slit-faced bat *Nycteris thebaica* (Chiroptera:
959   Nycteridae) in Natal, South Africa. *Biotropica* **12**, 241–246 (1980).

960   50.   G. Davison, A. Zubaid, Food habits of the Lesser false vampire, *Megaderma spasma*,
961   from Kuala Lompat, Peninsular Malaysia. *Z. Säugetierkd.* **57**, 310–312 (1992).

962   51.   M. B. Fenton, R. O. Museum., Observations on the biology of some Rhodesian bats:
963   Including a key to the Chiroptera of Rhodesia (Royal Ontario Museum, 1975).

964   52.   J. O. Whitaker, H. Black, Food habits of cave bats from Zambia, Africa. *J. Mammal.* **57**,
965   199–204 (1976).

966   53.   H. Raghuram, R. Deb, D. Nandi, R. Balakrishnan, Silent katydid females are at higher risk
967   of bat predation than acoustically signalling katydid males. *Proc. R. Soc. B Biol. Sci.* **282**,
968   20142319 (2015).

969   54.   L. Zhang, *et al.*, Diet of Flat-Headed Bats, *Tylonycteris pachypus* and *T. robustula*, in
970   Guangxi, South China. *J. Mammal.* **86**, 61–66 (2005).

971   55.   E. R. Buchler, S. B. Childs, Orientation to distant sounds by foraging big brown bats
972   (*Eptesicus fuscus*). *Anim. Behav.* **29**, 428–432 (1981).

973   56.   O. E. Murillo G, M. J. Bedoya, J. H. Velandia-Perilla, A. P. Yusti-Muñoz, Riqueza de
974   especies, nuevos registros y actualización del listado taxonómico de la comunidad de
975   murciélagos del Parque Nacional Natural Gorgona, Colombia . *Rev. Biol. Trop.* **62**, 407–
976   417 (2014).

57.   J. J. Belwood, G. K. Morris, Bat predation and its influence on calling behavior in

neotropical katydids. *Science.* **238**, 64–67 (1987).

58.   J. J. Belwood, "Anti-Predator Defences and Ecology of Neotropical Forest Katydids,
Especially the Pseudophyllinae" in *The Tettigoniidae. Biology, Systematics and Evolution*,
W. J. Bailey, D. Rentz, Eds. (Springer-Verlag, 1990), pp. 8–26.

59.   D. A. Nickle, J. L. Castner, Strategies utilized by katydids (Orthoptera: Tettigoniidae)
against diurnal predators in rainforests of northeastern Peru. *J. Orthoptera Res.* **4**, 75
(1995).

60.   H. ter Hofstede, *et al.*, Revisiting adaptations of neotropical katydids (Orthoptera:
Tettigoniidae) to gleaning bat predation. *Neotrop. Biodivers.* **3**, 41–49 (2017).

61.   F. Montealegre-Z, F. A. Sarria, M. C. Pimienta, A. C. Mason, Lack of correlation between
vertical distribution and carrier frequency, and preference for open spaces in arboreal
katydids that use extreme ultrasound, in Gorgona, Colombia (Orthoptera: Tettigoniidae).
Rev. Biol. Trop. **62**, 289 (2014).

62.   J. Rheinlaender, H. Römer, Insect hearing in the field. *J. Comp. Physiol. A* **158**, 647–651
(1986).

63.   R. H. Wiley, D. G. Richards, Physical constraints on acoustic communication in the
atmosphere: Implications for the evolution of animal vocalizations. *Behav. Ecol. Sociobiol.*
3, 69–94 (1978).

64.   H. Römer, Environmental and biological constraints for the evolution of long-range
signalling and hearing in acoustic insects. *Philos. Trans. R. Soc. London. Ser. B Biol. Sci.*
340, 179–185 (1993).

65.   D. C. Rentz, Two new katydids of the genus Melanonotus (*Melanonotus powellorum*) from
Costa Rica with comments on their life history strategies (Tettigoniidae: Pseudophyllinae).
Entomol. News (1975).

66.   G. K. Morris, M. Beier, Song structure and description of some Costa Rican katydids (
Orthoptera☐: Tettigoniidae) Author (s): Glenn K . Morris and Max Beier Source☐:
Transactions of the American Entomological Society (1890-) , Mar . - Jun ., 1982 ,
Published by☐: American E. **108**, 287–314 (1982).

67.   G. K. Morris, A. C. Mason, P. Wall, J. J. Belwood, High ultrasonic and tremulation signals
in neotropical katydids (Orthoptera: Tettigoniidae). *J. Zool.* **233**, 129–163 (1994).

68.   K. G. Heller, Acoustic signalling in palaeotropical bushcrickets (Orthoptera: Tettigonioidea:
Pseudophyllidae): does predation pressure by eavesdropping enemies differ in the
Palaeo- and Neotropics? *J. Zool.* **237**, 469–485 (1995).

69.   D. J. Robinson, M. J. Hall, Sound signalling in orthoptera. *Adv. In Insect Phys.* **29**, 151–
278 (2002).

70.   I. Geipel, *et al.*, Predation risks of signalling and searching: Bats prefer moving katydids.
Biol. Lett. **16**, 3–7 (2020).

71.   R. Page, X. E. Bernal, The challenge of detecting prey: Private and social information use
in predatory bats. *Funct. Ecol.* **34**, 344–363 (2020).

72.   J. J. Falk, *et al.*, Sensory-based niche partitioning in a multiple predator-multiple prey
1018   community. *Proc. R. Soc. B Biol. Sci.* **282** (2015).

1019   73.   I. Geipel, *et al.*, Bats actively use leaves as specular reflectors to detect acoustically
1020   camouflaged prey. *Curr. Biol.* **29**, 2731-2736.e3 (2019).

1021   74.   I. Geipel, K. Jung, E. K. V. Kalko, Perception of silent and motionless prey on vegetation
1022   by echolocation in the gleaning bat *Micronycteris microtis. Proc. R. Soc. B Biol. Sci.* **280**,
1023   20122830 (2013).

1024   75.   N. Yoh, P. Syme, R. Rocha, C. F. J. Meyer, A. López-Baucells, Echolocation of central
1025   Amazonian 'whispering' phyllostomid bats: Call design and interspecific variation. *Mammal*
1026   *Res.* **65**, 583–597 (2020).

1027   76.   J. Schul, A. C. Patterson, What determines the tuning of hearing organs and the
1028   frequency of calls? A comparative study in the katydid genus *Neoconocephalus*
1029   (Orthoptera, Tettigoniidae). *J. Exp. Biol.* **206**, 141–152 (2003).

1030   77.   J. A. Deily, J. Schul, Spectral selectivity during phonotaxis: A comparative study in
1031   *Neoconocephalus* (Orthoptera: Tettigoniidae). *J. Exp. Biol.* **209**, 1757–1764 (2006).

1032   78.   F. A. Sarria-S, G. K. Morris, J. F. C. Windmill, J. Jackson, F. Montealegre-Z, Shrinking
1033   wings for ultrasonic pitch production: Hyperintense ultra-short-wavelength calls in a new
1034   genus of neotropical Katydids (Orthoptera: Tettigoniidae). *PLoS One* **9**, e98708 (2014).

1035   79.   R. O. Y. E. Plotnick, D. M. Smith, Exceptionally preserved fossil insect ears from the
1036   Eocene Green River formation of Colorado. *J. Paleontol.* **86**, 19–24 (2012).

1037   80.   D. E. Greenwalt, J. E. S. Rust, A new species of *Pseudotettigonia Zeuner* (Orthoptera:
1038   Tettigoniidae) with an intact stridulatory field and reexamination of the subfamily
1039   Pseudotettigoniinae. *Syst. Entomol.* **39**, 256–263 (2014).

1040   81.   J. Rust, A. Stumpner, J. Gottwald, Singing and hearing in a Tertiary bushcricket. *Nature*
1041   **399**, 650 (1999).

1042   82.   E. C. Teeling, *et al.*, A molecular phylogeny for bats illuminates biogeography and the
1043   fossil record. *Science.* **307**, 580–584 (2005).

1044   83.   J. D. Mugleston, H. Song, M. F. Whiting, A century of paraphyly: a molecular phylogeny of
1045   katydids (Orthoptera: Tettigoniidae) supports multiple origins of leaf-like wings. *Mol.*
1046   *Phylogenet. Evol.* **69**, 1120–1134 (2013).

1047   84.   J. D. Mugleston, M. Naegle, H. Song, M. F. Whiting, A comprehensive phylogeny of
1048   Tettigoniidae (Orthoptera: Ensifera) reveals extensive ecomorph convergence and
1049   widespread taxonomic incongruence. *Insect Syst. Divers.* **2** (2018).

1050   85.   E. S. Schneider, H. Römer, T. Robillard, A. K. D. Schmidt, Hearing with exceptionally thin
1051   tympana: Ear morphology and tympanal membrane vibrations in eneopterine crickets. *Sci.*
1052   *Rep.* **7**, 1–12 (2017).

1053   86.   N. Vicente, *et al.*, In and out of the Neotropics: historical biogeography of Eneopterinae
1054   crickets. *J. Biogeogr.* **44**, 2199–2210 (2017).

87.   R. R. Hoy, "The Evolution of Hearing in Insects as an Adaptation to Predation from Bats
BT - The Evolutionary Biology of Hearing" in D. B. Webster, A. N. Popper, R. R. Fay, Eds.
(Springer New York, 1992), pp. 115–129.

88.   H. Song, *et al.*, Phylogenomic analysis sheds light on the evolutionary pathways towards
acoustic communication in Orthoptera. *Nat. Commun.* **11**, 4939 (2020).

89.   H. M. ter Hofstede, *et al.*, Calling songs of neotropical katydids (Orthoptera: Tettigoniidae)
from Panama. *J. Orthoptera Res.* **29**, 137–201 (2020).

90.   A. B. Lang, H. Römer, Roost site selection and site fidelity in the neotropical katydid
Docidocercus gigliotosi (Tettigoniidae). *Biotropica* **40**, 183–189 (2008).

91.   C. Woodrow, C. Pulver, D. Veitch, F. Montealegre-Z, Bioacoustic and biophysical analysis
of a newly described highly transparent genus of predatory katydids from the Andean
cloud forest (Orthoptera: Tettigoniidae: Meconematinae: Phlugidini). *Bioacoustics* **30**, 93–
109 (2019).

92.   J. H. Fullard, G. K. Morris, A. C. Mason, Auditory processing in the black-sided meadow
katydid *Conocephalus nigropleurum* (Orthoptera: Tettigoniidae). *J. Comp. Physiol. A* **164**,
501–512 (1989).

93.   N. C. E. Harness, T. Campbell, Acoustic ranging in meadow katydids: female preference
for attenuated calls. *Bioacoustics*, 1–10 (2021).

94.   H. Romer, J. Lewald, High-frequency sound transmission in natural habitats: Implications
for the evolution of insect acoustic communication. *Behav. Ecol. Sociobiol.* **29**, 437–444
(1992).

95.   Comsol, COMSOL Multiphysics. www.comsol.com.

96.   R. Courant, K. Friedrichs, H. Lewy, On the partial difference equations of mathematical
physics. *IBM J. Res. Dev.* **11**, 215–234 (1967).

97.   R. Lenth, M. R. Lenth, Package 'lsmeans.' *Am. Stat.* **34**, 216–221 (2018).

98.   R. C. Team, R: A language and environment for statistical computing (2021).

99.   A. Kuznetsova, P. B. Brockhoff, R. H. B. Christensen, lmerTest Package: Tests in Linear
Mixed Effects Models. *J. Stat. Software; Vol 1, Issue 13* (2017).

 Figures and Tables

1085
1086 **Figure 1.** The ear of *Copiphora gorgonensis. **A.*** Location of the ear in the foreleg. ***B.*** 3D anatomy

1087 of the ear, with pinnae present; ***C***. 3D anatomy of the following pinnae ablation, with the volume

1088 of the subslit cavities exhibited (light blue); ***D***. 3D model of only the subslit cavities.

1089

Figure 2. The effect of pinnae in the time domain and numerical simulations. *A*. Time plots from five incidence angles for the 60 kHz test sound illustrating changes in oscillation phase between the anterior (ATM, in red) and posterior (PTM, in blue) tympana of the same ear. Notice the phase difference of 0.25 cycles is 90° at -10° and 10°. An anatomical cross section of the ear is shown with each tympanum (ATM and PTM), auditory vesicle (AV), posterior and anterior bifurcated tracheal branches (PT and AT), haemolymph channel (HC) and posterior and anterior pinnal structures (PP and AP). *B*. Mean displacement amplitudes (nm) of the tympanic

membranes for each tested frequency (23, 40 and 60 kHz) with and without the presence of

cuticular pinnae ($n = 9$ ears). *C*. Cavity induced pressure gains with pinnae compared to sound

pressure (Pa) predictions with the pinnae ablated from numerical models using Comsol

Multiphysics (17 ears; 10 females, 7 males). For means comparison plots (*B* & *C*), significance

symbols from post hoc analyses: '***' 0.001, '**' 0.01, '*' 0.05, 'ns' 0.1, and ' ' 1. grey bars with

cuticular pinnae and black bars without cuticular pinnae showing standard error.

1104

1105

Figure 3. Acoustic experiments with 3D printed scaled ear models. *A*. Sound pressure gains (dB

SPL) of 3D printed ears calculated from scaled time domain recordings for 23, 40, 60 and 110

kHz 4-cycle pure tones. *B.* An example of a 3D printed ear model with pinnae present (dorsal

view) showing the probe microphone inside the PTM. *C*. An example of a 3D printed ear model

with pinnae ablated (anterior lateral view), showing probe microphone placement.

1116
Figure 4. Sound pressure gains measured by numerical simulations of sound capture in the
pinnae cavities (using COMSOL Multiphysics) and experimentally using printed 3D-scaled ear
geometries. Panels *A*, *C*, and *E* depict cavity induced sound pressure distribution and gains with
pinnae, panels *B*, *D*, and *F* represent sound pressure gains without the pinnae. *A* and *B*. Cross –
section of the ear of *Copiphora gorgonensis* with the pinnal structures intact (*A*) and ablated (*B*).

Sound pressure intensities depicted with colours for simulations of 23, 40, 60 and 110 kHz. Low

sound pressure dB (blue) to high sound pressure dB (red) distributions inside and outside the

cavities. *C* and *D* are plots of simulated sound pressure gains (dB SPL) in the frequency ranges

of 20 to 150 kHz for each tympanum. *E* and *F* are plots of relative dB gain of the tympanal

cavities in the 3D printed ears. ATM in red and PTM in blue.

1127

Figure 5. Tympanal tuning, behavioural and neural audiograms of *Copiphora gorgonensis*. **A.** Vibrational responses to broadband chirps (20 to 120 kHz) of real tympanal membranes ($n = 7$; 14 ears; four males and three females) of live *C. gorgonensis*. Maxima resonance peaks at 107.84 ± 3.74 kHz for the PTM and 111.13 ± 4.24 kHz for the ATM. Blue bar for PTM and red bar for ATM. **B**. Black outline with grey shadow indicate the behavioural audiogram of ultrasound response in nine female *C. gorgonensis*. Black outline shows mean vector of SPL response at a particular frequency, shaded area represents the standard deviation across measured SPL. **C**. Neural audiogram showing electrical activity in extracellular recordings of the auditory nerve during sound stimulation as sound pressure intensity (dB SPL) and sound frequency (kHz) are systematically altered. The coloured mesh shows the mean neuronal activity during the presentation of sound, and the grey mesh the mean neuronal activity during silent inter-pulse intervals. White symbols indicate a significant difference ($P < 0.05$) in paired t-tests comparing the sound-on and sound-off responses in each katydid tested; black symbols indicate a non-significant difference ($n = 5$). A strong neuronal response is apparent across a wide range of frequencies including to calling song (23 kHz) and to the high ultrasonic frequencies used by hunting bats (e.g., 100 kHz).

1147
Figure 6. Ecological relevance of pinnae in *Copiphora gorgonensis*. Sound pressure level gains

(left) induced by the pinnae are present only at frequencies above c.a. 50 kHz, covering the range

of echolocation frequencies of three native insectivorous gleaning bat species. The conspecific

call of *C. gorgonensis* (dominant frequency and harmonics) on the other hand (dB$_{peak}$ at 23 kHz),

is not enhanced by the presence of the pinnae (dB loss). Dotted line indicates the frequency at

which gain = 0 dB. Spectrogram parameters: FFT size 512, Hamming window, 50% overlap;

frequency resolution: 512 Hz, temporal resolution: 0.078 ms.

1155
1156