Proteogenomics: an analysis of how and when it enhances proteomics

Laura Fancello[1] and Thomas Burger[1]

[1] *Univ. Grenoble Alpes, CNRS, CEA, Inserm, Profi FR2048, Grenoble, France.*

ABSTRACT

Background: Proteogenomics aims to identify variant or unknown proteins in bottom-up proteomics, by searching transcriptome- or genome-derived custom protein databases. However, empirical observations reveal that these large proteogenomic databases produce lower-sensitivity peptide identifications. Various strategies have been proposed to avoid this, including the generation of reduced transcriptome-informed protein databases (*i.e.*, built from reference protein databases only retaining proteins whose transcripts are detected in the sample-matched transcriptome), which were found to increase peptide identification sensitivity. Here, we present a detailed evaluation of this approach.

Results: First, we established that the increased sensitivity in peptide identification is in fact a statistical artifact, directly resulting from the limited capability of target-decoy competition to accurately model incorrect target matches when using excessively small databases. As anti-conservative FDRs are likely to hamper the robustness of the resulting biological conclusions, we advocate for alternative FDR control methods that are less sensitive to database size. Nevertheless, reduced transcriptome-informed databases are useful, as they reduce the ambiguity of protein identifications, yielding fewer shared peptides. Furthermore, searching the reference database and subsequently filtering

proteins whose transcripts are not expressed reduces protein identification ambiguity to a

similar extent, but is more transparent and reproducible.

Conclusion: In summary, using transcriptome information is an interesting strategy that

has not been promoted for the right reasons. While the increase in peptide identifications

from searching reduced transcriptome-informed databases is an artifact caused by the use

of an FDR control method unsuitable to excessively small databases, transcriptome

information can reduce ambiguity of protein identifications.

Keywords [3-10]: proteogenomics, proteomics, transcriptome-informed protein

databases, peptide identification sensitivity, protein identification ambiguity, FDR control,

target-decoy competition

BACKGROUND

The term "proteogenomics" originally referred to the use of proteomics to enhance

genome annotation, by inferring coding genomic regions based on evidence from mass-

spectrometry-based proteomics[1]. Nowadays, it more broadly indicates the combined

analysis of genomics and/or transcriptomics with proteomics for a broad spectrum of

applications: from the study of gene expression regulation at transcript and protein level, to

the identification of cancer-specific protein variants[2,3]. Most importantly, proteogenomics

represents an attractive strategy to enhance proteomics in two main ways: *i.* improving

protein inference; *ii.* improving database searches for peptide identification.

Protein inference is a central issue in proteomics, given the presence of shared

peptides. These peptides might originate from different proteins sharing homology; or from

distinct proteoforms due to alternative mRNA splicing, post-translational modifications,

proteolytic cleavages, and/or allelic variants. Indeed, for experimental reasons, in bottom-up mass-spectrometry-based proteomics – the most widely used proteomic approach – peptide-protein connectivity is lost and protein identifications must be inferred from peptide identifications. Traditionally, the issue of protein inference was addressed using simple heuristics, such as the two-peptide rule (proteins must be identified by at least two peptides) or the parsimony principle (the smallest subset of proteins which can explain most or all peptides is retained)[4,5]. Later, more refined probability-based approaches were developed, which model shared peptide mapping to their parent proteins[6–9]. Most commonly, when proteins cannot be distinguished based on peptide identifications (*i.e.,* they are identified by an identical set of peptides) they are reported as a protein group. This complicates comparisons between distinct experiments and protein quantification. In this context, proteogenomics can enhance protein inference using evidence from transcript expression: in particular, some Bayesian approaches have been developed based on this strategy[10–12]. The other main contribution of proteogenomics to proteomics relates to refinements of the reference protein databases used for peptide identification. Classically, peptides produced by bottom-up proteomics are identified by matching their experimentally-measured mass spectra against theoretical spectra for all candidate peptides contained in a user-selected reference protein database. The underlying assumption is that the database exhaustively and accurately describes all of the protein sequences present in the sample. However, this assumption may be unrealistic for two reasons. First, reference databases only contain canonical – experimentally-validated or predicted – protein sequences, but other variants or isoforms may be present, especially in tumor samples. Second, one may simply lack a reference protein database for less studied organisms for which scarce or no genomic annotation is available. In the first case, more exhaustive protein databases including undocumented or variant peptides can be

generated by appending variant sequences from public genomic repositories (*e.g.*,

COSMIC or dbSNP) to the reference database[13–15] or adding sample-specific variants

identified from matched transcriptomes or genomes. In the second case, protein

databases can be generated by 6-frame translation of the genome or sample-matched

transcriptome[16,17]. A major downfall of these proteogenomic databases is that they tend to

be very large. Searching very large databases comes at a considerable computational

cost, and complicates the task of discriminating between correct and incorrect matches. In

particular, various studies have shown that when using target-decoy competition (TDC) for

FDR control on large database searches, fewer peptides are identified at the same FDR

level. This contrasts starkly with the initial reason for the development of

proteogenomics[18–20]. To avoid reducing the number of identifications, it was proposed that

FDR validation of canonical and novel peptides should be performed separately, and that

post-search filters or machine-learning methods should be applied to increase confidence

in the newly-identified peptides[13–15,21,22]. In addition, various strategies were adopted to limit

the size of databases generated by proteogenomics. When possible, 6-frame genome

translation was replaced by translation of candidate ORFs identified by gene prediction

algorithms. Alternatively, sample-specific variants from matched sequencing were

preferentially added to the reference database rather than variant sequences from

COSMIC or dbSNP[23–25]. In some studies, after appending variants identified from

sequencing data, the reference database was reduced to contain only proteins for which

transcripts were detected by transcriptomics, since according to the "central dogma of

biology", there can be no protein without the corresponding transcript[26–28]. Yet other groups

proposed to generate reduced transcriptome-informed protein databases by barely

reducing the reference database to proteins for which transcripts were detected, without

including any novel sequences[26,28,29]. The only declared objective of this approach is to

increase the sensitivity of identification of known sequences. Indeed, the authors claim that

searching such reduced transcriptome-informed databases can increase the number of

valid identifications. A strategy was also proposed to optimize the balance between

identifications lost due to the incompleteness of an excessively reduced database and

additional identifications made from searches of reduced transcriptome-informed

databases, so as to maximize the number of valid identifications[30].

However, in all these studies: *i.* Only limited attention was given to the mechanistic

explanation for the increased number of peptides identified searching smaller databases;

ii. Little is known about how reduced transcriptome-informed database searches affect

protein inference in terms of ambiguity of protein identification and shared peptide

assignments. Therefore, in this article, we investigated the use of reduced transcriptome-

informed sample-specific protein databases, focusing on these two methodological

aspects. Our investigations led to three conclusions. First, the reported increase in the

number of identifications obtained by searching a reduced transcriptome-informed

database is a statistical artifact: it is simply the spurious consequence of an

underestimated FDR, which results from the sensitivity of TDC to database size (also

reported in [31]). In other words, reducing the size of the database searched to increase

sensitivity broadly amounts to validating peptide identifications at a higher-than-reported

FDR. This observation consequently raises questions as to the validity of peptides that are

only identified when searching the reduced database, and as to cross-study comparability.

However, searching reduced transcriptome-informed protein databases followed by

accurate FDR control remains nonetheless an interesting strategy, as it decreases the

ambiguity of protein identifications by reducing the proportion of shared peptides and the

size of protein groups. Finally, searches against the reference database followed by post-

hoc filtering of proteins for which there is no evidence of transcript expression provides

comparable proteomic identifications to searches against the reduced transcriptome-based

database. This strategy guarantees better transparency and comparability between

studies. To facilitate use of this search strategy, we produced an R code to perform post-

hoc filtering on proteomic identifications based on transcript evidence that also allows

manual inspection of protein identifications and shared peptide assignments within protein

groups of interest while also providing information on transcript expression.

RESULTS

Reduced transcriptome-informed database search does not increase sensitivity if FDR is accurately controlled

To investigate how searching reduced transcriptome-informed protein databases

affects proteomic identifications, we used two human samples (hereafter referred to as

Jurkat and Lung) for which matched transcriptome and proteome data were publicly

available (**Additional File 1: Table S1**). For each of them, we built a sample-specific

reduced transcriptome-informed protein database, as follows. First, we processed

transcriptome datasets and identified the set of transcripts expressed in each sample

using StringTie, a common transcriptome assembly method (see "Transcriptome analysis"

in Methods). Then, we generated reduced databases for use in MS/MS searches by

retaining from the Ensembl human protein database only proteins for which transcripts

were expressed in the sample-matched transcriptome (see "Construction of reduced

transcriptome-informed protein databases for MS/MS searches" in Methods) (**Figure 1A-**

B). We compared valid peptide-spectrum matches (PSMs) obtained from the MS/MS

search against the whole Ensembl human database (referred to as the "full database") or

against the sample-specific reduced database (referred to as the "reduced database") at

1% FDR, as estimated by TDC. In agreement with previous studies[26,28,30], we found that a

few spectra and peptides identified in the full database were lost when searches were

performed against the reduced database ("lost in reduced DB"), whereas others were only

identified in the reduced database search ("additional in reduced DB") (**Figure 1C**). Lost

identifications are due to incompleteness of the reduced database. Indeed, even more

identifications were lost when using a further reduced protein database, such as that

generated on the basis of the smaller set of expressed transcripts identified by Cufflinks,

an alternative method of transcriptome assembly (**Additional File 2: Fig. S1**). Additional

identifications, in contrast, are commonly ascribed to increased sensitivity of MS/MS

searches when using smaller databases, such as reduced transcriptome-informed protein

databases[26,28,30]. In this study, we investigated the origin of these additional identifications

more thoroughly. To do so, we performed a detailed comparison of all (target or decoy)

PSMs retained from the full and reduced database searches, after applying validation

prefilters (*i.e.*, single best-scoring PSM for each spectrum, minimum peptide length of 7

amino acids), but before filtering at 1% FDR (**Figure 1A**). Since the reduced database was

constructed as a simple subset of the Ensembl human database and considered only a

single best-scoring peptide for each spectrum (see "Proteome analysis" in Methods), we

could easily map each spectrum match between the two searches. Two interesting

observations emerged from this comparison.

First, several spectra were reallocated in the reduced database (*i.e.*, assigned to different

matches in the reduced database and the full database). This phenomenon occurred when

the peptide match from the full database was not present in the reduced database.

However, the PSM score was never higher in the reduced database. At best, it was equal

(data points on the diagonal, **Figure 2A, Additional File 2: Fig. S2A**) to the score

obtained in the full database, but for the most part it was lower (**Figure 2B**, **Additional File 2: Fig. S2B**). Therefore, additional identifications in the reduced database do not come from an improved search score. For the sake of clarity, we emphasize that the few spectra which matched only sequences in the reduced database (indicated as "no match, target" or "no match, decoy" in **Figure 2A, Additional File 2: Fig. S2A, S3A, S4, and S5**) do not contradict this observation; they can all be explained by reallocation and the prefilters applied for validation (**Additional File 2: Fig. S3B,** see **Additional File 3: Supplementary Note 1** for a detailed explanation).

The second main observation was that the score cutoff estimated by TDC at 1% FDR (*i.e.*, the score defining the set of accepted PSMs, while respecting the constraint that less than 1% of them are expected to be false discoveries) was lower for the reduced database than for the full database search (**Figure 2A, Additional File 2: Fig. S2A**). Consequently, for a few spectra no match was validated after FDR control in the full database, whereas, at a lower or at most equal score, the match was validated in the reduced database search (pointed out by the arrow in **Figure 2A** and **Additional File 2: Fig. S2A**). This clearly explains why these PSMs are accounted for as additional identifications in the reduced database search. We also observed a few reallocations, which can likewise yield additional spectra and/or peptide identifications in the reduced database search. These cases are, in particular, reallocations from non-target matches in the full database to target matches in the reduced database search (2.9% and 1.9% of all spectra for Jurkat and Lung, respectively) and reallocations between different target matches (3.2% and 2.7% of all spectra for Jurkat and Lung, respectively) (**Figure 2A,C and Additional File 2: Fig. S2A,C**). However, only a minority of these reallocations are valid identifications when applying 1% FDR control (*i.e.*, pass the score cutoff for FDR control from the reduced database search) (**Figure 2C, Additional File 1: Table S2, Additional File 2: Fig. S2C**).

Furthermore, even fewer of them would pass the cutoff determined for the full database

search, and they are hereafter referred to as "pure reallocations" to indicate that additional

identifications from these PSMs originate solely from reallocation and they do not

represent additionally validated PSMs due to the lower cutoff for 1% FDR validation in the

reduced database (**Figure 2C, Additional File 1: Table S2, Additional File 2: Fig. S2C**

and S6A). Additional peptide identifications originating from either a lower cutoff for FDR

control or from pure reallocations had lower PSM scores compared to peptides identified in

both database searches (**Additional File 2: Fig. S6B**). For pure reallocations, the

difference in score between the full and reduced database match was sometimes quite

large, especially for target PSMs in the full database that were reallocated in the reduced

database search (**Additional File 2: Fig. S6C**). Furthermore, additional peptide

identifications only allowed 6 and 8 supplementary protein identifications (*i.e.*, protein

groups for which protein members were not identified in the full database search) in the

Jurkat and Lung samples, respectively (**Additional File 1: Table S3**). Thus, these

additional identifications are of lower quality and provide little benefit in terms of protein

identification.

Overall, only a small number of additional identifications were obtained thanks to pure

reallocations; they were mainly obtained due to the lower cutoff for FDR control in the

reduced database. Thus, the lower cutoff explained 98.6% (n=3,147) and 95.2% (n=1,875)

of additional spectral identifications and 96.5% (n=5,560) and 77.5% (n=1,524) of

additional peptide identifications for the Jurkat and Lung samples, respectively (**Figure 2D-**

E, Additional File 2: Fig. S2D-E). We next investigated the reasons why lower cutoffs

were observed at a same FDR threshold in the reduced databases. To do so, we first

simulated the outcome if the cutoff were instead equal to that of the full database (**Figure**

3A, Additional File 2: Fig. S7A). In these conditions, the proportion of valid decoys in the

reduced database search was observed to considerably decrease compared to the full

database, with a net loss of 38.4% of valid decoys in the Jurkat sample (**Figure 3B**) and

27.1% in the Lung sample (**Additional File 2: Fig. S7B**). Indeed, a significant fraction of

spectra matching valid decoys in the full database were assigned to invalid or non-decoy

matches in the reduced database, and were not counterbalanced by reallocations in the

other direction (*i.e.*, from invalid/non-decoy matches to valid decoys) (**Figure 3C,**

Additional File 2: Fig. S7C, S4, and S5). In contrast, the majority of spectra matching

valid targets in the full database matched the same valid target in the reduced database,

so that their loss was quite limited (**Figure 3C, Additional File 2: Fig. S7C**). Although

spectra matching valid decoys in the full database were reallocated much more frequently

in the reduced database than spectra matching valid targets, upon reallocation they

behaved similarly: few reallocations resulted in a valid match of the same type (**Figure 3C**,

Additional File 2: Fig. S7C), and the difference in score between full and reduced

database matches was comparable (**Additional File 2: Fig. S8A**). Hence, the proportion

of valid decoys lost in the reduced database was higher than that of targets lost, simply

because a higher proportion of decoys was reallocated. This observation can easily be

explained by how the reduced database was generated: only proteins whose transcript is

expressed, thus those more likely to be present, were retained from the canonical full

protein database. Therefore, all valid targets from the full database are theoretically still

present in the reduced database, but the same cannot be said for decoys, that by

definition represent random matches (**Additional File 2: Fig. S8B**). The lower cutoff

obtained by TDC for the reduced database allows a few more decoys to be validated and

thus recovers the proportion of valid decoys required to declare a nominal FDR level of 1%

(**Figure 3B, Additional File 2: Fig. S7B**). We suggest that the additional identifications

validated at a lower cutoff in the reduced database are simply a byproduct of the known

influence of database size on TDC[31], rather than evidence of increased sensitivity when searching reduced databases. Naturally, in the absence of a benchmark, it is impossible to determine whether these identifications represent correct matches that were missed in the full database due to FDR overestimation, or incorrect matches that were accepted in the reduced database due to FDR underestimation. Nevertheless, three main observations indicate that they should at least be considered with caution. First, these matches were accepted in the reduced database at quite low scores, meaning that, in any case, they represent low-quality spectra that cannot be identified with any great confidence. Second, it could be assumed that additional identifications arise due to the removal, in the reduced database, of high-scoring decoys that out-compete correct target matches, thus reducing sensitivity. However, in our study, most of the additional identifications did not represent reallocations from decoys to targets; rather, they consisted in the same PSMs that were accepted at 1% FDR only in the reduced database due to the lower score cutoff applied (**Figure 2D-E; Additional File 2: Fig. S2D-E**). Third, and most importantly, the artifactual origin of the additional identifications, given TDC sensitivity to database size, is supported by the comparison between the behavior of TDC and of the Benjamini-Hochberg (BH) procedure for FDR control[32]. The BH procedure is known to yield a conservative and stable FDR control, and it was recently successfully applied to peptide identification[31]. In particular, TDC was found to be less conservative and less stable than BH with respect to preliminary filters on precursor mass accuracy: at a narrower mass tolerance, fewer decoys were fair competitors for incorrect random matches, and consequently cutoffs were artificially lowered. Therefore, reducing the database size can similarly result in an insufficient number of decoys to accurately simulate incorrect target matches, thus leading to the observed lower cutoffs. To confirm this possibility, we applied the BH procedure to target-only database searches (see "Proteome analysis" in Methods). We obtained more

conservative score cutoffs and, most importantly, more stable with respect to database

size, compared to TDC and we confirmed this at various levels of FDR control (0.5%, 1%,

5%) (**Figure 3D, Additional File 2: Fig. S7D, S9A-B**). In line with this result, a much more

limited number of additional identifications was validated in the reduced database

searches when using the BH-based FDR control (**Additional File 2: Fig. S9C**). We also

employed the BH procedure for FDR control on concatenated target-decoy database

searches; while doing so is nonsensical from a practical data-processing viewpoint, from a

statistical methodology viewpoint, it simplifies comparisons between BH and TDC

stabilities. As expected, more conservative and stable score cutoffs were obtained with the

BH procedure (**Additional File 2: Fig. S9A-B)**.

Transcriptome information helps to reduce ambiguity of protein identifications

Although they do not enhance the sensitivity of peptide identifications, reduced

transcriptome-informed databases can still be of benefit in proteomics at the protein-

inference step, as they reduce the ambiguity of protein identifications. These databases

include fewer proteins – only the proteins which are most likely to be present given their

transcript expression – and it is reasonable to assume that with fewer possible protein

matches, we might obtain fewer shared peptides and smaller protein groups. Such a

decrease in protein group size has already been observed, but was either not discussed[33],

or was attributed to an additional number of identifiable peptides available for parsimony-

based protein inference[26]. We have already demonstrated that additional identifications

obtained when searching reduced databases actually derive from a flaw in TDC with

respect to the reduced database size, and how they can be largely avoided by applying

alternative FDR control procedures, such as BH. We will now show that straightforward

searches against reduced databases followed by BH-based FDR control nonetheless yield

smaller protein groups and less ambiguous protein identifications, thus regardless of

additional identifications or protein inference methods.

Concretely, we compared identifications obtained from the full or reduced database

searches followed by BH-based FDR control. The total number of identifications, at the

spectrum, peptide, and protein level, was comparable (**Figure 4A**). For the number of

protein-level identifications, we used the number of protein groups, as defined by the

Proline software. Protein groups include the unambiguous identification of a single protein

(single-protein groups) and groups of indiscernible proteins identified by the same sets of

peptides (multi-protein groups) (see "Proteome analysis" in Methods). Interestingly, the

proportion of single-protein groups was considerably higher for the reduced database

(**Figure 4B**), meaning that protein identifications were less ambiguous.

We further characterized the ambiguity of protein identifications using the graph's

connected components. Briefly, we first represented peptide-to-protein mappings on

bipartite graphs, with peptides and proteins as vertices and with edges featuring peptide-

to-protein membership: this representation provides an easy picturing of the complex

structures generated by shared peptides. Then, we calculated the connected components

(CCs), *i.e.*, the largest subgraphs in which any two vertices are connected to each other by

a path, and not connected to any of the other vertices in the supergraph. Proteins sharing

one or more peptides are thus gathered in the same CC (multi-protein CCs), whereas

unambiguous protein identifications are represented by CCs with a single protein vertex

(single-protein CCs) (**Figure 4C)**. As such, CCs constitute a peptide-centric strategy to

represent ambiguous protein identifications and their shared peptides, and should not be

confused with the classical protein-centric protein grouping strategy. We observed that,

while the total number of CCs obtained was comparable, there was a considerably higher

proportion of single-protein CCs in the graphs derived from the results of the reduced

database search. Along with the reduction in protein group size, this is further evidence of decreased protein identification ambiguity (**Figure 4D)**. Consistently, we also observed a greater proportion of specific peptides – and a correspondingly lower proportion of shared peptides – from the reduced database search (**Figure 4D)**. Within multi-protein CCs, the ratio between the number of protein members and the corresponding number of their encoding genes was also lower for the reduced database, suggesting that at least part of the initial ambiguity occurred between proteins encoded by different genes (**Figure 4E, Additional File 1: Table S4**). In addition to a decrease in protein identification ambiguity, our observations indicated that searches against reduced databases were associated with lower ambiguity at the PSM level, although to a lesser extent (see **Additional File 3: Supplementary Note 2, Additional File 2: Fig. S10**). Finally, we adopted an alternative strategy to enhance proteomics by transcriptomics, which consists in an MS/MS search against the full database, followed by post-hoc filtering to remove proteins for which the corresponding transcript was not expressed and no specific peptide was identified (**Figure 5A, Additional File 2: Fig. S11**). The driving principle was to remove ambiguous protein identifications not supported by specific peptides or by transcriptomics, and thus to reduce ambiguity resulting from shared peptides. Overall, we observed similar results to those obtained with reduced transcriptome-informed database searches and post-hoc filtering. First, a similar number of spectra and peptide identifications were obtained, comparable to that of the full database search (**Figure 5B**); second, these searches yielded a similarly increased proportion of single-protein CCs and specific peptides compared to full database searches (**Figure 5C**), indicating less ambiguous protein identifications. Post-hoc filtering is a transparent and easily interpretable approach, and we believe that it is highly suitable for use in studies seeking to enhance protein inference. While a few software tools already exist to generate reduced protein databases, we developed a specific toolbox of R scripts

345 to perform the post-hoc filtering described. This toolbox also allows very efficient

346 calculation of the CCs – which we have proposed as a means to quantify and compare

347 ambiguity of protein identifications –, visualization of CCs of interest, and their manual

348 inspection before and after post-hoc filtering.

DISCUSSION

In this article, we provide guidance for the mindful use of reduced transcriptome-

informed protein databases for MS/MS searches. This type of reduced database stems

from the attempt to counter excessive database inflation in proteogenomics studies, when

variant or novel proteoforms identified from sequencing data are added. Indeed, increased

database size complicates the task of discriminating between correct and incorrect

matches. When using TDC-based FDR control, inflated target databases come with an

inflated number of decoys, and consequently a higher probability of high-scoring decoy

matches. This has mainly been thought to reduce sensitivity of identifications in two ways.

First, decoy matches may score better than correct target matches, thus out-competing

them in spectrum-peptide assignment ("out-competing decoys") and resulting in a

decreased number of identifications. Second, decoys may have a higher probability of

matching than incorrect targets, which violates the so-called Equal Chance Assumption of

the TDC procedure and leads to an overestimated FDR, once again decreasing the

number of identifications. As the main *raison d'être* of proteogenomics is to maximize the

number of identifications, including variants or non-canonical peptides, much effort has

been expended to avoid loss of sensitivity linked to excessively large databases, for

example by reducing their size. While issues relating to the use of excessively large

databases have been abundantly discussed, fewer authors have pointed out that

excessively small databases may also be problematic, as they can also affect TDC

estimations[31,34,35]. With excessively small databases, TDC provides inaccurate FDR

estimates, as they can only be asymptotically accurate[34,36,37]. Furthermore, with too few

(high-scoring) decoys, the probability of matching a decoy might be lower than the

probability of matching an incorrect target, which once again violates the Equal Chance

Assumption, but leads in this case to FDR underestimation and to an artifactual increase in

identifications. In this study, we showed that the increased number of identifications

obtained by searching reduced transcriptome-informed protein databases is most likely a

statistical artifact due to the use of TDC on excessively small databases. We demonstrated

how TDC estimates a lower score cutoff for 1% FDR control on the reduced databases

compared to the full database search results. Consequently, some invalid PSMs in the full

database will be retained as valid additional identifications only in the reduced database.

We confirmed this observation at various levels of FDR control (0.5%, 1%, 5%) and for two

different human-derived samples – a tissue (Lung) and a cell line (Jurkat) – representing

different levels of proteomic complexity and coming with a different number of spectra.

Fewer spectra were available for the Jurkat sample, which, interestingly, also presented a

greater difference in score cutoffs between the full and reduced databases. Indeed, not

only reduced database sizes but also a smaller number of spectra is believed to affect the

ability of TDC to accurately estimate the FDR[34]. We suggest that additional identifications

obtained when searching such reduced databases are at least doubtful, and that it is

unwise to employ reduced transcriptome-informed protein databases in an attempt to

increase the number of identifications. Indeed, the additional identifications obtained had

quite low scores and did not result from removal of out-competing decoys, a known cause

of missed identifications in excessively large databases; rather, they represented identical

PSMs in the two database searches but that were only accepted in the reduced database

due to the lower score cutoff for the same level of FDR control. Most importantly, only a

negligible number of additional identifications was generated from the reduced database

search when using a method for FDR control that is known to be stable with respect to

database size, such as BH. Indeed, using BH, the score cutoffs estimated for the full and

reduced database searches, at the same level of FDR control, were almost identical. Thus,

the BH procedure constitutes an interesting alternative to TDC for stable FDR control

whatever the database size. However, many alternative approaches have been recently

developed to cope with the weaknesses of classical TDC[38–43]. It is important that

proteogenomics researchers use one of these alternatives to avoid risking the propagation

of statistical artifacts in their data. By doing so, they will no longer benefit from the

hypothetical sensitivity increment assumed up to now, but this seems to be the necessary

price to pay for rigorous control of the FDR.

Reduced transcriptome-informed protein databases are nonetheless useful in

bottom-up proteomics to reduce ambiguity in protein identifications due to the presence of

shared peptides. In particular, we showed that searching a reduced database yielded a

higher proportion of specific peptides and unambiguously identified proteins (*i.e.*, single-

protein CCs). Furthermore, the higher proportion of specific peptides and correspondingly

lower proportion of shared peptides has a positive impact on precision in relative protein

quantification. Indeed, when performing relative protein quantification, peptide abundances

are used as a proxy for the abundance of their parent protein. In this scenario, shared

peptides are difficult to handle, and since their relative abundance may depend on the

contribution of multiple proteins, they are frequently discarded. This strategy has a

downside, as it severely restricts the number of remaining quantifiable proteins – by

reducing it to proteins with at least one specific peptide – and the amount of information

available to estimate abundances – corresponding only to the number of specific

peptides. Therefore, a lower proportion of shared peptides represents more information

available for quantification.

Finally, we showed that full database searches followed by post-hoc filtering of

proteins for which no transcript is expressed provided comparable proteomic identifications

to reduced database searches. This filtering approach similarly reduced ambiguity of

protein identifications, while being more transparent and interpretable. We developed an R

code to implement this type of post-hoc filtering strategy. The code allows users to

visualize ambiguous protein identifications and their peptides via bipartite graphs, to prune

them based on transcript expression, and to manually inspect how this transcriptome-

based post-hoc filtering strategy reduces ambiguity. Ambiguous protein identifications are

represented and quantified using graph CCS, which constitute here subgraphs of proteins

connected by shared peptides. This representation provides the following advantages: it is

transparent, interpretable, non-redundant with respect to shared peptides, and

independent of any strategy developed to define protein groups.

Results from this study are of interest also beyond proteogenomics. Indeed,

database reduction is widely called for in proteomics, even though little attention is paid to

the limitations of TDC when using excessively small databases. For example, some

authors proposed to limit database size based on peptide detectability[30], and it has been

more generally claimed that "mass spectrometrists should only search for peptides they

care about"[44]. The statistical TDC artifacts observed with excessively small databases are

an issue that also affects multi-step search strategies implemented by some proteomics

search engines[45] or developed in metaproteomics[46,47]. Furthermore, the observation that

transcriptome information can help to decrease ambiguity in protein identification is

generally relevant in classical proteomics and even more so in metaproteomics, which has

to deal with an additional source of protein ambiguity: the presence of multiple organisms

in the same sample.

METHODS

Proteogenomic datasets description

Two samples for which matched transcriptome and proteome were publicly

available were analyzed: healthy lung tissue (referred to as Lung) and the Jurkat cell line

(referred to as Jurkat). The lung sample was from a dataset by Wang *et al.*[33], which

includes 29 histologically healthy human tissues generated to describe mRNA and protein

expression levels throughout the human body. The lung transcriptome dataset was

obtained by paired-end RNA sequencing on an Illumina HiSeq 2000/2500 system

generating 2×100 base-long reads. The matching proteome dataset was obtained by

quantitative label-free LC-MS/MS using an on-line nanoflow liquid chromatography system

coupled to a Q Exactive Plus mass spectrometer, operating in data-dependent mode.

Sample preparation included peptide fractionation via hSAX (hydrophilic strong anion)

chromatography. Raw transcriptome and proteome data were downloaded from the EBI

SRA (ArrayExpress accession: E-MTAB-2836; run accession: ERR315346) and the

ProteomeXchange (dataset identifier: PXD010154; sample identifier: P013163)

repositories, respectively.

The Jurkat cell line dataset was produced as part of a study by Sheynkman *et al.*[24]. The

Jurkat transcriptome dataset was obtained by paired-end RNA sequencing on an Illumina

HiSeq 2000 system generating 2×200 bases long reads. The matched proteome dataset

was obtained by quantitative label-free LC-MS/MS using a nanoAquity LC system

chromatography system coupled to a Velos-Orbitrap mass spectrometer, operating in data-

dependent mode. Sample preparation included peptide fractionation via high-pH LC

separation. Transcriptome and proteome raw data were downloaded from NCBI's Gene

Expression Omnibus (GEO; accession: GSE45428) and the PeptideAtlas repositories

(accession: PASS00215), respectively.

Transcriptome analysis

Raw reads were downloaded from public repositories and processed on the Galaxy

platform available at https://usegalaxy.org/[48] using common workflows for read

preprocessing and alignment to identify expressed transcripts (**Additional File 1: Table**

S5). First, sequencing adapters and low-quality (Phred score < 20) read ends were

trimmed off using TrimGalore

(https://www.bioinformatics.babraham.ac.uk/projects/trim_galore/), and reads shorter than

20 bp after trimming were discarded. Then, preprocessed reads were aligned against the

human reference genome (assembly GRCh38) by the splice-aware STAR aligner[49] in

default mode, using the Ensembl reference gene model for splice junctions. Only reads

mapped to a proper pair, and passing platform quality controls were retained. Reads

corresponding to optical or PCR duplicates were removed, as were non-primary and

supplementary alignments. Initially, two common strategies for transcriptome assembly

and quantification were applied: StringTie[50] and Cufflinks[51]. Both programs were run to

identify reference transcripts (and no novel transcripts), and two comparable sets of

expressed transcripts were obtained. Unless otherwise specified, StringTie output was

used for downstream analyses.

Construction of reduced transcriptome-informed protein databases for

MS/MS searches

For each sample, sample-specific protein databases were constructed for MS/MS search, containing only protein sequences for which the corresponding transcript is expressed in the sample. Briefly, sample-matched transcriptomes were processed as described above, and the subsets of transcripts expressed at FPKM>1 were identified according to the StringTie or Cufflinks algorithms for transcript assembly and quantification. Then, the human GRCh38 Ensembl protein database was filtered to only retain proteins for which the corresponding transcript is expressed in the sample. For each sample, two sample-specific reduced versions of the Ensembl database were obtained, based on expressed transcripts from either StringTie or Cufflinks transcript quantification (**Additional File 2: Fig. S1A**). Unless otherwise specified, all downstream analyses were performed using the reduced transcriptome-informed database built according to expressed transcripts identified by StringTie, which is more recent than Cufflinks.

Proteome analysis

Raw spectra were downloaded from public repositories and processed automatically using Mascot Distiller software (version 2.7, Matrix Science). PSMs were identified using Mascot search (version 2.6), against two different concatenated target-decoy databases: either the original human GRCh38 Ensembl protein database (release 98, September 2019) or a reduced version of it containing only proteins for which the transcript is expressed (as described in the "Construction of reduced transcriptome-based protein databases for MS/MS searches" section). In both cases an equivalent number of decoy sequences was appended, as well as a custom database of common contaminant sequences (n=500) (and the corresponding number of decoys). Decoy sequences were

generated by reversing target sequences running the perl script provided with Mascot

software. The parameters used for Mascot searches on Lung and Jurkat are reported in

Additional File 1: Table S6.

The Proline software[52] was used for post-search PSM validation, applying the following

prefilters: *i.* PSMs with score difference < 0.1 were considered of equal score and

assigned to the same rank (pretty rank); *ii.* only a single best-scoring PSM was retained for

each query (single PSM per rank); *iii.* minimum peptide length >= 7 amino acids.

Prefiltered PSMs were then filtered at the score cutoff estimated for the 1% FDR control.

Unless otherwise specified, the score cutoff for the FDR control was estimated by TDC[53].

No protein inference was performed, but for each peptide, all possible protein matches

were considered. Protein identifications were reported as protein groups, as defined in the

Proline software. Protein groups included both the unambiguous identification of a single

protein (single-protein groups) and groups of indistinguishable proteins identified by the

same sets of peptides (multi-protein groups).

Further analyses were performed using the BH procedure for FDR control[32], as an

alternative to TDC (see Results section "Transcriptome information helps to reduce

ambiguity of protein identifications"). For these analyses, PSMs obtained from target-only

protein databases, appended with the same database of common contaminant sequences

were used, and searched, applying the same Mascot parameters as before.

Bipartite peptide-protein graphs and connected components

Proteomic identifications were represented using bipartite graphs with two types of

vertices – *i.* identified peptides; *ii.* all their possible proteins of origin – to more easily

analyze and visualize groups of ambiguous protein identifications connected by shared

peptides. Indeed, peptide assignments to proteins can generate very complex structures,

when peptides are shared by different proteins, but they are easily represented using

bipartite graphs. CCs from the graph – defined as the largest subgraphs in which any two

vertices are connected to each other by a path and not connected to any other of the

vertices in the supergraph – were then used to quantify the level of ambiguity of protein

identifications.

To build bipartite graphs of proteomic identifications, first a tab-separated file

containing identified peptides and all proteins they map on (one protein per line) was

generated based on the output of PSM validation by Proline software. This file was then

converted into an incidence matrix, with proteins along the columns and peptides along the

rows, using the crosstab function from the GNU datamash program

(http://www.gnu.org/software/datamash). The cross-product of the incidence matrix was

used to produce the corresponding adjacency matrix, which describes protein-to-protein

connections, based on shared peptides. Finally, CCs were calculated using the

connComp() function from the "graph" R package applied to the adjacency matrix. Two

types of CCs were defined: *i.* those containing a single protein (single-protein CCs), with

only specific peptides, which constitute unambiguous protein identifications; *ii.* those

containing multiple proteins sharing peptides (multi-protein CCs), which represent

ambiguous protein identifications. Ambiguous protein identifications can be visually

inspected by taking the CC of interest, extracting all specific and shared peptides mapping

to the CC protein members from the incidence matrix and plotting peptide-to-protein

mappings as bipartite graphs, using the "*igraph*" R package.

To decrease the computational cost when dealing with very large datasets or if

computational resources are scarce, an alternative strategy was also developed to

calculate CCs (**Additional File 2: Fig. S12**). First, the incidence matrix was reduced by

removing all proteins not sharing peptides and all peptides unique to these proteins. Then,

the corresponding adjacency matrix was generated as the cross-product of the incidence matrix. CCs can be more rapidly calculated on this reduced adjacency matrix. In this case, only multi-protein CCs are obtained, since protein identifications with only specific peptides, corresponding to single-protein CCs, were removed from the incidence matrix. While multi-protein CCs are those of interest when investigating ambiguous protein identifications from shared peptides, single-protein CCs can still be easily retrieved from the original incidence matrix if necessary.

A companion R code is provided implementing all the above-described steps, including: *i.* generating the adjacency matrix; *iii.* calculating CCs; *iii.* visualizing CCs as bipartite graphs.

Transcriptome-informed post-hoc filtering

As an alternative to searching a reduced transcriptome-informed database, a transcriptome-informed post-hoc filtering strategy was tested. First, peptide identifications were obtained by searching the full reference protein database, and validated using Proline software, as described in the "Proteome analysis" section. An incidence matrix was generated to encode peptide-to-protein mappings (see the "Bipartite peptide-protein graphs and connected components" section). Then, the sample-matched transcriptome was analyzed to identify the set of transcripts expressed. Finally, the peptide-to-protein incidence matrix was filtered by removing proteins for which no expressed transcript and no specific peptide were detected. The one-to-one transcript-to-protein correspondence is guaranteed by the use of Ensembl as the reference protein database in proteomics and for genome annotation in transcriptomics. The filtered incidence matrix was then converted to an adjacency matrix to calculate CCs, as previously described (see "Bipartite peptide-protein graphs and connected components" section).

For this study, the post-hoc filtering strategy on PSMs obtained from searching the

target-only full Ensembl protein database was used, followed by the BH procedure for FDR

control, to allow comparison with the approach searching target-only reduced

transcriptome-informed protein databases, followed by the BH procedure for FDR control.

Indeed, the BH procedure was used as an alternative to TDC after searching reduced

transcriptome-informed protein databases to obtain accurate FDR control, as explained in

the Results section (see "Reduced transcriptome-informed database search does not

increase sensitivity if FDR is accurately controlled"). However, in other contexts, post-hoc

filtering could also be performed using PSMs from concatenated target-decoy searches

followed by TDC-based FDR control. An R code implementing this post-hoc filtering

strategy is also provided. In addition to filtering, the code allows the CCs of interest to be

visualized both before and after post-hoc filtering.

598   **ABBREVIATIONS**

BH   Benjamini-Hochberg procedure

CC   connected component

DB   database

FDR   false discovery rate

MS/MS tandem mass spectrometry

PSM   peptide-spectrum match

TDC   target-decoy competition

DECLARATIONS

Ethics approval and consent to participate

Not applicable

Consent for publication

Not applicable

Availability of data and materials

All datasets analyzed in this study correspond to publicly-available data from the works of Wang et al.[33] and Sheynkman et al.[24].

The transcriptome datasets were downloaded from the EBI SRA with ArrayExpress accession: E-MTAB-2836 (run accession: ERR315346), and from the NCBI Gene Expression Omnibus (GEO) with accession GSE45428. The proteome datasets were downloaded from PeptideAtlas with accession PASS00215 and from the ProteomeXchange repository with dataset identifier: PXD010154 (sample identifier: P013163).

Scripts used to perform these analyses are available as a platform-independent R package, under GPL-3 license, at https://github.com/laurafancello/net4pg. Guidelines for installation and usage are documented in the GitHub repository.

Competing interests

The authors have no competing interests to declare.

Funding

This work was supported by grants from the French National Research Agency: ProFI project (ANR-10- INBS-08), GRAL project (ANR-10-LABX49-01), DATA@UGA and SYMER projects (ANR-15-IDEX-02) and MIAI @ Grenoble Alpes (ANR-19-P3IA-0003).

Author's contributions

LF collected and reprocessed the data, developed the R package and drafted the manuscript. TB devised the experimental design and proposed algorithmic solutions. Both authors jointly interpreted the results and finalized the manuscript, which they approve.

Acknowledgments

The authors are grateful to the IFB (Institut Français Bioinformatique) infrastructure for providing computational resources.

REFERENCES

1.	Jaffe, J. D., Berg, H. C. & Church, G. M. Proteogenomic mapping as a complementary method to perform genome annotation. *Proteomics* **4**, 59–77 (2004).

2.   Ruggles, K. V *et al.* Methods , Tools and Current Perspectives in Proteogenomics.
Mol. Cell. Proteomics **16**, 959–981 (2017).

3.   Nesvizhskii, A. I. Proteogenomics: concepts, applications and computational
strategies. *Nat. Methods* **11**, 1114–25 (2014).

4.   Zhang, B., Chambers, M. C. & Tabb, D. L. Proteomic parsimony through bipartite
graph analysis improves accuracy and transparency. *J. Proteome Res.* **6**, 3549–
3557 (2007).

5.   Yang, X. *et al.* DBParser: Web-based software for shotgun proteomic data analyses.
J. Proteome Res. **3**, 1002–1008 (2004).

6.   Li, Y. F. *et al.* A bayesian approach to protein inference problem in shotgun
proteomics. *J. Comput. Biol.* **16**, 1183–1193 (2009).

7.   Nesvizhskii, A. I., Keller, A., Kolker, E. & Aebersold, R. A statistical model for
identifying proteins by tandem mass spectrometry. *Anal. Chem.* **75**, 4646–4658
(2003).

8.   Serang, O., MacCoss, M. J. & Noble, W. S. Efficient marginalization to compute
protein posterior probabilities from shotgun mass spectrometry data. *J. Proteome*
Res. **9**, 5346–5357 (2010).

9.   Huang, T. & He, Z. A linear programming model for protein inference problem in
shotgun proteomics. *Bioinformatics* **28**, 2956–2962 (2012).

10.   Shanmugam, A. K., Yocum, A. K. & Nesvizhskii, A. I. Utility of RNA-seq and GPMDB
Protein Observation Frequency for Improving the Sensitivity of Protein Identification
by Tandem MS. *J. Proteome Res.* **13**, 4113–9 (2014).

11.   Ramakrishnan, S. R. *et al.* Integrating shotgun proteomics and mRNA expression
data to improve protein identification. *Bioinformatics* **25**, 1397–1403 (2009).

12.   Carlyle, B. C. *et al.* Isoform-Level Interpretation of High-Throughput Proteomics Data
Enabled by Deep Integration with RNA-seq. *J. Proteome Res.* **17**, 3431–3444
(2018).

13.   Bunger, M. K. *et al.* Detection and Validation of Non-synonymous Coding SNPs from
Orthogonal Analysis of Shotgun Proteomics Data. *J. Proteome Res.* **6**, 2331–2340
(2007).

14.   Alfaro, J. A. *et al.* Detecting protein variants by mass spectrometry: A comprehensive
study in cancer cell-lines. *Genome Med.* **9**, 1–12 (2017).

15.   Li, J. *et al.* A Bioinformatics Workflow for Variant Peptide Detection in Shotgun
Proteomics. *Mol. Cell. Proteomics* **10**, M110.006536 (2011).

16. Guerrero-Sanchez, V. M., Maldonado-Alconada, A. M., Sànchez-Lucas, R. & Rey,
M.-D. Specific protein database creation from transcriptomics data in nonmodel
species: Holm Oak (Quercus ilex. L.). *Methods Mol. Biol.* **2139**, 57–68 (2020).

17. Maringer, K. *et al.* Proteomics informed by transcriptomics for characterising active
transposable elements and genome annotation in Aedes aegypti. *BMC Genomics*
18, 101 (2017).

18. Blakeley, P. & Overton, I. M. Addressing Statistical Biases in Nucleotide-Derived
Protein Databases for Proteogenomic Search Strategies. *J. Proteome Res.* **11**,
5221–5234 (2012).

19. Li, H. *et al.* Evaluating the effect of database inflation in proteogenomic search on
sensitive and reliable peptide identification. *BMC Genomics* **17**, (2016).

20. Krug, K., Popic, S., Carpy, A., Taumer, C. & Macek, B. Construction and assessment
of individualized proteogenomic databases for large-scale analysis of
nonsynonymous single nucleotide variants. *Proteomics* **14**, 2699–2708 (2014).

21. Park, H. *et al.* Compact variant-rich customized sequence database and a fast and
sensitive database search for efficient proteogenomic analyses. *Proteomics* **14**,
2742–2749 (2014).

22. Verbruggen, S. *et al.* Spectral Prediction Features as a Solution for the Search
Space Size Problem in Proteogenomics Authors Spectral Prediction Features as a
Solution for the Search Space Size Problem in Proteogenomics. *Mol Cell*
Proteomics **20**, 100076 (2021).

23. Zhang, B. *et al.* Proteogenomic characterization of human colon and rectal cancer.
Nature **513**, 382–387 (2014).

24. Sheynkman, G. M., Shortreed, M. R., Frey, B. L. & Smith, L. M. Discovery and Mass
Spectrometric Analysis of Novel Splice-junction Peptides Using RNA-seq. *Mol. Cell.*
Proteomics **12**, 2341–2353 (2013).

25. Sheynkman, G. M., Shortreed, M. R., Frey, B. L., Scalf, M. & Smith, L. M. Large-
scale mass spectrometric detection of variant peptides resulting from non-
synonymous nucleotide differences. *J. Proteome Res.* **13**, 228–240 (2014).

26. Wang, X. *et al.* Protein identification using customized protein sequence databases
derived from RNA-Seq data. *J. Proteome Res.* **11**, 1009–1017 (2013).

27. Wang, X. & Zhang, B. customProDB : an R package to generate customized protein
databases from RNA-Seq data for proteomics search. *Bioinformatics* **29**, 3235–3237
(2013).

28. Sheynkman, G. M. *et al.* Using Galaxy-P to leverage RNA-Seq for the discovery of
novel protein variations. *BMC Genomics* **15**, 1–9 (2014).

29.   Proffitt, J. M. *et al.* Proteomics in non-human primates: utilizing RNA-Seq data to
719   improve protein identification by mass spectrometry in vervet monkeys. *BMC*
720   *Genomics* **18**, 1–10 (2017).

721   30.   Shanmugam, A. K., Nesvizhski, A. I., Arbor, A. & Arbor, A. Effective leveraging of
722   targeted search spaces for improving peptide identification in MS/MS based
723   proteomics. *J. Proteome Res.* **14**, 5169–5178 (2015).

724   31.   Coute, Y., Bruley, C. & Burger, T. Beyond Target − Decoy Competition: Stable
725   Validation of Peptide and Protein Identifications in Mass Spectrometry-Based
726   Discovery Proteomics. *Anal. Chem.* **92**, 14898–14906 (2020).

727   32.   Benjamini, Y. & Hochberg, Y. Controlling the false discovery rate: a practical and
728   powerful approach to multiple testing. *J. R. Stat. Soc. Ser. B* **57**, 289–300 (1995).

729   33.   Wang, D. *et al.* A deep proteome and transcriptome abundance atlas of 29 healthy
730   human tissues. *Mol. Syst. Biol.* **15**, 1–16 (2019).

731   34.   Gupta, N., Bandeira, N., Keich, U. & Pevzner, P. Target-decoy approach and false
732   dscovery rate: when things may go wrong. *J. Am. Soc. Mass Spectrom.* **22**, 1111–20
733   (2011).

734   35.   Keich, U., Kertesz-farkas, A. & Sta, W. Improved False Discovery Rate Estimation
735   Procedure for Shotgun Proteomics. *J. Proteome Res.* **14**, 3148–61 (2015).

736   36.   Levitsky, L. I., Ivanov, M. V, Lobas, A. A. & Gorshkov, M. V. Unbiased False
737   Discovery Rate Estimation for Shotgun Proteomics Based on the Target-Decoy
738   Approach. *J. Proteome Res.* **397**, 6–10 (2017).

739   37.   Burger, T. Gentle Introduction to the Statistical Foundations of False Discovery Rate
740   in Quantitative Proteomics. *J. Proteome Res.* **17**, 12–22 (2018).

741   38.   Keich, U., Tamura, K. & Noble, W. S. Averaging strategy to reduce variability in
742   target-decoy estimates of false discovery rate. *J. Proteome Res.* **18**, 585–593
743   (2019).

744   39.   Emery, K., Hasam, S., Noble, W. S. & Keich, U. Multiple Competition-Based FDR
745   Control and Its Application to Peptide Detection. *arXiv* (2019).

746   40.   Yi, X., Gong, F. & Fu, Y. Transfer posterior error probability estimation for peptide
747   identification. *BMC Bioinformatics* **21**, 173 (2020).

748   41.   Lin, A., Plubell, D. L., Keich, U. & Noble, W. S. Accurately Assigning Peptides to
749   Spectra When Only a Subset of Peptides Are Relevant. *J. Proteome Res.* **20**, 4153–
750   4164 (2021).

751   42.   Ge, X., Chen, Y. E., Song, D., Mcdermott, M. & Woyshner, K. Clipper : p-value-free
752   FDR control on high-throughput data from two conditions. *bioRxiv* (2021).
753   doi:doi.org/10.1101/2020.11.19.390773

43. Etourneau, L., Varoquaux, N. & Burger, T. Unveiling the links between peptide
identification and differential analysis FDR controls by means of a practical
introduction to knockoff filters. *bioRxiv* 1–19 (2021).
doi:doi.org/10.1101/2021.08.20.454134

44. Noble, W. S. Mass spectrometrists should only search for peptides they care about.
Nat. Methods **12**, 605–608 (2016).

45. Everett, L. J., Bierl, C. & Master, S. R. Unbiased Statistical Analysis for Multi-Stage
Proteomic Search Strategies. *J. Proteome Res.* **9**, 700–707 (2010).

46. Jagtap, P. *et al.* A two-step database search method improves sensitivity in peptide
sequence matches for metaproteomics and proteogenomics studies. *Proteomics* **13**,
1352–7 (2013).

47. Cheng, K. *et al.* MetaLab : an automated pipeline for metaproteomic data analysis.
Microbiome **5**, 157 (2017).

48. Afgan, E. *et al.* The Galaxy platform for accessible , reproducible and collaborative
biomedical analyses : 2018 update. *Nucleic Acids Res.* **46**, W537–W544 (2018).

49. Dobin, A. *et al.* STAR: ultrafast universal RNA-seq aligner. *Bioinformatics* **29**, 15–21
(2013).

50. Pertea, M. *et al.* StringTie enables improved reconstruction of a transcriptome from
RNA-seq reads. *Nat. Biotechnol.* **33**, 290–5 (2015).

51. Trapnell, C. *et al.* Transcript assembly and quantification by RNA-Seq reveals
unannotated transcripts and isoform switching during cell differentiation. *Nat.*
Biotechnol. **28**, 511–515 (2010).

52. Boussyié, D. *et al.* Proline: an efficient and user-friendly software suite for large
scale proteomics. *Bioinformatics* **36**, 3148–3155 (2020).

53. Elias, J. E. & Gygi, S. P. Target-decoy search strategy for increased confidence in l
arge-scale protein identifications by mass spectrometry. *Nat. Methods* **4**, 207–214
(2007).
781

Figure 1. Comparison of proteomic identifications from the full reference database or the transcriptome-informed reduced database searches. A. Graphical representation of the two MS/MS search strategies compared here. MS/MS spectra were assigned searching either the reference human Ensembl protein database (full protein DB) or a subset of the reference database, generated based on transcript expression (reduced protein DB), using Mascot software. PSMs were first validated using Proline software with the following prefilters: *i.* PSMs with score difference < 0.1 were considered of equal score and assigned to the same rank (pretty rank); *ii.* only a single best-scoring PSM was retained per query (single PSM per rank); *iii.* minimum peptide length >= 7 amino acids. PSMs were then filtered at the score cutoff estimated by target-decoy competition for 1% FDR control. **B.** Size and overlap of the reference human Ensembl protein database (full protein DB) and the sample-specific reduced transcriptome-informed protein databases (reduced protein DB). **C.** Number of spectra (left) or peptides (right) exclusively identified in the reduced database ("additional in reduced DB", in blue) or exclusively identified in the full database ("lost in reduced DB", in red) searches. The net difference between identifications additional and lost when searching the reduced database is also reported on top of each bar ("net").

Figure 2. Lower cutoff for FDR control in the reduced database generates additional identifications (Jurkat). A. Scatter plot comparing for each spectrum its PSM score from the full (x axis) or reduced database (y axis) searches. A color code indicates the type of match ("target", "decoy", or "no match") in the two searches. Score cutoffs obtained by TDC at 1% FDR are shown as red and blue lines for the full and reduced database, respectively. The upper-right insert zooms in on PSMs accepted at 1% FDR only in the reduced database, due to the lower score cutoff at 1% FDR (arrow pointing to the dashed circle). **B.** Number of reallocations whose score in the reduced database was equal to or lower (never higher) than the score in the full database. **C.** PSM scores for reallocations to target matches in the reduced database, grouped by the type of match in the full database. The number of reallocations passing the reduced database cutoff at 1% FDR is shown in

blue ("nb valid reallocations") and of those passing the full database cutoff at 1% FDR - additional valid identifications exclusively generated by reallocation, independent of the lower cutoff - in red ("nb valid pure reallocations"). **D.** Number of additional spectra (left) and number of spectra identifying additional peptides (right) exclusively identified in the reduced database search due to: *i.* lower score cutoff at 1% FDR in the reduced database compared to the full database – *i.e.*, PSMs only passing the cutoff from the reduced database search, including identical PSMs in both searches (black) and reallocations from target (gray), decoy (orange) or no match (magenta) in the full database to target matches in the reduced database; *ii.* pure reallocation – *i.e.*, additional identifications exclusively due to reallocation. The Venn diagram illustrates the corresponding non-redundant number of additional peptides (*i.e.*, not identified in the full database search) identified by these spectra.

Figure 3. Lower cutoff for FDR control in the reduced database to recover valid decoys (Jurkat). A. Comparison of valid identifications obtained at 1% FDR from the full database (horizontal red arrow) or reduced database (vertical blue arrow) searches, and simulation of the valid identifications which would be obtained from the reduced database search if the score cutoff at 1% FDR were equal to that for the full database (dashed red arrow). **B.** Number of valid targets and decoys from the full or reduced database obtained at 1% FDR using the cutoffs estimated by TDC on the respective database search results (first and last rows). The second row presents the simulated number of valid targets and decoys which would be obtained from the reduced database if the estimated cutoff were the same as for the full database. Variations, expressed in percentages, are shown in gray. The associated nominal FDR level is reported (calculated as $(d+1)/t$, with d and t being the number of valid decoys and targets, as suggested in Levitsky *et al.* Proteome Res, 2016[36]. **C.** Match in the reduced database search for spectra matching valid targets or valid decoys in the full database. **D.** Score cutoffs obtained by TDC or by BH procedure for FDR control for the full or reduced database searches at various FDR levels (0.5%, 1%, and 5%). The variation in score cutoff between full and reduced database searches is reported as a percentage.

Figure 4. Transcriptome-informed reduced databases yield less ambiguous protein identifications. A. Number of valid identifications obtained from the full (red) or reduced (blue) target-only database searches, followed by BH procedure for 1% FDR control. The number of valid spectra, peptide and protein identifications are reported. Protein groups, as defined by the Proline software, represent protein identifications and include: *i.* proteins unambiguously identified by only specific peptides (single-protein protein groups); *ii.* groups of proteins identified by the same set of shared peptides (multi-protein protein groups). **B.** Percentage of single-protein groups. **C.** Bipartite graph representation of peptide-to-protein mapping and exploitation of graph connected components to visualize and quantify the ambiguity of protein identifications. Unambiguous protein identifications are represented by CCs with a single protein vertex (single-protein CCs), while proteins sharing peptides are grouped in the same CC (multi-protein CCs) **D.** Upper panel: total number of connected components. Lower panel: percentage specific peptides and single-protein CCs. **E.** Genes encoding proteins from the full and reduced database searches. Upper panel: total number of genes associated with protein matches in the two searches. Lower panel: ratio between the number of protein members in each multi-protein CC and the number of genes encoding them.

Figure 5. Transcriptome-informed post-hoc filtering and reduced database search strategies similarly reduce protein identification ambiguity. A. Illustration of the transcriptome-informed post-hoc filtering strategy. First, an MS/MS search was performed against the full canonical protein database. Then, proteins with no corresponding expressed transcript in the sample-matched transcriptome, and for which no specific peptide was detected (both conditions required) were removed. Peptides only mapping to that set of proteins were also removed. **B.** Number of valid spectra and peptide identifications obtained from the full or reduced target-only database search (red and blue) or from the post-hoc filtering strategy (orange), after 1% FDR control by BH procedure. **C.** Quantification of protein ambiguity for the full or reduced database search (red and blue) or the post-hoc filtering strategies (orange). Upper panel: total number of CCs obtained. Lower panel: percentage of specific peptides and single-protein CCs.

A.

match		# spectra	% all spectra
full DB	**reduced DB**		
target	target	123,074	67.8
decoy	decoy	24,647	13.6
target	decoy	5,491	3.0
decoy	target	4,936	2.7
target	no match	12,011	6.6
decoy	no match	10,715	5.9
no match	target	288	0.2
no match	decoy	274	0.2

B. score of reallocations in reduced DB (compared to full DB)

* ≠ PSMs

C.

nb valid reallocations
nb valid pure reallocations

target_target *
n=5,894 (3.2%)   132 / 85

decoy_target
n=4,936 (2.7%)   67 / 42

no match_target
n=288 (0.2%)   7 / 1

* ≠ PSMs

D. additional spectra origin / additional peptide origin

target_target*
decoy_target
no match_target
no reallocation

* ≠ PSMs

A.

transcriptome-informed post-hoc filtering

proteome
MS/MS

database search ⟷ full protein DB

↓

PSM validation
i. prefilters:
pretty rank
singlePSM per rank
peptide length >= 7aa
ii. FDR control

↓

post-hoc filtering ← **transcriptome**
remove proteins for which
no expressed transcript and no specific peptide
were detected ← expressed transcripts

↓

proteomic identifications

B.

	Jurkat	Lung

spectra
- 81,243 / 391,775
- 80,273 / 378,249
- 80,373 / 383,295

peptides
- 53,992 / 112,132
- 53,638 / 106,530
- 53,575 / 108,265

number of identifications

C.

	Jurkat	Lung

total number of CCs
- 6,667 / 9,341
- 6,335 / 8,456
- 6,453 / 8,707

specific peptides
- 7.8 / 8.1
- 31.2 / 45.6
- 31.1 / 46.01

single-protein CCs
- 13.4 / 14.0
- 39.2 / 51.2
- 40.4 / 52.2

percentage (%)

■ full DB search
■ reduced DB search
■ post-hoc filter