Layered Feedback Control Overcomes Performance Trade-off in Synthetic Biomolecular Networks

Chelsea Y. Hu[1] and Richard M. Murray[1]

[1]Division of Biology and Biological Engineering, California Institute of Technology, Pasadena, CA.

Abstract

Layered feedback is an optimization strategy in feedback control designs widely used in electrical and mechanical engineering. Layered control theory suggests that the performance of controllers is bound by the universal robustness-efficiency trade-off limit, which could be overcome by layering two or more feedbacks together. In natural biological networks, genes are often regulated with redundancy and layering to adapt to environmental perturbations. Control theory hypothesizes that this layering architecture is also adopted by nature to overcome this performance trade-off. In this work, we validated this property of layered control with a synthetic network in living *E.coli* cells. We performed system analysis on a node-based design to confirm the trade-off properties before proceeding to simulations with an effective mechanistic model, which guided us to the best performing design to engineer in cells. Finally, we interrogated its system dynamics experimentally with eight sets of perturbations on chemical signals, nutrient abundance, and growth temperature. For all cases, we consistently observed that the layered control overcomes the robustness-efficiency trade-off limit. This work experimentally confirmed that layered control could be adopted in synthetic biomolecular networks as a performance optimization strategy. It also provided insights in understanding genetic feedback control architectures in nature.

Introduction

Two of the major goals of synthetic biology are to engineer biological systems to perform desired tasks and to understand biomolecular networks by building them. These two goals are both very ambitious; fortunately, their advancements are strongly coupled. By building and studying synthetic systems, we gain insights into the natural networks; with a deeper understanding of how natural genetic networks allow life to persevere through constant adversity, we develop stronger theoretical principles to guide synthetic network design. Like many other systems humans have engineered, feedback controls are essential components of a reliable synthetic biological system. Over the past two decades, the synthetic biology toolbox of characterized genetic components, modules, and motifs has been expanding exponentially [1]. As the complexity of synthetic circuits grows, its interplay with control theory becomes more prominent. A significant amount of work has already shown that applying feedback controls improves the reliability, efficiency, and performances of synthetic biological systems [2, 3, 4, 5, 6, 7, 8]. Feedback control provides correcting actions based on the difference between desired and actual performance [9, 10], therefore it buffers systems from external disturbances and variations of components within the system. However, feedback can also destabilize the system when improperly designed [10]. Feedback design is especially challenging in biological systems due to its complexity — all molecular species are part of an extensive endogenous network that consists of numerous feedback mechanisms.

In nature, biology has developed remarkably sophisticated strategies to apply feedback controls to biomolecular and physiological networks. Interestingly, layering and redundancy appears to be a common style in these feedback architectures. For instance, bacteria cells layer a positive control to move towards nutrients and a negative control to move away from toxins through chemotaxis signaling [11, 12]. During a heat shock, the endogenous control in bacteria maintains the amount of heat shock proteins with a multi-layer control strategy via translation, chaperone interaction, and protein degradation [13]. At the physiological level, the human body maintains a relatively constant glucose level in the bloodstream through insulin, the production of which is regulated through the interplay of the pancreas with the brain, liver, gut, as well as adipose and muscle tissues [14]. It has also been discovered that the sleep and arousal states of animals are controlled with a layered architecture [15]. Control theorists found that layering is a powerful optimization method for feedback control design [16]. This is because the performance of feedback controls is often bound by hard limits. A system that is optimized for one type of disturbance is typically fragile to other types of disturbance [10, 17]. These constraints are also manifested as the robustness-efficiency trade-off limit, which are theorized to be fundamental and universal for all feedback systems [18, 19]. If a system responses to changes in inputs quickly, it is considered *efficient*; if a system shows strong attenuation against disturbances, it is considered *robust*. This trade-off limit prevents a system from being both *efficient and robust*. It is also theorized that, in both natural and engineered systems, if multiple control modules of various robustness-efficiency profiles are layered together, this hard limits could be overcome [20, 21] (Figure 1A).

In this work, we forward engineer layered feedback control in living *E.coli* to study the dynamical performance of this architecture in a biomolecular context. We first start with a node-based design of two layers of feedback (Figure 1B) and a minimal model of three species (Equations 1–3). By performing

system analysis on the minimal model, we observe the robustness-efficiency trade-off on the two single-layer designs, where one appears to be robust but inefficient while the other is efficient but fragile. Meanwhile, we see a clear integration of these two traits in the layered feedback system. Subsequently, we expand this design into a generic biomolecular model that describes the coarse-grained dynamics of a biomolecular feedback system. With simulation, we also observe that for all four sets of the proposed designs, the two single-layer feedback are bound by the robustness-efficiency trade-off limit, while the layered feedback design overcomes it. Based on the simulated result, we choose the best performing layered feedback design and construct it in *E.coli*. Finally, we present eight sets of dynamical perturbation experiments, with four different types of disturbances, each on two directions. We show that the layered feedback design in all cases overcomes the robustness-efficiency trade-off limit. This result applies layered feedback control in a biomolecular network and validates a key hypothesis of layered control theory. In addition to providing a validated optimization strategy to genetic network engineering, we hope the insights it provides will improve our understanding of natural dynamical systems in biology.

Results and Discussion

Robustness-efficiency Trade-off Analysis with a Node-based Design

In order to investigate the cooperative behavior of two layers of negative feedbacks, we started our analysis with a node-based design of three species. As shown in Figure 1B, we defined two nodes, A and B, where B is the observable output of the system that is activated by A. Species R is a byproduct of species B that negatively regulates the expression of B and itself through two possible routes: *cis* feedback (R represses B) and *trans* feedback (R represses A). The activation and repression here are estimated with first-order Hill functions:

$$\frac{dA}{dt} = \gamma \cdot \beta_A \cdot f_{trans} - d \cdot A \tag{1}$$

$$\frac{dR}{dt} = \gamma \cdot \beta_R \cdot (\frac{A}{K_A + A}) \cdot f_{cis} - d_R \cdot R \tag{2}$$

$$\frac{dB}{dt} = \gamma \cdot \beta_B \cdot (\frac{A}{K_A + A}) \cdot f_{cis} - d \cdot B \tag{3}$$

For the open loop, $f_{cis} = f_{trans} = 1$; for the *cis* only feedback, $f_{cis} = \frac{K_R}{K_R + R}$, $f_{trans} = 1$; for the *trans* only feedback, $f_{trans} = \frac{K_R}{K_R + R}$, $f_{cis} = 1$; for the layered feedback, $f_{cis} = f_{trans} = \frac{K_R}{K_R + R}$. Both A and B are assumed to be protein species, while R could be either protein or regulatory RNA. In the ODEs, β_A, β_R, and β_B denote the expression rate of A, R, and B, respectively. The constant K_A defines the activation coefficient of A, and K_R defines the repression coefficient of R. Both species A and B degrade at the same rate d, while R degrades at rate d_R. Here we define the output as species B. The input is defined as γ, a unitless scalar that impacts the expression rate of all three species (β_A and β_B). Our analysis in the rest of this work focuses on four designs: open loop, the *cis* feedback, the *trans* feedback, and the layered feedback.

Figure 1: Stability analysis of the layered feedback controller using a minimal model. (A) The theorized law of robustness-efficiency trade-off limit of feedback control. Layering is an optimization strategy to overcome these trade-off limits. (B) Schematics of the node-based system. Here A and B are two molecular species, where A activates the expression of B and R. Functioning as a regulator, R regulates species B directly through the *cis* feedback on B and indirectly through the *trans* feedback on A. When both types of feedback exist in the same system, the configuration is termed layered feedback. (C) Response magnitude with production disturbance at different frequencies. This plot shows the magnitude response of species B (y-axis) when all three species' production rates are subjected to a perturbation (on γ) at different frequencies (x-axis). The blue, red, yellow, and purple curves represent the open loop, the *cis* feedback, the *trans* feedback, and the layered feedback circuit structures, respectively. Solid lines represent the magnitude response of these four structures when regulator R is an RNA species, dashed lines when R is a protein species. (D) Disturbance attenuation and settling time of four architectures in a two-dimensional parameter space K_R and d_R. Top panel shows the output disturbance magnitude when all three species' production rates are subjected to a perturbation at low frequency. Bottom four panels show the time it takes for the systems to settle back to equilibrium after the perturbation. Both response magnitude and settling time are represented by the color schemes (see color bar). For each of the eight heat maps, the x-axis (d_R) represents the degradation rate of regulator R; a large d_R models a regulator with fast degradation rate. The y-axis (K_R) represents the repression constant of regulator R; a large K_R models a regulator with weak repression strength.

First, we performed a stability analysis of these four constructs at equilibrium using their transfer functions. The transfer function describes the relationships between inputs and outputs of a linear system in the frequency domain [10]. Since all four systems are nonlinear, we linearized them at their equilibrium points before converting them to the frequency domain. Figure 2C shows the magnitude response of these four systems in the frequency domain. In this figure, the x-axis represents the input frequency in rad/min, and the y-axis represents the output/input magnitude, which has a unit of nM. When the input frequency is low, this could be understood as a long-lasting perturbation to the universal expression scalar γ. When the input frequency is high, the input disturbance oscillates rapidly, and the output response to the disturbances diminishes. In this figure, we observe that the *cis* feedback (red) attenuates disturbances better than the *trans* feedback (yellow). The layered feedback shows the strongest attenuation effect (purple). We also observed that there is only a slight difference between an RNA regulator (solid lines, with $K_R = 10, d_R = 0.3$) and a protein regulator (dashed lines, with $K_R = 100, d_R = 0.03$) with intermediate input frequencies.

In the upper panel of Figure 1D, we plotted the magnitude response of each construct at low frequency in a two-dimensional parameter space K_R (y-axis) and d_R (x-axis). We found that over a wide parameter space, the *cis* feedback attenuated disturbances at low frequency better than the *trans* feedback, while the layered feedback showed the most attenuation. In each feedback design, regulators with strong repressive strength and a slow degradation rate achieved the most disturbance attenuation. In the lower panel of Figure 1C, we plotted the settling time of each construct after a step-disturbance in the same two-dimensional parameter space K_R (y-axis) and d_R (x-axis). We found that although the *cis* feedback had a strong attenuation of disturbance, it took longer to recover back to equilibrium, while the *trans* feedback recovered back to equilibrium faster but attenuated the disturbances less effectively. The layered feedback, on the other hand, appeared to have a moderate settling time and strong disturbance attenuation.

Robustness-efficiency Trade-off Analysis with Generic Biomolecular Configurations

To actuate the node-based design in the biomolecular context, we proposed four possible designs (Figure 2A) with the regulator species being either R (regulatory small RNA, or sRNA) and P (regulatory protein). As shown in Figure 2A, the system is induced with small molecule x, which activates the transcription of protein P_{ind}. Protein P_{ind} sequentially activates the gene of interest (GOI) cassette, which contains gene GOI, R, and/or P. The four illustrations in Figure 2A represent four designs of layered feedback: (1) sRNA mediated *cis* feedback layered with protein mediated *trans* feedback, (2) sRNA mediated *cis* feedback layered with sRNA mediated *trans* feedback, (3) protein mediated *cis* feedback layered with sRNA mediated *trans* feedback, and (4) protein mediated *cis* feedback layered with protein mediated *trans* feedback.

Next, we interrogated the performance of these four designs in simulation with pulse disturbances. The dynamics of these systems are described with reduced differential equations (Equation 4–11). The detailed species and parameters involved in this model are listed in Table 1 and Table 2, respectively. It is worth noting that we purposefully chose the degradation rates (d_r, d) and repression coefficients for

Figure 2: Efficiency-stability trade-off analysis on generic biomolecular configurations. (A) The four possible biomolecular configurations of the node-based design as shown in Figure 1B, with the regulator species being either sRNA or protein. In all cases, gene regulations happen at the transcriptional level. (B) The simulated dynamics of system with a transcriptional pulse perturbation at steady state. This plot corresponds to one of the four designs, where sRNA regulates via both *cis* and *trans* feedbacks. (C) The robustness-efficiency trade-off analysis of nine configurations. The plot is generated from simulated dynamics with randomized model parameters, one example of which is shown in 2B.

regulatory RNA R and regulatory protein P (K_R, K_p) to simulate the same effective repressive strength for fair comparison. The regulatory RNA is simulated to have strong binding affinity (small K_R) but is quickly degraded (large d_r); the regulatory protein is simulated to have weak binding affinity (large K_p) but is slowly degraded (small d).

$$\frac{dM_{ind}}{dt} = f_{tx} \cdot \beta_A \cdot \left(\frac{x}{K_x + x}\right) \cdot f_{trans} - d_m \cdot M_{ind} \tag{4}$$

$$\frac{dP_{ind}}{dt} = f_{tl} \cdot k_{tp} \cdot M_{ind} - d \cdot P_{ind} - K_r \cdot P_{ind} \tag{5}$$

$$\frac{dC_{ind}}{dt} = K_r \cdot P_{ind} - d \cdot C_{ind} \tag{6}$$

$$\frac{dM_G}{dt} = f_{tx} \cdot \beta_B \cdot \left(\frac{C_{ind}}{K_{ind} + C_{ind}}\right) \cdot f_{cis} - d_m \cdot M_G \tag{7}$$

$$\frac{dR}{dt} = f_{tx} \cdot \beta_B \cdot \left(\frac{C_{ind}}{K_{ind} + C_{ind}}\right) \cdot f_{cis} - d_r \cdot R \tag{8}$$

$$\frac{dP}{dt} = f_{tl} \cdot k_{tr} \cdot M_G - d \cdot P \tag{9}$$

$$\frac{dG}{dt} = f_{tl} \cdot k_{tg} \cdot M_G - \alpha \cdot G - d \cdot G \tag{10}$$

$$\frac{dG_m}{dt} = \alpha \cdot G - d \cdot G_m \tag{11}$$

If transcription is regulated by a protein species, the Hill function is written as $f_{Hill_P} = \frac{K_p}{K_p + P}$. If transcription is regulated by a sRNA species, the Hill function is written as $f_{Hill_R} = \frac{K_R}{K_R + R}$. For the open loop, $f_{cis} = f_{trans} = 1$. For the *trans* only feedback, $f_{cis} = 1$ and $f_{trans} = f_{Hill_P}$, if mediated by a a protein species; $f_{trans} = f_{Hill_R}$, if mediated by a sRNA species. For the *cis* feedback, $f_{trans} = 1$ and $f_{cis} = f_{Hill_P}$, if mediated by a protein species; $f_{cis} = f_{Hill_R}$, if mediated by a sRNA species. For the layered feedbacks, the four possible combinations are: (1) R *cis* R *trans*, $f_{cis} = f_{Hill_R}, f_{trans} = f_{Hill_R}$; (2) R *cis* P *trans*, $f_{cis} = f_{Hill_R}, f_{trans} = f_{Hill_P}$; (3) P *cis* R *trans*, $f_{cis} = f_{Hill_P}, f_{trans} = f_{Hill_R}$; (4) P *cis* P *trans*, $f_{cis} = f_{Hill_P}, f_{trans} = f_{Hill_P}$.

We simulated the system dynamics of all four sets of designs and compared them with their corresponding single-layer and open loop configurations. One of the four sets of dynamics is plotted in Figure 2B. We first scaled the expression of all four configurations to the same equilibrium signal value. At equilibrium, we gave the universal transcriptional rate scalar f_{tx} a 25% step pulse and held it for 50 minutes. Then we plotted each construct's percentage GOI response at its peak and the settling time after the disturbance. For a total of nine different configurations (one open loop, two *cis* feedbacks, two *trans* feedbacks, and four layered feedbacks), we generated six sets of parameters with a 25% randomization around the initial guesses for each simulation. Then for each of the nine configurations, the six sets of parameters were used to simulate six dynamical profiles in response to perturbations. The settling times and percentage disturbance magnitude of each simulation were recorded in the robustness-efficiency trade-off plot in Figure 2C. Similar to the result we obtained from the node-based design in Figure 1, we found that the *cis* feedback is more robust against disturbances but recovers slower, *trans* feedback is more fragile against

disturbances but recovers faster. As these two feedback controls are layered, the system inherits the strong disturbance attenuation from the *cis* feedback and the fast recovery speed from the *trans* feedback. Finally, we chose the design with sRNA-mediated *cis* feedback and protein-mediated *trans* feedback to proceed to the experimental portion of the work, as it demonstrated the most advantageous performance on the robustness-efficiency trade-off plot.

Table 1: Generic Biomolecular Model Species

Species	Description
M_{ind}	the mRNA of signaling protein P_{ind}
P_{ind}	the signaling protein translated peptides
C_{ind}	the signaling complex, with folded signaling protein bound with inducer molecules
R	the regulator sRNA repressor
P	the regulator protein repressor
M_G	the GOI mRNA transcript
G	the translated GOI peptides
G_m	the mature GOI (observable)

Table 2: Generic Biomolecular Model Parameters

Parameters	Description	Unit	Estimates
β_A	max transcription rate of the inducible promoter P_x	nM/min	2
K_x	activation coefficient of the chemical inducer x	nM	1.4e4
K_R	repression coefficient of the sRNA repressor	nM	20
K_p	repression coefficient of the protein repressor	nM	200
d_m	degradation/dilution rate of mRNA	1/min	0.1
k_{tp}	translation rate of the inducing protein P_{ind}	1/min	0.1
d	degradation/dilution rate of all proteins, dominated by dilution	1/min	0.03
K_r	the maturation rate of the activating complex	1/min	0.1
β_B	max transcription rate of the C_{ind} inducible promoter	nM/min	20
K_{ind}	activation coefficient of C_{ind}	nM	200
d_r	degradation/dilution rate of sRNA	1/min	0.3
α	maturation rate of GOI	1/min	0.2
x	the chemical inducer that activates P_x	nM	2.0e6
k_{tg}	translation rate of GOI	1/min	0.1
f_{tx}	scaling factor of universal transcription	NA	1
f_{tl}	scaling factor of universal translation	NA	1
k_{tr}	translation rate of the regulator protein	1/min	0.1

Experimental Implementation of a Layered Feedback Control in Living *E.coli* Cells

We designed four genetic constructs to test and experimentally analyze the layered feedback design we proposed based on the simulated results in Figure 2C. We aimed to compare the dynamical performances of the open loop, the *cis* feedback, the *trans* feedback, and the layered feedback. With the effect of genetic context in mind [22], we designed the four constructs with the same configuration. As shown in Figure 3A, the system is composed of two cassettes expressed on two plasmids. The combinatorial promoter $P_{Rhl/LacO}$ [23] drives the expression of CinR on a medium copy p15A backbone; promoter P_{cin} drives a another cassette containing sRNA repressor pair (AS and Att) [24], sfYFP, and LacI places on a high copy ColE1 backbone. The system is activated by the induction of combinatorial promoter $P_{Rhl/LacO}$ with an

Figure 3: Experimental construction of the layered feedback control in *E.coli*. (A) The four genetic constructs designed for experimental construction of the open loop, the *cis* feedback, the *trans* feedback, and the layered feedback. (B) Part-characterization of combinatorial promoter $P_{Rhl/LacO}$. Induction signal of $P_{Rhl/LacO}$, compared with constitutive promoter P_{con} and Rhl-inducible promoter P_{Rhl}, performing in RhlR integrated JS006 strain. (C) Part-characterization of sRNA regulator AS with its paired attenuator Att and its orthogonal attenuator Att(M). (D) Part-characterization of combinatorial promoter $P_{Rhl/LacO}$, tested with its repressor LacI and a mutated repressor LacI(M). LacI(M) was built off LacI, with the LacO binding site deleted. (E) RBS screening result for the expression of CinR to enable activation cascade. The RBS in Clone D8 was chosen to proceed with the next stages of construction. (F) RBS screening result for the expression of lacI to facilitate the *trans* feedback. The plot shows that the selected clone confirmed the functionality of the negative feedback without over-repression.

AHL inducer Rhl. The promoter then allows the expression of protein CinR, which subsequently binds to an AHL inducer Cin in growth medium to activate promoter P_{cin}. Promoter P_{cin} controls the transcript that contains sRNA regulating pair AS and Att, the observable system output sfYFP, and the protein regulator LacI. In this configuration, sRNA repressor AS regulates the expression of sfYFP via the *cis* feedback, and LacI represses $P_{Rhl/LacO}$ to regulate the expression of CinR through the *trans* feedback. To avoid genetic context change and metabolic load variation, we created mutated regulator pieces to disable feedbacks without changing the genetic context. Specifically, we paired AS with its orthogonal attenuator Att(M) [25] to disable the *cis* feedback, and we built LacI(M) off LacI with the LacO binding site sequence removed to disable the *trans* feedback. The construction of these four genetic networks is not trivial. It involves one combinatorial regulation, one activation cascade, and two nested autoregulatory motifs. Extensive part-characterization and expression optimization is required to confirm the networks' proper dynamical properties.

To characterize all the parts and confirm their functionalities, we started with the promoter $P_{Rhl/LacO}$. Because LacI was designed as a regulatory part of the construct, we chose strain JS006 [26] for its ΔLacI genotype and integrated a constitutively expressed RhlR into its genome. We characterized the promoter $P_{Rhl/LacO}$ in this RhlR containing JS006 strain with 200 μM Rhl induction (Figure 3B). The test confirmed that the combinatorial promoter has sufficient fold induction with about 5% leaky expression. Then, we tested the sRNA mediated *cis* feedback with AS-Att pair and AS-Att(M) pair. We confirmed that the AS-Att(M) pair functions as an appropriate control for the *cis* feedback, as the dynamics of the two constructs are consistent with previous findings [27] (Figure 3C). Next, we examined the repressive regulatory function of combinatorial promoter $P_{Rhl/LacO}$ with LacI and LacI(M) (Figure 3D). The result confirmed that $P_{Rhl/LacO}$ can be fully repressed by LacI with full Rhl induction. In the meantime, we determined that LacI(M) is an appropriate control for the *trans* feedback.

At last, we performed two sets of ribosome binding site (RBS) screening assays to achieve the ideal protein expression strength that actuates the desired circuit functionalities. First, we searched for an RBS to express CinR so that it facilitates the activation cascade in our circuit design context. The cascade is designed to be turned on by the inducible expression of CinR through promoter $P_{Rhl/LacO}$. Subsequently, CinR binds to inducer Cin in the growth medium, and then the complex activates the promoter P_{cin}. Because $P_{Rhl/LacO}$ exhibited some leaky expression, the RBS for CinR required optimization. If the RBS is too weak, the downstream cascade could be under-activated; if the RBS is too strong, the leaky expression of $P_{Rhl/LacO}$ could cause the cascade to be over-activated without Rhl induction. Here, we screened for an RBS so that the system is off (shows minimal sfYFP signal) with no inducer, only Rhl inducer, or only Cin inducer. Then the system turns on with both Rhl and Cin inducers. As shown in Figure 3E, Clone D8 presented the desired induction profile. The resulting RBS was selected to proceed with the circuit construction. Finally, we screened the RBS for LacI so that it facilitates the *trans* feedback. As we see in Figure 3D, LacI has a strong repressive effect on $P_{Rhl/LacO}$ with full Rhl induction. Therefore, a relatively weak RBS is required for the *trans* feedback to function. Figure 3F showed the desired dynamical profile of a clone resulting from the screen, where LacI is expressed enough to present a repressed trajectory yet is not over-expressed to shut off the sfYFP expression entirely.

Interrogating the Dynamics of Layered Feedback Control in *E.coli*

Figure 4: Dynamics of the four testing constructs – the open loop, the cis feedback, the *trans* feedback, and the layered feedback, as shown in Figure 3A. (A) Simulated dynamics of the four constructs with reduced model in Equation 4-11 run for 7 hours. (B) Experimentally observed dynamics of the four constructs run for 7 hours. (C) Experimentally observed dynamics of the four constructs run for 16 hours. (D) Simulated dynamics of the four constructs with growth-dependent model in Equation in SI section 1 run for 16 hours. (E)-(H) Dynamic analysis of the test and intact groups in Rhl and Cin wash perturbation experiment. Grey regions indicate the duration of disturbances. (E) Dynamical profile of the intact group. (F) Dynamical profile of the test group. (G) Disturbance profile, calculated by subtracting the dynamics of the test group by the dynamics of the intact group. (H) Scaled disturbance profile. The dynamical deviation of the test group from the intact group, scaled by each construct's pre-disturbance output value.

After building the four testing constructs in Figure 3A, we proceeded to analyze their dynamical profiles in living *E.coli* cells. We noticed that for the first 7 hours, our experimentally observed dynamics looked similar to the simulated dynamics generated by the reduced model (Figure 4A, Equation 4 to 11).

In comparison with the open loop, the three feedback versions all showed lower equilibrium output signals and faster responses after the induction of Rhl and Cin at $t = 0$ (Figure 4B). However, as the experiment continued, we observed that the reduced model no longer qualitatively describes the observed dynamics (Figure 4C). Notably, the experimental dynamics no longer reach equilibrium. We knew that the reduced model was built with numerous assumptions that do not hold as a bacterial culture grows towards capacity. One of many affected parameters is protein dilution d. The reduced model assumes a constant cell division rate, therefore a constant d. However, we observed that the cell division rate increases first, then decreases as population reaches capacity (Figure S1). As cell division slows down, protein division slows down, but the active protein degradation due to nutrient starvation speeds up. At the same time, protein production also slow down as it is tied to the nutrient availability in the growth medium. We then expanded our model with functions that approximate the connection between gene expression, cell growth, and nutrient availability (See SI Section 1). The dynamical profile we obtained (Figure 4D) roughly resembles the observation in Figure 4C. Although much more work is needed to create an accurate multiscale model with identified parameters, this preliminary model provided insights for understanding the gene expression dynamics across multiple growth phases.

Since the system dynamics in living cells do not reach equilibrium, we cannot use the same method in Figure 2 to interrogate system dynamics. To overcome this problem, we designed each perturbation experiment with a test group and an intact group. Figure 4E and Figure 4F showed the two groups from one of the eight sets of perturbation experiments. In this experiment, both groups were induced with 100 μL of Rhl and 10 μL of Cin at $t = 0$ and let grow for 7 hours. At hour 7, both groups were washed with phosphate buffered saline (PBS), and the growth medium was replaced. The intact group shown in Figure 4E was resuspended in fresh medium with 100 μL of Rhl and 10 μL of Cin; the test group was resuspended in fresh medium with no inducer. The perturbation window was 120 minutes (greyed section in Figure 4E–H), then both groups were washed and resuspended back to the recycled pre-disturbance media. We measured the disturbance of constructs by the deviation of the test group dynamics from the intact group dynamics (Figure 4G). Since the four constructs do not have the same signal output level, we scaled the disturbance profile in Figure 4G by each construct's pre-disturbance output value to obtain a fair comparison (Figure 4H).

Evaluating the Robustness-efficiency Performance of Layered Control in *E.coli*

In total, we performed eight sets of perturbation experiments on the four testing constructs to assess their robust-efficiency performance. As shown in Figure 4C, the experimental dynamics do not reach equilibrium. Additionally, due to the low nutrient availability in the stationary growth phase, systems also do not necessarily adapt after the disturbance is removed. Therefore, instead of using settling time, we used the response time to evaluate the system's efficiency. Response time is defined as the time it takes to reach half of the output equilibrium after input is supplied. Here we used pre-disturbance output values to approximate the output equilibrium. To evaluate system robustness, we scaled disturbance profiles by their assumed equilibrium values and plotted them in Figure 4H. We then plotted the scaled disturbance magnitude and response time of each of the five replicates of the open loop (blue), the *cis* feedback (red),

Figure 5: Robustness-efficiency performance of the four constructs in Figure 3A under perturbations presented in trade-off plots. The eight sets of perturbations are: (A) Cin and Rhl concentration dip, (B) Cin and Rhl concentration spike, (C) Rhl only concentration dip, (D) Rhl only concentration spike, (E) glucose concentration dip from 1% to 0%, (F) glucose concentration spike from 0.1% to 1%, (G) growth temperature dip from 37°C to 30°C, (H) growth temperature spike from 37°C to 42°C. All plots were generated with scaled disturbance profiles (Figure 4H and Figure S2, S3) in each set of the perturbation experiments. For each biological replicate, the largest value in the dynamical profile is plotted on the y-axis to represent its disturbance magnitude; the time it takes for the dynamics to reach half of its pre-disturbance output value is plotted on the y-axis to represent its response time. Each dot renders the robustness-efficiency performance of an individual cell culture. A small y-axis value indicates higher robustness; a small x-axis value indicates higher efficiency.

the *trans* feedback (orange), and the layered feedback (purple) to generate the trade-off plots for each type of perturbation (Figure 5). Figure 5A is the trade-off plot generated with the dynamics shown in Figure 4E-H, with Cin and Rhl wash. To examine system dynamics with positive perturbation, we also perturbed the system with a Cin and Rhl spike, as shown in figure 5B. Subsequently, we perturbed the system with Rhl only (Figure 5C, 5D), glucose concentration (Figure 5E, 5F), and the growth temperature (Figure 5G, 5H) in both negative and positive directions to evaluate system dynamics under perturbations. The detailed protocols of these dynamical experiments are listed in Table S3.

In electrical engineering and control theory, a system's response to disturbances is usually evaluated with a single perturbed input (Figure 1C). However, in biological systems, perturbations are often applied at the environmental level, which could have much broader, yet poorly understood impacts on the system dynamics. In our node-based design (Figure 1B) and generic biomolecular design (Figure 2A), perturbations were introduced as universal low-frequency transcriptional pulses. Here, we first applied the same perturbation at both negative and positive directions (Figure 5A, 5B) with Cin and Rhl. We saw that although the trade-off profiles of the *trans* and the *cis* feedbacks with the same perturbation in opposite directions were not consistent with each other, the layered feedbacks had advantageous robust-efficiency performance in comparison to the single-layer controls in both cases. After that, the next set of disturbances were induced through perturbation of system input Rhl in both directions. In this set of experiments, the *trans* feedback, compared to the *cis* feedback, showed more resilience against the perturbation to the promoter it directly regulates. More importantly, the layered control appeared to have a faster response and stronger resilience than the single-layer feedbacks. Finally, we introduced glucose and temperature perturbations to emulate the most common environmental disturbances in biological systems (Figure 5E to 5H). Specifically, we dropped the glucose concentration in the growth medium from 1% to 0% to apply a negative perturbation (Figure 5E) and raised it from 0.1% to 1% to apply a positive perturbation (Figure 5F). For the temperature disturbance, the dip was generated by dropping the incubation temperature from 37°C to 30°C (Figure 5G). The spike was generated by increasing it from 37°C to 42°C (Figure 5H). We observed that systems with layered control performed better in the trade-off plots for all four sets of environmental perturbations.

Through the measurement and analysis of all eight sets of experiments, many aspects of the dynamics posed interesting questions regarding the natural biological networks. For instance, when given a glucose wash, all four constructs exhibited an increase in gene expression, and this increase was sustained long after the disturbance was removed (Figure S3). Moreover, when the incubating temperature was raised from 37°C to 42°C, the *trans* and the layered feedback constructs demonstrated positive disturbances while *cis* feedback and open loop demonstrated negative disturbances (Figure S3). Interestingly, this observation was reversed when the systems were perturbed with Rhl and Cin spikes. The *trans* feedback and the layered feedback showed negative disturbances, while the *cis* feedback and the open loop demonstrated positive disturbances (Figure S2). In the Rhl dip perturbation experiment, although all four constructs revealed an output signal dip during the perturbation window, their dynamics in the recovery window progressed in different directions (Figure S2). These observations suggested that pieces in our synthetic circuits were coupled through unknown mechanisms that await discoveries, which provided new directions for future works. Nevertheless, without knowing all the mechanistic details, we were able to experimentally

confirm that layered feedback overcomes the robustness-efficiency trade-off limit that constrains single-layer controls and achieves better control performance.

Conclusion

This work provided experimental proof that layered feedback control as a control optimization strategy is applicable in biomolecular networks. We first showed that the layered architecture overcomes the robustness-efficiency trade-off in a wide range of parameter space with a node-based minimal model. Then we expanded the design to a generic biomolecular model to simulate system dynamics with perturbations. With the guidance of theory and simulation, we forward engineered a layered feedback controlled synthetic network in living *E.coli* cells. We successfully constructed this network with a combinatorial regulation, a activating cascade, and two nested autoregulatory motifs to achieve its desired dynamical functions. Finally, in eight sets of different dynamical perturbation experiments, we observed that the layered control feedback consistently overcomes the robustness-efficiency trade-off limit. This result not only provides validated theory guidance for controller design for synthetic biological networks. It also offers insights for understanding nature's dynamical control strategies.

The experimentally observed gene expression dynamics across different growth phases also revealed the dynamical entanglement across the populational and the molecular scales. We found that the common assumptions on constant cell division and unlimited resources are responsible for the major discrepancies between simulated and observed system dynamics. For system modeling, the quality of a model is bound by the accuracy and identifiability trade-off. Reduced models have fewer species and parameters so that they are more identifiable but less accurate and relevant due to over-simplification. On the other hand, chemical reaction network models are more accurate with fewer assumptions, but they are usually substantial in size and difficult to system identify. For future studies, we plan to layer the two types of models to overcome this trade-off. Also, we will expand the utilization of experimental data for system identification. We hope to utilize current collected dynamical data from this work to improve the accuracy and utility of biomolecular models and discover unknown mechanistic details in biomolecular networks.

Methods and Materials

Plasmid Construction and Purification

All plasmids used in this study were created using Golden Gate [28] assembly, Gibson assembly, or 3G assembly [29], with NEB® Turbo Competent *E. coli* as cloning strain. Plasmids were purified using a Qiagen QIAprep Spin Miniprep Kit (Qiagen 27104). Linear fragments were gel extracted and purified using MinElute Gel Extraction Kit (Qiagen 28606).

Model Simulations

All models were simulated by solving corresponding ODEs using MATLAB function *ode15s* over a set of discrete time steps using guessed or estimated parameters.

Strains, Growth Media and In-cell Part Characterization Experiments

All experiments were performed in *E. coli* strain JS006 [26] with either constitutively expressed RhlR or constitutively expressed CinR and RhlR [23] integrated into the chromosome with pOSIP integration plasmid into *O*-site containing Kanamycin resistance gene [30]. Plasmids with different constructs were transformed into the modified JS006 competent cells. Depending on the antibiotic resistance plated on LB + Agar plates containing 100 μg/ml carbenicillin or/and chloramphenicol, and incubated overnight at 37°C. At least three colonies of each experimental condition were inoculated into 200 μL of LB containing carbenicillin in a 2 mL 96-well block, and grown overnight at 37°C at 1000 rpm in a bench top shaker. Four microliters of the overnight culture were added to 196 μL of M9 supplemented M9 media (1X M9 minimal salts, 0.5 μg/mL thiamine hydrochloride, 1.0% glucose, 0.1% casamino acids, 0.2 mM $MgSO_4$, 0.1 mM $CaCl_2$) containing carbenicillin and/or chloramphenicol and grown for 4 hours at 37°C at 1000 rpm.

For single time-point measurements (Figure 3B, D, E), the sub-culture was then diluted 20 times with M9 its appropriate antibiotics and AHL inducers and grown in a 96 well plate for 6 hours before the measurement of fluorescence (504 nm excitation, 540 nm emission) and optical density (OD, 600 nm). The two AHL inducers used in this work are N-(3-Oxotetradecanoyl)-L-homoserine lactone (Cin, Sigma O9264) and 3-Hydroxy-C4-HSL, N-(3-Hydroxybutanoyl)-L-homoserine lactone (Rhl, Sigma 74359). Experiment in Figure 3B was grown with chloramphenicol, containing 0 μM or 200 μM of Rhl inducer; Experiment in Figure D was grown with carbenicillin and chloramphenicol, containing 0 μM or 200 μM of Rhl inducer; Experiment in Figure 3E was grown with carbenicillin and chloramphenicol with four inducer conditions: 0 μM Cin and 0 μM Rhl, 10 μM Cin and 0 μM Rhl, 0 μM Cin and 200 μM Rhl, and 10 μM Cin and 200 μM Rhl.

For time-course characterization measurements (Figure 3C, F), the sub-culture was then diluted 20X to 200 μL with M9 its appropriate antibiotics and inducers and on a 96 well plate in a Biotek SynergyH1 plate reader. The experiment in Figure 3C was grown in M9 media with carbenicillin and 10 μM Cin for 5 hours. Experiment in Figure 3F was grown in M9 media with carbenicillin, 10 μM Cin and 200 μM Rhl for 12 hours. The plate reader incubates the runs at 37°C with maximum linear shaking. It measures fluorescence (504 nm excitation, 540 nm emission) and optical density (OD 600 nm) every 10 minutes.

For RBS screening experiments that resulted in the appropriate constructs shown in figure 3D and 3E, the plasmids were assembled with an ARL (Anderson RBS library) using 3G assembly [29]. Colonies are picked and grown in 200 μL LB with carbenicillin and chloramphenicol overnight at 37°C at 1000 rpm on a benchtop shaker. Four microliters of the overnight culture were added to 196 μL of M9 supplemented

M9 media to grow to the exponential phase before the experiment. For the RBS screen experiment on CinR expression (Figure 3E), each culture resulted from a single colony was diluted 20X and grown in M9 media, induced with either Rhl only, or Cin and Rhl. The colonies that appeared to be "off" with Rhl and "on" with Cin and Rhl were selected. For the RBS screen experiment on LacI expression (Figure 3F), each culture resulted from a single colony was diluted 20X and grown in M9 media, induced with Rhl and Cin. Along with the screened colonies, a triplicate of positive control with LacI(M) was measured to provide screening reference (Figure 3F). The colonies with signals that are apparent but lower than the positive control references were selected. All selected colonies for RBS screening were sequenced, the resulting RBS sequenced were cloned into the constructs for verification with at least three replicates.

Dynamical Perturbation Experiments

All perturbation experiments were performed in JS006 *E.coli* with genome integrated RhlR. A blank ColE1 high copy plasmid is transformed with the $P_{rhl/lacO}$ controlled cassette on p15A backbone to serve as the negative control. Four colonies of negative control and five colonies of each of the four testing constructs showed in Figure 3A were picked. Cultures were grown in 200 μL LB with carbenicillin and chloramphenicol overnight at 37°C at 1000 rpm on a benchtop shaker. Four microliters of the overnight culture were added to 196 μL of M9 media and grown for four fours to prepare the sub-culture. The experiments started with a 20X dilution of the sub-culture into M9 media with carbenicillin and chloramphenicol, induced with Cin and Rhl. The plate reader incubates the runs at 37°C with maximum linear shaking. It measures fluorescence (504 nm excitation, 540 nm emission) and optical density (OD, 600 nm) every 10 minutes. The first stage of the run lasts 5.5–7 hours. After disturbances were introduced, both intact and perturbed cultures were grown in the plate reader for 2–3 hours, and the fluorescent and OD dynamics were collected. Then, the disturbance of both groups were removed. Subsequently, the run continued in the plate reader for the remainder of the 16 hours. The detailed protocols of each perturbation are listed in Table S3.

Acknowledgement

The authors would like to thank John Doyle, Fangzhou Xiao, Ayush Pandey, and Xinying Ren for their insightful discussions. The author C. Y. Hu is partially supported by Defense Advanced Research Projects Agency (Agreement HR0011-17-2-0008). The content of the information does not necessarily reflect the position or the policy of the government, and no official endorsement should be inferred.

References

[1] D. B. Pedrolli, N. V. Ribeiro, P. N. Squizato, V. N. de Jesus, D. A. Cozetto, and Team AQA Unesp at iGEM 2017, "Engineering Microbial Living Therapeutics: The Synthetic Biology Toolbox," *Trends in Biotechnology*, vol. 37, pp. 100–115, Jan. 2019.

[2] N. Rosenfeld, M. B. Elowitz, and U. Alon, "Negative autoregulation speeds the response times of transcription networks," *Journal of Molecular Biology*, vol. 323, pp. 785–793, Nov. 2002.

[3] F. Ceroni, A. Boo, S. Furini, T. E. Gorochowski, O. Borkowski, Y. N. Ladak, A. R. Awan, C. Gilbert, G.-B. Stan, and T. Ellis, "Burden-driven feedback control of gene expression," *Nature Methods*, vol. 15, pp. 387–393, May 2018.

[4] C. D. McBride, T. W. Grunberg, and D. Del Vecchio, "Design of genetic circuits that are robust to resource competition," *Current Opinion in Systems Biology*, p. 100357, July 2021.

[5] S. K. Aoki, G. Lillacci, A. Gupta, A. Baumschlager, D. Schweingruber, and M. Khammash, "A universal biomolecular integral feedback controller for robust perfect adaptation," *Nature*, vol. 97, pp. 1–21, June 2019.

[6] Y. Siu, J. Fenno, J. M. Lindle, and M. J. Dunlop, "Design and selection of a synthetic feedback Loop for optimizing biofuel tolerance," *ACS synthetic biology*, vol. 7, pp. 16–23, Jan. 2018.

[7] D. K. Agrawal, R. Marshall, V. Noireaux, and E. D. Sontag, "In vitro implementation of robust gene regulation in a synthetic biomolecular integral controller," *Nature Communications*, pp. 1–12, Dec. 2019.

[8] S. J. Doong, A. Gupta, and K. L. J. Prather, "Layered dynamic regulation for improving metabolic pathway productivity in Escherichia coli," *Proceedings of the National Academy of Sciences*, vol. 115, pp. 2964–2969, Mar. 2018.

[9] D. Del Vecchio and R. M. Murray, *Biomolecular Feedback Systems*. Princeton University Press, 2015.

[10] K. J. Aström and R. M. Murray, *Feedback Systems: An Introduction for Scientists and Engineers*. Princeton University Press, Apr. 2008.

[11] U. Alon, M. G. Surette, N. Barkai, and S. Leibler, "Robustness in bacterial chemotaxis," *Nature*, vol. 397, pp. 168–171, Jan. 1999.

[12] A. Hamadeh, M. A. J. Roberts, E. August, P. E. McSharry, P. K. Maini, J. P. Armitage, and A. Papachristodoulou, "Feedback control architecture and the bacterial chemotaxis network," *PLoS Computational Biology*, vol. 7, pp. e1001130–15, May 2011.

[13] H. El-Samad, H. Kurata, J. C. Doyle, C. A. Gross, and M. Khammash, "Surviving heat shock: control strategies for robustness and performance," *Proceedings of the National Academy of Sciences*, vol. 102, pp. 2736–2741, Feb. 2005.

[14] P. V. R. o. der, B. Wu, Y. Liu, and W. Han, "Pancreatic regulation of glucose homeostasis," *Experimental & Molecular Medicine*, vol. 48, pp. e219–19, Mar. 2016.

[15] M. C. Chen, S. K. Sorooshyari, J.-S. Lin, and J. Lu, "A Layered control architecture of sleep and arousal," *Frontiers in computational neuroscience*, vol. 14, p. 8, 2020.

[16] M. Chiang, S. H. Low, A. R. Calderbank, and J. C. Doyle, "Layering as optimization decomposition: A mathematical theory of network architectures," *Proceedings of the IEEE*, vol. 95, pp. 255–312, Feb. 2007.

[17] M. Csete and J. Doyle, "Bow ties, metabolism and disease," *Trends in Biotechnology*, vol. 22, pp. 446–450, Sept. 2004.

[18] F. A. Chandra, G. Buzi, and J. C. Doyle, "Glycolytic oscillations and limits on robust efficiency," *Science*, vol. 333, pp. 187–192, July 2011.

[19] N. Olsman, A.-A. Baetica, F. Xiao, Y. P. Leong, R. M. Murray, and J. C. Doyle, "Hard limits and performance tradeoffs in a class of antithetic integral feedback networks," *Cell Systems*, vol. 9, pp. 49–62.e17, July 2019.

[20] Y. Nakahira, Q. Liu, T. J. Sejnowski, and J. C. Doyle, "Diversity-enabled sweet spots in layered architectures and speed-accuracy trade-offs in sensorimotor control," *Proceedings of the National Academy of Sciences*, vol. 118, June 2021.

[21] J. C. Doyle and M. Csete, "Architecture, constraints, and behavior.," *Proceedings of the National Academy of Sciences*, vol. 108 Suppl 3, pp. 15624–15630, Sept. 2011.

[22] E. Yeung, A. J. Dy, K. B. Martin, A. H. Ng, D. Del Vecchio, J. L. Beck, J. J. Collins, and R. M. Murray, "Biophysical constraints arising from compositional context in synthetic gene networks," *Cell Systems*, vol. 5, pp. 11–24.e12, July 2017.

[23] Y. Chen, J. K. Kim, A. J. Hirning, K. Josic, and M. R. Bennett, "Emergent genetic oscillations in a synthetic microbial consortium," *Science*, vol. 349, pp. 986–989, Aug. 2015.

[24] J. B. Lucks, L. Qi, V. K. Mutalik, D. Wang, and A. P. Arkin, "Versatile RNA-sensing transcriptional regulators for engineering genetic networks," *Proceedings of the National Academy of Sciences*, vol. 108, pp. 8617–8622, May 2011.

[25] M. K. Takahashi and J. B. Lucks, "A modular strategy for engineering orthogonal chimeric RNA transcription regulators.," *Nucleic Acids Research*, vol. 41, pp. 7577–7588, Aug. 2013.

[26] J. Stricker, S. Cookson, M. R. Bennett, W. H. Mather, L. S. Tsimring, and J. Hasty, "A fast, robust and tunable synthetic gene oscillator," *Nature*, vol. 456, pp. 516–519, Nov. 2008.

[27] C. Y. Hu, M. K. Takahashi, Y. Zhang, and J. B. Lucks, "Engineering a functional small RNA negative autoregulation network with model-guided design," *ACS synthetic biology*, vol. 7, pp. 1507–1518, June 2018.

[28] C. Engler, R. Kandzia, and S. Marillonnet, "A one pot, one step, precision cloning method with high throughput capability," *PLoS ONE*, vol. 3, no. 11, p. e3647, 2008.

[29] A. D. Halleran, A. Swaminathan, and R. M. Murray, "Single day construction of multigene circuits with 3G assembly," *ACS synthetic biology*, vol. 7, pp. 1477–1480, May 2018.

[30] F. St-Pierre, L. Cui, D. G. Priest, D. Endy, I. B. Dodd, and K. E. Shearwin, "One-step cloning and chromosomal integration of DNA," *ACS synthetic biology*, vol. 2, pp. 537–541, May 2013.