Dynamic and stationary brain connectivity during movie watching as revealed by functional MRI

Xin Di [1][*], Zhiguo Zhang [2,3], Ting Xu [4], Bharat B. Biswal [1][*]

1. Department of Biomedical Engineering, New Jersey Institute of Technology, Newark, NJ, 07102, USA

2. School of Biomedical Engineering, Health Science Center, Shenzhen University, Shenzhen, China

3. Guangdong Provincial Key Laboratory of Biomedical Measurements and Ultrasound Imaging,

Shenzhen, China

4. Center for the Developing Brain, Child Mind Institute, New York, NY 10022, USA

* Corresponding author:

Xin Di, Ph.D.

604 Fenster Hall, University Height

Newark, NJ, 07102, USA

xin.di@njit.edu

Bharat B. Biswal, Ph.D.

607 Fenster Hall, University Height

Newark, NJ, 07102, USA

bbiswal@yahoo.com

Running title: Dynamic and stationary connectivity

Abstract

Spatially remote brain regions show synchronized activity as typically revealed by correlated functional MRI (fMRI) signals. An emerging line of research has focused on the temporal fluctuations of connectivity, however, its relationships with stationary connectivity have not been clearly illustrated. We examined dynamic and stationary connectivity when the participants watched four different movie clips. We calculated point-by-point multiplication between two regional time series to estimate the time-resolved dynamic connectivity, and estimated the inter-individual consistency of the dynamic connectivity time series. Widespread consistent dynamic connectivity was observed for each movie clip, which also showed differences between the clips. For example, a cartoon movie clip, The Present, showed more consistent of dynamic connectivity with the posterior cingulate cortex and supramarginal gyrus, while a court drama clip, A Few Good Men, showed more consistent of dynamic connectivity with the auditory cortex and temporoparietal junction, which might suggest the involvement of specific brain processing for different movie contents. In contrast, the stationary connectivity as measured by the correlations between regional time series was highly similar among the movie clips, and showed fewer statistically significant differences. The patterns of consistent dynamic connectivity could be used to classify different movie clips with higher accuracy than the stationary connectivity and regional activity. These results support the functional significance of dynamic connectivity in reflecting functional brain changes, which could provide more functionally related information than stationary connectivity.

Keywords: dynamic connectivity; movie connectome; movie watching; naturalistic stimuli; stationary connectivity

1. Introduction

The human brain exhibits a highly synchronized structure of activity as revealed by functional MRI (fMRI) in resting-state (Biswal et al., 1995, 2010), during task performance (Cole et al., 2014; Di et al., 2020; Krienen et al., 2014), and during watching naturalistic stimuli such as movies (O'Connor et al., 2017; Vanderwal et al., 2019). Functional connectivity, as measured by the correlations of observed blood-oxygen-level-dependent signals (Biswal et al., 1995; Friston, 1994), have been widely used to examine the organization of large-scale brain networks (Margulies et al., 2016; Salvador et al., 2005; Yeo et al., 2011) and to parcellate small brain structures such as the thalamus and striatum (Di Martino et al., 2008; Tian et al., 2020; Yuan et al., 2016). However, the spatial distribution of functional connectivity is highly similar across different tasks and movie watching conditions (Cole et al., 2014; Di et al., 2020; Krienen et al., 2014; Vanderwal et al., 2019). To localize functionally meaningful connections, it is therefore critical to examine the time-varying fluctuations of connectivity (Allen et al., 2014; Di and Biswal, 2020; Hutchison et al., 2013), as well as the changes of functional connectivity between different task conditions (Di and Biswal, 2019; Fornito et al., 2012; Friston et al., 1997).

Time-varying dynamic connectivity is mostly studied in the resting state by using the sliding-window approach (Allen et al., 2014; Hutchison et al., 2013; Lurie et al., 2020). It has been shown that the variability of dynamic connectivity fluctuations is lower between regions from the same functional networks and higher between regions from different networks (Fu et al., 2017), resulting in an overall negative correlation with the stationary functional connectivity (Thompson and Fransson, 2015; Zhang et al., 2018). However, because of the unconstrained nature of the resting-state, it is difficult to ensure that the obtained dynamic connectivity estimates are functionally meaningful or simply resulting from noise (Lindquist et al., 2014). Until recently, dynamic connectivity is also studied when the participants were given complex stimuli, such as watching movie clips (Di and Biswal, 2020). The advantage of using a movie stimulus is that the time course of dynamic connectivity can be compared across participants. If there are high inter-individual similarity (Hasson et al., 2004; Nastase et al., 2019), then it may imply that

the observed dynamic connectivity is functionally meaningful and is relevant to the processing of the

video stimuli.

In our previous study, we have demonstrated the inter-individual consistency of dynamic

connectivity when different participants watched the same animated movie Partly Cloudy (Di and Biswal,

2020). By using a seed-based analysis, we identified highly consistent dynamic connectivity between the

supramarginal gyrus and posterior cingulate gyrus, two regions that are critical in the processes of

empathy and theory of mind (Richardson et al., 2018). Moreover, among a set of regions of interest, the

dynamic connectivity pattern was largely dissociated with the stationary functional connectivity that was

measured by the correlations of the time series from the entire run. For example, the stationary functional

connectivity between the supramarginal gyrus and posterior cingulate gyrus was close to zero, while the

windowed dynamic connectivity showed highly consistent fluctuations. To date, only handful of studies

have examined dynamic connectivity during movie watching (Cooper et al., 2021; Di and Biswal, 2020;

Freitas et al., 2020; Simony and Chang, 2020). It is still largely unknown how the spatial pattern is

modulated by different movie contents, and how dynamic connectivity is spatially distributed.

The central goal of this study is to compare dynamic connectivity and stationary connectivity in

the context of movie watching. In addition to the previously analyzed Partly Cloudy dataset (Richardson

et al., 2018), we also analyzed the Healthy Brain Network Serial Scanning Initiative (HBN-SSI) dataset

(O'Connor et al., 2017), where same participants watched three different movie clips. The video clips

were derived from different types of movies, ranging from a science fiction cartoon comedy, a science

fiction action film, to a court drama. It is reasonable to expect that different brain systems are involved in

the process of the different movie clips. However, Vanderwal and colleagues have examined the

stationary connectivity of the three movies, and showed very similar spatial patterns among them

(Vanderwal et al., 2019). We speculate that dynamic connectivity might be more sensitive to reflect the

changes in brain functions among the movie clips.

Further, we systematically examine the relationships between dynamic and stationary

connectivity in terms of their spatial distributions and context modulations. The economic theory of brain

network organization has suggested that the maintenance of long-range between-system communications

is costly, and long-range and between-system connectivity may be more dynamic and depend on task

demands (Bullmore and Sporns, 2012). In line with this account, the dynamic connectivity between

different functional systems are more variable than within functional systems (Fu et al., 2017; Thompson

and Fransson, 2015), and task modulated connectivity are also likely to take place between regions from

different functional networks (Di and Biswal, 2019). Similarly, for the movie-watching data, we

speculate that dynamic connectivity might take place between regions from different functional modules.

In contrast, the stationary connectivity might tightly reflect the organizations of brain networks, i.e.,

higher stationary connectivity between regions from the same functional networks, and lower stationary

connectivity between regions from different networks. The dissociation might result in different spatial

patterns between the dynamic and stationary connectivity.

2. Materials and Methods

2.1. FMRI dataset

We analyzed two publicly available fMRI datasets when participants watched different movie clips, the

Partly Cloudy dataset (Richardson et al., 2018) and the HBN-SSI dataset (O'Connor et al., 2017). For the

Partly Cloudy dataset, we analyzed the adults' data where they watched the animated movie "Partly

Cloudy". And for the HBN-SSI dataset, we analyzed the data when the same participants watched three

different movie clips from different types of movies.

2.1.1. Partly Cloudy dataset

The Partly Cloudy data were obtained through openneuro (https://openneuro.org/; accession #:

ds000228). Consistent with our previous study, we only included the adult participants (n = 33) (Di and

Biswal, 2020). After dropping data due to large head motion (see below) and poor brain coverage, the

effective sample included 17 females and 12 males. The mean and standard deviation of age were 24.6

years and 5.3, respectively (age range: 18 to 39 years). The original study was approved by the

Committee on the Use of Humans as Experimental Subjects (COUHES) at the Massachusetts Institute of

Technology.

During the fMRI scan, the participants watched a 5.6-minute long silent version of Partly Cloudy

(Pixar, 2009). MRI images were acquired on a 3-Tesla Siemens Tim Trio scanner with the standard

Siemens 32-channel head coil. Blood-oxygen-level dependent (BOLD) sensitive fMRI images were

collected with a gradient-echo EPI sequence in 32 interleaved near-axial slices (EPI factor: 64; TR: 2 s,

TE: 30 ms, and flip angle: 90°). The participants were recruited for different studies with slightly

different voxel sizes and slice gaps. Three participants had 3.13 mm isotropic voxels with no gap, and 26

participants had 3.13 mm isotropic voxels with a 10% gap. All the functional images were resampled to 3

mm isotropic voxel size during preprocessing. 168 functional images were acquired, with four dummy

scans before the real scans to allow for steady-state magnetization. T1-weighted structural images were

collected in 176 interleaved sagittal slices with 1 mm isotropic voxels (GRAPPA parallel imaging,

acceleration factor of 3; FOV: 256 mm). More information can be found in Richardson et a. (2018).

2.1.2. HBN-SSI dataset

The HBN-SSI dataset was obtained through the project website

(http://fcon_1000.projects.nitrc.org/indi/hbn_ssi/). Thirteen participants were recruited in the study.

After removing data of four participants due to excessive head motion in any of the movie-watching

sessions, data from four females and five males were included in the current analysis. All the participants

are right-handed. The age range was from 23 to 37 years old (*Mean = 29.4; SD = 5.5*).

We selected the movie watching scans of three movie clips, Wall-E (Walt Disney Productions,

2008), The Matrix (Warner Bros., 1999), and A Few Good Men (Columbia Pictures, 1992), from the 12

repeated scanning sessions. Each movie clip was 10 minutes long and was watched by the same

participant four times in separate sessions. The order of the movie watching was counterbalanced across

sessions. The fMRI data were scanned using an EPI sequence with the following parameters, TR: 1,450

ms, TE: 40 ms, flip angle: 55°, and voxel size: 2.46 x 2.46 s 2.5 mm^3 without any gap. Four hundred and

twenty images were scanned for each run. However, for one participant, there were only 410 images for

several sessions. We, therefore, used the first 410 images for the current analysis for all the subjects and

sessions.

Lastly, the MPRAGE image from the first sequential scanning session of each participant was

also used to assist preprocessing of the fMRI and DWI data. The scanning parameters include TR, 2,730

ms; TE 1.64 ms; flip angle, 7°; voxel size 1 x 1 x 1 mm^3 with no gap. More information about the study

design and MRI acquisitions can be found in O'Connor et al., (2017).

2.2. FMRI data preprocessing

The fMRI data preprocessing was performed by using SPM12 (SPM, RRID: SCR_007037) under

MATLAB environment (https://www.mathworks.com/). The two datasets were preprocessed using very

similar pipelines. Specifically, the anatomical image of each participant was first segmented into gray

matter, white matter, cerebrospinal fluid, and other tissue types, and normalized into standard Montreal

Neurological Institute (MNI) space. The functional images of each session and subject were aligned to

the first image of their specific session and were coregistered to the skull stripped anatomical image of the

subject. The deformation field maps obtained from the segmentation step were used to normalize all the

functional images into MNI space. The fMRI images from the Partly Cloudy dataset were resampled to 3

x 3 x 3 mm^3 voxel size; and the images from the HBN-SSI dataset were resampled to 2.5 x 2.5 x 2.5 mm^3,

which were chosen according to their respective original voxel sizes. All the functional images were then

spatially smoothed using an 8 mm Gaussian Kernel. Lastly, we defined a generalized linear model

(GLM) for each session and subject by using 24 head motion variables (Friston et al., 1996) and a

constant term as regressors, with implicit high-pass filtering at 1/128 Hz. After model estimation, the

residual images were saved for further analysis.

We calculated framewise displacement for translation and rotation for each session and

participant (Di and Biswal, 2015). For the Partly dataset, we used strict criteria of maximum framewise

displacement of 1.5 mm or 1.5° to discard data with large head movements. Two participants' data were

discarded accordingly. For the HBN-SSI dataset, a participant's data were discarded if any of the sessions

exceeded the criteria. We adopted a slightly liberal criterion of maximum framewise displacement

greater than 2.5 mm or 2.5º or mean framewise displacement greater than 0.2 mm or 0.2º. Four

participants' data were removed accordingly.

2.3. Independent component analysis

Because the main goal of the current study is to study connectivity across brain regions, we adopted

spatial independent component analysis (ICA) to define connectivity nodes. We extracted 20 and 80 ICs

to represent different spatial scales of brain networks. We first analyzed the local activity and

connectivity with 20-IC solutions to identify statistically significant local effects. We then calculated

connectivity using the 80-IC solutions to examine their spatial distributions. For spatial ICA, the number

of ICs that could be extracted depends on the number of time points for each participant/session.

Theoretically, $t - 1$ components can be extracted where t represents the total number of time points. We

chose 80, which is roughly half of the time points for the Partly Cloudy dataset.

Group ICA of fMRI Toolbox v3.0b (Group ICA of fMRI Toolbox, RRID: SCR_001953) was

used for ICA (Calhoun et al., 2001). The ICA was performed for the Partly Cloudy and HBN-SSI

datasets separately. After extraction, we manually selected the ICs that were related to functional

networks and discarded the noise-like ICs. For the Partly Cloudy dataset, 16 and 65 ICs were considered

functionally meaningful ICs for the 20-IC and 80-IC solutions, respectively. And for the HBN-SSI

dataset, 16 and 54 ICs were kept. After ICA, the time series of each IC for each subject and session were

back reconstructed by using the group ICA algorithm. The time series were used for further activity and

connectivity analyses.

2.4. Inter-individual consistency of regional activity

For both regional activity and dynamic connectivity, we estimated the inter-individual consistency across

participants and sessions. Conventionally, the intersubject correlation was used to study the inter-

individual consistency (Chen et al., 2016; Hasson et al., 2004; Nastase et al., 2019). In our recent study,

we have shown that the principal component analysis (PCA) can be used to estimate the inter-individual

consistency, which is quantitively similar to intersubject correlation (Di and Biswal, 2021). Specifically,

for a given region we have a t (# of time points) by n (# of participants) matrix X. X is a 168 x 29 matrix

for the Partly Cloudy dataset and a 410 x 36 matrix (36 = 9 participants x 4 sessions) for each of the three

movie clips from the HBN-SSI dataset. We performed PCA on the matrix X and obtained the percent

variance explained by the first PC as a measure of intersubject consistency.

For the HBN-SSI dataset, there were four sessions for each participant and each movie. Ideally,

the multi-session and multi-participant design can be used to differentiate the consistent and idiosyncratic

responses. We have explored this issue and found that the within-participant consistency was mainly

driven by the overall across-participant consistency, but not participant-specific idiosyncratic responses

(see supplementary materials). Moreover, the idiosyncratic responses are not the focus of the current

study. Therefore, in the current analysis, we treated session and participant as separate data and

calculated inter-individual consistency across all the sessions and participants.

2.5. Dynamic connectivity

The sliding-window approach is the most commonly used method to estimate dynamic connectivity

(Allen et al., 2014; Di and Biswal, 2020; Fu et al., 2014). A recent development is to utilize point-by-

point multiplications of two time series to approximate their dynamic connectivity, a.k.a. edge-centric

time series (Faskowitz et al., 2020). The development comes from the intuition that the commonly used

measure of functional connectivity, i.e., Pearson's correlation coefficient, is the summation of the point-

by-point multiplications of two z transformed variables divided by the sample size minus 1. Therefore, if

we keep the original point-by-point multiplication time series, it can reflect estimates of dynamic

connectivity at every time point. In Figure 1, we show the averaged time series of two networks, i.e., the

posterior cingulate network and supramarginal network from the Partly Cloudy dataset. The averaged

sliding-window and point-by-point multiplication time series were also shown. Strong negative

multiplication values can be seen when the two original time series have strong anti-phase co-

fluctuations. Indeed, the peaks in the posterior cingulate network and supramarginal network represent

the theory-of-mind and pain empathy events, respectively, as indicated by the original paper (Richardson

et al., 2018). The point-by-point multiplication indicates strong negative connectivity during these

events. In contrast, the sliding window correlation can only reflect a smoothed trend of such interactions.

The point-by-point multiplication approach can avoid overly smoothing the time series data as done by

the sliding-window approach, therefore providing better interpretability of the results. On the other hand,

the multiplication term may be noisier and more prone to physiological noises and head motion artifacts.

But this may be less problematic for movie watching data, where we can estimate the consistent effects

cross individuals. We have performed statistical analyses on the Partly Cloudy dataset, and confirmed

that the point-by-point multiplication approach had better statistical sensitivity (see Supplementary

Materials). Therefore, we adopted the point-by-point multiplication approach to estimate dynamic

connectivity.

Figure 1 Averaged time series of regional activity in the posterior cingulate (PCC) network and

supramarginal network (SMG), and their point-by-point multiplication and sliding-window dynamic

connectivity when watching an animated short movie Partly Cloudy. The two brain networks shown in

the inserted slices correspond to independent components #15 and # 6 in Figure 2, respectively.

We calculated the point-by-point multiplication between each pair of networks (ICs). The time

series from each network (IC) were first z transformed, and then point-by-point multiplied. PCA was

then performed on the multiplication time series across participants. To determine the statistical

significance of the variance explained by the first PC, we performed circular time-shift randomization to

determine the null distribution (Di and Biswal, 2021; Kauppi et al., 2010). The time series from the two

network ICs from all the participants were circular-shifted with random delays. Point-by-point

multiplications were then calculated for each participant, and PCA was performed. The randomization

was performed 10,000 times for each pair of networks from the 16 networks. The real values were

compared with the null distribution to perform statistical inferences. This resulted in a 16 x 16 matrix.

False discovery rate (FDR) correction was used to correct for multiple comparisons (120: 16 x 15 / 2).

Figure 2 Illustration of the calculation of the consistency of dynamic connectivity and stationary

connectivity.

For the HBN-SSI dataset, we also compared the differences in variance explained by the first PC

among the three movies. For a pair of networks ICs, the multiplication between two IC time series were

first calculated, forming a 410 (time point) x 36 (participant/session) matrix for each movie. The matrices

from the three movie clips were concatenated to a 410 x 108 matrix, and permutation was performed

along the individual/session dimension to define three permutated matrices. The differences in variance

explained by the first PC between each movie clip and the other two clips were calculated and compared

with the permutated distributions of 10,000 times. FDR correction at $p < 0.05$ was used to correct

multiple comparisons of all three movie clips.

The randomization-based statistics were performed for all the analyses in the 20-IC solutions.

For the 80-IC solution, the goal of the analyses was not to identify specific statistically significant

connections. Rather, we examined the spatial distributions of the dynamic connectivity, and their

relations to stationary connectivity.

2.6. Relations to stationary connectivity

Next, we examined how the spatial distribution of consistent dynamic connectivity is associated with

stationary connectivity. Here we focused on a finer spatial scale of 80-IC solutions. To assess the

stationary connectivity, we calculated Fisher's z transformed Pearson's correlations across the included

networks (ICs). The matrices were averaged across individuals, and transformed back to r quantities.

First, we examined whether the dynamic and stationary connectivity has similar spatial distributions. For

both matrices, the upper triangular part was converted to vectors, which were in turn correlated with each

other between different movie clips. We adopted Spearman's correlation coefficients to avoid violations

of Gaussian distributions of the matrix data.

Next, we calculated connectivity gradients (Margulies et al., 2016; Vos de Wael et al., 2020)

based on the stationary connectivity patterns in the HBN-SSI dataset. By calculating gradients, the brain

networks (ICs) can be placed into a 2-D space based on their relative stationary connectivity strengths.

The 2-D gradients reflect large-scale brain organizations between unimodal networks and higher-order

transmodal areas (e.g. the default mode network) and between visual and sensorimotor regions (Margulies

et al., 2016). We can next display dynamic connectivity in the 2-D space to illustrate whether the

dynamic connectivity takes place between proximal or distal regions in the 2-D space. Specifically, we

first calculated the gradients for each movie clip based on the group stationary connectivity matrices

using the BrainSpace toolbox (Vos de Wael et al., 2020). The gradients were then aligned across the

movie clips with Procrustes alignment. The default diffusion-embedding and row-wise threshold (top

10% percentile) were used. After model fitting, the first two gradients were obtained. The network ICs

were mapped into the 2D gradient space. Lastly, the dynamic connectivity from the three movie clips

was plotted on the 2-D layout.

2.7. Movie clips classification

In addition to univariate analysis, we also explored whether the dynamic connectivity, stationary

connectivity, and regional activity can reliably reflect an individual's movie-watching condition (Finn et

al., 2015). The analysis was performed based on the 54 network ICs from the 80-IC solution. For each

participant of the HBN-SSI dataset, we calculated a connectivity or activity measure for each movie clip,

and also the corresponding connectivity or activity measure for the remaining 8 participants. We

compared three types of measures. First, we calculated the inter-individual consistency of point-by-point

multiplications. The individual's consistency was calculated across the four sessions of the same movie

clips. The consistency of the remaining participants was calculated across 32 participants/sessions. The

lower diagonal of the matrices was converted into a 1,431 (54 x 53 / 2) by 1 vector to perform the

classification analysis. Second, we calculated mean stationary connectivity for the individual (averaged

across 4 sessions) and the remaining participants (averaged across 32 sessions). Third, we calculated the

inter-individual consistency of the regional activity. Similarly, individual measures were calculated

across the four sessions, and the remaining participants' measures were calculated for the 32

participants/sessions. Each measure was a 54 by 1 vector, which was used for the classification analysis.

We used a winner-take-all algorithm to perform the movie clip classifications. To classify the

individual measure's state (movie clips), the individual's measures were correlated with the remaining

participants' measures from the three movie clips. The movie clips with the highest correlation were used

as the predicted class. The classification was performed for each of the 9 participants and 3 movie clips,

from which we calculated confusion matrices among the three movie clips and the overall classification

accuracy of all the three movie clips. Because three movie clips were used for the classifications, the

chance level accuracy is 33.33%. To determine statistical significance, we adopted a permutation

procedure to randomly shuffle the predicted movie label 10,000 times.

3. Results

3.1. Dynamic and stationary connectivity in 20-IC solution

We first examined the dynamic connectivity by calculating point-by-point multiplications between each

pair of 16 networks (IC) on the Partly Cloudy dataset (Figure 3a). We found widespread inter-individual

consistent effects at $p < 0.05$ of FDR correction. We also applied the sliding window approach, which

only yielded statistically significant effects on six pairs of networks (supplementary materials). This

suggests that the point-by-point multiplication approach has better sensitivity to detect dynamic

connectivity than the sliding-window approach. Although widespread, higher inter-individual

consistency was found mostly involving one network of the higher visual networks (IC# 2, 3, and 4 in

Figure 3c). And more interestingly, high inter-individual consistent dynamic connectivity was also found

between the supramarginal and default mode network (IC # 6 and 15), which was similar to our previous

analysis using a different analytic approach. In contrast, the stationary connectivity showed different

spatial patterns than the dynamic connectivity (Figure 3b). The networks with known functional

relations, e.g., all the visual related networks (IC # 1, 2, 3, and 4), had higher stationary connectivity,

which showed square-like structures along the diagonal.

Figure 3 a) Inter-individual consistent point-by-point multiplications (dynamic connectivity) across the

16 networks (independent components, ICs) from the Partly Cloudy dataset. The colors in the matrix

represent the percent variance explained by the first principal component of the point-by-point

multiplication. The red dots indicate a false discovery rate (FDR) $p < 0.05$ using a circular time-shift

randomization procedure. b) Mean stationary connectivity across the 16 network ICs. The networks are

ordered roughly according to their functions. The locations of the networks are shown in c).

Figures 4a through 4c show the consistent point-by-point multiplications among the 16 networks

(ICs) for the three movie clips in the HBN-SSI dataset. Consistent with the Partly Cloudy dataset,

widespread consistent dynamic connectivity was observed. The networks that had more consistent

dynamic connectivity were higher visual networks and the auditory network (IC 7). We further directly

compared the consistency of dynamic connectivity among the three movies (Figure 4d through 4f).

Compared with the other two movie clips, the Wall-E clip showed more consistent dynamic connectivity

between the supramarginal network (IC 6) and many other networks, and between the posterior cingulate

network (IC 13) and visual related networks. Compared with the other movie clips, the clip of The

Matrix showed greater consistency between only three pairs of networks, among the posterior visual

cortex, posterior parietal network, supramarginal network, and a left frontoparietal network. And lastly,

compared with the other two movie clips, the A Few Good Men clip showed greater consistency in the

multiplication of the auditory cortex (IC 7) with other networks, and between the temporoparietal junction

network (IC 5) and other networks.

Figure 4 a) through c), consistency of dynamic connectivity across 16 networks (independent

components, ICs) when watching the three movie clips in the Healthy Brain Network serial scanning

initiative dataset. The colors in the matrices represent the percent variance explained by the first principal

component of the point-by-point multiplication. d) through f), the differences in consistency of dynamic

connectivity between each movie clip and the other two clips. The red dots indicate statistical

significance at a false discovery rate $p < 0.05$ with permutation testing. The differences in consistency of

dynamic connectivity are also shown in graph representations in g) through i), where the node color

represents the consistency differences in regional activity. j) shows the representative maps for the 16

358   network ICs.

We also examined the relationships between regional activity consistency and dynamic

connectivity consistency. We first compared the variance explained by the first PC for regional activity

between the three movie clips (supplementary Figure S2). Four networks (ICs) showed higher

intersubject correlations in Wall-E compared with the other two movie clips, including the posterior

cingulate cortex, supramarginal gyrus, left fronto-parietal, and medial and lateral prefrontal networks.

Only one network covering the posterior parietal lobe showed higher intersubject synchronization in The

Matrix compared with the other two movie clips. Eight networks showed higher intersubject correlations

in A Few Good Men compared with the other movie clips, including the auditory cortex, medial visual,

temporo-parietal junction, and a few fronto-parietal networks. More interestingly, the regions with

greater consistency in regional activity in different movie clips seem to correspond well with the regions

with many consistent dynamic connectivities (Figure 4g through 4i).

We next examined the stationary connectivity among the 16 networks (ICs) (Figure 5). Not

surprisingly, the overall patterns in the three movies were very similar. When directly comparing the

differences among the three movies, no statistically significant differences were found even at the $p <$

0.05 threshold.

Figure 5 Top row, stationary connectivity among 16 networks (independent components, ICs) when

watching the three movie clips from Healthy Brain Network Serial Scanning Initiative dataset. Bottom

row, differences in stationary connectivity between a movie clip and the other two clips. No statistically

significant difference was found even with an uncorrected threshold of $p < 0.05$.

3.2. Dynamic and stationary connectivity in 80-IC solution

We further studied the relations between dynamic and stationary connectivity in a larger spatial scale of

the 80-IC solution. Figure 6 shows the dynamic connectivity consistency and stationary connectivity

matrices for the four movie clips. The patterns are very similar to what with the 20-IC solution. That is,

the stationary connectivity matrices showed modular structures, and were very similar across different

movie clips. In contrast, the dynamic connectivity distributions were highly skewed, with greater

consistency between lower-level brain regions such as the visual and auditory cortex.

Figure 6 Dynamic connectivity consistency (top row) and mean stationary connectivity (bottom row) for the four movie clips using the 80-independent-component solutions. Please note that the number of included independent components (ICs) are different between the Partly Cloudy dataset and the other three movie clips.

We next directly examine the correlations among the matrices. For the Partly Cloudy data, the correlation between stationary and dynamic connectivity consistency was only 0.09 (Figure 7a), although it was statistically significant due to the large number of IC pairs. The relations have been confirmed by the NBH-SSI dataset (Figure 7b). The stationary connectivity of the three movie clips had almost perfect correlations. On the other hand, the dynamic connectivity of the three movies had moderate correlations. There were very small correlations between the dynamic and stationary connectivity matrices.

Figure 7 Correlations between stationary and dynamic connectivity for the Partly Cloudy dataset (a) and

Healthy Brain Network Serial Scanning Initiative (HBN-SSI) dataset (b). The connectivity matrices were

calculated based on 80-independent-component solutions. Spearman's rank correlation (ρ) was used.

In order to show the spatial distributions of dynamic connectivity in the context of global

stationary connectivity, we calculated connectivity gradients based on the stationary connectivity of the

three movie clips in the HBN-SSI dataset (Top row in Figure 8). The first and second gradients

represented unimodal to transmodal gradient and visual to motor gradient, respectively. Next, we plotted

the top 10% of dynamic connectivity in each movie clip compared with the other two movie clips

(Bottom row in Figure 8). It can be seen that the consistent dynamic connectivity for the three movies

usually took place between networks from far connectivity space, connecting visual, sensorimotor, and

higher-order association systems. There are also notable differences among the three movie clips. For

example, for the movie clips A Few Good Men, the consistent dynamic connectivity connected the

higher-order associate areas to visual and sensorimotor regions, separately. But direct connections

between visual and sensorimotor regions were rare.

Figure 8 Top row, gradient maps of stationary connectivity in the Healthy Brain Network Serial Scanning

Initiative dataset. Bottom row, top 10% consistent dynamic connectivity in each movie clip compared

420   with the other two clips mapped to the connectivity gradient space.

3.4. Movie clips classification

Last we asked whether the dynamic or stationary connectivity pattern can enable individual-level

prediction of the different movie clips. For each participant from the HBN-SSI dataset, we classified one

of the three movie clips based on different measures. Overall, the consistency of dynamic connectivity

achieved the highest prediction accuracy (*Accuracy = 92.6%*), followed by the stationary connectivity

(*Accuracy = 85.2%*) and the consistency of regional activity (*Accuracy = 74.1%*). Compared with

chance level accuracy of 33.33%, all classification accuracies were statistically significant ($p < 0.001$)

based on permutation tests. The clip-to-clip classification results for the different features are shown in

Supplementary Table S1.

4. Discussion

In the current analysis, we have shown widespread dynamic connectivity that is consistent across

individuals when the participants watched the same movie clips. Different movie clips showed different

patterns of dynamic connectivity, suggesting that the moment-to-moment interactions between brain

regions may support the processing of context-specific information. For example, the two cartoon movie

clips showed similarly consistent dynamic connectivity between the posterior cingulate network and

supramarginal network. The action movie clip, The Matrix, showed more consistent dynamic

connectivity in networks related to attention. And the drama movie, A Few Good Men, showed more

consistent dynamic connectivity involving networks related to language processing, including bilateral

fronto-parietal networks and prefrontal cortex. In contrast, stationary connectivity showed very similar

spatial patterns in different movie clips, with few statistical differences. The dynamic connectivity

connected brain regions that are farther in the connectivity gradient space, and can better classify different

movie clips than the stationary connectivity and regional activity.

We first empirically compared the statistical results of inter-individual correlations of dynamic

connectivity measured by sliding window and point-by-point multiplication. Not surprisingly, the

multiplication approach showed higher statistical sensitivity than the sliding window approach, as

indicated by a much larger number of significant effects. It is not surprising because the point-by-point

multiplication has kept the information of every time point, while the sliding-window approach can be

seen as smoothed time series that could potentially filter out real signals. More specifically, the point-by-

point multiplication approach detected consistent interactions between almost every pair of network ICs.

This is in line with previous studies of regional activity, which also showed statistically significant effects

in almost all cortical regions (Chen et al., 2016; Di and Biswal, 2020). In contrast, the sliding window

approach can only detect a small number of the dynamic connectivity among higher visual networks, and

between supramarginal gyrus and posterior cingulate networks. This is probably because there is slow

time-varying dynamic connectivity between these regions (e.g., Figure 1), which can be detected by the

sliding window approach. This is in line with studies showing that higher-order brain regions process

longer time scale information (Baldassano et al., 2017). The results confirm the limitation of the sliding

window approach in studying dynamic connectivity.

Consistent dynamic connectivity is ubiquitous, but different movies clips were associated with

different patterns of dynamic connectivity. The movie clips from Wall-E showed a similar dynamic

connectivity pattern as another animated movie Partly Cloudy. Specifically, consistent dynamic

connectivity was mainly observed in connectivity with two networks, the supramarginal and posterior

cingulate networks. These regions involve higher-order social processes such as empathy and theory of

mind (Richardson et al., 2018; Schurz et al., 2021). This makes sense because understanding the cartoon

movies requires understanding the social interactions and intentions of the virtual characters. In contrast,

the court drama clip, A Few Good Men, showed higher dynamic connectivity consistency that involved

the auditory and temporoparietal junction networks. Because the court drama includes numerous

conversations, it is not surprising that the auditory cortex dynamically interacts with other cortical areas to

pass auditory information to those areas. The temporoparietal junction is thought to be responsible for

attributing other's mental states (Koster-Hale and Saxe, 2013; Wang et al., 2021), which may also be a

key component in understanding the conversations in the movie clip. Of course, these brain areas also

involve in many other higher-order brain functions, the correlational nature of the analysis doesn't allow a

specific function to the observed dynamic connectivity pattens (Poldrack, 2006).

In contrast to the dynamic connectivity, no differences were identified in stationary connectivity

among the three movie clips. In a larger spatial scale of 54/80 ICs, we further showed that the spatial

distribution of stationary connectivity was highly correlated among the three movie clips, which is

consistent in a previous study (Vanderwal et al., 2019). The largely similar patterns of connectivity

during watching different movies are also in line with the observations in conventional task fMRI. When

regressing out task activations (Cole et al., 2014; Di and Biswal, 2019) or using continuous task design

(Krienen et al., 2014), the stationary connectivity or task-independent connectivity showed largely similar

spatial patterns with each other and with what in resting-state. Similarly, the absolute correlation patterns

of trial-by-trial variability of the stop and go conditions in a stop signal task also showed similar patterns

with each other and with a separate resting-state run (Di et al., 2020). Taken together, all the results

convergently suggest that there is an overall connectivity pattern that may be related to the baseline brain

function, but may also be related to the underlying physiology (Chen et al., 2020) or anatomical network

structures (Laumann and Snyder, 2021). The lack of specificity of this global connectivity pattern makes

it less desirable as a measure of brain connectivity in specific cognitive and mental conditions. It should

be noted that when using multivariate classification analysis, the spatial patterns of stationary connectivity

can still be used to identify different movie clips, but with less accuracy than the dynamic connectivity

patterns. The high classification accuracy of the dynamic connectivity suggested that dynamic

connectivity could potentially be useful in predictive-based analysis to reflect individual differences (Finn

et al., 2015).

The spatial distributions of dynamic connectivity and stationary connectivity are largely

dissociated. On one hand, the dynamic connectivity could take place between regions within the same

functional systems, e.g., the visual system. This is less apparent when using the sliding-window

approach, probably due to that the sliding-window approach can only capture slow fluctuations of

dynamic connectivity. The point-by-point approach could capture the fast dynamics of the interactions.

It is reasonable that the lower-level sensory regions showed consistent interactions, but this may be

overlooked by using the conventional sliding window approach. On the other hand, the current results

also showed that dynamic connectivity could also take place between different functional systems, e.g.,

between visual areas and the default mode network. This is in line with the economic account of brain

network organizations, which suggests that transient communication between remote brain regions could

enable efficient information transmissions. When overlaying the dynamic connectivity on the

connectivity gradients space, it demonstrated more clearly that the dynamic connectivity took place

between higher association areas, such as the default mode network, and lower-level sensory or motor

regions.

One limitation of the current study is the sample size. The HBN serial scanning dataset has a

relatively small sample size (n = 9). However, each participant watched three different types of movie

clips and repeated four sessions, which enable us to directly compare connectivity among these diverse

movie types and ensure the robustness of the results within an individual. Although promising, a larger

sample size with an examination of behavioral scores is needed for future brain-behavioral association

studies (Finn and Bandettini, 2021), where researchers can directly examine the differences in behavioral

correlates between dynamic connectivity and stationary connectivity (Eichenbaum et al., 2021).

Secondly, the current analysis only focused on the spatial distributions of dynamic connectivity. Given

the ubiquitous dynamic connectivity identified in the current analysis, future studies could also examine

the time courses of the point-by-point multiplications, which could paint a more complete picture of the

dynamic connectivity.

5. Conclusion

By analyzing the inter-individual consistency of point-by-point multiplications between brain regions, we were able to identify functionally meaningful dynamic connectivity during movie watching. We found that compared with the stationary connectivity, the dynamic connectivity can be more sensitive to detect functional changes due to different movie contexts. The spatial distributions of dynamic connectivity and stationary connectivity were largely dissociated, with dynamic connectivity more reflect long-range communications. Overall, dynamic connectivity may provide more functionally related information than stationary connectivity.

Acknowledgment:

This study was supported by (US) National Institutes of Health grants R15MH125332 (XD) and R01AT009829 (BB).

Conflict of interest

The authors declare that there is no conflict of interest.

References

Allen, E.A., Damaraju, E., Plis, S.M., Erhardt, E.B., Eichele, T., Calhoun, V.D., 2014. Tracking whole-brain connectivity dynamics in the resting state. Cereb. Cortex N. Y. N 1991 24, 663–76. https://doi.org/10.1093/cercor/bhs352

Baldassano, C., Chen, J., Zadbood, A., Pillow, J.W., Hasson, U., Norman, K.A., 2017. Discovering Event Structure in Continuous Narrative Perception and Memory. Neuron 95, 709-721.e5. https://doi.org/10.1016/j.neuron.2017.06.041

Biswal, B., Yetkin, F.Z., Haughton, V.M., Hyde, J.S., 1995. Functional connectivity in the motor cortex of resting human brain using echo-planar MRI. Magn. Reson. Med. Off. J. Soc. Magn. Reson. Med. Soc. Magn. Reson. Med. 34, 537–41. https://doi.org/10.1002/mrm.1910340409

Biswal, B.B., Mennes, M., Zuo, X.-N., Gohel, S., Kelly, C., Smith, S.M., Beckmann, C.F., Adelstein, J.S., Buckner, R.L., Colcombe, S., Dogonowski, A.-M., Ernst, M., Fair, D., Hampson, M., Hoptman, M.J., Hyde, J.S., Kiviniemi, V.J., Kötter, R., Li, S.-J., Lin, C.-P., Lowe, M.J., Mackay, C., Madden, D.J.,

551   Madsen, K.H., Margulies, D.S., Mayberg, H.S., McMahon, K., Monk, C.S., Mostofsky, S.H., Nagel,
552   B.J., Pekar, J.J., Peltier, S.J., Petersen, S.E., Riedl, V., Rombouts, S.A.R.B., Rypma, B., Schlaggar,
553   B.L., Schmidt, S., Seidler, R.D., Siegle, G.J., Sorg, C., Teng, G.-J., Veijola, J., Villringer, A., Walter,
554   M., Wang, L., Weng, X.-C., Whitfield-Gabrieli, S., Williamson, P., Windischberger, C., Zang, Y.-F.,
555   Zhang, H.-Y., Castellanos, F.X., Milham, M.P., 2010. Toward discovery science of human brain
556   function. Proc. Natl. Acad. Sci. U. S. A. 107, 4734–9. https://doi.org/10.1073/pnas.0911855107
557 Bullmore, E., Sporns, O., 2012. The economy of brain network organization. Nat. Rev. Neurosci. 13, 336–
558   349. https://doi.org/10.1038/nrn3214
559 Calhoun, V.D., Adali, T., Pearlson, G.D., Pekar, J.J., 2001. A method for making group inferences from
560   functional MRI data using independent component analysis. Hum. Brain Mapp. 14, 140–51.
561 Chen, G., Shin, Y.-W., Taylor, P.A., Glen, D.R., Reynolds, R.C., Israel, R.B., Cox, R.W., 2016. Untangling the
562   relatedness among correlations, part I: Nonparametric approaches to inter-subject correlation
563   analysis at the group level. NeuroImage 142, 248–259.
564   https://doi.org/10.1016/j.neuroimage.2016.05.023
565 Chen, J.E., Lewis, L.D., Chang, C., Tian, Q., Fultz, N.E., Ohringer, N.A., Rosen, B.R., Polimeni, J.R., 2020.
566   Resting-state "physiological networks." NeuroImage 213, 116707.
567   https://doi.org/10.1016/j.neuroimage.2020.116707
568 Cole, M.W., Bassett, D.S., Power, J.D., Braver, T.S., Petersen, S.E., 2014. Intrinsic and task-evoked
569   network architectures of the human brain. Neuron 83, 238–251.
570   https://doi.org/10.1016/j.neuron.2014.05.014
571 Cooper, R.A., Kurkela, K.A., Davis, S.W., Ritchey, M., 2021. Mapping the organization and dynamics of
572   the posterior medial network during movie watching. NeuroImage 236, 118075.
573   https://doi.org/10.1016/j.neuroimage.2021.118075
574 Di Martino, a, Scheres, a, Margulies, D.S., Kelly, a M.C., Uddin, L.Q., Shehzad, Z., Biswal, B., Walters,
575   J.R., Castellanos, F.X., Milham, M.P., 2008. Functional connectivity of human striatum: a resting
576   state FMRI study. Cereb. Cortex N. Y. N 1991 18, 2735–47.
577   https://doi.org/10.1093/cercor/bhn041
578 Di, X., Biswal, B.B., 2021. Principal component analysis reveals multiple consistent responses to
579   naturalistic stimuli in children and adults 2020.05.01.073163.
580   https://doi.org/10.1101/2020.05.01.073163
581 Di, X., Biswal, B.B., 2020. Intersubject consistent dynamic connectivity during natural vision revealed by
582   functional MRI. NeuroImage 116698. https://doi.org/10.1016/j.neuroimage.2020.116698
583 Di, X., Biswal, B.B., 2019. Toward Task Connectomics: Examining Whole-Brain Task Modulated
584   Connectivity in Different Task Domains. Cereb. Cortex 29, 1572–1583.
585   https://doi.org/10.1093/cercor/bhy055
586 Di, X., Biswal, B.B., 2015. Characterizations of resting-state modulatory interactions in the human brain.
587   J. Neurophysiol. 114, 2785–96. https://doi.org/10.1152/jn.00893.2014
588 Di, X., Zhang, Z., Biswal, B.B., 2020. Understanding psychophysiological interaction and its relations to
589   beta series correlation. Brain Imaging Behav. https://doi.org/10.1007/s11682-020-00304-8
590 Eichenbaum, A., Pappas, I., Lurie, D., Cohen, J.R., D'Esposito, M., 2021. Differential contributions of static
591   and time-varying functional connectivity to human behavior. Netw. Neurosci. 5, 145–165.
592   https://doi.org/10.1162/netn_a_00172
593 Faskowitz, J., Esfahlani, F.Z., Jo, Y., Sporns, O., Betzel, R.F., 2020. Edge-centric functional network
594   representations of human cerebral cortex reveal overlapping system-level architecture. Nat.
595   Neurosci. 23, 1644–1654. https://doi.org/10.1038/s41593-020-00719-y
596 Finn, E.S., Bandettini, P.A., 2021. Movie-watching outperforms rest for functional connectivity-based
597   prediction of behavior. NeuroImage 235, 117963.
598   https://doi.org/10.1016/j.neuroimage.2021.117963

Finn, E.S., Shen, X., Scheinost, D., Rosenberg, M.D., Huang, J., Chun, M.M., Papademetris, X., Constable,
R.T., 2015. Functional connectome fingerprinting: identifying individuals using patterns of brain
connectivity. Nat. Neurosci. 18, 1664–1671. https://doi.org/10.1038/nn.4135
Fornito, A., Harrison, B.J., Zalesky, A., Simons, J.S., 2012. Competitive and cooperative dynamics of large-
scale brain functional networks supporting recollection. Proc. Natl. Acad. Sci. U. S. A. 109,
12788–12793. https://doi.org/10.1073/pnas.1204185109
Freitas, L.G.A., Bolton, T.A.W., Krikler, B.E., Jochaut, D., Giraud, A.-L., Hüppi, P.S., Van De Ville, D., 2020.
Time-resolved effective connectivity in task fMRI: Psychophysiological interactions of Co-
Activation patterns. NeuroImage 212, 116635.
https://doi.org/10.1016/j.neuroimage.2020.116635
Friston, K.J., 1994. Functional and effective connectivity in neuroimaging: A synthesis. Hum. Brain Mapp.
2, 56–78. https://doi.org/10.1002/hbm.460020107
Friston, K.J., Buechel, C., Fink, G.R., Morris, J., Rolls, E., Dolan, R.J., 1997. Psychophysiological and
modulatory interactions in neuroimaging. NeuroImage 6, 218–29.
Friston, K.J., Williams, S., Howard, R., Frackowiak, R.S., Turner, R., 1996. Movement-related effects in
fMRI time-series. Magn. Reson. Med. Off. J. Soc. Magn. Reson. Med. Soc. Magn. Reson. Med. 35,
346–55. https://doi.org/DOI 10.1002/mrm.1910350312
Fu, Z., Chan, S.-C., Di, X., Biswal, B., Zhang, Z., 2014. Adaptive covariance estimation of non-stationary
processes and its application to infer dynamic connectivity from fMRI. IEEE Trans. Biomed.
Circuits Syst. 8, 228–39. https://doi.org/10.1109/TBCAS.2014.2306732
Fu, Z., Tu, Y., Di, X., Biswal, B.B., Calhoun, V.D., Zhang, Z., 2017. Associations between Functional
Connectivity Dynamics and BOLD Dynamics Are Heterogeneous Across Brain Networks. Front.
Hum. Neurosci. 11. https://doi.org/10.3389/fnhum.2017.00593
Hasson, U., Nir, Y., Levy, I., Fuhrmann, G., Malach, R., 2004. Intersubject synchronization of cortical
activity during natural vision. Science 303, 1634–40. https://doi.org/10.1126/science.1089506
Hutchison, R.M., Womelsdorf, T., Allen, E. a., Bandettini, P. a., Calhoun, V.D., Corbetta, M., Della Penna,
S., Duyn, J.H., Glover, G.H., Gonzalez-Castillo, J., Handwerker, D. a., Keilholz, S., Kiviniemi, V.,
Leopold, D. a., de Pasquale, F., Sporns, O., Walter, M., Chang, C., 2013. Dynamic functional
connectivity: Promise, issues, and interpretations. NeuroImage 80, 360–378.
https://doi.org/10.1016/j.neuroimage.2013.05.079
Kauppi, J.-P., Jääskeläinen, I.P., Sams, M., Tohka, J., 2010. Inter-subject correlation of brain
hemodynamic responses during watching a movie: localization in space and frequency. Front.
Neuroinformatics 4. https://doi.org/10.3389/fninf.2010.00005
Koster-Hale, J., Saxe, R., 2013. Theory of Mind: A Neural Prediction Problem. Neuron 79, 836–848.
https://doi.org/10.1016/j.neuron.2013.08.020
Krienen, F.M., Yeo, B.T.T., Buckner, R.L., 2014. Reconfigurable task-dependent functional coupling
modes cluster around a core functional architecture. Philos. Trans. R. Soc. Lond. B. Biol. Sci. 369,
20130526-. https://doi.org/10.1098/rstb.2013.0526
Laumann, T.O., Snyder, A.Z., 2021. Brain activity is not only for thinking. Curr. Opin. Behav. Sci., Deep
Imaging - Personalized Neuroscience 40, 130–136.
https://doi.org/10.1016/j.cobeha.2021.04.002
Lindquist, M.A., Xu, Y., Nebel, M.B., Caffo, B.S., 2014. Evaluating dynamic bivariate correlations in
resting-state fMRI: A comparison study and a new approach. NeuroImage 101, 531–546.
https://doi.org/10.1016/j.neuroimage.2014.06.052
Lurie, D.J., Kessler, D., Bassett, D.S., Betzel, R.F., Breakspear, M., Kheilholz, S., Kucyi, A., Liégeois, R.,
Lindquist, M.A., McIntosh, A.R., Poldrack, R.A., Shine, J.M., Thompson, W.H., Bielczyk, N.Z.,
Douw, L., Kraft, D., Miller, R.L., Muthuraman, M., Pasquini, L., Razi, A., Vidaurre, D., Xie, H.,

Calhoun, V.D., 2020. Questions and controversies in the study of time-varying functional
connectivity in resting fMRI. Netw. Neurosci. 4, 30–69. https://doi.org/10.1162/netn_a_00116

Margulies, D.S., Ghosh, S.S., Goulas, A., Falkiewicz, M., Huntenburg, J.M., Langs, G., Bezgin, G., Eickhoff,
S.B., Castellanos, F.X., Petrides, M., Jefferies, E., Smallwood, J., 2016. Situating the default-mode
network along a principal gradient of macroscale cortical organization. Proc. Natl. Acad. Sci. 113,
12574–12579. https://doi.org/10.1073/pnas.1608282113

Nastase, S.A., Gazzola, V., Hasson, U., Keysers, C., 2019. Measuring shared responses across subjects
using intersubject correlation. Soc. Cogn. Affect. Neurosci. 14, 667–685.
https://doi.org/10.1093/scan/nsz037

O'Connor, D., Potler, N.V., Kovacs, M., Xu, T., Ai, L., Pellman, J., Vanderwal, T., Parra, L.C., Cohen, S.,
Ghosh, S., Escalera, J., Grant-Villegas, N., Osman, Y., Bui, A., Craddock, R.C., Milham, M.P., 2017.
The Healthy Brain Network Serial Scanning Initiative: a resource for evaluating inter-individual
differences and their reliabilities across scan conditions and sessions. GigaScience 6, 1–14.
https://doi.org/10.1093/gigascience/giw011

Poldrack, R.A., 2006. Can cognitive processes be inferred from neuroimaging data? Trends Cogn. Sci. 10,
59–63. https://doi.org/10.1016/j.tics.2005.12.004

Richardson, H., Lisandrelli, G., Riobueno-Naylor, A., Saxe, R., 2018. Development of the social brain from
age three to twelve years. Nat. Commun. 9, 1–12. https://doi.org/10.1038/s41467-018-03399-2

Salvador, R., Suckling, J., Coleman, M.R., Pickard, J.D., Menon, D., Bullmore, E., 2005. Neurophysiological
architecture of functional magnetic resonance images of human brain. Cereb. Cortex N. Y. N
1991 15, 1332–42. https://doi.org/10.1093/cercor/bhi016

Schurz, M., Radua, J., Tholen, M.G., Maliske, L., Margulies, D.S., Mars, R.B., Sallet, J., Kanske, P., 2021.
Toward a hierarchical model of social cognition: A neuroimaging meta-analysis and integrative
review of empathy and theory of mind. Psychol. Bull. 147, 293–327.
https://doi.org/10.1037/bul0000303

Simony, E., Chang, C., 2020. Analysis of stimulus-induced brain dynamics during naturalistic paradigms.
NeuroImage 216, 116461. https://doi.org/10.1016/j.neuroimage.2019.116461

Thompson, W.H., Fransson, P., 2015. The mean–variance relationship reveals two possible strategies for
dynamic brain connectivity analysis in fMRI. Front. Hum. Neurosci. 9.
https://doi.org/10.3389/fnhum.2015.00398

Tian, Y., Margulies, D.S., Breakspear, M., Zalesky, A., 2020. Topographic organization of the human
subcortex unveiled with functional connectivity gradients. Nat. Neurosci. 23, 1421–1432.
https://doi.org/10.1038/s41593-020-00711-6

Vanderwal, T., Eilbott, J., Castellanos, F.X., 2019. Movies in the magnet: Naturalistic paradigms in
developmental functional neuroimaging. Dev. Cogn. Neurosci. 36, 100600.
https://doi.org/10.1016/j.dcn.2018.10.004

Vos de Wael, R., Benkarim, O., Paquola, C., Lariviere, S., Royer, J., Tavakol, S., Xu, T., Hong, S.-J., Langs,
G., Valk, S., Misic, B., Milham, M., Margulies, D., Smallwood, J., Bernhardt, B.C., 2020.
BrainSpace: a toolbox for the analysis of macroscale gradients in neuroimaging and
connectomics datasets. Commun. Biol. 3, 1–10. https://doi.org/10.1038/s42003-020-0794-7

Wang, Y., Metoki, A., Xia, Y., Zang, Y., He, Y., Olson, I.R., 2021. A large-scale structural and functional
connectome of social mentalizing. NeuroImage 236, 118115.
https://doi.org/10.1016/j.neuroimage.2021.118115

Yeo, B.T.T., Krienen, F.M., Sepulcre, J., Sabuncu, M.R., Lashkari, D., Hollinshead, M., Roffman, J.L.,
Smoller, J.W., Zöllei, L., Polimeni, J.R., Fischl, B., Liu, H., Buckner, R.L., 2011. The organization of
the human cerebral cortex estimated by intrinsic functional connectivity. J. Neurophysiol. 106,
1125–65. https://doi.org/10.1152/jn.00338.2011

Yuan, R., Di, X., Taylor, P.A., Gohel, S., Tsai, Y.-H., Biswal, B.B., 2016. Functional topography of the
thalamocortical system in human. Brain Struct. Funct. 221, 1971–1984.
https://doi.org/10.1007/s00429-015-1018-7
Zhang, C., Baum, S.A., Adduru, V.R., Biswal, B.B., Michael, A.M., 2018. Test-retest reliability of dynamic
functional connectivity in resting state fMRI. NeuroImage 183, 907–918.
https://doi.org/10.1016/j.neuroimage.2018.08.021
699