Context-aware deconvolution of cell-cell communication with Tensor-cell2cell

Erick Armingol[1,2,7], Hratch M. Baghdassarian[1,2,7], Cameron Martino[1,2,3], Araceli Perez-Lopez[4], Caitlin Aamodt[2], Rob Knight[2,3,5,6], Nathan E. Lewis[2,6*]

[1] Bioinformatics and Systems Biology Graduate Program, University of California, San Diego, La Jolla, CA 92093, USA
[2] Department of Pediatrics, University of California, San Diego, La Jolla, CA 92093, USA
[3] Center for Microbiome Innovation, University of California San Diego, La Jolla, CA 92093, USA
[4] Biomedicine Research Unit, Facultad de Estudios Superiores Iztacala, Universidad Nacional Autónoma de México, Tlalnepantla, State of México 54090, México
[5] Department of Computer Science and Engineering, University of California San Diego, La Jolla, CA 92093, USA
[6] Department of Bioengineering, University of California, San Diego, La Jolla, CA 92093, USA
[7] These authors equally contributed to this work: Erick Armingol, Hratch Baghdassarian
*Correspondence: nlewisres@ucsd.edu

Abstract

Cell interactions determine phenotypes, and intercellular communication is shaped by cellular contexts such as disease state, organismal life stage, and tissue microenvironment. Single-cell technologies measure the molecules mediating cell-cell communication, and emerging computational tools can exploit these data to decipher intercellular communication. However, current methods either disregard cellular context or rely on simple pairwise comparisons between samples, thus limiting the ability to decipher complex cell-cell communication across multiple time points, levels of disease severity, or spatial contexts. Here we present Tensor-cell2cell, an unsupervised method using tensor decomposition, which is the first strategy to decipher context-driven intercellular communication by simultaneously accounting for multiple stages, states, or locations of the cells. To do so, Tensor-cell2cell uncovers context-driven patterns of communication associated with different phenotypic states and determined by unique combinations of cell types and ligand-receptor pairs. As such, Tensor-cell2cell robustly improves upon and extends the analytical capabilities of existing tools. We show Tensor-cell2cell can identify multiple modules associated with distinct communication processes (e.g., participating cell-cell and ligand receptor pairs) linked to COVID-19 severities and Autism Spectrum Disorder. Thus, we introduce an effective and easy-to-use strategy for understanding complex communication patterns across diverse conditions.

Introduction

Organismal phenotypes arise as cells adapt and coordinate their functions through cell-cell interactions within their microenvironments[1]. Variations in these interactions and the resulting phenotypes can occur because of genotypic differences (e.g. different subjects) or the transition from one biological state or condition to another[2] (e.g. from one life stage into another, migration from one location into another, and transition from health to disease states). These interactions are mediated by changes in the production of signals and receptors by the cells, causing changes in cell-cell communication (CCC). Thus, CCC is dependent on temporal, spatial and condition-specific contexts[3], which we refer to here as cellular contexts. "Cellular contexts" refer to variation in genotype, biological state or condition that can shape the microenvironment of a cell and therefore its CCC. Thus, CCC can be seen as a function of a context variable that is not necessarily binary and can encompass multiple levels (e.g. multiple time points, gradient of disease severities, different subjects, distinct tissues, etc.). Consequently, varying contexts trigger distinct strength and/or signaling activity[1,4–6] of communication, leading to complex dynamics (e.g. increasing, decreasing, pulsatile and oscillatory communication activities across contexts). Importantly, unique combinations of cell-cell and ligand-receptor (LR) pairs can follow different context-dependent dynamics, making CCC hard to decipher across multiple contexts.

Single-cell omics assays provide the necessary resolution to measure these cell-cell interactions and the ligand-receptor pairs mediating CCC. While computational methods for inferring CCC have been invaluable for discovering the cellular and molecular interactions underlying many biological processes, including organismal development and disease pathogenesis[5], current approaches cannot account for high variability in contexts (e.g., multiple time points or phenotypic states) simultaneously. Existing methods lose the correlation structure across contexts since they involve repeating analysis for each context separately, disregarding informative variation in CCC across such factors as disease severities, time points, subjects, or cellular locations[7]. Additional analysis steps are required to compare and

compile results from pairwise comparisons[8–11], reducing the statistical power and hindering efforts to

link phenotypes to CCC. Moreover, this roundabout process is computationally expensive, making

analysis of large sample cohorts intractable. Thus, new methods are needed that analyze CCC while

accounting for the correlation structure across multiple contexts simultaneously.

Tensor-based approaches such as Tensor Component Analysis[12] (TCA) can deconvolve patterns

associated with the biological context of the system of interest. While matrix-based dimensionality

reduction methods such as Principal Component Analysis (PCA), Non-negative Matrix Factorization

(NMF), Uniform Manifold Approximation and Projection (UMAP) and t-distributed Stochastic Neighbor

Embedding (t-SNE) can extract low-dimensional structures from the data and reflect important

molecular signals[13,14], TCA is better suited to analyze multidimensional datasets obtained from multiple

biological contexts or conditions[7] (e.g. time points, study subjects and body sites). Indeed, TCA

outperforms matrix-based dimensionality reduction methods when recovering ground truth patterns

associated with, for example, dynamic changes in microbial composition across multiple patients[15] and

neuronal firing dynamics across multiple experimental trials[12]. TCA exhibits superior performance

because it does not require the aggregation of datasets across varying contexts into a single matrix. It

instead organizes the data as a tensor, the higher order generalization of matrices, which better

preserves the underlying context-driven correlation structure by retaining mathematical features that

matrices lack[16,17]. Thus, with the correlation structure retained, the use of TCA with expression data

across many contexts allows one to gain a detailed understanding of how context shapes

communication, as well as the specific molecules and cells mediating these processes.

Here, we introduce Tensor-cell2cell, a TCA-based strategy that deconvolves intercellular

communication across multiple contexts and uncovers modules, or latent context-dependent patterns,

of CCC. These data-driven patterns reveal underlying communication changes given the simultaneous

interaction between contexts, ligand-receptor pairs, and cells. We demonstrate that Tensor-cell2cell is

broadly applicable, enabling the study of diverse biological questions about CCC in multiple organisms

and contexts. We first show that Tensor-cell2cell successfully extracts complex temporal patterns from

a simulated dataset. While our approach can simultaneously analyze more than two samples, we show

that Tensor-cell2cell is faster, demands less memory and can achieve better accuracy in separating

context-specific information in simpler analyses accessible to other tools. We further demonstrate that

Tensor-cell2cell can leverage existing CCC tools by using their output communication scores to

analyze multiple contexts.

Finally, we apply Tensor-cell2cell to two datasets, identifying communication patterns associated with

COVID-19 severity and Autism Spectrum Disorder (ASD). In the case of COVID-19, we demonstrate

that from just the single analysis of one dataset recapitulates findings across tens of published literature

resources. For example, we identify stronger interactions between epithelial and immune cells with

increased severity[18] and M1- and M2-like macrophage communication distinguishing moderate from

severe cases. In the case of ASD, we focus on a data-driven analysis, exemplifying the possible

downstream analyses that can be run on the outputs of Tensor-cell2cell, including pathway enrichment,

clustering, and the generation of factor-specific communication networks. From these analyses we also

show that combinations of CCC dysregulation across multiple context-dependent patterns distinguish

ASD patients from controls. Thus, Tensor-cell2cell's easily interpretable output enables quick

identification of key mediators of cell-cell communication across contexts, both reproducing known

results and identifying novel interactors.

Results

Deciphering context-driven communication patterns with Tensor-cell2cell

Organizing biological data through a tensor preserves the underlying correlation structure of the

biological conditions of interest[12,15,17]. Extending this approach to infer cell-cell communication enables

analysis of important ligand-receptor pairs and cell-cell interactions in a context-aware manner.

Accordingly, we developed Tensor-cell2cell, a method based on tensor decomposition[17] that extracts

context-driven latent patterns of intercellular communication in an unsupervised manner. Briefly,

Tensor-cell2cell first generates a 4D-communication tensor that contains non-negative scores to

represent cell-cell communication across different conditions (Figures 1a-c). Then, a non-negative

TCA[19] is applied to deconvolve the latent CCC structure of this tensor into low-dimensional components

or factors (Figures 1d-e). Thus, each of these factors can be interpreted as a module or pattern of

communication whose dynamics across contexts is indicated by the loadings in the context dimension

(Figure 1e).

To demonstrate how Tensor-cell2cell recovers latent patterns of communication, we simulated a

system of 3 cell types interacting through 300 LR pairs across 12 contexts (represented in our

simulation as time points) (Figure 2a). We built a 4D-communication tensor that incorporates a set of

embedded patterns of communication that were assigned to certain LR pairs used by specific pairs of

interacting cells, and represented through oscillatory, pulsatile, exponential, and linear changes in

communication scores (Figures 2a-f; see Supplementary Notes for further details of simulating and

decomposing this tensor). Using Tensor-cell2cell, we found that four factors led to the decomposition

that best minimized error (Supplementary Figure S1a), consistent with the number of introduced

patterns (Figure 2f). This was robustly observed in multiple independent simulations (Supplementary

Figure S2a).

Our simulation-based analysis further demonstrates that Tensor-cell2cell accurately detects context-

dependent changes of communication, and identifies which LR pairs, sender cells, and receiver cells

are important (Figure 2g). In particular, the context loadings of the TCA on the simulated tensor

accurately recapitulate the introduced patterns (Figures 2f-g), while ligand-receptor and cell loadings

properly capture the ligand-receptor pairs, sender cells and receiver cells assigned as participants of

the cognate pattern (Figure 2g). Indeed, we observed a concordance between the "ground truth" LR

pairs assigned to a pattern and their respective factor loadings through Jaccard index and Pearson

correlation metrics (Supplementary Tables S1-S2**)**. Moreover, Tensor-cell2cell robustly recovered

communication patterns when we added noise to the simulated tensor (Supplementary Figure S2 and

Supplementary Notes).

Figure 1. Tensor representation and factorization of cell-cell communication. In a given context (n-th context among N total contexts), cell-cell communication scores (see available scoring functions in REF[5]) are computed from the expression of the ligand and the receptor in a LR pair (k-th pair among K pairs) for a specific sender-receiver cell pair (i-th and j-th cells among I and J cells, respectively). This results in a communication matrix containing all pairs of sender-receiver cells for that LR pair (**a**). The same process is repeated for every single LR pair in the input list of ligand-receptor interactions, resulting in a set of communication matrices that generate a 3D-communication tensor (**b**). 3D-communication tensors are built for all contexts and are used to generate a 4D-communication tensor wherein each dimension represents the contexts (colored lines), ligand-receptor pairs, sender cells and receiver cells (**c**). A non-negative TCA model approximates this tensor by a lower-rank tensor equivalent to the sum of multiple factors of rank-one (R factors in total) (**d**). Each component or factor (r-th factor) is built by the outer product of interconnected descriptors (vectors) that contain the loadings for describing the relative contribution that contexts, ligand-receptor pairs, sender cells and receiver cells have in the factor (**e**). For interpretability, the behavior that context loadings follow represent a communication pattern across contexts. Hence, the communication captured by a factor is more relevant or more likely to be occurring in contexts with higher loadings. Similarly, ligand-receptor pairs with higher loadings are the main mediators of that communication pattern. By constructing the tensor to account for directional interactions (panels a-b), ligands and receptors in LR pairs with high loadings are mainly produced by sender and receiver cells with high loadings, respectively.

152
Figure 2. Tensor-cell2cell recovers simulated communication patterns. (**a**) Cell-cell communication scenario used for
simulating patterns of communication across different contexts (here each a different time point). (**b**) Examples of specific
ligand-receptor (LR) and (**c**) cell-cell pairs that participate in the simulated interactions. Individual LR pairs and cell pairs were
categorized into groups of signaling pathways and cell types, respectively. In this simulation, signaling pathways did not
overlap in their LR pairs, and each pathway was assigned 100 different LR pairs. (**d**) Distinct combinations of signaling
pathways with sender-receiver cell type pairs were generated (LR-CC combinations). LR-CC combinations that were assigned
the same signaling pathway overlap in the LR pairs but not in the interacting cell types. (**e**) A simulated 4D-communication
tensor was built from each time point's 3D-communication tensor. Here, a communication score was assigned to each ligand-
receptor and cell-cell member of a LR-CC combination. Each communication score varied across time points according to a
specific pattern. (**f**) Four different patterns of communication scores were introduced to the simulated tensor by assigning a
unique pattern to a specific LR-CC combination. From top to bottom, these patterns were an oscillation, a pulse, an
exponential decay and a linear decrease. The average communication score (y-axis) is shown across time points (x-axis). This
average was computed from the scores assigned to every ligand-receptor and cell-cell pair in the same LR-CC combination.
(**g**) Results of running Tensor-cell2cell on the simulated tensor. Each row represents a factor, and each column a tensor
dimension, wherein each bar represents an element of that dimension (e.g. a time point, a ligand-receptor pair, a sender cell
or a receiver cell). Factor loadings (y-axis) are displayed for each element of a given dimension. Here, the factors were visually
matched to the corresponding latent pattern in the tensor, and their loadings were normalized to unit Euclidean length.

Tensor-cell2cell adds new capabilities to cell-cell communication analysis

To demonstrate the power of accounting for multiple contexts simultaneously, we compared the

computational efficiency and accuracy of our method with respect to CellChat[10], the only tool that

summarizes multiple pairwise comparisons in an automated manner (Table 1). Since CellChat cannot

extract patterns of CCC across multiple contexts, we instead use the output of its joint manifold learning

on pairwise-based changes in signaling pathways as a comparable proxy to the output of Tensor-

cell2cell. Despite the use of these proxy comparisons, we emphasize that the conceptual outputs

reported by Tensor-cell2cell are unique. Briefly, we found that Tensor-cell2cell is faster, uses less

memory, and achieves higher accuracy when analyzing CCC of multiple samples (Supplementary

Figure S3); using a GPU further increases computational speed of Tensor-cell2cell. See more details

regarding this comparison in the Methods and *Tensor-cell2cell is fast and accurate* section of the

Supplementary Notes.

A major advantage of Tensor-cell2cell is that it acts as a robust dimensionality reduction method for any

communication scores arranged as a tensor. To illustrate this, we set out to harness the sample-wise

communication scoring outputs of other tools. Tensor-cell2cell can restructure these outputs into a 4D-

communication tensor (Figure 1), extending their capabilities to recover context-dependent patterns of

communication. This generalizability enables users to employ any scoring method. Thus, we ran

Tensor-cell2cell on communication scores generated by sample-specific analysis with CellPhoneDB[20],

CellChat[10], NATMI[9], and SingleCellSignalR[21], as well as the built-in scoring of Tensor-cell2cell.

Specifically, we analyzed twelve bronchoalveolar lavage fluid (BALF) samples from patients with

different severities of COVID-19 (healthy, moderate and severe) with each method listed above. We

assessed the consistency of decomposition between all five scoring methods by using the CorrIndex[22].

The CorrIndex value lies between 0 and 1, with a higher score indicating more dissimilar decomposition

outputs; we thus report our similarity results as (1-CorrIndex). Our results indicate that Tensor-cell2cell

can consistently identify context-dependent communication patterns independent of the initial

communication scoring method (Figure 3a, Supplementary Figure S4), with a mean similarity score of

0.82. Furthermore, differences in decomposition results are driven at the ligand-receptor resolution, yet

tend not to propagate to the cell- or context-resolution (Supplementary Notes and Supplementary

Figures S5-6). While these results agree with previous reports regarding the inconsistency of scoring

methods for ligand-receptor interactions[23], they also show the power of tensor decomposition to resolve

these inconsistencies and identify biologically and conceptually consistent communication patterns.

Since Tensor-cell2cell requires the use of multiple conditions or samples, we also assessed biases that

may have been introduced by batch effects during gene expression count transformation (e.g.,

normalization, batch correction, etc). Specifically, we assessed the impact of applying the log(CPM+1)

and the fraction of non-zero cells as preprocessing methods[24], and ComBat[25] and Scanorama[26] as

batch-effect correction. Here, we also used the BALF COVID-19 samples and built the 4D-tensors

using the gene expression values obtained in each case. After running the tensor decomposition, these

strategies generated results that seem biologically comparable, as measured with a mean similarity

score of 0.86 (Figure 3b). As expected, using the raw counts leads to the most biased and different

results in comparison to the other preprocessing methods; the mean similarity score between raw

counts and all other approaches is 0.77. In contrast, the highest similarity was between the log(CPM+1)

and the non-zero fraction of cells. This result is also expected since the non-zero fraction of cells is

comparable to the log(CPM+1). However, the non-zero fraction performs better in comparisons of lowly

expressed genes[24](e.g. receptors on the cell surface[27]), so we included this fraction as part of the

Tensor-cell2cell built-in workflow. Thus, Tensor-cell2cell can detect consistent CCC signatures

independent of the method by which gene expression is corrected, with the exception of raw counts, as

indicated by the high similarities observed (Figure 3b).

Table 1. Methodological strategy and context-based analysis in available tools

Tool	Communication Score[a]	Context Evaluation	Simultaneous Contexts	Multimeric LR pairs	Data Resolution	Platform	Refs.
Tensor-cell2cell	Expression Mean, Expression Product and Geometric Mean	Builds a tensor with all contexts simultaneously and runs a tensor decomposition, accounting for the correlation structure across contexts	Unlimited[b]	Yes	Bulk, Single Cell	Python	This work
CellChat	Mass-action-based probability	Runs separate analyses of each context, does pairwise comparisons and harmonizes them through a joint manifold learning	2	Yes	Single Cell	R	[10]
CellPhoneDB	Expression Mean	None	1	Yes	Single Cell	Python	[20]
CellTalker	Differential Combinations	Differential analysis between two contexts	2	No	Single Cell	R	[8]
Connectome	Modified Expression Product	Differential analysis between two contexts. An overall analysis of cell-type importance can be done for more contexts	2	No	Single Cell	R	[11]
ICELLNET	Expression Product	None	1	Yes	Bulk, Single Cell	R	[28]
iTalk	Differential Combinations	Differential analysis between two contexts	2	No	Single Cell	R	[29]
NATMI	Expression Product and Normalized Expression Product	None	1	No	Bulk, Single Cell	Python	[9]
NicheNet	Personalized-PageRank-based score	None	1	No	Bulk, Single Cell	R	[30]
scAgeCom	Geometric Mean	Differential analysis between two contexts	2	Yes	Single Cell	R	[31]
scTensor	Expression Product	None	1	No	Single Cell	R	[32]
SingleCellSignalR	Regularized Expression Product	None	1	No	Single Cell	R	[21]

218 [a] For further details about distinct communication scores, see REF[5] and/or respective references for each tool.
219 [b] Dependent on computational resources (e.g. memory availability)
220 LR, ligand-receptor
221
222
223

Figure 3. Comparison of tensor decompositions resulting from varying input values. The similarity of tensor decompositions performed on 4D-communication tensors constructed from the single-cell dataset of BALF in patients with varying severities. For a given comparison, constructed tensors have the same elements in each dimension. (**a**) Similarity between tensor decompositions performed on 4D-communication tensors, each corresponding to communication scores computed from different tools for inferring cell-cell communication. The scoring functions correspond to those of CellChat[10], CellPhoneDB[20], NATMI[9], SingleCellSignalR[21] and the built-in methods in Tensor-cell2cell. (**b**) Similarity between tensor decompositions performed on 4D-communication tensors, each modifying the gene expression values by different preprocessing methods (log(CPM+1) and the fraction of non-zero cells[24]) or batch-effect correction methods (Combat[25] and Scanorama[26]), as well as using the raw counts. The communication scores in (**b**) were calculated as the mean expression between the partners in each LR pair, previously aggregating gene expression at the single-cell level into the cell-type level. In (**a**) and (**b**) similarity was measured as (1-CorrIndex), where the CorrIndex[22] is a distance metric for comparing different decompositions on tensors containing the same indices and its values range from 0 to 1 (more similar to more dissimilar). Assessed methods were hierarchically clustered by the similarities of their tensor decompositions.

Tensor-cell2cell links intercellular communication with varying severities of COVID-19

Great strides have been made to unravel molecular and cellular mechanisms associated with SARS-CoV-2 infection and COVID-19 pathogenesis. Thus, we tested our method on a single-cell dataset of BALF samples from COVID-19 patients[33] to see how many cell-cell and LR pair relationships in COVID-19 could be revealed by Tensor-cell2cell. By decomposing the tensor associated with this dataset into 10 factors (Figure 4a and Supplementary Figure S1b), Tensor-cell2cell found factors representing communication patterns that are highly correlated with COVID-19 severity (Figure 4c) and other factors

that distinguish features of the different disease stages (Supplementary Figure S7), consistent with the

high performance that the classifier achieved for this dataset (Supplementary Figure S3f,h).

Furthermore, these factors involve signaling molecules previously linked with severity in separate works

(Supplementary Table S3).

The first two factors capture CCC involving autocrine and paracrine interactions of epithelial cells with

immune cells in BALF (Figure 4a). The sample loadings of these factors reveal a communication

pattern wherein the involved LR and cell-cell interactions become stronger as severity increases

(Spearman correlation of 0.72 and 0.61, Figure 4c and Supplementary Figure S7). Although this

observation was not reported in the original study, it is consistent with a previous observation of a

correlation between COVID-19 severity and the airway epithelium-immune cell interactions[18].

Specifically, epithelial cells are highlighted by Tensor-cell2cell as the main sender cells in factor 1

(Figure 4a), and we further provide new details of the molecular mechanisms involving top ranked

signals such as APP, MDK, MIF and CD99 (Figure 4b). These molecules have been reported to be

produced by epithelial cells[34–40] and participate in immune cell recruiting[36–38,41], in response to

mechanical stress in lungs[39] and regeneration of the alveolar barrier during viral infection[40]. In addition,

epithelial cells act as the main receiver in factor 2 (Figure 4a), involving proteins such as PLXNB2,

SDC4 and F11R (Figure 4b), which were previously determined important for tissue repair and

inflammation during lung injury[42–44]. Remarkably, a new technology for experimentally tracing CCC

revealed that SEMA4D-PLXNB2 interaction promotes inflammation in a diseased central nervous

system[45]; our approach suggests a similar role promoting inflammation in severe COVID-19,

specifically mediating the communication between immune and epithelial cells, as reflected in factor 2

(Figure 4b).

268
Figure 4. Deconvolution of intercellular communication in patients with varying severity of COVID-19. (**a**) Factors
obtained after decomposing the 4D-communication tensor from a single-cell dataset of BALF in patients with varying severities
of COVID-19. 10 factors were selected for the analysis, as indicated in Supplementary Figure S1b. Here, the context
corresponds to samples coming from distinct patients (12 in total, with three healthy controls, three moderate infections, and
six severe COVID-19 cases). Each row represents a factor and each column represents the loadings for the given tensor
dimension (samples, LR pairs, sender cells and receiver cells), normalized to unit Euclidean length. Bars are colored by
categories assigned to each element in each tensor dimension, as indicated in the legend. (**b**) List of the top 5 ligand-receptor
pairs ranked by loading for each factor. The corresponding ligands and receptors in these top-ranked pairs are mainly
produced by sender and receiver cells with high loadings, respectively. Ligand-receptor pairs with supporting evidence
(Supplementary Table S3) for a relevant role in general immune response (black bold) or in COVID-19-associated immune
response (red bold) are highlighted. (**c**) Coefficients associated with loadings of each factor: Spearman coefficient quantifying
correlation between sample loadings and COVID-19 severity, and Gini coefficient quantifying the dispersion of the edge
weights in each factor-specific cell-cell communication network (to measure the imbalance of communication). Important
values are highlighted in red (higher absolute Spearman coefficients represent stronger correlations; while smaller Gini
coefficients represent distributions with similar edge weights).

Our strategy also elucidates communication patterns attributable to specific groups of patients

according to disease severity (Figure 4a). For example, we found interactions that are characteristic of

severe (factor 8) and moderate COVID-19 (factors 3 and 10), and healthy patients (factor 9) (adj. P-

value < 0.05, Supplementary Figure S7). Factor 8 was the most correlated with severity of the disease

(Spearman coefficient 0.92, Figure 4c) and highlights macrophages playing a major role as pro-

inflammatory sender cells. Their main signals include CCL2, CCL3 and CCL8, which are received by

cells expressing the receptors CCR1, CCR2 and CCR5 (Figure 4b). Consistent with our result, another

study of BALF samples[18] revealed that critical COVID-19 cases involve stronger interactions of cells in

the respiratory tract through ligands such as CCL2 and CCL3, expressed by inflammatory

macrophages[18]. Moreover, the inhibition of CCR1 and/or CCR5 (receptors of CCL2 and CCL3) has

been proposed as a potential therapeutic target for treating COVID-19[18,46]. Tensor-cell2cell also

deconvolved patterns attributable to moderate rather than severe COVID-19, also highlighting

interactions driven by macrophages (factors 3 and 10; Figure 4a). However, top-ranked molecules

(Figure 4b) and gene expression patterns (Supplementary Figure S8) suggest that the intercellular

communication is led by macrophages with an anti-inflammatory M2-like phenotype, in contrast to

factor 8 (pro-inflammatory phenotype). Multiple top-ranked signals in factors 3 and 10 have been

associated with an M2 macrophage phenotype acting in the immune response to SARS-CoV-2[47–52].

In contrast to severe and moderate COVID-19 patients, communication patterns associated with

healthy subjects involve all sender-receiver cell pairs with a similar importance. In particular, factor 9

(Figure 4a) demonstrated the smallest Gini coefficient (0.09; Figure 4c), which measures the extent to

which edge weights between sender and receiver cells are evenly distributed in the factor-specific cell-

cell communication network. Smaller Gini coefficients show more even distributions, i.e., more equally

weighted potential of communication across sender and receiver cell pairs (see **Methods**). This

indicates that the intercellular communication represented by factor 9 is ubiquitous across cell types.

Thus, this conservation across cells may be an indicator of communication during homeostasis, since

the context loadings for this factor are not associated with disease (Supplementary Figure S7).

Interestingly, a top-ranked LR pair in factor 9 is MIF-CD74/CD44 (Figure 4b), which is consistent with

ubiquitous expression of MIF across tissues and its protective role in normal conditions[40,53]. Thus,

Tensor-cell2cell extracts communication patterns distinguishing one group of patients from another and

detects known mechanisms of immune response during disease progression (Supplementary Notes),

which is important for therapeutic applications.

Tensor-cell2cell elucidates communication mechanisms associated with Autism

Spectrum Disorders

Dysregulation of neurodevelopment in Autism Spectrum Disorders (ASD) is associated with perturbed

signaling pathways and CCC in complex ways[54]. To understand these cellular and molecular

mechanisms, we analyzed single-nucleus RNA-seq (snRNA-seq) data from postmortem prefrontal

brain cortex (PFC) from 13 ASD patients and 10 controls[55]. We built a 4D-communication tensor

containing 16 cell types present in all samples, including neurons and non-neuronal cells, and 749 LR

pairs; then we used Tensor-cell2cell to deconvolve their associated CCC into 6 context-driven patterns

(Figure 5a and Supplementary Figure S1c). In these factors, we observe communication between all

neurons (factor 1), as well as communication of specific neurons in the cortical layers I-VI (factors 2 and

3), interneurons (factor 4), astrocytes and oligodendrocytes (factor 5), and endothelial cells (factor 6).

Tensor-cell2cell's outputs can be further dissected using downstream analyses with common

approaches. To illustrate this, we ranked the LR pairs by their loadings in a factor-specific fashion, and

ran Gene Set Enrichment Analysis[56] (GSEA) using LR pathway sets built from KEGG pathways[57] (see

Methods). We observed that each factor was associated with different biological functions including

axon guidance, cell adhesion, extracellular-matrix-receptor interaction, ERBB signaling, MAPK

signaling, among others (Figure 5b). Dysregulation of axon guidance, synaptic processes and MAPK

pathway have been previously linked to ASD from differential analysis[55,58], supporting our observations.

Moreover, our results extend to other roles associated with extracellular matrix, focal adhesion of cells,

regulation of actin cytoskeleton, and signaling through ErbB receptors, which involves Akt, PI3K, and

mTOR pathways, as well as regulation of cell proliferation, migration, motility, differentiation, and

apoptosis[59]. Thus, Tensor-cell2cell outputs can be used to assign macro-scale biological functions to

each of the factors, extending the interpretation of factor-specific CCC.

After identifying main pathways involved in each factor, one can further use sample loadings to identify

how these functions are associated with each sample group. By doing so, we found that factors 3 and 4

significantly distinguish ASD from typically-developing controls (Figure 5c). Neurons in cortical layers

are the main sender cells in factor 3, while interneurons are key receiver cell types in factor 4 (Figure

5a and Supplementary Figure S9), with parvalbumin interneurons (IN-PV), and SV2C-expressing

interneurons (IN-SV2C) as the top ranked cells, consistent with the previously reported cell types that

are more affected in ASD condition[55] (i.e., with a greater number of dysregulated genes), and that

correspond to neurons in the cortical layers I-VI, IN-SV2C and IN-PV. Thus, considering the overall

decreased sample loadings in the ASD group, the GSEA results, and the factor-specific CCC networks

built from the cell loadings (Supplementary Figure S9), our analysis suggests that there is a

downregulation of axon guidance, cell adhesion, and ERBB signaling involving neurons in cortical

layers I-VI and interneurons in ASD patients. See Supplementary Notes for further discussion.

Clustering methods can be applied for grouping samples in an unsupervised manner. Thus, we can

assess the overall similarity between samples across all factors; considering combinations of factors

can offer additional insights to the analysis as compared to considering one factor at a time. We use

hierarchical clustering to group samples into four main clusters (Figure 5d). Cluster 1 mainly groups

controls, cluster 2 is not associated with any category, cluster 3 mostly represents ASD patients, and

cluster 4 is completely related to ASD condition. These clusters also reveal that combinations of factors

separate samples by ASD and control groups. For example, samples in cluster 1 seem to have smaller

loadings in factors 1 and 5, and higher loadings in factors 3 and 4. Interestingly, the only ASD sample

present in this cluster had the smallest ASD clinical score, suggesting that CCC mechanisms are more

similar to controls when the phenotype is mild. In contrast, cluster 3 shows an opposite CCC behavior

to cluster 1. Cluster 4 also reveals that the combination of factor 6 with low sample loadings and factors

1 and 5 with high values is a strong marker of several ASD patients, even though factors 1, 5, and 6 did

not show significant differences between sample groups (Figure 5c). Based on this, patients in cluster 4

had increased CCC through the NRXNs-NRLGs, CTNs-NRCAMs, and NCAMs-NCAMs interactions

(synapse and cell adhesion) in neurons as senders and receivers, and astrocytes and oligodendrocytes

as receivers, as well as a decreased CCC through VEGFs-FLT1, PTPRM-PTPRM, and PTN-NCL

interactions (angiogenesis, neural migration and neuroprotection) related to endothelial cells as the

main receivers (Supplementary Table S4). Finally, both ASD-clusters seem to be slightly distinct in

terms of phenotype, considering their mean clinical scores of 25.0 and 22.8, respectively for clusters 3

and 4, but without significant differences. Thus, downstream analyses reveal that multiple

dysregulations of CCC patterns captured by Tensor-cell2cell occur simultaneously in ASD condition

(Figure 5d), even though these patterns could not explain phenotypic differences when considered in

isolation (Figures 5c).

374 **Figure 5. Application of Tensor-cell2cell to study mechanisms underlying intercellular communication in patients**
375 **with ASD.** (**a**) Factors obtained after decomposing the 4D-communication tensor from a single-nucleus dataset of prefrontal
376 brain cortex samples from patients with or without ASD. Six factors were selected for the analysis, as indicated in
377 Supplementary Figure S1c. Here, the context corresponds to samples coming from distinct patients (23 in total, with thirteen
378 ASD patients and ten controls). Each row represents a factor and each column represents the loadings for the given tensor
379 dimension (samples, LR pairs, sender cells and receiver cells), normalized to unit Euclidean length. Bars are colored by
380 categories assigned to each element in each tensor dimension, as indicated in the legend. Cell-type annotations are those
381 used in REF[55]. (**b**) GSEA performed on the pre-ranked LR pairs by their respective loadings in each factor, and using KEGG
382 pathways. Dot sizes are proportional to the negative logarithmic of the P-values, as indicated at the top of the panel. The
383 threshold value indicates the size of a P-value=0.05. The dot colors represent the normalized enrichment score (NES) after

the permutations performed by the GSEA, as indicated by the colorbar. (**c**) Boxplot representation for ASD and control groups
of patients. Each panel represents the sample loadings, grouped by disease condition, in each of the factors. Groups were
compared by a two-sided independent t-test, followed by a Bonferroni correction. Annotations of significance are ns (P-value
>= 0.05) and * (0.01 < P-value < 0.05). (**d**) Heatmap of the standardized sample loadings across factors (z-scores) for each of
the samples. An agglomerative hierarchical clustering was performed on the z-scores to group both samples and factors.
Major clusters of the samples are indicated at the bottom. The category of each sample is colored on the top, according to the
legend. A clinical score of each patient is also shown, according to the colorbar. Controls, and ASD samples without an
assigned score, were colored gray. This clinical score summarizes the social interactions, communication, repetitive
behaviors, and abnormal development of the patients, as indicated in REF[55].

Discussion

Here we present Tensor-cell2cell, a computational approach that identifies modules of cell-cell

communication and their changes across contexts (e.g., across subjects with different disease severity,

multiple time points, different tissues, etc.). Our approach can rank LR pairs based on their contribution

to each communication module and connect these signals to specific cell types and phenotypes.

Tensor-cell2cell's ability to consider multiple contexts simultaneously to identify context-dependent

communication patterns is novel, in contrast to state-of-the-art tools that are either unaware of the

context driving CCC[5,20,30,60] or require analysis of each context separately to perform pairwise

comparisons in posterior steps[10,61]. Tensor-cell2cell is therefore a flexible method that can integrate

multiple datasets and readily identify patterns of intercellular communication in a context-aware

manner, reporting them through interconnected and easily interpretable scores.

Tensor-cell2cell robustly detects communication patterns using many other scoring methods[13]. Thus,

our method is not only an improvement over other tools, but also greatly extends these tools, enabling

new analyses with existing methods. One can choose any tool of interest, run it on each context

separately, and use the resulting communication scores to build and deconvolve a 4D-communication

tensor. Other tools, such as CellChat, allow the generation of scores at the signaling pathway level

instead of LR pairs. This, combined with Tensor-cell2cell, could provide additional information about

changes in signaling pathways. Thus, Tensor-cell2cell can also be used for analyzing any other score

linking gene expression from cell pairs, beyond just scores based on protein-protein interactions. In this

regard, our tool outputs consistent results regardless of the preprocessing and batch correction method

we evaluated (Figure 3b). Nevertheless, it is best practice to employ integration/batch-correction

methods to correct gene expression and annotate cell types before running Tensor-cell2cell to ensure

this source of variation is controlled[62].

Tensor-cell2cell is faster for analyzing multiple samples than pairwise comparisons, providing a

considerable improvement in running time and reduced memory requirements (Supplementary Notes).

Tensor-cell2cell's runtime can be further accelerated when a GPU is available (Supplementary Figure

S3a). It is also more accurate, resulting in 10-20% higher classification accuracy of subjects with

COVID-19 when compared to CellChat (Supplementary Figures S3e-h). However, we note that

benchmarking CCC prediction tools is challenging due to the lack of a ground truth[5], and it is hard to

compare and evaluate tools because of the qualitative differences in their outputs[23] (Supplementary

Notes). While pairwise comparisons can be informative about differential cellular and molecular

mediators of communication, the results are less interpretable (Supplementary Figures S10-13), do not

provide the multi-scale resolution available in Tensor-cell2cell (Figures 4a and 5a), and do not identify

context-dependent patterns.

Meaningful biology can be easily identified from Tensor-cell2cell. For example, a manual interpretation

of the BALF COVID-19 decomposition found communication results not previously observed in the

original study[33] and recapitulated findings spanning tens of peer-reviewed articles (Supplementary

Table S3). This included a correlation between the lung epithelium-immune cell interactions and

COVID-19 severity[18] and molecular mediators that distinguished moderate and severe COVID-19 (see

Tensor-cell2cell elucidates molecular mechanisms distinguishing moderate from severe COVID-19 in

the Supplementary Notes). Additionally, Tensor-cell2cell results can be coupled with downstream

analysis methods to facilitate interpretation and provide further insights of underlying mechanisms. In

our ASD case-study (Figure 5), such analyses included GSEA, clustering, visualization and statistical

comparison of factors, and factor-specific analysis of sender-receiver communication networks

(Supplementary Figure S9). In the ASD case-study, we found dysregulated CCC directly distinguished

ASD patients from controls and was linked with a downregulation of axon guidance, cell adhesion,

synaptic processes, and ERBB signaling in cortical neurons and interneurons (Figures 5a,b), consistent

with previous evidence[55,58,63,64]. Moveover, accounting for the combinatorial relationship of samples

across factors demonstrated additional complex relationships of CCC dysregulation (Figure 5d).

A limitation to consider is the potential of missing communication scores in the tensor (e.g., when a rare

cell type appears in only one sample). Although Tensor-cell2cell can handle cell types that are missing

in some conditions, the implemented tensor decomposition algorithm can be further optimized for

missing values. Since the implemented algorithm is not optimized for this purpose, we built a 4D-

communication tensor that contains only the cell types that are shared across all samples in our

COVID-19 and ASD study cases. Thus, further developments will facilitate analyses with missing

values to include all possible members of communication (i.e., LR pairs and cell types that may be

missing in certain contexts).

In addition to single cell data analyzed here, Tensor-cell2cell also accepts bulk transcriptomics data (an

example of a time series bulk dataset of *C. elegans* is included in a Code Ocean capsule, see

Methods), and it could further be used to analyze proteomic data. We demonstrated the application of

Tensor-cell2cell in cases where samples correspond to distinct patients, but it can be applied to many

other contexts. For instance, our strategy can be readily applied to time series data by considering time

points as the contexts, and to spatial transcriptomic datasets, by previously defining cellular niches or

neighborhoods as the contexts. We have included Tensor-cell2cell as a part of our previously

developed tool cell2cell[65], enabling previous functionalities such as employing any list of LR pairs

(including protein complexes), multiple visualization options, and personalizing the communication

scores to account for other signaling effects such as the (in)activation of downstream genes in a

signaling pathway[30,66]. Thus, these attributes make Tensor-cell2cell valuable for identifying key cell-cell

and LR pairs mediating complex patterns of cellular communication within a single analysis for a wide

range of studies.

Methods

RNA-seq data processing

RNA-seq datasets were obtained from publicly available resources. Datasets correspond to a large-

scale single-cell atlas of COVID-19 in humans[67], a COVID-19 dataset of single-cell transcriptomes for

BALF samples[33]. COVID-19 datasets were collected as raw count matrices from the NCBI's Gene

Expression Omnibus[68] (GEO accession numbers GSE158055 and GSE145926, respectively), while the

ASD dataset was obtained from https://cells.ucsc.edu/autism/downloads.html. In total, the first dataset

contains 1,462,702 single cells, the second 65,813 and the last one 104,559 single nuclei. The first

dataset contains samples of patients with varying severities of COVID-19 (control, mild/moderate and

severe/critical) and we selected just 60 PBMC samples among all different sample sources (20 per

severity type). In the second dataset, we considered the 12 BALF samples of patients with varying

severities of COVID-19 (3 control, 3 moderate and 6 severe) and preprocessed them by removing

genes expressed in fewer than 3 cells, which left a total of 11,688 genes in common across samples. In

the ASD dataset, PFC samples from 23 patients with and without ASD condition (13 ASD patients and

10 controls) were considered, and preprocessed similarly to the BALF dataset, resulting in a total of

24,298 genes in common across samples. In all datasets, we used the cell type labels included in their

respective metadata. We aggregated the gene expression from single cells/nuclei into cell types by

calculating the fraction of cells in the respective label with non-zero counts, as previously

recommended for properly representing genes with low expression levels[24], as usually happens with

genes encoding surface proteins[27].

Ligand-receptor pairs

A human list of 2,005 ligand-receptor pairs, 48% of which include heteromeric-protein complexes, was

obtained from CellChat[10]. We filtered this list by considering the genes expressed in the PBMC and

BALF expression datasets and that match the IDs in the list of LR pairs, resulting in a final list of 1639

and 189 LR pairs, respectively. While in the ASD dataset, 749 LR pairs that matched the gene IDs were

considered.

Building the context-aware communication tensor

For building a context-aware communication tensor, three main steps are followed: 1) A communication

matrix is built for each ligand-receptor pair contained in the interaction list from the gene expression

matrix of a given sample. To build this communication matrix, a communication score[5] is assigned to a

given LR pair for each pair of sender-receiver cells. The communication score is based on the

expression of the ligand and the receptor in the respective sender and receiver cells (Figure 1a). 2)

After computing the communication matrices for all LR pairs, they are joined into a 3D-communication

tensor for the given sample (Figure 1b). Steps 1 and 2 are repeated for all the samples (or contexts) in

the dataset. 3) Finally, the 3D-communication tensors for each sample are combined, each of them

representing a coordinate in the 4th-dimension of the 4D-communication tensor (or context-aware

communication tensor; Figure 1c).

To build the tensor for all datasets, we computed the communication scores as the mean expression

between the ligand in a sender cell type and cognate receptor in a receiver cell type, as previously

described[20]. For the LR pairs wherein either the ligand or the receptor is a multimeric protein, we used

the minimum value of expression among all subunits of the respective protein to compute the

communication score. In all cases we further considered cell types that were present across all

samples. Thus, the 4D-communication tensor for the PBMC, BALF and ASD datasets resulted in a size

of 60 x 1639 x 6 x 6; 12 x 189 x 6 x 6, and 23 x 749 x 16 x 16 respectively (that is, samples x ligand-

receptor pairs x sender cell types x receiver cell types).

Non-negative tensor component analysis

Briefly, non-negative TCA is a generalization of NMF to higher-order tensors (matrices are tensors of

order two). To detail this approach, let χ represent a *C* x *P* x *S* x *T* tensor, where *C*, *P*, *S* and *T*

correspond to the number of contexts/samples, ligand-receptor pairs, sender cells and receiver cells

contained in the tensor, respectively. Similarly, let χ_{ijkl} denote the representative interactions of context

i, using the LR pair *j*, between the sender cell *k* and receiver cell *l*. Thus, the TCA method underlying

Tensor-cell2cell corresponds to CANDECOMP/PARAFAC[69,70], which yields the decomposition,

factorization or approximation of χ through a sum of *R* tensors of rank-1 (Figure 1d):

516
$$\chi \approx \sum_{r=1}^{R} c^r \otimes p^r \otimes s^r \otimes t^r \qquad (1)$$

517 Where the notation $\otimes$ represents the outer product and $c^r, p^r, s^r \text{ and } t^r$ are vectors of the factor *r* that

518 contain the loadings of the respective elements in each dimension of the tensor (Figure 1e). These

519 vectors have values greater than or equal to zero. Similar to NMF, the factors are permutable and the

520 elements with greater loadings represent an important component of a biological pattern captured by

521 the corresponding factor. Values of individual elements in this approximation are represented by:

522
$$\chi_{ijkl} \approx \sum_{r=1}^{R} c_i^r \otimes p_j^r \otimes s_k^r \otimes t_l^r \qquad (2)$$

523 The tensor factorization is performed by iterating the following objective function until convergence

524 through an alternating least squares minimization[17,71]:

525
$$min_{\{c,p,s,t\}} \left\| \chi - \sum_{r=1}^{R} c^r \otimes p^r \otimes s^r \otimes t^r \right\|_F^2 \qquad (3)$$

526 Where $\left\| \, . \, \right\|_F^2$ represent the squared Frobenius norm of a tensor, calculated as the sum of element-wise

527 squares in the tensor:

$$\left\| \chi \right\|_F^2 = \sum_{i=1}^{C} \sum_{j=1}^{P} \sum_{k=1}^{S} \sum_{l=1}^{T} \chi_{ijkl}^2 \qquad (4)$$

529 All the described calculations were implemented in Tensor-cell2cell through functions available in

530 Tensorly[72], a Python library for tensors.

Measuring the error of the tensor decomposition

532 Depending on the number of factors used for approximating the 4D-communication tensor, the

533 reconstruction error calculated in the objective function can vary. To quantify the error with an

534 interpretable value, we used a normalized reconstruction error as previously described[12]. This

535 normalized error is on a scale of zero to one and is analogous to the fraction of unexplained variance

536 used in PCA:

$$\frac{\left\| \chi - \sum_{r=1}^{R} c^r \otimes p^r \otimes s^r \otimes t^r \right\|_F^2}{\left\| \chi \right\|_F^2} \qquad (5)$$

Running Tensor-cell2cell with communication scores from external tools

We assessed the similarity of tensor decomposition on the BALF dataset using different communication

scoring methods (CellChat[10], CellPhoneDB[20], NATMI[9], SingleCellSignalR[21], and Tensor-cell2cell's built-

in scoring). To enable consistency between methods, we used the same ligand-receptor PPI database

(CellChat – see "Ligand-receptor pairs") and ran each method via LIANA[23]. LIANA provides a number

of advantages over running each tool separately, including consistent thresholding and parameters,

interoperability between methods and LR databases, and modifications to allow methods that could not

originally account for protein complexes to do so. We adjusted parameters to match those of Tensor-

cell2cell's built-in scoring by not filtering for minimal proportions of expression by cell type or

thresholding for differentially expressed genes.

As input to LIANA, we constructed a Seurat object with log(CPM+1) normalized counts for each

sample. For each tool and sample, LIANA outputs an edge-list of communication scores for a given

combination of sender and receiver cells, as well as ligand-receptor pairs. We extended Tensor-

cell2cell's functionalities to restructure a set of these edge-lists, each associated with a sample, into a

4D-communication tensor (Figure 1). This functionality enables users to either provide input expression

matrices and use Tensor-cell2cell's built-in scoring, or to run their communication scoring method of

choice on each sample and provide the resultant edge-lists as input. To further ensure consistency, we

subsetted each resultant tensor to the intersection of ligand-receptor pairs scored across all 5 methods.

For each method, this resulted in a tensor consisting of 12 samples, 172 ligand-receptor pairs, and 6

sender- and receiver- cells.

Evaluating the effect of gene expression preprocessing and batch-effect correction on
Tensor-cell2cell

To evaluate how gene expression preprocessing and batch-effect correction impact the results of

Tensor-cell2cell, we assessed the similarity of tensor decomposition on the BALF dataset. To compute

the communication scores for building the tensors (Figure 1a), we used different gene expression

values, including the raw UMI counts, the preprocessed values with log(CPM+1) and the fraction of

non-zero cells[24], and the batch-corrected values with ComBat[25] and Scanorama[26]. Except by the

fraction of non-zero cells, which already aggregated single-cells into cell-types, other values were

aggregated into the cell-type level by computing their average value for each gene across single cells

with the same cell-type label. As the communication score, we used the expression mean of the

interacting partners in each LR pair. Thus, we built 4D-communication tensors as mentioned for the

BALF data in the Methods subsection ***Building the context-aware communication tensor***. The

tensor decomposition resulting with the fraction of non-zero cells in this case corresponds to the same

in Figure 4.

Measuring the similarity between distinct tensor decomposition runs

To assess decomposition consistency between different scoring methods or preprocessing pipelines,

we employed the CorrIndex[22]. The CorrIndex is a permutation- and scaling-invariant distance metric

that enables consistent comparison of decompositions between tensors containing the same elements,

without need to align the factors obtained in each case (separate tensor decompositions can output

similar factors but in different order). The CorrIndex value lies between 0 and 1, with a higher score

indicating more dissimilar decomposition outputs. To score tensor decompositions, the output factor

matrices must first be vertically stacked. We implemented a modification that instead assesses each

tensor dimension separately (see Supplementary Note for more details). While taking the minimal score

between all dimensions tends to be more stringent, it disregards the combinatorial effects of all

dimensions together. These combinatorial effects are important because they better reflect the goal of

tensor decomposition and because similarity in those dimensions that are not the minimal one may be

artificially inflated. To facilitate the use of the CorrIndex and its modified version, we wrote a Python

implementation that is available on the Tensorly package[72].

Downstream analyses using the loadings from the tensor decomposition

We incorporate several downstream analyses of Tensor-cell2cell's decomposition outputs to further

elucidate the underlying cell- and molecular- mediators of cell-cell communication. Each of these

analyses are associated with a specific tensor dimension, and thus, a specific biological resolution. This

includes 1) statistical, correlative, and clustering analyses to understand context associations for each

factor, 2) gene set enrichment analysis of ligand-receptor loadings to identify granular signaling

pathways associated with factors, 3) the generation of factor-specific cell-cell communication networks

to represent the overall communication state of cells in that factor.

We can understand the context associations for a factor by comparing the loadings of samples

associated with distinct contexts. For statistical significance, we conduct an independent t-test pairwise

between each context group associated with the samples and use Bonferonni's correction to account

for multiple comparisons. We use this for both the COVID-19 BALF dataset (Supplementary Figures S7

and S8) and the ASD dataset (Figure 5c). We also conduct correlative analyses – assuming ordinal

contexts (i.e., healthy control < moderate COVID-19 < severe COVID-19), we take the Spearman

correlation between the sample loadings and sample severity (Figure 4c). Finally, we also hierarchically

cluster the samples using their loadings across all factors (Figure 5d). For this purpose, we use the

normalized loadings resulting from the tensor decomposition, and standardize them across all factors.

Then, we apply an agglomerative hierarchical clustering by using Ward's method and the Euclidean

distance as a metric. Note that this type of clustering analysis can be applied to the other tensor

dimensions.

We can use the LR-pair loadings of a factor to identify the signaling pathways associated with it, by

using the Gene Set Enrichment Analysis[56] (GSEA). Before running the analysis, pathways of interest

have to be assigned to a list of associated LR pairs. We do that by considering the KEGG gene sets

available at http://www.gsea-msigdb.org/. We annotate a LR pair available in CellChat with the gene

sets that contain all genes participating in that LR interaction. Then, by filtering LR pathway sets to

those containing at least 15 LR pairs, we end up with 22 LR pathway sets. To run GSEA, we rank the

LR pairs in each factor by their loadings, and use the PreRanked GSEA function in the package

gseapy, by including the 22 LR pathway sets as input. As parameters of the "gseapy.prerank" function,

we consider 999 permutations, gene sets (LR pathway sets here) with at least 15 elements, and a

score weight of 1 for computing the enrichment scores[56].

Finally, we generate factor-specific cell-cell communication networks. To do so, for a factor r, we take

the outer product between the sender-cell loadings vector, s^r, and the receiver-cell loadings vector, t^r.

Conceptually, this outer product represents an adjacency matrix of a factor-specific cell-cell

communication network, where each value is an edge weight representing the overall communication

between a pair of sender-receiver cells (Supplementary Figure S9). We can further use this network to

understand the communication distribution inequality between sender- and receiver- cells. We compute

a Gini coefficient[73] ranging between 0 and 1 on the distribution of edge weights in the adjacency matrix

(Figure 4c). A value of 1 represents maximal inequality of overall communication between cell pairs (i.e.

one cell pair has a high overall communication value while the others have a value of 0) and 0 indicates

minimal inequality (i.e. all cell pairs have the same overall communication values). More generally, the

outer product between any two tensor dimension loadings for a given factor conceptually represents the

joint distribution of the elements in those two dimensions and can be informative of how the specific

elements are related.

Benchmarking of computational efficiency of tools

We measured the running time and memory demanded by Tensor-cell2cell and CellChat to analyze the

COVID-19 dataset containing PBMC samples. Each tool was evaluated in two scenarios: either using

each sample individually, or by first combining samples by severity (control, mild/moderate, and

severe/critical) by aggregating the expression matrices. The latter was intended to favor CellChat by

diminishing the number of pairwise comparisons to always be between three contexts; thus, increases

in running time or memory demand in this case are not due to an exponentiation of comparisons (n

samples choose 2). CellChat was run by following the procedures outlined in the

"Comparison_analysis_of_multiple_datasets" vignette

(https://github.com/sqjin/CellChat/tree/master/tutorial). Briefly, signaling pathway communication

probabilities were first individually calculated for each sample or context. Next, pairwise comparisons

between each sample or context were obtained by computing either a "functional" or a "structural"

similarity. The functional approach computes a Jaccard index to compare the signaling pathways that

are active in two cellular communication networks, while the structural approach computes a network

dissimilarity[74] to compare the topology of two signaling networks (see REF[10] for further details). Finally,

CellChat performs a manifold learning approach on sample similarities and returns UMAP embeddings

for each signaling pathway in each different context (e.g. if CellChat evaluates 10 signaling pathways in

3 different contexts, it will return embeddings for 30 points) which can be used to rank the similarity of

shared signaling pathways between contexts in a pairwise manner.

The analyses of computational efficiency were run on a compute cluster of 2.8GHz x2 Intel(R) Xeon(R)

Gold 6242 CPUs with 1.5 TB of RAM (Micron 72ASS8G72LZ-2G6D2) across 32 cores. Each timing

task was limited to 128 GB of RAM on one isolated core and one thread independently where no other

processes were being performed. To limit channel delay, data was stored on the node where the job

was performed, where the within socket latency and bandwidth are 78.9 ns and 46,102 MB/s

respectively. For all timing jobs, the same ligand-receptor pairs and cell types were used. Furthermore,

to make the timing comparable, all samples in the dataset were subsampled to have 2,000 single cells.

In the case of Tensor-cell2cell, the analysis was also repeated by using a GPU, which corresponded to

a Nvidia Tesla V100.

Training and evaluation of a classification model

A Random Forest[75] (RF) model was trained to predict disease status based on both COVID-19 status

(healthy-control vs. patient with COVID-19) and severity (healthy-control, moderate symptoms, and

severe symptoms). The RF model was trained using a Stratified K-Folds cross-validation (CV) with 3-

Fold CV splits. On each CV split a RF model with 500 estimators was trained and RF probability-

predictions were compared to the test set using the Receiver Operating Characteristic (ROC). The

mean and standard deviation from the mean were calculated for the area under the Area Under the

Curve (AUC) across the CV splits. This classification was performed on the context loadings of Tensor-

cell2cell, and the two UMAP dimensions of the structural and functional joint manifold learning of

CellChat, for both the BALF and PBMC COVID-19 datasets. All classification was performed through

Scikit-learn (v. 0.23.2)[76].

Code and data availability

Tensor-cell2cell is implemented in our cell2cell suite[65], which is available in a GitHub repository

(https://github.com/earmingol/cell2cell). All the code and input data used for the analyses are available

online in a Code Ocean capsule for reproducible runs (https://doi.org/10.24433/CO.0051950.v2). While

the code for benchmarking the computational efficiency in a local computer is available in a GitHub

repository (https://github.com/LewisLabUCSD/CCC-Benchmark).

References

1. Hwang, S., Kim, S., Shin, H. & Lee, D. Context-dependent transcriptional regulations between signal transduction pathways. *BMC Bioinformatics* **12**, 19 (2011).

2. Shakiba, N., Jones, R. D., Weiss, R. & Del Vecchio, D. Context-aware synthetic biology by controller design: Engineering the mammalian cell. *Cell Syst* **12**, 561–592 (2021).

3. Rachlin, J., Cohen, D. D., Cantor, C. & Kasif, S. Biological context networks: a mosaic view of the interactome. *Mol. Syst. Biol.* **2**, 66 (2006).

4. Schubert, M. *et al.* Perturbation-response genes reveal signaling footprints in cancer gene expression. *Nat. Commun.* **9**, 20 (2018).

5. Armingol, E., Officer, A., Harismendy, O. & Lewis, N. E. Deciphering cell–cell interactions and communication from gene expression. *Nat. Rev. Genet.* 1–18 (2020).

6. Griffiths, J. I. *et al.* Circulating immune cell phenotype dynamics reflect the strength of tumor–immune cell interactions in patients during immunotherapy. *Proc. Natl. Acad. Sci. U. S. A.* **117**, 16072–16082 (2020).

7. Omberg, L., Golub, G. H. & Alter, O. A tensor higher-order singular value decomposition for integrative analysis of DNA microarray data from different studies. *Proc. Natl. Acad. Sci. U. S. A.* **104**, 18371–18376 (2007).

8. Cillo, A. R. *et al.* Immune Landscape of Viral- and Carcinogen-Driven Head and Neck Cancer. *Immunity* vol. 52 183–199.e9 (2020).

9. Hou, R., Denisenko, E., Ong, H. T., Ramilowski, J. A. & Forrest, A. R. R. Predicting cell-to-cell communication networks using NATMI. *Nat. Commun.* **11**, 1–11 (2020).

10. Jin, S. *et al.* Inference and analysis of cell-cell communication using CellChat. *Nat. Commun.* **12**, 1088 (2021).

11. Raredon, M. S. B. *et al.* Computation and visualization of cell-cell signaling topologies in single-cell systems data using Connectome. *Sci. Rep.* **12**, 4187 (2022).

700 12. Williams, A. H. *et al.* Unsupervised Discovery of Demixed, Low-Dimensional Neural Dynamics

701   across Multiple Timescales through Tensor Component Analysis. *Neuron* **98**, 1099–1115.e8

702   (2018).

703 13. Stein-O'Brien, G. L. *et al.* Enter the Matrix: Factorization Uncovers Knowledge from Omics. *Trends*

704   *Genet.* **34**, 790–805 (2018).

705 14. Sun, S., Zhu, J., Ma, Y. & Zhou, X. Accuracy, robustness and scalability of dimensionality

706   reduction methods for single-cell RNA-seq analysis. *Genome Biol.* **20**, 269 (2019).

707 15. Martino, C. *et al.* Context-aware dimensionality reduction deconvolutes gut microbial community

708   dynamics. *Nat. Biotechnol.* **39**, 165–168 (2021).

709 16. Anandkumar, A., Jain, P., Shi, Y. & Niranjan, U. N. Tensor vs. Matrix Methods: Robust Tensor

710   Decomposition under Block Sparse Perturbations. in *Proceedings of the 19th International*

711   *Conference on Artificial Intelligence and Statistics* (eds. Gretton, A. & Robert, C. C.) vol. 51 268–

712   276 (PMLR, 2016).

713 17. Rabanser, S., Shchur, O. & Günnemann, S. Introduction to Tensor Decompositions and their

714   Applications in Machine Learning. *arXiv [stat.ML]* (2017).

715 18. Chua, R. L. *et al.* COVID-19 severity correlates with airway epithelium–immune cell interactions

716   identified by single-cell analysis. *Nat. Biotechnol.* (2020) doi:10.1038/s41587-020-0602-4.

717 19. Friedlander, M. P. & Hatz, K. Computing non-negative tensor factorizations. *Optim. Methods Softw.*

718   **23**, 631–647 (2008).

719 20. Efremova, M., Vento-Tormo, M., Teichmann, S. A. & Vento-Tormo, R. CellPhoneDB: inferring cell-

720   cell communication from combined expression of multi-subunit ligand-receptor complexes. *Nat.*

721   *Protoc.* (2020) doi:10.1038/s41596-020-0292-x.

722 21. Cabello-Aguilar, S. *et al.* SingleCellSignalR: inference of intercellular networks from single-cell

723   transcriptomics. *Nucleic Acids Res.* **48**, e55 (2020).

724 22. Sobhani, E., Comon, P., Jutten, C. & Babaie-Zadeh, M. CorrIndex: A permutation invariant

performance index. *Signal Processing* **195**, 108457 (2022).

23. Dimitrov, D. *et al.* Comparison of Resources and Methods to infer Cell-Cell Communication from

Single-cell RNA Data. *bioRxiv* 2021.05.21.445160 (2021) doi:10.1101/2021.05.21.445160.

24. Booeshaghi, A. S. & Pachter, L. Normalization of single-cell RNA-seq counts by log(x + 1)* or log(1

+ x). *Bioinformatics* (2021) doi:10.1093/bioinformatics/btab085.

25. Johnson, W. E., Li, C. & Rabinovic, A. Adjusting batch effects in microarray expression data using

empirical Bayes methods. *Biostatistics* **8**, 118–127 (2007).

26. Hie, B., Bryson, B. & Berger, B. Efficient integration of heterogeneous single-cell transcriptomes

using Scanorama. *Nat. Biotechnol.* **37**, 685–691 (2019).

27. Baccin, C. *et al.* Combined single-cell and spatial transcriptomics reveal the molecular, cellular and

spatial bone marrow niche organization. *Nat. Cell Biol.* **22**, 38–48 (2020).

28. Noël, F. *et al.* Dissection of intercellular communication using the transcriptome-based framework

ICELLNET. *Nat. Commun.* **12**, 1089 (2021).

29. Wang, Y. *et al.* iTALK: an R Package to Characterize and Illustrate Intercellular Communication.

Cancer Biology (2019) doi:10.1101/507871.

30. Browaeys, R., Saelens, W. & Saeys, Y. NicheNet: modeling intercellular communication by linking

ligands to target genes. *Nat. Methods* (2019) doi:10.1038/s41592-019-0667-5.

31. Lagger, C. *et al.* scAgeCom: a murine atlas of age-related changes in intercellular communication

inferred with the package scDiffCom. *bioRxiv* 2021.08.13.456238 (2021)

doi:10.1101/2021.08.13.456238.

32. Tsuyuzaki, K., Ishii, M. & Nikaido, I. Uncovering hypergraphs of cell-cell interaction from single cell

RNA-sequencing data. *bioRxiv* 566182 (2019) doi:10.1101/566182.

33. Liao, M. *et al.* Single-cell landscape of bronchoalveolar immune cells in patients with COVID-19.

Nat. Med. **26**, 842–844 (2020).

34. Schmitt, T. L., Steiner, E., Klingler, P., Lassmann, H. & Grubeck-Loebenstein, B. Thyroid epithelial

cells produce large amounts of the Alzheimer beta-amyloid precursor protein (APP) and generate

potentially amyloidogenic APP fragments. *J. Clin. Endocrinol. Metab.* **80**, 3513–3519 (1995).

35. Puig, K. L., Manocha, G. D. & Combs, C. K. Amyloid precursor protein mediated changes in

intestinal epithelial phenotype in vitro. *PLoS One* **10**, e0119534 (2015).

36. Zemans, R. L., Colgan, S. P. & Downey, G. P. Transepithelial migration of neutrophils:

mechanisms and implications for acute lung injury. *Am. J. Respir. Cell Mol. Biol.* **40**, 519–535

(2009).

37. Schenkel, A. R., Mamdouh, Z., Chen, X., Liebman, R. M. & Muller, W. A. CD99 plays a major role

in the migration of monocytes through endothelial junctions. *Nat. Immunol.* **3**, 143–150 (2002).

38. Pasello, M., Manara, M. C. & Scotlandi, K. CD99 at the crossroads of physiology and pathology. *J.*

Cell Commun. Signal. **12**, 55–68 (2018).

39. Sanino, G., Bosco, M. & Terrazzano, G. Physiology of Midkine and Its Potential Pathophysiological

Role in COVID-19. *Front. Physiol.* **11**, 616552 (2020).

40. Farr, L., Ghosh, S. & Moonah, S. Role of MIF Cytokine/CD74 Receptor Pathway in Protecting

Against Injury and Promoting Repair. *Front. Immunol.* **11**, 1273 (2020).

41. Weckbach, L. T., Muramatsu, T. & Walzog, B. Midkine in inflammation. *ScientificWorldJournal* **11**,

2491–2505 (2011).

42. Xia, J. *et al.* Semaphorin-Plexin Signaling Controls Mitotic Spindle Orientation during Epithelial

Morphogenesis and Repair. *Dev. Cell* **33**, 299–313 (2015).

43. Nikaido, T. *et al.* Serum Syndecan-4 as a Possible Biomarker in Patients With Acute Pneumonia.

J. Infect. Dis. **212**, 1500–1508 (2015).

44. Azari, B. M. *et al.* Transcription and translation of human F11R gene are required for an initial step

of atherogenesis induced by inflammatory cytokines. *J. Transl. Med.* **9**, 98 (2011).

45. Clark, I. C. *et al.* Barcoded viral tracing of single-cell interactions in central nervous system

inflammation. *Science* **372**, (2021).

46. Zhang, F. *et al.* IFN- γ and TNF- α drive a CXCL10 + CCL2 + macrophage phenotype expanded in
severe COVID-19 and other diseases with tissue inflammation. *bioRxiv* (2020)
doi:10.1101/2020.08.05.238360.

47. Kohyama, M. *et al.* Monocyte infiltration into obese and fibrilized tissues is regulated by PILRα.
Eur. J. Immunol. **46**, 1214–1223 (2016).

48. Saheb Sharif-Askari, N. *et al.* Enhanced expression of immune checkpoint receptors during SARS-
CoV-2 viral infection. *Mol Ther Methods Clin Dev* **20**, 109–121 (2021).

49. Martinez, F. O., Combes, T. W., Orsenigo, F. & Gordon, S. Monocyte activation in systemic Covid-
19 infection: Assay and rationale. *EBioMedicine* **59**, 102964 (2020).

50. Ocaña-Guzman, R., Torre-Bouscoulet, L. & Sada-Ovalle, I. TIM-3 Regulates Distinct Functions in
Macrophages. *Front. Immunol.* **7**, 229 (2016).

51. Grant, R. A. *et al.* Circuits between infected macrophages and T cells in SARS-CoV-2 pneumonia.
Nature **590**, 635–641 (2021).

52. Matsuyama, T., Kubli, S. P., Yoshinaga, S. K., Pfeffer, K. & Mak, T. W. An aberrant STAT pathway
is central to COVID-19. *Cell Death Differ.* **27**, 3209–3225 (2020).

53. Florez-Sampedro, L., Soto-Gamez, A., Poelarends, G. J. & Melgert, B. N. The role of MIF in
chronic lung diseases: looking beyond inflammation. *Am. J. Physiol. Lung Cell. Mol. Physiol.* **318**,
L1183–L1197 (2020).

54. de la Torre-Ubieta, L., Won, H., Stein, J. L. & Geschwind, D. H. Advancing the understanding of
autism disease mechanisms through genetics. *Nat. Med.* **22**, 345–361 (2016).

55. Velmeshev, D. *et al.* Single-cell genomics identifies cell type-specific molecular changes in autism.
Science **364**, 685–689 (2019).

56. Subramanian, A. *et al.* Gene set enrichment analysis: a knowledge-based approach for interpreting
genome-wide expression profiles. *Proc. Natl. Acad. Sci. U. S. A.* **102**, 15545–15550 (2005).

57. Kanehisa, M. & Goto, S. KEGG: kyoto encyclopedia of genes and genomes. *Nucleic Acids Res.*

28, 27–30 (2000).

58. Astorkia, M., Lachman, H. M. & Zheng, D. Characterization of Cell-cell Communication in Autistic

Brains with Single Cell Transcriptomes. *bioRxiv* 2021.10.15.464577 (2021)

doi:10.1101/2021.10.15.464577.

59. Avraham, R. & Yarden, Y. Feedback regulation of EGFR signalling: decision making by early and

delayed loops. *Nat. Rev. Mol. Cell Biol.* **12**, 104–117 (2011).

60. Almet, A. A., Cang, Z., Jin, S. & Nie, Q. The landscape of cell-cell communication through single-

cell transcriptomics. *Current Opinion in Systems Biology* (2021) doi:10.1016/j.coisb.2021.03.007.

61. Raredon, M. S. B. *et al.* Connectome: computation and visualization of cell-cell signaling topologies

in single-cell systems data. *bioRxiv* 2021.01.21.427529 (2021) doi:10.1101/2021.01.21.427529.

62. Luecken, M. D. & Theis, F. J. Current best practices in single-cell RNA-seq analysis: a tutorial. *Mol.*

Syst. Biol. **15**, e8746 (2019).

63. Abbasy, S. *et al.* Neuregulin1 types mRNA level changes in autism spectrum disorder, and is

associated with deficit in executive functions. *EBioMedicine* **37**, 483–488 (2018).

64. Gazestani, V. H. *et al.* A perturbed gene network containing PI3K-AKT, RAS-ERK and WNT-β-

catenin pathways in leukocytes is linked to ASD genetics and symptom severity. *Nat. Neurosci.* **22**,

1624–1634 (2019).

65. Armingol, E. *et al.* Inferring a spatial code of cell-cell interactions across a whole animal body.

bioRxiv 2020.11.22.392217 (2020) doi:10.1101/2020.11.22.392217.

66. Wang, S., Karikomi, M., MacLean, A. L. & Nie, Q. Cell lineage and communication network

inference via optimization for single-cell transcriptomics. *Nucleic Acids Res.* **47**, e66 (2019).

67. Ren, X. *et al.* COVID-19 immune features revealed by a large-scale single-cell transcriptome atlas.

Cell **184**, 1895–1913.e19 (2021).

68. Edgar, R., Domrachev, M. & Lash, A. E. Gene Expression Omnibus: NCBI gene expression and

hybridization array data repository. *Nucleic Acids Res.* **30**, 207–210 (2002).

69. Carroll, J. D. & Chang, J.-J. Analysis of individual differences in multidimensional scaling via an n-

way generalization of 'Eckart-Young' decomposition. *Psychometrika* **35**, 283–319 (1970).

70. Harshman, R. A. & Others. Foundations of the PARAFAC procedure: Models and conditions for an'

explanatory' multimodal factor analysis. (1970).

71. Anandkumar, A., Ge, R. & Janzamin, M. Guaranteed Non-Orthogonal Tensor Decomposition via

Alternating Rank-1 Updates. *arXiv [cs.LG]* (2014).

72. Kossaifi, J., Panagakis, Y., Anandkumar, A. & Pantic, M. TensorLy: Tensor Learning in Python.

arXiv [cs.LG] (2016).

73. Farris, F. A. The Gini Index and Measures of Inequality. *Am. Math. Mon.* **117**, 851–864 (2010).

74. Schieber, T. A. *et al.* Quantification of network structural dissimilarities. *Nat. Commun.* **8**, 13928

(2017).

75. Breiman, L. Random Forests. *Mach. Learn.* **45**, 5–32 (2001).

76. Pedregosa, F. *et al.* Scikit-learn: Machine learning in Python. *the Journal of machine Learning*

research **12**, 2825–2830 (2011).

Acknowledgements

EA is supported by the Chilean Agencia Nacional de Investigación y Desarrollo (ANID) through its

scholarship program DOCTORADO BECAS CHILE/2018 - 72190270 and by the Fulbright Commission

Chile. HMB is supported by NIMH T32GM008806. APL is supported by the InnovaUNAM of the

National Autonomous University of Mexico (UNAM) and Alianza UCMX of the University of California.

This work was further supported by NIGMS (R35 GM119850) and the Novo Nordisk Foundation

(NNF20SA0066621) to NEL. The authors also thank Daniel McDonald for providing useful guidance

about the timing analysis of the tools, the Code Ocean team for providing extra computational time for

developing the capsule associated with this work, Aaron Meyer for giving practical insights about tensor

decomposition methods, and Daniel Dimitrov for providing helpful guidance about running LIANA.

Author contributions

EA, HB and NEL conceived the work. CM contributed important insights for creating Tensor-cell2cell.

EA implemented Tensor-cell2cell and performed the analyses on the datasets of COVID-19 and ASD.

HB designed and created the simulated 4D-communication tensor and performed the analyses on the

simulated data. EA, HB and CM performed benchmarking and statistical analyses. CM trained

classifiers and compared Tensor-cell2cell to CellChat. HB performed benchmarking analyses using

different external CCC tools. EA performed benchmarking analyses using different pre-processing and

batch-correction methods. EA and HB developed downstream analyses. APL helped to interpret the

COVID-19 results and researched literature. CA helped to interpret the ASD study case and researched

literature. RK contributed to the benchmarking analyses. EA and HB wrote the paper and all authors

carefully reviewed, discussed and edited the paper.

Competing interests

861 The authors declare no competing interests.

a

Ligand-Receptor Pairs

LR-Pair 1
LR-Pair 2
⋮
LR-Pair K

Expression Matrix of *n-th* Context

Genes

Cells / Tissues

Expression Value

Communication Matrix of *k-th* LR-Pair

Communication Score of a LR-Pair
f(Ligand in i-th cell, Receptor in j-th cell)

Sender Cells

Cell 1
Cell 2
Cell I

Cell 1 Cell 2 Cell J

Receiver Cells

b

LR-Pair 1   LR-Pair 2   LR-Pair K

Sender Cells

Receiver Cells   LR Pairs

3D-Communication Tensor of *n-th* Context

c

Context 1   Context 2   Context N

4D-Communication Tensor

d

4D-Communication Tensor

≈

Factor 1   Factor 2   ⋯   Factor R

+   +   +

e

Vectors of *r-th* Factor

Loadings

Contexts   Ligand-Receptor Pairs   Sender Cells   Receiver Cells

a

300 ligand-receptor pairs
3 signaling pathways
3 cell-types
4 directed cell-cell pairs
12 contexts

Cell-type A

Cell-type B

Cell-type C

b

**Network of
Ligand-Receptor Pairs**

LR-Pair 1
LR-Pair 2 } Signaling pathway "X"

LR-Pair 3
LR-Pair 4 } Signaling pathway "Y"

LR-Pair 5
LR-Pair 6 } Signaling pathway "Z"

c

**Network of
Cell-Cell Communication**

Cell-type "A" → Cell-type "C"

Cell-type "C" → Cell-type "A"

Cell-type "B" → Cell-type "B"

Cell-type "A" → Cell-type "A"

Sender   Receiver
Single Cells   Single Cells

d

**Ligand-Receptor & Cell-Cell (LR-CC)
Combinations**

&

&

&

&

e

Context 1

Communication score
Sender Cell-type A
Receiver Cell-type C
Ligand-Receptor Pair 1
(Signaling Pathway X)

Sender Cells

Receiver Cells LR Pairs

Context 2

Sender Cells

Receiver Cells LR Pairs

Context 12

Sender Cells

Receiver Cells LR Pairs

4D-Communication Tensor

Assigned Pattern

f

Assigned Patterns

Communication Scores

Contexts

g

Tensor Decomposition

Factor 1

Factor 2

Factor 3

Factor 4

Contexts   Ligand-Receptor Pairs   Sender Cell-Types   Receiver Cell-Types