Feature-reweighted RSA: A method for improving the fit between computational models, brains, and behavior

Philipp Kaniuth[a,*], Martin N. Hebart[a,*]

[a]*Vision and Computational Cognition Group, Max Planck Institute for Human Cognitive and Brain Sciences, Stephanstrasse 1A, Leipzig, Germany*

Abstract

Representational Similarity Analysis (RSA) has emerged as a popular method for relating representational spaces from human brain activity, behavioral data, and computational models. RSA is based on the comparison of representational dissimilarity matrices (RDM), which characterize the pairwise dissimilarities of all conditions across all features (e.g. fMRI voxels or units of a model). However, classical RSA treats each feature as equally important. This 'equal weights' assumption contrasts with the flexibility of multivariate decoding, which reweights individual features for predicting a target variable. As a consequence, classical RSA may lead researchers to underestimate the correspondence between a model and a brain region and, for model comparison, it may lead to selecting the inferior model. While previous work has suggested that reweighting can improve model selection in RSA, it has remained unclear to what extent these results generalize across datasets and data modalities. To fill this gap, the aim of this work is twofold: First, utilizing a range of publicly available datasets and three popular deep neural networks (DNNs), we seek to broadly test feature-reweighted RSA (FR-RSA) applied to computational models and reveal the extent to which reweighting model features improves RDM correspondence and affects model selection. Second, we propose voxel-reweighted RSA, a novel use case of FR-RSA that reweights fMRI voxels, mirroring the rationale of multivariate decoding of optimally combining voxel activity patterns. We find that reweighting individual model units (1) markedly improves the fit between model RDMs and target RDMs derived from several fMRI and behavioral datasets and (2) affects model selection, highlighting the importance of considering FR-

---

*Corresponding authors. (kaniuth@cbs.mpg.de — hebart@cbs.mpg.de)

RSA. For voxel-reweighted RSA, improvements in RDM correspondence were even more pronounced, demonstrating the utility of this novel approach. We additionally demonstrate that classical noise ceilings can be exceeded when FR-RSA is applied and propose an updated approach for their computation. Taken together, our results broadly validate the use of FR-RSA for improving the fit between computational models, brain and behavioral data, possibly allowing us to better adjudicate between competing computational models. Further, our results suggest that FR-RSA applied to brain measurement channels could become an important new method to assess the match between representational spaces.

Keywords: Representational similarity analysis, multivariate pattern analysis, functional MRI, MEG, behavior, deep neural networks, noise ceilings

1. Introduction

A core aim of cognitive neuroscience is to reveal the nature of our neural representations and determine their role in shaping cognition and overt behavior. Central to this aim are comparisons of representations measured in brain activity data (e.g. fMRI, MEG) with representations derived from computational models or behavior. A powerful framework for such comparisons is offered through representational similarity analysis (RSA). RSA abstracts away from the measurement level (e.g. voxels, sensors) to the level of representational dissimilarities, allowing for direct comparisons across modalities, species, models, and behavior (Kriegeskorte et al., 2008a; Kriegeskorte and Kievit, 2013). By characterizing representations as dissimilarities of activity patterns, RSA has become a central tool for multivariate pattern analysis, complementing multivariate decoding (Haynes and Rees, 2006; Hebart and Baker, 2018) and other methods operating at the level of multivariate activity patterns (Haxby et al., 2014; Diedrichsen et al., 2018).

At the heart of RSA lies the computation of representational dissimilarity matrices (RDMs), which characterize the dissimilarity of all pairs of conditions (e.g. visual stimuli) across all features (e.g. measurement channels, units of a computational model). While in recent years a lot of focus has been placed on improving the reliability of RDMs (Walther et al., 2016; Charest et al., 2018) and identifying the most appropriate dissimilarity measure (Walther et al., 2016; Bobadilla-Suarez et al., 2020; Ramírez et al.,

2020), much less emphasis has been placed on the contribution of individual features in the computation of representational dissimilarities. In fact, most RSA approaches assume that each feature is of equal importance and will thus contribute equally to the final dissimilarity estimate. This 'equal weights' assumption is at odds with the idea that for a given comparison of RDMs, some features may carry more information than others. This has several important consequences. First, for computational models, classical RSA may underestimate the correspondence between the model and a given brain region. This may lead not only to suboptimal model performance, but may also affect different models to different degrees, which in case of model comparisons may lead to the selection of an inferior model (Khaligh-Razavi and Kriegeskorte, 2014; Peterson et al., 2016; Jozwik et al., 2017; Storrs et al., 2021). Second, for brain data, classical RSA may overemphasize the importance of individual brain measurement channels, treating noisy channels (e.g. voxels) as equally important to channels that carry signal. This contrasts with the intuition used in multivariate linear decoding, where each voxel's importance is reweighted according to the contribution to the final classification task (Figure 1a). Surprisingly, reweighting of individual brain measurement channels is not routinely applied to the measurement of representational similarities. This suggests large untapped potential for improving the representational correspondence between computational models, brain activity, and behavior (Figure 1b,c).

The aim of the present study is twofold. First, for the reweighting of computational model units, we seek to broadly validate the degree to which feature-reweighted RSA (FR-RSA) can act as a general-purpose method to relate representational spaces of models with those of brain and behavior. To achieve this aim, we systematically apply FR-RSA to representations from deep neural networks (DNN) on the one hand and relate them to diverse publicly available neuroimaging and behavioral datasets on the other hand. Second, for the reweighting of brain measurement channels, we demonstrate the broad applicability of FR-RSA applied to fMRI data - *voxel-reweighted* RSA - for improving the correspondence between representational dissimilarities derived from the brain and from models or behavior. Previewing our results, we find that reweighting features of a DNN reliably improves the fit between model, brain, and behavioral RDMs and indeed affects which DNN is selected as the best model of brain activity (Storrs et al., 2021), generalizing the utility of FR-RSA to a broad set of neural network models, brain imaging methods and behavior, and stimuli. Further, when reweighting is applied to fMRI

a) Multivariate decoding in fMRI

b) Classical representational similarity analysis

c) Feature reweighted representational similarity analysis

Figure 1: Parallel between multivariate decoding and feature-reweighted RSA (FR-RSA). (a) Multivariate decoding in fMRI can be described as a linear reweighting of features (e.g. voxels) to optimize the linear read out of a binary target variable (e.g. stimulus category). Voxel weights reflect their importance for the final classification objective. (b) In classical RSA, no reweighting is applied, which assumes that all voxels are equally important. Relative to multivariate decoding, this underestimates the linear information contained in multivoxel activation patterns. (c) FR-RSA utilizes linear feature-reweighting in order to best reflect pairwise dissimilarity relative to a target RDM, therefore improving the use of multivariate information present in the data.

voxels, our results demonstrate consistent and pronounced improvements of RDM correspondence, suggesting that feature reweighting applied at the level of brain measurements may act as a general-purpose method for improving the representational correspondence between brains, models, and behavior. To facilitate future use of this method, we provide a toolbox to run FR-RSA in both Python and Matlab (https://github.com/ViCCo-Group/frrsa), with recommendations regarding implementational choices.

2. Methods

2.1. Datasets and computational models

We sought to evaluate the general applicability of feature-reweighted RSA (FR-RSA), both when (1) reweighting individual features of a computational model, as has been done previously with similar approaches (e.g. Peterson et al., 2016; Jozwik et al., 2017; Storrs et al., 2021) and (2) when reweighting measurement channels of brain data, an approach which to our knowledge has not been carried out before. To this end, we used datasets from several published studies in which participants had been exposed to a range of object images (Mur et al., 2013; Cichy et al., 2014, 2016; Bankson et al., 2018;

Cichy et al., 2019). The datasets are centered around four sets of natural object images and reflect a combination of functional MRI data, magnetoencephalography data, and behavioral similarity judgments. In addition, for the object images, we extracted neural network activations as computational models. Together, this makes these datasets well suited for evaluating FR-RSA across a wide range of possible analyses. One study (Bankson et al., 2018) used two twin sets of 84 natural object images, which were tested in two sets of participants and which we thus treated as two separate datasets. Another image set (Kriegeskorte et al., 2008b; Mur et al., 2013; Cichy et al., 2014) consisted of 92 images of human and non-human faces and bodies, as well as natural and artificial objects. Finally, another image set (Cichy et al., 2016, 2019) consisted of 118 natural images. Details regarding which kinds of data were available for which image set, as well as the task carried out by participants, can be found in Table 1.

2.1.1. fMRI data

For the fMRI data of two image sets (92 and 118), we used voxelwise beta estimates for each object which were provided with the publicly available datasets and which had been estimated by applying a general linear model to the preprocessed data (for methodological details, see Cichy et al., 2014, 2016). For simplicity, we focused on early visual cortex (EVC) and higher visual cortex (HVC) as regions of interest. Since data were provided in MNI space only, EVC and HVC were defined using anatomical criteria, based on a projection of the Glasser atlas to MNI space (Glasser et al., 2016). For EVC, we used a mask of areas V1, V2, and V3. For HVC, we used a mask consisting of areas V8 (VO1), PIT, VVC, FFC, VMV1-3, PHA1-3, TF, and TE2p. For each participant and area, a conservative preselection of voxels was conducted by only selecting the most strongly activated 250 voxels.

2.1.2. MEG data

While human MEG data were available for all image sets, due to the extensive number of possible comparisons, we focused on MEG data for image sets 92 and 118. Both MEG datasets had been acquired with 306 channels at a sampling rate of 1,000 Hz. Data were filtered between 0.03 and 330 Hz and were baseline corrected (for methodological details, see Cichy et al., 2014, 2016). For image set 92, MEG signals were extracted for each trial for 100ms before and 1,200ms after stimulus presentation, resulting in 1,301ms length in total. Across all measurement channels, this yielded a data matrix

Image set	Types of images	Experimental task	MEG (n)	fMRI ROI (n)	MEG type (channels)	Behavior (n)	References
84 (Set 1)	natural images cropped and placed on grey background	oddball detection	-	-	-	single arrangement similarity (n =16)	Bankson et al. (2018)
84 (Set 2)	natural images cropped and placed on grey background	oddball detection	-	-	-	single arrangement similarity (n =16)	Bankson et al. (2018)
92	human and non-human faces and bodies as well as natural and artificial objects cropped and placed on grey background	MEG: button press when paperclip shown fMRI: button press when null trial	Yes (16)	Early visual cortex (n = 15) Higher visual cortex (n = 15)	204 planar gradiometers, 102 magnetometers	multiple arrangement similarity (n=16)	Mur et al. (2013) Cichy et al. (2014)
118	diverse natural images, on natural background	MEG: button press and eyeblink when paperclip shown fMRI: button press when null trial	Yes (15)	Early visual cortex (n = 15) Higher visual cortex (n = 15)	204 planar gradiometers, 102 magnetometers	multiple arrangement similarity (n=20)	Cichy et al. (2016); Cichy et al. (2019)

Table 1. Overview over the datasets used in this study. For each image set, data from several measurement modalities were available. For fMRI, we focused on data from early visual cortex (EVC) and higher visual cortex (HVC). The number of participants, n, for every measurement modality is stated in parentheses. Note that not all available datasets from these image sets were used in all analyses, given the exceedingly large number of possible comparisons.

of size 306×92 for every time point and participant. For the image set 118, MEG signals were extracted for 100ms before and 1,000ms after stimulus presentation, resulting in 1,101ms length in total. This yielded a data matrix of size 306×118 for every time point and participant.

2.1.3. Behavioral data

The behavioral data of all image sets included in this study were sampled using either the single (Hout et al., 2013) or multiple object arrangement method (Kriegeskorte and Mur, 2012). In this task, participants are required to arrange objects in a circular arena according to the perceived dissimilarity between images by dragging-and-dropping them to different locations within

the arena. Dissimilar images are positioned further away from each other, while similar images are positioned closer to each other. Importantly for later analyses, this method directly produces fully-sampled RDMs, rather than yielding feature vectors which are then converted into RDMs. The single arrangement method was used for both image sets with 84 images, while the multiple arrangement method was used for image sets 92 and 118. Further details regarding the specifics of behavioral data acquisition can be found in the original studies (Mur et al., 2013; Bankson et al., 2018; Cichy et al., 2019).

2.1.4. Layer activations from chosen deep neural networks

We chose three popular DNN architectures for our investigation: AlexNet (Krizhevsky et al., 2012), VGG-16 (Simonyan and Zisserman, 2015), and ResNet-50 (He et al., 2016). We used versions of the DNNs which had been pre-trained on the 1,000 object classes used in the Imagenet Large-Scale Visual Recognition Competition (ILSVRC, Russakovsky et al., 2015), implemented in the Matlab toolbox MatConvNet (Vedaldi and Lenc, 2015). For each DNN, we extracted activity patterns for each image of each image set for a subset of DNN layers. For AlexNet, we selected all five pooling layers and the first two fully-connected layers, resulting in seven layers in total. Similarly, for VGG-16, all five pooling layers and the first two fully connected layers were chosen, respectively. For ResNet-50, layers conv1, res2b, res3b, res3d, res4c, res4f, and res5c were chosen as roughly corresponding to the chosen layers in AlexNet and VGG-16 in terms of network depth. Subsequently, we will refer to these layers as layers 1 to 7. For each layer, we concatenated all units of all feature maps into one long vector, yielding one activity pattern per stimulus per layer. No dimensionality reduction was conducted for any DNN layer.

2.2. Constructing classical representational dissimilarity matrices

For MEG and behavioral data, we used RDMs as provided by the original studies. For MEG data, RDMs consisted of pairwise linear support vector machine classification accuracies, where higher accuracies are supposed to reflect better linear separability and thus larger dissimilarity (Cichy et al., 2014, 2016). For DNN and fMRI activity patterns, when constructing full RDMs, we computed dissimilarities using 1 - Pearson's correlation coefficient. Behavioral RDMs were chosen as the final result from the object arrangement task (see Behavioral data).

2.3. Reweighting features of a given modality to predict dissimilarities in another modality

2.3.1. Overview over the algorithm

The key differences between classical RSA and FR-RSA are illustrated in Figure 2. In classical RSA, individual cells in one RDM reflect the overall dissimilarity of two feature patterns for conditions x and y (e.g. DNN layer activations for two object images). The resulting RDM, henceforth called the "predicting RDM", is then related to another RDM, henceforth called the "target RDM". In contrast, the rationale of feature-reweighted RSA is that individual RDM cells are treated as a linear combination of univariate, feature-specific dissimilarities. The resulting predicting RDM can thus be conceptualized as a linear combination of feature-specific RDMs (Figure 2b). The aim of FR-RSA is then to learn weights that allow optimally combining these feature-specific predicting RDMs in a way that maximizes their correspondence with the target RDM. In our implementation, this is realized using L2-regularized multiple linear regression in a cross-validation framework.

2.3.2. Rationale of the statistical model

More specifically, in classical RSA with 1 minus Pearson correlation as the dissimilarity measure, an RDM cell is quantified by:

$$1 - r_{xy} = 1 - \frac{cov_{xy}}{s_x s_y}$$

with x and y referring to the current pair of objects and s_x and s_y referring to the standard deviation of the respective object's activity pattern. Since the covariance reflects the centered dot product and the correlation coefficient the scaled covariance, it is possible to alternatively z-transform each object pattern, which then reduces the correlation coefficient to the product of the object pairs' feature values, summed across all features i, with a constant scaling factor p in the denominator denoting the number of features:

$$1 - \frac{\Sigma x_i y_i}{p}$$

Figure 2: Comparison of classical and feature-reweighted RSA (FR-RSA). (a) In classical RSA, the predicting RDM is computed across all features before it is related to the target RDM. (b) In FR-RSA, for the predicting RDM, one RDM for each feature is computed. Each feature's RDM receives its own β weight to optimally predict the target RDM using regularized linear regression. The reweighted predicting RDM is then related to the target RDM.

In feature-reweighted RSA, this formula simply translates to:

$$1 - \frac{\Sigma \beta_i x_i y_i}{p}$$

For a given feature i, across all object pairs, the same β weight is learned. This is equivalent to learning a linear combination of weighted univariate feature-specific RDMs, as illustrated in Figure 2b. Thus, to accurately combine these features and easily fit feature-specific weights, each pattern is z-transformed when using 1 minus Pearson correlation as the dissimilarity measure. Note that the constant p can be ignored as it affects the scaling of all β weights equally.

Therefore, the predicting RDM in FR-RSA is a linear combination of feature-specific RDMs, in which each feature-specific RDM receives its own β weight. Identifying this weight can be formulated as a multiple regression problem, in which each feature-specific RDM acts as an individual predictor, each with its own unique weight. For this multiple regression model, each

feature-specific RDM is flattened so that only its unique upper (or lower) triangular part is used, since each RDM is symmetric along its diagonal.

There are two potential issues with this multiple regression model: First, it can contain a very large number of predictors, which is given by the number of features making up the predicting RDM. Second, given possible redundancy across features, these predictors may exhibit high covariance (e.g. feature-specific RDMs for a number of neighboring voxels). To counteract possible collinearity resulting from these issues, we add a regularization term to the objective function. Since we did not aim at selecting specific features but rather leverage the complete range of information present in the data, we opted for an L2 regularization, that is, ridge regression (Hoerl and Kennard, 1970), which also offers a closed-form solution. For that purpose, we used fractional ridge regression (Rokem and Kay, 2020) since it allows automatic evaluation of the entire range of possible hyperparameters.

Finally, to avoid overfitting, we cross-validated the multiple linear ridge regression model and also conducted a nested cross-validation to establish the best regularization parameter for each cross-validation iteration. The next paragraph provides a step-by-step run-through of the algorithm.

2.3.3. The full sequence of feature-reweighted RSA

1. Data from two modalities (e.g. activity patterns from a specific DNN's layer and fMRI voxel activities from a pre-defined ROI) are selected. One of the modalities is declared the predicting dataset for which feature-reweighted RDMs are computed. The other modality is the target dataset for which the full RDM is explained by the predicting dataset. In matrix form, the former is provided as a $p \times k$ matrix, while the latter reflects a full $k \times k$ RDM, with p referring to the number of measurement channels and k to the number of conditions (see Diedrichsen and Kriegeskorte, 2017).

2. Activity patterns for all conditions (e.g. images) of the predicting dataset are z-transformed.

3. Data are split randomly into five folds for the outer cross-validation. Importantly, data are split along the condition axis, so that the outer training and test set contain non-overlapping sets of condition pairs (different from Peterson et al., 2016, but similar to Jozwik et al., 2017). Other cross-validation schemes are possible but we confirmed with post-hoc analyses that 5-fold cross-validation reflects a good trade-off between speed and accuracy (see Appendix A).

4. For a given outer cross-validation iteration, the outer training set is again split repeatedly into five folds, yielding an inner training and inner test set for the inner cross-validation.

5. With the inner cross-validation, the best hyperparameter for ridge regression is estimated. For ridge regression, we used fractional ridge regression (Rokem and Kay, 2020). Hence, the hyperparameter to be optimized is the fraction between ordinary least squares and L2-regularized regression coefficients.

6. Once the best hyperparameter for the current outer cross-validation iteration has been established, ridge regression is estimated on the outer training set.

7. Finally, the fitted statistical model returns reweighted dissimilarities for the predicting RDM on the test set, which are correlated with the respective dissimilarities of the target RDM using Pearson's r to evaluate their fit.

Note that in our implementation, the outer 5-fold cross-validation was repeated ten times and the inner 5-fold cross-validation five times, using different random splits in each iteration. Hence, for a single analysis, 50 outer ridge regression models were fitted. For each of these models, Pearson's r between the reweighted predicted and the respective target dissimilarities was derived, so that all 50 Fisher's z-transformed Pearson's r's were averaged across outer cross-validation folds.

2.3.4. Reweighting analyses conducted in this study

The reweighting analyses we carried out can roughly be divided into two kinds: (1) feature-reweighted RSA applied to DNNs, where activations are reweighted to predict individual participant's fMRI or behavioral RDMs, and (2) voxel-reweighted RSA, where individual participant's fMRI activity patterns are reweighted to predict group-averaged behavioral RDMs, DNN RDMs, or group-averaged MEG RDMs (that is, applying reweighting to MEG-fMRI fusion, see Cichy et al., 2014).

Thus, for every reweighting analysis conducted, each participant received one overall score that indicates the correlation between reweighted and target RDM. These scores were used for further statistical analyses (similar to Storrs et al., 2021) and compared to classical RSA. Analyses reweighting DNN units were conducted for all image sets, whereas analyses reweighting fMRI voxels were conducted only for the image sets with 92 and 118 images. Analyses

involving fMRI were conducted separately for both EVC and HVC ROIs. Analyses involving MEG were conducted separately for every time point. For further statistical analyses and graphical presentation of the results, we averaged every ten samples for results pertaining to MEG data, yielding MEG results for 130 and 110 samples, respectively. Across image sets and use-cases, on the group level, this resulted in a total of 736 comparisons of classical and feature-reweighted RSA, reflecting different combinations of a predicting and target RDM. Due to the large number of individual results we only discuss a selection of them in detail in the main text. For a full overview of all results and their complete statistics, please refer to the figures and the Supplemental Material.

2.4. Statistical analyses

2.4.1. Assessing the strength of RDM correspondence

To determine the statistical significance of the correlation between two RDMs at the group-level, we conducted one-sided Wilcoxon signed-rank tests, comparing participants' rank-transformed correlation values against zero. Similarly, to test whether RDMs derived from two different computational models are related to different degrees to an RDM derived from either human brain activity or human behavior, we performed two-sided Wilcoxon signed-rank tests. We corrected for multiple comparisons by controlling the expected false discovery rate at 0.05 (Benjamini and Hochberg, 1995).

2.5. Estimating noise ceilings

Noise ceilings provide an estimate of the best performance any model can achieve given the noise in the data. As is common in RSA, the upper noise ceiling is estimated as the mean correlation between the group-average RDM and each participant-specific RDM. The lower noise ceiling is estimated as the mean correlation between the group-average RDM and each participant-specific RDM while iteratively excluding a given participant from the group-average (Nili et al., 2014).

2.5.1. Estimating reweighted noise ceilings

When conducting feature-reweighted RSA, geometrically speaking, successful reweighting will move the model's RDM closer to each individual participant's RDM (or vice versa when reweighting voxels) (see Figure 3). However, at the same time, the position of the group-average RDM relative to the individual participant's RDMs, which is used for the estimation of the

Figure 3: Geometrical reasoning for reweighted noise ceiling. In classical RSA, noise ceilings are calculated based on individual participant's RDMs (gray circles) and their respective group average (red circle), to get an estimate of the best performance a given model RDM (yellow star) could achieve. (a) When a given model's units are reweighted, the model iteratively moves closer to each participant's fMRI RDM. Here, the reweighted model may be closer to each participant, than the group-average is (small panel). (b) Similarly, when reweighting is applied to individual participant's fMRI voxels, their RDMs move closer towards the model RDM. That way, they can then be closer to the model than the non-reweighted ones are to their mean (small panel). However, when calculating noise ceilings based on the non-reweighted participant RDMs and their respective group average, reweighting is not taken into account. (c) Therefore, in either case, noise ceilings should be calculated based on individual participant's RDMs that have been reweighted to best predict the group-average RDM.

noise ceiling, remains unchanged. As a consequence, for feature-reweighted RSA, classical noise ceilings underestimate the best possible performance any model can achieve since they themselves do not take reweighting into account. This can lead to results that appear to approach or even exceed the noise ceiling while in actual fact this comparison is no longer valid. As a remedy, we propose to also apply reweighting to noise ceilings to get an estimate of the best performance any model can achieve given the noise in the data *and* given that reweighting has been applied. To obtain valid noise ceiling estimates in the context of feature reweighting, for the reweighted upper noise ceiling, we applied reweighting to each participant-specific RDM to optimally predict the group-average RDM and averaged the resulting correlations. For the lower noise ceiling, we reweighted each participant-specific RDM to optimally predict the group-average RDM from which the current participant-specific RDM was left out, again averaging the resulting RDM correlations.

Each correlation between RDMs was tested regarding whether it was significantly below any of the lower noise ceilings, using uncorrected one-sided Wilcoxon signed-rank tests. Not controlling the false discovery rate works against finding a non-significant difference and is therefore a more conservative procedure (Storrs et al., 2021). Note that when a behavioral RDM is the target variable, then estimating reweighted noise ceilings is not possible, given that feature-reweighting cannot be applied without the presence of features (see Behavioral data). In this case, reweighted noise ceilings are omitted.

3. Results

3.1. Reweighting features of computational models

3.1.1. Reweighting features consistently improves correspondence between two RDMs

Our first aim was to evaluate whether FR-RSA reliably increases the correspondence between two RDMs. To this end, we applied FR-RSA to seven different layers of three different DNNs to predict RDMs of behavior, higher visual cortex (HVC) or early visual cortex (EVC), as measured with fMRI in several publicly available datasets (see Datasets and computational models for details). Figure 4 shows the results of comparing classical RSA with FR-RSA across all 168 combinations of analyses. Irrespective of the kind of image set, we found that FR-RSA robustly increased the fit between two RDMs as compared to classical RSA. A chi-squared test revealed that a significantly larger proportion of RDM comparisons showed improvements (147) than comparisons that were worse (21) after reweighting DNN units ($\chi^2(1$, N $= 168) = 94.5$, $p < .001$). Altogether, in 120 cases (71.43%) the fit between two RDMs was significantly increased when feature reweighting was applied to units of DNN layers. In 6 cases (3.57%) FR-RSA performed significantly worse than classical RSA, while in 42 cases (25%) the difference to classical RSA was not significant. Breaking this down into different types of analyses, for the prediction of behavioral RDMs, FR-RSA significantly outperformed classical RSA in 59 cases, with 3 cases that showed significantly worse performance of FR-RSA and 22 cases with a non-significant difference between both methods. Similarly, for the prediction of fMRI RDMs, FR-RSA significantly outperformed classical RSA in 61 cases, performed significantly worse in 3 cases, and showed non-significant differences in 20 cases. Together, these

Figure 4: Comparison of classical RSA with feature-reweighted RSA when reweighting DNN units. For most comparisons, feature-reweighted RSA reveals a stronger RDM correspondence than classical RSA (147 stronger, 21 weaker). Of all 168 comparisons, FR-RSA significantly outperformed classical RSA in 120 cases, often leading to strong increases in the fit between two RDMs.

results demonstrate that FR-RSA robustly improves the correspondence between DNNs, brain activity, and behavior.

3.1.2. Reweighting model features influences model selection

Having demonstrated the reliable performance of FR-RSA, we next sought to evaluate whether applying FR-RSA also leads to changes in the model selection process: Does the same model produce the best fit to brain or behavioral data, no matter whether classical RSA or FR-RSA is used, or can FR-RSA lead to qualitative changes in the results, leading to different models that are chosen to be optimal (Storrs et al., 2021)? To this end, we assessed the relative predictive performance of three common DNN architectures (AlexNet, VGG-16, ResNet-50) for each of seven layers, when

relating their classical and reweighted RDMs to target RDMs derived from either, behavior, HVC, or EVC. These results are shown in Figure 5. While in the following we will highlight a subset of findings, detailed results (all exact correlation coefficients between RDMs, outputs of all one- and two-sided Wilcoxon tests, as well as corrected and uncorrected p-values) for all combinations of image set and target RDMs can be found in the supplemental material.

Let us first focus on the DNN layers' scores for the image set 118 and EVC target RDM (see Figure 5, bottom right panel). Before reweighting, AlexNet and VGG-16 were correlated significantly with the target RDM across most layers, while ResNet-50 showed fewer significant effects (range of correlations across all layers: AlexNet: 0.024 to 0.191, $M = 0.079$, all layers significant; VGG-16: -0.034 to 0.087, $M = 0.047$, layers 2-6 significant; ResNet-50: -0.14 to 0.063, $M = -0.011$, layers 1, 6, 7 significant; all $p < 0.035$, FDR corrected). AlexNet and VGG-16 also performed significantly better than ResNet-50 for layers 1-6 and 2-5, respectively, while ResNet-50 outperformed AlexNet and VGG-16 only for layer 7 and layers 1 and 7, respectively (all $p < 0.009$, FDR corrected). This picture changed strongly after reweighting DNN units of each layer. ResNet-50's performance improved strongly (range of correlations: -0.002 to 0.265, $M = 0.205$; layers 2-7 significant; $p < 0.001$, FDR corrected) and no longer showed a significant difference from reweighted AlexNet's or VGG-16's performance for layers 1-3 and for layer 4, respectively. ResNet-50 in fact outperformed AlexNet and VGG-16 for layers 4-7 and for layers 2-3 and 5-7, respectively (all $p < 0.004$, FDR corrected). Based on these results, it becomes evident that feature-reweighted RSA does, indeed, affect model selection, showing that ResNet-50 is the superior model across multiple layers.

Shifting the focus from one specific dataset to all comparisons in Figure 5, another general pattern to observe for classical RSA is that VGG-16 is very often the best performing model for layer 5 (range of correlations: 0.07 to 0.357; $M = .19$). For 7/8 combinations of image set and target RDM, VGG-16 performed significantly better than both AlexNet and ResNet-50 in layer 5 (all $p < 0.004$, FDR corrected). After feature-reweighting, though, ResNet-50 was the superior model (range of correlations: 0.104 to 0.406; $M = .262$), being significantly better than AlexNet and VGG-16 in 3/8 and 7/8 cases for layer 5 (all $p < 0.04$, FDR corrected). Note that, for the remaining cases, ResNet-50 was never significantly worse than AlexNet or VGG-16. A similar trend can be observed for layer 6 when comparing non-reweighted

Figure 5: Detailed comparison of classical and feature-reweighted RSA applied to DNN units. Each panel shows the predictive performance of three DNNs (blue: AlexNet, orange: ResNet-50, green: VGG-16) with classical and feature-reweighted RSA (light and dark hues, respectively), for a target RDM of a given image set as indicated above each panel. In each panel, the dashed gray and the dotted black line indicate the lower classical and lower reweighted noise ceiling, respectively. In many cases, feature-reweighting leads to an increased fit between RDMs and strongly influences relative model performance. Also, in many panels, FR-RSA leads to models performing not significantly different from a lower noise ceiling (see Supplemental Material for detailed statistics for each panel). Note that in cases where behavioral RDMs are the target RDMs, the calculation of reweighted noise ceilings was not possible (see main text). Error bars indicate 95% confidence intervals computed using bootstrapping. Most fits are significantly different from zero.

AlexNet to reweighted VGG-16. These results support the notion that model selection is affected by applying feature-reweighted RSA.

Another interesting finding is that for classical RSA, EVC target RDMs (Figure 5, bottom panels) are much better explained by early layers than late layers, indicating that these DNNs show a plausible correspondence between layer depth and cortical processing stages. However, after reweighting, most layers of VGG-16 and ResNet-50 fit EVC to a similar degree. This result argues against the idea that DNNs contain similar information as brains across the hierarchy of layers on the one hand and visual cortical regions on the other hand (Nonaka et al., 2020).

Taken together, there is indeed strong evidence that model selection is affected by applying feature-reweighted RSA. These results highlight the importance of considering alternatives to classical RSA for comparing competing models and suggest the general utility of FR-RSA for adjudicating amongst them.

3.2. Voxel-reweighted RSA: Reweighting individual voxels improves prediction of model RDMs, MEG data, and behavior

The second major aim of this study was to explore a novel use-case of feature-reweighting: rather than reweighting individual units of a computational model, we tested the degree to which reweighting brain measurements can improve the ability to predict a computational model's RDM. This approach parallels multivariate decoding which also reweights individual measurement channels (e.g. voxels) to maximize the fit with a target variable. To this end, we applied FR-RSA to fMRI data from higher and early visual cortex to predict RDMs either from behavior, DNN layers, or MEG time points

(MEG-fMRI fusion). The results of all 568 comparisons between classical RSA and voxel-reweighted RSA are shown in Figure 6. FR-RSA applied to voxels overwhelmingly increased the correspondence between two RDMs. A chi-squared test revealed that a significantly larger proportion of RDM comparisons showed improvements (368) than comparisons that were worse (200) after reweighting fMRI voxel ($\chi^2(1, N = 568) = 49.69, p < .001$). Overall, in 240 cases (42.25%) the fit between two RDMs increased significantly, in 69 (12.15%) cases FR-RSA performed significantly worse than classical RSA, and in 259 (45.6%) cases the difference to classical RSA was not significant. Again breaking this down into different types of analyses, for the prediction of behavioral RDMs, FR-RSA significantly outperformed classical RSA in all 4 cases. Similarly, for the prediction of DNN RDMs, FR-RSA significantly outperformed classical RSA in 80 cases, never performed significantly worse, and showed non-significant differences in 4 cases. Finally, when predicting MEG RDMs, FR-RSA significantly outperformed classical RSA in 156 cases, performed significantly worse in 69 cases, and showed non-significant differences in 255 cases. Please note that a large number of the MEG comparisons include time points during which likely no information was present at all. However, we chose all time points for a conservative estimate. Detailed results (exact correlations between RDMs, outputs of all one- and two-sided Wilcoxon tests, as well as corrected and uncorrected p-values) for all combinations of datasets and target RDMs when fMRI voxels had been reweighted can be found in the Supplemental Material.

Focusing on individual results, Figure 7 shows how well reweighted fMRI voxels from two different ROIs explain behavioral RDMs with classical and FR-RSA. While EVC voxels predict behavioral RDMs significantly already before reweighting ($r = 0.054$ and $r = 0.053$ for image set 92 and 118, respectively), these correlations are increased significantly after reweighting ($r = 0.122$ and $r = 0.094$; $p < 0.001$ FDR corrected for all correlations, $p < 0.05$ uncorrected for the differences). The improvement in RDM correlations is even stronger for HVC: the RDM correspondence before reweighting ($r = 0.209$ and $r = 0.165$) is again significantly improved after reweighting took place ($r = 0.424$ and $r = 0.332$; $p < 0.001$ FDR corrected for all correlations, $p < 0.001$ uncorrected for the differences).

Figure 8 shows the relative correspondence of the three DNN architectures for each of seven layers, when relating their RDMs to either classical or reweighted voxel RDMs derived from either HVC or EVC. Overall, reweighting individual voxels leads to even stronger improvements in RDM corre-

Figure 6: Comparison of classical RSA with feature-reweighted RSA when reweighting fMRI voxels. For most comparisons, feature-reweighted RSA reveals a stronger RDM correspondence than classical RSA when applied to voxels (368 vs. 200). FR-RSA significantly outperformed classical RSA in 240 cases, often leading to very strong increases in the fit between two RDMs.

spondence than reweighting DNN units, at times approaching the reweighted lower noise ceiling. In all four panels in Figure 8, all of the 84 RDM correlations for classical RSA are significantly below the classical lower noise ceiling (all $p < 0.04$, uncorrected). However, for voxel-reweighted RSA, there are seven cases in which a DNN layer's RDM and brain RDM correlate to an extent that is not significantly different from the *reweighted* lower noise ceiling. These results demonstrate that voxel reweighted RSA can strongly improve the fit between RDMs.

3.3. Reweighting amplifies existing and reveals new peaks when applied to MEG-fMRI fusion

To test whether results generalize beyond the prediction of DNN layer and behavioral RDMs, we conducted MEG-fMRI fusion with classical and feature-reweighted RSA for two datasets for which fMRI and MEG data were available (Figure 9). For each participant separately, we reweighted fMRI voxels at each time point of MEG data, to best predict dissimilarity. For most time points, classical and FR-RSA each yielded a representational

Figure 7: Voxel-reweighted RSA improves the prediction of behavioral similarity from EVC and HVC. Results across both datasets (92, 118) and regions of interest (EVC, HVC) yield consistent increases in representational similarity when applying voxel-reweighted RSA. The dashed gray line indicates the lower classical noise ceiling, while the computation of reweighted noise ceiling was not possible (see main text). Detailed statistics for each panel is found in the Supplemental Material. Error bars indicate 95% confidence intervals computed using bootstrapping.

similarity significantly larger than zero, as indicated by the purple and red horizontal lines in Figure 9, respectively. Further, for many time points, there were significant differences between classical and FR-RSA (uncorrected), as indicated by the black horizontal line in Figure 9. Overall, FR-RSA revealed peaks which would not have been detected using classical RSA, and it also markedly increased existing peaks.

3.4. Reweighting can lead to RDM correspondences higher than the classical upper noise ceiling

As argued earlier, for feature-reweighted RSA, classical noise ceilings underestimate the best possible performance any model can achieve, invalidating inferences based on classical noise ceilings (see 2.5.1 "Estimating reweighted noise ceilings"). Supporting our reasoning, the results indeed showed 13 cases in which a reweighted RDM correspondence was not significantly below the classical *upper* noise ceiling, with 4 cases even exceeding it numerically. However, no model should be able to explain more variance than explainable given the data at hand. Using reweighted noise ceilings again provides a sensible measure for assessing a model's performance; in our analyses, no model's performance exceeded the upper reweighted noise ceiling.

Figure 8: Detailed comparison of classical and voxel-reweighted RSA. Reweighting of individual fMRI voxels leads to strong and consistent increases in the fit between RDMs. Each panel shows how well the RDMs of three DNNs (purple: AlexNet, red: VGG-16, yellow: ResNet-50) can be explained with classical and feature-reweighted RSA (light and dark hues, respectively), when applied to either HVC or EVC RDM of a given image set as indicated above each panel. In each panel, the dashed gray and the dotted black line indicate the lower classical and lower reweighted noise ceiling, respectively (see Supplemental Material for detailed statistics for each panel). Error bars indicate 95% confidence intervals computed using bootstrapping. Most fits are significantly different from zero.

Figure 9: Voxel-reweighted RSA applied to MEG-fMRI fusion. MEG-fMRI fusion can be improved consistently by applying voxel-reweighted RSA, amplifying existing peaks and yielding new ones. Each panel reflects a combination of one dataset and brain region, with MEG-fMRI fusion for classical (purple) and feature-reweighed (red) RSA. Purple and red dots indicate time points for which classical and voxel-reweighted RSA yield RDM correlations significantly bigger than zero, respectively. Black dots indicate time points with significant differences between classical and voxel-reweighted RSA (all uncorrected). Shaded areas indicate 95% confidence intervals computed using bootstrapping.

4. Discussion

RSA is widely used to assess the correspondence between brains, behavior and models and select amongst several candidates the model that best explains a given representational space (Kriegeskorte et al., 2008a; Kriegeskorte and Kievit, 2013). In this work, we evaluated a powerful extension of classical RSA called feature-reweighted RSA (FR-RSA) in which individual features of a predicting RDM are reweighted to maximize the fit with a target RDM. Using fMRI, MEG, and behavioral data from multiple neuroscience datasets as well as several DNNs as computational models, we broadly validated the general applicability of this approach. Further, we present an important novel use case of FR-RSA by applying feature reweighting to brain measurement channels; compared to classical RSA, voxel-reweighted RSA leverages more of the multivariate information content present in human brain (dis)similarity data, thus nicely complementing existing multivariate decoding techniques. Altogether, we find strong and robust increases in the fit between any two RDMs and often changes in the model selection process when applying feature-reweighting as opposed to classical RSA. Based on these results, we suggest that FR-RSA applied to brain measurement channels could become an important new method to assess the match between representational spaces.

4.1. Past developments of reweighted RSA approaches: Similarities and differences

Classical RSA as introduced by Kriegeskorte et al. (2008a) has been studied extensively as a research method. Below, we will briefly outline past developments leading up to our contribution, as well as similarities and differences to our approach. Khaligh-Razavi and Kriegeskorte (2014) were the first to propose reweighting in the form of layer-reweighted RSA, where an entire layer of a computational model (in this case a DNN) receives a single weight to predict a target RDM. Peterson et al. (2016) were the first to use feature-reweighted RSA (FR-RSA), by reweighting individual DNN units of a fully-connected layer using ridge regression to predict behavioral RDMs. Jozwik et al. (2017) applied a similar approach to predict human object similarity judgments from entire feature maps of convolutional DNN layers or individual units of fully-connected layers. Finally, Storrs et al. (2021) recently proposed a two-stage RSA approach applied to RDMs of human inferior temporal cortex, first reweighting principal components of DNN layers

and then combining individual layers together with another reweighting step. When comparing multiple trained DNNs with each other regarding how well they predict inferior temporal cortex activity after reweighting, they found that performance differences between DNNs were strongly diminished.

While these studies each contributed important novel information and already highlighted the potential value of FR-RSA, our study (1) broadly validates FR-RSA across numerous behavioral and neuroimaging datasets, (2) provides a new use case of FR-RSA by applying reweighting to individual voxels, offering a powerful new method for assessing the fit of brain data with models and behavior and (3) introduces feature-reweighted noise ceilings, providing a more suitable approach for evaluating the upper limit of the predictive performance of any model given the available data.

While all previous FR-RSA approaches have in common the reweighting of individual features, there are also important differences. Several previous approaches (Jozwik et al., 2016, 2017; Storrs et al., 2021) have limited themselves to non-negative weights given that true dissimilarities can only be positive, while our proposed FR-RSA approach avoids this constraint. As a consequence, our approach not only stretches or squeezes individual features, but can also invert their values. However, this is a reasonable choice given the potential information contained in individual units. For example, a DNN unit responding more strongly to dark than bright stimuli still carries information about the brightness of stimuli, no matter the sign, and the sign may still change in downstream operations. In addition to omitting the non-negativity constraint, our approach additionally uses an L2 penalty similar to Peterson et al. (2016) and Jozwik et al. (2017), but in contrast to Jozwik et al. (2016) and Storrs et al. (2021). This choice of regularization, however, is reasonable given the expected collinearity of features. While Storrs et al. (2021) countered multicollinearity with principal components regression, our choice of ridge regression provides smoother shrinkage of regression parameters and may lead to slightly improved prediction (Hastie et al., 2009). Finally, during cross-validation, Peterson et al. (2016) left out individual object pair similarities, while we and others (e.g. Jozwik et al., 2017) left out entire objects, thus avoiding potential leakage effects given that object pair similarities are not all independent. While Storrs et al. (2021) cross-validated across participants, our approach leaves the option to carry out reweighting at the participant level, thus allowing for conducting classical statistical analyses for statistical generalization to the population, beyond the given sample (Allefeld et al., 2016).

4.2. A novel approach for feature reweighting

Further, different from all previous developments, we present a novel approach for feature reweighting altogether by applying it to brain activity patterns: voxel reweighted RSA. This application is motivated by classical multivariate decoding. In multivariate decoding, individual voxels receive their own weights which reflect their importance in optimally conducting a linear read-out of a binary (e.g. stimulus category) or a continuous target variable (e.g. stimulus size). However, in the context of RSA where all voxels receive equal weights, this approach to our knowledge has not been applied previously. Thus, relative to multivariate decoding, classical RSA may underestimate the linear information content of multivariate measurements. By reweighting individual voxels to optimally predict dissimilarity, feature-reweighted RSA can leverage more of the rich multivariate information content of the data.

4.3. Reweighted noise ceilings for reweighted RSA approaches

The fit between a model and data is limited by the quality of the model and the noise in the data. Noise ceilings provide an estimate of the best performance any model can achieve and thus allow us to tell how far off a given model is, given the noise in the data. However, when reweighting individual features, classical noise ceilings underestimate this upper performance threshold, since they themselve do not take reweighting into account. This can lead to the paradoxical result of reweighted RDMs performing better than the upper classical noise ceiling, a result we confirmed empirically. In the context of feature reweighting, we therefore suggest calculating *reweighted* noise ceilings which again provide a sensible performance corridor for reweighted RDMs

4.4. When does feature-reweighted RSA make sense?

While FR-RSA generally yielded strong improvements of the correspondence between computational models and brain data and affected which model was selected among competing models, it may be argued that, while feature reweighting is computationally feasible, it should not be applied to model RDMs in general (see Storrs et al., 2021, for a previous discussion of this topic). According to this line of reasoning, the representational similarity between a model and a given dataset already provides a good estimate of the explanatory power of this model, and reweighting the model's features would be testing the performance of a different model. To illustrate this line

of reasoning, assume for a moment that a model RDM is built not from computational models but originates from an experimental design with several conditions merged together, as is common practice when using RSA. When a researcher is interested primarily in the fit of a static model, we would argue that reweighting of individual model features should not be applied since it would change what hypothesis is tested. However, if each feature is treated as a separate variable for which the contribution to a target RDM is unknown, then reweighting can improve the fit, and indeed, this approach is already commonly used in practice when conducting RSA in a multiple regression framework (e.g. Jozwik et al., 2016; Groen et al., 2018; Hebart and Baker, 2018).

Likewise, for computational models, when the model is treated as a good approximation of all relevant aspects of a brain or behavioral dataset, we would argue that reweighting should not be carried out. For example, a learned DNN model can, among others, be characterized as a product of its architecture (e.g. number of layers and units per layer, transition functions, etc.), its learning objective (e.g. object classification), and the stimuli and object classes that had been used during training. When testing the degree to which all of these aspects are already representative of brain and behavioral datasets, applying reweighting may distort this assessment. However, it is well known that commonly used datasets for training DNNs do not reflect the categories most relevant to humans (Hebart et al., 2019; Mehrer et al., 2021), and the learning objective of ventral visual cortex is known to go beyond simple object classification (Kravitz et al., 2013). Thus, successful feature reweighting promises to yield a better match beyond the images a DNN had been trained on and beyond its limited training objective, possibly better reflecting the explanatory power of a DNN architecture trained on object images. More generally, when interested merely in the information contained in a given computational model, we would argue that FR-RSA can be applied more liberally. Thus, whether FR-RSA should be applied to features of a computational model depends entirely on what aspects of the computational model are supposed to be fixed and what aspects are allowed to vary. Crucially, researchers should be explicit about this choice in their studies to avoid confusion and draw valid conclusions.

Beyond the discussion to which degree FR-RSA can be applied to computational models, we would argue that reweighting of measurement channels (e.g. voxel-reweighted RSA) can be carried out more generally. Drawing the parallel to multivariate decoding, voxel-reweighted RSA would allow

weighting individual voxels in a way that reflects a plausible lower bound of the potential representations that can be read-out by downstream regions (Kriegeskorte and Bandettini, 2007). Whether these representations are indeed used by other brain regions or behavior remains an empirical question for both multivariate decoding and RSA (Williams et al., 2007; Ritchie et al., 2019). Given its increased statistical power, applying FR-RSA to measurement channels promises to advance our understanding of representational content in a way similar to how multivariate decoding has leveraged information contained in measured brain activity patterns.

4.5. Possible extensions of feature-reweighted RSA

There are several ways to refine feature-reweighting in the context of RSA. First, other penalization regimes could be applied. Instead of using an L2-penalty, one could either use an L1-penalty or a combination of L1- and L2-penalization. We opted for the L2-penalization since we did not want to select a subset of features (as any penalization regime utilizing the L1-norm would do) and since an L1-penalization would incur a greater computational load. Second, one could not only penalize the predictors' variances but also their covariance so that all features that exhibit a high covariance with other features are penalized. This approach might, however, strongly increase the computational load of the fitting procedure. A third possible extension of feature-reweighting would be to fit weights bidirectionally. That way, both RDMs would receive weights to optimally predict the other RDM, possibly using a latent vector approach (e.g. canonical correlation analysis). Fourth, the fitting procedure could be repeated so that the residuals of the first fitting procedure are predicted by a linear weighted combination of some other predicting RDM. Finally, a feature-reweighting which automatically selects the best reweighting options from those just mentioned could be combined with reweighting entire layers of a DNN (i.e. two-stage RSA, Storrs et al., 2021). The bottleneck for implementing such a procedure will be computational limits with regards to CPU and RAM resources and the complexity of cross-validation schemes for identifying hyperparameters and splitting data in independent folds.

4.6. Considerations when using FR-RSA

In addition to broadly validating feature-reweighting and exploring a novel use case of it, we also provide an implementation of FR-RSA in both, Python and Matlab (https://github.com/ViCCo-Group/frrsa). In the

following, we would like to provide important considerations when using FR-RSA and mention possible drawbacks.

The first aspect to consider is that FR-RSA utilizes cross-validation to prevent overfitting and nested cross-validation to identify the optimal regularization parameter for ridge regression. Both, outer and inner cross-validation require data to be split into independent training and test sets. For the outer cross-validation, by default, FR-RSA uses 5-fold cross-validation, repeated 10 times with different random splits. On a subset of the analyzed data, we assessed different fold sizes of the outer cross-validation post-hoc and found results being largely unaffected (see Appendix A). We opted for 5-fold cross-validation because it provides enough data for stable estimation of the statistical models in the training set, while at the same time not consuming too many computational resources for actually fitting the models. This cross-validation was repeated 10 times to make sure that many different object pairs will at some point be part of training or test folds. For the inner cross-validation, 5-fold cross-validation is used, repeated five times with different random splits. We tested different numbers of repetition post-hoc and found that results were largely unaffected by how the inner cross-validation was set up (see Appendix B). We opted to repeat the inner cross-validation five times as a good balance between how well the best hyperparameter for a given outer cross-validation is estimated (more repetitions should lead to a better estimation) and computational load. Note that increasing either the fold size or the number of repetitions can have noticeable effects on the computation resources needed to run the algorithm.

A drawback of FR-RSA in comparison to classical RSA is the higher computational load, specifically for models with a large number of features, such as early layers of a DNN. For many different computational problem sizes, we measured how much time and RAM were needed to solve the problem (see Appendix C). Note, however, that computational resources might also depend on the hardware of the machine in question, the operating system that machine uses, and other software-specific factors.

4.7. Conclusion

Representational Similarity Analysis (RSA) has emerged as a popular tool for relating representational spaces of the brain, computational models, and behavior to each other (Kriegeskorte et al., 2008a). As such, it can reveal which model best captures how the brain represents relations between stimuli. Feature-reweighted RSA, the approach we investigated here, not only

consistently increases the fit between RDMs, but also changes which models reproduce most closely a given brain's representational geometry. Further, when applied not to model units but to brain measurement channels, voxel reweighted RSA fully leverages the information content present in representational spaces of the brain and thus nicely complements classical multivariate decoding. Overall, FR-RSA is well suited to become a general-purpose method for measuring the information content shared between representations in computational models, brain, and behavior, and may improve our ability as scientists to adjudicate between competing models.

References

Allefeld, C., Görgen, K., Haynes, J.D., 2016. Valid population inference for information-based imaging: From the second-level t-test to prevalence inference. NeuroImage 141, 378–392. URL: https://www.sciencedirect.com/science/article/pii/S1053811916303470, doi:10.1016/j.neuroimage.2016.07.040.

Bankson, B., Hebart, M., Groen, I., Baker, C., 2018. The temporal evolution of conceptual object representations revealed through models of behavior, semantics and deep neural networks. NeuroImage 178, 172–182. URL: https://linkinghub.elsevier.com/retrieve/pii/S1053811918304440, doi:10.1016/j.neuroimage.2018.05.037.

Benjamini, Y., Hochberg, Y., 1995. Controlling the false discovery rate: A practical and powerful approach to multiple testing. Journal of the Royal Statistical Society: Series B (Methodological) 57, 289–300. URL: https://rss.onlinelibrary.wiley.com/doi/abs/10.1111/j.2517-6161.1995.tb02031.x.

Bobadilla-Suarez, S., Ahlheim, C., Mehrotra, A., Panos, A., Love, B.C., 2020. Measures of neural similarity. Computational Brain & Behavior 3, 369–383. URL: http://link.springer.com/10.1007/s42113-019-00068-5, doi:10.1007/s42113-019-00068-5.

Charest, I., Kriegeskorte, N., Kay, K.N., 2018. GLMdenoise improves multivariate pattern analysis of fMRI data. NeuroImage 183, 606–616. URL: https://www.sciencedirect.com/science/article/pii/S1053811918307626, doi:10.1016/j.neuroimage.2018.08.064.

Cichy, R.M., Khosla, A., Pantazis, D., Torralba, A., Oliva, A., 2016. Comparison of deep neural networks to spatio-temporal cortical dynamics of human visual object recognition reveals hierarchical correspondence. Scientific Reports 6, 27755. URL: http://www.nature.com/articles/srep27755, doi:10.1038/srep27755.

Cichy, R.M., Kriegeskorte, N., Jozwik, K.M., van den Bosch, J.J., Charest, I., 2019. The spatiotemporal neural dynamics underlying perceived similarity for real-world objects. NeuroImage 194, 12–24. URL: https://www.sciencedirect.com/science/article/pii/S1053811919302083, doi:10.1016/j.neuroimage.2019.03.031.

Cichy, R.M., Pantazis, D., Oliva, A., 2014. Resolving human object recognition in space and time. Nature Neuroscience 17, 455–462. URL: http://www.nature.com/articles/nn.3635, doi:10.1038/nn.3635.

Diedrichsen, J., Kriegeskorte, N., 2017. Representational models: A common framework for understanding encoding, pattern-component, and representational-similarity analysis. PLOS Computational Biology 13, e1005508. doi:10.1371/journal.pcbi.1005508.

Diedrichsen, J., Yokoi, A., Arbuckle, S.A., 2018. Pattern component modeling: A flexible approach for understanding the representational structure of brain activity patterns. NeuroImage 180, 119–133. URL: https://www.sciencedirect.com/science/article/pii/S1053811917306985, doi:10.1016/j.neuroimage.2017.08.051.

Glasser, M.F., Coalson, T.S., Robinson, E.C., Hacker, C.D., Harwell, J., Yacoub, E., Ugurbil, K., Andersson, J., Beckmann, C.F., Jenkinson, M., Smith, S.M., Van Essen, D.C., 2016. A multi-modal parcellation of human cerebral cortex. Nature 536, 171–178. URL: http://www.nature.com/articles/nature18933, doi:10.1038/nature18933.

Groen, I.I.A., Greene, M.R., Baldassano, C., Fei-Fei, L., Beck, D.M., Baker, C.I., 2018. Distinct contributions of functional and deep neural network features to representational similarity of scenes in human brain and behavior. eLife , e32962doi:10.7554/eLife.32962.

Hastie, T., Tibshirani, R., Friedman, J.H., 2009. The elements of statistical learning: Data mining, inference, and prediction. 2 ed., Springer.

Haxby, J.V., Connolly, A.C., Guntupalli, J.S., 2014. Decoding neural representational spaces using multivariate pattern analysis. Annual Review of Neuroscience 37, 435–456. URL: http://www.annualreviews.org/doi/10.1146/annurev-neuro-062012-170325, doi:10.1146/annurev-neuro-062012-170325.

Haynes, J.D., Rees, G., 2006. Decoding mental states from brain activity in humans. Nature Reviews Neuroscience 7, 523–534. URL: http://www.nature.com/articles/nrn1931, doi:10.1038/nrn1931.

He, K., Zhang, X., Ren, S., Sun, J., 2016. Deep residual learning for image recognition, in: 2016 IEEE Conference on Computer Vision and Pattern

Recognition (CVPR), pp. 770–778. URL: http://ieeexplore.ieee.org/document/7780459/, doi:10.1109/CVPR.2016.90.

Hebart, M.N., Baker, C.I., 2018. Deconstructing multivariate decoding for the study of brain function. NeuroImage 180, 4–18. URL: https://www.sciencedirect.com/science/article/pii/S1053811917306523, doi:10.1016/j.neuroimage.2017.08.005.

Hebart, M.N., Dickter, A.H., Kidder, A., Kwok, W.Y., Corriveau, A., Van Wicklin, C., Baker, C.I., 2019. THINGS: A database of 1,854 object concepts and more than 26,000 naturalistic object images. PLOS ONE 14, e0223792. doi:10.1371/journal.pone.0223792.

Hoerl, A.E., Kennard, R.W., 1970. Ridge regression: Biased estimation for nonorthogonal problems. Technometrics 12, 55–67. URL: https://www.tandfonline.com/doi/abs/10.1080/00401706.1970.10488634, doi:10.1080/00401706.1970.10488634.

Hout, M.C., Goldinger, S.D., Ferguson, R.W., 2013. The versatility of SpAM: A fast, efficient, spatial method of data collection for multidimensional scaling. Journal of Experimental Psychology: General 142, 256–281. URL: https://psycnet.apa.org/record/2012-17536-001, doi:10.1037/a0028860.

Jozwik, K.M., Kriegeskorte, N., Mur, M., 2016. Visual features as stepping stones toward semantics: Explaining object similarity in it and perception with non-negative least squares. Neuropsychologia 83, 201–226. URL: http://www.sciencedirect.com/science/article/pii/S0028393215301998, doi:10.1016/j.neuropsychologia.2015.10.023.

Jozwik, K.M., Kriegeskorte, N., Storrs, K.R., Mur, M., 2017. Deep convolutional neural networks outperform feature-based but not categorical models in explaining object similarity judgments. Frontiers in Psychology 8, 1726. URL: https://www.frontiersin.org/article/10.3389/fpsyg.2017.01726, doi:10.3389/fpsyg.2017.01726.

Khaligh-Razavi, S.M., Kriegeskorte, N., 2014. Deep supervised, but not unsupervised, models may explain it cortical representation. PLoS Computational Biology 10, e1003915. doi:10.1371/journal.pcbi.1003915.

Kravitz, D.J., Saleem, K.S., Baker, C.I., Ungerleider, L.G., Mishkin, M., 2013. The ventral visual pathway: an expanded neural framework for the processing of object quality. Trends in Cognitive Sciences 17, 26–49. URL: https://www.sciencedirect.com/science/article/pii/S1364661312002471, doi:10.1016/j.tics.2012.10.011.

Kriegeskorte, N., Bandettini, P., 2007. Analyzing for information, not activation, to exploit high-resolution fMRI. NeuroImage 38, 649–662. URL: https://www.sciencedirect.com/science/article/pii/S1053811907001188, doi:10.1016/j.neuroimage.2007.02.022.

Kriegeskorte, N., Kievit, R.A., 2013. Representational geometry: Integrating cognition, computation, and the brain. Trends in Cognitive Sciences 17. URL: https://www.cell.com/trends/cognitive-sciences/fulltext/S1364-6613(13)00127-7, doi:10.1016/j.tics.2013.06.007.

Kriegeskorte, N., Mur, M., 2012. Inverse MDS: Inferring dissimilarity structure from multiple item arrangements. Frontiers in Psychology 3, 245. URL: https://www.frontiersin.org/article/10.3389/fpsyg.2012.00245, doi:10.3389/fpsyg.2012.00245.

Kriegeskorte, N., Mur, M., Bandettini, P., 2008a. Representational similarity analysis - connecting the branches of systems neuroscience. Frontiers in Systems Neuroscience 2, 4. URL: https://www.frontiersin.org/article/10.3389/neuro.06.004.2008, doi:10.3389/neuro.06.004.2008.

Kriegeskorte, N., Mur, M., Ruff, D.A., Kiani, R., Bodurka, J., Esteky, H., Tanaka, K., Bandettini, P.A., 2008b. Matching categorical object representations in inferior temporal cortex of man and monkey. Neuron 60, 1126–1141. doi:10.1016/j.neuron.2008.10.043.

Krizhevsky, A., Sutskever, I., Hinton, G.E., 2012. ImageNet classification with deep convolutional neural networks, in: Advances in neural information processing systems, p. 1097–1105.

Mehrer, J., Spoerer, C.J., Jones, E.C., Kriegeskorte, N., Kietzmann, T.C., 2021. An ecologically motivated image dataset for deep learning yields better models of human vision. Proceedings of the National Academy of Sciences 118. URL: https://www.pnas.org/content/118/8/e2011417118, doi:10.1073/pnas.2011417118.

Mur, M., Meys, M., Bodurka, J., Goebel, R., Bandettini, P., Kriegeskorte, N., 2013. Human object-similarity judgments reflect and transcend the primate-IT object representation. Frontiers in Psychology 4, 128. URL: https://www.frontiersin.org/article/10.3389/fpsyg.2013.00128, doi:10.3389/fpsyg.2013.00128.

Nili, H., Wingfield, C., Walther, A., Su, L., Marslen-Wilson, W., Kriegeskorte, N., 2014. A toolbox for representational similarity analysis. PLoS Computational Biology 10, 1–11. doi:10.1371/journal.pcbi.1003553.

Nonaka, S., Majima, K., Aoki, S.C., Kamitani, Y., 2020. Brain hierarchy score: Which deep neural networks are hierarchically brain-like? bioRxiv URL: https://www.biorxiv.org/content/early/2020/07/25/2020.07.22.216713, doi:10.1101/2020.07.22.216713.

Peterson, J.C., Abbott, J.T., Griffiths, T.L., 2016. Adapting deep network features to capture psychological representations. arXiv URL: http://arxiv.org/abs/1608.02164.

Ramírez, F.M., Revsine, C., Merriam, E.P., 2020. What do across-subject analyses really tell us about neural coding? Neuropsychologia 143, 107489. URL: https://www.sciencedirect.com/science/article/pii/S0028393220301603, doi:10.1016/j.neuropsychologia.2020.107489.

Ritchie, J.B., Kaplan, D.M., Klein, C., 2019. Decoding the brain: Neural representation and the limits of multivariate pattern analysis in cognitive neuroscience. The British Journal for the Philosophy of Science 70, 581–607. doi:10.1093/bjps/axx023.

Rokem, A., Kay, K., 2020. Fractional ridge regression: a fast, interpretable reparameterization of ridge regression. GigaScience 9. doi:10.1093/gigascience/giaa133.

Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., Huang, Z., Karpathy, A., Khosla, A., Bernstein, M., Berg, A.C., Fei-Fei, L., 2015. ImageNet large scale visual recognition challenge. International Journal of Computer Vision 115, 211–252. URL: https://doi.org/10.1007/s11263-015-0816-y, doi:10.1007/s11263-015-0816-y.

Simonyan, K., Zisserman, A., 2015. Very deep convolutional networks for large-scale image recognition. arXiv URL: https://arxiv.org/abs/1409.1556, arXiv:1409.1556.

Storrs, K.R., Kietzmann, T.C., Walther, A., Mehrer, J., Kriegeskorte, N., 2021. Diverse deep neural networks all predict human inferior temporal cortex well, after training and fitting. Journal of Cognitive Neuroscience 33, 2044–2064. doi:10.1162/jocn_a_01755.

Vedaldi, A., Lenc, K., 2015. MatConvNet: Convolutional neural networks for matlab, in: Proceedings of the 23rd ACM International Conference on Multimedia, Association for Computing Machinery, New York, NY, USA. p. 689–692. URL: https://doi.org/10.1145/2733373.2807412, doi:10.1145/2733373.2807412.

Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., Diedrichsen, J., 2016. Reliability of dissimilarity measures for multi-voxel pattern analysis. NeuroImage 137, 188–200. URL: https://www.sciencedirect.com/science/article/pii/S1053811915011258, doi:https://doi.org/10.1016/j.neuroimage.2015.12.012.

Williams, M.A., Dang, S., Kanwisher, N.G., 2007. Only some spatial patterns of fmri response are read out in task performance. Nature Neuroscience 10, 685–686. URL: https://www.nature.com/articles/nn1900, doi:10.1038/nn1900.

Appendix   A.   Effects of different fold sizes of the outer cross-validation

Figure A.10: For a subset of the analyzed data, we systematically varied the size of the outer k-fold in post-hoc analyses. Results were largely invariant across different fold sizes. For computational reasons, we opted for a 5-fold cross-validation, which was repeated 10 times.

Appendix B. Effects of different repetition times of the inner cross-validation

Figure B.11: For a subset of the analyzed data, we systematically varied how often the inner 5-fold cross-validation was repeated. Results were largely invariant across different repetition times. For computational reasons, we opted for repeating the inner cross-validation 5 times.

Appendix C. Time and RAM usage of different computational problems

Figure C.12: For different computational problems, we measured how much time was needed to solve the problem. For an outer 5-fold which was repeated ten times, we measured the time in seconds needed (y-axis in log scale with base 10) as a function of the number of reweighted features (x-axis) for different numbers of objects (rows) and whether the outer cross-validation was explicitly parallelized or not (columns). Note that the scale of the y-axis differs for each panel.

Figure C.13: For different computational problems, we measured how much RAM was needed to solve the problem. For an outer 5-fold which was repeated ten times, we measured the RAM usage in megabyte needed (y-axis in log scale with base 10) as a function of the number of reweighted features (x-axis) for different numbers of objects (rows) and whether the outer cross-validation was explicitly parallelized or not (columns). Note that the scale of the y-axis differs for each panel.