Finding landmarks – An investigation of viewing behavior during spatial navigation in VR using a graph-theoretical analysis approach

7 by Jasmin L. Walter[1¶*], Lucas Essmann[1¶], Sabine U. König[1], Peter König[1,2]

8
9 1 Institute of Cognitive Science, University of Osnabrück, Osnabrück, NI, Germany
10 2 Department of Neurophysiology and Pathophysiology, University Medical Center
11 Hamburg-Eppendorf, Hamburg, HH, Germany
12
13
14 * Corresponding author:
15 jawalter@uni-osnabrueck.de (JLW)
16

17 ¶ These authors contributed equally to this work.

19 **Key words: Spatial Navigation, VR, Graph Theory, Eye Tracking, Landmarks**

Abstract

Vision provides the most important sensory information for spatial navigation. Recent technical advances allow new options to conduct more naturalistic experiments in virtual reality (VR) while additionally gather data of the viewing behavior with eye tracking investigations. Here, we propose a method that allows one to quantify characteristics of visual behavior by using graph-theoretical measures to abstract eye tracking data recorded in a 3D virtual urban environment.

The analysis is based on eye tracking data of 20 participants, who freely explored the virtual city Seahaven for 90 minutes with an immersive VR headset with an inbuild eye tracker. To extract what participants looked at, we defined "gaze" events, from which we created gaze graphs. On these, we applied graph-theoretical measures to reveal the underlying structure of visual attention.

Applying graph partitioning, we found that our virtual environment could be treated as one coherent city. To investigate the importance of houses in the city, we applied the node degree centrality measure. Our results revealed that 10 houses had a node degree that exceeded consistently two-sigma distance from the mean node degree of all other houses. The importance of these houses was supported by the hierarchy index, which showed a clear hierarchical structure of the gaze graphs. As these high node degree houses fulfilled several characteristics of landmarks, we named them "gaze-graph-defined landmarks". Applying the rich club coefficient, we found that these gaze-graph-defined landmarks were preferentially connected to each other and that participants spend the majority of their experiment time in areas where at least two of those houses were visible.

Our findings do not only provide new experimental evidence for the development of spatial knowledge, but also establish a new methodology to identify and assess the function of landmarks in spatial navigation based on eye tracking data.

Author Summary

The ability to navigate and orient ourselves in an unknown environment is important in everyday life. To better understand how we are able to learn about a new environment, it is important to study our behavior during the process of spatial navigation. New technical advances allow us to conduct studies in naturalistic virtual environments with participants wearing immersive VR-headsets. In addition, we can use eye trackers to observe the participant's eye movements. This is interesting, because observing eye movements allows us to observe visual attention and, therefore, important cognitive processes. However, it can be difficult to analyze eye tracking data that was measured in a VR environment, as there is no established algorithm yet. Therefore, we propose a new method to analyze such eye tracking data. In addition, our method allows us to transform the eye tracking data into graphs which we can use to find new patterns in behavior that were not accessible before. Using this methodology, we found that participants who spend 90 min exploring a new virtual town, viewed some houses preferentially and we call them gaze-graph-defined landmarks. Our further analysis reveals also new characteristics of those houses that were not yet associated with landmarks.

Introduction

Having a sense of orientation and being able to navigate in the world that surrounds us is essential in everyday life. Specifically, the awareness of one's own position in space combined with the ability to remember key locations to plan mental routes between them (1) is crucial. This enables efficient navigation to a location by using globally accessible knowledge of a new environment or previously acquired knowledge of a known environment. Overall, the ability to remember and use important locations and their relations is essential for spatial navigation.

The impact of remembered objects in the environment, called landmarks, on spatial navigation abilities is widely investigated. Even though it lacks a clear definition, the term landmark is most commonly used for visually salient objects in the environment (2). Landmarks can be distal objects that can be seen from far away, termed global landmarks, or more proximal objects that serve as local landmarks (3). Single landmarks can be used as navigational beacons, e.g., a church tower (2,4,5) and can also provide visual cues for direction and orientation information (2,6,7). Getting to know an environment, environmental objects develop action-relevant associations, like turn left at the supermarket, for wayfinding to a goal (2,8,9). Furthermore, multiple landmarks and their intrinsic geometry can be used as an allocentric reference frame for object location information (2,4,10,11). Thus, visual landmarks and their multiple function in everyday navigation, have been cornerstones for spatial navigation.

In spite of their ubiquitous use, investigating the concept of landmarks does not come without problems. Often, studies investigate landmark based navigational learning by introducing single cues to serve as landmarks in an otherwise undifferentiated environment. For example, the Morris water-maze is a widely used task to study the physiological mechanisms of spatial learning in rodents (12–14). Similarly, adaptations of the Morris water-maze in virtual environments (15–17) and other maze tasks (18,19) have been used to investigate spatial navigation in humans. However, in recent years experimental designs of spatial navigation research have shifted to make us of more naturalistic settings (20–27). The trend towards more naturalistic environments can be also observed in virtual environments, where technical advances allow for more complex and visually rich environments (28,29), as well as increased ecological validity including freedom of movement using head mounted virtual reality headsets (30–32).This development towards more complex environments creates the need to clearly define the concept of landmarks.

In addition, performing eye tracking during spatial navigation also allows capturing visual behavior in real-time, and investigating the most important sense for spatial navigation in humans (33). While there are studies investigating visual behavior in real world indoor (22,23) and outdoor (24–27) environments, they are often challenged by limited experimental control due to variance in environmental conditions (24–26) and technical drawbacks of mobile eye tracking like manual frame-based detection of regions of interests (22,26,27) and limited calibration options (26). In contrast, technological advances in VR technology often allow the direct integration of eye trackers into head-mounted VR headsets (34), therefore facilitating eye tracking recording in complex and more ecologically valid environments while maintaining full experimental control. However, although eye tracking in VR facilitates

technical aspects related to the calibration and localization of regions of interests (34), it still
creates new challenges for the analysis of eye tracking data. In classical visual exploration of
static 2D images, fixations and saccades dominate. In a complex 3D environment vestibulo-
ocular reflexes and pursuit movements additionally occur on a regular basis. However, there
is no established algorithm to differentiate this expanded set of eye movements in eye
tracking data collected in a 3D environment. Thus, to identify characteristics of visual behavior
during free exploration of a virtual village and how they relate to spatial navigation, a new
method is needed.

In this study, we propose a procedure to analyze eye tracking data and a data driven
method to objectively define and quantify visual behavior with respect to spatial information.
We use a graph-theoretical analysis approach to access global navigation characteristics
across participants and investigate the occurrence, connectivity, and navigation function of a
subset of houses, consistently outstanding in their graph-theoretical properties. The approach
is applied to eye tracking data recorded during free exploration of a virtual town that was
originally designed to investigate spatial learning within an immersive virtual environment in
comparison with learning of a city map of the same environment (35,36). Overall, our findings
establish a new methodology to identify and assess the function of outstanding houses in
spatial navigation based on eye tracking data.

Results

We collected eye tracking data of 22 participants (11 females, age: M = 22.86y, SD = 2.59y)
during 90 min of free exploration in the virtual city Seahaven. All participants gave their
written informed consent to participate. The study was approved by the Ethics Committee of
the Osnabrück University following the Institutional and National Research Committees'
ethical standards. The participants wore a VR headset with an inbuild eye tracker. They moved
using a controller and physically rotated their body on a swivel chair to turn in the virtual world
(Fig. 1a). The virtual city was built on an island and comprised 213 houses (Fig. 1b). Colliders,
i.e., transparent closely fit box-like structures, surrounded all houses, trees, and roads. They
are invisible to the participants and serve to facilitate computations in the virtual
environment, e.g., detecting collisions and determining viewing direction. Specifically,
colliders are components in Unity that can be fit to an object to identify the object's physical
boundary. Colliders therefore provide the basis for the system calculating properties of the
real world like an object being solid and therefore "colliding" with other solid objects.
Furthermore, we calculated the viewing direction based on the position of the participant in
the VR, the rotation of the headset, and information from the eye tracker. After data
collection, we cast a virtual ray in the viewing direction until it hit a collider, thus the boundary
of an object, indicating that the participant viewed the respective object (34). This process
was completed 30 times per second. Aggregated over all participants, this led to about
3.500.000 hit points that form the basis of our data analysis.

a.

b.

Figure 1: Experimental Setup and Seahaven (a)*The participant sits on a fully rotatable swivel chair wearing headset and controller. The experimenter's screens in the background allow monitoring the participant's visual field of Seahaven (left) and the pupil labs camera images (right).* ***(b)*** *The island of Seahaven in aerial view.*

Defining gazes in VR

Eye tracking in an VR environment provides several challenges for data quality. Compared to conventional desktop settings, VR environments allow increased freedom of movement. Under these conditions, participants perform fixations, saccades, vestibulo-ocular reflexes, and smooth pursuit movements. No general algorithm to classify these types of eye movements has been established yet. Thus, the development of appropriate processing algorithms for the eye tracking data is crucial.

As a first step, we use the collider hit points resulting from casting a ray in viewing direction until it hits an object's collider to identify the object the participants focused their gaze on. Each collider corresponds to an entire object; thus, each hit point identifies an entire object. For our analysis, houses form the regions of interests (ROIs). The "no house" category (NH) summarizes all other collider hits except houses, e.g., grass, roads, trees, and the water. Samples that do not hit a collider, thus hitting the sky or the sun, are identified as "sky" category. We then combine directly consecutive hit points on the same collider to identify clusters. Please note that the clusters do not contain information on where in the participant's visual field the viewed object occurred. This pre-processed data of combined consecutive hit points on the same collider serves as the basis for all following data processing.

As a second step, we address the problem of missing data in individual participants. We label all data samples that were recorded with a probability of correct pupil detection of less than 50% as "missing data samples". Subsequently, we exclude two participants who had

more than 30% of their eye tracking data classified as missing data. All further data analysis is
conducted with the data of the remaining 20 participants.

In the following we will need to differentiate between periods where participants
could perceive the visual stimuli or not. Given that vestibulo-ocular reflexes and smooth
pursuit movements stabilize the retinal image in dynamic situations and allow perception in
that period similar to fixations (37), here and in all following analyses we subsume these under
the general term of fixations. In contrast, participants are blind to visual input during saccadic
suppression (37,38). While classical fixation detection algorithms often differentiate eye
movements based on velocity, these eye movements also display a temporal disparity.
Specifically, saccades usually range from a duration of 10 to 100 ms, while fixations typically
occur from 150 to 600 ms with a mode around 250 ms (37). Therefore, we conjecture that
with an appropriate temporal threshold, it is possible to identify data clusters containing
fixations. Based on our 30 Hz sampling rate, a hit point sample is created after every 33.33 ms,
limiting the temporal resolution of the gaze movement data available. Consequently, the
available thresholds closest to the mode at 250 ms are 233 ms and 266 ms, which are
equivalent to seven and eight samples respectively. We select the more conservative value of
at least eight samples (~266 ms) as a threshold to identify data clusters containing fixations.

However, since the data still includes a considerable amount of missing data points,
we expect a significant number of clusters to be "cut" by missing data points, thus appearing
to be of shorter duration. Consequently, using a fixed temporal threshold to identify clusters
containing fixations creates the problem of falsely failing to identify these "cut" clusters as
clusters containing fixations. Therefore, to counteract this effect, it is crucial to interpolate
missing data samples if possible.

Therefore, as a third step in our pre-processing algorithm, we interpolate short
intervals of missing data. If fewer than eight consecutive data points (~266 ms) are missing, it
is improbable that participants had enough time to make a saccade to a different spatial area
(ROI), finish a fixation, and make a saccade back to the same area. This reasoning is done in
close analogy to the reasoning of the threshold value to determine data clusters containing
fixations above. Consequently, we interpolate data if fewer than eight consecutive data points
are missing and only if these occur between two clusters on the same collider (ROI) (Fig. 2a).
In case these interpolation criteria apply, the interpolated data points are labelled with the
collider name and combined with the data clusters surrounding the short interval of missing
data. Larger gaps are not interpolated but treated as missing data. Furthermore, missing data
points occurring between samples of different colliders are not interpolated, independently
of the duration of the gap. This procedure ensures that most fixations are captured while
minimizing false interpretations of missing data.

Figure 2: Defining gazes. (a) We interpolate missing data only if less than eight samples are missing consecutively (pupil detection with less than 50% probability) and if these samples occur between two clusters on the same collider. During the interpolation process, these samples are then unified with the two clusters to form a new cluster on the same collider. The first row shows three clusters of missing samples (marked noData), while the second row represents the result of the algorithm. In the first cluster (green box), both interpolation conditions apply: there are fewer than eight consecutive missing data samples (#4) and they are surrounded by two clusters on the same collider. Consequently, these missing samples are interpolated and combined to a new cluster. In the second cluster (1st orange box) the first interpolation condition applies (#noData samples < 8) but the cluster occurs between clusters on two different colliders (H103 and H54). Therefore, no interpolation is performed. In the third cluster (2nd orange box) only the second interpolation condition applies. Even though the missing data samples occur between two clusters on the same collider (H55), the first interpolation condition is violated (#noData samples ≥ 8). Consequently, no interpolation is performed. (b) Histogram of hit point cluster length distribution after interpolation. The longest hit point cluster on a house had a duration of 18.9 s. For improved visibility, we combined all cluster durations that are longer than 1000 ms into the last bin. The ordinate corresponds to the probability of each duration. Since previous work used gamma distributions to model the distribution of fixation durations or response latencies (39,40), we model the two partly overlapping gamma distributions for visualization only, fitting the distributions of the duration of fixations (green) and non-fixation events (grey). The dashed red line marks the separation threshold for gazes. (c) The pie chart shows the result of the gaze classification across all participants.

As a fourth step, we finally apply the temporal threshold to identify clusters that contain fixations during which the participants could process the visual input. As described above, we adopt a threshold of eight samples to identify clusters that contain at least one

fixation (Fig. 2b). Using this approach, shorter clusters likely to be caused by samples during
saccades, i.e., periods during which perception was suppressed, would be excluded from
further analysis. In the following, we will define these clusters containing fixations as new
meaningful "gaze" events and they will form the basis of our further analysis.

This procedure classifies on average 86% of the data samples as belonging to gazes
(Fig. 2c). Previous studies reported that humans spent approximately 90% of viewing time on
fixations (37). This indicates that our attempt to capture gaze events under dynamic
conditions in VR is on the conservative side.

How to create graphs from gazes

To capture information gathered by the participants during exploration of the virtual town,
we create gaze graphs based on the gaze events. In these graphs each node represents a
house. Viewing two houses in the VR environment in direct succession gives information on
their relative spatial location. Therefore, if anytime during the experiment a gaze event on a
house is directly followed by a gaze event on another house the respective nodes are
connected by an undirected edge. All gaze graphs are undirected and unweighted. Hence,
they do not contain information about the directionality or frequency of their edges (i.e.,
direction and frequency of succession of gaze events). The completed gaze graphs capture the
spatial information obtained by the visual exploration in the virtual town.

The first 30 seconds of one participant exploring Seahaven serve as an example of the
process to create a graph (Fig. 3a). The graph contains one node for each house (ROI), but
does not consider the spatially unspecific no-house and sky category. The graph creation
process starts with an edge between the first house viewed and the second house viewed (Fig.
3b). If the gaze on a house is followed by a missing data cluster, then no edge is created. As
stated above, the edges are unweighted, i.e., binary. That is, if the participant looked back to
two houses already seen in sequence, an edge between these houses is already in place and
the graph is not changed. The process of edge creation is iterated for all gaze transitions.
Whenever a new house is viewed, a new node is created in the graph. Fig. 3c shows a
visualization of the result of applying this procedure to the complete data of the example
participant.

The construction of the graphs uses two free parameters. The first parameter
determines the width of gaps that are not interpolated. The second parameter sets a
threshold for the minimal number of samples in a cluster required to define a gaze event. Both
parameters relate to the typical length of a fixation and are set to a value of eight samples (k
= 8). In order to estimate the impact of this choice, we rerun the graph generation algorithm
with a lower (k = 7) and a higher (k = 9) setting. Averaged over participants, we obtain a mean
number of nodes of 209.05+/-2.21, 208.20+/-2.65, and 207.55+/-2.78 mean+/-standard
deviation for k = 7, 8, 9 respectively. Thus, the differences in the mean number of nodes for
different parameter values are of the order of 1% of the total number of nodes. Averaged over
participants the mean number of edges results in 898.1+/-139.03, 883.45+/-134.16, and
855.45+/-127.56 mean+/-standard deviation for k = 7, 8, 9 respectively. Thus, the differences
in the mean number of edges for different parameter values are of the order of 2.5% of the

mean number of edges. In this analysis the nodes and edges need not necessarily be identical,
and the variance of the number of edges is large. Nevertheless, the number of nodes and
edges is rather consistent comparing the mean number of nodes and edges over all
participants of all three thresholds. The choice of the parameter does not appear to be critical
and in case of doubt, k=7 implies smaller changes than a choice of k=9.
280

Figure 3: Graph creation. (a) *Time line of gaze events by a participant. The abscissa*
represents the first 30 seconds (900 hit points) of the recordings. The ordinate contains all
viewed houses viewed during that time line. We number houses and name them accordingly,
e.g., H148 for house number 148. In this panel each house has a distinct color for visualization
only. The grey bars represent clusters of the NH category, which are not considered during
graph creation. The black bar identifies a remaining cluster of missing data samples.
Therefore, no edge will be created at this moment in the time line. (b) The graph corresponding
to the time line of panel A is visualized on top of the map of Seahaven. The colors of the nodes
match the colors of the boxes in panel A. Edges are labelled according to the order they were
created. (c) The complete graph of a single participant based on all gaze events during 90 min
of exploration visualized on top of the 2D map of Seahaven. Note that in this visualization the
locations of the nodes correspond to the locations of the respective houses they represent in
Seahaven, however, this locational information is not contained in the graph itself.

Is it a single city or multiple suburbs? – Graph partitioning

To address questions on spatial cognition, we are interested whether the virtual city should
be treated as a loosely connected set of suburbs or as a coherent single city. The search for
distinct clusters in the graph directly relates to the problem of graph partitioning. In the field
of graph theory, partitioning is a well investigated problem as it divides a graph into smaller
mutually non-overlapping subgraphs. In other words, the procedure of partitioning a graph

has the objective to investigate whether the graph can be easily cut into two or more
completely separate graphs. Here, "cut" is used as a term to remove an edge from a graph.
For this, the number of connections between nodes is relevant. Nodes that form a cluster have
a high number of within-cluster connections. Separate clusters are only connected with a few
between-cluster connections. The fewer these between-cluster connections are the fewer
need to be cut to separate the clusters from each other. Of specific interest are therefore
approaches that maximize within-cluster connections (those connections are maintained) and
minimize between-cluster connections (those are cut). If two distinct clusters would be found,
the viewing behavior in Seahaven would be concentrated, in other words 'clustered', in two
distinct areas and the city could not be treated as one coherent city. In that case, the following
analyses would have to be applied to the separate clusters individually, ignoring and cutting
the edges between them. Thus, graph partitioning is an important step to classify Seahaven
as a set of suburbs or as one coherent city.

Graph partitioning, the search for clusters of nodes heavily connected within but few
connections to the remaining nodes forms a difficult computational problem. In principle, it
can be addressed by exhaustive search. However, even for graphs of moderate size, the
computational requirements are staggering. Therefore, we employ the spectral graph
analysis, which is a highly efficient procedure in graph theory. In the next paragraph, we give
the technical details to allow exact reproduction. A more detailed definition as well as simple
introductory examples are provided in the method section 'Graph Theory – detailed
explanations of used graph measures – Graph Partitioning'. However, these details of "how"
to obtain the partitioning of a graph into subgraphs are not critical for the further
understanding of the results. The question "does such a partitioning have few or many
connections between the subgraphs" is more relevant as described further down.

The spectral graph analysis is based on the eigenvalue spectrum of a network's
Laplacian matrix that gives insights into the graph's connectivity (41,42). First, we consider the
adjacency matrix and the degree matrix of a graph. The former is a binary square matrix where
each entry indicates whether an edge connects the two nodes / houses. The latter is a square
matrix that contains the degree of each node on its diagonal and is zero otherwise. We
calculate the Laplacian matrix by subtracting the degree from the adjacency matrix. By
construction of the Laplacian matrix the smallest eigenvalue of this matrix is always zero. The
spectral graph analysis then uses the 2^{nd} smallest eigenvalue of the Laplacian matrix. The
larger the 2^{nd} smallest eigenvalue of the Laplacian matrix is, the higher is the overall
connectivity of the network (μ_2 = 0.300+/-0.097). The eigenvector of this 2^{nd} smallest
eigenvalue is also called Fiedler vector (43,44). This Fiedler vector has one entry for each node
and gives insight into groups of nodes that are mostly interconnected with each other. The
Fiedler vector (Figure 4c) has a negative and positive component that can be used to divide
two clusters. The further the Fiedler vector is away from 0 the higher is the connectivity of the
particular node within its cluster. Figure 4c shows that many entries of the Fiedler vector are
around 0, meaning that those nodes are also connected with nodes from the other cluster,
i.e., indicating the absence of separate clusters. A Fiedler vector that indicates a clustering
effect can be examined in the graph partitioning toy example of Figure 12c in the method

section. By sorting the adjacency matrix according to the sorting index of the Fiedler vector,
the potential clusters can be visualized, which would manifest in a modular block pattern (Fig.
4a). However, this pattern is not visible in the present analysis, illustrating the absence of
distinct clusters, but can be also examined in the graph partitioning toy example of Figure 12a
in the methods section.
348

Figure 4: Graph partitioning. (a) *The sparsity pattern of the graph's adjacency matrix sorted*
by the entries in second smallest eigenvector. Color coded into edges between nodes of one
cluster (green), edges between nodes of the other cluster (blue), edges between nodes of the
two clusters (black) and a distinction between the clusters (yellow). ***(b)*** *The two clusters are*
displayed onto the map of participant 35. ***(c)*** *The second smallest eigenvector of the Laplacian*
matrix is sorted ascendingly and color coded into two clusters.
356

357   To investigate the quality of the partitioning, we follow the definitions used by
358   Schaeffer (45). As a measure of cluster goodness, we consider the intra-cluster density and
359   the inter-cluster density. The density of a graph is defined as the ratio of instantiated edges
360   relative to the number of possible edges:

361
$$\delta(G) = \frac{m}{\binom{n}{2}}$$

362   with $n = |V|$ as the number of nodes, and $m = |E|$ as the edge count. Furthermore, we
363   define the intra-cluster density as the average of the densities of both clusters and the inter-
364   cluster density as the ratio of inter-cluster edges to the maximum possible inter-cluster edges.
365   We analyze the graphs of individual participants based on 90 min exploration time. On
average, the participants' graphs contain 883 edges. The mean density of the graphs is
0.041+/-0.006. This means that compared to a fully connected graph (each house is connected

to each other house) on average 4.1% of all possible edges are instantiated. Furthermore,
dividing the graphs into two parts would require on average a cut of at least 9.3% of the edges
of the graph. Specifically, a sufficient cut has to cut on average 82.6 edges resulting in two
clusters with approximately 400 edges each. After partitioning, the mean intra-cluster density
was 0.079+/-0.012, while the mean inter-cluster density was 0.0083+/-0.0020. These numbers
indicate that the graph cannot be easily partitioned, without cutting a fair number of edges.

In conclusion, our results reveal that the graphs cannot be distinguished into large-
scale clusters. That is, the exploration of Seahaven does not show separate city blocks, but
was rather well-balanced. Thus, the virtual environment can be treated as one coherent city.

The distribution of gazes on houses - Node degree centrality

378 We characterize the role of different houses during visual exploration by indices adapted from
379 graph theory. The node degree centrality is the main and most basic graph-theoretical
380 measure in graph-theoretical research. It is defined as the number of edges connecting a node,
381 which is the sum over the entries of a column of the adjacency matrix:

382
$$c(i) = \sum_{j}^{N} x_{ij}$$

with i being the node under consideration and x_{ij} the adjacency matrix. Here, the node degree
of a house reflects the number of other houses a participant made a gaze to or from the house
under consideration in direct succession. Thus, the node degree centrality in the gaze graph
differentiates houses according to their importance during visual exploration in the virtual
town.

First, we use the node degree centrality to investigate the viewing behavior on an
individual participant level. Fig. 5a shows the gaze graph of a participant with individual nodes
color coded according to the respective node degree. Whereas many nodes have a degree
centrality in the single digit range, a few houses reach rather high values. The node degree for
each participant ranged up to 33. It is apparent that the range of node degrees is surprisingly
large.

Figure 5: Node degree centrality. (a) The graph of one participant is visualized on top of the map of Seahaven. The nodes were colored according to their respective node degree centrality. (b) The individual mean node degrees of all participants (blue line) and their respective standard deviation (grey lines) are depicted sorted by increasing values. (c) A pseudo 3D plot color coding the node degree of every house (abscissa) for every participant (ordinate). The houses are sorted so that the average node degree value increases along the abscissa. Similarly, the participants are sorted, so that the average node degree increases along the ordinate. The marginals of this plot result in the panels b and e. (d) The distribution of the pairwise inter-participant correlation coefficients of the node degree values of all houses. (e) The mean node degree of each house sorted according to the mean node degree along the abscissa (blue line) and their respective standard deviations (grey lines).

Next, we investigate the similarity of the node degree centrality distribution over participants. We calculate the average node degree of each participant across all houses and for visualization sort the participants in increasing order (Fig. 5b). This reveals limited variations between participants. The average node degree of each house across all participants (Fig. 5e) showed a monotonous linear increase. Both aspects are also combined in a pseudo-3D visualization (Fig. 5c) that matches the order of the houses and the order of participants. Sorting the houses according to the average node degree centrality leads to a near monotonous increase on the individual participant level as well. Thus, the set of houses with highest node degrees are largely overlapping between participants. This was quantified by the high correlation of 0.70 (+/- 0.06) of node degree centrality between participants (Fig. 5d). In summary, the node degree centrality varies considerably between houses, while the values of individual houses are rather consistent across participants.

The distribution of node degree centrality over houses reveals interesting aspects. Over a large range of houses the average node degree centrality increases only slowly. Only for the last few houses, we observe a steep increase. These houses stand out from the other houses and are viewed directly before or directly after viewing many other houses. Therefore, the high node degree centrality houses may serve as important reference points.

In summary, the node degree is a simple yet powerful centrality measure that can be used to identify important nodes in the gaze graph, hence important houses in visual behavior. First results indicate that a small number of houses show an especially high node degree across all participants, setting themselves apart from the rest of the city. Interestingly, a small number of houses with participant independent high node degree values, i.e., houses with many visual connections to other houses, would also be the characteristics that we would expect landmarks to display in gaze graphs.

High node degree centrality houses – Hierarchy index

To further investigate the houses with a high node degree in respect to their distribution, we apply the graph-theoretical measurement of the hierarchy index. This index characterizes hierarchical configurations within networks. By applying it to the degree values that are above the participant's respective median, we focus the index on the upper tail of the distribution of

node degree centrality. Here, we fit in a bi-log plot of the node degree centrality with frequency against the node degree values with the slope of the regression line starting from the participant's respective median, depicted in Fig. 6a for one example participant with a slope of -2.6349. Performing this analysis for all participants results in a slope smaller than -2.00 throughout, with a mean of -2.91. Furthermore, the small standard deviation of 0.34 showed, that the hierarchy index is similar across participants (Fig. 6b). According to Rodrigue (46), networks with strong hierarchical configurations, i.e., with many low degree nodes and few high degree nodes, had a slope of below -2 (or above 2). Therefore, the hierarchy index reveals a clear hierarchical structure of the gaze graphs and emphasizes the importance of the few exceptionally high node degree centrality houses.

a.   **b.**

***Figure 6: Hierarchy index. (a)** The frequency of occurrence of the node degree for a single participant. The green line indicates the linear regression starting at the median of the distribution. **(b)** The distribution of the hierarchy index across all participants.*

This observation triggers a detailed look at the mean node degree distribution over all participants to identify those special high node degree houses. Plotting the mean node degree of houses averaged across participants onto the map of Seahaven (Fig. 7c) highlights the scattered subset of high node degree houses. Furthermore, the mean node degree across all houses and all participants measures 8.3 with a standard deviation of 3.98 (Fig. 7a). We select the value of the 2-sigma distance (16.25) as the threshold to identify the high node degree houses. This results in a set of 10 houses in Seahaven with node degree centrality values exceeding the threshold.

Figure 7: The high node degree centrality houses. (a) *The mean node degree distribution across all participants with mean, 1σ- and 2σ-thresholds.* **(b)** *A box plot of the 10 houses with at least 2σ-distance to the mean node degree.* **(c)** *A map plot with all nodes color coded with their respective average node degree across all participants.* **(d)** *The 10 houses, which exceeded the 2σ-distance to the mean displayed on the map for our example participant with all their connections and color coded with their respective node degree.*

Next, we analyze these houses with respect to their interconnectivity and visibility in the city. The distribution of the node degree centrality over participants for each of the 10 houses in Seahaven reveals considerable variance (Fig. 7b). However, all 10 houses for all participants have a node degree centrality of 9 or above. Plotting them jointly with all their edges onto the map of Seahaven for our example participant shows that they are located centrally within the city. However, these houses are connected to the outer areas of the city and together cover nearly the whole city (Fig. 7d). All in all, these 10 high node degree houses, are located centrally in the city and their connections reach out into outer areas, i.e., they are viewed from much of the city area.

The characteristics of high visibility of a small number and similar use over participants would be expected in landmarks. Our results show that the node degree distribution is similar across participants and that only a few houses have exceptionally high node degrees. This is supported by the hierarchical configuration of the network. The 10 houses with an average node degree distribution exceeding a 2-sigma threshold are more centrally located and had viewing connections into the outer areas covering nearly the whole city. All things considered, these findings suggest the notion that this set of houses is exceptional across multiple domains and displays the characteristics expected from landmarks. Therefore, in the following we will refer to these 10 buildings as "gaze-graph-defined landmarks".

The connections between the gaze-graph-defined landmarks – The rich club coefficient

In this section we investigate, whether the gaze-graph-defined landmarks serve as the core of a network that could be used for navigation in the city. For a quantitative investigation, we applied the concept of the rich club coefficient to our gaze graphs. The rich club coefficient is a frequently practiced graph-theoretical method in network theory and was initially applied in internet network analyses (47). Yet, the rich club coefficient has also been transferred to neuroscientific contexts. The approach has been used to map out both subcortical and neocortical hub regions and to show that those regions with high linkages are also highly connected between each other and, thus, indeed form a rich club (48). In this study, the rich club coefficient allows one to quantify in how far gaze-graph-defined landmarks are preferentially connected to each other.

We calculated the connectivity between a subset of nodes with at least a specific degree value using

$$RC(k) = \frac{2E_{\geq k}}{N_{\geq k}(N_{\geq k} - 1)}$$

with k as the set node degree threshold of the rich club, $E_{\geq k}$ as the number of edges between nodes with degree larger or equal to k, and $N_{\geq k}$ as the number of nodes with degree larger or equal to k. Thus, the rich club coefficient is the fraction of edges instantiated between nodes of degree k or larger and the total number of edges possible between nodes with the same degree or larger. In other words, we first check how interconnected the whole graph is and subsequently decrease the subset of nodes considered by removing low degree nodes from the set.

For the interpretation of the rich club coefficient, we need a baseline. For that purpose, we compare generated random graphs with similar statistics of node degrees and calculate their rich club coefficient. For each participant, we generate 1000 random graphs with the same number of nodes as the respective original graph. Of these, we select the 10 graphs with the most similar, in terms of the two-sample Kolmogorov Smirnov test, distributions of node degrees to the original distribution and use these as a baseline. Subsequently we take the ratio of the original rich club coefficient and the coefficient of one of the control random graphs. Finally, we average this ratio over all control graphs. This results in an adjusted rich club coefficient that compares the connectivity between those houses that pass the threshold with a random graph with matched node degree statistics. A value of 1.0 indicates no bias in connectivity, higher values would indicate a preferential connectivity within the considered set of nodes.

As a next step we investigate the rich club coefficient as a function of the threshold node degree. For example, for a threshold of 1 all nodes of a degree 1 or larger are considered. For this case we observe a coefficient at 1.0 (Fig. 8a). Raising the threshold to 2, i.e., excluding all nodes of degree 1, leads only to a minor increase of the index. That is, houses of degree 2 or higher are preferentially connected within this group only to a small degree. This indicates that such a liberal threshold including the larger part of all houses does not reveal a meaningful bias in graph connectivity. Increasing the threshold value, i.e., removing low

degree nodes from the set of considered nodes for the connectivity calculation, results to a
monotonically increasing coefficient rising up to 1.5 (Fig. 8a). Thus, the subset of high degree
nodes is preferably interconnected in comparison to a random graph. However, increasing the
threshold node degree naturally leads to a smaller number of nodes included and therefore
increasing variance in the estimate. Therefore, we cut off the plot at a threshold value of 13,
which is the mean node degree centrality plus one standard deviation rounded up (compare
Fig. 7a). Please note that the rich club coefficient is a continuous value. That is, there is no
single threshold value defining a strict qualitative boundary. Instead, the selectivity of
connectivity rises continuously. We consider the threshold value of 13 as the value with the
largest bias, where the index can be reliably determined. This demonstrates that the nodes
with a degree of 13 and above, are interconnected much more than expected by chance and
can therefore be considered as part of a rich club.

As a final step, we counted the nodes with a node degree of at least 13 for each
participant subsequently creating a list of houses and their frequency of having a degree of at
least 13. From that list, we specifically mark the top 10 houses with the highest frequency of
being part of the rich club across all participants (Fig. 8b). These houses had the average
highest interconnectivity and were the same houses that were identified as the top 10 node
degree houses, i.e., gaze-graph-defined landmarks, earlier. This connection is expected since
the rich club is based on a node degree threshold and the node degree distributions of
participants have a very high correlation (Fig. 5d) meaning that the rich club nodes have high
node degrees across participants. Overall, this analysis does not only confirm that the high
node degree nodes are participant independent, but it gives evidence for a highly
interconnected network of gaze-graph-defined landmarks in the city, a rich club.
549

Figure 8: The rich club coefficient (a) *The development of the rich club coefficient with*
increasing node degree. The dot-lines are the rich club coefficients of individual participants,
while the green line is the mean across all participants. **(b)** *All houses displayed on the map*
both color coded and size coded according to their frequency of being part of the rich club
across participants.

Spatial arrangement of the gaze-graph-defined landmarks - Triangulation

To elucidate the role of the gaze-graph-defined landmarks in spatial navigation, we explore whether they could serve as a basis for triangulation. Triangulation is a method to infer one's own location based on the viewing angle in respect to two location anchors. Our analysis has revealed that the gaze-graph-defined landmarks form a highly interconnected rich club. Thus, if the gaze-graph-defined landmarks are visible from most places in the city they could serve as a basis for triangulation.

As a first step we determine the parts of the city where at least one or two of the gaze-graph-defined landmarks were viewed by the participants. We evaluate the spatial distribution of our participants during exploration of the virtual town and how many gaze-graph-defined landmarks were actually viewed from each location. This analysis is performed with a spatial resolution of 4x4m and an additional smoothing with a 3x3 unity kernel. Please note that this analysis depends on the actual gaze data and, thus, reflects from where participants actually did view the gaze-graph-defined landmarks. Next, we differentiated the locations in three categories: zero/one/two gaze-graph-defined landmark were viewed. The resulting map represents the potential of triangulation based on the gaze-graph-defined landmarks at different locations in the virtual city (Fig. 9). In 39.1% of the city areas that were visited by participants, two or more gaze-graph-defined landmarks were viewed from that location, potentially providing the basis for triangulation. In an additional 32.7% of the city area, exactly one gaze-graph-defined landmark was viewed. Only in 28.1% of the visited city area, none of the gaze-graph-defined landmarks were viewed. Weighting the city areas with the absolute time of presence in respective city areas, participants spend an even bigger fraction of the experiment time in areas where the theoretical basis of triangulation was given. Specifically, participants spent 53.2% of the experiment time in areas where at least two or more gaze-graph-defined landmarks were viewed, 19.4% of the time in areas where one gaze-graph-defined landmark was viewed and 27.4% of the time in areas where none was viewed. The latter regions were mostly at the fringes of the city map. Our data do not allow any conclusion on whether the participants actually performed triangulation or whether this option influenced their exploration. However, in principle triangulation based on gaze-graph-defined landmarks is possible in areas of the city where participants spent slightly more than half of their time.

a.

588 ***Figure 9: Triangulation.*** *Location data of all participants plotted on the map of Seahaven.*
589 *The color code indicates how many of the gaze-graph-defined landmark houses were viewed*
590 *by participants at each location.*

Discussion

In this study, we establish a method to quantify characteristics of visual behavior by using
graph-theoretical measures to abstract eye tracking data recorded in a 3D virtual urban
environment. We define gazes of participants that freely explored the virtual city Seahaven,
and use these to convert the viewing behavior into graphs. In these gaze graphs, nodes
represent houses while edges represent their visual connection, i.e., gazes in direct succession
on the respective houses. Thus, the gaze graphs capture relevant spatial information gathered
during exploration. The node degree centrality graph measure reveals a surprisingly large
variance. However, the values of individual houses were rather consistent across participants,
as shown by the high mean correlation. Additionally, we observed that the degree distribution
across houses increased steadily, except for only a few high node degree houses. These houses
may serve as important reference points, the so-called gaze-graph-defined landmarks. The
analysis of the hierarchy index demonstrates that the frequency of houses decreased
drastically with increasing node degree, revealing a hierarchical graph structure. The set of
identified gaze-graph-defined landmarks were indeed preferentially connected, as
demonstrated by the rich club coefficient. Finally, participants spent more than half their
exploration time at locations, where at least two of the houses of the rich club were viewed,

allowing in principle triangulation for spatial navigation. Thus, we presented a graph-
theoretical approach for analyzing gaze movements supporting spatial cognition.

The importance of the VR setup for spatial cognition research

The process of spatial navigation is abundant in everyday life, therefore investigating
the process of gathering spatial navigation under natural conditions is our goal. New mobile
eye tracking systems allow investigating spatial navigation and the role of landmarks under
more natural conditions in real-world environments while recording real-time eye tracking
data, thus capturing the most important sense for spatial navigation (33). For example, Ohm
et al. (22) investigated the selection process of landmarks in large scale indoor environments
via the visual attraction measured with mobile eye tracking and evaluated pedestrian
navigation systems based on indoor landmarks (23). Furthermore, Wenczel et al. (27) found
differences in gaze behavior during incidental and intentional route learning in a natural
outdoor environment with intentional learning leading to more fixations on landmarks.
However, studies conducted with mobile eye tracking systems in natural environments are
usually challenged with several disadvantages. In addition to the poor accuracy of mobile eye
tracking systems, another major issue comes with identifying frames with areas of interest
during the data pre-processing. Often, identification of regions of interests and therefore
identifying the relevant fractions of the eye tracking data could only be solved by manual
detection in each frame (22,26,27). Furthermore, the natural environment allows only limited
control of the experimental conditions, especially regarding variances in light affecting the eye
tracker systems (26), and variance in the environment due to other people or traffic (24,25).
Depending on the system, eye tracking calibration can be distorted for some distances,
therefore limiting the valid distance of gazed objects that can be analyzed (26). Consequently,
most eye tracking studies struggle to be conducted under natural conditions and thus reduce
the ecological validity of gathered information of viewing behavior under natural conditions.

In the present study we follow the idea that virtual reality allows experimental
paradigms in VR with high control while still providing a more naturalistic environment.
However, given that spatial navigation is based on multimodal sensory input, it can be
questioned whether a virtual reality setup to investigate spatial navigation is ecological valid.
Specifically, in the present study we employ a virtual environment that is more restricted in
sensory input than the real world, i.e., limited to visual and vestibular information. In contrast,
recent literature highlights the importance of idiothetic and sensorimotor information about
self-position and about self-motion (49,50). Nevertheless, the dominating sense of spatial
perception is vision (33). Only this sense can gather reliable information of space and the
environment independently of the physical distance and also allows one to perceive
topographic characteristics over large distances. Therefore, by observing visual attention and
visual behavior using the method of eye tracking, we could gather important insights about
the usage of spatial cues, that indicate cognitive processes related to spatial navigation,
specifically landmark usage. Moreover, using a VR setup with additional eye tracking providing
a solution to the technical problems observed in previous studies in real-world environments.
Furthermore, our proposed analysis method using hit point clusters and gaze events allows a

fast and precise analysis option, including the automated identification of ROIs and a cleaning
and interpolation pipeline. Therefore, the proposed analysis improves the ecological validity
of the analyzed data by considering the reduced sampling rate, increased noise sources, and
extended set of eye movements expected in a 3D environment compared to common 2D
desktop eye tracking setups. Consequently, applying the experimental paradigms using the VR
setup and eye tracking analysis proposed in this paper, provides an ecological valid option to
investigate spatial navigation under naturalistic conditions, while avoiding the problems
observed in real-world environments.

Accuracy of eye tracking data recorded in virtual reality

Resting our analysis on eye tracking data allows us to observe and investigate
participants visual attention during spatial navigation processing. However, the combination
of eye tracking and a head mounted virtual reality headset comes with several challenges.
Accuracy of mobile eye tracking systems is often reduced compared to other systems (51).
Specifically, in VR experiments, this is often due to the freedom of head movements and
weight of the VR headset. Since typical errors due to slippage and head movements increase
over time, we conducted a short validation and if necessary, a complete calibration validation
procedure every 5 minutes during the experiment (34). Nevertheless, the mean validation
error of 1.55° before experiment start and 1.88° during the experiment is rather high
compared to classical lab-based eye tracking studies. However, unlike lab-based eye tracking
studies, our preprocessing and analysis is based on hit point clusters that fell on the same
collider in the VR environment. Thus, we summarized data points that were located in rather
close proximity. Though the notion of close proximity must be taken with care since most
colliders still corresponded to the size of a complete house, therefore making a small deviation
in gaze location due to the validation error less problematic. All in all, considering that the
preprocessing is based on the spatial distribution of the accumulated hit point clusters, a
minor increase of validation error should not affect our data significantly.

The data type of "gaze events"

One major factor in the analysis of eye tracking data recorded in an VR environment is
the algorithm differentiating the different types of eye movements and in our case the
definition and creation of the data form "gaze". Essentially, the four different types of eye
movements expected to occur in such a natural setting, i.e., saccades, fixations, vestibulo-
ocular reflexes, and smooth pursuit movements, can be separated into two categories. On the
one hand, we have fixations as the typical source of visual perception. Since vestibulo-ocular
reflexes and smooth pursuit movements stabilize the retinal image in dynamic situations, they
lead to visual perception similar to the input during fixations (37). Thus, we can classify
fixations, vestibulo-ocular reflexes, and smooth pursuit movements as the first category of
visual perception. Saccades, on the other hand, render the participant blind to the momentary
visual input, hence a hit point sample created during a saccade will not have been perceived
by the participant (37,38). Consequently, it is essential to differentiate the data between the

688 first category of visual perception and saccades. Usually, this is done either by velocity or gaze

689 location-based algorithm. However, the virtual environment in Unity3D results in three

690 impeding factors. Firstly, the complexity of the VR environment in Unity3D only allowed for a

691 30 Hz sampling rate, thus it does not allow a saccade detection based on sudden changes in

692 gaze velocity. Secondly, the estimation of gaze location based on the ray cast process is limited

693 to whole colliders, often covering the size of a house, therefore it does not allow to identify

694 small changes in gaze location. And thirdly, depth perception is usually not accounted for in

695 saccade detection algorithms, therefore making it questionable to apply to eye tracking data

696 recorded in 3D. Consequently, the available eye tracking data recorded in the VR environment

697 did not provide the reliable information necessary in classical fixation detection algorithms

698 that allows one to cleanly separate the different eye movements. Therefore, defining the new

699 data form "gaze" allows for a functional method to clean the data. This process did not allow

700 the identification of single eye movements nor did it exclude all saccades from the data.

701 However, by identifying the data clusters that contained at least one fixation and excluded

702 the data clusters that very likely did not contain any fixation, we could clean the data from

703 samples that were unlikely to be visually processed by the participant. This is further

704 supported by our data, since the process identified 86% of the data as gazes on average across

705 all participants. With approximately 90% of viewing time being expected to be spend on

706 fixations (37), the process identifying gazes appears to be on the conservative side. Overall,

707 with higher sampling rates available in virtual environments, new options to identify saccades

708 might become available. However, we believe that given the data we have available, defining

709 the new data form "gaze" was the best option to differentiate between stray samples

710 unprocessed by the participant and meaningful data carrying important information of the

711 first category of visual perception including fixations, vestibulo-ocular reflexes, and smooth

712 pursuit movements.

Gaze graphs

714 The graph-theoretical analysis approach used in this study is crucial, since it leads to a

715 large compression and abstraction of the data. Using this method, a few million of gaze

716 samples were condensed into a few graphs. In general, graph theory is used in many areas to

717 make complex information of pairwise relations accessible (52–54). This process includes

718 several decisions, which might critically influence the later analysis. First, the visibility of the

719 houses depended on the participant's location in the virtual world, which is not necessarily

720 close to one of the respective houses. Accordingly, the participant might view two houses in

721 direct succession leading to a visual connection, even though the houses themselves might

722 not be visible from each other's location. Second, in case the data contained a cluster of

723 missing data points no information about visual connections during this time was available

724 and no edge could be created between nodes. Third, the gaze graph was undirected and

725 binary. It did not contain any information about the order in which the two successive gaze

726 events took place. Consequently, the gaze graphs only contained information about whether

727 a visual connection took place at some point during the experiment, and not how often. It is

728 easy to conceive that quantitative information on the direction and frequency of gaze

trajectories contains useful information. Further, graph theory provides a variety of tools
applicable to such enriched information. While we do consider further studies with enriched
graphs to be a promising avenue for future studies, for the present first step we deliberately
kept the attempt to utilize gaze-graphs for research of spatial cognition simple. Applying the
above considerations for graph creation, our graphs represented the gaze data in a well-
defined and meaningful way.

Gaze graphs and landmarks

Our results of the graph-theoretical analysis revealed a small subgroup of houses that
matched several characteristics of landmarks. Landmark knowledge refers to the knowledge
of salient objects that serve as orientation anchors and are memorized when exploring a new
environment (55–57). Since the node degree is a common measure to investigate the
importance of single nodes in the network (58), we expected landmarks to stand out in visual
behavior compared to other houses and therefore show high importance in the gaze graph
visible in high values of their node degree centrality. The gaze graph represented the visual
connections between houses, therefore, the node degree centrality measured how many
different houses were visually connected with the house in question. If a house would serve
as a landmark, we would expect participants to often create visual connections between the
landmark house and other houses. The results of our node degree centrality analysis showed
a clear difference between a subgroup of houses with the average node degree values of the
houses exceeding the mean node degree over two times the standard deviation. Moreover,
those houses were above chance level interconnected with each other forming a rich club.
The distinctiveness of these buildings is strengthened by the high mean hierarchy index.
Taking all these findings into account, we suggest that these houses fit the characteristics a
landmark would display in a gaze graph and thus propose to call this subgroup of houses gaze-
graph-defined landmarks.
This interpretation of our results was supported by further characteristics of the gaze-
graph-defined landmarks. In a navigational context, the term landmark usually refers to any
type of object that is highly visible or easily recognizable in the environment and thus serves
as a point of reference (2,59). In addition, landmarks are often differentiated into global and
local landmarks (3). Typically, global landmarks can be seen from far distances and provide a
reference for beacon and directional and more compass-like orientation, whereas local
landmarks might only be visible in a local area and are often located at road crossings
developing action-relevant spatial information (3,8,9). Looking at the visual appearance of the
gaze-graph-defined landmarks, we found typical characteristics of landmarks including visual
saliency due to size, color or location in the city with a high variability in appearance between
the defined landmarks. For example, the house with the highest average node degree across
all participants is higher than most surrounding buildings and has a large distinct blue window
front that sets it aside from its surrounding suggesting its function as a global landmark (Fig.
6b,7b and Fig. 10a, 1). Additionally, it is located in the very center of the city making it visible
from most parts of the city. The house with the second highest average node degree across
all participants stood out due to its size regarding its surface area but not its height (Fig. 10a,

2). It was located next to the main road that connects the north and south part of the city,
even though it was only visibly in the south-east part of the city. This location at an important
crossing in the city for navigating might make it a local landmark with navigational relevance.
In general, most of the gaze-graph-defined landmarks were located next to crossings of main
roads in the city thus fitting a characteristic of local landmarks (3). It has to be considered that
our gaze-graph-defined landmarks had some inadvertent features even though we took care
in designing the virtual city to make all houses unique and varying in style, color and size (Fig.
10). The houses were placed randomly in the city without the intention of a city center and
city districts. Our results revealed that the gaze-graph-defined landmarks also had features of
global and local landmarks.
While it is undisputed that landmarks are important for spatial navigation, the details
about their functionality are not yet completely understood. Our results are in line with two
possible uses of fixated landmarks in agreement with previous research (2,4,5). Participants
could have fixated a single landmark to use it as either a beacon for goal directed navigation
or a visual cue for direction and orientation information (2,6,7). Looking at two landmarks
would allow triangulation. In contrast to trilateration, triangulation does not involve distance
measurements to the two reference points. Thus, only with knowledge of the base length, the
distance between the two reference points, explicit distances can be determined.
Nevertheless, triangulation is widely used in a multitude of applications, including spatial
navigation. Our investigation of a triangulation revealed that in 71.9% of the visited city area
at least one gaze-graph-defined landmark was viewed. Furthermore, in 39.1% of the city area
that was visited by participants and 50% of their experiment time, two or more gaze-graph-
defined landmarks were viewed. Thus, participants could have combined information from
viewing two or more landmarks from these locations. Multiple landmarks and knowledge of
their interrelations could serve as the basis for an allocentric representation of the
environment (2,4,10,11). This is supported by calculating the rich club coefficient of all gaze
graphs. Here, we found a correlation between increasing node degree and increasing
connectivity between the respective nodes. Gaze graph-defined landmarks were above
chance level visually interconnected to each other. Thus, the interconnected gaze-graph-
defined landmarks of the city seem to form a network, i.e., a rich club, covering a large, mostly
central part of the city. This could be a further indication that landmarks are not only used as
orientation anchors, but could form an underlying network of orientation anchors that span
out the framework of a mental map. Consequently, landmarks could anchor the mental map
and thus, serve as an important feature of survey knowledge.
804

Outlook & Conclusion

While the application of graph theory has enabled us to use a variety of already
established graph-theoretical measures to analyze the gaze graphs and resulted in very
promising results, only a small amount of the available graph-theoretical measures was
applied during our analysis. For example, the node degree centrality is defined as the sum of
connections of each node. Generally speaking, nodes with a lot of connections are likely to be

important for most networks (53) which is why the node degree centrality is widely used in
graph-theoretical analyses and serves as the basis of our gaze graph analysis (60). According
to Sporns (53), the usage of graph theory in neuroscientific studies has increased in the recent
years and the node degree centrality can be a useful measure for network analyses. However,
these analyses are mostly based on pairwise dyadic approaches and the full potential of graph
theory has not yet been applied.

A variety of graph measures is available for analyzing networks and node importance
can be defined in different ways, exceeding the node degree-based analysis. A particularly
important measure in social network analyses is the so-called betweenness centrality (61).
The measure counts how many shortest paths cross a particular node that is "between" a lot
of nodes. In social network analyses, betweenness centrality is beginning to replace the node
degree centrality to explain social network dynamics with respect to the importance of nodes
with high node betweenness for attracting and strengthening new links (62). Consequently,
the betweenness centrality could be a potential candidate for explaining spatial knowledge
acquisition. As mentioned, the centrality measure gains importance within the field of social
network analysis and is used to characterize the attraction and strengthening of connections.
A person, represented by a node in a social network, would have a high betweenness
centrality if the person connects a variety of other persons that themselves do not know the
connecting person. By transferring this thought to spatial navigation, a house with high
betweenness centrality would connect the views to two buildings that are not viewed in direct
succession themselves. Thus, this building serves as an anchor point for these two buildings
and forms a part of the route between them. Betweenness centrality could serve as a measure
for characterizing the gathered route knowledge. Overall, graph theory offers a variety of
different measures and has not yet reached its full potential within neuroscientific research.

Overall, our results establish a new methodology to process eye tracking data in
complex 3D environments and identify and assess the function of landmarks in spatial
navigation. Applying this methodology provides a new and unique insight into behavioral data
of visual attention processes during spatial navigation and opens the door for a novel
approach to investigate spatial navigation. To fully unlock the potential of graph theory, we
propose additional graph-theoretical measures to investigate gaze graphs in the future.
Specifically, we consider the betweenness centrality that could help to understand the
formation of spatial knowledge beyond landmark knowledge.

Methods

The virtual town of Seahaven

The virtual town of Seahaven was built to investigate spatial learning during free exploration
of the virtual environment and compare it to learning of a city map (34–36). Seahaven is a
fictional place and was created for the specific purpose of that experiment with the Unity
game engine using buildings, streets, and landscape objects acquired from the Unity asset
store. The city was designed as a connected urban space of roughly 216,000 m^2 (36). In total,

Seahaven contains 213 unique houses with individual appearance of style, shape and size (Fig.
10). The houses were randomly placed in the city to avoid typical city districts or clusters of
houses with outstanding features as well as avoiding a urban design with a city center and
surrounding suburbia areas (for more details see (34,35,63)). The street structure consisted
of winding and straight, small and big roads, and overall resembled a small European city. The
entire virtual environment reflects natural spatial relations, with one Unity unit corresponding
to one meter. The virtual height of the participant was set to 2 meters and was unified for
every participant. To provide a better frame rate in Unity, a far clipping plane in a distance of
160 meters was introduced. Consequently, no objects were visible to the participants that
were located further than 160m away from current participant location.
860

862 **Figure 10: Example buildings in Seahaven. a)** *The upper two rows show the ten houses*
863 *being labeled as gaze-graph defined landmarks. House 1 being the house with the highest*
864 *and house 2 with the second highest node degree.* **b)** *The lower two rows show ten other*
865 *randomly selected houses out of the remaining 203 houses that are located in Seahaven.*

Structure of the experiment

In total, 22 participants took part in the experiment for the present publication. The
experiment consisted of three repeated sessions within 10 days of the first session. Each
session consisted of five parts. First, participants received a brief introduction to the
experiment and signed the necessary paper work. In the second part, participants were
introduced to the type of spatial tasks they would need to complete after the exploration
session of the virtual city. The spatial tasks included judging the orientation of a house towards

north, judging the orientation between houses, and judging the direction between houses
using a pointing task. All tasks were performed in two response conditions (within 3 s and
infinite time) and designed as two alternative forced choice (2 AFC) tasks outside the virtual
environment. Participants were then asked to complete task examples with test stimuli using
photographs of houses of the city of Osnabrück. The third part was the setup of the
participants for the exploration of the VR environment. This consisted of the adjustment of
the VR-headset including the eye tracker and the calibration and validation of the eye tracker.
In the 1st session it was complemented by a movement training on a separate virtual island to
get participants accustomed to the possible movements in VR. In the fourth part, the main
experiment took place. Here, participants explored the virtual town for 30 minutes while
movements and eye tracking data were recorded. Participants were instructed to freely
explore the city as if they would explore a new real-world city for the first time. In the fifth
and final part of the experiment, participants performed the three spatial tasks (see above)
outside of the VR using images of houses of the virtual city Seahaven. A complete description
of the experimental procedures can be found in (49,56).

Laboratory setup

Participants wore a head mounted HTC Vive virtual reality headset and were seated on a
swivel chair. To prevent limitations on rotations as well as removing the tactile directional
feedback due to hanging cables, a vertical cable solution was implemented. Participants
moved using the HTC controller at walking speed. To decrease the risk of motion sickness,
participants were instructed to only walk forward with the controller. If they wanted to switch
directions or turn, they were instructed to stop walking and then rotate their entire body with
the chair in the desired direction.

Eye tracking

A pupil labs eye tracker (gaze accuracy 1.0°, gaze precision 0.08°) was directly integrated in
the HTC Vive headset (screen resolution: 1080 x 1200 pixels per eye (2160 x 1200 pixels
combined), screen refresh rate: 90 Hz, field of view: 110 degrees)(34). Both calibration and
validation were executed in the virtual reality while the participants where still on a separate
training island. For each participant, a 17-point calibration and a 9-point validation were
conducted until the validation error was below 2° (on average 1.53°). During the experiment,
a 1-point validation was performed every 5 minutes ensuring the correct tracking precision. If
the error exceeded 2°, a complete 17-point calibration and 9-point validation was performed
until the error was below the original threshold of 2° (mean 3.14°, median 2.11° before and
mean 1.88°, median 1.28° after a new calibration). 55% of all 1-point validations had a
validation error above 2° and had to be recalibrated, hence, highlighting the importance of
regular validation control. When the calibration and validation process was performed during
the exploration of Seahaven, the display of the virtual city disappeared until the process was
completed.

Graph Theory – detailed explanation of used graph measures

In the following, we describe the graph theory measures that are used in this publication on examples of simple networks.

Node degree centrality

The main measure of this publication is the node degree centrality. In the field of graph theory, the node degree gives the total number of connections (edges) of one node to any other node. An isolated node has a degree of zero. The maximal degree occurs when a node is connected to all other nodes, i.e., it acquires a node degree of the number of nodes in the graph minus one. When calculating the node degree centrality for every node in the network, the node degree distribution can give insights into the general connectivity of the network or to identify outliers i.e., nodes with extremely high or low node degree. For example, the node degree distribution of the graph shown in Fig. 11a has a mean node degree value of 3.82+/-1.8. Therefore, a 1-sigma distance to the mean at 5.62 and a 2-sigma distance to the mean at 7.42. We have one node with a degree larger than 7, which thus seems to be especially well connected. It can be examined as the only yellow node (Fig. 11b). Thus, it is rather fundamental and one of the most widespread used measures.

a. **b.**

Figure 11: Node degree – toy example. *(a) The node degree distribution of an example graph with similar distribution to the graphs used in the publication **(b)** The example graph with color-coded nodes according to their individual node degree defined by the number of edges that connects a node to other nodes.*

Graph partitioning

Partitioning investigates whether a graph can be considered as one connected graph or clearly distinguishable subgraphs. As an example, we applied the spectral partitioning approach to a graph shown in figure 12. It has two nearly fully connected subgraphs that are interconnected by two edges only (Fig. 12b). The spectral partitioning approach includes three

steps: the calculation of the graph's Laplacian matrix, finding the second smallest eigenvalue, and splitting the graph based on the corresponding eigenvector. First, we consider the adjacency matrix and the degree matrix of the graph. The former is a binary square matrix where each entry indicates whether an edge connects the two nodes / houses. The latter is a square matrix that contains the degree of each node on its diagonal and is zero otherwise. We calculate the Laplacian matrix by subtracting the degree from the adjacency matrix. Second, according to (41,42), the spectrum of a graph, i.e., the eigenvalues of the Laplacian matrix can be used as a measure of graph connectivity. We calculate these eigenvalues μ_i and sort them in ascending order. They have the properties that $\mu_1 = 0$ and $\mu_2 \geq 0$. If the graph is connected the second property holds strictly with $\mu_2 > 0$, which is the case in our analysis ($\mu_2 = 0.5858$). Third, we consider the eigenvector corresponding to the second smallest eigenvalue, the so-called Fiedler vector. It is an approximate solution to the optimization problem of finding the minimum cut that is the minimum number of connections that have to be cut to separate two clusters of nodes. When calculating the eigenvector of a graph's eigenvalue, each entry corresponds to a node of the graph. Thus, we map each node onto the corresponding entry of the Fiedler vector. Then we sort the adjacency matrix of the example graph according to the sorting index of the Fiedler vector (Fig. 12c). The color coding indicates the distinction into the two subsets with the two interconnecting edges plotted in black (note that there are 4 dots because the adjacency matrix is a symmetric matrix and each edge appears twice. The block structure is clearly visible and indicates clustering. The partitioning of the graph is performed by splitting of the Fiedler vector into positive and negative parts (Fig. 11c) and assigning the corresponding nodes to the two separate groups. The larger the gap between positive and negative values, the fewer inter-cluster connections are present.

Figure 12: Graph partitioning – toy example. (a) The sparsity pattern of the graph's

adjacency matrix sorted by its second smallest eigenvector. Color coded into edges between
nodes of one cluster (blue), edges between nodes of the other cluster (green), edges between
nodes of the two clusters (black) and a distinction between the clusters (yellow). **(b)** *The toy*
graph with two color coded clusters **(c)** *The second smallest eigenvector of the Laplacian*
matrix is sorted ascendingly and color coded into two clusters by division into positive and
negative components.
971

Hierarchy index

The hierarchy index characterizes hierarchical configurations within networks. More
specific, the hierarchy index describes how fast the frequency of nodes of certain degree drops
when increasing the degree. Here, we calculated the hierarchy index for an example graph
that was designed to have a hierarchical configuration, but is still similar to the Seahaven
graphs. Thus, it has a low number of nodes with a node degree of 1, a larger number of poorly
connected nodes with a node degree of 2 or higher, and a small number of highly connected
nodes (Fig. 13a, b). To calculate the hierarchy index, first individual degree values are plotted
against their frequency of appearance on a double logarithmic plot (Fig. 13c). Then, the data
points above the median of the degree distribution are linearly fitted (green line in Fig. 13c).
In our toy example the median 4 with a logarithm of 1.39. The hierarchy index is the negative
slope of this fitted line and for our toy example results in 2.40. Values above 1 are considered
a strong hierarchical configuration.

Figure 13: Hierarchy index – toy example. *(a) The node degree distribution of the example*
graph. (b) The example graph (c) A scatter plot of the logarithm of degree against the logarithm
of the frequency of occurrence. The green line shows the linear fit to the part of the data above
the median degree.
990

Rich club coefficient

The rich club coefficient investigates, whether high node degree nodes are
preferentially connected to each other, and, thus, form a rich club. Here, we designed the
example graph to have a dense core of 5 highly interconnected nodes and several low degree
nodes on the outside (Fig. 14b). Figure 14a shows the node degree distribution of the graph.
It is obvious that the five central high degree nodes have degrees of at least 5, while the rest
of the nodes have a degree below 4. The rich club coefficient is based on the relation of edges
in the graph in comparison to the number of possible edges that could be instantiated.
Therefore, the first step is the calculation of the number of edges of nodes with a node degree
of at least 1, i.e., all edges of the graph, and dividing it by the maximum possible number of
edges (see the rich club formula in result section 'The connections between the gaze-graph-
defined landmarks – The rich club coefficient'). Afterwards, the degree threshold of 1 is

increased to 2 and the number of edges of nodes with a node degree of at least 2 are divided by the maximum possible number of edges between those nodes. This procedure is repeated until there are no nodes left with the specified degree. However, to be able to interpret these connectivity values, we need a baseline. Therefore, we repeat the same procedure for a random graph that has the same degree distribution as the example graph. Figure 13c shows the rich club coefficient of the example graph divided by the rich club coefficient of a random graph with the same node degree distribution. In the low degrees, the adjusted rich club coefficient has a value of 1, which indicates that this subset of nodes is not preferably connected. However, with increasing degree, low degree nodes are excluded from the rich club calculation. Thus, an increasing slope with increasing degree indicates that the subset of high degree nodes is preferably connected within itself compared to a random graph with the same node degree distribution.

Figure 14: Rich club coefficient – toy example. *(a) The node degree distribution of the example graph. **(b)** The example graph with color-coded nodes according to their node degree **(c)** The adjusted rich-club coefficient, i.e., normalized using a random graph with similar node degree centrality statistics.*

Acknowledgments

We gratefully thank Viviane Clay and Nicolas Kuske for their assistance and support. In addition, we gratefully acknowledge the support by the GK Computational Cognition and the Open Access Publishing Fund of Osnabrück University.

Conflict of Interest Statement

The authors have declared that no competing interests exist.

Funding

The project was financed by the funds of the research training group Computational Cognition provided by the Deutsche Forschungsgemeinschaft (DFG), Germany (GRK2340).

Data Availability

All data files the described pre-processing and analysis are based on, are available at the Center for Open Science https://osf.io/aurjk/, DOI 10.17605/OSF.IO/AURJK.

All pre-processing, visualization and analysis scripts applied in this publication are available on our Github repository including an extensive documentation to allow full reproducibility: https://github.com/JasminLWalter/FindingLandmarks_a_publication_repository

In addition, we have archived the repository using Zenodo and assigned a persistent identifier to it: DOI: 10.5281/zenodo.5918548.

References

1. Kelly JW, McNamara TP. Spatial Memory and Spatial Orientation. In: Freksa C, Newcombe NS, Gärdenfors P, Wölfl S, editors. Spatial Cognition VI Learning, Reasoning, and Talking about Space. Berlin, Heidelberg: Springer Berlin Heidelberg; 2008. p. 22–38.

2. Chan E, Baumann O, Bellgrove MA, Mattingley JB. From objects to landmarks: The function of visual location information in spatial navigation. Front Psychol. 2012;3(AUG):304. doi:10.3389/fpsyg.2012.00304

3. Steck SD, Mallot HA. The role of global and local landmarks in virtual environment navigation. Presence Teleoperators Virtual Environ. 2000;9(1):69–83. doi:10.1162/105474600566628

4. Ekstrom AD, Isham EA. Human spatial navigation: representations across dimensions and scales. Curr Opin Behav Sci. 2017;17:84–9. doi:10.1016/j.cobeha.2017.06.005

5. Ekstrom AD, Spiers HJ, Bohbot VD, Rosenbaum RS. Human Spatial Navigation. Princeton University Press; 2018. doi:10.23943/9781400890460

6. Foo P, Warren WH, Duchon A, Tarr MJ. Do humans integrate routes into a cognitive map? Map- versus landmark-based navigation of novel shortcuts. J Exp Psychol Learn Mem Cogn. 2005 Mar;31(2):195–215. doi:10.1037/0278-7393.31.2.195

7. Baumann O, Mattingley JB. Medial Parietal Cortex Encodes Perceived Heading Direction in Humans. J Neurosci. 2010 Sep 29;30(39):12897–901. doi:10.1523/JNEUROSCI.3077-10.2010

8. Waller D, Lippa Y. Landmarks as beacons and associative cues: Their role in route learning. Mem Cogn. 2007;35(5):910–24. doi:10.3758/BF03193465

9. Mallot HA, Gillner S. Route navigating without place recognition: What is recognised in recognition-triggered responses? Perception. 2000 Jun 25;29(1):43–55. doi:10.1068/p2865

10. Klatzky RL. Allocentric and Egocentric Spatial Representations: Definitions, Distinctions, and Interconnections. In: Freksa C, Habel C, Wender KF, editors. Spatial Cognition. Berlin, Heidelberg: Springer Berlin Heidelberg; 1998. p. 1–17. doi:10.1007/3-540-69342-4_1

11. Mou W, Fan Y, McNamara TP, Owen CB. Intrinsic frames of reference and egocentric viewpoints in scene recognition. Cognition. 2008 Feb 1;106(2):750–69. doi:10.1016/J.COGNITION.2007.04.009

12. Morris RGM. Spatial localization does not require the presence of local cues. Learn Motiv. 1981 May 1;12(2):239–60. doi:10.1016/0023-9690(81)90020-5

13. McDonald RJ, White NM. Parallel information processing in the water maze: Evidence for independent memory systems involving dorsal striatum and hippocampus. Behav Neural Biol. 1994 May 1;61(3):260–70. doi:10.1016/S0163-1047(05)80009-3

14. Packard MG, McGaugh JL. Inactivation of hippocampus or caudate nucleus with lidocaine differentially affects expression of place and response learning. Neurobiol Learn Mem. 1996;65(1):65–72. doi:10.1006/NLME.1996.0007

15. Mueller SC, Jackson CPT, Skelton RW. Sex differences in a virtual water maze: An eye tracking and pupillometry study. Behav Brain Res. 2008 Nov 21;193(2):209–15. doi:10.1016/j.bbr.2008.05.017

16. Iaria G, Petrides M, Dagher A, Pike B, Bohbot VD. Cognitive strategies dependent on the hippocampus and caudate nucleus in human navigation: Variability and change with practice. J Neurosci. 2003 Jul 1;23(13):5945–52. doi:10.1523/jneurosci.23-13-05945.2003

17. Hamilton DA, Driscoll I, Sutherland RJ. Human place learning in a virtual Morris water task: Some important constraints on the flexibility of place navigation. Behav Brain Res. 2002 Feb 1;129(1–2):159–70. doi:10.1016/S0166-4328(01)00343-6

18. Andersen NE, Dahmani L, Konishi K, Bohbot VD. Eye tracking, strategies, and sex differences in virtual navigation. Neurobiol Learn Mem. 2012 Jan 1;97(1):81–9. doi:10.1016/j.nlm.2011.09.007

19. Newman EL, Caplan JB, Kirschen MP, Korolev IO, Sekuler R, Kahana MJ. Learning your way around town: How virtual taxicab drivers learn to use both layout and landmark

information. Cognition. 2007;104:231–53. doi:10.1016/j.cognition.2006.05.013

20.   Ishikawa T, Montello DR. Spatial knowledge acquisition from direct experience in the
environment: Individual differences in the development of metric knowledge and the
integration of separately learned places. Cogn Psychol. 2006 Mar 1;52(2):93–129.
doi:10.1016/j.cogpsych.2005.08.003

21.   Ishikawa T, Fujiwara H, Imai O, Okabe A. Wayfinding with a GPS-based mobile
navigation system: A comparison with maps and direct experience. J Environ Psychol.
2008 Mar 1;28(1):74–82. doi:10.1016/J.JENVP.2007.09.002

22.   Ohm C, Müller M, Ludwig B, Bienk S. Where is the Landmark? Eye tracking studies in
large-scale indoor environments. CEUR Workshop Proc. 2014;1241:47–51.

23.   Ohm C, Müller M, Ludwig B. Evaluating indoor pedestrian navigation interfaces using
mobile eye tracking. Spat Cogn Comput. 2017;17(1–2):89–120.
doi:10.1080/13875868.2016.1219913

24.   Kiefer P, Straub F, Raubal M. Towards location-aware mobile eye tracking. Eye Track
Res Appl Symp. 2012;313–6. doi:10.1145/2168556.2168624

25.   Kiefer P, Straub F, Raubal M. Location-Aware Mobile Eye Tracking for the Explanation
of Wayfinding Behavior. In: Gensel J, Josselin D, Vandenbroucke D, editors.
Proceedings of the AGILE'2012 International Conference on Geographic Information
Science. 2012.

26.   Kiefer P, Giannopoulos I, Raubal M. Where am i? Investigating map matching during
self-localization with mobile eye tracking in an urban environment. Trans GIS.
2014;18(5):660–86. doi:10.1111/tgis.12067

27.   Wenczel F, Hepperle L, von Stülpnagel R. Gaze behavior during incidental and
intentional navigation in an outdoor environment. Spat Cogn Comput. 2017;17(1–
2):121–42. doi:10.1080/13875868.2016.1226838

28.   Farran EK, Formby S, Daniyal F, Holmes T, Van Herwegen J. Route-learning strategies
in typical and atypical development; eye tracking reveals atypical landmark selection
in Williams syndrome. J Intellect Disabil Res. 2016;60(10):933–44.
doi:10.1111/jir.12331

29.   Hejtmánek L, Oravcová I, Motýl J, Horáček J, Fajnerová I. Spatial knowledge
impairment after GPS guided navigation: Eye-tracking study in a virtual town. Int J
Hum Comput Stud. 2018;116(May 2017):15–24. doi:10.1016/j.ijhcs.2018.04.006

30.   Kim JY, Kim MJ. Exploring visual perceptions of spatial information for wayfinding in
virtual reality environments. Appl Sci. 2020;10(10):1–15. doi:10.3390/app10103461

31.   Meilinger T, Frankenstein J, Bülthoff HH. Learning to navigate: Experience versus
1128   maps. Cognition. 2013 Oct 1;129(1):24–30. doi:10.1016/J.COGNITION.2013.05.013

1129   32.   Meilinger T, Frankenstein J, Watanabe K, Bülthoff HH, Hölscher C. Reference frames in
1130   learning from maps and navigation. Psychol Res. 2015 Nov 22;79(6):1000–8.
1131   doi:10.1007/s00426-014-0629-6

1132   33.   Ekstrom AD. Why vision is important to how we navigate. Hippocampus.
1133   2015;25(6):731–5. doi:10.1002/hipo.22449

1134   34.   Clay V, König P, König SU. Eye tracking in virtual reality. J Eye Mov Res. 2019 Apr
1135   5;12(1). doi:10.16910/jemr.12.1.3

1136   35.   König SU, Clay V, Nolte D, Duesberg L, Kuske N, König P. Learning of Spatial Properties
1137   of a Large-Scale Virtual City With an Interactive Map. Front Hum Neurosci. 2019 Jul
1138   10;13:240. doi:10.3389/FNHUM.2019.00240

1139   36.   König SU, Keshava A, Clay V, Rittershofer K, Kuske N, König P. Embodied Spatial
1140   Knowledge Acquisition in Immersive Virtual Reality: Comparison to Map Exploration.
1141   Front Virtual Real. 2021 Mar 3;2. doi:10.3389/frvir.2021.625548

1142   37.   Duchowski AT. Eye Tracking Methodology [Internet]. Third Edit. Eye Tracking
1143   Methodology. Springer; 2017. doi:10.1007/978-3-319-57883-5

1144   38.   Breitmeyer BG, Ganz L. Implications of sustained and transient channels for theories
1145   of visual pattern masking, saccadic suppression, and information processing. Psychol
1146   Rev. 1976 Jan;83(1):1–36. doi:10.1037/0033-295X.83.1.1

1147   39.   Reichle ED, Pollatsek A, Fisher DL, Rayner K. Toward a Model of Eye Movement
1148   Control in Reading. Psychol Rev. 1998;105(1):125–57. doi:10.1037/0033-
1149   295X.105.1.125

1150   40.   Nuthmann A, Smith TJ, Engbert R, Henderson JM. CRISP: A Computational Model of
1151   Fixation Durations in Scene Viewing. Psychol Rev. 2010 Apr;117(2):382–405.
1152   doi:10.1037/a0018924

1153   41.   Fiedler M. Algebraic connectivity of graphs. Czechoslov Math J. 1973;23(2):298–305.
1154   doi:10.21136/CMJ.1973.101168

1155   42.   Fiedler M. Laplacian of graphs and algebraic connectivity. Vol. 25, Banach Center
1156   Publications. 1989. p. 57–70. doi:10.4064/-25-1-57-70

1157   43.   Von Luxburg U. A tutorial on spectral clustering. Stat Comput. 2007;17(4):395–416.
1158   doi:10.1007/s11222-007-9033-z

44.   Fiedler M. A property of eigenvectors of nonnegative symmetric matrices and its

application to graph theory. Czechoslov Math J. 1975;25(4):619–33.

45.   Schaeffer SE. Graph clustering. Comput Sci Rev. 2007;1(1):27–64.
doi:10.1016/j.cosrev.2007.05.001

46.   Rodrigue J-P. The Geography of Transport Systems. 5th ed. Routledge; 2020. 480 p.

47.   Zhou S, Mondragón RJ. The rich-club phenomenon in the internet topology. IEEE
Commun Lett. 2004 Mar 21;8(3):180–2. doi:10.1109/LCOMM.2004.823426

48.   Van Den Heuvel MP, Sporns O. Rich-club organization of the human connectome. J
Neurosci. 2011 Nov 2;31(44):15775–86. doi:10.1523/JNEUROSCI.3539-11.2011

49.   Colombo D, Serino S, Tuena C, Pedroli E, Dakanalis A, Cipresso P, et al. Egocentric and
allocentric spatial reference frames in aging: A systematic review. Neurosci Biobehav
Rev. 2017 Sep 1;80:605–21. doi:10.1016/j.neubiorev.2017.07.012

50.   Chrastil ER, Warren WH. Active and passive contributions to spatial learning. Psychon
Bull Rev. 2012 Feb 15;19(1):1–23. doi:10.3758/s13423-011-0182-x

51.   Ehinger B V., Groß K, Ibs I, König P. A new comprehensive eye-tracking test battery
concurrently evaluating the Pupil Labs glasses and the EyeLink 1000. PeerJ. 2019;7:1–
43. doi:10.7717/peerj.7086

52.   Mondal B, De K. Overview Applications of Graph Theory in Real Field. Int J Sci Res
Comput Sci Eng Inf Technol. 2017;2(5):751–9.

53.   Sporns O. Graph theory methods: applications in brain networks. Dialogues Clin
Neurosci. 2018;20(2):111–20. doi:10.31887/DCNS.2018.20.2/osporns

54.   Singh RP. Application of Graph Theory in Computer Science and Engineering. Int J
Comput Appl. 2014;104(1):10–3. doi:10.5120/18165-9025

55.   Siegel AW, White SH. The Development of Spatial Representations of Large-Scale
Environments. Adv Child Dev Behav. 1975 Jan 1;10:9–55. doi:10.1016/S0065-
2407(08)60007-5

56.   Montello DR. A new framework for understanding the acquisition of spatial
knowledge in large-scale environments. Spat temporal Reason Geogr Inf Syst.
1998;143–54.

57.   Klippel A, Winter S. Structural Salience of Landmarks for Route Directions. In: Cohn
AG, Mark DM, editors. Spatial Information Theory. Berlin, Heidelberg: Springer Berlin
Heidelberg; 2005. p. 347–62. doi:10.1007/11556114_22

58. Srinivasan S, Hyman JD, O'Malley D, Karra S, Viswanathan HS, Srinivasan G. Chapter Three - Machine learning techniques for fractured media. Moseley B, Krischer L, editors. Vol. 61, Advances in Geophysics. Elsevier; 2020. 109–150 p. doi:10.1016/BS.AGPH.2020.08.001

59. Presson CC, Montello DR. Points of reference in spatial cognition: Stalking the elusive landmark. Br J Dev Psychol. 1988 Nov 1;6(4):378–81. doi:10.1111/j.2044-835x.1988.tb01113.x

60. Farahani F V., Karwowski W, Lighthall NR. Application of graph theory for identifying connectivity patterns in human brain networks: A systematic review. Front Neurosci. 2019;13(JUN):1–27. doi:10.3389/fnins.2019.00585

61. Diestel R. Graph Theory [Internet]. Fifth Edit. Axler S, Ribet K, editors. Graduate Texts in Mathematics. Berlin, Heidelberg: Springer Berlin Heidelberg; 2017. 49–64 p. (Graduate Texts in Mathematics; vol. 173). doi:10.1007/978-3-662-53622-3

62. Topirceanu A, Udrescu M, Marculescu R. Weighted Betweenness Preferential Attachment: A New Mechanism Explaining Social Network Formation and Evolution. Sci Rep. 2018;8(1):1–14. doi:10.1038/s41598-018-29224-w

63. König SU, Keshava A, Clay V, Rittershofer K, Kuske N, König P. Embodied Spatial Knowledge Acquisition in Immersive Virtual Reality: Comparison to Map Exploration. Front Virtual Real. 2021;2. doi:10.3389/frvir.2021.625548