NPOmix: a machine learning classifier to connect mass spectrometry fragmentation data to biosynthetic gene clusters

Authors: Tiago F. Leão[1,2], Mingxun Wang[1,3], Ricardo da Silva[4], Alexey Gurevich[5], Anelize Bauermeister[1], Paulo Wender P. Gomes[1], Asker Brejnrod[1], Evgenia Glukhov[6], Allegra T. Aron[1], Joris J. R. Louwen[7], Hyun Woo Kim[8], Raphael Reher[9], Marli F. Fiore[2], Justin J.J. van der Hooft[7,10**], Lena Gerwick[6], William H. Gerwick[1,6], Nuno Bandeira[1,3], Pieter C. Dorrestein[1,11,12,*].

Author Affiliations:
– Collaborative Mass Spectrometry Innovation Center, Skaggs School of Pharmacy and Pharmaceutical Sciences, University of California San Diego, La Jolla, California, USA.
– Center for Nuclear Energy in Agriculture, University of São Paulo, Piracicaba, Brazil.
– Center for Computational Mass Spectrometry, University of California San Diego, La Jolla, California, USA.
– NPPNS, Physic and Chemistry Department, School of Pharmaceutical Sciences of Ribeirão Preto, University of São Paulo, Ribeirão Preto, Brazil.
– Center for Algorithmic Biotechnology, St. Petersburg State University, St. Petersburg, Russia.
– Center for Marine Biotechnology and Biomedicine, Scripps Institution of Oceanography, University of California San Diego, La Jolla, California, USA.
– Bioinformatics Group, Wageningen University, Wageningen, the Netherlands.
– College of Pharmacy and Integrated Research Institute for Drug Development, Dongguk University, Gyeonggi-do, Korea.
– Institute of Pharmaceutical Biology and Biotechnology, University of Marburg, Marburg, Germany.
- Department of Biochemistry, University of Johannesburg, Johannesburg, South Africa.
– Center for Microbiome Innovation, University of California San Diego, La Jolla, California, USA.
– Departments of Pharmacology and Pediatrics, University of California San Diego, La Jolla, California, USA.

* Corresponding author.
** to whom correspondence should be addressed regarding the creation and management of the training data.

Preprint: https://www.biorxiv.org/content/10.1101/2021.10.05.463235.
Classification: Biological Sciences – Microbiology.
Keywords: genomics; mass spectrometry; machine learning; *in silico* predictions; specialized metabolites; biosynthetic gene clusters.

Author Contribution: T.F.L. conceptualized the software; T.F.L., R.d.S., and A.B (Asker Brejnrod) programmed the software; M.W. and A.G. assembled the metagenomic reads and annotated all biosynthetic gene clusters; A.B. (Anelize Bauermeister) and R.R. worked on the predicted fragmentation for brasilicardin A; P.W.P.G. matched the predicted structure to the fragmentation of promising candidates and created structural insights; T.F.L, J.J.J.v.d.H., and M.W. curated the dataset and verified the known BGCs-metabolites links; T.F.L, J.J.R.L., J.J.J.v.d.H., and A.G. compared the performance of our tool with other multi-omics tools; E.G. cultured cyanobacterial samples and collected the cyanobacterial LC-MS/MS data published at PoDP database; J.J.J.v.d.H., H.W.K., R.R., A.T.A, P.W.P.G., and A.B. provided feedback on the approach and how to present the results; T.F.L and J.J.J.v.d.H. wrote the manuscript; J.J.J.v.d.H., L.G., W.H.G, N.B., M.F.F., and P.C.D. funded and designed the research; L.G., W.H.G, N.B., M.F.F., J.J.J.v.d.H, and P.C.D. edited the manuscript; all authors read, reviewed, and agreed to the published version of the manuscript.

Abstract

Microbial specialized metabolites are an important source of and inspiration for many pharmaceutical, biotechnological products and play key roles in ecological processes. However, most bioactivity-guided isolation and identification methods widely employed in metabolite discovery programs do not explore the full biosynthetic potential of an organism. Untargeted metabolomics using liquid chromatography coupled with tandem mass spectrometry is an efficient technique to access metabolites from fractions and even environmental crude extracts. Nevertheless, metabolomics is limited in predicting structures or bioactivities for cryptic metabolites. Linking the biosynthetic potential inferred from (meta)genomics to the specialized metabolome would accelerate drug discovery programs. Here, we present a *k*-nearest neighbor classifier to systematically connect mass spectrometry fragmentation spectra to their corresponding biosynthetic gene clusters (independent of their chemical compound class). Our pipeline offers an efficient method to link biosynthetic genes to known, analogous, or cryptic metabolites that they encode for, as detected via mass spectrometry from bacterial cultures or environmental microbiomes. Using paired data sets that include validated genes-mass spectral links from the Paired Omics Data Platform, we demonstrate this approach by automatically linking 18 previously known mass spectra to their corresponding previously experimentally validated biosynthetic genes (i.e., via NMR or genetic engineering). Finally, we demonstrated that this new approach is a substantial step towards making *in silico* (and even *de novo*) structure predictions for peptidic metabolites and a glycosylated terpene. Altogether, we conclude that NPOmix minimizes the need for culturing and facilitates specialized metabolite isolation and structure elucidation based on integrative omics mining.

Significance

The pace of natural product discovery has remained relatively constant over the last two decades. At the same time, there is an urgent need to find new therapeutics to fight antibiotic-resistant bacteria, cancer, tropical parasites, pathogenic viruses, and other severe diseases. Here, we introduce a new machine learning algorithm that can efficiently connect metabolites to their biosynthetic genes. Our Natural Products Mixed Omics (NPOmix) tool provides access to genomic information for bioactivity, class, (partial) structure, and stereochemistry predictions to prioritize relevant metabolite products and facilitate their structural elucidation. Our approach can be applied to biosynthetic genes from bacteria (used in this study), fungi, algae, and plants where (meta)genomes are paired with corresponding mass fragmentation data.

Introduction

Microbial specialized metabolites are often made by biosynthetic genes that are physically grouped into clusters known as biosynthetic gene clusters (BGCs). Currently, the most common drug discovery methods utilize metabolomics but do not make use of genomics and, consequently, they cannot explore the full biosynthetic potential found in nature. In fact, it has very recently been estimated that metabolomics could only discover 3% of the bacterial biosynthetic potential so far (1). This percentage indicates the number of classes in the NPAtlas structure database (2) that corresponds to the predicted potential of the bacterial kingdom (over a million gene clusters known for encoding specialized metabolites), estimated by Gavriilidou and collaborators, 2022 (1). Additionally, the great majority of these metabolomics approaches rely on culturing and/or chromatographic isolation for bioactivity assays and structure elucidation. Recent advances in computational metabolomics and metabolome mining do also facilitate specialized metabolite discovery and characterization (3). However, the full elucidation of a structure of a metabolite is usually done via a set of 1D/2D nuclear magnetic resonance (NMR) experiments or X-ray crystallography, two techniques that are expensive and time-consuming. Genome mining would allow making accurate *in silico* predictions about the structure, bioactivity, and novelty of a given unknown metabolite from microbial cultures or even environmental microbiomes.

One of the challenges in the genome mining field is to connect microbial metabolites to their BGCs with confidence. Even the genome of *Streptomyces coelicolor* A3(2), one of the first sequenced microbial genomes, still contains a large number of cryptic BGCs – BGCs without known associated metabolites (4). In 2011, the bioinformatics tool antiSMASH (5) improved the identification and annotation of BGCs based on automated genome mining. AntiSMASH annotates BGCs by searching them with profile hidden Markov models of domains from gene/protein sequences known to biosynthesize metabolites and these models are specific to a certain class of BGC. We used antiSMASH to annotate all BGCs in this study. Moreover, since 2018, BiG-SCAPE (6) can reliably calculate the similarity between pairs of BGCs, grouping them into gene cluster families (GCFs). Recently, some approaches and tools have been created to connect specialized metabolites (known and cryptic MS/MS spectra) to their biosynthetic gene clusters, such as Pattern-based Genome Mining (7, 8), MetaMiner (9), DeepRiPP (10), NRPquest (11), NRPminer (12), GNP (13) and NPLinker (14), recently reviewed by Van der Hooft *et al.*, 2020 (15). Nerpa (16) and GARLIC (17) can connect structures to BGCs; structures are normally represented in the SMILES (Simplified Molecular-Input Line-Entry System) format, a type of computer-readable annotation language for chemical structures. However, most of these tools are neither high throughput, nor efficient, or can only be used for a particular class of BGC (e.g., peptides or BGCs homologous to known BGCs). It has been challenging to create a systematic tool that can work at the repository scale to connect genotypes (BGCs) with their phenotypes (for example fragmentation spectra, MS/MS spectra, from untargeted liquid chromatography coupled with mass spectrometry profiles, LC-MS/MS). As a result, a large disparity exists between the number of known metabolites from an organism versus the number of BGCs with known metabolite products. For example, the recently designated cyanobacterial genus *Moorena* has already yielded over 200 metabolites, yet only a dozen of validated BGCs are currently deposited for this genus in the expert-annotated Minimum Information about a

Biosynthetic Gene cluster (MIBiG) database (18). Connecting metabolites to their biosynthetic
genes would also facilitate research concerning the ecological role and functions of the
specialized metabolome by studying the regulation of the expression of their biosynthetic gene
clusters.
As an analogy, structure prediction for proteins is extremely challenging and a brute
force approach would take longer than the age of the universe to correctly predict a structure
of a single protein, an issue that was named "the protein structure problem". A similar problem
exists for metabolite discovery and these structures are key for mining novel and bioactive
specialized drug-like candidates (via docking or specific genes that already can be used to
indicate bioactivity). The deep learning algorithm named AlphaFold 2 (19) was able to use only
amino acid sequences to make protein structure predictions with over 90% precision and this
precision was considered (by the comparative modeling community) as enough to solve "the
protein structure problem". A part of the reason this problem could be solved was because
billions of dollars were spent in the past few decades to solve protein structures, whereas, in
contrast, training sets for genomes, metabolomes, and metabolite structure links are just
becoming available. So, one of the main questions is how we can begin solving the "metabolite
structure problem" and what algorithms are needed to do so? It is certainly a very challenging
task, but we believe that the first step toward it is to use the power of genomics for *in silico*
predictions by developing a tool that can efficiently connect known or cryptic metabolites
(detected via LC-MS/MS) to their correct BGC.
In silico predictions using raw DNA sequence and unlabeled mass fragmentation data
can be used to predict: bioactivity, either by gene content or docking experiments; full planar
structures, by dereplication, homology, or *de novo*; partial stereochemistry, and; novelty, based
on the abundance from all bacteria sampled from nature so far. For example, some random
forest classifiers by the Clardy lab (20) at Harvard medical center use only the BGC sequences to
predict with about 80% precision if a BGC will produce an anticancer, antifungal, or
antibacterial metabolite. Coelichelin was isolated using an *in silico* structure prediction that
indicated the peptide to be a siderophore, which was confirmed by culturing the producer in an
iron-deficient media and isolating the induced metabolite (overexpressed when compared to
the control). BiG-SLICE was used to predict the connections between more than 1 million BGCs,
providing clues to the most unique BGCs in thousands of samples.
To start addressing the above-mentioned "metabolite structure problem" and the gap
between genomics and metabolomics in drug discovery, we deployed a *K*-Nearest Neighbor
(KNN) algorithm that uses similarity BGC fingerprints and analogously similarity MS/MS
fingerprints to classify gene cluster family (GCF, a group of similar BGCs) candidates for each
MS/MS spectrum. We showed that the addition of biosynthetic class and substructure features
improves the performance of our Natural Products Mixed Omics tool (NPOmix, available at
https://www.tfleao.com/npomix1). While our approach uses unique fingerprints and machine
learning algorithms for connecting metabolites to BGCs, it can be considered a type of Pattern-
based Genome Mining which was previously reported by Doroghazi *et al.* in 2014 and Duncan
et al. in 2015 (7, 8). Pattern-based Genome Mining is based on the idea that the distribution of
a given natural product should be comparable to the distribution of the BGCs responsible for
their production. We would like to acknowledge that this approach is limited to organisms that
have BGCs (not all organisms have BGCs as well-defined as bacteria and fungi, for example,

higher plants and animals typically have less well-structured clusters of biosynthesis genes) and
to BGCs that are somewhat similar to at least one of the reference BGCs in the Paired Omics
Data Platform (PoDP)(21) datasets used by NPOmix. Benchmarked to eight other multi-omics
tools, NPOmix is the only currently available tool that is: i) scalable – it can run on a personal
laptop with 8GB of RAM and four cores for 550 metabolites in less than 4 hours, using over four
thousand genomic/metabolomic files; ii) systematic – it works for many different NP classes
(e.g., non-ribosomal peptides, polyketides, terpenes, and so on); and iii) highly efficient – its
maximum performance was markedly higher than the other tested tools with a 92.3% precision
during benchmarking (using a single nearest neighbor candidate and 22 validated BGCs-
metabolite links). Of note, in this study, six of the 11 BGC-metabolite links used for validation
(not counting analogs) were previously fully characterized via knockouts, heterologous
expression, and/or isolation, and unambiguous NMR structure elucidation as recorded at the
PoDP. The number of genomes, metabolomes, BGCs, GCFs, GNPS metabolites, metabolites with
MIBiG BGC, and BGC-metabolite links (with and without filtering) are listed in Table S1. The
major limitation of the evaluation of our method was the lack of available test data for
structures that are linked to their MS/MS spectra and biosynthetic gene clusters - a bottleneck
that the application of NPOmix can help to solve and we discuss more details in the
Supplementary Information, Background section. We believe that our NPOmix tool will assist
with the discovery of novel metabolites as well as known metabolites with new biosynthesis
(more details in the Supplementary Information Background).
192

Results

194
195 **Our proposed solution: the Natural Products Mixed Omics (NPOmix) approach.**
196
To enable *in silico* predictions of molecular novelty, bioactivity, and chemical structure,
metabolites need to be connected to their corresponding BGCs, a major challenge in the
metabolite discovery field that has been tackled by eight different approaches that are:
MetaMiner (9), DeepRiPP (10), NRPquest (11), NRPminer (12), GNP (13) and NPLinker (14)(that
includes Metcalf's co-occurrence-based Pattern-based Genome Mining and a standardized form
thereof)(7, 8), Nerpa (16) and GARLIC (17). However, i) none of these approaches are widely
used for drug discovery, and ii) genomics is often not included in drug discovery pipelines,
despite the numerous advantages of using paired genomics-metabolomics for *in silico*
predictions (as exemplified in the introduction). Therefore, we decided to leverage the power
of multidisciplinary expert knowledge (from a team including 2 molecular biology, 11
metabolomics, 1 genomics, and 5 multi-omics experienced researchers from around the globe)
and machine learning to create a high-performance KNN classifier to solve this issue. Our KNN
classifier named Natural Products Mixed Omics (NPOmix) can use just DNA sequences and
unlabeled mass fragmentation profiles to accurately create links between metabolites and their
corresponding biosynthetic gene cluster.
To use the NPOmix approach, it is required to have a paired dataset with genomic and
MS/MS information. Figure 1 shows a conceptual example using only four samples and only
using similarity as a feature. The genomic information can be either that of a genome or

metagenome and the MS/MS spectra should be obtained via untargeted LC-MS/MS. Paired
datasets have become available at the Paired Omics Data Platform (PoDP)(21), one of the first
initiatives to gather paired genomic and MS/MS information. Our analysis contained 3,331
BGCs (used for training) that were present in 1,040 networked genomes/metagenomes with
paired LC-MS/MS data that could be downloaded from the PoDP database.
We first used grouped known and cryptic BGCs in GCFs based on domain similarity using
BiG-SCAPE (6) to obtain labels that can be used for supervised learning (Fig. 1A). To create a
BGC fingerprint (Fig. 1C), we identified the similarity between the query BGC and each of the
BGCs in each genome in the training dataset (similarity scores are computed as "1 minus the
raw distance"). The BGC fingerprint that emerges is a series of columns for each compared
genome, the column value of which represents the similarity score between the query BGC and
the BGC to which it is maximally similar in each genome (column). Similarity scores range from
0.0 to 1.0; identical BGCs have perfect similarity and are scored as 1.0 whereas a score of 0.8
would indicate that a homologous BGC is present in the genome. A score below the (user-
defined) similarity cutoff of 0.7 indicates that the queried BGC is likely absent in the genome.
We selected the cutoff as 0.7 because it is the same cutoff used for BiG-SCAPE (6) similarity (a
value which was determined using a cutoff calibration with the MIBiG database)(22). An
analogous process is used to create MS/MS fingerprints (Fig. 1B and 1D); a query MS/MS
spectrum is compared to all of the MS/MS spectra in the query set. Furthermore, we add the
presence/absence of biosynthetic classes and substructures to the BGC and MS/MS fingerprints
(for more details, refer to the Methods section). We then use the BGC fingerprint in the training
together with the generated family labels. In more detail, the BGC fingerprints form a training
matrix (Fig. 1E, where each column is a genome and each value is the maximum similarity
between the query BGC and the BGCs in this given genome) and, in this case, the matrix
contains 1,040 columns due to the 1,040 sets of paired experimental samples plus the columns
corresponding to the biosynthetic class and annotated substructures.
The trained KNN classifier takes as input the same kind of features (MS/MS fingerprint,
Fig. 1D, and the testing matrix is exemplified in Fig. 1F, where the similarity is now represented
by the modified cosine score) but these features are annotated from individual mass
fragmentation profiles (known or cryptic metabolites). The aim of NPOmix is then to label these
MS/MS fingerprints with the proper gene cluster family, thus accurately linking metabolites to
their corresponding BGCs. The query MS/MS spectrum could be either a reference spectrum
from the Global Natural Products Social Molecular Networking database (GNPS) (23, 24) or a
cryptic MS/MS spectrum from a new sample that contains a sequenced genome and
experimental MS/MS spectra. In more detail, the KNN algorithm links BGCs to metabolites by
plotting the BGC fingerprints in the KNN feature space (in Fig. 1G). The KNN feature space is
exemplified by only two dimensions using dimension reduction techniques since a 1,040-
dimensional space is not feasible to comprehensively visualize (one dimension per sample).
More details of how this multidimensional plotting occurs are illustrated in Fig. S1, where the
samples correspond to the 3D axes and the similarity scores are the coordinates. Each query
MS/MS fingerprint (a row in the testing metabolomic matrix and columns are the experimental
MS/MS spectra per sample) is plotted into the same KNN feature space (Fig. 1G) so the
algorithm can obtain the GCF labels for the nearest neighbors to the query MS/MS fingerprint
(e.g., for three most similar BGC neighbors, k = 3). We note that GCF labels can be present more

than once in the returned list if two or more BGC nearest neighbors belong to the same GCF.
Given that many related BGCs are part of the same GCF, this repetition of the GCF classification
is a common behavior of our KNN approach.
In principle, our approach is suitable for bacterial (exemplified here), fungal, algal, and
plant genomes and MS/MS spectra obtained from the same organism (if these organisms
contain BGCs). Metagenomes and metagenome-assembled genomes (MAGs) can also be used
instead of genomes; however, complete genomes are preferred in the training set primarily due
to the expected data quality. This KNN approach also supports LC-MS/MS from fractions or
different culture conditions; multiple LC-MS/MS files for the same genome were merged into a
single set of experimental MS/MS spectra.
269

273
274
Fig. 1. The genomics and metabolomics pipelines use the proposed KNN approach for a hypothetical dataset with 4
paired genomes-MS/MS samples. Representation of how to calculate the similarity scores between BGCs
(displayed in A) and between MS/MS spectra (displayed in B). Schematic of how to create BGCs (C) and MS/MS (D)
fingerprints using a paired genomics-metabolomics dataset of four samples, i.e., genomes, metagenomes, or
MAGs (samples A-D) and similarity scores from BiG-SCAPE and GNPS. The dashed red line represents the selected
cutoff of 0.7. The query BGC is highly similar to a BGC in sample B (indicating an identical BGC), while it is probably
absent in samples A and C. The BGC fingerprints are grouped together in a training matrix and the MS/MS
fingerprints compose the testing matrix (F). All fingerprints are plotted in the multi-dimensional KNN space (G,
here represented in only 2D for simplification) where each circle represents a BGC fingerprint, and each X
represents an MS/MS fingerprint. BGCs are labeled according to one of the five GCFs (five differently colored
circles). KNN ranking of neighbors is based on the proximity between the query MS/MS fingerprint and the
neighboring BGC fingerprints. In this example, a KNN = 3 (three closest neighbors) is depicted. BGC = biosynthetic
gene cluster; MS/MS = mass fragmentation spectrum; KNN = K-nearest neighbor; BiG-SCAPE = software to
calculate pairwise BGC-BGC similarity; GCF = gene cluster family (group of similar BGCs); Cosine score = modified
cosine score from GNPS to calculate pairwise spectrum-spectrum similarity. For example, the blue circle shared
between X_1 and X_2 could represent a lipopeptide that shares the peptidic portion with other blue circles and a fatty
acid portion with the yellow circles or vice versa.

292
293

Validation and multi-omics dereplication: linking known metabolites to known BGCs,
validated links from the PoDP database and BGCs from the MIBiG database.

To validate our NPOmix approach, we used 36 out of 71 datasets from the Paired Omics
Data Platform (PoDP, from February 2021, datasets listed at Dataset S1, sheet one). There are
currently 75 datasets in the PoDP database. We selected genomic samples that contained a
valid Genome ID or BioSample ID to aid their downloading from the National Center for
Biotechnology Information database and totaling 732 genomes/MAGs obtained from these 36
meta-datasets. We also selected and assembled 1,034 metagenomes from two major
metagenomic datasets: 1) MSV000082969 and PoDP ID cd327ceb-f92b-4cd3-a545-
39d29c602b6b.1 – 556 cheetah fecal samples and environmental samples (23); 2)
MSV000080179 and PoDP ID 50f9540c-9c9c-44e6-956c-87eabc960d7b.3 – The American Gut
Project (24) that contains fecal samples from 481 human subjects. These (meta)genomes were
downloaded with the code shared at the GitHub repository
https://github.com/tiagolbiotech/NPOmix, notebook 1. The LC-MS/MS files can be downloaded
using "FTP" from links recorded in Dataset 1, sheet two. We were able to network 1,040
(meta)genomes that contained 3,331 BGCs (including 260 BGCs from the MIBiG database)
distributed into 997 GCFs. In the untargeted metabolomics data, we matched 3,248 LC-MS/MS
files to 22 GNPS (13, 25) reference library MS/MS spectra and one spectrum not available at
GNPS (brasilicardin A, obtained from the microbial metabolome) to create the MS/MS
fingerprints for testing the KNN classification (one fingerprint per spectrum). We envision to
create a more balanced, diverse, and less sparse training dataset in ongoing efforts. To
maximize precision rates in the future, we plan to purchase cultures from collections that have
well-assembled genomes so we can obtain the paired LC-MS/MS. However, the current dataset
produced highly supportive results by testing validated links from the PoDP, links generated by
the Gerwick lab dataset, and semi-manually connected links used in the NPLinker publication,
all of which will be reused for posterior benchmarking of BGC-MS/MS linking algorithms. We
attempted to test all 242 BGC-metabolite links used as training data for the Rosetta scoring
method in NPLinker (totaling 2,069 unique MS/MS spectra, Dataset S1, sheet two) plus 109
manually added MS/MS links (connected to BGCs, annotated by experts at the PoDP, Dataset
S1, sheet three). However, most of these validated MS/MS spectra were not present in the
1,040 paired (meta)genomes-MS/MS samples from the PoDP or their BGC scores did not co-
occur with their MS/MS scores because they were not present in the nearly exact same
samples. To further illustrate this, 178 MIBiG BGCs networked with PoDP BGCs and 50 GNPS-
annotated metabolites were reported at PoDP. The intersection of these two resulted in 22
BGC-metabolite links including analogs. You can see these and other metrics in Table S1.

Hence, our validation dataset was limited to 11 validated links (22 with analogs) from
the MIBiG and PoDP databases and found in the paired (meta)genomes-MS/MS samples
(barbamides, antimycin, pyocyanines, 2,4-diacetylphloroglucinol, brasilicardin A, orfamides,
albicidins, bafilomycin B1, nevaltophin D, jamaicamides and cryptomaldamide, totaling 22
references MS/MS spectra that were present in the GNPS database). We only included analogs
for which the MIBiG BGC was present in our paired samples downloaded from the PoDP; hence,
we included orfamide A-C but not orfamide E, F and so on (because they are not reported as
products from the MIBiG orfamide BGCs). We stress that a larger training dataset with more

complete genomes is likely to increase the size of the validation set by adding more valid BGCs
into the analysis. We were also able to combine NPOmix with *in silico* metabolomics tools like
Dereplicator+ (20) to make new links between MS/MS spectra, BGCs, and molecular structures,
as we will exemplify by brasilicardin A. This was accomplished by annotating cryptic MS/MS
spectra (without a GNPS library hit and therefore not present in the GNPS database) to known
BGCs (found in the MIBiG database). Such new links could be confirmed experimentally to
improve the size of the validation set, as well as to expand MS/MS databases by adding these
cryptic spectra to them.
A two-dimensional comparison of both types of fingerprints (BGC and MS/MS) can be a
proxy for distinguishing some true positives from false positives. As observed in Fig. S2, we can
visualize a mismatch between the BGC fingerprints (one GCF) and the MS/MS fingerprint in the
"reduced" KNN-space (represented schematically in only two dimensions), indicative of a
possible false positive link. This GCF is dereplicated as the known metabolite, pyocyanin, and it
was incorrectly associated with the metabolite 2,4-diacetylphloroglucinol, confirming the false
positive (at k = 3). In contrast, Fig. 2 illustrates that 5 metabolites, albicidin (structure in Fig. 2A
and MS/MS spectra in Fig. 2B) and four albicidin analogs, could be correctly assigned to their
corresponding GCF that contains 2 BGCs (one from the MIBiG database and another from
Xanthomonas albilineans GPE PC73, GenBank ID GCA_000087965.1). In this case, the BGC
fingerprints match the MS/MS fingerprints (Fig. 2C and 2D). This observation of "co-
occurrence" between the strains in the BGC fingerprint and MS/MS fingerprints can be
quantified by the Jaccard index (a score ranging from zero to one and calculated by the
intersection of the presence/absence between the strains in fingerprints over the total number
of strains).
Using the PoDP dataset, a Jaccard index cutoff of 0.7 and similarity plus biosynthetic
class as features for the machine learning model, we obtained a precision of 92.9% as 13 out of
14 references MS/MS spectra were correctly labeled when top-n = 3 (k nearest neighbors equal
to 3, metabolites and their predicted GCFs listed in Table 1). Top-n represents how often the
correct GCF label was found among the top n labels classified by the KNN approach. We have
determined that the use of three neighbors is the optimal performance (also using the co-
occurrence threshold), providing a good balance between precision and the number of links to
validate (very high precision and randomness equal to 0, as detailed in Table S2). Randomness
is observed by shuffling the testing columns, experimental MS/MS names, and counting how
many correct links are present between the top-n GCF candidates. Lastly, we regard our
NPOmix approach as multi-omics enabled dereplication (or *in silico* structure prediction by
homology) because the 13 MS/MS spectra were automatically assigned to a known GCF that
confirmed their metabolite labels, thereby minimizing the need for purchasing standards,
performing isolation and NMR characterization, gene knockout or heterologous expression.
This kind of multi-omics analysis allows to dereplicate more metabolites than genomics or
metabolomics separately and it helps researchers to focus on novel structures that can also
present novel bioactivities.
We expect that our approach will improve with a larger training set and with further
improvement of the features in the BGC and MS/MS fingerprints (e.g., by adding BGC
regulation and predicted bioactivity). We confirmed that all 13 correct GCF predictions reported
here were found in the original producer of the identified metabolites, they matched the

reported masses and most of these BGC-metabolite links were reported at the PoDP as
validated via knockouts, heterologous expression, and/or isolation and NMR structure
elucidation. NPLinker (14), another recently published paired-omics tool, also uses validated
links from the PoDP to assess linking precision scores. With 50 known GCF-MS/MS links that
were present in the 1,040 samples with paired data (some metabolites have multiple MS/MS
spectra), the annotation rate was reasonably good (around 28%, 14 out of 50 links were
retained after the Jaccard co-occurrence threshold, a threshold to keep only the metabolites
that are found among the same samples that contain the candidate BGCs). Table S1 provides an
overview of the various numbers of genomes, metabolomes, BGCs, metabolites, etc.
391

392
Fig. 2. Multi-omics enabled the dereplication of albicidin by automatically predicting a true BGC-metabolite link.
Structure of the dereplicated metabolite (A) and its corresponding representative MS/MS spectrum (B, spectrum
example from GNPS ID CCMSLIB00000579285 and *m/z* of 843.2700), obtained via Metabolite Spectrum Resolver
(26). The two BGC fingerprints (1130 and 1131) are represented in a 2D plot (C) and they match the 2D plot for the
5 MS/MS fingerprints obtained from GNPS for albicidin and its analogs (D). BGC = biosynthetic gene cluster;
MS/MS = mass fragmentation spectrum; *m/z* = mass over charge calculated via mass spectrometry.
399
400

Table 1. 14 links between GNPS MS/MS spectra (with metabolite ID) and networked gene cluster family (true GCF
that contained a known MIBiG BGC and passed the co-occurrence threshold). The table also includes their KNN
predictions (*k* = 3); the predicted GCFs are ordered according to the value for *k*, from 1 (nearest) to 3 (furthest),
and the first correct family is marked in bold red font. GCF labels can be repeated because multiple BGCs from the
same GCF can be predicted as the nearest neighbors. Classification is considered correct if the true GCF is among
the top-3 candidates. Annotations are according to each MIBiG BGC(s) found in the true GCFs. GNPS = Global
Natural Products Social Molecular Networking database; KNN = *K*-nearest neighbor; MS/MS spectra =
fragmentation spectra; BGC = biosynthetic gene cluster; GCFs = gene cluster family; MIBiG = Minimum Information
about a Biosynthetic Gene cluster database; * = new analogous MS/MS spectra that were automatically connected
to validated BGCs.

Metabolite ID	True GCF	Predicted GCFs for *k* = 3	Annotation
CCMSLIB00004679298	GCF450	GCF360, **GCF450**, GCF360	Orfamide A*
CCMSLIB00004679299	GCF450	GCF360, **GCF450**, GCF360	Orfamide B*
CCMSLIB00004679300	GCF450	GCF360, **GCF450**, GCF360	Orfamide C*
CCMSLIB00000001573	GCF468	**GCF468**, GCF468, GCF235	Barbamide
CCMSLIB00000001575	GCF468	**GCF468**, GCF468, GCF235	Barbamide
CCMSLIB00000001706	GCF471	**GCF471**, GCF498, GCF550	Jamaicamide A
CCMSLIB00000001708	GCF471	**GCF471**, GCF498, GCF550	Jamaicamide C
CCMSLIB00000579285	GCF476	**GCF476**, GCF219, GCF235	Albicidin
CCMSLIB00004681475	GCF476	**GCF476**, GCF219, GCF235	Propionyl-albicidin
CCMSLIB00004681481	GCF476	**GCF476**, GCF219, GCF235	Beta-methoxy-albicidin
CCMSLIB00004681486	GCF476	**GCF476**, GCF219, GCF235	Carbamoyl-ß-methoxy-albicidin
CCMSLIB00004681487	GCF476	**GCF476**, GCF219, GCF235	Carbamoyl-ß-methoxy-asn-albicidin
CCMSLIB00000840594	GCF488	GCF740, GCF740, GCF739	Nevaltophin D
CCMSLIB00005724004	GCF498	GCF471, **GCF498**, GCF550	Cryptomaldamide

412
413

Dereplicating a new analogous MS/MS spectrum (with a library hit from GNPS but not found at the PoDP database) to a known BGC and accurately predicting its full *in silico* structure.

In addition to dereplicating known metabolites (from the GNPS and/or the PoDP database), NPOmix can also dereplicate new putative analogs (orfamides marked by asterisks in Table 1). For example, the BGC for the metabolite orfamide C (genes 1-6 in Fig. S3, MIBiG ID BGC0000399) was automatically connected by our KNN approach (both using only similarity as a training/testing feature or by adding the biosynthetic class) to a GNPS metabolite labeled "putative orfamide C" (CCMSLIB00004679300). This MS/MS spectrum was also found in the same strain where the BGC was first identified (*Pseudomonas protegens* Pf-5, Genbank ID GCA_000012265)(27). The nine amino acid (AA) predictions for this BGC, based on the specificity of adenylation domains, match the structure for orfamide C in the correct order: leu, asp, thr, ile, leu, ser, leu, leu, and ser. AntiSMASH was not able to predict the tenth and last AA in the biosynthetic series, although, the mass difference between the partial structure and the experimentally observed *m/z* pointed that the last AA was indeed valine. The matching between the predicted structures (via dereplication versus *de novo* prediction using the NPOmix link) confirmed the multi-omics enabled dereplication of this "putative orfamide C" (using *k* = 3, BGC predictions and predicted metabolite structure are represented in Fig. S3), annotating this metabolite without the need for isolation. We would like to stress that this version of the KNN GCF predictions did not use structures/substructures for linking MS/MS spectra to BGCs; hence, as demonstrated in Fig. S3, substructure predictions can be an extra dimension for selecting links that are true positives over false positives.

Connecting a cryptic/new MS/MS spectrum (not present in the GNPS database) to a known BGC (validated link from the PoDP database).

We used a combination of MS/MS fingerprints (notebook 2 from https://github.com/tiagolbiotech/NPOmix), BGC fingerprints (notebook 3), Mzmine (28), Dereplicator+ (29) to link and dereplicate brasilicardin A. After selecting 300 MS/MS spectra from the 16 most diverse genomes in the dataset (diversity estimated using GCF presence/absence) of 1,040 samples, Dereplicator+ had three *in silico* metabolomics predictions and one of them was the unique tricyclic glycosylated terpene brasilicardin A. The observed *m/z* matches the value previously reported in the literature)(30), identifying an MS/MS spectrum that is currently absent from the GNPS database. NPOmix connected the MS/MS spectrum (predicted to be brasilicardin A by Dereplicator+; please note that this information was not used during the NPOmix training) with the correct BGC (brasilicardin A MIBiG ID BGC0000632 from the strain *Nocardia terpenica* IFM 0406, GenBank ID GCA_001625105)(31), highlighting how NPOmix can connect cryptic metabolites without library matches (absent from MS/MS databases like GNPS) to their corresponding BGCs. Predicted fragmentation (Fig. S4) strongly suggested that the query MS/MS spectrum is corresponding to the planar structure of brasilicardin A (all deltas between fragmented exact *m/z* and observed *m/z* were extremely low, below 0.001, more information in Dataset S1, sheet four). Thus, NPOmix can provide links between cryptic MS/MS spectra and known/cryptic BGCs from the most diverse strains and potentially new BGCs that can be explored experimentally (e.g., BGC

knock-out, heterologous expression, or isolation and NMR structure elucidation), especially if
coupled to SMART-NMR analysis (32) to confirm their novelty. We observed that this
compound was not in GNPS but it was already validated (via "knockouts, heterologous
expression, or other gene cluster manipulation", information at the dataset 1b0dccac-5212-
4dfd-a9f2-6fa953ab16bd.5) and deposited in the PoDP database (same *m/z*, LC-MS/MS
metabolome and retention time).
464
465 **Comparing the three different kinds of structural features for linking metabolites to BGCs**
466 **using NPOmix.**
467
In order to increase the precision of our NPOmix algorithm, we added to the BGC and
MS/MS similarity fingerprints the presence/absence of biosynthetic classes (polyketide
synthases, nonribosomal peptide-synthetases, terpenes, siderophores, ribosomally synthesized
and post-translationally modified peptides, phosphonates, oligosaccharides, phenolic
metabolites, others/unknowns, other minor classes, and combinations of more than one class)
and substructures (tyrosine, proline, amine, malonyl-CoA, and so on - all 85 predicted
substructures can be found at Dataset S1, sheet five). A comparison of the various models is
provided in Figure 3, with Fig. 3A without using the co-occurrence threshold, and Fig. 3B with
use of the co-occurrence threshold.
The comparison of the different features for running NPOmix is exhibited in Fig. 3, using
the same set of samples previously described (1,040 paired samples and 22 validated BGC-
metabolite links). As observed in the figure, the Jaccard co-occurrence threshold (a threshold to
ensure that the query metabolite is connected to BGCs in the genome of the same microbial
producer) substantially improved the precision scores, but it dropped the number of validated
links from 22 to around 14 (these links are listed in Table 1). However, we obtained great scores
even without threshold (Fig. 3A), for example, 81.8% for k = 5 using the three kinds of features
(similarity, biosynthetic class, and substructure prediction) or just similarity and substructure
features. Interestingly, we observed a slightly higher precision for k = 1 when only the
substructures and similarity features are used in opposed to using all three kinds of features
(without threshold); this is because the biosynthetic class for pyocyanines at MIBiG (used for
manual annotation of the MS/MS spectrum) are annotated as "other" but antiSMASH
automatically annotates its corresponding BGCs as "minor" and in some cases as both "minor"
and "NRPS", creating a mismatch between the biosynthetic classes. Additionally, we
summarized KS domains and PKS substrates in only two columns (one for each) but we
obtained the same precision scores. We elected the best precision score as 92.9% (red dot in
Fig. 3B, score with co-occurrence threshold) because this very high value was obtained using
only the similarity and the biosynthetic class features and three nearest neighbors, a good
number of candidates for genome mining. Moreover, the use of just the similarity and
biosynthetic class is very appealing because these kinds of features can be well predicted for
metabolites with known or unknown metabolites, for example by using GNPS for similarity and
CANOPUS and/or MolNetEnhancer for biosynthetic class predictions, as demonstrated by
NPClassScore (33). It is much more challenging to predict substructures for unknown/cryptic
metabolites, which is a topic of ongoing research by our group and others.

Fig. 3C, if a given BGC is a hybrid polyketide synthase (PKS) and nonribosomal peptide-
synthetase (NRPS), it was annotated as 1 in the PKS and NRPS columns, and with a 0 in the
remaining classes (additional columns). Analogously to the biosynthetic classes, each
substructure prediction represented a new column in the BGC fingerprint or MS/MS
fingerprints, and the columns were filled with 1 (if the substructure was present) and 0 (if the
substructure was absent). For the MS/MS fingerprints in the testing set, we manually annotated
these biosynthetic class features based on the known structures and MIBiG information. In
cases where the structure is unknown, tools like CANOPUS (34) and MolNetEnhancer (35) can
provide a similar biosynthetic class prediction relying on NPClassifier (36). For the substructure
features in the MS/MS testing set, we used antiSMASH to annotate substructures for a BGC
from the same GCF as the validated MIBiG BGC. In cases where the BGC is unknown, these
predictions can be obtained: manually (by checking the known structure for common
substructures); via unsupervised tools like MS2LDA (37), or; via supervised tools like MassQL
(based on specific MS/MS fragments found in the spectra, manuscript in preparation) or
CSI:FingerID/SIRIUS 4 (38). For example, we manually annotated the substructures predicted
from the palmyramide A structure and we were able to correctly link the validated MS/MS
spectrum with the corresponding palmyramide A BGC. This BGC is not yet published at MIBiG,
but the biosynthetic gene cluster was previously annotated and reported in *Moorena*
producens PAL (39), and in this study, the same genome, LC-MS/MS metabolome, and MS/MS
spectral data were used to obtain this BGC-metabolite correlation.
521
522

Fig. 3. A) Precision curves without the Jaccard co-occurrence threshold for different features: similarity only (blue),
biosynthetic class and similarity (green), substructure predictions and similarity (brown), and using both
biosynthetic class, substructure predictions, and similarity (pink). B) Precision curves for the same cases using the
co-occurrence threshold. Random (yellow) was calculated by using similarity only and shuffling the testing
columns. The red dot indicates the best precision of 92.9% (using biosynthetic class and similarity as features, co-
occurrence threshold, and *k*=3). *K* represents the number of nearest neighbors. C) we illustrate the modifications
made in the training matrix with the addition of biosynthetic class and substructure prediction. For this work, we
used 1,040 samples, therefore, 1,040 similarity columns plus 12 biosynthetic classes and 82 predicted
substructures.

How well can we predict *de novo* structures from NPOmix links?

As observed by the four examples in Fig. 4, structural prediction can be very successful using multi-omics for peptidic metabolites without using library hits (the metabolite annotation such as orfamide C, and structure, was not provided in the training data for NPOmix); however, in some cases (like unusual amino acids in albicidin), it can be very difficult. We also showed that these *de novo* predictions are feasible to other classes, like the glycosylated terpene brasilicardin A (Fig. 4). Nonetheless, it is more challenging to predict the final structure (e.g., cyclization of the isoprene units in a diterpene) if compared to peptidic metabolites. As previously mentioned, we were able to correctly predict (*in silico* and *de novo*) the full structure for a new orfamide C MS/MS spectrum, including parts of its stereochemistry. This shows that NPOmix not only can dereplicate new MS/MS spectrum very efficiently, but it can also make very accurate predictions for cases where we did not use the library hits (in the MIBiG and/or GNPS databases). In other cases, we could only predict partial structure, as demonstrated by cryptomaldamide (85.7% correctly predicted), palmyramide A (66.6% correctly predicted), brasilicardin A (55.5%), and albicidin (29% correctly predicted). However, developments in the antiSMASH algorithm and the use of MassQL can almost certainly improve these predictions. With MassQL (a tool data uses query language to find patterns in the MS2 data), specific mass spectral peak patterns that correspond to class-defining substructures or scaffolds can be mined from LC-MS/MS datasets (manuscript in preparation). Of note, we are mostly showing peptidic metabolites as examples because antiSMASH is currently better trained in predicting core structures from this biosynthetic class; nonetheless, we plan to expand this approach to other classes in the future, building on improvements in the genome mining field. Additionally, peptides are known for being bioactive (for example, orfamides and albicidins were reported as antifungal and the latter metabolite family was also reported as antibacterial), and they are likely the most abundant biosynthetic class in nature (accounting for 45% of the currently available BGCs at the antiSMASH database that contains over 82,000 BGCs)(40). Therefore, NPOmix links can already be used to explore environmental samples and make interesting *in silico* predictions about the structure and bioactivity of naturally occurring peptides.

Metabolite, strain and class:		% of correct structural prediction and its difficulty:
Orfamide C *Pseudomonas protegens* Pf-5 NRPS-like		89/89 total excluding H atoms (100.0%) Very straight-forward
Cryptomaldamide *Moorena producens* JHB NRPS		24/28 total excluding H atoms (85.7%) Average difficulty
Palmyramide A *Moorena producens* PAL PKS-NRPS		32/48 total excluding H atoms (66.6%) Fairly difficult
Brasilicardin A *Norcadia terpenica* IFM0406 Glycoterpene		35/63 total excluding H atoms (55.5%) Fairly difficult
Albicidin *Xanthomonas albilineans* GPEPC73 PKS-NRPS		18/62 total excluding H atoms (29.0%) Extremely difficult

Red = not predicted or incorrectly predicted

Fig. 4. NPOmix automatically connected MS/MS spectra annotated with library hits to their peptidic MIBiG BGC (exemplified by orfamide C, cryptomaldamide, palmyramide A and albicidin), however, we did not use library hits for structure prediction. The figure illustrates the matches between the correctly predicted portion of the structures (atoms in black) versus the incorrectly predicted (substructures in red). We counted all atoms except for hydrogens (H). These predictions via antiSMASH used the BGC's amino acids (AA) specificities and the PKS domains present in each investigated BGC. We would like to emphasize that these *in silico* predictions did not use the library annotations (obtained via dereplication or from the PoDP database) and, therefore, they are *de novo* predictions. In the structure of orfamide, only one AA (the last valine in the biosynthesis) out of 10 AA could not be predicted by the BGC annotation tool (antiSMASH), however, this valine residue was suggested by the *m/z* mass difference. In albicidin, unusual AAs are more difficult to predict than canonical AAs, leading to a lower number of

583 correctly predicted atoms. BGC = biosynthetic gene cluster; AA = amino acid; H = hydrogen; PKS = polyketide
584 synthase; NRPS = nonribosomal peptide-synthetase.
585
586 **Comparing the performance of NPOmix with other published tools.**
587
We used the same previously described dataset of 1,040 paired samples that includes
22 validated BGCs-metabolites links to compare precision scores (same links used in the
calculation of the precision scores in Fig. 3) to other 8 multi-omics (tools and their websites are
listed in Table S3). For the tools that do not have a training step, we selected from the 1,040
paired samples only the ones that contained at least one of the 22 BGCs-metabolites validated
links, a total of 9 paired samples. We compared NPOmix to NRPminer (12) and NPLinker (14),
the other currently available tools that create links between MS/MS data and BGCs. NPLinker
includes the correlation scores first developed in the Pattern-based Genome Mining
publications (7, 8) and derivatives thereof. GNP (13) and NRPquest (11) seem to be
discontinued (see Table S3 for further details).
MetaMiner (9) and DeepRiPP (10) could not be used in the comparison because,
unfortunately, there are no ribosomally synthesized and post-translationally modified peptides
(RiPPs) among the 22 links in our validation set. As far as we can tell, there are only two
validated RiPPs in the entire PoDP database: capistruin C and polytheonamide A-B. However,
neither of the two were available for our validation test (more details in the Supplementary
Information, Results section). Under these circumstances, we did not test RiPP BGC-metabolite
links, and we could not measure the performance of MetaMiner and DeepRiPP for this
validation set, however, we tested both for the full metabolomes and genomes of these 9
validation strains. In this test, MetaMiner annotated zero matches, despite the presence of 49
uncharacterized RiPP BGCs in the 9 genomes. DeepRiPP "failed to load results", even though
the input data was correctly processed by other tools. On top of testing tools that connect mass
spectrometry fragmentation data to BGCs, we also tested Nerpa (16) and GARLIC (17) which
can connect structures (SMILES strings) to BGCs.
Fig. 5 is a histogram illustrating the performance of these tools, including the two best
versions out of eight versions of NPOmix displayed in Fig. S5 (four with and four without co-
occurrence threshold). Fig. S6 exemplifies how fragmented BGCs can lead to scores below the
threshold. More details on the Fig. S5 and S6 in the Supplementary Information, Results
section. We note that we did not observe differences in NPLinker results using the standardized
Metcalf score, the Rosetta score or both together. We selected top-1 accuracy to represent the
precision scores since some tools only provide a single BGC candidate per metabolite tested. In
theory, NRPminer and Nerpa should be able to test four links that are nonribosomal peptides
(three orfamides and nevaltophin D) plus eleven additional hybrids between nonribosomal
peptides and polyketides (two barbamides, five albicidins, two jamaicamides,
cryptomaldamide, and antimycin). However, NRPminer could only generate predictions for four
of these peptidic metabolites in the validated set (one incorrect and three correct links) and
Nerpa only predicted three metabolites that were correctly linked to their BGCs. GARLIC can
test all but four links (three pyocyanines and brasilicardin A) since it should work for
nonribosomal peptides, polyketides, and hybrids. We were unable to compile GRAPE (tool
required to use GARLIC) and we found an unanswered issue on their GitHub page with that

same question, as well as another issue from 2016 that is left unanswered, thus it seems that
this tool is also no longer supported or discontinued.
NPLinker is systematic (it does not depend on the BGC/metabolite class) and, just like
NPOmix without threshold, it can test all links. For all tools, we used standard settings
(commands found in the notebook "NPOmix_SI-installation_and_running", GitHub repository
https://github.com/tiagolbiotech/NPOmix); and we note that for these analyses we did not
attempt to optimize settings and scores of the various tools but used their (recommended)
default settings. We also note that the use of a relatively small number of strains for the
NPLinker benchmarking purposes (9 strains), it is likely that the correct links are part of a longer
list of possible matches based on their co-occurrence score and that several links have the same
score. Hence, the correct match may not be in the top-1 rank if we do not consider a shared
rank (for example, from the second to the tenth position, if all scores were equal, then all of
them would be tied for second using their shared rank). The use of (many) more strains is likely
to improve some rankings as the co-occurrence score is more likely to differentiate between
different links. Both precisions for top-1, and top-1 shared ranks are provided in Fig. 5. The
complete results list with regular ranking and shared ranking for NPLinker can be found at
Dataset S1, sheet seven.
As illustrated in Fig. 5, the maximum number of correct links corresponded to using
NPOmix with substructure and similarity scores without threshold, but the highest precision
(92.3%) could be found using NPOmix with all three features (similarity, substructures, and
biosynthetic classes) with threshold. This top precision from NPOmix in our benchmarking
experimentation was about 46% more precise than the second-best tool tested, NPLinker with
shared rank (the precision without shared rank was about 40% lower), and we were able to
correctly predict about 2.5 times more BGCs-metabolites links than NPLinker. As
aforementioned, five tools could not be tested because they were: discontinued like GNP and
NRPquest; generated no results like MetaMiner; had unclear instructions like GARLIC; or could
not read the same input that other tools were able to process normally like DeepRiPP. We
concluded from this figure that NPOmix not only can predict more links (Fig. 5A) than most of
the other tools but also the ratio of correct links is significantly higher than other
methodologies (Fig. 5B). Of note, the prediction power of machine learning tools like NPOmix
and NPLinker can be even higher with more top candidates (for this comparison we only used
top-1) and better features, such as demonstrated by the implementation of biosynthetic class
with NPClassScore (38) to improve NPLinker links and the use of extra features other than
similarity by NPOmix. Machine learning tools can also improve with a bigger training set. In the
future, we will compare NPOmix using the biosynthetic class feature with NPClassScore, since it
would require standardizing and improving the current class predictions (using CANOPUS and
MolNetEnhancer) for unknown/cryptic MS/MS spectra.

665
Fig. 5. A) Histogram displaying the number of correct links (true positives, in black), incorrect links (false positives, in grey), links not tested (due to limitations of the tool or threshold selected, in blue), and links without results (in yellow) for different currently available multi-omics tools. NPOmix, NPLinker, and NRPminer can link MS/MS spectra (known or cryptic) to BGCs; GARLIC and Nerpa can link known structures to BGCs. NPOmix has different versions that yield different precision scores and so does NPLinker, however, in this case the scores were the same for the different versions. NPLinker has regular ranks and shared ranks (for example, from the second to the tenth position, if all scores were equal, then all of them would be tied for second). Precision is the ratio between true positive links overall tested positives (true, false, and links without result), and this metric was calculated using only the best candidate (top-1) from the tools' outputs. NPOmix (all three features with co-occurrence threshold) had 9 links below the threshold and these links were not tested. NRPminer and Nerpa can only test peptidic metabolites. GARLIC and GNP were discontinued (in pink), and they could not test any of the links. NRPquest was replaced by NRPminer (hence, also discontinued, in pink). There were no known RiPP metabolites in the validation set for MetaMiner and DeepRiPP to test, however, these tools did not generate results for the 49 unknown RiPP BGCs found in the genomes from the validation set. W/ = with; W/o = without; RiPP = ribosomally synthesized and post-translationally modified peptides.

Discussion

In this work, we demonstrated the use of machine learning (a new a K-Nearest Neighbors algorithm named Natural Products Mixed Omics, NPOmix) and genome mining for processing several thousand LC-MS/MS files and about a thousand genomes to connect MS/MS spectra to GCFs. Our approach can systematically connect MS/MS spectra from known metabolites (links validated experimentally), spectra from metabolites analogous to known (links with GNPS library matches, exemplified by orfamide C), and spectra from cryptic metabolites (links without GNPS library matches and therefore absent from the MS/MS database, as exemplified by brasilicardin A). The advantage of using paired data is that the genomic information represents the full metabolic potential of an organism, and hence, we can prioritize the discovery of the most diverse naturally occurring BGCs via genome mining. In other words, novelty predictions using BGC-metabolite links are likely more comprehensive than just using metabolomics and a more accurate picture of the actual chemical diversity in nature. Additionally, the use of genetic information can help in the structure elucidation and

prediction of bioactivity (18), highlighting the advantage of using the BGC information in the
drug discovery process. Moreover, predicting linked MS/MS spectra for a promising BGC can
facilitate their heterologous expression as the expression can be difficult if the target
metabolite is not known. We also show how cryptic MS/MS spectra (absent from MS/MS
databases like GNPS) can be annotated using NPOmix, MZmine (28), and Dereplicator+ (29),
allowing expansion of the current MS/MS databases.
NPOmix focus was on finding BGCs for metabolites, however, NPOmix could also be
used to go vice-versa. Also, despite this manuscript being centered on how paired data can
make better *in silico* predictions than just metabolomics, this same manuscript could also be
focused on how paired data is better than just genomics and the benefits would be very similar.
We believe this strategy aims to be a pipeline that better uses the wealth of available data; and
therefore, it could maximize the chances of finding new drug-like metabolites.
We observed very good precision scores of top-1 = 81.8% and top-10 = 92.9% (both with
randomness equal to 0, using the similarity and biosynthetic class features and using the
Jaccard co-occurrence threshold). Additionally, we also obtained a good precision score of
77.3% even without the co-occurrence threshold (for $k = 3$ and all three kinds of features
including similarity, biosynthetic class, and substructure predictions). We observed an
annotation rate of around 28%, as 14 out of 50 MS/MS validated spectra that were retained
after the co-occurrence threshold. The annotation rate was even higher without the use of the
co-occurrence threshold, 44% (22 out of 50 dereplicated MS/MS validated spectra). Table S1
details the number of genomes, metabolomes, BGCs, GCFs and metabolites used in this study.
More details on these 22 BGC-MS/MS links can be found in the Supporting Information
(Discussion section) and Fig. S7.
In fact, compared to the other eight multi-omics tools, NPOmix seems to be the only
available tool that is i) systematic (suitable to many classes of BGCs), ii) highly efficient (about
46% higher score in Fig. 5B than other approaches), iii) high-throughput (we processed around
a thousand genomes and 3x more LC-MS/MS files), and iv) scalable (requiring low processing
power, we used 8MB of RAM and 8 cores). We note that NPLinker is also systematic, high
throughput, and scalable, however, its precision score during benchmarking was 46% lower
than NPOmix, in part due to the relatively low number of strains used during NPLinker
benchmarking. NPOmix was able to correctly predict about 2.5 times more BGCs-metabolites
links than other tools. The combination of multiple multi-omics tools (and other genomics and
metabolomics tools) can be a potent genome mining approach that would enable the
visualization of many kinds of predictions (similarity scores for the links, biosynthetic classes,
complete/partial structures, taxa, and bioactivity) in a single "omics network" (work in
progress), prioritizing new true positives.
Of note, new links between metabolites with predicted structure and known BGCs may
not mean that the metabolite fully corresponds to the predicted structure because mass
spectrometry tends to not distinguish isomers and small changes in BGCs can yield substantial
changes in the final structure. Therefore, NPOmix (a correlation-based approach) does not have
the resolution to distinguish between isomers and regioselectivity of the various homologs. We
would like to emphasize that new links (not experimentally validated links that are, for
example, reported in the PoDP database) require proper elucidation to confirm the
metabolite's planar (2D) and absolute (3D) chemical structure. Hence, in this study, 6 of the 11

BGC-metabolite links (family of analogs) used for validation were previously fully elucidated (via
knockouts, heterologous expression, and/or isolation and NMR structure elucidation) as
recorded in the PoDP database. We want to emphasize that despite the small size of the
validation set (11 BGC-metabolite links plus analogs, a total of 22 MS/MS spectra), we were
able to combine *in silico* tools like Mzmine, Dereplicator+, and NPOmix to create new links that
can expand MS/MS mass spectral reference database as level bronze metabolites (new
putatively annotated MS/MS spectra). Another aspect to mention is that the precision score
may not be reproducible for every dataset, especially if the dataset is not too similar to the
current training set, as they may present very different features; and therefore, NPOmix
features might not perform as well on a given atypical dataset. Interestingly, some of our *in*
silico (*de novo*) structure predictions (such as for orfamides) were very accurate and they would
substantially facilitate NMR structure elucidation of the naturally occurring metabolite.
The use of complete genomes over MAGs and metagenomes is preferred to create a
more "complete" training set; we predict that this would result in better precision than if the
training set is populated with several fragmented BGCs. It is important to clarify that some
organisms do not have BGCs (e.g., higher plants and animals) and therefore their metabolites
cannot be linked to biosynthetic genes using NPOmix. Regarding lower plants, the annotation of
BGCs is now a hot topic, however, there is a current lack of paired data for plants and the
current NPOmix demonstration is done on the suitable and available data from the PoDP
(almost exclusively from bacteria). On top of that, BGC detection is more challenging for plants
(e.g., more scattered biosynthesis genes).
Another challenging type of samples are microbiomes, such as non-axenic
cyanobacterial cultures like the example of the mix between *Moorea producens* JHB and its 15
detected heterotrophic genera plus viruses (41). Although, we successfully processed 40
cyanobacterial microbiomes and we linked five metabolites to their correct BGCs,
demonstrating that this tool can also be used with microbiomes. A major limitation of using
microbiomes for genome mining is that the quality of their metagenomes can hinder BGC
assembly, leading to a smaller number of BGCs than expected and many of these BGCs can be
fragmented. We plan to address microbiomes, plants, algae, and fungi samples more
comprehensively in our future work (other future goals also highlighted in the Supplementary
Information, Discussion section).
Finally, we would like to stress that all true positive BGC-MS/MS validated links reported
here were found in a known producer of the metabolites, they matched the reported masses,
and six of the 11 BGC-metabolite links used for validation (true and false positives, including
brasilicardin A) were reported at the PoDP as validated via knockouts, heterologous expression,
or isolation and/or NMR structure elucidation. In a similar way, NPLinker also used such
validated links from the PoDP database to assess the impact of novel BGC-MS/MS linking scores
and the complementary of them. Palmyramide A was also previously validated via isolation and
NMR structure elucidation (42) (hence, making seven out of 12 validated family links), and it
will be soon published at MIBiG and PoDP. The putative orfamides were not confirmed via
structure elucidation or co-elution with standards (the new metabolite spectra were annotated
via GNPS library matching) but the comparison to a reference from GNPS and BGC amino acid
predictions strongly indicates that they share the same planar structure as the reference
metabolite from GNPS. Our results highlight the importance of making genomics and

metabolomics data publicly available with curated metadata, because more available paired
data would enable better training of models, and therefore, better tools for the research
community.

Conclusions
787

We developed a promising tool to search for new specialized metabolites in paired
omics data of natural extracts by using links between cryptic MS/MS and cryptic biosynthetic
gene clusters (BGCs) but also more efficiently dereplicating known BGCs or known metabolites.
This will facilitate the use of genome mining in drug discovery pipelines. For example, we
illustrated that our tool could integrate multiple kinds of information about biosynthetic
classes, family beta-diversity, dereplication, and the probability of being a correct link. These
bits of information are very useful to find novel metabolites from nature (cultures or
metagenomic samples. Thus, we believe that the current version of NPOmix will already
facilitate the access to the so far under-explored bacterial biosynthetic potential, moving from
bioprospecting about 3% (1) to bioprospecting a larger portion of this potential.
Of note, we developed NPOmix and correctly used NPLinker (14), CANOPUS (34),
NRPminer (12), Nerpa (16), GNPS molecular networking (13), BiG-SCAPE (6), and MetaMiner
(9); these tools processed data from three databases (MIBiG, PoDP, and GNPS)(13, 18, 43).
Interestingly, the information from linked BGC-MS/MS data was able to provide good
predictions for partial structures like cryptomaldamide and even complete planar structures
like orfamide C (including hints of the AA stereochemistry that can aid in the elucidation of
absolute structures). Many of the links were known antifungal and antibiotic metabolites,
therefore, reproducing this analysis for new metabolites can be a very promising methodology
for drug discovery (work also in progress, especially focusing on the discovery of new
siderophores).
To facilitate the use of NPOmix, we are hosting workshops (in English and Portuguese)
and we created video tutorials, both available at https://www.tfleao.com/npomix1). We will
assist the NPOmix use so the genome mining community can benefit from its capabilities,
especially via GitHub (https://github.com/tiagolbiotech/NPOmix_python for the python version
or https://github.com/tiagolbiotech/NPOmix for the Jupyter notebook version).
We anticipate the use of this pipeline for many applications including (but not limited
to): 1) studying siderophores and iron cycling under nutrient limitation; 2) studying humans,
mammals, plants, marine invertebrates, and other microbiomes and their relationship with host
health; 3) finding new bioactive metabolites for drug development; 4) better understanding
metabolite-mediated cell function of a model organism like *E. coli* (important for heterologous
expression); 5) learning how plants, corals and phytoplankton can be more resilient to global
warming and other anthropogenic impacts. In conclusion, this tool is going to be very important
for the community, and it has a range of implications for genomics, metabolomics, and other
research fields.

Code and Data Availability

The code (a collection of Jupyter notebooks) required to reproduce this work and to use the NPOmix tool for new samples can be found on the following GitHub repository page: https://github.com/tiagolbiotech/NPOmix. The repository also includes short video explanations on how the tool works and its importance for natural product discovery. We also wrapped the code in a few python scripts found here: https://github.com/tiagolbiotech/NPOmix_python. This page with the python version also includes a video explanation of how to prepare inputs and how to run NPOmix in python. Additionally, we provide a webpage (https://www.tfleao.com/npomix1) for submitting a limited number of samples for free processing (maximum of 50 queries MS/MS fragmentation spectra) and this page also includes workshops on how to submit samples and interpret results. We are going to purchase a server and allow users to submit many more metabolites than just 50.

The (meta)genomes used to create the NPOmix training dataset for validation were downloaded from the Paired omics Data Platform (PoDP)(21) using notebook 1 from the GitHub repository (Jupyter notebook version). The paired experimental MS/MS files were downloaded using the ftp links (also from the PoDP) found in Dataset S1, sheet six. The testing set included MS/MS spectra from PoDP, spectra from the Global Natural Products Social Molecular Networking database (GNPS)(13), and also spectra also used in the NPLinker publication (33). If the potential users find the tool challenging to run, we have our contact information on the main webpage (link above) to submit samples and we expect that promising results will lead to fruitful collaborations.

Funding and Acknowledgments

This research was supported by National Institutes of Health (NIH) Grants GM107550 (to P.C.D., W.H.G., and L.G.) and GM118815 (to W.H.G. and L.G.). This work was supported in part by a seed grant from the Center for Microbiome Innovation at the University of California San Diego. R.S. was supported by the São Paulo Research Foundation (Awards FAPESP 2017/18922–2 and 2019/05026–4). J. J. J. v. d. H. and J.J.R.L. were supported by the Netherlands eScience Center (ASDI eScience grant ASDI.2017.030). J. J. J. v. d. H. was supported by the Netherlands eScience Center Open eScience Call (NLESC.OEC.2021.002). A.G. was supported by the System Biology Fellowship of Skoltech & PMI (Research Agreement number 8299). We would like to acknowledge Sandra Neubert, Bohan Ni, Dr. Kiefer Forsch, Dr. Christopher Leber, Dr. Chen Zhang, Dr. Andres Mauricio Caraballo-Rodriguez, Dr. Louis-Félix Nothias, Dr. Benjamin Naman, and Dr. Mitja Zdouc for the productive discussions about the topic. Additionally, we would like to acknowledge Dr. Andrew Ramsay for the help and advice on how to run NPLinker.

Conflict of Interest

W.H.G. has an equity interest in NMRFinder and SirenasMD Inc., companies that may potentially benefit from the research results and W.H.G. also serves on the companies' Scientific Advisory Boards. The terms of this arrangement have been reviewed and approved by the University of California San Diego in accordance with its conflict-of-interest policies. P.C.D. is a scientific advisor to SirenasMD Inc., Galileo and Cybele, and co-founder and scientific advisor to Ometa and Enveda with approval by the University of California San Diego. M.W. is a cofounder of Ometa Labs, LLC. J.J.J.v.d.H is a member of the Scientific Advisory Board of NAICONS Srl., Milano, Italy.

Methods

See Supplementary Information Methods section for details on obtaining the data, assembly, BGC comparison, the NPOmix tool itself and other bioinformatic analyses.

Supplementary Information

Background

Besides the fact that our validation set is small (11 BGC-metabolite links plus analogs, a total of 22 MS/MS spectra), we do show that the combination of *in silico* tools like Mzmine (28), Dereplicator+ (29) and NPOmix can create new links that can expand MS/MS databases as level bronze metabolites (new putative MS/MS spectra). Whilst >2000 validated BGCs are described in the MIBiG database, a minority of them have associated MS/MS spectra, and a subset of these can be expected to be present in samples under study for which actual paired omics data is available, explaining why the validation set is small). Nevertheless, we were able to correctly connect 17 known metabolites (including analogs) to their validated BGCs using their similarity, biosynthetic class, and substructure features. We also exemplified with orfamide C (peptidic metabolite) how the information from these links can yield very accurate *in silico* and *de novo* planar structure prediction with a low delta *m/z* (error between predicted and observed *m/z*). We believe the same approach can be used for new/cryptic metabolites since the KNN algorithm does not know the metabolite labels (e.g., orfamide C) while making the BGCs-metabolites links. Moreover, we could partially predict the stereochemistry of orfamide C and other metabolites using genomic data.

Generally, finding novel metabolites for cryptic BGCs or even known BGCs (e.g., new analogs) is very useful to accelerate natural product discovery, however, connecting known metabolites to their biosynthetic gene clusters is also important. Newly linked BGCs for known metabolites can lead to the discovery of new enzymatic processes. For example, in the strain *Anabaena variabilis* ATCC 29413, a nonribosomal peptide-synthetase (NRPS) gene is responsible for the attachment of a serine residue to generate the final mycosporine-like amino acids (MAA) product. However, in the strain *Nostoc punctiforme* ATCC 29133, this same step is performed by an ATP-grasp ligase (44). This highlights that different microbes can generate the same metabolite through different convergent biosynthetic routes.

Results

Comparing the performance of NPOmix with other published tools. Capistruin C was "bioinformatically inferred through comparative analysis with another experimentally defined gene cluster". Therefore, capistruin C was not validated in the reported strain at PoDP (*Burkholderia thailandensis* E264). The strain in which the BGC was validated is absent from the MassIVE database (*Burkholderia thailandensis* E444), meaning that we could not obtain the metabolome required for testing this strain. Moreover, we believe that this prediction "inferred through comparative analysis" does not need to be correct because the *B. thailandensis* E264 genome was included in the NPOmix analysis but the MIBiG BGC did not network with any other BGC in the full dataset (including the MIBiG BGC known for producing capistruin C), and we also checked the *B. thailandensis* E264 antiSMASH result for a capistruin C annotation but, again, none of its BGCs had the capistruin C annotation as the "most similar known cluster". We

were unable to find the MS/MS spectra for polytheonamide A and B, they are not published at
GNPS.
As observed in Fig. S5A, the absolute number of correct BGC-metabolite links is bigger
for NPOmix using the substructure and similarity features without the co-occurrence threshold
compared to the same condition using the co-occurrence threshold, because some links are
present in several samples and some BGCs can be silent or very fragmented. This typically
creates mismatches between the fingerprints and drops the Jaccard index in the
presence/absence of the fingerprints used for the co-occurrence threshold. However, some not
so fragmented BGCs can be connected via BiG-SCAPE similarity to a reference BGC and then get
grouped into the same family, see for example in Fig. S6. Additionally, in some samples, the
MS/MS spectra might not be acquired due to the complexity of the sample and the nature of
the data-dependent acquisition. Hence, in these cases, the co-occurrence threshold may
remove links (illustrated as "links not tested" in Fig. S5A and Fig. 5) even if they are true
positives (metabolite correctly linked to its BGC). For NPOmix using similarity only and using
both similarity and biosynthetic class, the threshold only removed false positives. Despite the
higher number of correct links without the threshold, the threshold increases the relative ratio
of correct links, leading to higher precision scores if compared to the NPOmix versions without
threshold (Fig. S5B).

Discussion
938
We created a machine learning solution, a K-Nearest Neighbors algorithm named
Natural Products Mixed Omics (NPOmix) approach, to connect natural products observed by
untargeted mass spectrometry to their corresponding biosynthetic gene clusters (BGCs). We
showed that a large dataset, deriving from heterogeneous sources such as the ones currently
available in the Paired Omics Data Platform (PoDP), can create good fingerprints and can thus
successfully connect known metabolites to their corresponding BGCs, such as albicidin and its
analogs to a BGC in *Xanthomonas albilineans* GPE PC73 (GenBank ID GCA_000087965.1),
orfamides A-C to a BGC in *Pseudomonas protegens* Pf-5 (GCA_000012265), and
cryptomaldamide and jamaicamide A and C to BGCs in *Moorena producens* JHB
(GCA_001854205). All three of these strains were the original producers of these metabolites.
In Fig. S3, we illustrated how the BGC predictions (such as predicted moieties) can help to
prioritize true links over false positives via comparing predicted structures between a given
MS/MS spectrum and its BGC candidates (the matching was done using only similarity and
biosynthetic class as features for the NPOmix algorithm).
We are developing an integrated pipeline for metabolite discovery using genomics, LC-
MS/MS metabolomics, and other multi-omics tools. Additional future work will include the
testing of other similarity metrics for networking and fingerprinting such as BiG-SLICE (45) for
genomics and Spec2Vec (46) and MS2DeepScore (47) for the metabolomics. We will also look
for synergy with correlation scores from NPLinker (14) to better annotate paired omics
datasets. We intend to implement biosynthetic class and substructure predictions straight from
the MS/MS fragmentation spectra using tools like SIRIUS 4 (38), MS2LDA (37), MolNetEnhancer
(35), or CANOPUS (34), prioritizing candidates that have several substructures or predicted
classes matching between BGCs and MS/MS spectra. The GNPS molecular family information

could be used to select a consensus prediction among different MS/MS spectra from the same
family. Enrichment of the current Paired Omics Data Platform dataset (we could now use 1,040
PoDP samples for NPOmix) with higher quality samples as well as more validated BGC-MS/MS
links will further drive the development of tools such as NPOmix, and this will spark the
discovery of more novel NPs.
We intend to add to this multi-omics approach: 1) BGC bioactivity (20); 2) MS/MS
bioactivity, by creating a new machine learning tool to predict bioactivity straight from the
MS/MS spectra, and; 3) MS/MS substructure predictions, by integrating tools like MS2LDA (37),
CSI: FingerID /SIRIUS 4 (38) and MassQL (not published yet). NPClassScore (33) demonstrated
that biosynthetic class can be predicted with a combination of CANOPUS and MolNetEnhancer,
hence, the NPOmix users can already run the KNN version with similarity and biosynthetic class
as features, a version that yielded a precision of 92.9% in the validation set. Accurate *in silico*
structure and bioactivity predictions allow start using a more "modeling" way to investigate all
sequenced environmental bacteria/microbiomes, reducing the need for multiple cell assays and
significantly aiding structure elucidation.
NPOmix was able to correctly link nine out of 12 different known metabolites (18 out of
23 MS/MS spectra, including analogs) to their corresponding BGCs. These metabolites (and
analogs) were barbamide, antimycin A1, pyocyanine, brasilicardin A, orfamide A-C, albicidins,
jamaicamide A and C, cryptomaldamide and palmyramide A (the last one was tested separately
from the validation set and it was not used to estimate precision scores in Fig. 3 and 5). These
known metabolites were reported from 9 strains belonging to the phyla Proteobacteria
(44.44%), Actinobacteria (33.33%), Cyanobacteria (22.22%), and from seven different genera
(Fig. S7A), indicating taxonomic diversity in this bacterial validation dataset. Most of these links
were reported to be active against fungi and bacteria (Fig. S7B). We can also see in Fig. S7B that
these links encompass distinct biosynthetic classes like polyketide synthase (PKS), nonribosomal
peptide-synthetase (NRPS), hybrid PKS-NRPS, hybrid terpene-oligosaccharide, and other;
indicating that the tool is indeed systematic.

Methods

990
991 **Obtaining paired data.** The paired data used in this manuscript is available at the Paired omics
992 Data Platform (PoDP) and we were able to obtain 36 out of 71 meta-datasets that were
993 available at the time. We automatically downloaded the paired (meta)genomics-metabolomics
994 data from the samples in the PoDP according to the code in notebook 1 at the GitHub
995 repository described below.

996
Metagenome assembly and annotation, BGC, and MS/MS similarity calculation. Metagenomic
reads were assembled with SPAdes 3.15.2. (48). For BGC annotation, we used antiSMASH 5.0
(5) and for gene cluster networking we used BiG-SCAPE 1.0 (similarity cutoff of 0.7)(6). BiG-
SCAPE raw distance is measured via the domain sequence similarity (DSS) index, an index that
calculates the Pfam domain copy number differences and sequence identity. For networking
metabolites, we used GNPS classical molecular networking release 27 (similarity cutoff of 0.7).
We did not use the full classical molecular networking capabilities in the NPOmix approach, as

only the functions required to calculate a modified cosine score between a pair of MS/MS
spectra were needed.
1006
Creating fingerprints. We developed python scripts and we combined them with scripts from
sklearn (https://scikit-learn.org/stable/index.html) to create both BGC and MS/MS fingerprints
and to run the KNN algorithm. A BGC fingerprint is created by pairwise BiG-SCAPE comparison
between the queried BGC and all the BGCs found in the (meta)genomes in the training set,
selecting the highest similarity scores for each (meta)genome. An MS/MS fingerprint (part of
the testing set) is created by pairwise modified cosine comparison between the queried MS/MS
and all the MS/MS present in the LC-MS/MS files paired with the genomes from the training
set, also selecting only the highest similarity scores per set of experimental MS/MS spectra.
1015
Jupyter notebooks. All scripts used in this research can be found at this GitHub repository:
https://github.com/tiagolbiotech/NPOmix. For instructions on installing and running the tools
used in this publication, please see "NPOmix_SI-installation_and_running". Notebook 1 can be
used to download (meta)genomes and metagenome-assembled genomes (MAGs) that contain
paired untargeted metabolomics (LC-MS/MS)(metabolomic files will also be downloaded by the
notebook). We selected genomic samples that contained a valid Genome ID or BioSample ID,
resulting in 732 genomes/MAGs. We also selected and assembled 1,034 metagenomes.
Notebook 2 can be used to process downloaded metabolomics files and a selected set of ".mgf"
reference MS/MS spectra, creating a matrix containing the MS/MS fingerprints for the selected
set of reference spectra (reference MS/MS spectra for the validation but for using the tool
these reference spectra will be replaced by cryptic MS/MS spectra). If there were more than
one LC-MS/MS file per genome (for example different media conditions or different chemical
fractions), these files were merged into a single file representing these experimental MS/MS
spectra. Notebook 3 can be used to process the antiSMASH results to create BGC fingerprints
and use those to train the KNN algorithm. The MS/MS fingerprints are used to predict
a/multiple GCF(s) for each tested reference MS/MS spectra found in the paired genomes-
MS/MS data. We filtered the GCF-MS/MS links for cases in which the top GCF candidate had co-
occurrence with a cutoff of 0.7 (GCF and MS/MS scores were present in the same set of
samples (the cutoff is the same as the similarity cutoffs for consistency). Notebook 3 also
performs cross-validation (dividing the data into 5 parts) and the average precision score for
the cross-validation was 56.9%. Notebook 4 can be used to generate metadata such as the type
of GCF or the count of BGCs per each genus in the database. Notebook 5 presents the code for
genome mining that yielded the annotation of brasilicardin A (more details below). Notebook 6
expanded the similarity/absence fingerprints by including the biosynthetic class as new
features, notebook 7 included the substructure predictions as new features and notebook 8
uses all three features (similarity, biosynthetic class, and substructures).
1042
Genome mining for new MS/MS spectra using Dereplicator+ and NPOmix. In order to use the
NPOmix approach to find new NPs without any GNPS library matches (absent from the MS/MS
database), we developed a pipeline combining NPOmix, MZmine (28), and Dereplicator+ (29).
First, several strains can be selected using MZmine, here exemplified with 16 strains, based on
their BGC beta-diversity scores. The Jaccard beta-diversity score metric of the similarity

between a pair of strains was calculated as the intersection over the union of the detected gene
cluster families. Using MZmine, we select peaks that were above a certain intensity threshold
(we used base peak relative abundance of 1E6) to prioritize the chromatographic peaks that
could reasonably be isolated for structure elucidation. In this example, we detected
approximately 3,800 peaks with MS/MS spectra found in the analysis of the 16 most diverse
strains. This MZmine list of peaks that have associated MS/MS data was filtered for a minimum
precursor mass of m/z 500 to promote the presence of multiple moieties (substructures) in the
predicted structures, generating 300 ".mgf" files. These mgf files were used by NPOmix to
predict the GCFs/BGCs for each of the 300 MS/MS spectra. We filtered for BGC-MS/MS links
that the query MS/MS spectra existed in the same strains that the query BGCs were found and
not across different strains, using the Jaccard index in the presence/absence of the fingerprints,
essentially a pairwise analysis between the BGC fingerprint and the MS/MS fingerprint. This
second filter narrowed down the number of mgf files to 72. These 72 mgf files were processed
by Dereplicator+ for predicting structures for each MS/MS spectrum, leading to the annotation
of brasilicardin A. Two other Dereplicator+ hits did not match the predicted GCFs. MZmine
parameters were as follows: noise level of 1E6 for MS1 and 1E3 for MS/MS, minimum group
size in the number of scans of 4, group intensity threshold of 1E6, the minimum highest
intensity of 3E6, m/z tolerance of 10 ppm, retention time tolerance of 0.2, weight for m/z of
75%, and weight for a retention time of 25%.
1067
Expanding BGC and MS/MS fingerprints using biosynthetic classes. In notebook 6, the BGC
classes were annotated and included in the BGC fingerprints. To accomplish this, all of the
antiSMASH annotations for a given BGC were added to the presence of all predicted classes.
Each class represented a new column in the fingerprints and the columns were filled with 1 (if
the class was present) and 0 (if the class was absent). We observed the following classes in our
dataset: polyketide synthases, nonribosomal peptide-synthetases, terpenes, siderophores,
ribosomally synthesized and post-translationally modified peptides, phosphonates,
oligosaccharides, phenolic metabolites, others/unknowns, other minor classes
(aminoglycoside/aminocyclitol, beta-lactone, beta-lactam, butyrolactone, ectoine, furan, fused,
indole and phenazine), and combinations of more than one class (like PKS-NRPS). We added in
total 10 new presence/absence biosynthetic features. In the MS/MS fingerprint, for each one of
the 22 validated MS/MS spectra, we annotated the presence/absence of the biosynthetic
classes based on the known structures. These new fingerprints were used in the machine
learning process, analogously to the notebook 3.
1082
Expanding BGC and MS/MS fingerprints using substructure prediction. The substructure
predictions were also annotated using antiSMASH and they were implemented in the BGC
fingerprints. Analogously to the biosynthetic classes, each substructure prediction represented
a new column in the fingerprints and the columns were filled with 1 (if the class was present)
and 0 (if the class was absent). We annotated 85 substructures (the substructures found in our
samples are listed in Dataset S1, sheet five) and these substructures were added as 85 new
features. We also tested summarizing and PKS substructures (malonyl-CoA, methylmalonyl-
CoA, and so on) and all KR domains into two columns (one for each). Regarding the MS/MS
fingerprints for each of the 22 validated MS/MS spectra, we annotated the columns based on

the information from the known BGCs. For palmyramide A we manually annotated the
substructures from its known structure. The new BGC and MS/MS fingerprints were used in the
machine learning algorithm to calculate precision scores. Predicted structures were obtained by
analyzing the substrate-specific from the antiSMASH BGCs and manually matching them to the
MS/MS fragmentation spectra.
1097
Benchmarking multi-omics tools (comparing the performance of NPOmix with other tools).
We attempted to execute eight multi-omics tools for benchmarking NPOmix: MetaMiner (9),
DeepRiPP (10), NRPquest (11), NRPminer (12), GNP (13) and NPLinker (14), Nerpa (16) and
GARLIC (17). For the sake of computational resources, we only performed the benchmarking on
the 9 strains that contained the 22 BGC-metabolite-structure links used for NPOmix validation
and for calculating the NPOmix precision scores. We selected standard configurations for all
these eight multi-omics tools and, unfortunately, we were unable to run DeepRiPP (could not
process the FASTA files), NRPquest (discontinued), GNP (discontinued), and GARLIC (we were
unable to compile its pre-requirement, GRAPE, and it seems that this tool was also
discontinued). MetaMiner produced no results, despite the presence of 49 unknown RiPP BGCs
in these 9 samples.

Fig. S1. Representation of how BGCs can be plotted in the KNN (*k*-nearest neighbor) space by using the values in the training matrix, each column represents a genome in the training set and it also represents a dimension in the KNN space (1,040 genomes distributed in 1,040 columns). This example has three dimensions because it uses only three genomes; the actual training matrix used in this study had 1,040 genomes and therefore 1,040 dimensions. BGC = biosynthetic gene cluster; GCFs = gene cluster family.

1118
1119
1120 **Fig. S2.** Representation of a mismatch linked by the KNN algorithm using *k* = 3. It is visually clear that the closest
1121 neighboring BGC fingerprints for pyocyanine do not properly match the MS/MS fingerprint from the metabolite
1122 2,4- diacetylphloroglucinol, indicating that NPOmix suggested the wrong GCF for the 2,4- diacetylphloroglucinol
1123 MS/MS spectrum. BGC = biosynthetic gene cluster; GCFs = gene cluster family.
1124
1125

1126
Fig. S3. NPOmix automatically connected an MS/MS spectrum annotated as "putative orfamide C" to the MIBiG
BGC annotated as orfamide C. The figure illustrates the matches between the BGC's AA predictions (via
antiSMASH) and the predicted metabolite structure (orfamide C, predicted via MS/MS spectral matching). Only
one AA (valine, in red) out of 10 AA could not be predicted by the BGC annotation tool (antiSMASH), however, this
valine residue was predicted by the MS/MS spectrum. BGC = biosynthetic gene cluster; AA = amino acid; AmT =
aminotransferase; TE = thioesterase; A = adenylation domain; ER = enol reductase; "?" in the BGC represents that
one AA could not be predicted by antiSMASH.
1134
1135
1136

1137

Exact Mass: 892.45688

1138
1139
1140

1141
1142
Fig. S4. Proposed mechanism for the fragmentation of brasilicardin A by ESI mass spectrometry. The structure was
proposed by NPOmix as a possible match for the MS/MS spectrum with protonated *m/z* 893.4624. Dataset S1,
sheet four, shows the SMILES strings and delta *m/z* values for the predicted structural fragments and the observed
fragments in the MS/MS spectrum. All delta *m/z* values in the table were extremely small, strongly indicating that
brasilicardin A is the correct structure for this MS/MS spectrum and it matches well with the BGC identified in the
genome of *Nocardia terpenica* IFM 0406 (BGC known to produce brasilicardin A, ID BGC0000632).
1149

1150
1151
1152 **Fig. S5.** A) Histogram displaying the number of correct links (true positives, black), incorrect links (false positives,
1153 grey), links not tested (due to limitations of the tool or threshold selected, light blue) for different currently
1154 available multi-omics tools.
1155

1156
1157
1158 **Fig. S6.** Example of fragmented biosynthetic gene clusters (BGCs) where the fragments are connected by BiG-
1159 SCAPE similarity, grouping them in a gene cluster family (in some cases). In other cases, the partial BGC still
1160 matches the reference, or some fragments are networked.

1161

1162
1163
1164 **Fig. S7.** Diversity of 9 different bacteria (in A) from the PoDP database used for benchmarking NPOmix, the
1165 biosynthetic classes (in B), and the reported bioactivity (in C) found in the metabolites connected to their BGCs
1166 used in the validation dataset. Na = sodium; PKS = polyketide synthase; NRPS = nonribosomal peptide-synthetase.
1167

1168   **Table S1.** The number of genomes, metabolomes, total BGCs, total GCFs, MIBiG BGCs networked, GNPS
1169   metabolites dereplicated, metabolites with MIBiG BGC (and the subset correctly linked by NPOmix), and
1170   metabolites with MIBiG BGC post-filtering with 0.7 Jaccard similarity (and the subset correctly liked by NPOmix).
1171   Pal* = to palmyramide A, which the BGC is not on MIBiG yet.
1172

Type of feature in our dataset	
Number of genomes	1,040
Number of metabolomes	3,248
Number of BGCs	3,331
Number of GCFs	997
MIBiG BGCs networked	178
GNPS metabolites dereplicated (most of them are reported at PoDP)	50
Metabolites dereplicated with MIBiG BGC	22+Pal*
Metabolites dereplicated with MIBiG BGC and correctly linked by NPOmix	17+Pal*
Metabolites dereplicated with MIBiG BGC post-filtering	14
Metabolites dereplicated with MIBiG BGC post-filtering and correctly linked by NPOmix	13

1173
1174
Table S2. Top-n precision scores (how often the correct GCF label was found among the top n labels classified by
the KNN approach) for around 14 references GNPS MS/MS spectra connected to a BGC found in the paired 1,040
(meta)genomes-MS/MS downloaded from the GNPS, MIBiG and PoDP databases (these links passed the co-
occurrence threshold). These known links were obtained from the NPLinker dataset, GNPS, and PoDP databases.
For this analysis, we only used similarity and biosynthetic classes as features because they are easier to annotate
even from cryptic MS/MS spectra. Randomness is observed by shuffling the testing columns, experimental MS/MS
names, and counting how many correct links are present between the top-n GCF candidates. Based on this, we
believe the best performance is n = 3 (and it is the same value for k) for the examined dataset.
1183

	Top-1	Top-3	Top-5	Top-10	Top-50	Top-100
Data	81.8%	92.9%	92.9%	92.9%	92.9%	92.9%
Random	0%	0%	0%	0%	0%	60%

1184
1185

Table S3. Multi-omics tools published to date, the type of links they can generate, and their websites for running
samples or downloading their command-line version. Of note, only NPOmix, NPLinker, and GNP ("service
unavailable") are systematic (work for many classes of natural products). MetaMiner, and DeepRiPP are specific for
ribosomally synthesized and post-translationally modified peptides (RiPPs); nonribosomal peptides (NRPs) can be
processed by NRPquest (apparently discontinued), NRPminer and Nerpa. Nerpa can also process hybrid
polyketides-nonribosomal peptides and GARLIC can process NRPs, polyketides, and hybrids.
1192

Tool	Type of links	Website for running samples	Command line version
NPOmix (this study)	BGC-MS/MS	https://www.tfleao.com/npomix1	https://github.com/tiagolbiotech/NPOmix_python
NPLinker (14)	BGC-MS/MS BGC-SMILES	Not available	https://github.com/sdrogers/nplinker
GNP (13)	BGC-MS/MS	https://magarveylab.ca/gnp ("Service unavailable")	Not available
DeepRiPP (10)	BGC-MS/MS BGC-SMILES	http://deepripp.magarveylab.ca	Not fully available (only NLPPrecursor module)
MetaMiner (9)	BGC-MS/MS	https://gnps.ucsd.edu/ProteoSAFe/index.jsp?params=%7B%22workflow%22:%22RIPPQUEST%22%7D	https://github.com/ablab/npdtools/blob/master/docs/MetaMiner.md
NRPquest (11)	BGC-MS/MS	http://mohimanilab.cbd.cmu.edu/software/	Not available
NRPminer (12)	BGC-MS/MS	https://metabologenomic.cbd.cs.cmu.edu/#/login	https://github.com/mohimanilab/NRPminer (read me and test data only)
Nerpa (16)	BGC-SMILES	Not available	https://github.com/ablab/nerpa
GARLIC (17)	BGC-SMILES	Not available	https://github.com/magarveylab/garlic-release

1193
1194

References

1. A. Gavriilidou, *et al.*, Compendium of secondary metabolite biosynthetic diversity encoded in bacterial genomes. *Nat. Microbiol.* **7**, 726–735 (2022).

2. J. A. Van Santen, *et al.*, The Natural Products Atlas 2.0: A database of microbially-derived natural products. *Nucleic Acids Res.* **50**, D1317–D1323 (2022).

3. M. A. Beniddir, *et al.*, Advances in decomposing complex metabolite mixtures using substructure- And network-based computational metabolomics approaches. *Nat. Prod. Rep.* **38**, 1967–1993 (2021).

4. S. D. Bentley, *et al.*, Complete genome sequence of the model actinomycete Streptomyces coelicolor A3(2). *Nature* **417**, 141–147 (2002).

5. K. Blin, *et al.*, AntiSMASH 5.0: Updates to the secondary metabolite genome mining pipeline. *Nucleic Acids Res.* **47**(W1):W81-W87 (2019).

6. J. C. Navarro-muñoz, *et al.*, A computational framework to explore large-scale biosynthetic diversity. *Nat. Chem. Biol.* **47**, W81–W87 (2019).

7. J. R. Doroghazi, *et al.*, A roadmap for natural product discovery based on large-scale genomics and metabolomics. *Nat. Chem. Biol.* **10**, 963–8 (2014).

8. K. R. Duncan, *et al.*, Molecular Networking and Pattern-Based Genome Mining Improves Discovery of Biosynthetic Gene Clusters and their Products from Salinispora Species. *Chem. Biol.*, **22**, 60-68 (2015).

9. L. Cao, *et al.*, MetaMiner: A Scalable Peptidogenomics Approach for Discovery of Ribosomal Peptide Natural Products with Blind Modifications from Microbial Communities. *Cell Syst.* **9**, 600-608.e4 (2019).

10. N. J. Merwin, *et al.*, DeepRiPP integrates multiomics data to automate discovery of novel ribosomally synthesized natural products. *Proc. Natl. Acad. Sci. U. S. A.* **117**, 371–380 (2020).

11. H. Mohimani, *et al.*, NRPquest: Coupling mass spectrometry and genome mining for nonribosomal peptide discovery. *J. Nat. Prod.* **77**, 1902–1909 (2014).

12. B. Behsaz, *et al.*, Integrating genomics and metabolomics for scalable non-ribosomal peptide discovery. *Nat. Commun.* **12**, 3225 (2021).

13. M. Wang, *et al.*, Sharing and community curation of mass spectrometry data with Global Natural Products Social Molecular Networking. *Nat. Biotechnol.* **34**, 828–837 (2016).

14. G. Hjörleifsson Eldjárn, *et al.*, Ranking microbial metabolomic and genomic links in the NPLinker framework using complementary scoring functions. *PLOS Comput. Biol.* **17**, e1008920 (2021).

15. J. J. J. Van Der Hooft, *et al.*, Linking genomics and metabolomics to chart specialized metabolic diversity. *Chem. Soc. Rev.* **49**, 3297-3314 (2020).

16. O. Kunyavskaya, *et al.*, Nerpa : A Tool for Discovering Biosynthetic Gene Clusters of Bacterial Nonribosomal Peptides. *Metabolites*. **11**(10), 693 (2021).

17. C. A. Dejong, *et al.*, Polyketide and nonribosomal peptide retro-biosynthesis and global gene cluster matching. *Nat. Chem. Biol.* **12**, 1007–1014 (2016).

18. S. A. Kautsar, *et al.*, MIBiG 2.0: A repository for biosynthetic gene clusters of known function. *Nucleic Acids Res.* **48**, D454–D458 (2020).

1238   19.   J. Jumper, *et al.*, Highly accurate protein structure prediction with AlphaFold. *Nature* **596**,
1239   583–589 (2021).
1240   20.   A. S. Walker, J. Clardy, A Machine Learning Bioinformatics Method to Predict Biological
1241   Activity from Biosynthetic Gene Clusters. *J. Chem. Inf. Model.* **61**, 2560-2571 (2021).
1242   21.   M. A. Schorn, *et al.*, A community resource for paired genomic and metabolomic data
1243   mining. *Nat. Chem. Biol.* **17**, 363–368 (2021).
1244   22.   T. Leão, *et al.*, A Multi-Omics Characterization of the Natural Product Potential of
1245   Tropical Filamentous Marine Cyanobacteria. *Mar. Drugs* **19**(1), 20 (2021).
1246   23.   J. M. Gauglitz, *et al.*, Metabolome-Informed Microbiome Analysis Refines Metadata
1247   Classifications and Reveals Unexpected Medication Transfer in Captive Cheetahs.
1248   *mSystems* **5**, 1–14 (2020).
1249   24.   D. McDonald, *et al.*, American Gut: an Open Platform for Citizen Science Microbiome
1250   Research. *mSystems.* **3**, e00031-1 (2018).
1251   25.   A. T. Aron, *et al.*, Reproducible molecular networking of untargeted mass spectrometry
1252   data using GNPS. *Nat. Protoc.* **15**, 1954–1991 (2020).
1253   26.   W. Bittremieux, *et al.*, Universal MS/MS Visualization and Retrieval with the
1254   Metabolomics Spectrum Resolver Web Service. *bioRxiv* (2020).
1255   27.   H. Gross, *et al.*, The Genomisotopic Approach: A Systematic Method to Isolate Products
1256   of Orphan Biosynthetic Gene Clusters. *Chem. Biol.* **14**, 53–63 (2007).
1257   28.   T. Pluskal, S. Castillo, A. Villar-Briones, M. Orešič. MZmine 2: Modular framework for
1258   processing, visualizing, and analyzing mass spectrometry-based molecular profile data.
1259   *BMC Bioinformatics* **11**, 395 (2010).
1260   29.   H. Mohimani, *et al.*, Dereplication of microbial metabolites through database search of
1261   mass spectra. *Nat. Commun.* **9**, 4035 (2018).
1262   30.   H. Komaki, *et al.*, Brasilicardin A, a new terpenoid antibiotic from pathogenic Nocardia
1263   brasiliensis: Fermentation, isolation and biological activity. *J. Antibiot.* **52**, 13-19 (1999).
1264   31.   Y. Hayashi, *et al.*, Cloning of the gene cluster responsible for the biosynthesis of
1265   brasilicardin a, a unique diterpenoid. *J. Antibiot. (Tokyo).* **61**, 164–174 (2008).
1266   32.   R. Reher, *et al.*, A Convolutional Neural Network-Based Approach for the Rapid
1267   Annotation of Molecularly Diverse Natural Products. *J. Am. Chem. Soc.* **142**, 4114–4120
1268   (2020).
1269   33.   J. J. R. Louwen, M. H. Medema, J. J. J. Van Der Hooft. Enhanced correlation-based linking
1270   of biosynthetic gene clusters to their metabolic products through chemical class
1271   matching. *Research Square* (2022).
1272   34.   K. Dührkop, *et al.*, Systematic classification of unknown metabolites using high-resolution
1273   fragmentation mass spectra. *Nat. Biotechnol.* **39**, 462–471 (2020).
1274   35.   M. Ernst, *et al.*, Molnetenhancer: Enhanced molecular networks by integrating
1275   metabolome mining and annotation tools. *Metabolites.* **9**, 144 (2019).
1276   36.   H. W. Kim, *et al.*, NPClassifier: A Deep Neural Network-Based Structural Classification
1277   Tool for Natural Products. *J. Nat. Prod.* **84**, 2795–2807 (2021).
1278   37.   J. J. J. Van Der Hooft, *et al.*, Unsupervised Discovery and Comparison of Structural
1279   Families Across Multiple Samples in Untargeted Metabolomics. *Anal. Chem.* **89**, 7569–
1280   7577 (2017).
1281   38.   K. Dührkop, *et al.*, SIRIUS 4: a rapid tool for turning tandem mass spectra into metabolite

1282   structure information. *Nat. Methods.* **16**, 299–302 (2019).

1283 39. T. Leao, *et al.*, Comparative genomics uncovers the prolific and distinctive metabolic
1284   potential of the cyanobacterial genus Moorea. *Proc. Natl. Acad. Sci.* **114**, 3198–3203
1285   (2017).

1286 40. K. Blin, M. H. Medema, R. Kottmann, S. Y. Lee, T. Weber, The antiSMASH database , a
1287   comprehensive database of microbial secondary metabolite biosynthetic gene clusters.
1288   **45**, 555–559 (2017).

1289 41. S. L. Cummings, *et al.*, A novel uncultured heterotrophic bacterial associate of the
1290   cyanobacterium Moorea producens JHB. *BMC Microbiol.* **16**(1), 198 (2016).

1291 42. M. Taniguchi, *et al.*, Palmyramide a, a cyclic depsipeptide from a palmyra atoll collection
1292   of the marine cyanobacterium lyngbya majuscula. *J. Nat. Prod.* **73**, 393–398 (2010).

1293 43. M. A. Schorn, *et al.*, A community resource for paired genomic and metabolomic data
1294   mining. *Nat. Chem. Biol.* **17**, 363–368 (2021).

1295 44. E. P. Balskus, C. T. Walsh, The Genetic and Molecular Basis for Sunscreen Biosynthesis in
1296   Cyanobacteria. *Science (80-.).* **329**, 1653–1656 (2010).

1297 45. S. A. Kautsar, J. J. J. Van Der Hooft, D. De Ridder, M. H. Medema, BiG-SLiCE: A highly
1298   scalable tool maps the diversity of 1.2 million biosynthetic gene clusters. *Gigascience*. **45**,
1299   W55–W63 (2021).

1300 46. F. Huber, L. Ridder, S. Rogers, J. J. J. van der Hooft, Spec2Vec: Improved mass spectral
1301   similarity scoring through learning of structural relationships. *PLoS Comput. Biol.* **17**,
1302   e1008724 (2020).

1303 47. F. Huber, S. van der Burg, J. J. J. van der Hooft, L. Ridder. MS2DeepScore - a novel deep
1304   learning similarity measure to compare tandem mass spectra. *bioRxiv* (2021).

1305 48. A. Bankevich, *et al.*, SPAdes: A New Genome Assembly Algorithm and Its Applications to
1306   Single-Cell Sequencing. *J. Comput. Biol.* **19**, 455–477 (2012).

1307