A robust receptive field code for optic flow detection and decomposition
during self-motion

Authors/affiliations

Zhang, Yue[1,2]; Huang, Ruoyu[1]; Nörenberg, Wiebke[1,2,3]; Arrenberg, Aristides[1]

Author list footnotes

1. Werner Reichardt Centre for Integrative Neuroscience, Institute of
Neurobiology, University of Tübingen, D-72076, Tübingen, Germany

2. Graduate Training Centre for Neuroscience, University of Tübingen, D-72076,
Tübingen, Germany

3. Present address: Humboldt-Universität zu Berlin, Faculty of Philosophy, Berlin
School of Mind and Brain, Germany; Humboldt-Universität zu Berlin, Faculty
of Life Sciences, Department of Psychology, Germany.

Contact info

aristides.arrenberg@uni-tuebingen.de

Summary

The perception of optic flow is essential for any visually guided behavior of a moving
animal. To mechanistically predict behavior and understand the emergence of self-
motion perception in vertebrate brains, it is essential to systematically characterize
the motion receptive fields (RFs) of optic flow processing neurons. Here, we present
the fine-scale RFs of thousands of motion-sensitive neurons studied in the
diencephalon and the midbrain of zebrafish. We found neurons that serve as linear
filters and robustly encode directional and speed information of translation-induced
optic flow. These neurons are topographically arranged in pretectum according to
translation direction. The unambiguous encoding of translation enables the
decomposition of translational and rotational self-motion information from mixed
optic flow. In behavioral experiments, we successfully demonstrated the predicted
decomposition in the optokinetic and optomotor responses. Together, our study
reveals the algorithm and the neural implementation for self-motion estimation in a
vertebrate visual system.

Keywords: diencephalon, self-motion, optic flow decomposition, zebrafish, receptive
field, visually guided behavior, optokinetic response, optomotor response, matched
filter algorithm

Introduction

When you walk across a street, the image of the street is also shifted across your retina. This global retinal image shift induced by translational and/or rotational self-motion is known as optic flow (Gibson, 1954; Lappe et al., 1998; Nakayama and Loomis, 1974). Optic flow is used for self-motion estimation (Britten, 2008; Festl et al., 2012; Jr et al., 2001; Srinivasan et al., 1996; Warren and Hannon, 1988), which is a critical task for all visually guided navigation, as well as for gaze and posture stabilization behaviors.

The anatomical substrates associated with this task have been identified in a range of species. For instance, optic flow is processed in the medial superior temporal and parietal cortical areas in primates (Duffy and Wurtz, 1991, 1995; Luo et al., 2019; Sunkara et al., 2016; Tanaka and Saito, 1989; Warren and Hannon, 1988), the nucleus lentiformis mesencephali in pigeons (Wylie, 2000), and the lobula plate in flies (Krapp and Hengstenberg, 1996). In zebrafish, the pretectal area processes optic flow and is necessary for body position and gaze stabilization in optomotor responses (OMR) and optokinetic responses (OKR), respectively (Kubo et al., 2014; Naumann et al., 2016; Wang et al., 2019, 2020).

Knowing which neurons are involved does not answer how these neurons process optic flow and mediate stabilization behavior. For example, we cannot predict how an animal will respond to the optic flow induced by a banked turn, which contains both translation and rotation self-motion components. To answer this question, it is essential to reveal the underlying neural mechanism, or the algorithm, of optic flow processing. Theoretical studies have described several distinct biologically plausible algorithms (Dahmen et al., 2001; Koenderink and van Doorn, 1987; Longuet-Higgins and Prazdny, 1980). One of these algorithms, the "matched filter" model, suggests that motion receptive fields (RFs) of optic flow sensitive neurons form filters with similar structure to certain types of optic flow, i.e. each RF contains a vector field of locally preferred directions that matches a particular self-motion axis. These matched filters may then form a mathematical basis of self-motion induced optic flow and thus encode translation or rotation induced optic flow in a discriminable manner (Dahmen et al., 2001; Franz and Krapp, 2000).

In compact insect brains, systematic motion RF characterization has revealed the existence of such RF filters, which match certain types of translational or rotational optic flow (Huston and Krapp, 2008; Krapp and Hengstenberg, 1996; Wertz et al., 2009). However, there are many more neurons involved in optic flow processing in vertebrate brains than in insects. For example, the population of translation- and rotation-sensitive neurons in the pretectal area of larval zebrafish is at least 10 times larger than the population of horizontal system and vertical system neurons in blowfly (Krapp and Hengstenberg, 1996; Kubo et al., 2014). It is thus unclear, whether the matched filter algorithm discovered in the compact fly brain is also employed by vertebrate brains. Also, with greater number of neurons comes greater difficulty in systematic RF characterization. Although calcium imaging enables

recordings of hundreds of neurons simultaneously, no efficient approaches had been
available to characterize fine-grained motion RFs in vertebrate brains.

To overcome these limitations, we here made use of contiguous motion noise stimuli
and reverse correlation techniques developed recently for the systematic RF
characterization of motion-sensitive neurons via calcium imaging (Zhang and
Arrenberg, 2019). We measured the fine-grained motion RFs of thousands of
neurons in the pretectum and optic tectum of larval zebrafish. The identified RF
structures reveal a neural mechanism for robust optic flow encoding in the
pretectum. Furthermore, we show that larval zebrafish decompose translation and
rotation components in optokinetic and optomotor behavior as suggested by the
underlying encoding mechanisms.

Results

Identification of unimodal and bimodal receptive fields sensitive to motion stimuli

To estimate motion receptive fields (RFs), we used a full-surround cylindrical stimulus arena (Figure 1A) and recorded neuronal responses to motion stimuli in zebrafish larvae expressing the calcium indicator GCaMP6s. The stimulus consisted of a contiguous motion noise pattern in which moving directions were spatiotemporally coherent (Zhang and Arrenberg, 2019). Using reverse correlation, we estimated the RF by averaging across response-evoking stimulus frames and rejecting noise components based on a spatial directional bootstrapping statistic (Figure 1A, also see Figure S1 and method for details). We successfully identified the RF structures of 3,926 motion-sensitive neurons in the optic tectum and the pretectal area of seven fish. The shape, scale, location, and direction preference of these RFs were highly diverse, as illustrated by the estimated RF structures of the four example neurons in Figure 1A.

Despite the high structural diversity, we found that most estimated RFs (99 %), contained either one or two significant modes (Figure 1B), i.e. they could be classified into unimodal (or uni-partite) and bimodal (bipartite) RFs. The "mode" here is defined as a patch of spatially connected RF components. Although both unimodal and bimodal RFs can be found in optic tectum (OT) and the area pretectalis (APT, Figure 1B), most unimodal RFs are located in the OT and the bimodal RFs are predominantly located in the APT (Figure 1B).

Due to the fundamental structural difference of the unimodal and bimodal neurons, we characterized them in different ways. For unimodal RFs, we characterized the averaged preferred direction and mode center location. Consistent with a previous study (Wang et al., 2019), the preferred directions of most unimodal neurons were roughly corresponding to the up, down, left and right directions (Figure 1D), with only few neurons preferring oblique directions. The RF centers of most unimodal neurons (66.8%) in the APT but not the OT (45.8%) were in the lower visual field (the region below 0° elevation in Figure 1F).

Figure 1 Characterization of unimodal receptive fields (RFs). (A) Illustration of the RF estimation
method using a contiguous motion noise stimulus (see methods). (B) Histograms of RF mode number
for neurons in the optic tectum (OT), area pretectalis (APT) and adjacent brain regions. (C) Examples
of unimodal (upper row) and bimodal motion RFs (lower row). The direction and size of the arrows
indicate the local preferred direction and the motion sensitivity within the RF. (D) Anatomical
locations of neurons with unimodal RFs (n=3504, in 7 fish) The anterior-posterior (AP), dorsal-ventral
(DV) and left-right (LR) axes are labeled. (E-F) The distribution of averaged preferred direction and
center locations in the visual fields for unimodal RFs. Each dot in (F) indicates the center of an RF

Asymmetric location and patterned direction selectivity of the modes in bimodal RFs

For the bimodal RFs, the preferred directions and center locations were calculated
separately for each mode. We also calculated the distance between the two mode
centers (intermodal distance, illustrated in Figure 2B), as it's a good measure of the
span of bimodal RFs. As shown in Figure 2C, the intermodal distances ranged from
ca. 60° to 315° in our dataset (Figure 2C), and intermodal distances of 180° were
scarce. During the RF estimation experiment, the eyes of the whole-mounted fish
were in their normal resting position. According to a previous study (Bianco et al.,
2011), the binocular overlapping zone in this condition should be smaller than 30° as
illustrated in Figure 2D. Therefore, the bimodal RFs spanning across two sides of the
overlapping zone are classified as binocular RF. Based on this principle and the
intermodal distance, the bimodal RFs were divided into 3 groups: 1. Putative
monocular RFs receiving visual input from the nasal (-45° to + 45 °) and temporal end
(-168° to -90° or 90°to 168°) of a visual hemi-field (shown in red in Figure 2C & 2D);
2. Binocular RFs with short intermodal distance (average: ~150°, colored in green); 3.
Binocular RFs with long intermodal distance (average ~223°, colored in blue). For
most bimodal RFs, the mode centers were distributed asymmetrically in relation to
the anterior-posterior (AP) body axis as shown in Figure 2D and 4D.

Next, we compared the preferred directions within the two modes of each bimodal
RF by plotting the distribution of preferred directions in the left mode grouped by
their right mode preferred directions (Figure 2E). We found that the RFs preferring
leftward (clockwise from above) motion with their right modes are mostly preferring
the opposite direction (rightward motion) in their left mode (Figure 2E), and vice
versa. This architecture suggests the encoding of horizontal translational, but not
rotational optic flow. Among the neurons with vertical direction preferences in the
right mode (31 % of all bimodal neurons), 43% of them preferred motion in the
opposite direction in the left mode (corresponding to rotation), while the other 57%
showed similar direction preference (corresponding to lift translation, Figure 2E).

Figure 2 Inter-mode distances and preferred direction combinations of bimodal RFs. (A) Anatomical
locations of bimodal RF somata B) Illustration of inter-mode distance and mode-averaged preferred
directions (PD, large black arrows) for a bimodal RF. (C- D) Bimodal RFs grouped by their inter-mode
distance and locations in visual field. Each pair of linked dots in (D) indicated the mode centers of a
bimodal RF. The RFs tilted to the right hemi-field were colored darker for clarity. The approximate RF
distributions within the visual field are summarized on the right. (E) Polar histograms of the PD
combinations for all mode pairs grouped by the PD of their right modes (indicated by the arrow and
shade inside the polar histogram).

Complex bimodal RFs act as linear filters to encode optic flow directions

The directional preferences of the bimodal RFs (Figure 2E) implied these RFs may
have similar structures to specific optic flow fields. For example, the bimodal RFs

preferring leftward motion in its left mode and rightward motion in its right mode
might be similar to the translational optic flow field (TOF) resulting from forward
self-motion. And the RFs preferring upward and downward motion in their left and
right modes, respectively, might be similar to the rotational optic flow field (ROF)
resulting from roll. To quantify this similarity to optic flow fields, we calculated the
average cosine similarity of all unimodal and bimodal RFs to their closest TOF and
ROF (Figure 3A). The similarity can vary from -1 to 1, where 1 means in the regions
the RF covered, the RF structure is the same as the corresponding optic flow field,
and 0 means the RF is not similar to any optic flow field.

For most RFs (89%), both highly similar TOFs and ROFs existed (cf. dots whose
translation and rotation incongruity are both less than 0.2 in Figure 3B). These RFs
were called "simple RFs", because most of them are unimodal RFs (98%) of relatively
simple structure and small spatial extent, and thus they can be interpreted as parts
of TOFs and ROFs at the same time. Most of the other RFs were similar to either
TOFs or ROFs only (Figure 3B). These RFs were called "complex RFs" as they are
mostly bimodal RFs (82%) containing heterogenous vector field structures. In these
complex RFs, the 329 RFs which were more similar to TOFs were called translation
RFs while the 60 RFs similar to ROFs were rotation RFs. Two flow field examples for
translation and rotation RFs are shown in Figure 3D. Both simple and complex RFs
can be well explained by the fitted ROF and/or TOF (median cosine similarity = 0.98
and 0.92 respectively, Figure 3D). Only 23 of the 398 bimodal RFs were neither
similar to any TOF nor ROF (the ones in the upper right corner of Figure 3B). These
results suggest most bimodal RFs are similar to specific optic flow fields induced
either by translation or rotational self-motion components.

Figure 3 Prediction of optic flow responses in complex RF neurons with the matched filter model.
(A) The best matching rotational (red) and translational (blue) optic flow field for an example motion
RF (gray). (B) Score of the match of each RF to the fitted rotation (rot.) and translation (trans.) optic
flow field. Values below 0.2 (dashed lines) indicate good matched filter RFs; Trans./Rot. sim.:
translation or rotation cosine similarity. RFs within blue and red regions were defined as "complex".
(C) Similarities of the fitted optic flow fields for complex and simple RFs. (D) Two examples of rotation
(top) and translation (bottom) RFs (colored) and the matching optic flow fields (gray); (E) The
recorded maximum calcium responses of an example neuron to combinations of different optic flows
(OFs, lower left) compared with the matched-filter model predictions (lower right). Three example
OFs (1-3) were illustrated at the top and the neuron's corresponding calcium trace is shown in the
middle row. (F) The correlation of the recorded and predicted responses for complex and simple RFs.
(G) Bee swarm plot of the translation-rotation index (TR index, see methods) for neurons with
translation, simple or rotation RFs. The dashed lines in C and F and the red horizontal lines in G
indicated the median values of the corresponding distributions.

This finding is consistent with the observation in the blowfly, where the RF
organization of directional selective wide-field neurons were concluded to serve as
linear filters indicating the presence of particular self-motions (Franz and Krapp,
2000). To test whether or not these complex RFs in larval zebrafish play a similar
role, we displayed 36 distinct optic flow stimuli to the neurons whose RFs had been
characterized earlier. Each stimulus displayed a pure translation or rotation optic
flow, or a unique combination of translational and rotational optic flow with a fixed

time period of displaying and pause (a stimulus phase). The linear correlation of the
calcium responses during the 36 optic flow stimuli and the RF-based prediction of
calcium responses (Figure 3E and S2) was computed as the quantitative measure of
the prediction accuracy. The average correlation for the neurons with complex RFs
(0.81) was higher than the correlation for the neurons with simple RFs (0.65), which
suggests the complex RFs gave better prediction of the neural responses to optic
flow stimuli than the simple RFs (Figure 3F). We quantified the response specificity
to translation vs. rotation (TR index, see methods) and found that bimodal
translation neurons had a higher specificity for translation (average TR index >0.5,
Figure 3G) than rotation neurons for rotation (TR index ~ -0.3). The index distribution
of simple RFs did not show strong preference to either translation or rotation stimuli
as they were also active during presentation of combined rotation/translation optic
flow fields.

Together, these results suggest that the identified complex RFs act as linear filters to
process optic flow. Most complex RFs prefer either translation or rotation and not a
particular combination of the two.

Figure 4 A topographic map of global translation direction in the pretectum. (A) The preferred
translation directions of each translation RF indicated by a dot. (B) Anatomical locations of neurons
(n=329) with translational RFs, colored according to preferred translation direction in the horizontal

plane. The AMC pretectal region is contained within the horizontal dashed lines. (C) Linear regression (black dashed line, $R^2 = 0.714$) between the preferred translation directions and the locations of AMC neurons on the left-right body axis. The vertical dashed lines in B and C indicated the midline of the recorded brain regions. (D). The angular distance of mode centers in relation to the preferred translation directions (D1) and the symmetry (D2) of mode pairs relative to translation direction and body axis. (E) The responses of the neurons in the topographic map to translation optic flows with different direction and/or speed (indicated by the nodes in the upper left plot). The translation speed here are represented by the angular speed in the gray areas in the upper right plots. Two examples of OF stimuli are shown (① and ②) (F). The recorded response (upper row) and the fitted tuning model (lower row) for 4 example neurons. The response intensity is normalized by the averaged response amplitude for visualization. (G) The preferred translation speeds of the translation-sensitive neurons inferred from the fitted tuning map. (H) The discrimination index (DI) for the tuning to translation speed and direction of the 369 translation-sensitive neurons in the AMC of 2 fish.

Joint encoding of translational optic flow direction and speed

The encoding of global translation direction is essential for any visually guided locomotion. In the sections above, we showed the encoding algorithm (matched filter) implemented by the complex RFs of optic flow sensitive neurons. This allows us to directly infer the preferred translation direction of these neurons as the direction of the translational optic flow field matching their complex RFs the best (see Figure 3).

We plotted the azimuth and elevation of the contraction point or the focus of contraction (FoC) of the closest TOF to indicate the estimated preferred translation direction in Figure 4A. Consistent with Figure 2E, most of these neurons prefer translation directions close to the horizontal plane, and another, smaller proportion of neurons prefer vertical translational optic flows (Figure 4A).

The majority of these neurons were anatomically arranged in the anterior medial cluster (AMC) region (Kubo et al., 2014) of the APT (Figure 4B and S3). These neurons surprisingly formed a topographic map running from left-to-right across the midline according to preferred translation direction, with medial neurons preferring forward translation. Linear regression showed that the preferred translation direction is strongly correlated with anatomical position ($R^2 = 0.72$, Figure 4C). To visualize this anatomical arrangement further, we recorded the neural responses in the AMC to a translation optic flow stimulus, whose direction changed clockwise (CW) at a constant rate. As expected, the active region in the AMC gradually shifted from left to right, when the translation direction was smoothly changing (Movie S1).

There are different ways in which a translation-sensitive neuron could detect the direction of translational optic flow. For example, its complex RF could sample the contraction point, or the regions with stronger and more coherent local motion of the translation flow field. To identify how the zebrafish complex translation-sensitive RFs solve this task, we calculated the angular distance between mode center(s) and the preferred translation directions, including both unimodal and bimodal RFs in the analysis. We found that the mode centers of most bimodal translation RFs were located 60-90 degrees away from the preferred translation direction (Figure 4D-1), corresponding to regions with highest speed and strongest local motion coherence

in the optic flow field. Furthermore, we found the mode centers of most bimodal
translation RFs, which distributed asymmetrically in relation to the body axis (Figure
2D), to distribute symmetrically in relation to the preferred translation directions
(Figure 4D-2). Unimodal complex neurons, however, were distributed more widely
and located slightly closer to the translation contraction or expansion point (~51°
distance on average)

Since our RF characterization method has limited power in speed tuning estimation,
we perform an additional experiment to determine how direction and speed tuning
are combined in AMC neurons. We recorded their responses to translational optic
flow stimuli in 8 different horizontal directions at 5 different speed levels (7.5°/s to
120°/s) in random order (Figure 4E). To avoid the speed/distance ambiguity in
translational optic flow which is not the focus of our study, all visual cues in the optic
flow stimuli are equidistant to the animal. The maximal angular speed in the
translational optic flow is proportional to the fictive translation speed of the animal.
Thus we addressed this angular speed as the translation speed.

Many recorded neurons were jointly tuned to translation direction and speed (Figure
4F). We fitted the neural responses with a joint model of von Mises and lognormal
distributions to parameterize their preferred translation speed and direction
(examples shown in Figure 4F, see method for details). This joint model could explain
measured activity well for most neurons ($R^2 > 0.6$ for 324 out of 369 neurons, which
were used in the following analysis, Figure S4A). Most translation-sensitive neurons
preferred translational optic flow with maximum speeds in-between 15 to 40
degree/second (Figure 4G). The distribution of preferred directions was similar to
those measured in Figure 4A (see Supplementary Figure S4B for a comparison). To
estimate the fidelity of the joint speed and direction encoding, we computed the
discrimination index for the translation direction and speed for each neuron (using
the raw data but not the fitted model). A higher discrimination index means the
neural responses are more discriminable, which in turn, indicates the neuron is more
strongly tuned to the variable. We found that almost all neurons were tuned to both
translation direction and speed, while the tuning discriminability for translation
direction was slightly higher than that for translation speed in most neurons (Figure
4H).

Figure 5 Robust encoding of translational optic flow information by translation RFs. (A) The working principles of the constructed population decoder estimating the stimulus parameters from the responses of optic flow sensitive neurons (see Methods). (B) The translation direction estimated with the data presented in Figure 4E-F plotted in bee swarm style. Colored bars indicate ground truth horizontal translation directions and circles the estimations. (C) The translation speed estimated with the data presented in Figure 4E-H in bee swarm style. The dashed line indicates the line of unity. (D) The estimation errors of the translation directions of the optic flows containing translation and rotation components (mixture, illustrated in the top right image) or only translation components. The median errors are indicated by the dashed lines. (E) An illustration of the autoencoder constructed with the translation RFs for determining the direction of tampered or incomplete translational optic flow fields (TOFs, see Methods). (F-G). Bee swarm plots showing the estimation errors for the TOFs with different degrees of incompleteness (F) or tamper (G). The dashed lines and shaded area indicate the median ± the standard deviation. (H) The drifted distance over time of 100 simulated fish (black lines) using the population decoder in D to estimate and swim against the direction of ego motion (illustrated in the upper drawing). The gray lines correspond to the drifted distance when the simulated fish swam randomly.

Robust encoding of translation direction

So far we demonstrate the neural mechanism for optic flow processing implemented in AMC neurons, which in turn determine the observed neuronal preferences to e.g. translational vs. rotational optic flow. An essential question to ask is whether the information encoded by neurons with translation RFs is sufficient to estimate the translation direction and speed? In other words, can an animal successfully estimate their ego-motion direction and speed using solely the neural responses of these translation-sensitive neurons in the AMC region?

To answer this question, we first constructed a population decoder with the neural
response data collected for Figure 4E-H. This decoder is essentially a variant of the
maximum-a-posteriori decoder, which estimated the direction and speed of the
presented translational optic flow stimuli by minimizing the difference between the
recorded and predicted responses of the translation-sensitive neurons (Figure 5A,
see Method for details). Since the accuracy of any decoding algorithm is limited
under the Cramér Rao bound which is determined by the encoding information
(Abbott and Dayan, 1999), a low or no decoding error may prove the information
encoded by these translation sensitive neurons is sufficient, even if the decoding
algorithm implemented in zebrafish brain might be very different from our decoder.
To avoid circular reasoning, we split the data into a training set and a test set for
cross-validating the decoder accuracy (see Method for details).

In Figure 5B, the position of each circle represents the decoded translation direction
for each direction-speed parameter combination. The median decoding error for the
8 directions tested was 6.6 degrees which is very accurate given the low signal-to-
noise ratio (SNR) in the calcium imaging data. And the decoded results for different
directions did not overlap with each other. The median decoding error for
translation speed is 8.56 degree/second or 32.6% of the stimulus speed, however
the decoding results for different speed levels were often overlapping which
indicates a poorer performance of speed decoding than direction decoding (Figure
5C).

Translational optic flow field will be greatly affected by additional rotational optic
flow component (e.g. the shift of the FoC point and the changes of spatial
symmetry). To quantitatively determine whether the encoding of translation
direction is robust against rotational self-motion interference, we constructed
another population decoder with the stimuli and neural response data in Figure 3E-
G. While the previous decoder estimated the response likelihood [P(response |
stimulus)] based on the empirical likelihood distribution from the training set, this
decoder directly used the translational RFs and the matched filter algorithm to
determine the response likelihood.

As the decoder has no prior knowledge of the stimulus in this case, there was no
circular analysis problem, and we thus did not need to divide the data into training
and test sets.

The similar decoding error distribution for pure translational optic flow and the
translational optic flow superimposed with rotational optic flow fields suggests a
robust encoding of translation direction against interference from the rotation
components (Figure 5D, Movie S2). In other words, the translation information can
be extracted from the mixed optic flow field solely with the information encoded by
these translation RFs, which in turn, suggests a segregation of translational and
rotational optic flow information occurs already in these neurons.

In the natural environment, available optic flow fields may be incomplete or
corrupted due to sparseness of visual cues and interfering object motion. We are
interested to know how robustly the translation directions of incomplete optic flow

fields are encoded by these translation-sensitive neurons. Since their responses can be well predicted based on their RF structure (Figure 3F), the question is equivalent to asking how well these RFs can reconstruct the complete optic flow field from an incomplete input? Thus, we constructed an autoencoder whose encoder and decoder employ the same response functions determined by the corresponding translation RFs (Figure 5E). Again, the estimation error for translation direction was used as a measure of the reconstruction quality.

We first tested the reconstruction quality for translation optic flow fields with 100 different translation directions at 4 completeness levels (100%, 75%, 50% and 25%). For each TOF, an autoencoder was constructed with 50 RFs randomly sampled from the total 329 translation RFs(see methods for details). As expected, the estimation error gradually increased with the decreasing completeness levels, however even for the 25% completeness level in which most of the optic flow field is missing, the median estimation error was still below 20 degrees. It was only 5.7 degrees higher than the one for 100% completeness level (8.7 degrees, Figure 5F), suggesting that the corresponding RFs are well prepared to encode self-motion direction in environments with sparse motion information. Next, we tested the decoding accuracy for partially "tampered" optic flow fields, in which local object motion of up to 8 simulated objects had been inserted. For this type of interference, the decoding was less robust, especially when half or more than half of the visual field was covered by moving objects (Figure 5G). The median estimation errors for the 50% and 25% completeness levels (65 and 41degrees) were 2-3 times higher than the median error for 75% completeness (16 degrees). This poor performance was not surprising, since it is hard to distinguish the cues for global motion and object motion purely from the optic flow fields without additional information.

The robust encoding of translation direction is critical for many locomotor behaviors, e.g. for self-stabilizing behavior in water currents (Roeser and Baier, 2003). The continuous change of the water current direction and the relative distance to the surround alter the optic flow continuously, which requires fish to constantly adjust their swimming direction to maintain their body position. We were curious to see, whether the translation optic flow encoding algorithm implemented by these translation RFs is capable of such a complicated task. We constructed 100 random shape "ponds". In each of these simulated ponds, the water flowed at constant speed (1 a.u./iteration) in a random direction. The simulated fish then swam at the same speed into the directions estimated by the autoencoder from the instantaneous optic flow fields (Figure 5H, also see example fish in Movie S3). In most simulations, the total drifted distances were smaller than 1 a.u., which suggested that the translation RFs accurately encoded sufficient information in this highly dynamic process to determine appropriate translation directions for self-stabilization behavior.

Figure 6 Zebrafish decompose mixed rotation and translation optic flow in optokinetic and optomotor responses (OKR, OMR). (A) Illustration of the optic flow field composition resulting from the counterclockwise (CCW) turning of a forward moving fish. (B) Setup for simultaneous OKR (eye movements) and OMR (swimming trajectory) recording for freely swimming fish (see Methods). For OKR (right), saccades were removed to analyze cumulative slow phase eye movements. (C) The OKR and OMR upon optic flow stimuli containing translation and/or rotation components in 24 fish (black arrows on top indicate the OF stimulus composition; solid line: mean; shaded area: standard deviation across all fish). One example swimming trajectory is colored in red for each stimulus. "F", "B", "L", "R": the forward / backward / left / right direction, respectively. (D) Illustration of the OKR recording setup for agarose-mounted fish in a spherical water container. The agarose around the eyes was removed to allow free eye movement. (E) The eye position traces (mean ± standard deviation) across 18 trials recorded in five fish. The OF stimuli are illustrated on top. Dark gray corresponds to binocular overlap region and the curvy arrows in D and E indicate the average motion in each hemi visual field. Arrow thickness corresponds to the relative stimulus speed. ① and ② label two local features present when adding rotation on top of translation OF: the contraction point shifts and the unequal speed in two hemi visual fields. (F). Ocular vergence index for different OF patterns (based on eye traces in (E)). For comparison, we also simulated the vergence index (black mean ± std. error bars) expected for independently moving eyes responding to the average stimulus directions and speed in each hemi-field (using bootstrapping of local stimulus statistics, see Methods). 1 and 0 correspond to pure convergent/divergent and pure conjugate movement, respectively. The asterisk indicates significantly lower vergence indices compared to the other three groups. The "§" indicated a significantly lower measured ocular vergence index in comparison to the corresponding local flow statistic. The Ranksum test (α = 0.05) and Bonferroni correction was used to assess significant differences.

Distinct optokinetic and optomotor responses to translational and rotational components in complex optic flow field

Earlier, we asserted that without systematic characterization of neural mechanisms, we cannot even answer how will fish respond to the optic flow during a bank turn as it consists of both translation and rotation (Figure 6A). Now the neural mechanisms for optic flow processing have been revealed. The robust encoding of translation direction (Figure 5 and Movie S2) against the interference of rotational optic flow component strongly suggests translation and rotation information from the optic flow input are segregated in fish brain. It is thus very likely that fish will respond separately and simultaneously to the translation and rotation related optic flow components during any movements involving both translation and rotation.

To prove this, we selected the optomotor responses (OMR) and optokinetic responses (OKR) as two behavior readouts as they are tightly linked to optic flow perception and represent prominent stabilization behaviours in zebrafish (Kubo et al., 2014; Roeser and Baier, 2003). We recorded the OKR and OMR of 24 freely swimming fish to pure forward/backward translational and CW/CCW rotational optic flow, as well as to combinations of both.

As shown in Figure 6C and S6, fish responded to pure rotation with both OMR and OKR, as indicated by their circular swimming trajectories and conjugate eye movements. For the pure translation optic flow, fish swam with the optic flow direction, while clear conjugate or vergence eye movements were absent. Interestingly, when combinations of translation and rotation stimuli were presented, fish clearly swam with the translation direction while performing conjugate eye movements in the rotation direction, indicating the perception of both translation and rotation components in the optic flow stimuli (Figure 6 and S6).

Since OKR during translation stimuli may be disrupted by changes of head direction in freely swimming fish, we repeated the experiment in semi-restrained fish, which could not swim but were able to move their eyes (Figure 6D). In contrast to the results in freely swimming fish, the semi-restrained fish performed clear vergence eye movements to pure translational optic flows. For optic flow combinations, both semi-restrained and freely swimming moving fish showed conjugate eye movements without significant vergence components (Figure 6E). Together, these behavioral evidences suggest that translation and rotation components are perceived separately and simultaneously by zebrafish.

There are at least two local features that are different between the pure translational and the mixed optic flow: are the FoC position and the average motion speed of the left and right visual hemi-fields (cf. upper right illustration in Figure 6E). The head direction invariant OKR implied that the distinct processing of translation optic flow with or without rotational components does not rely on particular local motion features. To test this, we constructed two variants of translational optic flow. In the "slanted translation" variant, the translation direction of the pure translational optic flow field was shifted so its FoC was at the same position as the one in the mixture of translation- and rotation-induced optic flow field. The average speed in

the left and right halves of the "asymmetric translation" optic flow fields was altered
to mimic the different speed in the mixture optic flow field. The OKRs to these
stimuli were slightly different from the ones to pure translation optic flow, however,
none of them could be classified as conjugate eye movements (Figure 6E).

We quantified the extent of conjugate vs. vergence eye movements using a vergence
index (Figure 6F, 1 = pure vergence movement; 0 = pure conjugate movement; see
method for details). The vergence index for the translation optic flow combined with
a rotation component was significantly shifted towards conjugate eye movements in
comparison to all other translation stimuli, while the vergence indices for the various
translation stimuli were similar to each other (Figure 6F, Wilcoxon rank-sum tests).
Furthermore, each vergence index (except for the "asymmetric translation"
stimulus") was slightly shifted toward conjugacy in comparison to what would be
expected based on the distribution of local velocity vectors in the optic flow field
(see black crosses in Figure 6F which show the bootstrapped null distribution).
Together, these results show that the animal cannot be tricked into processing
rotational motion when only certain local aspects of rotational flow are
implemented in overall translational flow patterns.

Discussion

Via the systematic characterization of fine-grained receptive field structure of motion-sensitive neurons in the optic tectum and pretectal area, we revealed that many neurons, especially pretectal ones, perform large-scale motion integration with their bimodal RFs. Most of these RFs belong to a novel RF class, complex RFs, and play a pivotal role in encoding translational and rotational optic flow. By revealing the algorithms implemented in these complex RFs for optic flow encoding, we successfully demonstrate how the encoding properties, such as translation/ rotation selectivity may emerge from these complex RFs. We used this information to uncover a topographic map of preferred translation directions in the AMC region of the pretectal area, and most of the motion-sensitive neurons in this map were found to jointly encode both the speed and the direction of translational optic flow.

Furthermore, we demonstrate that the information encoded by the translation-sensitive neurons with their complex RFs is sufficient for determining the direction and speed of the translational self-motion component. Moreover, the encoding is robust against corruption of the optic flow field and against interference from additional rotational components. Finally, optokinetic and optomotor behavioral responses clearly showed that zebrafish decompose the translation and rotation components from the combinatory optic flow.

Complex RFs implement the optic flow detection algorithm

The perception of self-motion requires large scale integration of local motion information. The corresponding neural correlates for this integration have been discovered in many different regions in the visual system from insects to primate (Eckmeier et al., 2013; Egelhaaf, 2002; Horseman et al., 2011; Huston and Krapp, 2008; Joesch et al., 2008; Stone et al., 2017; Sunkara et al., 2016). It has been proposed for a long time that there is a tight link between the RFs and the optic flow tuning properties of corresponding neurons. However due to the throughput limit of RF estimation methods, this link has only been demonstrated in insects with a small number of neurons involved (Egelhaaf, 2002; Franz and Krapp, 2000). To our knowledge, this is the first study that systematically estimated the detailed RF structure of optic flow processing neurons in a vertebrate animal model. The feasibility to estimate the 3926 motion RFs reported here, hinged on the availability of a fast, multiplexed RF estimation technique developed for calcium imaging (Zhang and Arrenberg, 2019). The RF structures of the global motion sensitive neurons revealed in this study showed remarkable similarity to translational and rotational optic flow fields (Figure 3C). This observation is consistent with the previous studies lobula plate tangential cells (LPTC) in flies for which a "matched filter" model has been proposed (Franz and Krapp, 2000; Krapp and Hengstenberg, 1996; Krapp et al., 1998). In short, this model suggests the LPTC neurons may filter impinging optic flow fields with their RFs, resulting in a stronger response for an optic flow field matching the RF structure (Franz and Krapp, 2000). The calcium responses of our complex RF neurons, especially the ones with translation RFs, are well described by this model

(Figure 3F, Figure S5). Furthermore, we establish how the translation/rotation
preference may emerge from complex RF structure as a result of this linear filter and
show that the level of remaining unexplained response modulation is small for most
of the complex RF neurons.

In contrast, the responses of the simple RF neurons frequently differed from the
predictions of the matched-filter model. For a fraction of neurons, the responses to
optic flow mixtures were even opposite to the prediction based on the measured RF
(correlation <0 in Figure 3F, Figure S5). This finding is quite unexpected, because
their RFs, as the name suggests, should be rather simple. The poor prediction for
simple RFs suggests that our RF estimates were missing important functional aspects
for these neurons. One possibility is that many of these neurons had suppressive RF
components remaining undetected in our RF estimation. In neurons with low
baseline activity, inhibition (or in general activity suppression) is notoriously hard to
demonstrate via calcium imaging (Zhang and Arrenberg, 2019). A previous study
(Wang et al., 2020) showed that about 80% of the motion-sensitive neurons in the
optic tectum have suppressive surround structures, i.e. they were suppressed when
the motion stimulus covered too large a region of visual space. Therefore, it is very
likely that many of our simple RF neurons had additional suppressive components in
their RFs. Similarly in the salamander retina, some local motion sensitive retinal
ganglion cells (RGC) are also suppressed by large scale motion (Kühn and Gollisch,
2016). An alternative (and not mutually exclusive) explanation for the observed
prediction discrepancy is that our simple RF neurons carry out functions in the visual
system, which are only distantly related to optic flow encoding. Further investigation
is needed to characterize inhibitory components and functions of simple RF neurons
in the brain.

A topographic map of preferred translation directions in the AMC pretectal region

Within the pretectal AMC region, translation-selective neurons are arranged
according to preferred translation directions in a single topographic map that spans
both pretectal hemispheres (Figure 4B-C, Movie S1 & S2). Previous reports already
revealed differential directional processing across pretectal locations and related
these direction-selective neurons to the triggering of optomotor responses (Kubo et
al., 2014; Naumann et al., 2016; Wang et al., 2019, 2020; Yildizoglu et al., 2020).

These results agree with our findings despite major differences in employed visual
stimulus setups. In the studies by Naumann et al. (2016) and Yildizoglu et al. (2020),
motion stimuli were projected on a flat screen from below, which can be interpreted
as the bottom part of a translational optic flow field. For example, the nasal-
temporal-ward motion covering the bottom visual field can be interpreted as the
bottom part of a translational optic flow field resulting from forward self-motion.
Using this interpretation, the topographic map of translation direction found in this
study (Figure 4B) is consistent with the direction map described in the previous study
(Naumann et al., 2016, Figure 3A) in terms of the preferred direction in different
regions of the AMC. Furthermore, our results show that this pretectal structure

encodes the translation axes of optic flow rather than local motion directions for each eye. Unfortunately, RF structures in the peripheral lower visual field (<-40° elevation) could not be estimated due to the hardware limitation in our study. A whole field stimulus display setup will be desired for estimating the complete RF structure in the entire visual field.

Robust and unambiguous coding of translation direction in translation RFs

The estimation of the translation direction requires the integration of motion from different parts of the visual field. In principle, this information can be encoded either by the complex translation RFs as shown in this study, or a population of neurons tuned to more simple and basic motion features, such as the direction-selective retinal ganglion cells (DSRGCs) in mouse retina described in a previous study (Sabbah et al., 2017). However, with the latter encoding strategy, the translation direction cannot be extracted as a standalone feature because of the encoding ambiguity due to the absence of translation selectivity. In other words, without additional decoders, it is not possible to discriminate translational optic flow from other types of optic flows from the population code. Carlson and Kawasaki (2006) showed – for a different sensory modality - how such an ambiguous representation of stimuli will eventually result in the confusion in behavioral responses to distinct features. And this is not observed in zebrafish responses to the mixture of translational and rotational optic flow (Figure 6). Therefore, we hypothesize that our identified population of pretectal neurons with complex RFs directly extract and convey the translation direction to the motor system. These neurons and thus forms a visual encoding pivot before information is passed on to premotor areas.

Furthermore, in Figure 5 we showed the population code of translational optic flow is robust against loss or tamper of optic flow field. This explained why motion in relatively small parts of the visual field can already trigger strong OKR and OMR (Dehmelt et al., 2020; Kist and Portugues, 2019; Wang et al., 2020), which is a result that seems puzzling at first glance when considering the optomotor response as a "whole field" stabilization behavior.

How is speed information used?

Besides translation direction, speed is another critical factor for locomotor behavior. Larva zebrafish can adjust their swimming behavior to match the speed of wide-field visual motion stimuli (Portugues et al., 2015; Severi et al., 2014). While neurons tuned to different translation directions have been found in many species, for example the LPTC neurons in *Drosophila* and blowfly (Evans et al., 2019; Karmeier et al., 2003; Longden et al., 2017), the uvula/nodulus neurons in pigeon's cerebellum (Pakan and Wylie, 2006), and the medial superior temporal (MST) neurons in primates (Duijnhouwer et al., 2013), little is known about their speed tuning properties. Here we show that most translation-sensitive neurons in the AMC region are jointly tuned to both translation direction and speed (Figure 4G), and the speed information can be encoded (to a certain extent) by their neural activities (Figure 5C). However, these findings only tackle the tip of the iceberg of the speed integration problem. The speed of motion cues in a naturalistic translational optic

flow depends on their depths and locations in the visual field (Koenderink and van
Doorn, 1987). To robustly determine the translation speed in the naturalistic
environment, these translation-sensitive neurons in the AMC regions might need
access to the depth information and also need to exclude disturbing motion cues not
related to translation optic flow. How these multiple features of visual stimuli get
integrated in the zebrafish brain, and possibly within the AMC region, requires
further investigation.

Represented optic flow axes

We noticed there are some invariant properties across RFs in the optic tectum and
pretectum: I) the preferred directions for both the unimodal and bimodal RFs are
biased toward either horizontal or vertical motion, with only a few neurons
responding to oblique motion (Fig. 1D and 2E) (Hunter et al., 2013; Lowe et al., 2013;
Wang et al., 2019); II) bimodal vertical neurons together encode translation and
rotation, where most bimodal horizontal neurons encode translation; III) the modes
of bimodal translation RFs are mostly distributed symmetrically in relation to the
preferred translation direction which does not coincide with the animal's
longitudinal body axis as shown in Figure 2D and 4D; And IV) most bimodal RF
centers are located 45° to 90° degrees away from the translation directions (Figure
4D), where motion speed and direction coherence is maximal ("hot zone"). These
properties together constrain the preferred translation directions of the bimodal RFs
(cf. Figure 4A). Few RFs are tuned to oblique translation directions (combinations of
horizontal and lift/weight translations) as these optic flows contain oblique local
motion in the "hot zone" of the RFs. It is unclear at this point, what the specific
advantages of this layout are. One possibility is that this representation serves to
improve the coding efficiency by balancing the needed number of active neurons
(sparseness) and the needed total neuron number: the orthogonal representations
could form a mathematical basis, so that oblique directions could be encoded by the
activity of (at least) two neurons with orthogonal preferred directions. Our decoder
simulations show that the relatively rich representation of horizontal directions can
be beneficial for targeted locomotor responses in the horizontal plane, e.g. during
OMR (Fig. 5H). However, spontaneous swimming as well as prey capture behavior
includes frequent locomotor deviations from the horizontal plane (Bolton et al.,
2019; Ehrlich and Schoppik, 2017) as well. The surprising scarcity of representations
of yaw rotation suggests that it is negligible in visual brain areas of the zebrafish.
Possibly, inhibitory outputs of translation-selective neurons could be integrated in
downstream neurons to signal the presence of rotation stimuli. Furthermore, each
eye can, to some extent, correct for horizontal image slip by itself, potentially
making a binocular rotation representation dispensable.

Decomposition of translation and rotation self-motion components

In the behavioral sequence of prey capture in zebrafish characterized by a recent study, three motion components are superimposed in the retinal projection of the optic flow field: the translation component from the forward swimming behavior, the rotation component from turning behavior, and the object motion component from the prey movement (Bolton et al., 2019). The ability of the animal to hunt and orient in the environment suggests that decomposition of these motion components must occur, but how and to what extent flow decomposition occurs in vertebrate animals had been unclear.

While evidence for separate processing of translation and rotation information in the corresponding neural correlate has been presented before (Kubo et al., 2014; Sunkara et al., 2016; Wang et al., 2019; Wylie, 2013), our study shows that translation/rotation sensitive neurons are not exclusively responsive to pure translational/rotational optic flow, but also respond to the mixed optic flows in a predictable manner (Figure 3). Furthermore, the population encoding of translation direction is robust against rotation interference (Figure 5D and Movie S2), which indicates that the zebrafish pretectum decomposes translation and rotation components and is biased towards the identification of translation components. In contrast to translation RFs, the responses of rotation-sensitive neurons to mixed optic flow stimuli are often strongly modulated by the non-preferred (translation) components and poorly explained by their RF structure (Figure S5). In a previous study, two types of translation-sensitive neurons have been found in primate parietal cortex: neurons only tuned to translation components of a given optic flow fields, and neurons modulated by both translation and rotation components (Sunkara et al., 2016). The latter are suggested to provide a joint representation of translation direction and rotation velocity which may contribute to the decomposition of translation and rotation components in complex optic flow fields. It remains to be answered whether these rotation-sensitive neurons in zebrafish are similar to the neurons jointly representing translation and rotation components in primate parietal lobes, and what role they do play in optic flow decomposition.

The translation and rotation filters implemented in pretectal neurons provide the substrate for the decomposition of global motion components in visually guided behavior. The OMR and OKR are two prominently studied visually guided behaviors, and their correspondence to translational and rotational self-motion, respectively, have been investigate separately before (Kist and Portugues, 2019; Maaswinkel and Li, 2003; Marques et al., 2018; Qian et al., 2005; Rinner et al., 2005). However, it was unknown whether the translation- and rotation- induced optic flow components, can guide the OMR and OKR in separate ways, or in other words, do zebrafish "decompose" these global motion components in their OKR and OMR behavior? Here we answered this question by recording OKR and OMR simultaneously in freely swimming larvae. Fish clearly processed the translation- and rotation-induced components in the presented optic flow stimulus separately, as they were swimming toward the corresponding translation direction implemented in the optic flow field while performing OKR in the direction of rotation. Apparently the OMR is predominantly modulated by the translation-induced components (Figure 6C), while

the OKR is more sensitive to the rotation-induced components of the optic flow
stimuli (Figure 6C, E and F). The local velocity vector statistics of the rotation-induced
optic flow component, but not the translation-induced optic flow component does
not vary by horizontal fish body orientation. This difference is also reflected in the
OKR of freely swimming zebrafish: for the pure translational optic flow we observed
vergence OKR in head mounted fish but not in freely swimming fish, while the
conjugate OKR to the optic flow stimuli with rotational component can be observed
in both cases. This result also implies the discrimination of optic flow with and
without rotational component does not rely on local features at certain positions of
the visual field which will vary during head direction changes. Instead, the isolated
local features resulting from rotational component interference were unable to
trigger conjugate eye movements (Figure 6E&F), suggesting the integration of local
features but not a specific local feature is essential for the optic flow processing in
zebrafish. It will be interesting to determine the full neural circuit for this
decomposition in the future, including the connectivity of translation-sensitive
neurons in AMC (Kramer et al., 2019)

In summary, we have systematically characterized the receptive field properties in
zebrafish visual brain areas that help us to reveal a neural mechanism for optic flow
processing. Our results suggest that individual neurons form matched filters to
extract translation and rotation self-motion components from optic flow. We
identified an anatomically ordered arrangement of different functional cell types,
which, as a population, decompose rotational and translational self-motion
components of the animal. Future work is needed to show, how these cellular
building blocks are wired together in a hierarchical circuit to mediate visually driven
reflexes and voluntary behaviors.

Materials and methods

Ethical approval

All animal experiments were licensed by the local authorities (Regierungspräsidium Tübingen) in accordance with German federal law and Baden-Württemberg state law.

Animal preparation

Zebrafish (Danio rerio) were maintained on a 14/10h light–dark cycle at 28°C. The transgenic zebrafish line *Tg(elavl3:nls-GCaMP6s)mpn400* was used for the *in vivo* two-photon calcium imaging (Dal Maschio et al., 2017). The top 10 - 20% of larval zebrafish with high calcium indicator expression levels and strong optokinetic responses (OKR) to moving gratings were selected from all hatched fish at 4-day post-fertilization (dpf) for *in vivo* calcium imaging experiments.

5-7 dpf zebrafish larvae carrying mutations in the mitfa gene (nacre)was used for OKR and optomotor responses (OMR) recordings. Again, the top 10-20% larval zebrafish sensitive to visual motion stimuli indicated by their strong OKR to moving gratings were selected at 4 dpf for these behavioral experiments.

All behavioral and *in vivo* calcium imaging experiments were performed on 5-6 dpf larval zebrafish at room temperature.

Visual stimulation setup

All visual stimuli used in this study were displayed on a custom-built cylindrical green LED arena (160 mm height, inner diameter = 198 mm) covering 336°-by-80° of the visual field (-168° to 168° in azimuth; -40° to 40° in elevation). The 2 halves of LED arena consisted of 224 square LED tiles (8 rows × 14 columns × 2 arena halves); each tile had 8×8 evenly distributed LEDs emitting at 570nm (Kingbright TA08-81CGKWA). Each LED covered ˜1.5 visual degrees on average, note the coverage on vertical direction varied slightly with the latitude of LEDs. All stimuli displayed in the arena had 100% contrast as the LEDs in the stimuli were either on or off. All LED tiles were covered with a diffusion filter foil (LEE no. 252, article 595-1780-2520) and a high-pass filter foil (LEE no. 779, article 595-1700-7790, castinfo.de, Hagen, Germany) for light homogenization and light interference reduction in calcium imaging respectively.

The custom software developed in previous studies (Joesch et al., 2008; Reiser and Dickinson, 2008) was used for stimulus uploading and display control. To minimize the interference of LED light with the calcium imaging, the LEDs were flickering in a duty cycle to be switched on only during the fly-back time of the scanning mirrors in-between line scans.

Contiguous motion noise stimulus

The contiguous motion noise (CMN) stimulus for motion RF estimation was constructed as described in our previous study (Zhang and Arrenberg, 2019). Briefly, the optic flow in the CMN stimulus was determined by a three-dimensional (8 rows × 28 columns x 12000 frames) motion vector noise matrix, in which motion vectors were spatiotemporally correlated. The vector length and direction indicate the motion speed and direction in the corresponding local region. The spatiotemporal correlation in the noise was achieved by convolving a white vector noise matrix with a multidimensional Gaussian kernel ($\mu_{x,y,t} = 0$, $\sigma_{x,y} = 18.78$ visual degrees, $\sigma_t = 0.33$ seconds). The spatiotemporal correlation in our stimulus may introduce bias to the RF estimation, i.e. overestimation of the local coherence in the RF. The spatiotemporal extent of this bias was quantified as the contiguous radius (CR) of the CMN stimulus for which the pairwise vector correlation surpassed 0.1. The CR is calculated as:

$$CR = 2\sigma\sqrt{-\ln(0.1)} \approx 3.03\sigma$$

The CR in spatial and temporal domain are therefore 57 (3.03×18.78) visual degrees and 1 (3.03×0.33) second respectively.

The noise vector matrix was then transformed to a 64 (row) × 224 (column) × 12000 (frame) binary movie displaying at 15 frame-per-second (fps) with the Reichardt encoder described previously (Zhang & Arrenberg, 2019). Each motion vector in the noise vector matrix was approximated by the displacement of the binary noise pattern displayed on an 8×8 LED patch at the corresponding position on the arena. The spatial frequency of the 224 binary noise patterns (one for each LED patch) was set to 0.1 cycles per visual degree which is optimized for visual motion perception in larval zebrafish (Rinner et al., 2005).

The speed distribution of the CMN stimulus follows the Rayleigh distribution:

$$s(x) = \frac{x}{\sigma^2} e^{\frac{-x^2}{2\sigma^2}}$$

, where $\sigma = 12.35$ visual degrees/second. Therefore, the speed in 95% of the pixels in our CMN stimulus movie was contained in the range between 0 to 30 visual degree/second.

Optic flow stimuli design

Similar to the CMN stimulus, the optic flow stimuli were designed in vector field forms with the same spatial resolution (8×28) as in the CMN stimulus, and they were converted to binary noise movies by the same Reichardt encoder to be displayed on the LED arena. The rotational ($\vec{V}_{rot}$) and translational optic flow vector fields ($\vec{V}_{trans}$) were constructed as following:

$$\vec{V}_{rot} = -\vec{P} \times \vec{R},$$

$$and \ \vec{V}_{trans} = \vec{T} - (\vec{P} \cdot \vec{T})\vec{P}$$

$\vec{P}$ is a unit vector point from the observer (the origin) to the location P in the visual field. $\vec{T}$ and $\vec{R}$ are the unit vectors indicating the translation direction and the rotation axis of the translational and the rotational optic flow fields respectively. The operations <×> and <·> are the cross and dot products of two vectors respectively. And a mixture optic flow containing both translation and rotation components can be obtained as:

$$\vec{V}_{mix} = w_{trans}\vec{V}_{trans} + w_{rot}\vec{V}_{rot}$$

,where the w_{trans} and w_{rot} represent the relative strength of the translation and rotation components in the mixed flow field.

The speed of motion cues in a translational optic flow field depends on both their locations in the optic flow field and the distance to the observer. As this study is not focused on the distance effect, all motion cues in our optic flow fields were set to be equally distant from the observer. To correct the projection distortion of the optic flow fields on the cylindrical LED arena, the optic flow fields calculated above ($\vec{V}_{raw}$) were transformed as following:

$$\begin{aligned}
\vec{V}_{corrected} &= \mathbf{D}\left(\vec{V}_{raw} - (\vec{V}_{raw} \cdot \vec{N})\,\vec{N}\right), \\
where \ \vec{N} &= \frac{(x, y, 0)}{|(x, y, 0)|}, \\
and \ \mathbf{D_i} &= \frac{r}{\cos(\theta)} = \frac{r}{\sqrt{1 - z^2}}
\end{aligned}$$

, where the x, y, z are the LED locations in the Cartesian coordinate system where the origin is the location of the observer, and θ is the corresponding elevation angle.

In the translational optic flow fields, the motion speed is maximum at the locations S which are perpendicular to the translation direction ($\vec{S} \perp \vec{T}$). For convenience, the translation speed of a translational optic flow field was defined as the speed in these locations (circled region in the illustrations of Figure 4E).

In vivo two-photon calcium imaging and data preprocessing

The selected fish were immobilized in 1.7% low melting-temperature agarose (wt/vol, E3 medium) at the tip of a transparent plastic triangle stage (tip angle < 45%, Figure S9) on the experiment day. The triangle stage with the mounted fish was later placed in the center of a spherical glass container filled with transparent E3 medium. Then the water container was fixed on a metal holder placed in the center of the LED arena. The body position and orientation of the mounted fish was adjusted so it was

centered in the LED arena with the dorsal side facing up (roll correction) and the noise pointing straight to the front (0° azimuth and elevation) without any tilting.

The calcium activities in neuron soma were recorded with a movable objective microscope two-photon setup (Sutter Instruments, Novato, California, USA; Euler et al., 2009) coupled to a Coherent Vision-S Ti-Sa laser. The emitted fluorescence light of the calcium indicator protein, GCaMP6s, triggered by the excitation laser beam at 920 nm (prepulse compensation: 9756 fs^2) was collected with a 20x/1.0 Zeiss objective using an emission dichroic with bandpass 500–550 nm. The image time series were recorded using MScan software (Sutter instruments). The calcium images acquisition rate was 2 fps at 512 × 512 pixel^2 and a magnification of 2 (0.44 × 0.44 μm^2 per pixel).

The midbrain and diencephalon of mounted fish were sampled in the calcium imaging recording in dorsoventral direction from 20 μm to 120 μm below the top of tectum with the step size 10 μm. The motion artifacts along the recording plane (XY plane) were corrected, and all visible neuron soma in the time-averaged image of the corrected recording video were automatically selected as region-of-interests (ROIs) by a marker-controlled watershed algorithm. Per-ROI calcium time series were extracted as the sum of all pixel values within the ROI for each frame.

A 3D z-stack that imaged along the dorsal-ventral axis from the top of tectum to deep ventral pretectum and dorsal thalamus (step size: 0.44 μm) was recorded for each fish. The ROIs in each recording were first registered to the corresponding z-stack. The neurons recorded in different fish were registered to the z stack of *Tg(elavl3:Hsa.H2B-GCaMP6s)mpn400* transgenic line provided by the Max Planck zebrafish brain atlas (mapzebrain) by registering the ROIs in each recording to the corresponding z-stack aligned with the atlas z-stack with a custom-written Matlab program.

High throughput motion RF estimation

The high throughput motion RF estimation method used in our study was described in detail in a previous study (Zhang and Arrenberg, 2019). Briefly, the neural responses to the CMN stimulus were recorded with *in vivo* calcium imaging. As the abrupt, high amplitude increases of somatic calcium signals are usually correlated with significant increases of neural firing rate, these events were detected in the calcium traces and extracted for each ROI to obtain a binary event train (0 = no event, 1 = event detected). ROIs with event trains that only showed sporadic activity (#events/#stimulus frames < 8 %) were excluded for the following steps as we found only few of them could yield successful RF estimations with this method.

For each event train, an event triggered average (ETA) was computed as the raw RF estimation as follows:

$$ETA = \frac{1}{n_{event}} \Sigma_{i=1}^{I} e_i B(\vec{V_i})$$

$$n_{event} = \Sigma_{i}^{I} e_i$$

The e_i was the event state (0 or 1) for the ith stimulus frame, and I is the total number of frames in the stimulus. To avoid the ambiguity in the vector summation, the corresponding motion vector field of the ith frame $\vec{V_i}$ was transformed into a sparse, one-hot representation $B(\vec{V_i})$ where the phase angles of motion vector are evenly divided into 16 direction bins as described in the previous study (see Zhang & Arrenberg, 2019 for details). For instance, for a vector $\vec{v}$ in $\vec{V_i}$ whose phase angle is in the range of the k^{th} direction bin, its one hot transformation $B(\vec{v})$ will be a 16-element array where the k_{th} element is the vector norm $|\vec{v}|$ and the other elements are 0. Therefore, the size of these ETAs was 8 row×28 column×16 direction bins.

To identify the spatially connected ETA components significantly related with RF structures, a two-step non-parametrical cluster-based bootstrapping test (2-step NCB test) is applied (see Zhang and Arrenberg, 2019 for detailed explanations). For the sake of clarity and convenience, the identified ETA components were converted from the one-hot representation form back to the vector field form for the downstream analyses and visualization. An RF mode is defined as a cluster of the spatially connected ETA components. The center and preferred directions of RF modes were calculated as the averaged location and preferred direction of the components in each mode.

Fitting translational and rotational optic flow fields to RFs

To determine the similarity of the estimated RF to translational or rotational optic flow fields, we identified the most similar translational and rotational optic flow field for each RF estimation by fitting the optic flow fields to RF estimations with the least squares estimation method. The residual sum of squared angular difference (RSS_{angle}) between an RF estimation ($\vec{E}$) and the fitted optic flow field ($\vec{F}$) were calculated as:

$$RSS_{angle} = \Sigma_{i=1}^{I} \angle\left(\vec{E_i}\vec{F_i}\right)^2$$

$$\angle\left(\vec{E_i}\vec{F_i}\right) = \arccos\left(\frac{\vec{E_i} \cdot \vec{F_i}}{|\vec{E_i}||\vec{F_i}|}\right)$$

And the fitting problem can be solved by searching the translation/rotation axis that minimized the RSS_{angle}. The similarity between the fitted translation/rotation flow fields and the motion RF estimations were calculated as the averaged cosine similarity between each vector pair of the RF-related ETA components and the optic flow fields:

$$Similarity = \frac{1}{I} \Sigma_{i=1}^{I} \frac{\vec{E_i} \cdot \vec{F_i}}{|\vec{E_i}||\vec{F_i}|}$$

940   The translation and rotation statistics in Figure 3B is calculated as 1-Similarity.

941   In addition, the symmetry of bimodal translation RFs in relation to the preferred
942   translation directions in Figure 4D-2 was calculated as:

943
$$\text{Symmetry} = 1 - abs\left(\frac{2\angle(\vec{\Delta}_{center}, \vec{T})}{\pi} - 1\right),$$

944
$$where\ \vec{\Delta}_{center} = \mu_{left} - \mu_{right}$$

945   The μ_{left} and μ_{right} are the left and right mode center positions of the bimodal RFs.
946   The bimodal RF is most symmetric when the vector linking its mode centers is
947   perpendicular to its preferred translation direction ($\angle(\vec{\Delta}_{center}, \vec{T}) = \frac{\pi}{2}$).

Optic flow preference of motion-sensitive neurons

To determine how well the responses of corresponding neurons to optic flow can be
explained by their RFs, we recorded the calcium responses of neurons in optic
tectum and the pretectal areas to the translational and rotational optic flow in 6
orthogonal directions and the 24 combinations of these translational and rotational
flow displayed in random order (Figure 3E). Due to the memory limitation of our
stimulus setup, we were unable to test all the combinations of translation and
rotation optic flow fields, the 12 untested combinations were colored in white in
Figure 3E. The maximum speed for all optic flow stimuli were 30 degree/seconds.
The translation and rotation component in the mixture optic flows were mixed in the
ratio of 2:1 (w_{trans} and w_{rot}).

Each optic flow stimulus was displayed at 15 fps for 4 seconds followed with a 6-
second pause before switching to next stimulus. The binary noise pattern of the last
frame of the previous stimulus phase lasted over the pause period to become the
first frame of the next stimulus phase, so the stimuli were switched seamlessly. After
all optic flow stimuli had been displayed, the CMN stimulus was displayed for RF
estimation.

The means and standard deviations of calcium fluorescence activities of each ROI in
the 16-second period before and after all stimuli had been displayed were measured
as μ_{init} / μ_{end} and σ_{init} / σ_{end}. The ROIs whose $|\mu_{init} - \mu_{end}| > 4\sigma_{init}$ and/or
$\sigma_{init}/\sigma_{end} > 4$ were excluded as either they might be bleached or drifted out of the
imaged region. The calcium activities of the remaining ROIs were converted into z-
score calcium traces as follows:

972
$$\text{Z-score} = \frac{F - \mu_{init}}{\sigma_{init}}$$

973   The z-score calcium traces (2 fps) were upsampled to match with the stimulus frame
974   rate (15 fps). The response intensity (R) for each stimulus phase was calculated as:

975
$$R = \max(R_{max} - R_{init}, 0)$$

976 R_{max} is the maximum normalized calcium activity (z-score) in a stimulus phase and
977 R_{init} corresponds to the normalized activity in the first frame of the stimulus phase
978 (same as the last frame of the pause). Only the ROIs with estimated RFs and strong
979 responses to optic flow stimuli ($max(R) > 3$) were selected. The RF-predicted
980 responses ($R_{prediction}$) to these optic flow stimuli ($\overrightarrow{GF}$) were calculated as follows:

981
$$R_{\text{prediction}} = max\left(\frac{1}{N}\Sigma_{n=1}^N \frac{\overrightarrow{RF_n} \cdot \overrightarrow{GF_n}}{|\overrightarrow{RF_n}||\overrightarrow{GF_n}|}, 0\right)$$

982 N is the number of significant components in the RF estimations, $\overrightarrow{RF_n}$ and $\overrightarrow{GF_n}$ are
983 the vectors of the n^{th} components in the RF and in the optic flow field respectively.
984 Note in the following section, this function will be addressed as the "RF-based
985 response function".

986 The translation-rotation index (TR index) was computed as:

987
$$\text{TR index} = \frac{Rmax_{trans} - Rmax_{rot}}{Rmax_{trans} + Rmax_{rot}}$$

$Rmax_{trans}$ and $Rmax_{rot}$ are the maximum response intensity of all pure translation or
rotation optic flow stimuli respectively.

Direction and speed tuning of translation sensitive neurons

To determine the tuning properties of the translation-sensitive neurons found in the
pretectal area, we measured their responses to the translational optic flows moving
in 8 horizontal directions (azimuth: 0°,45°,90°,135°,180°,225°,270°,315°; elevation:
0°, Figure 4E) and 5 speed levels (7.5, 15, 30, 60, 120 degree/seconds). Each stimulus
phase lasted for 15 seconds, including a 5-second moving phase and a 10-second
pause phase. The stimuli were displayed in random order to avoid any historical
effect.

The data preprocessing and the calculation of response intensity were the same as
described in the previous section. We employed the discrimination index (DI) used in
a previous study as a quantitative measure for the direction and speed tuning
intensity separately (DeAngelis and Uka, 2003):

1003
$$\text{Discrimination Index} = \frac{R_{max} - R_{min}}{R_{max} - R_{min} + 2\sqrt{SSE/(N-M)}},$$

where R_{max} and R_{min} are the responses to the most and least effective stimulus,
and the SSE is the sum squared error of the averaged responses, N and M are the
number of trials and the degrees of freedom, respectively. Because the DI for one
parameter of interest may be affected by the other irrelevant parameter, the R_{max}
and R_{min} were calculated as the maximum and the minimum responses averaged for
the irrelevant stimulus parameter. This way we could quantify DIs separately for
speed and direction.

To quantitatively summarize the direction and speed tuning properties for all
translation optic flow sensitive neurons, we fitted the joint distributions of von Mises
and log Gaussian distributions to the neuron response data with the nonlinear
optimization function "*fminsearch" in* MATLAB. The fitted distribution was:

$$\text{von Mises-log Gaussian distribution} = \overbrace{\frac{1}{v\sigma\sqrt{2\pi}}\exp-\frac{\ln(v-\mu_s)^2}{2\sigma^2}}^{\text{Log Gaussian term}}\overbrace{\frac{e^{\kappa cos(\theta-\mu_d)}}{2\pi I_0(\kappa)}}^{\text{von Mises term}}$$

The log Gaussian and the von Mises term aimed to capture the speed and direction
tuning properties, respectively. The preferred speed and direction of each neuron
can therefore be quantified as the mode of the log Gaussian model $e^{\mu_s-\sigma^2}$ and the
von Mises model (μ_d) respectively. The measure of concentration of the von Mises
distribution κ provides a quantitative measure of the direction tuning width. Note
that the choice of log Gaussian function was mainly due to the non-negative
property of speed and the similar shape to the speed tuning curves observed
empirically. There was no biological basis for this model thus it was used only for
description purpose.

1025

Population decoder and autoencoder for translational optic flow estimation

To determine if the information encoded by the translation-sensitive neurons was
sufficient for determining the translation direction and speed, we constructed a
population decoder derived from the maximum likelihood decoder with the calcium
response data recorded. As illustrated in Figure 5A, the stimulus parameter S is
estimated by least square fitting which minimizes the sum squared residue between
the calcium responses R of the recorded n translation sensitive neurons, and the
responses predicted by their response functions ($F(S)$):

$$\hat{S} = argmin\left(\sum_i^n (F_i(S) - R_i)^2\right)$$

The responses functions were approximated with either the joint distribution model
fitted to the direction-speed tuning data (Figure 5B, 5C) or the RF-based response
function (Figure 5D, see the section "Optic flow preference of motion-sensitive
neurons" for details). Since the decoding accuracy was limited by the encoding
quality, the decoding error provides a quantitative measure for the encoding quality
of translational optic flow. The error was calculated as the absolute difference
between the real stimulus parameter and the estimation.

One problem in estimating the encoding quality of translation direction and speed
using the joint distribution model in Figure 4F, is that the tuning model already
contains the response information of the target stimuli to be tested with. We
employed a jackknife test ("leave-ten-out") to avoid this circular analysis. The neural
response data to translational optic flow with 40 different combinations of direction
and speed parameters were evenly divided into 4 groups, so each group contained
the responses to 10 different optic flow stimuli. For any target stimulus to be

decoded, the decoder was only allowed to access the groups that did not contain the
responses to the target stimulus for tuning model estimation.

To test the robustness of translation direction encoding algorithms implemented
with the translation RFs, we constructed a population autoencoder which encodes
the partially occluded or tampered translational optic flow field with n translation
RFs into a one-dimensional array of neural responses as:

1055
$$R_j = F_j(S) + \varepsilon ,$$

1056
$$where\ F(S) = max\left(\frac{1}{I}\Sigma_{i=1}^{I}\frac{\overrightarrow{RF_i}\cdot\overrightarrow{GF_i}}{|\overrightarrow{RF_i}||\overrightarrow{GF_i}|}, 0\right)$$

R_j and $F_j(S)$ are the simulated recorded response and the RF-based response
function of the j^{th} simulated neurons, and ε is the noise term. The neural responses
were decoded to estimate the translation direction with the same population
decoder described above, which makes the decoding process basically a reverse
operation of the encoding. Thus, the reconstructed error is representing mostly the
encoding quality which is affected by the number of neurons involved (n), the noise
in the encoding process (ε), and the input translational optic flow field ($\overrightarrow{GF}$).

To determine the noise effect on the encoding process, the reconstruction error of
the autoencoder was tested with different encoding signal-to-noise ratio (SNR = +∞
(ε = 0), 2.6, 1.3 and 0.65) which was calculated as:

1067
$$SNR = \frac{\mu}{\sigma},$$

The μ is the averaged output from the response functions of all 329 simulated
neurons, and σ is the standard deviation of the noise ε.

We also evaluated the encoding quality when the number of translation RFs involved
n = 10, 20, 50, 100 and 329. Based on the results in Figure S7, the autoencoder used
in Figure 5 was constructed with 50 translation RFs and the SNR = 1.3. As a
reference, on average, more than 100 translation sensitive neurons were found in
the pretectal area per fish in the *in vivo* calcium imaging experiments, and as
mentioned previously, the calcium signal SNR of the optic flow sensitive neurons
analyzed were all higher than 3.

The optic flow in naturalistic scenes is contiguous, so are the occlusions and object
motions that partially block or tamper the optic flow fields. To mimic this contiguity,
we created a 2D Gaussian blurred white noise matrix (σ = 12 visual degree) which
had the same size as the optic flow fields for each optic flow field. Only the
corresponding vectors in the optic flow field of the top N% elements (sorted by
value) in the noise matrix were preserved in the final flow field (examples in Figure
S8). The rest of the optic flow field were occluded or replaced with random object
motion. For the latter, each spatially connected region in the rest of the optic flow
field was assigned with a single random object motion. Similar to the calculation of
translational optic flow fields, let the unit vector $\vec{O}$ indicates the object motion in the

3D environment, the motion vector $\vec{V}$ in a region of the visual field indicated by a
unit vector $\vec{P}$ was calculated as:

1089
$$\vec{V} = \vec{P} - (\vec{P} \cdot \vec{O})\vec{O}$$

1090

Simultaneous recording of eye movement and body position in freely swimming
zebrafish

The fish at 5-6 dpf with strong behavioral responses to moving gratings were
selected on the days of OKR or OMR experiments. To determine the optomotor
responses of freely swimming larvae to optic flow stimuli, we built a cylindrical
swimming reservoir (diameter: 20mm, depth: 3mm) on the center of a 50mm-
diameter round transparent plastic plate. To make the stimulus displayed on the LED
arena completely visible, the cylindrical reservoir wall was made from 2% low
melting-temperature agarose (i.e. no plastic wall) to prevent plastic-agarose
interfaces, which would introduce additional optical artifacts. This reservoir was
placed in the center of the LED arena, whose radius was >9 times larger than the
radius of the reservoir. Because the optic flow stimuli were all symmetric to the
horizontal plane, therefore we do not expect any strong disturbance from internal
reflection to animal behavior as discussed in a previous paper (Wang et al., 2021). A
selected fish was then placed in the reservoir filled with E3 medium.

An infrared LED lamp (850 nm, Conrad, Item No. 491248-62) was placed above the
LED arena to provide relative homogeneous light for illumination. A CMOS camera
(DMK23UV024, The Imaging Source GmbH, Bremen, Germany) with a 6 mm lens (C-
Mount Lens FL-HC0614-2M, Ricoh) was placed at 30 mm below the reservoir. Fish
behavior were recorded in 100 frame-per-second (fps) with a custom written Python
application.

The body axis, body position, and raw eye angles were extracted offline by a custom
written OpenCV based Python script. Briefly, the eye pixels and body pixels were
extracted using a threshold-based segmentation method. The eye and body center
positions were computed as the first moment of the corresponding pixel ensembles.
To obtain the body axis or the head direction, we first applied the principal
component analysis (PCA) to the body pixel ensemble to obtain the rough body
orientation as the first principal component (PC) vector. The coarse body direction
(the sign of the first PC vector) was then determined as the side with higher variation
on the second PC axis. We further refined the body axis by computing the vector
which is perpendicular to the line linking the centers of two eyes and pointing into
the coarse body direction determined previously. The orientation of the two eyes
were also computed with PCA in the same manner. The eye position was computed
as the angular difference between the eye orientation and the body axis (Figure 6B).
The eye traces were first smoothed with a moving mean filter with the window size
of 25 frames (250 ms) to reduce noise interference. In order to extract the OKR-
related slow phase eye movement, the eye angle changes faster than 90

degrees/second were set to zero. The total eye angle changes over the entire
stimulus period were computed for the left and right eyes (Δleft and Δright).

1130

Eye movement recording and detection in mounted fish

The selected 5-6 dpf fish were immobilized in 1.7% low melting-temperature agarose
(wt/vol, E3 medium) at the tip of a transparent plastic triangle stage (tip angle <
45%) on the experiment day. The agarose surrounding the eyes of the mounted fish
were carefully removed to allow free eye movement. The triangle stage with the
mounted fish was later transferred into a spherical glass container filled with E3
medium. The container was placed in the center of the cylindrical LED arena. The
body position and orientation of the mounted fish was adjusted later, so it was in the
center of the LED arena with the dorsal side facing up (roll correction) and the head
pointing to 0° elevation (pitch correction) and 0° azimuth (yaw correction).

A CMOS camera (DMK23UV024, The Imaging Source GmbH, Bremen, Germany) was
placed at ~7 centimeters below the mounted fish (~3 cm below the bottom of the
glass bulb) to record the horizontal eye movement. To create homogeneous light for
eye illumination, a 3-cm-width white paper stripe was placed above the opening of
the glass bulb to diffuse the light emitted from a high-power infrared LED light (850
nm, Conrad, Item No. 491248-62) placed behind the glass bulb. The eyes were
recorded at 60 frames per second (fps). The eye movement recording and stimulus
synchronization were achieved via the same custom written Python application for
freely swimming fish recording. The eye tracking and preprocessing were done
offline by a custom written Matlab script in the same way described in the section
above.

1152

Stimulus design and behavior data analysis for optic flow decomposition experiments

As illustrated in Figure 6C, 8 different optic flow stimuli were used in the global
motion decomposition experiments in freely swimming fish, which includes the pure
forward/backward translation stimuli, the pure CW/CCW rotational stimuli, and the
4 different mixtures of these pure translation/rotation stimuli. The design detail of
these optic flow stimuli was described in a previous section ("Optic flow stimuli
design"). The relative strength for the translation and rotation components in all
mixed optic flow stimuli, w_{trans} and w_{rot}, were set to 1 and 0.67 respectively. All optic
flow stimuli for OMR experiments were normalized by the maximum local
movement speed to the range of 0-60 visual degrees/second. We also measured the
baseline OMR and OKR activities as the swimming trajectory and eye movement
when a static binary noise pattern was displayed.

As shown in Figure 6E, we designed 3 variants of translation stimuli to determine if
and which visual features were involved in the conjugate eye movement observed in
the optic flow decomposition experiment. The pure translation and "T+R" mixture

optic flow stimuli in the OKR experiments in mounted fish are constructed in the
exact same way as above, except the local motion speed in the optic flow stimuli was
reduced to the range of 0-30 visual degrees/second to better trigger OKR behavior.
The slanted translation was constructed by rotating the pure translation
$\sin^{-1}\left(\frac{w_{rot}}{w_{trans}}\right) = \sin^{-1}(0.67) \approx 42.1°$, which corresponds to the azimuth of the
contraction point of the "T+R" mixture. When the motion cue in one hemi visual field
is closer than the other side, the speed difference is similar to the difference caused
by the rotation interference. To mimic this, the asymmetric translation stimuli was
constructed by multiplying each flow vector in the pure translation stimuli by the
inverse of a distance factor (**D**) which was calculated as:

1179
$$\boldsymbol{D} = \sqrt{1 + \left(\frac{w_{rot}}{w_{trans}}\right)^2 - 2\,\frac{w_{rot}}{w_{trans}}\cos(\angle\vec{P}_{azi})}$$

$\angle\vec{P}_{azi}$ is the azimuth angle of the unit vector $\vec{P}$ pointing from the observation point
(the origin) to the location P in the visual field. The transformation mimicked the
changes caused by shifting the observation points which are equidistant from all
motion cues (**D** = 1 a.u.) in the pure translation stimuli to the left by $\frac{w_{rot}}{w_{trans}}$ a.u.

A conjugate-vergence index (CV index) was computed for evaluating whether the
OKR to each stimulus was more similar to a conjugate movement or a vergence
movement:

1187
$$\text{CV index} = \frac{1}{2\pi}\arctan\left(\left|\frac{\Delta_{right} - \Delta_{left}}{\Delta_{right} + \Delta_{left}}\right|\right)$$

The CV index equals to 0 and 1 when the fish perform pure conjugate and vergence
eye movement respectively. The CV indices of OKR to different optic flow stimuli
were compared with one-sided, Bonferroni-corrected Wilcoxon rank-sum test to
determine if any of them are significantly more similar to conjugate eye movement.

To determine if the conjugate eye movement to the rotation component in the T+R
mixture optic flow is caused by local statistics, we randomly sampled the hemi optic
flow fields for 1000 times and computed the averaged motion vectors for the left
and right hemi field separately. The bootstrapped distribution of CV index in Figure
6F was computed in the same way from these pairs of bootstrapped motion vectors
as described above.

1198

Retrograde labeling of the nucleus of the medial longitudinal fasciculus (nMLF)
The retrograde labeling of nMLF in nls-GCaMP6s zebrafish larvae was performed as described
previously (Thiele et al., 2014). Briefly, a 50% Texas Red dextran (10000MW, Thermo Fisher)
in Evans solution was injected into the spinal cord of 4 dpf. larvae embedded in 1.7% agarose
and anesthetized with tricaine. The injected fish was imaged with the two-photon microscope
at 5 dpf.

1205

Acknowledgments

We thank Thomas Nieß (glassblower shop, University of Tübingen) and Klaus Vollmer (fine mechanics workshop, University of Tübingen) for technical support, and Herwig Baier (MPI of Neurobiology) for providing the Tg(elavl3:nls-GCaMP6s)mpn400 zebrafish line. We thank Holger Krapp (Imperial College London), Eva Naumann (Duke School of Medicine), Julian Hinz (Friedrich Miescher Institute for Biomedical Research) and members of the laboratory for feedback on the manuscript.

Declaration of interests

All authors declare that they have no competing interests.

Reference

Abbott, L.F., and Dayan, P. (1999). The Effect of Correlated Variability on the Accuracy of a Population Code. Neural Computation *11*, 91–101.

Bianco, I.H., Kampff, A.R., and Engert, F. (2011). Prey Capture Behavior Evoked by Simple Visual Stimuli in Larval Zebrafish. Front. Syst. Neurosci. *5*.

Bolton, A.D., Haesemeyer, M., Jordi, J., Schaechtle, U., Saad, F.A., Mansinghka, V.K., Tenenbaum, J.B., and Engert, F. (2019). Elements of a stochastic 3D prediction engine in larval zebrafish prey capture. ELife *8*, e51975.

Britten, K.H. (2008). Mechanisms of self-motion perception. Annu Rev Neurosci *31*, 389–410.

Carlson, B.A., and Kawasaki, M. (2006). Ambiguous Encoding of Stimuli by Primary Sensory Afferents Causes a Lack of Independence in the Perception of Multiple Stimulus Attributes. J. Neurosci. *26*, 9173–9183.

Dahmen, H.-J., Franz, M.O., and Krapp, H.G. (2001). Extracting Egomotion from Optic Flow: Limits of Accuracy and Neural Matched Filters. In Motion Vision: Computational, Neural, and Ecological Constraints, J.M. Zanker, and J. Zeil, eds. (Berlin, Heidelberg: Springer), pp. 143–168.

DeAngelis, G.C., and Uka, T. (2003). Coding of Horizontal Disparity and Velocity by MT Neurons in the Alert Macaque. J Neurophysiol *89*, 18.

Dehmelt, F.A., Meier, R., Hinz, J., Yoshimatsu, T., Simacek, C.A., Wang, K., Baden, T., and Arrenberg, A.B. (2020). Gaze stabilisation behaviour is anisotropic across visual field locations in zebrafish. BioRxiv 754408.

Duffy, C.J., and Wurtz, R.H. (1991). Sensitivity of MST neurons to optic flow stimuli. I. A continuum of response selectivity to large-field stimuli. Journal of Neurophysiology *65*, 1329–1345.

Duffy, C.J., and Wurtz, R.H. (1995). Response of monkey MST neurons to optic flow stimuli with shifted centers of motion. J. Neurosci. *15*, 5192–5208.

Duijnhouwer, J., Noest, A., Lankheet, M., Van Den Berg, A., and Van Wezel, R.J.A. (2013). Speed and direction response profiles of neurons in macaque MT and MST show modest constraint line tuning. Front. Behav. Neurosci. *7*.

Eckmeier, D., Kern, R., Egelhaaf, M., and Bischof, H.-J. (2013). Encoding of naturalistic optic flow by motion sensitive neurons of nucleus rotundus in the zebra finch (Taeniopygia guttata). Front. Integr. Neurosci. *7*.

Egelhaaf, M. (2002). Neural encoding of behaviourally relevant visual-motion information

in the fly. Trends in Neurosciences *25*, 96–102.

Ehrlich, D.E., and Schoppik, D. (2017). A novel mechanism for volitional locomotion in
larval zebrafish. BioRxiv 189191.

Evans, B.J.E., O'Carroll, D.C., Fabian, J.M., and Wiederman, S.D. (2019). Differential Tuning
to Visual Motion Allows Robust Encoding of Optic Flow in the Dragonfly. J. Neurosci. *39*,
8051–8063.

Festl, F., Recktenwald, F., Yuan, C., and Mallot, H.A. (2012). Detection of linear ego-
acceleration from optic flow. Journal of Vision *12*.

Franz, M.O., and Krapp, H.G. (2000). Wide-field, motion-sensitive neurons and matched
filters for optic flow fields. Biol Cybern *83*, 185–197.

Gibson, J.J. (1954). The visual perception of objective motion and subjective movement.
Psychological Review *61*, 304–314.

Graham, D.J., and Wylie, D.R. Zebrin-Immunopositive and -Immunonegative Stripe Pairs
Represent Functional Units in the Pigeon Vestibulocerebellum. 11.

Horseman, B.G., Macauley, M.W.S., and Barnes, W.J.P. (2011). Neuronal processing of
translational optic flow in the visual system of the shore crab Carcinus maenas. Journal of
Experimental Biology *214*, 1586–1598.

Hunter, P.R., Lowe, A.S., Thompson, I.D., and Meyer, M.P. (2013). Emergent Properties of
the Optic Tectum Revealed by Population Analysis of Direction and Orientation Selectivity.
Journal of Neuroscience *33*, 13940–13945.

Huston, S.J., and Krapp, H.G. (2008). Visuomotor Transformation in the Fly Gaze
Stabilization System. PLOS Biology *6*, e173.

Joesch, M., Plett, J., Borst, A., and Reiff, D.F. (2008). Response Properties of Motion-
Sensitive Visual Interneurons in the Lobula Plate of Drosophila melanogaster. Current
Biology *18*, 368–374.

Jr, W.H.W., Kay, B.A., Zosh, W.D., Duchon, A.P., and Sahuc, S. (2001). Optic flow is used to
control human walking. Nature Neuroscience *4*, 213–216.

Karmeier, K., Krapp, H.G., and Egelhaaf, M. (2003). Robustness of the Tuning of Fly Visual
Interneurons to Rotatory Optic Flow. Journal of Neurophysiology *90*, 1626–1634.

Kist, A.M., and Portugues, R. (2019). Optomotor Swimming in Larval Zebrafish Is Driven
by Global Whole-Field Visual Motion and Local Light-Dark Transitions. Cell Reports *29*,
659-670.e3.

Koenderink, J.J., and van Doorn, A.J. (1987). Facts on optic flow. Biol. Cybern. *56*, 247–254.

Kramer, A., Wu, Y., Baier, H., and Kubo, F. (2019). Neuronal Architecture of a Visual Center
that Processes Optic Flow. Neuron *103*, 118-132.e7.

Krapp, H.G., and Hengstenberg, R. (1996). Estimation of self-motion by optic flow
processing in single visual interneurons. Nature *384*, 463.

Krapp, H.G., Hengstenberg, B., and Hengstenberg, R. (1998). Dendritic structure and
receptive-field organization of optic flow processing interneurons in the fly. J.
Neurophysiol. *79*, 1902–1917.

Kubo, F., Hablitzel, B., Dal Maschio, M., Driever, W., Baier, H., and Arrenberg, A.B. (2014).
Functional Architecture of an Optic Flow-Responsive Area that Drives Horizontal Eye
Movements in Zebrafish. Neuron *81*, 1344–1359.

Kühn, N.K., and Gollisch, T. (2016). Joint Encoding of Object Motion and Motion Direction
in the Salamander Retina. J. Neurosci. *36*, 12203–12216.

Lappe, M., Pekel, M., and Hoffmann, K.-P. (1998). Optokinetic Eye Movements Elicited by
Radial Optic Flow in the Macaque Monkey. Journal of Neurophysiology *79*, 1461–1480.

Longden, K.D., Wicklein, M., Hardcastle, B.J., Huston, S.J., and Krapp, H.G. (2017). Spike
Burst Coding of Translatory Optic Flow and Depth from Motion in the Fly Visual System.
Current Biology *27*, 3225-3236.e3.

Longuet-Higgins, H.C., and Prazdny, K. (1980). The interpretation of a moving retinal
image. Proceedings of the Royal Society of London. Series B. Biological Sciences *208*,
385–397.

Lowe, A.S., Nikolaou, N., Hunter, P.R., Thompson, I.D., and Meyer, M.P. (2013). A Systems-
Based Dissection of Retinal Inputs to the Zebrafish Tectum Reveals Different Rules for
Different Functional Classes during Development. Journal of Neuroscience *33*, 13946–
13956.

Luo, J., He, K., Andolina, I.M., Li, X., Yin, J., Chen, Z., Gu, Y., and Wang, W. (2019). Going
with the Flow: The Neural Mechanisms Underlying Illusions of Complex-Flow Motion. J.
Neurosci. *39*, 2664–2685.

Maaswinkel, H., and Li, L. (2003). Spatio-temporal frequency characteristics of the
optomotor response in zebrafish. Vision Research *43*, 21–30.

Marques, J.C., Lackner, S., Félix, R., and Orger, M.B. (2018). Structure of the Zebrafish
Locomotor Repertoire Revealed with Unsupervised Behavioral Clustering. Current Biology
28, 181-195.e5.

Nakayama, K., and Loomis, J.M. (1974). Optical Velocity Patterns, Velocity-Sensitive
Neurons, and Space Perception: A Hypothesis. Perception *3*, 63–80.

Naumann, E.A., Fitzgerald, J.E., Dunn, T.W., Rihel, J., Sompolinsky, H., and Engert, F. (2016).
From Whole-Brain Data to Functional Circuit Models: The Zebrafish Optomotor Response.
Cell *167*, 947-960.e20.

Pakan, J.M.P., and Wylie, D.R.W. (2006). Two optic flow pathways from the pretectal

nucleus lentiformis mesencephali to the cerebellum in pigeons (Columba livia). Journal of Comparative Neurology *499*, 732–744.

Portugues, R., Haesemeyer, M., Blum, M.L., and Engert, F. (2015). Whole-field visual motion drives swimming in larval zebrafish via a stochastic process. Journal of Experimental Biology *218*, 1433–1443.

Qian, H., Zhu, Y., Ramsey, D.J., Chappell, R.L., Dowling, J.E., and Ripps, H. (2005). Directional Asymmetries in the Optokinetic Response of Larval Zebrafish (Danio rerio). Zebrafish *2*, 189–196.

Rinner, O., Rick, J.M., and Neuhauss, S.C.F. (2005). Contrast Sensitivity, Spatial and Temporal Tuning of the Larval Zebrafish Optokinetic Response. Invest. Ophthalmol. Vis. Sci. *46*, 137–142.

Roeser, T., and Baier, H. (2003). Visuomotor behaviors in larval zebrafish after GFP-guided laser ablation of the optic tectum. Journal of Neuroscience *23*, 3726–3734.

Sabbah, S., Gemmer, J.A., Bhatia-Lin, A., Manoff, G., Castro, G., Siegel, J.K., Jeffery, N., and Berson, D.M. (2017). A retinal code for motion along the gravitational and body axes. Nature *advance online publication*.

Severi, K.E., Portugues, R., Marques, J.C., O'Malley, D.M., Orger, M.B., and Engert, F. (2014). Neural Control and Modulation of Swimming Speed in the Larval Zebrafish. Neuron *83*, 692–707.

Srinivasan, M., Zhang, S., Lehrer, M., and Collett, T. (1996). Honeybee navigation en route to the goal: visual flight control and odometry. Journal of Experimental Biology *199*, 237–244.

Stone, T., Webb, B., Adden, A., Weddig, N.B., Honkanen, A., Templin, R., Wcislo, W., Scimeca, L., Warrant, E., and Heinze, S. (2017). An Anatomically Constrained Model for Path Integration in the Bee Brain. Current Biology *27*, 3069-3085.e11.

Sunkara, A., DeAngelis, G.C., and Angelaki, D.E. (2016). Joint representation of translational and rotational components of optic flow in parietal cortex. PNAS *113*, 5077–5082.

Tanaka, K., and Saito, H. (1989). Analysis of motion of the visual field by direction, expansion/contraction, and rotation cells clustered in the dorsal part of the medial superior temporal area of the macaque monkey. Journal of Neurophysiology *62*, 626–641.

Thiele, T.R., Donovan, J.C., and Baier, H. (2014). Descending Control of Swim Posture by a Midbrain Nucleus in Zebrafish. Neuron *83*, 679–691.

Wang, K., Hinz, J., Haikala, V., Reiff, D.F., and Arrenberg, A.B. (2019). Selective processing of all rotational and translational optic flow directions in the zebrafish pretectum and

tectum. BMC Biology *17*, 29.

Wang, K., Hinz, J., Zhang, Y., Thiele, T.R., and Arrenberg, A.B. (2020). Parallel Channels for
Motion Feature Extraction in the Pretectum and Tectum of Larval Zebrafish. Cell Reports
30, 442-453.e6.

Wang, K., Arrenberg, B., Hinz, J., and Arrenberg, A.B. (2021). Reduction of visual stimulus
artifacts using a spherical tank for small, aquatic animals. Scientific Reports *11*, 3204.

Warren, W.H., and Hannon, D.J. (1988). Direction of self-motion is perceived from optical
flow. Nature *336*, 162–163.

Wertz, A., Haag, J., and Borst, A. (2009). Local and global motion preferences in
descending neurons of the fly. J. Comp. Physiol. A Neuroethol. Sens. Neural. Behav.
Physiol. *195*, 1107–1120.

Wylie, D.R. (2013). Processing of visual signals related to self-motion in the cerebellum of
pigeons. Front Behav Neurosci *7*.

Wylie, D.R.W. (2000). Binocular neurons in the nucleus lentiformis mesencephali in
pigeons: responses to translational and rotational optic flowfields. Neuroscience Letters
291, 9–12.

Wylie, D.R., Kripalani, T., and Frost, B.J. (1993). Responses of pigeon vestibulocerebellar
neurons to optokinetic stimulation. I. Functional organization of neurons discriminating
between translational and rotational visual flow. J Neurophysiol *70*, 2632–2646.

Yildizoglu, T., Riegler, C., Fitzgerald, J.E., and Portugues, R. (2020). A Neural
Representation of Naturalistic Motion-Guided Behavior in the Zebrafish Brain. Current
Biology *30*, 2321-2333.e6.

Zhang, Y., and Arrenberg, A.B. (2019). High throughput, rapid receptive field estimation
for global motion sensitive neurons using a contiguous motion noise stimulus. Journal of
Neuroscience Methods *326*, 108366.

1384