A multi-dataset evaluation of frame censoring for task-based fMRI

10
11
12
Michael S. Jones, Zhenchen Zhu*, Aahana Bajracharya, Austin Luor, Jonathan E. Peelle

Department of Otolaryngology, Washington University in St. Louis, St. Louis MO USA
* Current affiliation: MD Program, Chinese Academy of Medical Sciences and Peking Union Medical College, Beijing China

Running title: Motion correction in task-based fMRI

Keywords: motion correction, head movement, frame censoring, scrubbing, FD, DVARS, task-based fMRI

Please address correspondence to:

Dr. Michael Jones   Dr. Jonathan Peelle
Department of Otolaryngology   Department of Otolaryngology
Washington University in St. Louis   Washington University in St. Louis
660 South Euclid, Box 8115   660 South Euclid, Box 8115
St. Louis, MO 63110   St. Louis, MO 63110
email: jones.mike@wustl.edu   email: jpeelle@wustl.edu

Abstract

Subject motion during fMRI can affect our ability to accurately measure signals of interest. In recent years, frame censoring—that is, statistically excluding motion-contaminated data within the general linear model using nuisance regressors—has appeared in several task-based fMRI studies as a mitigation strategy. However, there have been few systematic investigations quantifying its efficacy. In the present study, we compared the performance of frame censoring to several other common motion correction approaches for task-based fMRI using open data and reproducible workflows. We analyzed eight datasets available on OpenNeuro.org representing eleven distinct tasks in child, adolescent, and adult participants. Performance was quantified using maximum t-values in group analyses, and ROI-based mean activation and split-half reliability in single subjects. We compared frame censoring to the use of 6 and 24 canonical motion regressors, wavelet despiking, robust weighted least squares, and untrained ICA-based denoising. Thresholds used to identify censored frames were based on both motion estimates (FD) and image intensity changes (DVARS). Relative to standard motion regressors, we found consistent improvements for modest amounts of frame censoring (e.g., 1–2% data loss), although these gains were frequently comparable to what could be achieved using other techniques. Importantly, no single approach consistently outperformed the others across all datasets and tasks. These findings suggest that although frame censoring can improve results, the choice of a motion mitigation strategy depends on the dataset and the outcome metric of interest.

Introduction

Obtaining high-quality neuroimaging data depends on minimizing artifacts. Although
advancements in hardware and pulse sequence design have reduced many types of noise
inherent to functional MRI, other sources remain (Bianciardi et al., 2009). One prominent
challenge is artifacts caused by subject head motion. Among other effects, head motion
changes the part of the brain sampled by a particular voxel and can introduce changes in signal
intensity through interactions with the magnetic field, which add noise to the data and make it
harder to identify signals of interest.
The effects of head motion have received recent scrutiny in the context of resting state
functional connectivity. Because motion-related artifacts occur in many voxels simultaneously,
they can introduce correlations in fMRI time series that are unrelated to BOLD activity, leading
to inaccurate estimates of functional connectivity (Power et al., 2015; Satterthwaite et al., 2019).
However, spurious activation is also of concern in task-based functional neuroimaging. Rigid
body realignment—a mainstay of fMRI analysis for decades—goes some way towards
improving correspondence across images (Ashburner and Friston, 2004), but does not remove
extraneous signal components introduced by movement (Friston et al., 1996). A common
approach for mitigating motion-related artifacts is to include the 6 realignment parameters
(translation and rotation around the X, Y, and Z axes) as nuisance regressors in first-level
models.
Alternatively, several data-driven strategies have been developed to reduce the
influence of high-motion scans on estimated activations. Wavelet decomposition identifies
artifacts by exploiting their non-stationarity across different temporal scales (Patel et al., 2014).
The method has been applied in resting state studies but is also applicable to task-based data.
Independent component analysis (Pruim et al., 2015) identifies artifacts based on the spatial
distribution of shared variance. In robust weighted least squares (Diedrichsen and Shadmehr,
2005), a two-pass modeling procedure is used to produce a collection of nuisance regressors
which are then included in the final analysis to weight frames by the inverse of their variance
(that is, downweighting frames with high error).
An alternative motion correction strategy is "scrubbing" or "frame censoring" (Lemieux et
al., 2007; Siegel et al., 2014). In this approach, bad scans are identified and excluded from
statistical analysis. One approach is to do so by modeling them in the general linear model
using nuisance regressors (i.e. "scan-nulling regressors" or "one-hot encoding"). Although frame
censoring has received considerable interest in resting state fMRI over the past several years
(Power et al., 2012; Gratton et al., 2020a), it has not seen widespread use in the task-based
fMRI literature. Censoring approaches involve some effective data loss, in that censored frames
do not contribute to the task-related parameter estimates, and that columns introduced to the
design matrix to perform censoring reduce the available degrees of freedom. Choosing an
appropriate metric and associated threshold for identifying bad scans can also be challenging.
Thus, additional information over what threshold should be used for identifying bad frames—and
relatedly, how much data is lost vs. retained—is necessary to make informed decisions.
Although several published studies comparing differing correction strategies exist
(Ardekani et al., 2001; Oakes et al., 2005; Johnstone et al., 2006), a drawback of prior work is
that evaluation was often limited to a single dataset (see **Supplemental Table 1**). The degree to
which an optimal strategy for one dataset generalizes to other acquisition schemes, tasks, or
populations is not clear. With the increased public availability of neuroimaging datasets
(Poldrack et al., 2013; Markiewicz et al., 2021), the possibility of evaluating motion correction
approaches across a range of data has become more feasible.
In the present work, we sought to compare the performance of identical pipelines on a
diverse selection of tasks, using data from different sites, scanners, and subject pools.

Although our primary interest was frame censoring, we considered seven different motion-
correction approaches:

1. six canonical head motion estimates (RP6)
2. 24-term expansions of head motion estimates (RP24)
3. wavelet despiking (WDS)
4. robust weighted least squares (rWLS)
5. untrained independent component analysis (ICA)
6. frame censoring based on frame displacement (FD)
7. frame censoring based on variance differentiation (DVARS)

This list is not exhaustive but representative of approaches that are currently used and feasible
to include in an automated processing pipeline.
Because it is impossible to determine a "ground truth" result with which to compare the
effectiveness of these approaches, we instead considered three complementary outcome
metrics: 1) the maximum group t-statistic both across the whole-brain and in a region-of-interest
relevant to the task; 2) the average parameter estimates from within the same ROI (that is,
effect size); and 3) the degree of test-retest consistency exhibited by subject-level parametric
maps. These metrics are simple to define yet functionally meaningful, and can be applied to
data from almost any fMRI study.

133   **Methods**

Datasets
We analyzed eight studies obtained from OpenNeuro (Markiewicz et al., 2021), several of which
included multiple tasks or multiple participant groups. As such, the eight selected studies
provided a total of 15 datasets. The selection process was informal, but studies given priority
included 1) a clearly-defined task, 2) a sufficient number of subjects to allow second-level
modeling, 3) sufficient data to make test-retest evaluation possible, and 4) a publication
associated with the data describing a result to which we could compare our own analysis.
A summary of the eight datasets selected is shown in **Table 1** (acquisition details
provided in **Supplemental Table 2**). Additional information, including task details,
modeling/contrast descriptions compiled from publication(s) associated with a given study, and
any data irregularities encountered during analysis, is provided in the **Supplemental Materials**.

Analysis
Analysis was performed using Automatic Analysis version 5.4.0 (Cusack et al., 2015) (RRID:
SCR_003560), which scripted a combination of SPM12 (Wellcome Trust Centre for
Neuroimaging) version 7487 (RRID: SCR_007037) and FMRIB Software Library (FSL; FMRIB
Analysis Group; (Jenkinson et al., 2012) version 6.0.1 (RRID: SCR_002823). BrainWavelet
Toolbox v2.0 (Patel et al., 2014) was used for wavelet despiking, and rWLS version 4.0
(Diedrichsen and Shadmehr, 2005) for robust weighted least squares. Analysis scripts used in
the study are available at https://osf.io/n5v3w/.
To the extent possible, we used the same preprocessing pipeline for all datasets (**Figure
1a**). Briefly, structural and functional images were translated to the center of the scanned
volume and the first four frames of each session were removed in functional images to allow for
signal stabilization. This was followed by bias correction of the structural image, realignment,
coregistration of the functional and structural images, normalization into MNI space using a
unified segmentation approach (Ashburner and Friston, 2005) resampled at 2 mm, and
smoothing of the functional images using an 8 mm FWHM Gaussian kernel.
160

Table 1. Summary of datasets analyzed

Dataset	Reference	Task	Age group*	# subs	FD (median ± SD)	frames per subject
ds000102	Kelly et al. (2008)	flanker	YA	22	0.11 ± 0.12	284
ds000107	Duncan et al. (2009)	1-back	YA	43	0.08 ± 0.14	323
ds000114	Gorgolewski et al. (2013a)	motor (lips)	YA	10	0.14 ± 0.16	360
		covert verb	YA	10	0.11 ± 0.11	338
		overt word	YA	10	0.13 ± 0.12	144
		line bisection	YA	9	0.13 ± 0.18	468
ds000228	Richardson et al. (2018)	movie viewing	C	122	0.21 ± 0.93	164
			YA	33	0.18 ± 0.27	164
ds001497	Lewis-Peacock and Postle (2008)	face perception	YA	10	0.11 ± 0.12	1146
ds001534	Courtney et al. (2018)	food images	YA	42	0.10 ± 0.16	552
ds001748	Fynes-Clinton et al. (2019)	memory retrieval	C	21	0.16 ± 0.36	438
			T	20	0.12 ± 0.17	438
			YA	21	0.08 ± 0.17	438
ds002382	Rogers et al. (2020)	word recognition	YA	29	0.14 ± 0.35	710
			OA	32	0.30 ± 0.34	710

Note: * OA = older adults; YA = young adults; T = teens; C = children

Functional images were corrected for motion artifacts using each of the following approaches: 1) inclusion of six canonical motion estimates in the first-level model as nuisance regressors, 2) inclusion of 24 nuisance regressors based on a second-order expansion of the motion estimates and first derivatives, 3) wavelet despiking, 4) robust weighted least squares, 5) ICA denoising, 6) frame censoring based on framewise displacement (FD) or 7) differential variance (DVARS) thresholding (FD/DVARS thresholding is described below).

Statistical modeling was performed in SPM in all motion correction approaches. First-level modeling included a contrast of interest described in a publication associated with the dataset for evaluation, followed by second-level analysis to produce group-level statistical maps. All first- and second-level t-maps were thresholded at a voxelwise threshold of $p < 0.001$ (uncorrected).

Minor pipeline modifications were required for robust weighted least squares, wavelet despiking, and ICA denoising. As recommended by developers of the rWLS toolbox, unsmoothed data was used for variance estimation and contrast maps were smoothed after modeling. For wavelet despiking, functional images were rescaled to a whole-brain median of 1000 across all frames prior to processing. The default toolbox settings (wavelet: d4, threshold: 10, boundary: reflection, chain search: moderate, scale number: liberal) were used. Finally, ICA-

180 based denoising was implemented using ICA-AROMA (Pruim et al., 2015) with additional
181 processing steps performed within FSL. Briefly, the unsmoothed coregistered functional image
182 was demeaned, detrended, smoothed, and then nonlinearly warped to the FSL 2 mm MNI152
183 template using FNIRT. The normalized functional image was then passed to AROMA for
184 denoising.
185

Figure 1. Schematic of processing pipeline and outcome measures. **(a)** Summary of preprocessing and model steps in common and differing across motion correction strategies. **(b)** Following statistical modeling, outcomes are summarized in mean parameter estimates and Dice overlap of thresholded single-subject maps (top) and maximum t-value from the group analysis (bottom).

Evaluation of Motion Correction Performance
Three measures were used to quantify the performance of each motion correction strategy,
illustrated in **Figure 1b**: 1) maximum t-value, 2) effect size, and 3) subject replicability. In the
first measure, the maximum t-value occurring in the group level parametric map was extracted
both at the whole-brain level and also within a region-of-interest relevant to the task. The effect
size was quantified as the mean of all voxels within the ROI for each subject using the first-level
beta maps. To evaluate subject replicability, session data were treated as a test-retest paradigm
(the first session versus the second session in studies having fewer than three sessions; even-
numbered versus odd-numbered sessions otherwise). Replicability was quantified as the Dice
coefficient of thresholded first-level t-maps (0.001, uncorrected) in each subject (restricted to the
ROI).
197
FD and DVARS Thresholding

Motion correction approaches based on frame censoring required quantification of motion
artifacts which could then be subjected to thresholding. Both framewise displacement (FD) and
differential variance (DVARS) were used. Framewise displacement was calculated as the sum
of the six head motion estimates obtained from realignment, with a dimensional conversion of
the three rotations assuming the head is a 50 mm sphere (Power et al., 2012). DVARS was
calculated as the root-mean-squared of the time difference in the BOLD signal calculated across
the entire brain (Smyser et al., 2011). As shown in **Figure 2A**, both metrics closely tracked
artifacts apparent in voxel intensities and also each other. Although FD and DVARS in a given
session tended to be correlated (**Figure 2B**), they were not identical and could exhibit slightly
different time courses and relative peak amplitudes. As such, we explored the use of both
measures.
210   Thresholds were determined by calculating FD and DVARS across all sessions in all
subjects, which allowed values to be identified that resulted in 1%, 2%, 5%, 10%, and 20%
frame violations across the entire dataset (**Figure 2C**). We adopted this strategy rather than
using a fixed value of FD or DVARS for several reasons. First, FD and DVARS magnitudes
change with the TR of the data, because the TR is the sampling rate (for a given movement,
sampling more rapidly will give smaller FD values, even though the total motion is the same).
Secondly, different calculations of FD provide different values (Jenkinson et al., 2002; Power et
al., 2012; Van Dijk et al., 2012), and thus any absolute threshold would necessarily be metric-
specific. Finally, datasets differ in their tasks and populations, and we anticipated that a
constant threshold would not be suitable for all datasets. We, therefore, employed the frame-
percent thresholding strategy in order to obtain an informative range of results in all studies
examined. Because the threshold is chosen to limit data loss in the whole group, it allows high-
motion subjects to have more frames censored than low-motion subjects, which was one of our
primary goals.
224   The threshold values that resulted from percent data loss targeting in these datasets are
225   shown in **Supplemental Figure 1**.
226

Figure 2. Calculation of frame censoring thresholds. **(a)** Example grayplot (Power, 2017) showing 500 random gray matter voxels (single subject data from ds001534). DVARS and FD for this session are plotted above. Spikes in the metrics can be used to identify frames contaminated by artifacts. **(b)** DVARS and FD are correlated but exhibit differing amplitudes and time courses. As such, the use of both was explored. **(c)** The collection of metric values (here shown for DVARS) used for frame censoring was determined by plotting frameloss for each subject as a function of threshold (thin blue traces). Interpolation of the mean response (thick black trace) then provided estimates of metric values corresponding to a target data loss of 1%, 2%, 5%, 10%, or 20%. Box plot (inset) summarizes the resulting data loss across all subjects at each threshold (*box*: 25-75% percentiles; *crosses*: >3 SD outliers).

227
To impose frame censoring, first-level modeling was repeated for each threshold with a delta
function (i.e. a scan-nulling regressor) included in the design matrix at the location of each
violation, which effectively removes the contribution of the targeted frame from the analysis.

Region of Interest Definition
A task-relevant ROI for each study/task was defined in one of three ways: 1) a 5-mm sphere (or
spheres) centered at coordinates reported in a publication associated with the dataset, 2) a
whole-brain Z-mask generated by a task-relevant search term (e.g., "incongruent task") in
NeuroQuery (Dockès et al., 2020) and thresholded $z > 3$, or 3) a binarized tissue probability
map in the SPM Anatomy Toolbox (Eickhoff et al., 2005) for a task-relevant brain structure or
anatomical region (e.g., "V2").

238   **Results**

Performance of the motion correction strategies organized by dataset is shown in **Figure 3**.
Each panel includes a representative second-level thresholded t-map at the upper left ($p <$
0.001, uncorrected) using the "RP6" approach (six canonical motion parameters included as
nuisance regressors). A contrast descriptor is given below the map. The ROI used for
evaluation is shown at lower left with the source listed under the rendered image; "NQ"
indicates search term from NeuroQuery (Dockès et al., 2020); all other labels indicate either an
Anatomy Toolbox tissue probability map (Eickhoff et al., 2005) or a 5 mm sphere. Additional
details on ROI definition used in each analysis are provided in the **Supplemental Materials**.
These results show there is substantial variability in motion correction approaches, with
performance depending both on the data under consideration and the chosen performance
metric. However, some general trends are apparent. Wavelet despiking tended to offer the best
maximum t-value in both the whole-brain and ROI-constrained evaluation, with robust weighted
least squares also exhibiting good performance (note the ROI-restricted maximum t-value,
shown in filled bars, are superimposed on the whole-brain results, shown in open bars in Figure
3 due to space restrictions). Conversely, ICA gave consistently poorer results although it offered
the best maximum t-value in the ds000114 covert verb task. Performance of FD and DVARS
frame censoring were highly variable, with the application of increasingly stringent thresholds
improving performance in some datasets while decreasing it in others. A somewhat consistent
behavior is a loss of performance at the highest (20%) FD or DVARS threshold. As a rule, frame
censoring performed better than RP6 and RP24 motion correction, although RP6 is competitive
(if not optimal) in both ds000107 and ds001748.
260
261

Figure 3. Summary of denoising algorithm performance for all datasets examined in the study. Each panel includes a representative thresholded group t-map at left (p=0.001, uncorrected) for the given contrast with the ROI used for evaluation plotted below. At center, ROI-restricted maximum t-values are superimposed on whole-brain results for each denoising approach. Plots at right show individual-subject mean ROI effect size (*top*) and Dice coefficient for a split-half test-retest evaluation (*bottom*). Datasets that did not permit test-retest evaluation are noted "n/a." The horizontal dotted line in a given plot indicates RP6 results for reference.

264
The mean effect size shown in these results is largely insensitive to the selected motion
correction approach. The two exceptions are wavelet despiking and ICA, which produced
consistently smaller values than the other approaches. This may reflect suboptimal parameter
selection in these algorithms (see Discussion). Robust weighted least squares offered
competitive results in all datasets and notably superior results in ds002382 and the ds000114
overt word task. FD and DVARS frame censoring neither improved nor degraded results
regardless of threshold, producing a mean effect size indistinguishable from both the RP6 and
RP24 approaches save for a few isolated individual subjects.
The test-retest results also demonstrate a great deal of variability. The Dice coefficients
exhibit substantial inter-subject differences, resulting in a mean performance that is similar
across all motion correction strategies. However, excluding ds000102, ds001534, and the
ds000114 line bisection task which provide an uninformative test-retest quantification, some
trends can be identified. There is a detectable decrease in both the FD and DVARS frame
censoring results, especially at 20% thresholding. In general, all differences are minor, save for
ICA which performs notably better in the ds000114 motor task and notably worse in ds001487.
A summary of these results is shown in **Figure 4a**, in which average values of the four
performance metrics are plotted for all 15 datasets/tasks. Several of the trends noted above
remain apparent. Wavelet despiking gives the largest whole-brain maximum t-value. Robust
weighted least squares resulted in the best ROI-constrained performance. Light-to-moderate
frame censoring results in improvement which then declines as more aggressive thresholding is
applied. Robust weighted least squares produces the largest average effect size. Wavelet
despiking and ICA produce poor results as measured by this metric. Finally, the averaged Dice
coefficient is less than 0.5 in all datasets. A decline of FD and DVARS frame censoring
performance with increasing threshold is apparent. However, all of the test-retest results exhibit
substantial variability (error bars denote +1 SD in the maximum t-value plot; +/- 1 SD in ROI
mean effect size and Dice).
291
292

Figure 4. (a) Whole-brain and ROI-restricted maximum t-values (*left*), mean effect size (*upper right)* and test-retest Dice coefficient (*lower right)* averaged across all datasets. A value of 1 indicates equivalent performance to the "standard" RP6 approach. **(b)** Motion correction performance summarized as the proportion of datasets a given approach gave the best (top row) or worst (bottom) results as measured by the four performance metrics.

An alternate summary of algorithm performance is presented in **Figure 4b**, in which the
best and worst performer measured by each metric was identified in each of the 15 datasets
and the resulting proportions plotted as pie charts. The trends and variability evident in the
grand averages are also apparent in these data. Robust weighted least squares offered best
performance on many datasets and worst performance on none. Wavelet despiking gave the
best maximum t-value in about half (whole-brain) or one quarter (ROI-restricted) of the studies,
but the worst ROI mean effect size in over half. ICA denoising was often the worst performer,
yet gave best results across all four metrics in at least one dataset. Frame censoring performed
roughly equally well (or equally poorly) using either FD or DVARS, with one notable result being
FD was never the worst performer for effect size. Finally, the performance of the RP6 and RP24
approaches are middling, producing best or worse maximum t-value on only one or two
datasets and, with one exception, never producing best nor worst ROI mean or test-retest
results.

307   **Discussion**

We explored the performance of a variety of approaches to correcting motion-related artifacts in
task-based fMRI. The studies examined represent a broad range of task domains, including
sensory, motor, language, memory, and other cognitive functions, with participants varying in
age, sex, and other characteristics. Although we set out expecting to find converging evidence
for an optimal strategy, instead our results demonstrate that the performance of motion
correction approaches depends on both the data and the outcome of interest. We review our
selected metrics below—whole-brain and ROI-restricted maximum t-value, mean effect size,
and test-retest repeatability—followed by some general comments on each motion correction
approach.

Comparing outcome metrics
The use of whole-brain maximum t-value measured in group-level statistical maps has the
advantage that it requires few assumptions about the data or the expected pattern of activity.
However, we did not observe a consistent pattern regarding which motion correction approach
optimized the whole-brain maximum t-value. Disparity was even evident between different
participant groups within a given study. For example, wavelet despiking had the highest whole-
brain t statistic in ds0001748 in teens but RP6 offered better performance in adults.
In addition to whole-brain statistics, we examined maximum t-values within a selected
region of interest. Our rationale for doing so was that researchers interested in task-based
effects frequently have prior intuitions about where the most informative results are localized. A
potential downside of this approach is the need to specify an ROI to examine. We found that
motion correction approaches can exhibit substantially different whole-brain and ROI-restricted
performance. In the ds000114 overt word task, for example, RP6 offered best performance
within the motor cortex but poor performance in a whole-brain evaluation. Furthermore, frame
censoring performance improved in some datasets but degraded in others as more stringent
thresholding was applied. Obviously, a challenge inherent in such an evaluation is the actual
ROI selection. Although we believe our choices are sensible, selection of a different ROI set
may well result in a different overall view of performance.
To complement these group-level measures, we also considered two single-subject
metrics: mean effect size and test-retest repeatability measured by Dice overlap in thresholded t
maps. Effect size permits an examination of parameter estimates, and our use of averaging
offers a direct and simple quantification. However, with the exceptions of wavelet despiking and
aggressive frame censoring (revisited below), we observed that effect size was largely
insensitive to the choice of motion correction strategy, although less than the variability
observed in maximum t-value. This suggests the main effect of different motion correction
approaches is a differential reduction in model error variance. If parameter estimation is the
primary result of interest, then the choice of motion correction strategy may not be critical.
The test-retest evaluation was perhaps the least helpful result, with the performance of
all motion correction approaches essentially indistinguishable under this metric. Although the
outcome is disappointing, it should be noted that many of the studies included here were not
designed to include a split-half repeatability analysis. It may be that more data per subject may
be needed for this metric to be informative. In that sense, our analyses speak to the general
challenges of obtaining reliable single-subject data in fMRI (Smith et al., 2005; Bennett and
Miller, 2010; Gorgolewski et al., 2013b; Elliott et al., 2020), at least under conventional scanning
protocols (Gratton et al., 2020b). Investigators of resting state fMRI have confronted a similar
issue, and recommendations have appeared in the resting state fMRI literature outlining the
minimal scan time required for reproducible results (Birn et al., 2013; Laumann et al., 2015).
Perhaps an analogous standard might be possible for task-based fMRI, although any guideline
would necessarily require the cognitive complexity of the task under investigation to be
considered.

Comparing Motion Correction Approaches
No single denoising approach exhibited optimal performance on all datasets and all metrics.
Algorithm performance did not appear to be systematically related to the nature of the task,
acquisition parameters, nor any feature of the data that could be identified.
Interestingly, computationally-intensive approaches did not necessarily perform better
than basic corrective measures. For some datasets, including six motion estimates as
continuous nuisance regressors—a standard approach used in functional imaging for
decades—could perform as well or better than more sophisticated algorithms that have
emerged in recent years. Increasing the head motion estimate from a 6- to a 24-parameter

expansion led to an improvement in some data but degraded results in others. Although such
results are rather counterintuitive, we can provide a few observations, even if these data do not
currently permit conclusive recommendations.
Two motion correction approaches that showed generally strong performance were
wavelet despiking (WDS) and robust weighted least squares (rWLS). Together, these
approaches offered best performance in approximately half of the datasets across all
performance metrics (**Figure 4**). Additionally, in no evaluation did rWLS produce the worst
results. In a statistical sense, robust weighted least squares might be seen as an optimal
solution, in that it uses the error in the model to re-weight time points, reducing the influence of
motion on parameter estimates. However, we also found that other motion correction strategies
supplied similar, or superior, performance in several instances. One reason might be that rWLS
linearly weights time points inversely related to their variance. To the degree that motion
artifacts include a nonlinear component, linear weighting may not adequately (or at least, not
optimally) remove all of the artifact.
In contrast to good performance of wavelet despiking as measured by maximum t-value,
it gave notably low scores on mean effect size. However, this finding may simply reflect data
scaling specific to the WDS implementation. It should also be noted the WDS toolbox offers 20
wavelets, and additional options that control algorithm behavior such as thresholding and chain
search selection. The results obtained here are what can be expected using the default settings
recommended by the toolbox developers, which includes a median 1000 rescaling of the
functional data (and hence the lower effect size). Thus, numeric comparison to other
approaches (that do not include rescaling) are problematic. It also may be possible to improve
performance–including obtaining effect sizes concomitant with other motion correction
approaches if that is judged critical by tuning the algorithm, although it is unclear how that
process could be automated.
One unexpected result was the relatively poor performance of ICA denoising. Although
individual exceptions exist, the approach produced consistently low scores on all evaluation
metrics. However, ICA denoising was implemented here using FSL's ICA-AROMA. This
package was selected because it does not require classifier training. More sophisticated ICA
denoising tools such as MELODIC or ICA-FIX involve a visual review of training data to
generate a set of noise classifiers based on the temporal, spatial, and frequency characteristics
of identified artifacts (Salimi-Khorshidi et al., 2014; Griffanti et al., 2017). These options were not
considered here because we sought to evaluate tools for motion correction that could be
implemented in an automated pipeline. The potential of ICA for denoising task-based data
should not be dismissed; rather, our results only indicate that the use of untrained ICA is
probably suboptimal compared to other options, many of which are also less computationally
intensive.
Frame censoring has appeared in several recent task-based studies (O'Hearn et al.,
2016; Bakkour et al., 2017; Davis et al., 2017). In fact, it was an experience with frame
censoring in the analysis of in-scanner speech production (Rogers et al., 2020) that motivated
our interest in comparing motion correction approaches. We found that modest levels of frame
censoring (e.g., 2–5% data loss) revealed a regional activation in high-motion subjects that
appeared in low-motion subjects but was not apparent when standard (RP6) motion
compensation was used. This suggested that use of a discrete rather than a continuous
nuisance regressor may better preserve task variance in some applications. However, a more
nuanced picture emerges from the present results, which suggest frame censoring is neither
universally superior to nor worse than RP6. One possibility is that frame censoring performance
involves a complex interaction between data quantity and quality. As each censored frame
introduces an additional regressor to the design matrix, eventually the reduction in error
variance may be overwhelmed by a loss of model degrees of freedom. This is anecdotally
supported by a decline in many of the metric results observed here at the most stringent FD or

DVARS thresholds, an effect that was even more pronounced when 40% maximal censoring
was explored in pilot work (data not shown). A prerequisite to improving frame censoring
performance in future work would be to quantify this tradeoff.
420   One might argue that frame censoring should be based on a selected fixed threshold
rather than a targeted percent data loss. The present results offer only mixed support for such a
position. We investigated applying a fixed FD threshold of 0.9 to these data (**Supplemental**
Figure 1). This value was used by Siegel and colleagues (2014) in their exploration of frame
censoring and has since been used in published functional studies (e.g., Davis et al., 2017). In
most of the datasets considered here, a 0.9 FD threshold would have resulted in less than 1%
of frames being censored. This would be a reasonable amount of data loss, and might lead to
some improvements compared to a standard RP6 approach (although we did not test this
directly). However, ds000228/adults, ds001748/teens, and ds002382/YA would have incurred a
1-2% data loss, ds001748/child and ds002382/OA approximately 5% data loss, and
ds000228/child approximately 13% data loss. These outcomes do not correspond to the best
performance obtained across all approaches. Whole-brain or ROI-constrained maximum-t
metrics peak at these values in some, but not all, datasets. Mean effect size and Dice
coefficients add little to the evaluation as they appear largely insensitive to frame censoring
thresholds in this range. Taken together, these results suggest there is no single threshold value
that will optimize frame censoring for all applications.
436   Finally, it should be noted that we have focused on retrospective correction—that is,
strategies for dealing with motion in existing data. A complementary approach would be to
reduce head motion during acquisition. Protocols have been developed that offer promise to
reduce subject motion, including movie viewing (Greene et al., 2018), custom head molds
(Power et al., 2019), and providing feedback to participants (Dosenbach et al., 2017; Krause et
al., 2019). However, these have not yet been widely adopted, nor are all compatible with task-
based fMRI. With increasing awareness of the challenges caused by participant motion,
perhaps greater interest in motion reduction (as opposed to mitigation) will follow.
444   Clearly, the present results do not identify unequivocal guidelines to select a motion
correction strategy. Given the variability observed across datasets, with identical processing
pipelines, exploring multiple strategies in a given dataset may be the best way of reducing
motion artifacts, adding another set of parameters to an already large space of possible
analyses (Carp, 2012; Poldrack et al., 2017; Botvinik-Nezer et al., 2020). Our results suggest
that—frustratingly—no single motion correction strategy will give optimal results on every metric
in every study, and that choices require considering both the nature of the specific data of
interest and the most relevant outcome measure.
452
453

455 **Acknowledgments**

456   This work was supported by grants R01 DC014281, R01 DC016594, R21 DC016086, and T32
457   EB014855 (to A.B.) from the US National Institutes of Health. OpenNeuro is supported by NSF
458   Grant OCI-1131441.

459
460
461

References

Ardekani BA, Bachman AH, Helpern JA (2001) A quantitative comparison of motion detection
algorithms in fMRI. Magn Reson Imaging 19:959–963.

Ashburner J, Friston KJ (2004) Rigid Body Registration. In: Human Brain Function, Second.
(Frackowiak RSJ, Friston KJ, Frith CD, Dolan RJ, Price CJ, Zeki S, Ashburner J, Penny W,
eds), pp 635–653. New York: Elsevier.

Ashburner J, Friston KJ (2005) Unified segmentation. Neuroimage 26:839–851.

Bakkour A, Lewis-Peacock JA, Poldrack RA, Schonberg T (2017) Neural mechanisms of cue-
approach training. Neuroimage 151:92–104.

Bennett CM, Miller MB (2010) How reliable are the results from functional magnetic resonance
imaging? Ann N Y Acad Sci 1191:133–155.

Bianciardi M, Fukunaga M, van Gelderen P, Horovitz SG, de Zwart JA, Shmueli K, Duyn JH
(2009) Sources of functional magnetic resonance imaging signal fluctuations in the human
brain at rest: a 7 T study. Magn Reson Imaging 27:1019–1029.

Birn RM, Molloy EK, Patriat R, Parker T, Meier TB, Kirk GR, Nair VA, Meyerand ME,
Prabhakaran V (2013) The effect of scan length on the reliability of resting-state fMRI
connectivity estimates. Neuroimage 83:550–558.

Botvinik-Nezer R et al. (2020) Variability in the analysis of a single neuroimaging dataset by
many teams. Nature 582:84–88.

Carp J (2012) On the plurality of (methodological) worlds: estimating the analytic flexibility of
FMRI experiments. Front Neurosci 6:149.

Courtney AL, PeConga EK, Wagner DD, Rapuano KM (2018) Calorie information and dieting
status modulate reward and control activation during the evaluation of food images. PLoS
One 13:e0204744.

Cusack R, Vicente-Grabovetsky A, Mitchell DJ, Wild CJ, Auer T, Linke AC, Peelle JE (2015)
Automatic analysis (aa): Efficient neuroimaging workflows and parallel processing using
Matlab and XML. Front Neuroinform 8:90.

Davis T, Goldwater M, Giron J (2017) From Concrete Examples to Abstract Relations: The
Rostrolateral Prefrontal Cortex Integrates Novel Examples into Relational Categories.
Cereb Cortex 27:2652–2670.

Diedrichsen J, Shadmehr R (2005) Detecting and adjusting for artifacts in fMRI time series data.
Neuroimage 27:624–634.

Dockès J, Poldrack RA, Primet R, Gözükan H, Yarkoni T, Suchanek F, Thirion B, Varoquaux G
(2020) NeuroQuery, comprehensive meta-analysis of human brain mapping. Elife 9
Available at: http://dx.doi.org/10.7554/eLife.53385.

Dosenbach NUF, Koller JM, Earl EA, Miranda-Dominguez O, Klein RL, Van AN, Snyder AZ,
Nagel BJ, Nigg JT, Nguyen AL, Wesevich V, Greene DJ, Fair DA (2017) Real-time motion
analytics during brain MRI improve data quality and reduce costs. Neuroimage 161:80–93.

Duncan KJ, Pattamadilok C, Knierim I, Devlin JT (2009) Consistency and variability in functional
localisers. Neuroimage 46:1018–1026.

Eickhoff SB, Stephan KE, Mohlberg H, Grefkes C, Fink GR, Amunts K, Zilles K (2005) A new
SPM toolbox for combining probabilistic cytoarchitectonic maps and functional imaging
data. Neuroimage 25:1325–1335.

Elliott ML, Knodt AR, Ireland D, Morris ML, Poulton R, Ramrakha S, Sison ML, Moffitt TE, Caspi
A, Hariri AR (2020) What Is the Test-Retest Reliability of Common Task-Functional MRI
Measures? New Empirical Evidence and a Meta-Analysis. Psychol Sci 31:792–806.

Friston KJ, Williams S, Howard R, Frackowiak RS, Turner R (1996) Movement-related effects in
fMRI time-series. Magn Reson Med 35:346–355.

Fynes-Clinton S, Marstaller L, Burianová H (2019) Differentiation of functional networks during
long-term memory retrieval in children and adolescents. Neuroimage 191:93–103.

Gorgolewski KJ, Storkey A, Bastin ME, Whittle IR, Wardlaw JM, Pernet CR (2013a) A test-retest
functional MRI dataset for motor, language and spatial attention functions. Available at:
http://gigadb.org/dataset/100051.

Gorgolewski KJ, Storkey AJ, Bastin ME, Whittle I, Pernet CR (2013b) Single subject fMRI test–
retest reliability metrics and confounding factors. Neuroimage 69:231–243.

Gratton C, Dworetsky A, Coalson RS, Adeyemo B, Laumann TO, Wig GS, Kong TS, Gratton G,
Fabiani M, Barch DM, Tranel D, Dominguez OM-, Fair DA, Dosenbach NUF, Snyder AZ,
Perlmutter JS, Petersen SE, Campbell MC (2020a) Removal of high frequency
contamination from motion estimates in single-band fMRI saves data without biasing
functional connectivity. Neuroimage:116866.

Gratton C, Kraus BT, Greene DJ, Gordon EM, Laumann TO, Nelson SM, Dosenbach NUF,
Petersen SE (2020b) Defining Individual-Specific Functional Neuroanatomy for Precision
Psychiatry. Biol Psychiatry 88:28–39.

Greene DJ, Koller JM, Hampton JM, Wesevich V, Van AN, Nguyen AL, Hoyt CR, McIntyre L,
Earl EA, Klein RL, Shimony JS, Petersen SE, Schlaggar BL, Fair DA, Dosenbach NUF
(2018) Behavioral interventions for reducing head motion during MRI scans in children.
Neuroimage 171:234–245.

Griffanti L, Douaud G, Bijsterbosch J, Evangelisti S, Alfaro-Almagro F, Glasser MF, Duff EP,
Fitzgibbon S, Westphal R, Carone D, Beckmann CF, Smith SM (2017) Hand classification
of fMRI ICA noise components. Neuroimage 154:188–205.

Jenkinson M, Bannister PR, Brady JM, Smith SM (2002) Improved optimisation for the robust
and accurate linear registration and motion correction of brain images. Neuroimage
17:825–841.

Jenkinson M, Beckmann CF, Behrens TEJ, Woolrich MW, Smith SM (2012) FSL. Neuroimage
62:782–790.

Johnstone T, Ores Walsh KS, Greischar LL, Alexander AL, Fox AS, Davidson RJ, Oakes TR
(2006) Motion correction and the use of motion covariates in multiple-subject fMRI analysis.

539   Hum Brain Mapp 27:779–788.

540 Kelly AMC, Uddin LQ, Biswal BB, Castellanos FX, Milham MP (2008) Competition between
541   functional brain networks mediates behavioral variability. Neuroimage 39:527–537.

542 Krause F, Benjamins C, Eck J, Lührs M, van Hoof R, Goebel R (2019) Active head motion
543   reduction in magnetic resonance imaging using tactile feedback. Hum Brain Mapp
544   40:4026–4037.

545 Laumann TO, Gordon EM, Adeyemo B, Snyder AZ, Joo SJ, Chen M-Y, Gilmore AW,
546   McDermott KB, Nelson SM, Dosenbach NUF, Schlaggar BL, Mumford JA, Poldrack RA,
547   Petersen SE (2015) Functional System and Areal Organization of a Highly Sampled
548   Individual Human Brain. Neuron 87:657–670.

549 Lemieux L, Salek-Haddadi A, Lund TE, Laufs H, Carmichael D (2007) Modelling large motion
550   events in fMRI studies of patients with epilepsy. Magn Reson Imaging 25:894–901.

551 Lewis-Peacock JA, Postle BR (2008) Temporary activation of long-term memory supports
552   working memory. J Neurosci 28:8765–8771.

553 Markiewicz CJ, Gorgolewski KJ, Feingold F, Blair R, Halchenko YO, Miller E, Hardcastle N,
554   Wexler J, Esteban O, Goncalves M, Jwa A, Poldrack RA (2021) OpenNeuro: An open
555   resource for sharing of neuroimaging data. bioRxiv:2021.06.28.450168 Available at:
556   https://www.biorxiv.org/content/10.1101/2021.06.28.450168v1.full.pdf+html [Accessed July
557   5, 2021].

558 Oakes TR, Johnstone T, Ores Walsh KS, Greischar LL, Alexander AL, Fox AS, Davidson RJ
559   (2005) Comparison of fMRI motion correction software tools. Neuroimage 28:529–543.

560 O'Hearn K, Velanova K, Lynn A, Wright C, Hallquist M, Minshew N, Luna B (2016)
561   Abnormalities in brain systems supporting individuation and enumeration in autism. Autism
562   Res 9:82–96.

563 Patel AX, Kundu P, Rubinov M, Jones PS, Vértes PE, Ersche KD, Suckling J, Bullmore ET
564   (2014) A wavelet method for modeling and despiking motion artifacts from resting-state
565   fMRI time series. Neuroimage 95:287–304.

566 Poldrack RA, Baker CI, Durnez J, Gorgolewski KJ, Matthews PM, Munafo MR, Nichols TE,
567   Poline JB, Vul E, Yarkoni T (2017) Scanning the horizon: towards transparent and
568   reproducible neuroimaging research. Nat Rev Neurosci 18:115–126.

569 Poldrack RA, Barch DM, Mitchell JP, Wager TD, Wagner AD, Devlin JT, Cumba C, Koyejo O,
570   Milham MP (2013) Toward open sharing of task-based fMRI data: the OpenfMRI project.
571   Front Neuroinform 7:12.

572 Power JD (2017) A simple but useful way to assess fMRI scan qualities. Neuroimage 154:150–
573   158.

574 Power JD, Barnes KA, Snyder AZ, Schlaggar BL, Petersen SE (2012) Spurious but systematic
575   correlations in functional connectivity MRI networks arise from subject motion. Neuroimage
576   59:2142–2154.

577 Power JD, Schlaggar BL, Petersen SE (2015) Recent progress and outstanding issues in

motion correction in resting state fMRI. Neuroimage 105:536–551.

Power JD, Silver BM, Silverman MR, Ajodan EL, Bos DJ, Jones RM (2019) Customized head
molds reduce motion during resting state fMRI scans. Neuroimage 189:141–149.

Pruim RHR, Mennes M, van Rooij D, Llera A, Buitelaar JK, Beckmann CF (2015) ICA-AROMA:
A robust ICA-based strategy for removing motion artifacts from fMRI data. Neuroimage
112:267–277.

Richardson H, Lisandrelli G, Riobueno-Naylor A, Saxe R (2018) Development of the social brain
from age three to twelve years. Nat Commun 9:1027.

Rogers CS, Jones MS, McConkey S, Spehar B, Van Engen KJ, Sommers MS, Peelle JE (2020)
Age-related differences in auditory cortex activity during spoken word recognition.
Neurobiology of Language 1:452–473.

Salimi-Khorshidi G, Douaud G, Beckmann CF, Glasser MF, Griffanti L, Smith SM (2014)
Automatic denoising of functional MRI data: combining independent component analysis
and hierarchical fusion of classifiers. Neuroimage 90:449–468.

Satterthwaite TD, Ciric R, Roalf DR, Davatzikos C, Bassett DS, Wolf DH (2019) Motion artifact
in studies of functional connectivity: Characteristics and mitigation strategies. Hum Brain
Mapp 40:2033–2051.

Siegel JS, Power JD, Dubis JW, Vogel AC, Church JA, Schlaggar BL, Petersen SE (2014)
Statistical improvements in functional magnetic resonance imaging analyses produced by
censoring high-motion data points. Hum Brain Mapp 35:1981–1996.

Smith SM, Beckmann CF, Ramnani N, Woolrich MW, Bannister PR, Jenkinson M, Matthews
PM, McGonigle DJ (2005) Variability in fMRI: a re-examination of inter-session differences.
Hum Brain Mapp 24:248–257.

Smyser CD, Snyder AZ, Neil JJ (2011) Functional connectivity MRI in infants: exploration of the
functional organization of the developing brain. Neuroimage 56:1437–1452.

Van Dijk KRA, Sabuncu MR, Buckner RL (2012) The influence of head motion on intrinsic
functional connectivity MRI. Neuroimage 59:431–438.