MACA: Marker-based automatic cell-type annotation for single cell expression data

Yang Xu[1,2], Simon J. Baumgart [1,3], Christian Stegmann[1], Sikander Hayat[1,4]

1. Bayer-Broad Joint Precision Cardiology Lab, Cambridge, MA, USA

2. Current address: UT-ORNL Graduate School of Genome Science and Technology, The

University of Tennessee, Knoxville, TN, USA

3. Current address: Novo Nordisk, Data Mining and Bioinformatics, Copenhagen, Denmark

4. Current address: Institute of Experimental Medicine and Systems Biology, RWTH Aachen

University, Aachen, Germany

Abstract

Summary: Accurately identifying cell-types is a critical step in single-cell sequencing analyses.

Here, we present marker-based automatic cell-type annotation (MACA), a new tool for

annotating single-cell transcriptomics datasets. We developed MACA by testing 4 cell-type

scoring methods with 2 public cell-marker databases as reference in 6 single-cell studies. MACA

compares favorably to 4 existing marker-based cell-type annotation methods in terms of

accuracy and speed. We show that MACA can annotate a large single-nuclei RNA-seq study in

minutes on human hearts with ~290k cells. MACA scales easily to large datasets and can broadly

help experts to annotate cell types in single-cell transcriptomics datasets, and we envision

MACA provides a new opportunity for integration and standardization of cell-type annotation

across multiple datasets.

Availability and implementation: MACA is written in python and released under GNU

General Public License v3.0. The source code is available at https://github.com/ImXman/MACA.

Contact: Yang Xu (yxu71@vols.utk.edu), Sikander Hayat (hayat221@gmail.com)

1 Introduction

Identifying constituent cell-types in a single-cell dataset is fundamental to understand the

underlying biology of the system. Many computational methods have been proposed to

automatically label cells, and a benchmark study shows that a standard Support Vector Machine

(SVM) classifier outperforms most other sophisticated supervised methods and can achieve high

accuracy in cell-type assignment (Abdelaal, et al., 2019). However, due to lack of ground-truth

in most single cell studies, supervised classification approaches are not feasible and may not be

generalized for new single cell studies with different experimental designs. Therefore,

unsupervised clustering approaches are still the predominant options for single-cell data analysis

(Lähnemann, et al., 2020). Unsupervised approaches usually require human assistance in both

defining clustering resolution and manual annotation of cell-types. This results in cell-type

annotation being time-consuming and less reproducible due to human inference. As more single

cell studies are available, summarizing markers identified in these studies to construct a marker

database becomes an alternative approach for automatic cell-type annotation. For example,

PanglaoDB (Franzén, et al., 2019) and CellMarker (Zhang, et al., 2019) are two marker

databases that summarize markers found in numerous single cell studies and cover a broad range

of major cell-types in human and mouse. Also, NeuroExpresso (Mancarci, et al., 2017) is a

specialized database for brain cell-types. Taking advantage of those databases for robust cell-

type identification, we present MACA, a **m**arker-based **a**utomatic **c**ell-type **a**nnotation method

and show how MACA automatically annotates cell-types with high speed and accuracy. We

envision MACA as an aid for cell-type annotation to be used by both experts and non-experts.

2 MACA implementation

MACA takes as input expression profiles measured by single cell or nuclei RNA-seq experiments. MACA calculates two cell-type labels for each cell based on 1) an individual cell expression profile and 2) a collective clustering profile. From these, a final cell-type label is generated according to a normalized confusion matrix (Figure 1a). MACA first computes cell-type scores for each cell, using a scoring method based on a marker database or user-defined marker lists. The scoring method uses the raw gene count to calculate a cell-type score for each cell, according to gene markers of this cell-type. This results in converting a gene expression matrix to cell-type score matrix. Then, MACA generates a label (Label 1) for each cell by identifying the cell-type associated with the highest score. Independently, using the matrix of cell-type scores as input, the Louvain community detection algorithm (Blondel, et al., 2008) is applied to generate Label 2, which is a clustering label to which a cell belongs. Since the number of cell types is usually unknown, MACA tries clustering at greater resolution to over-cluster cells into many small but homogeneous groups.

Both Label 1 and Label 2 serve complimentary functions. Label 1 is assigned on a per-cell basis which may result in incorrectly annotating many cells due to noisiness in the maximum cell-type score for each cell. This may occur when the putative cell-type feature is covered up by ambient RNAs from dominant cell-types (Pliner, et al., 2019). On the other hand, Label 2 is likely to suffer from a common problem in single cell RNA-seq clustering analysis, where cells may share the same dominant features, even though they have been clustered into different groups because of subtle differences. Additionally, results from a clustering analysis can often vary since

clustering is non-deterministic. Due to its dependence on user's decisions, mostly the choices of

clustering resolution and neighborhood size.

To address these issues, MACA combines Label 1 and Label 2 to get a comprehensive cell-type

annotation by mapping Label 2 to Label 1 through a normalized confusion matrix. In the

confusion matrix C, $c_{i,j}$ represents the number of cells that were clustered as the i^{th} cluster in

Label 2 and labeled as the j^{th} cell-type in Label 1. The basic assumption of mapping Label 2 to

Label 1 through a confusion matrix is that cells with the same clustering label (Label 2) should

have the same cell-type label (Label 1). Ideally, if cells were identified to be in the same cluster,

they should all share the same cell-type, and this cell-type has the highest score for cells in that

cluster. However, in real data, this is rarely the case, as we argued above. Therefore, using a

confusion matrix, we look for consensus between Label 1 and Label 2, by searching for the

highest cell-type score in each cluster. Here, we compute the normalized confusion matrix C_n

through dividing confusion matrix C by the size of the cluster: $c_{i,j} = \frac{c_{i,j}}{\sum_{j=1}^{N} c_{i,j}}$, and we search for

column number with the largest value for each row (Figure 1b). If $max_j(c_{i,j}) \geq 0.5$, the i^{th}

cluster would be assigned as the j^{th} cell-type, as more than 50% of cells in the i^{th} cluster are

labeled as the j^{th} cell-type (Case 1). For cases where $max_j(c_{i,j}) < 0.5$, it is likely that cell

identities of some cells were covered up by ambient RNAs from dominant cell-types (Case 2).

Therefore, MACA records significant or at least the top-3 cell-types for each cell in the i^{th}

cluster based on cell-type scores. To find significant cell-types for each cell, we get a distribution

of scores of all cell-types for each cell and define those cell-types as significant if their z-scores >

3. If the number of significant cell-types is less than 3, we would keep the top-3 cell-types.

Doing this can retrieve more potential cell-type labels for this cluster, and each cell will

contribute at least 3 candidates into a pool of candidate cell-types for this cluster. Then, MACA

calculates frequency of each candidate cell-type in this pool and assigns the i^{th} cluster as the

cell-type with the highest frequency if the frequency exceeds half the size of the cluster

($max_j(f_{i,j}) \geq 0.5$) (Case 2a). Otherwise, the i^{th} cluster would be labeled as "unassigned"

($max_j(f_{i,j}) < 0.5$) (Case 2b), which is the case that cells in this cluster do not have an

agreement on which cell-types they belong to. For the choice of 0.5, we will show our

examination in the next Results section. As we mentioned before, clustering-based cell-type

identification largely depends on user's choice, for example the choices of clustering resolution

and neighborhood size. Therefore, the outcome may vary among different users. To have a more

reproducible outcome, we cluster cells with different clustering parameters to get multiple

clustering assignments (Label 2s). Repeating the procedure of mapping Label 2 to Label 1 will

enable us to get an ensemble annotation through voting, and this ensemble annotation is less

influenced by a single clustering choice (Figure 1c). Using ensemble approach also offers a naïve

way of scoring MACA-based cell-type predictions. Users can set up a threshold to filter cells

whose annotations are less consistent in outcomes of different clustering trials, and we also

provide examinations in the next section to help users choose a reasonable threshold for

annotation with quality. In this study, we generated clusters using Louvain method with 3

different resolutions and 3 different numbers of neighborhood, which results in 9 different

clustering labels (Label 2s). After mapping these 9 Label 2s to Label 1, we generated 9 cell-type

annotations. Then, we used a voting approach to get the final annotations (the highest votes from

the 9 annotations). Users can also increase the number of clustering trials to have a larger voting

pool for annotation ensemble or decrease the number to save computation time.

Back to converting gene expression matrix to cell-type score matrix, we collected 4 different

scoring methods that were proposed to do the conversion. These scoring methods are either

named by authors, or we named them after the last name of the first author. PlinerScore was a

part of Garnett that was designed to annotate cell-types through supervised classification (Pliner,

et al., 2019). The uniqueness of PlinerScore is the use of TF-IDF transformation to deal with

specificity of a gene marker and a cutoff to deal with issue of free mRNA in single-cell RNA-seq

data. AUCell comes from SENIC, which uses gene sets to quantify regulon activities of single-

cell expression data (Aibar, et al., 2017). In this study, AUCell quantifies the enrichment of

every cell-type as an area under the recovery curve (AUC) across the ranking of all gene markers

in a particular cell. This assessment is cell-wise and is different from PlinerScore that requires

transformation of the whole dataset. Both CIM and DingScore simply use the total expression of

all gene markers of a particular cell-type as the cell-type score (Ding, et al., 2020; Efroni, et al.,

2015). CIM normalizes the total expression by multiplying a weight that is defined as the number

of expressed gene markers divided by the number of all gene markers of this cell-type.

DingScore, on the other hand, normalizes the total expression of one cell-type by dividing total

expression of all genes. Since some cell-types have a longer list of marker genes than others,

cell-types with more marker genes in the database would have larger cell-type scores.

Normalization in CIM was considered to address this issue. However, PlinerScore and

DingScore were not intentionally designed to cope with unbalanced marker lists. To deal with

this issue, we did a similar processing to normalization in CIM, which is dividing the score of

each cell type by the number of expressed markers in that cell type. However, AUCell is a

completely different approach from the other 3 scoring methods, which does not simply sum up

values of marker genes for a given cell-type. So, we ran AUCell without extra processing for

returned values. Meanwhile, we show that the number of expressed marker genes in both

PanglaoDB and CellMarker across 6 single cell datasets tested in this study, and we found that

most cell-types in PanglaoDB have expressed marker genes within 0~60, while most cell-types

have less than 10 marker genes expressed in CellMarker (Supplementary Figure S1). For both

PanglaoDB and CellMarker, we can conclude that cell-types with over 100 expressed marker

genes are a minority.

In practice, we build MACA in the analysis pipeline of Scanpy, and MACA takes data in the

format of "anndata" in Python (Wolf, et al., 2018). Expression data are preprocessed through cell

and gene filtering, and transformed by LogNormlization method, the common practice in single

cell analysis. Then, the user provides marker information in the form of Python dictionary, and

MACA transforms gene expression matrix to cell-type score matrix. Next, annotation by MACA

can be summarized into 4 steps as shown in Figure 1: 1) Louvain clustering to generate Label 2;

2) Generating Label 1 via max function; 3) Mapping Label 2 to Label 1 through normalized

confusion matrix; 4) Repeating step 1 to 3 to have ensembled annotation.

3 Results

The key component for optimal performance of MACA is constructing cell-type scores from the

gene expression matrix. We investigated 4 scoring methods that have been proposed to transform

gene expression matrix to cell-type score matrix (Aibar, et al., 2017; Ding, et al., 2020; Efroni, et

al., 2015; Pliner, et al., 2019), and we tested these methods with 2 public marker databases

(Franzén, et al., 2019; Zhang, et al., 2019) in 6 single cell studies comprised of 3000 to 20000

cells (Baron, et al., 2016; Cui, et al., 2019; Tian, et al., 2019; Vieira Braga, et al., 2019; Wang, et

al., 2020; Zheng, et al., 2017), which include 3 benchmark datasets (Supplementary Table S1)

(Abdelaal, et al., 2019). To evaluate these annotation outcomes, we used Adjusted Rand Index

(ARI) and Normalized Mutual Information (NMI). Both ARI and NMI are calculated by

measuring similarity or agreement between our annotations and authors' annotations. For the 3

benchmark datasets, authors' annotations would be the ground truth label, while authors'

annotations in the other 3 datasets are at least created under careful investigation. Therefore, use

of ARI and NMI, in this case, is to show how well we can reproduce authors' outcomes. We

found annotations using PlinerScore with markers in PanglaoDB have the largest agreement with

authors' annotations for all 6 datasets, in terms of both ARI and NMI (Table 1). Therefore,

MACA uses PanglaoDB with PlinerScore as the main marker database and scoring method,

respectively. When we define if Label 2 agrees with Label 1, we selected 0.5 as the threshold. It

is out of a simple reasoning of whether the half agrees. However, it is possible to set up a less or

more stringent threshold to define the consensus between Label 1 and 2. Thus, we further tested

how different thresholds will affect MACA's performance. We changed the threshold from 0.2

to 0.9 and performed our test in these 6 datasets. We expect annotations would vary, but

surprisingly, MACA's performance is quite robust to the choice of this parameter, except that we

observed drops of ARI and NMI in two datasets when using 0.9 as threshold (Supplementary

Table S2).

Next, we seek to compare MACA with other existing marker-based annotation tools. CellAssign

and SCINA are two computational methods that have been proposed for automatic cell-type

assignment (Zhang, et al., 2019; Zhang, et al., 2019). Both methods rely on statistical

interference to compute the probabilities of cell types, which are time- and computation-

intensive. Recently, Cell-ID was released for extraction of gene signature as well as cell-type

annotation (Cortal, et al., 2021). We also noticed scCATCH and SCSA, which are both cluster-

based annotation tools (Cao, et al., 2020; Shao, et al., 2020). Both scCATCH and SCSA require

identifying differential marker genes for each cluster via a statistical test implemented in Seurat

and then matching identified cluster markers to marker database (Butler, et al., 2018). Here, we

compared MACA with CellAssign, SCINA, Cell-ID, and scCATCH using these 6 single cell

studies and cell markers in PanglaoDB. We tested MACA, CellAssign, SCINA, Cell-ID, and

scCATCH on a workstation with 16-core CPU and 64GB memory. MACA can finish annotation

within 1 minute (cells around 3,000) and less than 2 minutes for a relatively large dataset (cells

up to 20,000 cells). On the datasets used and on our computational resources, scCATCH and

Cell-ID took longer than MACA to compute annotations and ranks as the second and third

fastest. In our hands, SCINA took around 20-minute time to finish annotation for a large dataset,

and CellAssign took the longest time to complete cell-type assignment and failed to annotate

data with > 20,000 cells due to lack of memory (Supplementary Table S3). Because annotation

by scCATCH needs clustering first and differential marker identification is highly affected by

clustering outcome, the investigator will need to do a thorough investigation to make sure that

clustering is not overdone or underestimated. In this study, we reported the highest and the

averaged outcomes of scCATCH in each dataset. Comparing these results with manual

annotations from the authors, we found 1) MACA labels cells had a higher consensus than

CellAssign, SCINA, Cell-ID, and scCATCH, in terms of both ARI and NMI, and 2) MACA and

scCATCH identify similar numbers of cell-types to author's annotations, while the other 3

methods, especially Cell-ID, report overall more different cell-types (Table 1). The low ARIs

and NMIs of CellAssign and Cell-ID can be counted as results of 1) many "unassigned" cells and

2) exceeding numbers of different cell-types over the numbers reported by authors. It is

important to note that other methods compared here were run on their default parameters. In

future, parameter tuning of those methods on a computer with higher memory should be carried

out for a comprehensive benchmarking on many datasets. Finally, to better evaluate annotations,

we used a machine learning approach to assess cell-type assignment. Training classifiers was

recently proposed by (Miao, et al., 2020) to assist in finding a good clustering resolution, and we

adopt this idea to evaluate our annotations. Basically, if the annotation is good enough, we can

train a classifier to predict cell type using gene-expression values with high accuracy. Conversely,

if there are many wrong labels, it would be hard for a classifier to make the right decision. We

performed 5-fold cross-validated training, where we split one dataset into 4-fold training set and

1-fold testing set and trained a SVM classifier on the training sets and applied the classifier to

predict labels for the testing set. This procedure repeats 5 times to get a mean accuracy. Instead

of treating authors' annotations as ground truth, this machine-learning evaluation provides an

independent angle to judge annotation quality. Indeed, MACA achieves high concordance with

authors' reported annotations and higher mean of accuracies than other methods (Supplementary

Table S4). Of note, high accuracy of SVM classifier is not equal to correctness of annotation.

Meanwhile, ARI and NMI reports similarity between two annotations but cannot reflect the

difference of annotation resolution. For example, MACA may return less cell-types than authors.

Moreover, annotation resolution of MACA highly depends on the number of cell-types in the

marker database, and it is likely that MACA cannot annotate some rare subtypes that do not

show up in the marker database. Here, we used confusion matrix to show how cell-type labels by

MACA are against cell-type labels by authors (Supplementary Figure S2). Take annotation of

human pancreas as an example, cells annotated by MACA as "Pancreatic stellate cells" fall into

3 groups that were annotated by author as "activated stellate cells", "quiescent stellate cells", and

"Schwann cells", respectively. Since MACA may have a different annotation resolution from the

author's, we performed a test to show how different annotation resolutions can affect

calculations of ARI and NMI. We included the human kidney (CD10-) data, which has 3

different annotation resolutions by the authors, from 5 major cell-types to 29 intermediate cell-

types, and to 50 fine cell-types (Kuppe, et al., 2021). We used MACA to annotate this data and

compared MACA's annotation with these 3 annotations. We found NMI is more robust to

change of annotation resolution than ARI. It also suggests that a higher ARI reflects similar

resolution between MACA and author. (Supplementary Figure S3).

As we mentioned above, using ensemble approach also offers user an option to filter cells whose

annotations are less consistent in outcomes of different clustering trials. However, it also causes

loss of cells for downstream analysis, like cellular composition analysis. To find a good balance

between having higher annotation quality and keeping most cells for downstream analysis, we

tested threshold of voting from 1/9 to 9/9, where the numerator means the minimum number of

votes required to keep the cell-annotation. With 1/9, all cells will be kept, with 2/9, cells with

annotations with at least 2 votes will be kept, while only cells that have the same annotation

across 9 clustering trials will be considered if threshold is set up as 9/9. We reported the results

across 10 datasets in Supplementary Table S5, and it may provide a reference for user to choose

a threshold that serves user's need. Of note, we kept all cells in other evaluations. Particularly, all

cells were used in benchmark with other methods. Here, we suggest setting up the threshold as

7/9. Next, we expect to show that annotation by MACA is applicable for most single cell RNA-

seq platforms. We re-annotated PBMC data from a new study by (Ding, et al., 2020). This data

consists of two biological samples from 9 platforms. We found that 1) both PBMC samples have

the same major cell-types, and these 9 platforms can successfully profile them (Supplementary

Figure S4a), and 2) annotation by MACA shows that all platforms profile similar cellular

components for these two PBMC samples, except CEL-Seq2 (Supplementary Figure S4b). These

results are largely consistent to the original report (Ding, et al., 2020). However, this PBMC data

didn't come with a ground-truth annotation, we further added the human pancreas data, which

consists of 5 independent studies profiled by 4 different single-cell RNA-seq platforms (Baron,

et al., 2016; Grün, et al., 2016; Lawlor, et al., 2017; Muraro, et al., 2016; Segerstolpe, et al.,

2016). Annotation by MACA has 0.929 ARI and 0.908 NMI against author-reported annotation,

and we also observed all major cell-types were revealed across all 4 platforms (Supplementary

Figure S4c).

Finally, we applied MACA to a single-nuclei RNA-seq dataset from all 4 chambers of the human

heart, comprised of ~290k nuclei (Tucker, et al., 2020). MACA could annotate each of the 4

chambers comprising of ~80K cells each in < 6 mins. Annotations by MACA have major

agreement with author's reported annotations with an average ARI and NMI of 0.63 and 0.76,

respectively (Supplementary Table S6). However, we also found some disagreements exist in

annotation of cells in from left and right atria. Therefore, we investigated disagreement between

MACA's and author's annotations, and found the biggest difference stems from disagreement in

assignments for neuronal cells and lymphocytes, which are both small-population cell types in

this dataset (1702 neuronal cells and 1503 lymphocytes out of ~290k). We found neuronal cells

weren't revealed and author-reported lymphocytes were reported as memory T cells in MACA's

annotation (Supplementary Table S7a and b).

By default, MACA works with the list marker genes and cell-types present in PanglaoDB, but

users can also input their own gene-lists. A major limitation of MACA is that it can only

annotate cell-types that are pre-defined in the marker reference, but with more marker gene-sets

becoming available with single-cell sequencing studies, we believe that MACA will be useful to

annotate heterogeneous single-cell datasets. This points us two future directions to improve

MACA. First, with more atlas studies that profile all sorts of biological systems, more refined

markers for small cell populations can be defined, and MACA could reach finer annotation

resolution by integrating markers from these new atlas studies. Second, weights of markers

should be incorporated into the scoring method of MACA, for example marker specificity and

expression strength. However, at the current stage, all markers have equal weights when they

contribute to cell-type scores, and we believe that incorporating marker weights will be

beneficial for accurate annotation. With a more refined marker database and cell-type scoring

method, MACA would rapidly perform integrated annotation across multiple datasets, and this is

very critical for downstream analyses like cellular component analysis across datasets under

different conditions. In fact, we noticed that combining PlinerScore and PanglaoDB to generate

new features has the advantages of correcting batch effects for integrated annotation across

datasets, and we aim to extend the use of MACA to standardization of cell-type annotation

across datasets in the future (see application in integrated annotation on GitHub of MACA).

Finally, we conclude that MACA is a suitable tool for automatic cell-type annotation that can aid

both experts and non-experts in rapid annotation of their single-cell datasets.

Acknowledgements

We would like to thank Mark Chaffin, Stephen Fleming and other members of the Precision

Cardiology Lab for providing useful feedback on the manuscript.

Disclosures

Simon Baumgart, Christian Stegmann and Sikander Hayat are employees of Bayer US LLC (a

subsidiary of Bayer AG) and may own stock in Bayer AG.

References

Abdelaal, T., *et al.* A comparison of automatic cell identification methods for single-cell RNA sequencing
data. *Genome biology* 2019;20(1):194-194.
Aibar, S., *et al.* SCENIC: single-cell regulatory network inference and clustering. *Nature methods*
2017;14(11):1083-1086.
Baron, M., *et al.* A Single-Cell Transcriptomic Map of the Human and Mouse Pancreas Reveals Inter- and
Intra-cell Population Structure. *Cell systems* 2016;3(4):346-360.e344.
Blondel, V.D., *et al.* Fast unfolding of communities in large networks. *Journal of Statistical Mechanics:*
Theory and Experiment 2008;2008(10):P10008-10012.
Butler, A., *et al.* Integrating single-cell transcriptomic data across different conditions, technologies, and
species. *Nature biotechnology* 2018;36(5):411-420.
Cao, Y., Wang, X. and Peng, G. SCSA: A Cell Type Annotation Tool for Single-Cell RNA-seq Data. *Frontiers*
in genetics 2020;11:490-490.
Cortal, A., *et al.* Gene signature extraction and cell identity recognition at the single-cell level with Cell-
ID. *Nature Biotechnology* 2021.
Cui, Y., *et al.* Single-Cell Transcriptome Analysis Maps the Developmental Track of the Human Heart. *Cell*
reports (Cambridge) 2019;26(7):1934-1950.e1935.
Ding, J., *et al.* Systematic comparison of single-cell and single-nucleus RNA-sequencing methods. *Nature*
biotechnology 2020;38(6):737-746.
Efroni, I., *et al.* Quantification of cell identity from single-cell gene expression profiles. *Genome biology*
2015;16(1):9-9.
Franzén, O., Gan, L.-M. and Björkegren, J.L.M. PanglaoDB: a web server for exploration of mouse and
human single-cell RNA sequencing data. *Database : the journal of biological databases and curation*
2019;2019.
Grün, D., *et al.* De Novo Prediction of Stem Cell Identity using Single-Cell Transcriptome Data. *Cell stem*
cell 2016;19(2):266-277.
Kuppe, C., *et al.* Decoding myofibroblast origins in human kidney fibrosis. *Nature* 2021;589(7841):281-
286.
Lähnemann, D., *et al.* Eleven grand challenges in single-cell data science. *Genome biology* 2020;21(1):31-
35.
Lawlor, N., *et al.* Single-cell transcriptomes identify human islet cell signatures and reveal cell-type–
specific expression changes in type 2 diabetes. *Genome research* 2017;27(2):208-222.
Mancarci, B.O., *et al.* Cross-Laboratory Analysis of Brain Cell Type Transcriptomes with Applications to
Interpretation of Bulk Tissue Data. *eNeuro* 2017;4(6):ENEURO.0212-0217.2017.
Miao, Z., *et al.* Putative cell type discovery from single-cell gene expression data. *Nature methods*
2020;17(6):621-628.

Muraro, Mauro J._, et al._ A Single-Cell Transcriptome Atlas of the Human Pancreas. _Cell systems_
2016;3(4):385-394.e383.
Pliner, H.A., Shendure, J. and Trapnell, C. Supervised classification enables rapid annotation of cell
atlases. _Nature methods_ 2019;16(10):983-986.
Segerstolpe, Å._, et al._ Single-Cell Transcriptome Profiling of Human Pancreatic Islets in Health and Type 2
Diabetes. _Cell metabolism_ 2016;24(4):593-607.
Shao, X._, et al._ scCATCH: Automatic Annotation on Cell Types of Clusters from Single-Cell RNA
Sequencing Data. _iScience_ 2020;23(3):100882.
Tian, L._, et al._ Benchmarking single cell RNA-sequencing analysis pipelines using mixture control
experiments. _Nature methods_ 2019;16(6):479-487.
Tucker, N.R._, et al._ Transcriptional and Cellular Diversity of the Human Heart. _Circulation (New York, N.Y.)_
2020.
Vieira Braga, F.A._, et al._ A cellular census of human lungs identifies novel cell states in health and in
asthma. _Nature medicine_ 2019;25(7):1153-1163.
Wang, L._, et al._ Single-cell reconstruction of the adult human heart during heart failure and recovery
reveals the cellular landscape underlying cardiac function. _Nature cell biology_ 2020;22(1):108-119.
Wolf, F.A., Angerer, P. and Theis, F.J. SCANPY: large-scale single-cell gene expression data analysis.
Genome biology 2018;19(1):15-15.
Zhang, A.W._, et al._ Probabilistic cell-type assignment of single-cell RNA-seq for tumor microenvironment
profiling. _Nature methods_ 2019;16(10):1007-1015.
Zhang, X._, et al._ CellMarker: a manually curated resource of cell markers in human and mouse. _Nucleic_
acids research 2019;47(D1):D721-D728.
Zhang, Z._, et al._ SCINA: A Semi-Supervised Subtyping Algorithm of Single Cells and Bulk Samples. _Genes_
2019;10(7):531.
Zheng, G.X.Y._, et al._ Massively parallel digital transcriptional profiling of single cells. _Nature_
communications 2017;8(1):14049-14049.

Figure 1

Figure 1. Schematic workflow of MACA. a, MACA converts gene expression matrix into cell-type score matrix based on cell marker database. MACA generates Label 1 by using max function and Label 2 by over-clustering all cells into small groups. MACA finally maps Label 2 to Label 1 via confusion matrix. b, Use of confusion matrix for cell-type annotation. c, In practical implementation, n sets of clustering parameters are used to generate n Label 2s. Mapping all Label 2s to Label 1 returns multiple annotations, and MACA ensembles these annotations by voting to generate the final cell-type prediction.

Table 1

ARI	PBMC (Zheng et al., 2017)	CellBench (Tian et al., 2019)	Pancreas (Baron et al., 2016)	Heart (Wang et al., 2020)	Heart (Cui et al., 2019)	Lung (Vieira et al., 2019)
PanglaoDB+PlinerScore	**0.95**	**0.92**	**0.90**	**0.71**	**0.61**	**0.45**
PanglaoDB+AUCell	0.04	0.00	0.78	0.39	0.47	0.29
PanglaoDB+CIM	0.28	**0.65**	**0.90**	0.27	0.30	0.33
PanglaoDB+DingScore	**0.83**	**0.74**	0.69	0.07	0.44	0.20
CellMarker+PlinerScore	0.38	0.43	0.27	**0.57**	0.13	0.21
CellMarker+AUCell	0.29	0.52	0.32	0.34	0.09	0.14
CellMarker+CIM	0.24	0.60	0.54	**0.56**	0.07	0.09
CellMarker+DingScore	0.22	0.55	0.38	0.37	0.19	NA
SCINA	0.46	0.63	**0.89**	0.13	**0.55**	0.31
CellAssign	NA	0.00	**0.89**	0.15	**0.53**	0.26
Cell-ID	0.50	0.17	0.57	0.10	0.49	**0.35**
scCATCH (best)	**0.62**	0.56	0.86	0.04	0.14	**0.60**
scCATCH (average)	0.57	0.40	0.66	0.04	0.05	**0.35**
NMI	PBMC (Zheng et al., 2017)	CellBench (Tian et al., 2019)	Pancreas (Baron et al., 2016)	Heart (Wang et al., 2020)	Heart (Cui et al., 2019)	Lung (Vieira et al., 2019)
PanglaoDB+PlinerScore	**0.89**	**0.92**	**0.88**	0.59	0.62	**0.59**
PanglaoDB+AUCell	0.09	0.00	0.79	0.41	0.50	0.31
PanglaoDB+CIM	0.51	**0.80**	**0.88**	0.30	0.44	0.40
PanglaoDB+DingScore	0.74	**0.85**	0.70	0.10	0.47	0.33
CellMarker+PlinerScore	0.44	0.64	0.57	**0.51**	0.32	0.42
CellMarker+AUCell	0.23	0.67	0.46	0.32	0.33	0.17
CellMarker+CIM	0.49	0.78	0.73	**0.41**	0.31	0.21
CellMarker+DingScore	0.43	0.73	0.60	0.34	0.33	0.08
SCINA	0.54	0.71	0.84	0.07	**0.54**	0.46
CellAssign	NA	0.06	**0.86**	0.08	0.51	0.49
Cell-ID	0.67	0.38	0.74	0.08	**0.55**	0.58
scCATCH (best)	**0.77**	0.70	0.84	0.05	0.30	**0.73**
scCATCH (average)	**0.75**	0.62	0.75	0.04	0.12	**0.63**
# of cell-types	PBMC (Zheng et al., 2017)	CellBench (Tian et al., 2019)	Pancreas (Baron et al., 2016)	Heart (Wang et al., 2020)	Heart (Cui et al., 2019)	Lung (Vieira et al., 2019)
MACA	8	6	11	8	7	13
SCINA	14	14	17	16	23	41
CellAssign	NA	9	17	18	24	31
Cell-ID	33	55	48	35	37	63
scCATCH (best)	9	5	10	3	3	16
Author's annotation	5	5	14	5	9	13

Table 1. Performance of MACA, CellAssign, SCINA, Cell-ID, and scCATACH in 6 scRNA-seq datasets, measured by ARI and NMI. 8 different settings of MACA include using 4 cell-type scoring methods (PlinerScore, AUCell, CIM, and DingScore) with 2 marker databases (PanglaoDB and CellMarker).