Joint modeling of choices and reaction times based on Bayesian contextual behavioural control

Sarah Schwöbel[1*]**, Dimitrije Markovic**[1]**, Michael N. Smolka**[2]**, Stefan Kiebel**[1,3]

*For correspondence:
sarah.schwoebel@tu-dresden.de

[1]Department of Psychology, Technische Universität Dresden, Dresden, Germany;
[2]Department of Psychiatry and Neuroimaging Center, Technische Universität Dresden, Dresden, Germany; [3]Centre for Tactile Internet with Human-in-the-Loop (CeTI), Technische Universität Dresden, Dresden, Germany

Abstract   In cognitive neuroscience and psychology, reaction times are an important behavioral measure. However, in instrumental learning and goal-directed decision making experiments, findings often rely only on choice probabilities from a value-based model, instead of reaction times. Recent advancements have shown that it is possible to connect value-based decision models with reaction time models, for example in a joint reinforcement learning and diffusion decision model. We propose a novel joint model of both choices and reaction times by combining a mechanistic account of Bayesian sequential decision making with a sampling procedure. Specifically, we use a recent context-specific Bayesian forward planning model which we extend by an MCMC sampler to obtain both choices and reaction times. We show that we can explain and reproduce well-known experimental findings in value based-decision making as well as classical inhibition and switching tasks. First, we use the proposed model to explain how instrumental learning and automatized behaviour result in decreased reaction times and improved accuracy. Second, we reproduce classical results in the Eriksen flanker task. Third, we reproduce established findings in task switching. These findings show that the proposed joint behavioral model may describe common underlying processes in all these types of decision making paradigms.

Introduction

Many key findings in psychology and cognitive neuroscience of the last decades are based on the measurement and analysis of both response accuracy and reaction times in behavioral experiments. For example, changes in both mean reaction times and response accuracy during and after conflicting decisions are typically interpreted to demonstrate underlying decision making processes. Such effects of classical experimental paradigms are remarkably stable and have also been used to show how decision making is impaired in several mental disorders (*Goschke, 2014*; *Gratton et al., 2018*; *Kozak and Cuthbert, 2016*; *Gratton et al., 1992*; *Stins et al., 2007*; *Kiesel et al., 2010*; *Monsell, 2003*).

Two important aspects that many of these classical experiments typically do not take into account are the influence of uncertainty and reward structure. To study these aspects, often sequential decision making tasks are used in the instrumental learning and value-based decision making literature, e.g. (*Daw et al., 2011*; *Kolling et al., 2014*). Here, the experimental findings usually do not rely on reaction time effects, but on a value-based decision model and associated choice prob-

abilities. These allow to infer model parameters that are used to characterize the underlying mechanism and explain inter-individual differences. The value-based decision making models typically used for such experiments are either variants of reinforcement learning models or Bayesian (active inference) models. However, in their original variants, these models do not describe reaction times associated with decisions.

Recently, there have been some successful joint applications of value-based decision models, specifically reinforcement learning, and reaction time models (*Milosavljevic et al., 2010*; *Pedersen et al., 2017*; *Fontanesi et al., 2019*; *Shahar et al., 2019*; *Miletić et al., 2021*), which are typically evidence accumulator models such as diffusion decision models (DDM) (*Ratcliff, 1978*; *Forstmann and Wagenmakers, 2015*, Chapter 3) and so-called race diffusion models (*Milosavljevic et al., 2010*). Here, the principled idea is to connect choice values and probabilities to reaction times by linking parameters in both models. For example, the trial-wise expected reward (Q-values) in reinforcement learning models can be used to vary the drift rate of a DDM (*Pedersen et al., 2017*). This approach has recently been extended to multi-choice tasks using race diffusion models, where instead of having one accumulator as in the DDM, each available choice option is associated with a different accumulator (*Fontanesi et al., 2019*; *Miletić et al., 2021*).

In this article, we will build upon and extend these recent approaches in combining value-based models with reaction times. We propose a novel model that accounts for both repetition and contextual effects, and encompasses uncertainty at multiple levels. We will show that this formalization allows us to model a wide range of findings, from classical reaction-time based cognitive control tasks to sequential value-based decision tasks.

As a value-based decision model we use a recently introduced Bayesian prior-based contextual control model for forward planning and goal-directed decision making (*Schwöbel et al., 2021*). This model has two key ingredients: (i) a prior over actions or action sequences which is learned based on repetitions and independent of reward expectations, and (ii) differences in the environment are described as different contexts that need to be inferred. To connect these internal variables to choices and reaction times, we use here a sampling-based action selection and reaction time algorithm. Sequences to be executed are sampled using a modified version of an independent Markov chain Monte Carlo (MCMC) sampler. The result of this probabilistic inference based on Bayesian independence sampling is a choice among a potentially large number of possible action sequences and the reaction time.

To illustrate this novel approach of jointly modeling choices and reaction times, we present three simulations that capture several well-established experimental findings. We use a sequential value-based decision task and two well-known cognitive control tasks, the Eriksen flanker task and task switching, which are commonly used as experimental paradigms to study cognitive processes and impaired decision making in mental disorders (*Goschke, 2014*; *Gratton et al., 2018*). First, using the value-based decision task, we show that our approach explains decreasing reaction times when learning goal-directed actions. As an agent becomes more certain about its context, reaction times decrease. Additionally, if a prior over behavior is learned, it facilitates faster and more reliable behavior, even up to the point that automatic, goal-independent, behavior emerges. Second, we demonstrate that the novel approach can in principle also be generalized to experiments and phenomena which would usually not be labelled as value-based decision making. To show this, we provide a mechanistic understanding of experimental phenomena in the Flanker task, a typical cognitive control task. This task is often interpreted to interference control which is a component of inhibitory control and we show how the conflict can be re-interpreted as a conflict between priors and contexts. Third, we demonstrate that we can provide an explanation for choices and reaction times in task switching, which is typically interpreted to measure updating of task-relevant information. We show that the effects can be interpreted as updating of context-specific representations as participants switch between two contexts. We close by discussing the implications of the underlying mechanism and its relation to alternative models.

 Methods

 In this section, we sketch the main idea behind the computational model of behavior used for

 simulations, and the novel reaction time algorithm which was used to generate agent's reaction

 times.

 Prior-based contextual control model

 The computational model of behavior is based on a hierarchical partially observable Markov de-

 cision process which is represented as a Bayesian generative model. In this model, the dynamics

 of the environment are clustered into episodes of fixed length, where the transition and reward

 dynamics in an episode are determined by the current context. Meaning, an agent represents dif-

 ferences in the environment as separate Markov decision processes (MDPs) which are learned for

 each context separately. Following ideas of active inference (*Friston et al., 2015*, *2016*) and the

 free energy principle (*Friston, 2009*, *2010*), an agent inverts this generative model using approxi-

 mate inference based on the variational free energy. More specifically, the computational model is

 an extension of the recently proposed hierarchical Bayesian forward planning and habit learning

 model (*Schwöbel et al., 2021*). Using this approach, we enable an agent to infer beliefs about future

 states, rewards, the context, as well as probabilities of choosing different actions or sequences of

 actions. In accordance with the active inference literature (*Friston et al., 2015*, *2016*) we will call a

 deterministic sequence of actions a policy.

 Concretely, in each episode, the agent infers the active context and loads the corresponding

 MDP. Using this MDP, it infers future states and rewards, and based on that posterior probabilities

 of choosing actions or policies. At the end of an episode, the agent also uses the newly observed

 rewards to update the parameters of the generative model, therewith learning the structure of the

 environment.

 We will only outline the key ideas of the computational model here, the interested reader can

 find the full mathematical details in the supplementary material (Supplementary files), as well as

 its python implementation on github[1]. The main idea can be sketched in a Bayesian equation as

$$p\left(\pi|c, R\right) \propto p\left(\pi|c\right) p\left(R|\pi, c\right) \tag{1}$$

 which describes the posterior probability $p\left(\pi|c, R\right)$ of whether an agent should choose policy π,

 given desired rewards R in the current context c. This posterior is a categorical distribution and

 according to Bayes' rule it is proportional to the likelihood of obtaining rewards under a policy in

 the current context $p\left(R|\pi, c\right)$ times a context-specific prior over policies $p\left(\pi|c\right)$.

 Importantly, the likelihood of rewards is calculated based on the MDP of the current context,

 which contains action-outcome contingencies and therewith encodes a goal-directed value of a pol-

 icy. The prior over policies on the other hand, is updated and learned based on Bayesian learning

 rules, which yield higher a priori probabilities for policies which have been previously chosen in this

 context. In our past work (*Schwöbel et al., 2021*) we proposed to interpret this as repetition-based

 habit learning, as this term implements a priori tendencies to repeat policies, independent of any

 reward expectations. Due to the prior being over policies, i.e. full action sequences, habits in this

 model can be additionally interpreted as context-dependent automatized action sequences.

 Response conflicts can emerge when the context is not directly observable, and there is uncer-

 tainty over the current context that cannot be fully resolved. Here, the agent may not not know

 with certainty which rules of the environment currently apply. To enable context inference, we

 introduced context observations, i.e. cues, into the model, where the agent maintains a genera-

 tive model of observation probabilities $p\left(o_c|c\right)$. Using Bayesian inversion, as well as the observed

 events of the context-dependent MDP, and context change probabilities $p\left(c|c'\right)$ the agent can infer

---

[1]https://github.com/SSchwoebel/BalancingControl

135 a posterior over contexts $p\left(c|o_c\right)$. The resulting posterior over policies

$$p\left(\pi|R\right) \quad \propto \quad \sum_c p\left(\pi|c, R\right) p\left(c|o_c\right) \tag{2}$$

$$= \quad p\left(\pi\right) p\left(R|\pi\right) \tag{3}$$

is then a mix of the context-specific posteriors over policies, weighted by the posterior probabilities
of each context. The posterior over policies $p\left(\pi|R\right)$ gives the probability that an agent should
choose a specific policy π, given it wants to receive rewards R. To select a policy, an agent will
sample from this posterior and execute the corresponding policy, the concrete sampling procedure
is described below. This posterior is proportional to the prior over policies $p\left(\pi\right)$ times the likelihood
of receiving rewards $p\left(R|\pi\right)$. In a conflict situation, the two conflicting policies would be similarly
weighted in the posterior, which leads to an increased error rate, as they would be similarly likely
to be selected.

Free parameters and simulation setups

This model has three free parameters which we will vary in the Results section to recreate known
reaction time effects in behavioral paradigms (see also Supplementary files): The initial values of
the hyperparameters of the prior over policies, the expected context transition probability, and
the context cue uncertainty.

As the prior over policies is learned, the parameters of the priors are treated hyper-priors (latent
random variables), defined as a Dirichlet distribution. The Dirichlet distribution is parameterised
using concentration parameters or pseudo counts α. Essentially, they count how often a policy was
chosen in a context, enabling repetition-based learning. While the counting rule is given by the
Bayesian updates, the initial values from which counting starts are free parameters which can be
chosen at the beginning of a simulation. We defined a so-called habitual tendency $h = \frac{1}{\alpha_{init}}$, where
$h = 1.0$ mean the counting starts at 1, giving each new choice a big effect on the prior over policies.
Hence we call an agent with high habitual tendency a "strong prior learner". Lower values of h, e.g.
$h = 0.001$, means the counting starts at high values, e.g. $\alpha = 1000$, which has the effect that each new
choice has little influence on the prior over policies. We call such an agent a "weak prior learner"
as in this setting the prior learning is almost neglectable as the pseudo counts are dominated by
initial values. In our previous study, we argued that the habitual tendency parameter may be used
to model inter-individual differences in habit tasks (*Schwöbel et al., 2021*). We show the effects of
strong and weak prior learning on reaction times and accuracy in a sequential decision task (see
Section Grid world).

However, not all initial pseudo counts need to be set to the same values. In order to model
a priori context–response associations, the initial values can be set so that the prior over policies
initially has a bias for specific actions or policies in a specific context. Additionally, the pseudo
counts can be subjected to a forgetting factor (see Supplementary files) which has them slowly
decrease over the course of an experiment, so that later choices still have a measurable effect on
the prior over policies. We use such a priori context–response associations to model interference
effects in the Flanker task (see Section Flanker task).

The free parameter of the context transition probability encodes an agent's assumption of how
likely a context change is expected to occur after the end of a behavioral episode. For example
in a task switching experiment, two task sets would correspond to two contexts, and the context
transition probability encodes how often an agent thinks the current task set will change. If set low,
an agents expects to stay within the same context, and even a context cue may not be enough for
the agent to infer that the context indeed changed. Traces of the previous context may then still
be present even after a context change. If set high, an agent expects a context change to happen
after every episode which eases inference of an actual context change, but may also lead to an
agent falsely loading the wrong context for action evaluation. We will use this to model inter trial
effects in a task switching experiment (see Section Task switching).

The context cue uncertainty encodes how certain an agent is to have perceived the context
cue correctly. For example in a task switching experiment, the current task set is cued, and the
uncertainty determines how well an agent perceived the cue. A high uncertainty means an agent
may not always rely on the cue and may instead use the previous context to make decisions, while
a low uncertainty means an agent perceived the cue well and can reliably load the current context.
We use this to model known cue presentation time effects on reaction times in a task switching
experiment (see Section Task switching).

Reaction time algorithm

To connect the quantities of the prior-based contextual control model to reaction times and their
distributions, we propose here a novel sampling-based reaction time modeling approach that gen-
eralizes well to arbitrary numbers of policies.
The idea of this approach is that the prior is learned and stored by the brain, and can quickly be
recalled and loaded upon receiving a context cue or inferring a context. This would allow the brain
to use the prior as a heuristic based on past choices, which would allow for fast action selection
in familiar situations, or when there is a tight deadline for selecting the action. The goal-directed
likelihood on the other hand may be slow and costly to evaluate fully, as it is based on an MDP.
We propose that the prior could be used to iteratively sample policies for which the likelihood is
then being evaluated. This sampling concludes once the agent is sufficiently sure to have sampled
enough policies to estimate the posterior accurately.
Mathematically, this process can be described using Markov chain Monte Carlo (MCMC) meth-
ods, specifically a modified independent Metropolis-Hastings algorithm which yields a Bayesian
independence sampler. Here, instead of using a conditional proposal distribution, a sample policy
π^* is drawn from the prior over policies $p(\pi)$

$$\pi^* \quad \sim \quad p(\pi) \tag{4}$$

$$\rho \quad = \quad \min\left\{\frac{p(\pi^*|R)\,p(\pi_{n-1})}{p(\pi_{n-1}|R)\,p(\pi^*)}, 1\right\} = \min\left\{\frac{p(R|\pi^*)}{p(R|\pi_{n-1})}, 1\right\} \tag{5}$$

$$\pi_n \quad = \quad \begin{cases} \pi^* & \text{with prob. } \rho \\ \pi_{n-1} & \text{with prob. } 1-\rho \end{cases} \tag{6}$$

after which the likelihood $p(R|\pi^*)$ of the sample π^* is evaluated, and the sample is accepted or
rejected into the chain (*Equation 6*) based on the ratio ρ of the likelihoods of the current and the
previous sample (*Equation 5*). The samples in the chain constitute i.i.d. drawn samples from the
posterior over policies.
Since the posterior being estimated is a categorical distribution, and the samples are i.i.d. drawn,
we can infer the parameters ϑ of the sampled distribution $p(\pi|\vartheta)$ from the entries of the chain, us-
ing a Dirichlet prior $p(\vartheta|\eta)$. To model reaction times, we propose that the sampling concludes
once a sufficient level of certainty about the distribution and therefore the best action sequence
is reached. To achieve this we use the Dirichlet distribution $p(\vartheta|\eta)$, whose entropy encodes how
certain one can be of having found the true parameters of the distribution to be estimated, where
a lower entropy corresponds to more certainty. Hence we use a threshold value $H_{thresh} = H_{init} +$
$(H_{init} + 1) * f$ of the Dirichlet entropy $H\left[p(\theta|\eta)\right]$ as a stopping criterion for the sampling, where the
free parameter $f \in (0, \infty)$ relates to the initial entropy H_{init} (see Section Grid world for influences
of f on reaction times). We define the threshold value depending on the initial entropy because
for continuous distributions, such as the Dirichlet distribution, entropy may become negative and
the initial entropy takes that into account.
Once the entropy has fallen below this threshold, the last sample in the chain determines which
policy is executed, and the number of samples the chain $N_{samples}$ required before finishing is taken
as an analogon of the reaction time. The resulting algorithm is shown in Algorithm 1 The parameter

f determines how much lower than the initial entropy the current entropy has to become, before
sampling concludes, and additional implements a constant value, in case the initial entropy is 0.
This way, the parameter f will allow us to up- and down-regulate sampling duration and reaction
times. Additionally, the shapes of the input distributions influence mean reaction times. As a
rule of thumb, under this algorithm sampling concludes earlier and reaction times are faster, the
more pronounced prior, likelihood, and the corresponding posterior over policies are. Vice versa,
for very uncertain distributions, e.g. when the goal is unknown or uncertain, sampling continues
longer and reaction times become slower.

> **Data:** prior $p(\pi)$, likelihood $p\left(R|\pi\right)$
> **Result:** sample $\pi_{execute}$, number of samples N_{sample}
> initialize Dirichlet counts $\eta_i = 1$
> initialize entropy $H_{curr} \leftarrow H\left[p\left(\vartheta|\eta\right)\right]$
> $n \leftarrow 0$
> draw $\pi_0 \sim p(\pi)$
> **while** $H_{curr} > H_{thresh}$ **do**
> > $n \leftarrow n + 1$
> > draw $\pi^* \sim p(\pi)$
> > calculate acceptance probability $\rho = \min\left\{\frac{p(R|\pi^*)}{p(R|\pi_{n-1})}, 1\right\}$
> > draw random number $r \in [0, 1]$
> > **if** $r < \rho$ **then**
> > > $\pi_n \leftarrow \pi^*$
> >
> > **else**
> > > $\pi_n \leftarrow \pi_{n-1}$
> >
> > **end**
> > $\eta_{\pi_n} \leftarrow \eta_{\pi_n} + 1$
> > $H_{curr} \leftarrow H\left[p\left(\vartheta|\eta\right)\right]$
>
> **end**
> $N_{samples} \leftarrow n$
> $\pi_{execute} \leftarrow \pi_n$

Algorithm 1: Action selection and reaction time algorithm

232 To describe measured reaction time data, we assume that the true reaction time in milliseconds
233 is linearly related to the number of samples by

$$RT = t_{nd} + t_{sample}N_{samples} \tag{7}$$

234 multiplying the number of samples $N_{samples}$ with a sampling time t_{sample}, and adding a non-decision
235 time t_{nd} which is due to perceptual processes and loading of information. In the simulations of the
236 flanker and task switching tasks below, we set $t_{sample} = 0.2ms$ and $t_{nd} = 100ms$, to map the number
237 of samples to reaction times below $1000ms$.

Results

We will first illustrate properties of the agent by showing reaction time effects and choice behavior
during a sequential value-based decision task, where goal-directed action sequences are learned
and executed. We specifically show how an agent starts learning rewards and becomes faster in its
actions. To focus on the reaction times effects, we keep these simulations deliberately simple and
let an agent learn paths to goals in a so-called grid world environment, as used before in theoret-
ical neuroscience, e.g. (*Doya et al., 2002*; *Schwöbel et al., 2018*; *Blakeman and Mareschal, 2020*).
We go on to show that the information processing principle underlying the prior-based contex-
tual control model can also be applied to qualitatively explain reaction time changes in standard
experimental cognitive control tasks. We use two different tasks, the Eriksen flanker task which
is typically interpreted to measure the inhibition aspect of cognitive control, and Task Switching,
which is usually interpreted to measure the cost of switching.

Grid world

In this section, we want to present key properties of the prior-based contextual control agent, as well as the novel reaction time algorithm, by showing we can replicate predicted experimental effects, as well as make novel predictions about how prior learning biases action selection and affects reaction times. Importantly, the agent evaluates behavior based on policies (action sequences) which allows us to not only show behavior and reaction times in single trial experiments, but when an agent learns sequential behavior in a multi-trial simulated experiment.

For simulations, we set up a simple grid world (Fig 1A). The grid consists of four rows by five columns yielding 20 grid cells. Agents start in the lower middle cell in position 3 (brown square) and have to navigate to either one of the two goal positions at cells 15 (blue square) and 11 (green square). In each cell, the agent has three options: move left, up and right. The tasks consists of 200 so-called miniblocks, where one miniblock consists of four trials. In each miniblock, the agent will start in cell 3 and is given the task to move to the indicated goal (either 1 or 2) within the four trials. During the first 100 miniblocks, goal 1 is active, and goal 2 is active in miniblocks 101 - 200. These two phases constitute two distinct contexts as they have different action–outcome contingencies. The agent is not informed about what cells give reward but has to find out by trial and error, inferring the contingencies of the current context.

Figure 1. Reaction times and behavior in a sequential instrumental learning task A: The grid world is an environment with 20 states. In each miniblock of four trials, the agent starts in the brown square (cell 3) and has to navigate to either goal 1 (blue square, cell 15) or goal 2 (green square, cell 11). The agent can use either of three actions in each step in the miniblock: left, up, and right. The experiment consist of 200 miniblocks. In the first 100 miniblocks, goal 1 is active, and in the second 100 miniblocks, goal 2 is active. **B**: Reaction times (as number of samples) of the first action in each miniblock over the course of the simulated experiment. The solid blue line shows the mean reaction time of 50 strong prior learning agents ($h = 1.0$). The dashed brown line shows the mean reaction time of 50 weak prior learning agents ($h = 0.001$). The shaded areas indicate a confidence interval of 95%. **C**: Accuracy in the same experiment, colors as in B. The accuracy was calculated as the percentage of miniblocks where agents successfully navigated to the currently active goal (goal 1 in trials 1-100, goal 2 in trials 101-200).

Reaction times and learning

Here we show that reaction times in the beginning of the experiment, as well after a context change, are high and decrease as an agent familiarizes itself with the environment. Additionally, we show that, as expected, how strongly an agent learns a prior over policies, has an effect on how fast reaction times decrease during the transition from goal-directed to more automatized behavior.

To do this, we divided up the agents to be simulated into 50 weak prior learner agents ($h = 0.001$) (see Section Free parameters and simulation setups) and 50 strong prior learning agents ($h = 1.0$). In our simulations, we use the reaction time of the first action as an indicator how fast an agent decided to use a specific sequence of four actions to reach its goal. *Figure 1*B shows the mean reaction times per miniblock, for strong and weak prior learners. As expected, both agent types, in the beginning of learning how to reach the goal, have slow reaction times. This is because the agent does not know where the goal is yet, which means that all policies have equal value and hence sampling takes longer. These reaction times decrease massively within the first 25 miniblocks, as agents become more certain about the goal location. Strong prior learners additionally learn a pronounced prior over policies (see Section Free parameters and simulation setups), thereby confining their action selection strongly, and displaying faster reaction times than the weak prior learners. The reaction times of both agent types converge after around 50 trials to stable values, where strong prior learners have generally larger and more variable reaction times.

After trial 100, the contingencies of the environment change and goal 2 becomes active. This means that agents have to infer a new context and learn new goal-directed action sequences. This switching and learning of a new context is clearly expressed in a large increase in reaction times for both agent types, see Fig 1B. As in the first context, both agent types learn the new goal location within the first 25 trials and the mean reaction times decrease again to a stable value.

*Figure 1*C shows the accuracy of the two agent types. At first, the accuracy increases for both the weak and strong prior learner, as they learn where the goal location is. Once this knowledge and reaction times have stabilized, the strong prior learner navigates to the goal more reliably, leading to an increased accuracy compared to the weak prior learner. This indicates that a strong prior in a stable context not only helps to make faster decisions, but also to choose policies that lead to the goal with more reliability. The accuracy drops to zero as goal 1 is deactivated and goal 2 pays out a reward. The weak prior learner has little a priori tendency to repeat any policies, so it is earlier able to reemploy trial and error and find the new goal location, achieving an average accuracy of 0.164 in trials 101-105. The strong prior learner on the other hand is influenced by the previous prior for 5 trials after the goal switch, which leads to it not becoming as slow with action selection, but also finding and navigating to the new goal later, achieving only an accuracy of 0.096 in trials 101-105.

Time pressure

How does one model time pressure of a decision in the proposed framework? To show this, we analyze the influence of the stopping criterion factor f, see Section Reaction time algorithm. This factor determines how long an agent will sample before committing to a policy, and it therewith up- and down-regulates reaction time means. Even though the stopping criterion factor f is an internal variable, it can be up- or down-regulated in response to external time pressure, allowing us to model time pressure when making a decision. Setting the parameter to a high value means that an agent can sample for a long time, until it is sufficiently certain it knows how successful different policies are expected to be. Setting the factor to a low value, indicates time pressure and a short deadline for making a decision. Values of this parameter not only influence reaction times, but also what policies an agent will choose.

We illustrate this in *Figure 2*A by showing the Kullback-Leibler (KL) divergence of sampled policies in the Markov chain to the prior and the posterior as a function of the factor f. One can see for a low factor, i.e. a short deadline, that an agent will rather choose a policy from the prior (low KL divergence to the prior), which corresponds to a repetition-based heuristic of behavior or a habit-

ual choice. For long factors and long deadlines, the agent will choose accurately from the posterior (low KL divergence to the posterior), which balances the a priori heuristic with the goal-directed value in the likelihood.

Figure 2. Properties of the RT algorithm This figure illustrates properties of the reaction time algorithm for exemplary values of prior and likelihood that were chosen similar to values which arise in the grid world. **A**: Kullback-Leibler divergence between the samples in the Markov chain and the prior over policies (dashed line) and the true posterior over policies (solid line), as a function of the factor f in the stopping criterion $H_{thresh} = H_{init} + (H_{init} + 1)f$. **B**: RT histograms for different factors f: 0.1 (left), 0.3 (middle), 0.5 (right). The distributions from C were used as input. The orange histograms are from a setting where only the prior was pronounced, but the likelihood was flat, which corresponds to purely prior-based behavior. The blue histograms were from a setting where only the likelihood was pronounced, but the prior was flat, which can be interpreted as purely reward-based behaviour. The histograms were produced from 1,000 samples for each f and each combination of prior and likelihood. **C**: Distributions used as input for B. The blue line shows an exemplary pronounced distribution over the 81 policies in the grid world (Fig 1A), which is for example found in likelihood after an agent learned the goal location. $81 = 3^4$ is the number of possible combinations of 3 actions that can be used in 4 time steps. Due to the goal position, there are 6 policies that can lead to each goal. Here, they are each assigned a value of ca 0.16, while all other policies have a value close to 0. The red line shows a flat distribution. **D**: RT histograms with the distributions from E as the input, as in B for three different values of f. The orange histograms correspond to RTs when prior and likelihood were in agreement, and the blue histograms correspond to prior and likelihood being in conflict. **E**: Distributions that were used as input for D. The orange and green lines show the distribution of the prior when it was in agreement and conflict, respectively. The numbers were also taken from intermediate values during prior learning in the grid world. The blue line shows the values of the likelihood in this setting.

Goal-based and prior-based behavior

Note that priors over policies play the role of a memory of policies that has been used before in the same context. Here we ask the question how these priors influence reaction times. In what follows, we will show that the modelling framework recreates the known log-normal distribution of reaction times, as well how the factor f and different combinations of prior and likelihood change the resulting distributions.

326   *Figure 2*B shows reaction time distributions for three different exemplary values of the factor
327 f. All distributions exhibit the classical log-normal shape[2], where the distributions for higher fac-
328 tors have a larger mean and a larger variance and tail. An interesting question is how reaction
329 times of an agent which solely relies on its learned prior over policies (orange distributions), differ
330 from reaction times of an agent which, conversely, relies only on the reward-based likelihood (blue
331 distributions). Prior and likelihood shapes are shown in *Figure 2*C. In both cases, the distributions
332 have a similar mean, but the shapes of the distributions differ substantially. The purely prior-based
333 distributions have a lower variance and no tail, while the purely reward-based distributions have
334 a large variance and are clearly right skewed.

335 Conflicts

336 A well-known phenomenon in reaction time experiments is that reaction times are longer for situ-
337 ations where prior information is in conflict with incoming sensory input. We can model this in a
338 straightforward fashion simply by providing the agent with a prior that prefers action sequences
339 which are not supported by the likelihood, see *Figure 2*E. For example, this conflicting situation
340 arises when the goal switched at trial 101, see *Figure 1*B, when the agent has learned a prior which
341 is no longer useful for the changed goal location.

342   We show the resulting reaction time distributions for agreeing and conflicting settings in *Fig-*
343 *ure 2*D. Indeed, agreeing distributions lead to reaction time distributions that have a lower mean
344 and variance in contrast to conflicting distributions. This shows that we would expect larger re-
345 action times in conflict situations as agents resolve the conflict, while we see decreased reaction
346 times when both prior and likelihood are in agreement.

347 **Flanker task**

348 The Eriksen flanker task is a widely used behavioral task to measure inhibition under response con-
349 flicts (*Gratton et al., 2018*). Typically, in this task participants learn a stimulus-response mapping
350 where one or two stimuli correspond to pressing one key, e.g. right, while one or two different
351 stimuli correspond to pressing another key, e.g. left. The stimulus determining which answer is
352 correct is typically shown in the middle of the screen. Conflict is introduced by showing distractor
353 stimuli (flankers) surrounding the relevant stimulus in the middle. The distractors are chosen to
354 be one of the stimuli that also indicate correct and incorrect responses. This induces congruent
355 trials where the distractors indicate the same key as the relevant stimulus, and incongruent trials
356 where the distractors indicate the other key.

357   It is typically found that RTs are increased while accuracies are decreased in incongruent trials
358 compared to congruent trials. The classical explanation of this effect is that, early in visual percep-
359 tion, all stimuli are processed in parallel, while perception focuses on the relevant stimulus in a
360 later phase (*Gratton et al., 1992*). Here, we want to show that this process may be translated into
361 the scope of the proposed prior-based contextual control model, where we do not model the per-
362 ceptual process explicitly, but interpret flankers in terms of context cues and task stimuli in terms
363 of goal-directed information. Concretely, we assume an a priori inference scheme by setting the
364 the hyperparameters of the prior over actions (see Section Free parameters and simulation setups),
365 which maps a response to a specific context. We further assume, that this leads to the distractor
366 stimuli being perceived as context cues which indicate what the correct response would be. This
367 results in a quick loading of the respective prior over this action, which is supposed to facilitate fast
368 action selection. In an incongruent trial, this prior is in conflict with the actual goal-directed stimu-
369 lus encoded in the likelihood. Additionally we assume this inference machine is subject to a small
370 forgetting factor and can be relearned during the course of the experiment. In our simulations, we
371 used a flanker task version with four stimuli.

---

[2]Log-normality was tested using the python scipy normaltest function on the log of the RT in number of samples. All distributions pass the normal test with $p < 0.01$

Conditional accuracy function

One typical finding in flanker tasks is the conditional accuracy function (Fig 3A) (*Stins et al., 2007*). In congruent trials, responses preceded by long as well as short RTs are correct to a high degree. In incongruent trials, responses preceded by short RTs are most likely incorrect with the accuracy dropping below chance. The more the RT increases, the more the accuracy of responses increases. Fig 3B shows the averaged accuracy function of 50 simulated agents which shows the typical dip below chance for low RTs in incongruent trials. In the model, this effect comes from the fact that for lower RTs, choices are more often made in accordance with the prior, while for long RTs, choices are mostly made in accordance with the posterior (see also Fig 2A).

Figure 3. Conditional accuracy function A: Idealized accuracy function in the flanker task, figure taken from (*White et al., 2012*). The solid and dashed lines show the proportion of correct responses for congruent and incongruent trials, respectively, as a function of reaction time. The grey dashed line indicates chance level. **B**: Simulated accuracy function, the line styles are as in A. The lines indicate the mean proportion of correct responses of 50 agents. The shaded area shows the confidence interval of 95%. The proportions were calculated by binning reaction times.

Gratton effect

Another typical finding in the flanker task is the so-called Gratton effect (Fig 4A) (*Gratton et al., 1992*). Here, mean reaction times decrease in the second consecutive trial of the same type (congruent vs incongruent). Usually, the Gratton effect is interpreted as being due to different degrees of recruitment of cognitive control depending on the previous trial type. According to our model, the Gratton effect would rather be a sequential effect, which is due to strengthened or weakened associations between the distractor (context) and the response. A congruent trial would strengthen the association, making prior and likelihood more or less similar in a following congruent or incongruent trial. This in turn de- or increases reaction times. In *Figure 4*B, we show that we can replicate the Gratton effect using this mechanism.

Task switching

In a typical task switching task (*Kiesel et al., 2010*; *Monsell, 2003*), participants are presented with two different response rules, for example participants must indicate whether a number is even or odd, and whether a letter is a vowel or a consonant. In each trial, the current task set is cued, and a stimulus is presented with features from both task sets, such as a letter and a number. The participant has to respond to the stimulus under the current task set. Due to the stimulus consisting of both features, trials can be congruent or incongruent: In congruent trials both features require the same response, and in incongruent trials the two features require different responses.

   In the proposed model, task switching corresponds to switching between two different contexts with different outcomes rules. The agent learns the outcome rules for each context at the beginning of the experiment and later in the experiment loads the task-specific learned rules in

Figure 4. Gratton effect A: Typical Gratton effect findings in the flanker task, figure taken from (*Davelaar and Stevens, 2009*). The x-axis shows the previous trial type, either congruent (CON) or incongruent (INC). The circles indicate the current trial as either incongruent (black) or congruent (white). Reaction times on the y-axis differ between congruent and incongruent trials, and depending on the previous trial type. **B**: Simulated Gratton effect. The axes are as in A, and the dashed line indicates a current incongruent trial, and the solid line a current congruent trial. The shaded areas show a confidence interval of 95%.

response to the task set (context) cue. The agent is set up such that context cues are observed with low uncertainty in addition to context transitions being treated probabilistically (see also Section Free parameters and simulation setups). These two sources of uncertainty are motivated by the idea that human participants may not be always 100% aware of the context cue throughout the experiment and experience uncertainty about the upcoming context. This leads to uncertainty in the context inference and results in the previous context still being loaded to some degree in a switch trial, which decreases as the number of consecutive trials in the same context decreases. The previous context may then introduce conflicts which increase reaction times. Note that here, we use a weak prior learner ($h = 0.001$) to focus less on learning a prior, probably as a human participant would do when switching tasks are expected.

In this section, we show three common findings from the task switching literature (*Kiesel et al., 2010*; *Monsell, 2003*; *Steyvers et al., 2019*; *Jamadar et al., 2015*): (1) decreased reaction times in repetition trials of the same task set, (2) decreased reaction times with longer cue–target intervals, and (3) decreased reaction times with longer response–stimulus intervals.

Repetition trials

In the first trial after a task switch, reaction times typically increase. This finding is typically interpreted as being caused by underlying costs associated with switching the task set. In particular, the previous task set may interfere with the response to the new task set. Additionally, as in the Flanker task, participants are typically slower in incongruent trials than in congruent trials. Lastly, reaction times typically decrease as more trials in the task have been trained. These results are shown in *Figure 5*A. *Figure 5*B shows simulated average reaction times of 50 agents over the course of a 70 trial task switching experiment. As in the experimental findings on the left, shorter periods of training lead to larger reaction times. Both in the experiment and the model, incongruent trials lead to increased reaction times, especially in switch trials. In addition, reaction times decrease as a function of repeated trials.

In the agent, these effects are due to the previous task, i.e. context, lingering because of the remaining uncertainty in the context inference. The longer the same task was active, the lower the remaining uncertainty over tasks, and the less the action-outcome contingencies of the previous task influence the decision. This effect is stronger in conflict trials, as the contingencies of the other task may contradict the contingencies of the current task, which induces uncertainty in the action

selection and therewith increases reaction times.

The converse has been found experimentally for response accuracy: Accuracy drops in switch trials, and is lower in incongruent trials (*Figure 5*C). In *Figure 5*D, we show the simulated average accuracy. The accuracy difference between congruent and incongruent trials is not quite as large in the simulated data compared to the experimental data, but it is present. As described above, these effects are due to the contingencies of the previous task influencing action selection in proportion to the context uncertainty.

Figure 5. RTs and accuracy as a function of repeating trial after switch A: Reaction time in a typical task switching experiment as a function of trial number after the switch, taken from (*Steyvers et al., 2019*). Red lines indicate little previous training (∼10 trials), green lines indicate medium training (∼20 trials), and blue lines long training (∼40 trials). Dashed lines are incongruent trials, and solid lines congruent trials. The shaded areas correspond to a 95% confidence interval. **B**: Simulated average reaction times from 50 agents. Colors as an A. **C**: Response accuracy as a function of trial number after switch from the same experiment as A. Colors as in A. **D**: Simulated average response accuracy from the same simulated experiment as in C. Colors as in A.

Cue–target interval

Another well known effect in task switching is the influence of the cue–target interval (CTI) on reaction times (*Jamadar et al., 2015*). The cue–target interval is the time between the presentation of the current task cue and the onset of the stimulus (target) upon which a response has to be made. Longer CTIs allow participants to better process the cue and load the task set before the onset of the stimulus. *Figure 6*A shows how reaction times increase with shorter CTI, compared to a single task experiment (*Jamadar et al., 2015*).

To model the CTI, we assume that for shorter CTIs, there is higher uncertainty when perceiving the context cue that indicates the current task (see Section Free parameters and simulation setups). *Figure 6*B shows average reaction times in switch trials, repeat trials, and trials in a single task experiment as a function of context cue uncertainty. Using this setup, we were able to qualitatively recreate the typical shape of CTI effects. The higher uncertainty during perception and processing

of the task cue leads to increased reaction times because the previous task's contingencies have higher influence on action selection.

Figure 6. Cue–target interval A: Reaction times in a single task experiment (green), in repeat trials in a task switching experiment (red), and in switch trials (blue), as a function of CTI; adapted from (*Jamadar et al., 2015*). **B**: Mean simulated reaction times from 50 agents, as a function of cue uncertainty, colors as in A. The shaded ares indicate the 95% confidence interval.

Response–stimulus interval

A similar effect has been observed when varying the response–stimulus interval (RSI) (*Monsell, 2003*), which is the time between a response and the next trial. Longer RSIs allow participants to better prepare for a possible switch and as a result decrease reaction times. *Figure 7*A shows reaction times in switch and repeat trials as a function of the RSI (ref).

We model RSI differences as different levels of an agent's assumption about change probability in between trials (see Section Free parameters and simulation setups). The higher the change probability, the easier it is for an agent to infer that the context and task changed, and to load the new task set and respond accordingly. *Figure 7*B shows average reaction times as a function of change probability. The same decrease of reaction times with higher change probability emerges, as with the RSI.

Figure 7. Response–stimulus interval A: reaction times as a function of RSI for switch trials (pink) and repeat trials (purple), taken from (*Monsell, 2003*). **B**: Mean simulated reaction times from 50 agents, as a function of change probability, colors as in A. The shaded areas indicate the 95% confidence interval.

Discussion

We proposed a joint behavioral modeling approach for choices and reaction times in cognitive neuroscience experiments. To model (value-based) choices we use a Bayesian model of goal-directed behavior with two key components: (i) A prior over actions or policies (sequences of actions) which

is learned over time to match the history of past actions (repetition-based prior); and (ii) a hierarchical factorization of latent variables into states and contexts, where contexts determine the state transition and outcome rules of the environment. Additionally, the prior is learned in a context-dependent manner and encodes which policies should be preferred by the agent in the current context. This model is coupled with a reaction time algorithm which is based on a Bayesian independent Markov Chain Monte Carlo (MCMC) sampler which evaluates and selects policies. The MCMC sampler uses prior and likelihood of policies to generate reaction times and to sample policies from the posterior, which are executed.

Using this approach, we showed that the components of this joint model can qualitatively explain several experimental findings in value-based decision tasks as well as typical cognitive control experiments: (1) Decreases in reaction times in a sequential value-based decision task. (2) Classical log-normal shapes of reaction time distributions and prior-based, automatic choices for shorter reaction times. (3) For a flanker task, we replicated the reaction time dependent conditional accuracy function, as well as the sequential Gratton effect. (4) In a typical task switching task, we replicated repetition effects, cue–target interval (CTI) effects, and inter-trial (response–stimulus interval, RSI) effects.

Both the adaptive prior over policies and the hierarchical contextualisation of the generative model are critical for capturing this rather wide range of effects. The context-dependent prior over actions or policies encodes a tendency to repeat specific policies in a specific context. This allowed us to model how behavioral sequences can become more independent of goal representations and thereby automatized. This increases accuracy and decreases reaction times and helps an agent to make faster and more reliable choices. Additionally, this prior encodes cue–response associations which enabled us to model response conflicts in the flanker task, where distractors indicate a different response than the relevant stimulus.

The hierarchical description of the dynamic tasks as context dependent action–outcome contingencies and state transitions furthermore enabled us to model changes in the task structure and dynamics as for example in task switching. As the context itself is a latent variable, the agent forms beliefs over possible contexts and assigns precision to those beliefs. Imprecise beliefs over contexts are critical to modeling effects in a task switching task, as both the effects of the cue–target interval as well as the response–stimulus interval depended on context inference uncertainty.

Although the typical cognitive control tasks are usually not interpreted to rely on value-based or goal-directed decision making, the two key components in the model seem to capture some of the underlying cognitive processes. Hence, the proposed modeling approach leads to an interesting view on cognitive control, which is typically interpreted as top-down control (*Botvinick et al., 2001*; *Miyake et al., 2000*; *Goschke, 2014*; *Gratton et al., 2018*). In contrast, in the model, bottom-up inference plays an important role as well. Here, a context determines not only which task rules currently hold but also which policies should be preferred in the current situation. Consequently, contexts are modeled at a higher level in the hierarchy, relative to actions. This enables the agent to probabilistically infer the high-level state context from its sensory inputs. In this sense, cognitive control, from a modeling perspective, is not only about 'control' but also about 'inference' (*Attias, 2003*; *Botvinick and Toussaint, 2012*). This 'cognitive inference' determines what rules the agent should currently follow, and which a priori information to use (*Marković et al., 2019*). To an outside observer, some resulting behavior may look like 'top-down control' but may be understood as the agent's recognition of the current situation and having learnt how to behave in it, based on previous exposures to the same or similar situations (*Lieder et al., 2018*).

Relation to other joint behavioral models

The classical modeling approach for reaction times is the influential diffusion decision model (DDM) (*Ratcliff, 1978*; *Boucher et al., 2007*; *Ratcliff et al., 2016*; *Forstmann et al., 2016*) which is in cognitive science one of the most established textbook models (*Forstmann and Wagenmakers, 2015*, Chapter 3). It has been successfully applied across many experimental domains, most notably

to perceptual decision making where the task rests on perceptual evidence accumulation. DDMs fall under the umbrella of evidence accumulation models which describe the process of action selection and resulting reaction times as a biased random walk with a drift and white noise. This approach has been extended to multi-choice tasks in so-called race diffusion models, where instead of having one accumulator as in the DDM, each available choice option is associated with a different accumulator (*Fontanesi et al., 2019*; *Miletić et al., 2021*).

The evidence accumulation reaction time modeling approach has been recently combined with reinforcement learning models to provide joint instrumental learning and reaction time models (*Milosavljevic et al., 2010*; *Pedersen et al., 2017*; *Fontanesi et al., 2019*; *Miletić et al., 2021*). Here, usually internal variables from the reinforcement learning agent, particularly expected reward (Q-values) are mapped to variables in the evidence accumulator model, such as the drift rate, e.g. (*Miletić et al., 2021*). Learned values or value differences drive the random walk until a boundary is reached and the respective choice is executed. These models were typically validated in one-step instrumental learning experiments and reproduce the classic log-normal shape of reaction time distributions. However, the resulting modeling approach lacks mechanistic appeal as it is unclear what the white noise component of the DDM represents. As it stands, this noise component is a useful modeling device to explain reaction time distributions but it is difficult to link to an underlying generative mechanism.

We use here a sampling-based approach for generating reaction times as opposed to an evidence accumulator model such as the DDM. Additionally, the sampling not only provides a way to generate reaction times from the choice values of the value-based model, but importantly describes a potential mechanism how the inherent noise of the sampling contributes to the decision process. Policies are sampled from the prior over policies, which provides a heuristic about which parts of the decision tree should be evaluated first, and which can be ignored. For each sampled policy, the goal-directed value is computed. This way, the prior not only encodes context–response associations but also helps to confine the space of what behavior to evaluate in a goal-directed manner. If the prior is close to zero, as is typically the case for many policies, these are effectively a priori, due to the sampling, excluded, and the prior hence helps to save resources and time when selecting actions. Taken together the sampling describes a mechanistic iteration to test, in a manner informed by the prior, hypotheses about future behavior and which action could be the best.

The sampling continues until the agent is sufficiently certain that the sampling has yielded enough information on what outcomes to expect. The level of certainty is regulated by the stopping criterion factor f. This approach automatically integrates the uncertainty about outcomes into action selection, and is related to optimal stopping problems (*Shiryaev, 2007*). For small factors, sampling stops when the sampled estimate crosses the true posterior of a policy for the first time, while larger factors let the sampling converge longer, thereby leading to more accurate values. Furthermore, certainties of the prior, as well as goal-directed values in the likelihood are reflected in different reaction time distribution shapes and means, for the same factor value. These differences in resulting RT distributions for different prior and likelihood combinations can be linked to between participant RT differences measured in behavioural experiments, and therefore enabling identification of generative models employed by the participants (*Daunizeau et al., 2010*).

MCMC was chosen as a sampling algorithm because it is a well-established general method to sample from probability distributions. It has even been argued recently that probabilistic computations may be implemented by neurons in the brain via types of MCMC sampling (*Pecevski et al., 2011*; *Sanborn and Chater, 2016*; *Aitchison and Lengyel, 2016*). In this article, we focused on describing reaction time variability as caused by sampling in the decision and action selection process. However, it is also possible that additional RT variability may be generated by sampling in other domains, such as in the planning process which can be implemented via sampling (*Browne et al., 2012*; *Vien et al., 2013*; *Fountas et al., 2020*), and perceptual processes (*Orbán et al., 2016*; *Echeveste et al., 2020*). For example in the flanker task, past modeling approaches have focused on perceptual uncertainty to explain reaction time effects, e.g. (*White et al., 2012*) while we fo-

cused solely on the decision process itself. It is hence possible that explicitly modeling perceptual effects in the flanker task may further improve the match to observed reaction time distributions and effects.

Acknowledgments

We thank Maarten Jung for his help with a previous version of the MCMC sampling algorithm as part of his masters thesis (https://nbn-resolving.org/urn:nbn:de:bsz:14-qucosa2-740483).

Funding acknowledgements

Funded by the German Research Foundation (DFG, Deutsche Forschungsgemeinschaft), SFB 940/3 - Project number 178833530, and TRR 265 - Project number 402170461, and as part of Germany's Excellence Strategy – EXC 2050/1 – Project ID 390696704 – Cluster of Excellence "Centre for Tactile Internet with Human-in-the-Loop" (CeTI) of Technische Universität Dresden.

Additional files

Supplementary files

- Detailed derivations of the mathematical model.

Code availability

The code has been made publicly available on github:

https://github.com/SSchwoebel/BalancingControl

References

Aitchison L, Lengyel M. The Hamiltonian brain: Efficient probabilistic inference with excitatory-inhibitory neural circuit dynamics. PLoS computational biology. 2016; 12(12):e1005186.

Attias H. Planning by probabilistic inference. In: *AISTATS*; 2003. .

Blakeman S, Mareschal D. A complementary learning systems approach to temporal difference learning. Neural Networks. 2020; 122:218–230.

Botvinick M, Toussaint M. Planning as inference. Trends in cognitive sciences. 2012; 16(10):485–488.

Botvinick MM, Braver TS, Barch DM, Carter CS, Cohen JD. Conflict monitoring and cognitive control. Psychological review. 2001; 108(3):624.

Boucher L, Palmeri TJ, Logan GD, Schall JD. Inhibitory control in mind and brain: an interactive race model of countermanding saccades. Psychological review. 2007; 114(2):376.

Browne CB, Powley E, Whitehouse D, Lucas SM, Cowling PI, Rohlfshagen P, Tavener S, Perez D, Samothrakis S, Colton S. A survey of monte carlo tree search methods. IEEE Transactions on Computational Intelligence and AI in games. 2012; 4(1):1–43.

Daunizeau J, Den Ouden HE, Pessiglione M, Kiebel SJ, Stephan KE, Friston KJ. Observing the observer (I): meta-bayesian models of learning and decision-making. PloS one. 2010; 5(12):e15554.

Davelaar EJ, Stevens J. Sequential dependencies in the Eriksen flanker task: A direct comparison of two competing accounts. Psychonomic bulletin & review. 2009; 16(1):121–126.

Daw ND, Gershman SJ, Seymour B, Dayan P, Dolan RJ. Model-based influences on humans' choices and striatal prediction errors. Neuron. 2011; 69(6):1204–1215.

Doya K, Samejima K, Katagiri Ki, Kawato M. Multiple model-based reinforcement learning. Neural computation. 2002; 14(6):1347–1369.

Echeveste R, Aitchison L, Hennequin G, Lengyel M. Cortical-like dynamics in recurrent circuits optimized for sampling-based probabilistic inference. Nature neuroscience. 2020; 23(9):1138–1149.

Fontanesi L, Gluth S, Spektor MS, Rieskamp J. A reinforcement learning diffusion decision model for value-based decisions. Psychonomic bulletin & review. 2019; 26(4):1099–1121.

612 **Forstmann BU**, Ratcliff R, Wagenmakers EJ. Sequential sampling models in cognitive neuroscience: Advantages,
613 applications, and extensions. Annual review of psychology. 2016; 67:641–666.

614 **Forstmann BU**, Wagenmakers EJ. An introduction to model-based cognitive neuroscience. Springer; 2015.

615 **Fountas Z**, Sajid N, Mediano PA, Friston K. Deep active inference agents using Monte-Carlo methods. arXiv
616 preprint arXiv:200604176. 2020; .

617 **Friston K**. The free-energy principle: a rough guide to the brain? Trends in cognitive sciences. 2009; 13(7):293–
618 301.

619 **Friston K**. The free-energy principle: a unified brain theory? Nature reviews neuroscience. 2010; 11(2):127–138.

620 **Friston K**, FitzGerald T, Rigoli F, Schwartenbeck P, Pezzulo G, et al. Active inference and learning. Neuroscience
621 & Biobehavioral Reviews. 2016; 68:862–879.

622 **Friston K**, Rigoli F, Ognibene D, Mathys C, Fitzgerald T, Pezzulo G. Active inference and epistemic value. Cogni-
623 tive neuroscience. 2015; 6(4):187–214.

624 **Goschke T**. Dysfunctions of decision-making and cognitive control as transdiagnostic mechanisms of mental
625 disorders: advances, gaps, and needs in current research. International journal of methods in psychiatric
626 research. 2014; 23(S1):41–57.

627 **Gratton G**, Coles MG, Donchin E. Optimizing the use of information: strategic control of activation of responses.
628 Journal of Experimental Psychology: General. 1992; 121(4):480.

629 **Gratton G**, Cooper P, Fabiani M, Carter CS, Karayanidis F. Dynamics of cognitive control: Theoretical bases,
630 paradigms, and a view for the future. Psychophysiology. 2018; 55(3):e13016.

631 **Jamadar S**, Thienel R, Karayanidis F. Task switching processes. Brain mapping: An encyclopedic reference.
632 2015; 3:327–335.

633 **Kiesel A**, Steinhauser M, Wendt M, Falkenstein M, Jost K, Philipp AM, Koch I. Control and interference in task
634 switching—A review. Psychological bulletin. 2010; 136(5):849.

635 **Kolling N**, Wittmann M, Rushworth MF. Multiple neural mechanisms of decision making and their competition
636 under changing risk pressure. Neuron. 2014; 81(5):1190–1202.

637 **Kozak MJ**, Cuthbert BN. The NIMH research domain criteria initiative: background, issues, and pragmatics.
638 Psychophysiology. 2016; 53(3):286–297.

639 **Lieder F**, Shenhav A, Musslick S, Griffiths TL. Rational metareasoning and the plasticity of cognitive control.
640 PLoS computational biology. 2018; 14(4):e1006043.

641 **Marković D**, Reiter AM, Kiebel SJ. Predicting change: Approximate inference under explicit representation of
642 temporal structure in changing environments. PLoS computational biology. 2019; 15(1):e1006707.

643 **Miletić S**, Boag RJ, Trutti AC, Stevenson N, Forstmann BU, Heathcote A. A new model of decision processing in
644 instrumental learning tasks. Elife. 2021; 10:e63055.

645 **Milosavljevic M**, Malmaud J, Huth A, Koch C, Rangel A. The drift diffusion model can account for value-based
646 choice response times under high and low time pressure. Judgment and Decision Making. 2010; 5(6):437–
647 449.

648 **Miyake A**, Friedman NP, Emerson MJ, Witzki AH, Howerter A, Wager TD. The unity and diversity of executive
649 functions and their contributions to complex "frontal lobe" tasks: A latent variable analysis. Cognitive psy-
650 chology. 2000; 41(1):49–100.

651 **Monsell S**. Task switching. Trends in cognitive sciences. 2003; 7(3):134–140.

652 **Orbán G**, Berkes P, Fiser J, Lengyel M. Neural variability and sampling-based probabilistic representations in
653 the visual cortex. Neuron. 2016; 92(2):530–543.

654 **Pecevski D**, Buesing L, Maass W. Probabilistic inference in general graphical models through sampling in
655 stochastic networks of spiking neurons. PLoS computational biology. 2011; 7(12):e1002294.

656 **Pedersen ML**, Frank MJ, Biele G. The drift diffusion model as the choice rule in reinforcement learning. Psy-
657 chonomic bulletin & review. 2017; 24(4):1234–1251.

658 **Ratcliff R**. A theory of memory retrieval. Psychological review. 1978; 85(2):59.

659 **Ratcliff R**, Smith PL, Brown SD, McKoon G. Diffusion decision model: Current issues and history. Trends in
660 cognitive sciences. 2016; 20(4):260–281.

661 **Sanborn AN**, Chater N. Bayesian brains without probabilities. Trends in cognitive sciences. 2016; 20(12):883–
662 893.

663 **Schwöbel S**, Kiebel S, Marković D. Active inference, belief propagation, and the bethe approximation. Neural
664 computation. 2018; 30(9):2530–2567.

665 **Schwöbel S**, Marković D, Smolka MN, Kiebel SJ. Balancing control: a Bayesian interpretation of habitual and
666 goal-directed behavior. Journal of Mathematical Psychology. 2021; 100:102472.

667 **Shahar N**, Hauser TU, Moutoussis M, Moran R, Keramati M, Consortium N, Dolan RJ. Improving the reliabil-
668 ity of model-based decision-making estimates in the two-stage decision task with reaction-times and drift-
669 diffusion modeling. PLoS computational biology. 2019; 15(2):e1006803.

670 **Shiryaev AN**. Optimal stopping rules, vol. 8. Springer Science & Business Media; 2007.

671 **Steyvers M**, Hawkins GE, Karayanidis F, Brown SD. A large-scale analysis of task switching practice effects
672 across the lifespan. Proceedings of the National Academy of Sciences. 2019; 116(36):17735–17740.

673 **Stins JF**, Polderman JT, Boomsma DI, de Geus EJ. Conditional accuracy in response interference tasks: Evidence
674 from the Eriksen flanker task and the spatial conflict task. Advances in cognitive psychology. 2007; 3(3):409.

675 **Vien NA**, Ertel W, Dang VH, Chung T. Monte-Carlo tree search for Bayesian reinforcement learning. Applied
676 intelligence. 2013; 39(2):345–353.

677 **White CN**, Brown S, Ratcliff R. A test of Bayesian observer models of processing in the Eriksen flanker task.
678 Journal of Experimental Psychology: Human Perception and Performance. 2012; 38(2):489.