Multi-scale Adaptive Differential Abundance Analysis in Microbial Compositional Data

Shulei Wang*

University of Illinois at Urbana-Champaign

(November 2, 2021)

Abstract

Differential abundance analysis is an essential and commonly used tool to characterize the difference between microbial communities. However, identifying differentially abundant microbes remains a challenging problem because the observed microbiome data is inherently compositional, excessive sparse, and distorted by experimental bias. Besides these major challenges, the results of differential abundance analysis also depend largely on the choice of analysis unit, adding another practical complexity to this already complicated problem. In this work, we introduce a new differential abundance test called the MsRDB test, which embeds the sequences into a metric space and integrates a multi-scale adaptive strategy for utilizing spatial structure to identify differentially abundant microbes. Compared with existing methods, the MsRDB test can detect differentially abundant microbes at the finest resolution offered by data and provide adequate detection power while being robust to zero counts, compositional effect, and experimental bias in the microbial compositional data set. Applications to both simulated and real microbial compositional data sets demonstrate the usefulness of the MsRDB test.

---

*Address for Correspondence: Department of Statistics, University of Illinois at Urbana-Champaign, 725 South Wright Street, Champaign, IL 61820 (Email: shuleiw@illinois.edu).

1 Introduction

Differential abundance analysis is a commonly used tool to decipher the difference between microbial communities and identify dysbiotic microbes. The primary goal of differential abundance analysis is to detect a set of microbes associated with experimental conditions based on observed count data generated from high-throughput sequencing technologies. Although popular, differential abundance analysis in microbiome data remains a challenging statistical problem as the observed count data is inherently compositional (Li, 2015; Gloor et al., 2017; Vandeputte et al., 2017; Morton et al., 2019), excessive sparse (Brill et al., 2019), and distorted by experimental bias (McLaren et al., 2019) (Figure 1). To address these challenges, a number of studies have proposed differential abundance analysis procedures for microbiome data (Paulson et al., 2013; Fernandes et al., 2013; Mandal et al., 2015; Chen et al., 2018; Morton et al., 2019; Brill et al., 2019; Lin and Peddada, 2020a; Martin et al., 2020; Wang, 2021). See a comprehensive review of differential abundance analysis in Weiss et al. (2017) or Lin and Peddada (2020b).

Figure 1: **The limitations inherent in the observed microbial compositional data set.** This figure shows that the sampling process and experimental bias in sequencing workflow create a systemic distinction between absolute abundance in the ecosystem and our observed count data. The observed composition after normalization can also be significantly different from the relative abundance in the original ecosystem owing to the experimental bias. The measurement efficiency in this example is $(2, 3, 1, 1)$.

Before applying these existing methods, one must choose an appropriate analysis unit for differential abundance analysis. The reads in 16S rRNA sequencing data are clustered into operational taxonomic units (OTUs) (Hamady and Knight, 2009) or denoised as amplicon sequence variants (ASVs) (Callahan et al., 2016; Amir et al., 2017). Using OTUs or ASVs as the analysis unit, we can detect the differentially abundant microbes at the finest resolution offered by 16S rRNA sequencing data (Figure 2A). However, such a strategy sometimes can suffer a loss of detection power as the sparse counts in each OTU or ASV are not informative enough for an effective comparison. To increase power, one commonly used strategy is to aggregate similar OTUs or ASVs as taxa, such as genera, according to their assigned/mapped taxonomy (Figure 2B). Treating taxa as analysis units can provide more power to detect

differentially abundant microbes but at a coarser resolution. Choosing a taxonomy rank in the taxon-wise analysis also needs facing a tradeoff between resolution and sequence utilization. On the one hand, a lower taxonomy rank can provide finer resolution but requires throwing out many unassigned sequences due to the current coarse taxonomic classification. On the other hand, a higher taxonomy rank can keep and utilize more sequences but loses resolution to capture the heterogeneous signal. It is natural to wonder if there is a way to detect differentially abundant microbes at OTU or ASV resolution while maintaining enough power and using all available sequences. Motivated by this need, we introduce an alternative way to conduct differential abundance analysis in this paper.

Here, we propose the MsRDB test (Multiscale Adaptive Robust Differential Abundance Test), a multi-scale method for differential abundance analysis in microbial compositional data. Instead of independent units, the MsRDB test embeds ASVs' sequences or OTUs' representative sequences into a metric space where their pairwise distance can be utilized. The metric space embedding allows us to exploit the fact that similar OTUs/ASVs often perform similarly and utilize their spatial structure to gain more detection power. To identify multi-scale signals, the MsRDB test adopts a propagation and separation (PS) approach (Polzehl and Spokoiny, 2000, 2006) to aggregate information from the neighborhood iteratively and adaptively. Notably, the MsRDB test only integrates OTUs/ASVs with similar levels of differential abundance so that we can capture the heterogeneous signal easily and avoid false discovery inflation caused by aggregation. As a generalization of robust differential abundance (RDB) test (Wang, 2021), the MsRDB test inherits many good properties from the RDB test, including robustness to zero counts, compositional effect, and experimental bias. We evaluate the performance of the MsRDB test using both simulated and 16S rRNA data set from published studies. Through these numerical examples, we compare the MsRDB test with ASV-wise and taxon-wise analysis. We demonstrate that the MsRDB test can help reveal the multi-scale differentially abundant microbes at ASV resolution, providing more insights into the subtle difference between microbial communities.

2 Results

2.1 Overview of MsRDB Test

We give a brief overview of the new MsRDB test. For the sake of concreteness and illustration, we focus primarily on the ASVs in this work, while all the techniques introduced here are readily applicable to OTUs. Before analysis, the MsRDB test first embeds all ASVs' sequences into a metric space so that we can measure the similarities between any pair of ASVs' sequences. After embedding, the MsRDB test consists of two main steps (Figure 2C and 2D). At the first step (Figure 2C), the MsRDB test assigns the weights for each ASV's neighborhood and then constructs a weighted count table by these weights. The weights in the MsRDB test are assigned in an iterative and multi-scale fashion. Specifically, we adopt a propagation and separation (PS) approach to update weights adaptively in a series of nested neighborhoods. Through the PS approach, the weights in the MsRDB test allow

each ASV to effectively borrow strength from other similar ASVs, thus increasing the power in detecting more subtle levels of differential abundance. Importantly, the weights in the MsRDB test reflect both similarities of ASVs' sequences and their differential abundance levels so that only ASVs with similar levels of differential abundance are aggregated. Based on the assigned weights, we aggregate the relative abundance of ASVs to obtain a weighted abundance table, where each row still corresponds to each ASV. In the second step (Figure 2D), we introduce a weighted version of robust differential abundance (RDB) test and apply it to the weighted abundance table. The weighted version RDB test evaluates the standard two-sample t-test statistics on the weighted relative abundance of each ASV. Like the vanilla RDB test, we integrate these test statistics to infer the testing direction and then conduct directional two-sample tests to identify differential ASVs. After removing the identified ASVs, we renormalize the weighted abundance table and repeat the above procedures. The detailed description of these two steps is explicated in the Methods section.

The analysis unit in the conventional differential abundance analysis is either individual ASV or taxon after aggregation. The ASV-wise analysis can help detect the highest resolution of differential abundance but could suffer power loss owing to the sparse count in each ASV. The taxon-wise analysis can boost detection power as the count data in different ASVs are aggregated. However, the taxon-wise analysis has lost the resolution in data and usually throws out some unassigned ASVs. Compared with these two commonly used strategies, the MsRDB test has the best of both worlds. MsRDB test not only can detect the differential abundance in ASV level but also maintain adequate power as it allows borrowing strength from similar ASVs. With the MsRDB test, we can take full advantage of all sequences in data. In addition, the MsRDB test inherits many good properties from vanilla RDB test: 1) there is no need for an extra step to handle zero counts in data; 2) it is designed to take compositional nature of data into account; 3) it is robust to experimental bias in the microbial compositional data.

2.2   Borrowing Strength from Neighborhood can Increase Power

To evaluate the performance of MsRDB, we simulate the ASV data from a data set collected in Yatsunenko et al. (2012) (Supplement Material). By the simulated data set, we compare the performance of the RDB test, k-nearest neighbors weighted RDB test, and the MsRDB test in terms of false discovery rate (FDR) and power. Here, as we aim to investigate the effect of ASV aggregation, this simulation study only includes different versions of the RDB tests for a fair comparison.

The power is significantly improved if we incorporate information from the ASVs in the neighborhood. In particular, both the k-nearest neighbors weighted RDB test and the MsRDB test have larger power than the RDB test in all simulation experiments (Figures 3, S1, and S2). When the number of neighbors increases, the power of both tests also increases since more information is borrowed from neighbors. However, simple incorporation from similar ASVs in the k-nearest neighbors weighted RDB test can lead to the highly inflated false discovery. Specifically, the FDR level can be as high as more than 50% sometimes. The inflation of false discovery is mainly because the non-differentially abundant ASVs can

Figure 2: **Illustration demonstrating OTU/ASV-wise analysis, taxon-wise analysis, and MsRDB test.** (A) OTU/ASV-wise analysis treats OTUs or ASVs as independent units in differential abundance analysis. (B) According to the mapped or assigned taxon, OTUs or ASVs are first grouped as taxa. The taxa are regarded as independent units in taxon-wise analysis. (C) The first step in the MsRDB test constructs a weighted count table by exploiting the spatial structure of ASVs. Instead of independent units, the MsRDB test embeds the ASVs into a metric space and utilizes their spatial structure to gain more power. The PS approach used in the MsRDB test allows borrowing strength from the neighborhood in a multi-scale and adaptive way. (D) The second step in the MsRDB test identifies differential ASVs by iterative directional two-sample tests and renormalization.

be falsely identified when they aggregate information from some differentially abundant neighbors. Unlike the RDB test and k-nearest neighbors weighted RDB test, the MsRDB test can help improve power while controlling FDR at the desired level since the PS approach only allows sharing information between ASVs with similar levels of differential abundance. Note that the FDR in the MsRDB test may be slightly inflated when the number of neighbors becomes larger.

Figure 3: **FDR and power comparisons in simulated data set.** Left and right figures show the FDR and power of various versions of RDB methods when the sample sizes are 50, 100, 200, and 400. The dashed line in the left figure is the target level of FDR at 10%. The results in this figure show that aggregation of information from the neighborhood can increase the power. However, simple aggregation in k-nearest neighbors could result in inflation of false discoveries. In contrast, the MsRDB test increases the power and avoids FDR inflation since only ASVs with similar levels of differential abundance are aggregated.

These simulation experiments also help us investigate the influence of sample size, effect size, and the number of differentially abundant ASVs on these three different versions of the RDB tests. When the sample size increases, all these tests become more powerful and achieve similar FDR (Figure 3). Unlike the sample size, the number of differentially abundant ASVs has a relatively small influence on the performance of these tests (Figure S2). Similar to sample size, large effect size can lead to more powerful tests, but the small effect size can slightly inflate the FDR in the MsRDB test (Figure S1). The intuition behind this phenomenon is that it is more difficult for the PS approach to distinguish ASVs with different levels of differential abundance when the effect size is small. Hence, the non-differentially abundant ASVs are more likely to aggregate information from differentially abundant ASVs.

2.3 MsRDB Detects Differentially Abundant Microbes Associated with Immigration

To elucidate the differences between ASV-wise analysis, taxon-wise analysis at different ranks, and the MsRDB test, we apply these microbiome data analysis strategies to a gut microbiota data set from an immigration effect study (Vangay et al., 2018). In particular,

we focus on the pairwise comparisons between Hmong female individuals who were living in Thailand (HmongThai, $n = 96$) or were born in the US but whose parents were born in Southeast Asia (Hmong2nd, $n = 54$), and European American female individuals (Control, $n = 36$). Through pairwise comparisons, we can identify the microbes associated with immigration. To conduct comparisons, we apply four different analysis strategies: ASV-wise analysis, taxon-wise analysis at the genus level, taxon-wise analysis at the class level, and the MsRDB test. In ASV-wise and taxon-wise analysis, we consider three differential abundance tests: ANCOM.BC, RDB test and ALDEx2.

Overall, the differential abundance analysis results suggest that Hmong2nd is very similar to Control while there are some differences between HmongThai and the other two groups. Regardless of the choices for differential abundance test, there are fewer discoveries if we regard each ASV as an analysis unit (Figure 4, S5, and S6). The low detection power in ASV-wise analysis is mainly because low counts at each ASV are not informative enough for an effective comparison. The power is significantly improved after aggregation based on taxonomy, but we still need to choose an appropriate rank for analysis. A lower taxonomy rank brings finer resolution but also results in throwing out a fair amount of sequence. Specifically, at least 5% of valuable sequences in more than half samples are assigned to the NA genus and thus removed from the analysis if we choose genus as analysis unit (Figure 4D). Compared with ASV-wise analysis, the genus-wise analysis leads to more discoveries. On the other hand, if a higher taxonomy rank is used, we can keep more sequences but could lose resolution. More concretely, only a tiny proportion ($< 1\%$ in most samples) of sequences are removed from the class-wise analysis (Figure 4D). However, the class-wise analysis only reports differentially abundant microbes at the class level and loses the resolution. In particular, we can observe that the analysis at different ranks contradicts each other sometimes in Figure 4. For example, genus-wise analysis suggests that some genera in class *Coriobacteriia*, *Bacilli*, *Desulfovibrionia*, *Negativicutes*, and *Gammaproteobacteria* are differentially abundant in HmongThai and Control comparison, but class-wise analysis makes an opposite conclusion.

The MsRDB test combines the advantages of both ASV-wise analysis and taxon-wise analysis. Like ASV-analysis, the MsRDB test utilizes all sequences and detects the differentially abundant microbes at ASV resolution. Since strength is borrowed from the neighborhood, the MsRDB test is more powerful and has more discoveries than ASV-wise or taxon-wise analysis. Importantly, most discoveries by all different methods are recovered by the MsRDB test, whether they are detected at ASV, genus, or class level (Figure 4, S5, and S6). This phenomenon is mainly because the weights in the MsRDB test are constructed iteratively so that the MsRDB test can capture multi-scale signals.

The aggregation strategy in the taxon-wise analysis can help increase power but could also miss some heterogeneous signals. To illustrate this, we focus on the comparison between group HmongThai and Control. The class-wise analysis suggests that *Bacilli* is a non-differentially abundant class (Figure 5A). However, *Bacilli* is known to be associated with the western diet and is expected to be more abundant in the Control group (Clarke et al., 2012). Through the genus-wise analysis, we identify five differentially abundant genera in *Bacilli* (Figure 5C). Figure 5A shows the box plot of the abundance in these five significant

Figure 4: **Comparisons between ASV-wise analysis, taxon-wise analysis, and MsRDB test on the microbiota data set in an immigration study.** (A-C) shows the overlap of results obtained by different analysis strategies in pairwise comparisons of three groups of people. The three rows are the comparisons of HmongThai vs. Control, Hmong2nd vs. HmongThai, and Hmong2nd vs. Control. The first column is the overlap of identified ASV by ASV-wise analysis and the MsRDB test. The second column is the overlap of identified genera by ASV-wise analysis, genus-wise analysis, and the MsRDB test. The third column is the overlap of identified classes by ASV-wise analysis, genus-wise analysis, class-wise analysis, and the MsRDB test. (D) The histograms of proportions of NA genus (left) and class (right) in each sample. Most samples need to remove at least 5% sequences from the genus-wise analysis.

genera and the rest of the genera in *Bacilli*. These dominant non-differentially abundant genera make it difficult to identify *Bacilli* in class-wise analysis. This example indicates we might miss some subtle heterogeneous signals in taxon-wise analysis.

Unlike taxon-wise analysis, the MsRDB test only aggregates ASVs with similar levels of differential abundance and thus can easily capture these heterogeneous signals. This special aggregation strategy partially explains why the MsRDB test identifies more genera or classes than taxon-wise analysis and potentially provides more biological insights into the microbial communities. In MsRDB analysis results, several ASVs assigned to genus *Phascolarctobacterium* are more abundant in group Control than HmongThai (Figure 5B, present in 26% of HmongThai < present in 47% of Control), while it is non-differentially abundant in genus-wise analysis. This discovery is consistent with previous results that *Phascolarctobacterium* is associated with a high-fat diet (Ariefdjohan et al., 2017). MsRDB analysis results suggest a decrease in the abundance of several ASVs assigned to *Ruminococcus torques* in HmongThai, compared with Control (Figure S4A, present in 21% of HmongThai < present in 78% of Control). A plant-based diet in Southeast Asia could explain the decrease in the abundance of *Ruminococcus torques* (Meslier et al., 2020). It is also interesting to observe that the rest of the ASVs assigned to *Ruminococcus torques* are not significantly differentially abundant, so genus-wise analysis finds it difficult to detect.

The ASVs removed from the taxon-wise analysis could also help to provide insight into the microbial communities. The MsRDB test identifies a few significant ASVs removed from genus-wise analysis in HmongThai and Control comparison. Figure S4B compares these significant ASVs' abundance if we aggregate them together. There is a significant increase in Control compared with HmongThai. Although these significant ASVs are assigned to the NA genus, their taxonomy classification at family or order rank can still provide a rich source of information (Figure 5D). Specifically, these genus-unassigned ASVs mainly come from the family *Ruminococcaceae*, *Oscillospiraceae*, and *Lachnospiraceae*, or order *Oscillospirales* and *Lachnospirales*.

2.4   MsRDB Reveals Microbial Biogeography of Wine Grapes

To further demonstrate the performance of the MsRDB test, we apply it to a grape microbiota data set (Bokulich et al., 2014). We consider studying the association between growing region and microbial community of grape Chardonnay. The grape must samples we consider here are divided into three groups based on their growing regions: 19 samples from Sonoma, 46 samples from Napa, and 11 samples from Central Coast. Unlike the previous data set, a considerable amount of sequences in this data set are assigned to the NA genus and family (Figure 6A). We need to remove these sequences from analysis if we adopt taxon-wise analysis to detect differentially abundant microbes at a resolution of genus or family. We apply the MsRDB test and ASV-wise analysis to explore differentially abundant microbes at an ASV resolution. Again, the MsRDB test is more powerful and can help detect more significant ASVs (Figure S7).

We cluster the differentially abundant ASVs into small groups since only partial information on the microbial taxonomy is known in this data set. Figures 6B-D show the clustering

Figure 5: **Taxa detected by different differential abundance analysis strategies on the real microbiota data set.** The reference set in all box plots is the collection of all non-differentially abundant ASVs revealed by the MsRDB test. (A) The box plots show the relative abundance with respect to the reference set in class *Bacilli* (left), in five significant genera within *Bacilli* (right), and in the rest of genera within *Bacilli* (middle). (B) The box plot shows the relative abundance with respect to the reference set in significant ASVs within genus *Phascolarctobacterium*. (C) The relative abundance with respect to the reference set in five significant genera within *Bacilli* is shown. The five significant genera are identified by genus-wise analysis. (D) The family (left) and order (right) of significant ASVs assigned to the NA genus. These ASVs are identified by the MsRDB test and removed from the genus-wise analysis.

results in pairwise comparisons between Sonoma, Napa, and Central Coast and indicate that the differentially abundant microbes naturally form around 10 small groups in each comparison. After comparing each small group with the assigned taxonomy, the small groups can correspond to different taxonomy ranks (Table S1). For example, in comparing between Central Coast and Sonoma, ASVs in cluster 1 come from the same genus *Lactobacillus* while ASVs in cluster 11 come from the same order *Burkholderiales*. This example again demon-

strates that the MsRDB test can indeed capture multi-scale signals. Although some ASVs lack assigned genus and family, they may still provide insight into microbial communities. For instance, ASVs cluster 8 in the Sonoma and Napa comparison are assigned to NA genus and family, but the information in order *Enterobacterales* is still beneficial. The analysis in (Bokulich et al., 2014) concludes that class *Actinobacteria* is more abundant in Central Coast than Napa. Our results confirm this finding and further suggest that the differentially abundant microbes come from family *Micrococcaceae* (cluster 8), *Geodermatophilaceae* (cluster 9), and *Kineosporiaceae* (cluster 10) (Figure 6E).

3 Discussion

Differential abundance analysis is a challenging and complicated statistical problem because the observed data set in microbiome studies only reflects the relative abundance of taxa, has excessive zeros, and is perturbed in experiments. Besides these major challenges, this work focuses on another important practical issue in differential abundance analysis: the choice of analysis unit. Through several numerical examples, we show that the analysis unit has a significant impact on the results of differential abundance analysis. On the one hand, the ASV-wise analysis can help detect differentially abundant microbes at the finest resolution but usually has small detection power. On the other hand, taxon-wise analysis enforce a tradeoff between resolution and sequence utility, although it can help increase detection power.

MsRDB test has both advantages of ASV-wise and taxon-wise analysis: it detects the differentially abundant microbes at a resolution of ASV, has larger detection power, and keeps all sequences in the analysis. Due to these good properties, the MsRDB test not only recovers most discoveries detected by conventional ASV-wise or taxon-wise analysis but also identifies some extra subtle differences between microbial communities. These new findings revealed by the MsRDB test could potentially provide more biological insights into the microbial communities and help identify new diagnostic or prognostic biomarkers in disease. As a generalization of the RDB test, findings reported by the MsRDB test is reliable and trustworthy as it is robust to compositional constraint, prevalent zero counts and experimental bias in the microbial data set. We hope this new differential abundance analysis method will help biological researchers in making more scientific discoveries.

This work not only develops a new differential abundance test but also suggests a change in how we utilize the ASVs' sequence information in the differential abundance analysis. Conventional differential abundance analysis treats ASVs (or taxa) as independent units and thus does not take the most advantage of sequences' information. In contrast, we show that embedding into a metric space makes it possible to exploit the spatial structure among ASVs' sequences and significantly improve the power of differential abundance analysis. The MsRDB test presented in this work is mainly designed based on the RDB test because of its robustness. However, the perspective of embedding and spatial analysis is readily generalizable to other popular differential abundance analysis methods. For instance, after embedding into a metric space, the linear models used in ANCOM.BC can also work with

Figure 6: **Analysis of the grape microbiota data set by MsRDB test.** (A) The histograms of proportions of the NA genus (left), class (middle), and order (right) in the grape microbiota data. A considerable amount of sequences are removed from the genus-wise or family-wise analysis. (B-D) The clustering results of significant ASVs in the pairwise comparisons. 13 clusters are obtained in Sonoma vs. Napa comparison, 11 clusters are obtained in Central Coast vs. Napa comparison, and 11 clusters are obtained in Central Coast vs. Sonoma comparison. (E) The box plots show the relative abundance with respect to the reference set in clusters 8, 9, and 10 in Central Coast vs. Napa comparison.

the PS approach, as illustrated in Li et al. (2011). Therefore, we believe this new perspective will lead to more exciting methods for analyzing microbial compositional data.

The current MsRDB test mainly considers a standard two-sample t-test as test statistics and Gaussian distribution as its null distribution. As we illustrate in our numerical examples,

such a strategy works very well when the sample size is large. However, when the sample size becomes small, the false discovery might not be controlled well. This problem might be alleviated by a rank-based test, such as the Wilcoxon test, as the null distribution of the rank-based test does not rely on the underlying distribution. Because of the two-sample t-test, the current MsRDB test is designed for testing the mean shift between groups. It would also be interesting to explore if the framework of the MsRDB test can be used to test other characteristics of microbial distribution, such as dispersion. Another potential extension of the MsRDB test is to study the association between microbial community and a continuous or multiple-level outcome, e.g., BMI. This extension is possible if we consider replacing the t-test with a correlation test, as Wang (2021) illustrates.

4 Methods

4.1 Model for Microbiome Data

In this work, we consider the ASV counts data from $m_1 + m_2$ subjects, where m_1 subjects are in the first group, and m_2 are in the second group. Let $\mathcal{S}$ be the collection of observed distinct ASVs, and $s \in \mathcal{S}$ represents an ASV. For the jth subject in the kth group, we observe a vector of ASVs' counts $\mathbf{N}_{k,j} = \{\mathbf{N}_{k,j}(s) : s \in \mathcal{S}\}$, where $\mathbf{N}_{k,j}(s)$ is the number of ASV s observed in the subject, and a vector of covariates $\mathbf{X}_{k,j}$, such as age and gender. Since the total counts of ASVs observed from each subject do not reflect the absolute abundance, we usually normalize the count data from each subject as a vector of observed relative abundance $\hat{\mathbf{P}}_{k,j} = \{\hat{\mathbf{P}}_{k,j}(s) : s \in \mathcal{S}\}$, where $\hat{\mathbf{P}}_{k,j}(s) = \mathbf{N}_{k,j}(s)/\sum_{s \in \mathcal{S}} \mathbf{N}_{k,j}(s)$. In practice, such a vector of observed relative abundance is also called a compositional data vector. In differential abundance analysis, our goal is to compare the observed relative abundance from these two groups of subjects.

We assume the ASV counts data are drawn from the following model. For the jth subject in the kth group, there exists a latent vector of absolute abundance $\mathbf{A}_{k,j} = \{\mathbf{A}_{k,j}(s) : s \in \mathcal{S}\}$, which we do not observe in practice. We assume the absolute abundance vectors and covariates vectors are drawn from two populations

$$(\mathbf{A}_{k,1}, \mathbf{X}_{k,1}), \ldots, (\mathbf{A}_{k,m_k}, \mathbf{X}_{k,m_k}) \sim \pi_k(\mathbf{A}, \mathbf{X}), \qquad k = 1, 2,$$

where $\mathbf{X} \in \mathbb{R}^d$. $d = 0$ means that there are no observed covariates in the data set. These absolute abundance vectors $\mathbf{A}_{k,j}$ represent the abundance of ASVs in each subject. Our observed ASV counts data $\mathbf{N}_{k,j}$ are related to absolute abundance $\mathbf{A}_{k,j}$ through a relative abundance model with experimental bias. Specifically, we adopt the multiplicative factors model (McLaren et al., 2019) for experimental bias in relative abundance

$$\mathbf{P}_{k,j}(s) = \frac{\beta(s)\mathbf{A}_{k,j}(s)}{\sum_{s \in \mathcal{S}} \beta(s)\mathbf{A}_{k,j}(s)},$$

where $\beta(s)$ is the uniform measurement efficiency constant for the ASV s. Here, we want to emphasize that the relative abundance $\mathbf{P}_{k,j}(s)$ already takes the experimental bias into

account. Given the relative abundance, we assume the ASV counts $\mathbf{N}_{k,j}$ is drawn from a multinomial model

$$\mathbf{N}_{k,j}|\mathbf{P}_{k,j}, N_{k,j} \sim multinomial(N_{k,j}, \mathbf{P}_{k,j}),$$

where $N_{k,j}$ is the total reads we observe for each subject. This model suggests that the observed relative abundance $\hat{\mathbf{P}}_{k,j}$ is just an empirical version of relative abundance $\mathbf{P}_{k,j}$.

4.2 Reference-Based Hypothesis

In differential abundance analysis, we need to define a rigorous statistical hypothesis to conduct testing. Although it seems that the definition of a hypothesis is straightforward, compositional constraints and experimental bias make it challenging to define a statistically identifiable and interpretable hypothesis. See more discussions in Wang (2021). In this work, we formulate the differential abundance analysis as a reference-based hypothesis testing problem.

Specifically, we first need to define a reference set in order to define a reference-based hypothesis (Brill et al., 2019). A subset of ASVs, $\mathcal{S}_0 \subset \mathcal{S}$, is called a reference set if there exists a constant b such that

$$\mathbf{Q}_1(s) = b\mathbf{Q}_2(s), \qquad s \in \mathcal{S}_0,$$

where $\mathbf{Q}_k(s) = \mathbb{E}(\mathbf{P}_{k,1}(s))$ is the expected relative abundance of ASV s in the kth population. This definition suggests that the expected relative abundance changes in the same amplitude and the relationship between ASVs within $\mathcal{S}_0$ does not change across the two populations. If the absolute abundance does not change in a subset of ASVs, this subset can be seen as a reference set. The definition of reference set we use here is not sensitive to the experimental bias or the choice of ASVs included in the analysis.

In the reference-based hypothesis, we consider the reference set as a benchmark and compare all ASVs with this benchmark. In particular, we consider the following reference-based hypothesis at each ASV s

$$H_{s,0} : \frac{\mathbf{Q}_1(s)}{\sum_{s \in \mathcal{S}_0} \mathbf{Q}_1(s)} = \frac{\mathbf{Q}_2(s)}{\sum_{s \in \mathcal{S}_0} \mathbf{Q}_2(s)} \qquad vs. \qquad H_{s,1} : \frac{\mathbf{Q}_1(s)}{\sum_{s \in \mathcal{S}_0} \mathbf{Q}_1(s)} \neq \frac{\mathbf{Q}_2(s)}{\sum_{s \in \mathcal{S}_0} \mathbf{Q}_2(s)}. \qquad (1)$$

Equivalently, the goal is to identify all ASVs such that $\mathbf{Q}_1(s) \neq b\mathbf{Q}_2(s)$. Based on this definition, a change in the differential components can be interpreted as a change with respect to the reference set $\mathcal{S}_0$ or the collection of all non-differentiate ASVs. Similar to the reference set, the definition of hypothesis here is invariant to experimental bias and choices of ASVs included in the analysis. However, such a hypothesis' definition depends on the choice of the reference set. In practice, the reference set is usually unknown, leading to inconsistent null hypothesis conclusions when different reference sets are used. In order to make the hypothesis identifiable, we always assume the $\mathcal{S}_0$'s size is larger than half of $\mathcal{S}$'s size, i.e., $|\mathcal{S}_0| > |\mathcal{S}|/2$, where $|\cdot|$ is the number of elements in the set (Wang, 2021).

A toy example is shown in Figure 1 to illustrate the idea of the reference set and reference-based hypothesis. In Figure 1, we have two ecosystems of red, orange, green,

and blue components, A and B, and their absolute abundances are shown on the left-hand side. Due to the sampling process and experimental bias, the observed counts and relative abundance, shown on the right-hand side, cannot honestly reflect the relative relationship between different components' absolute abundance. However, despite the experimental bias, the reference-based hypothesis framework suggests that the orange, green, and blue components can be seen as a reference set since their relative abundances change in the same amplitude (37.5%/30%=18.75%/15%=6.25%/5%=1.25). Based on this reference set, only the red component belongs to the alternative hypothesis. These conclusions are consistent with the fact that there is only a change in the red component's absolute abundance. This toy example shows that the reference-based hypothesis is a statistically identifiable and interpretable hypothesis for differential abundance analysis.

4.3   Embedding of ASVs' Sequences

Different ASVs are not equally distinct, as some of them are more similar than others. Motivated by this observation, we can consider a general way to incorporate the similarity between ASVs. Specifically, we opt to embed different ASVs into a metric space and define a distance between ASVs' raw sequences $d(\cdot, \cdot)$. To reflect different aspects of ASVs, we provide several different possible ways to calculate a distance between two distinct ASV sequences:

- *Pairwise alignment distance.* One of the most commonly used ways to compare two sequences is pairwise sequence alignment, e.g., the Needleman-Wunsch algorithm. After alignment, the scoring schemes in the alignment algorithm can be used to calculate the distance between sequences.

- *kmer-based distance.* Another way to compare two sequences is $k$mer-based distance. Given a positive integer k, each sequence is transformed to a vector of $k$mer counts. Then, a distance between two $k$mer count vectors is used to measure the dissimilarity of sequences. For example, Euclidian squared and Mahalanobis distances are two of the most commonly used distances (Gentleman and Mullin, 1989).

- *Phylogenetic distance.* If the evolutionary history of sequences is believed to relate to the outcome of interest, we can also use the existing phylogenetic tree to measure the dissimilarity of sequences. Specifically, the sequences are placed on a reference phylogenetic tree by phylogenetic placement algorithms, such as SEPP (Janssen et al., 2018). The distance between the sequences can then be defined as the length of the unique path connecting them on the tree.

This list of distance options is by no means complete, as some other information can also be incorporated into the distance. For example, the sequence can also be used to predict gene family or pathway (Douglas et al., 2020), and they can define the distance between sequences. In addition, a weighted sum of several distances could also be used when it is needed. In most of the analyses in this work, the distances between ASVs are calculated by function `DistanceMatrix` in `DECIPHER` R package (Wright, 2016).

4.4 Weighted RDB test

To test the ASV-wise reference-based hypotheses in (1), it is natural to design an ASV-wise differential abundance test based on the data at each ASV. For example, we can apply the RDB test directly to the ASV table. However, such an ASV-wise method neglects the similarity relationship between different ASVs. We introduce a new ASV-weighted differential abundance test to fully take advantage of such information by extending the RDB test.

Vanilla RDB test. Before introducing the new test, we first briefly review the idea of the RDB test proposed in Wang (2021) when applied directly to the ASV table. The RDB test is an iterative way to detect differentially abundant components in compositional data. In the RDB test, we usually choose $\mathcal{S}_{(0)}^* = \emptyset$ and $\mathcal{S}_{(0)} = \mathcal{S}$ to initialize the procedure. Let $\mathcal{S}_{(t)}^*$ be the set of identified differential ASVs, and $\mathcal{S}_{(t)}$ be the rest of non-detected ASVs in the tth iteration. In each iteration, the relative abundance is renormalized with respect to all non-detected taxa $\mathcal{S}_{(t)}$. Specifically, we write the expected renormalized relative abundance in two populations as

$$\mathbf{Q}_1(s|\mathcal{S}_{(t)}) = \frac{\mathbf{Q}_1(s)}{\sum_{s' \in \mathcal{S}_{(t)}} \mathbf{Q}_1(s')} \qquad \text{and} \qquad \mathbf{Q}_2(s|\mathcal{S}_{(t)}) = \frac{\mathbf{Q}_2(s)}{\sum_{s' \in \mathcal{S}_{(t)}} \mathbf{Q}_2(s')}.$$

The RDB test aims to directly compare the renormalized relative abundance and determine the sign of their absolute difference $\mathbf{R}(s|\mathcal{S}_{(t)}) = \mathbf{Q}_1(s|\mathcal{S}_{(t)}) - \mathbf{Q}_2(s|\mathcal{S}_{(t)})$, that is,

$$H_{s,+}^{(t)} : \mathbf{R}(s|\mathcal{S}_{(t)}) > 0, \quad H_{s,0}^{(t)} : \mathbf{R}(s|\mathcal{S}_{(t)}) = 0, \quad \text{and} \quad H_{s,-}^{(t)} : \mathbf{R}(s|\mathcal{S}_{(t)}) < 0.$$

To test $H_{s,+}^{(t)}$, $H_{s,0}^{(t)}$, and $H_{s,-}^{(t)}$ in each iteration, the RDB test evaluates t-test statistics on the renormalized relative abundance

$$\hat{\mathbf{R}}(s|\mathcal{S}_{(t)}) = \frac{\bar{\mathbf{P}}_1(s|\mathcal{S}_{(t)}) - \bar{\mathbf{P}}_2(s|\mathcal{S}_{(t)})}{[\hat{\sigma}_1(s|\mathcal{S}_{(t)})/m_1 + \hat{\sigma}_2(s|\mathcal{S}_{(t)})/m_2]^{1/2}},$$

where $\bar{\mathbf{P}}_k(s|\mathcal{S}_{(t)})$ and $\hat{\sigma}_k(s|\mathcal{S}_{(t)})$ are mean and variance of renormalized relative abundance. The differential ASVs can then be identified by comparing the value of each $\hat{\mathbf{R}}(s|\mathcal{S}_{(t)})$ and the value of their median. This iterative method stops when no more differential ASVs are detected. If the last iteration is T, the estimator for $\mathcal{S}_0 = \{s : \mathbf{Q}_1(s) = b\mathbf{Q}_2(s)\}$ and $\mathcal{S}_1 = \{s : \mathbf{Q}_1(s) \neq b\mathbf{Q}_2(s)\}$ are $\hat{\mathcal{S}}_0 = \mathcal{S}_{(T)}$ and $\hat{\mathcal{S}}_1 = \mathcal{S}_{(T)}^*$.

ASV-weighted RDB test. As we mentioned before, a rich source of information neglected by the ASV-wise method is that similar ASVs are more likely to share a similar level of differential abundance. Motivated by this fact, we consider utilizing information from similar ASVs to determine the sign of $\mathbf{R}(s|\mathcal{S}_{(t)})$. By borrowing a classical idea in nonparametric statistics, we assign weights $w(s; s')$ to each pair of ASVs to reflect their similarity between ASV s and s'. Given fixed weights $w(s; s')$, we opt to adopt an ASV-weighted t-test statistic

$$\hat{\mathbf{R}}_w(s|\mathcal{S}_{(t)}) = \frac{\bar{\mathbf{P}}_{1,w}(s|\mathcal{S}_{(t)}) - \bar{\mathbf{P}}_{2,w}(s|\mathcal{S}_{(t)})}{[\hat{\sigma}_{1,w}^2(s|\mathcal{S}_{(t)})/m_1 + \hat{\sigma}_{2,w}^2(s|\mathcal{S}_{(t)})/m_2]^{1/2}}.$$

Here, $\bar{\mathbf{P}}_{k,w}(s|\mathcal{S}_{(t)})$ and $\hat{\sigma}_{k,w}(s|\mathcal{S}_{(t)})$ are mean and variance of ASV-weighted renormalized relative abundance at ASV s, defined as

$$\hat{\mathbf{P}}_{k,j,w}(s|\mathcal{S}_{(t)}) = \sum_{s' \in \mathcal{S}} w(s;s') \frac{\hat{\mathbf{P}}_{k,j}(s')}{\sum_{s'' \in \mathcal{S}_{(t)}} \bar{\mathbf{P}}_k(s'')}.$$

Note that the goal of ASV-weighted strategy is not to estimate relative abundance more accurately but to boost the power of testing $H_{s,+}^{(t)}$, $H_{s,0}^{(t)}$, and $H_{s,-}^{(t)}$. Before applying the ASV-weighted t-test, we still need to choose the appropriate weights $w(s;s')$ to borrow strength from similar ASVs better.

4.5 Adaptive Weights

Form of weights. One important advantage of weights $w(s,s')$ is that they can incorporate different types of similarity information between ASVs. More specifically, the weights we use here reflect two types of information: how different the two ASVs' sequences are and how different the levels of differential abundance are. The form of weights we consider is

$$w(s;s') = \mathbf{K}_s\left(\frac{d(s,s')}{r}\right) \mathbf{K}_a\left(\frac{D(\widehat{DA}(s);\widehat{DA}(s'))}{h}\right).$$

Here, $\mathbf{K}_s$ and $\mathbf{K}_a$ are two non-negative and non-increasing kernels with compact support. For example, $\mathbf{K}_a(x) = \max(1-x,0)$ and $\mathbf{K}_s(x) = \mathbf{I}(x < 1)$, where $\mathbf{I}$ is an indicator function. $d(s,s')$ is the distance between ASVs' sequences introduced in Section 4.3, and r is a tuning parameter to control the size of the neighborhood. We introduce a coefficient to measure the level of differential abundance and a corresponding estimator

$$DA(s) = \frac{\mathbf{Q}_1(s) - \mathbf{Q}_2(s)}{\mathbf{Q}_1(s) + \mathbf{Q}_2(s)} \qquad \text{and} \qquad \widehat{DA}(s) = \frac{\bar{\mathbf{P}}_1(s) - \bar{\mathbf{P}}_2(s)}{\bar{\mathbf{P}}_1(s) + \bar{\mathbf{P}}_2(s)}.$$

If s is a non-differential ASV, that is $s \in \mathcal{S}_0$, $DA(s) = (b-1)/(b+1)$. $D(\widehat{DA}(s);\widehat{DA}(s'))$ in the weights is a normalized estimator for the difference of differential abundance levels at s and s', $D(\widehat{DA}(s);\widehat{DA}(s')) = |\widehat{DA}(s) - \widehat{DA}(s')|/[\hat{\sigma}_{DA}^2(s)]^{1/2}$, where $\hat{\sigma}_{DA}^2(s)$ is an estimator for the variance of $\widehat{DA}(s)$. h is a tuning parameter to penalize the similarity of differential abundance between ASVs.

Propagation and separation. The performance of the weighted method usually depends on the choice of neighborhood size r. Large r could result in more bias because of over-smoothing, while the variance can be inflated if r is small. Moreover, the optimal choice of r could be different at different ASVs. Thus, it is usually difficult to find the optimal ASV-wise neighborhood sizes in practice. In addition, we can expect an ASV-weighted method to estimate $DA(s)$ more accurately than $\widehat{DA}(s)$. On the other hand, the weighted estimator relies on $w(s;s')$, of which $DA(s)$ is part. We adopt an iterative approach, propagation and separation method (PS) (Polzehl and Spokoiny, 2000, 2006), to select neighborhood size

and update estimation for $DA(s)$ simultaneously. The PS approach has been widely used in various imaging analyses (Li et al., 2011; Wang et al., 2019). By the PS approach, the weights $w(s; s')$ are determined in a data-driven way.

In the PS approach, we first choose a sequence of increasing radii, $0 = r_0 < r_1 < \ldots < r_v < \ldots < r_V$. We let radius $r_0 = 0$ and weights $w(s; s'; 0) = \mathbf{I}(s = s')$ to initialize the process, where $\mathbf{I}(\cdot)$ is an indicator function. Based on the $w(s; s'; 0)$, we can estimate the level of differential abundance at each ASV by $\widehat{DA}(s)$. $D(\widehat{DA}(s; 0); \widehat{DA}(s'; 0)) = |\widehat{DA}(s) - \widehat{DA}(s')|/[\hat{\sigma}_{DA}^2(s)]^{1/2}$ then estimates the difference of differential abundance levels. At iteration v, we first update the weights by the new radius r_v and the differential abundance level estimator in the last iteration

$$w(s; s'; v) = \mathbf{K}_s \left(\frac{d(s, s')}{r_v} \right) \mathbf{K}_a \left(\frac{D(\widehat{DA}(s; v - 1); \widehat{DA}(s'; v - 1))}{h} \right).$$

After updating weights, we then update the estimation for differential abundance level by the new weights

$$\widehat{DA}(s; v) = \frac{\bar{\mathbf{P}}_1(s; v) - \bar{\mathbf{P}}_2(s; v)}{\bar{\mathbf{P}}_1(s; v) + \bar{\mathbf{P}}_2(s; v)}, \qquad \text{where} \quad \bar{\mathbf{P}}_k(s; v) = \sum_{s' \in \mathcal{S}} w(s; s'; v) \bar{\mathbf{P}}_k(s').$$

We can update the weights and differential abundance level alternatively. When does this iterative procedure stop?

The stopping criteria for the above iterative procedure are based on the estimated level of differential abundance. Specifically, we choose the V_L as the number of required iteration and V_U as the largest possible iteration number. We shall not stop the PS approach when $v \leq V_L$ and always end it when $v = V_U$. When $V_L < v \leq V_U$, we compare $\widehat{DA}(s; v)$ with $\widehat{DA}(s; V_L)$ and stop if

$$D \left(\widehat{DA}(s; v); \widehat{DA}(s; V_L) \right) < H.$$

After the PS approach stops, we collect the weights in the final iteration and use them in the ASV-weighted RDB test.

4.6 Multiscale Adaptive Robust Differential Abundance Analysis

After introducing the ASV-weighted RDB test and propagation and separation approach, we are now ready to present our newly proposed multi-scale adaptive robust differential abundance test (MsRDB). The input of the MsRDB test is the ASV counts table and ASVs' sequences. MsRDB test consists of the following three steps:

1. Initialization: the ASV counts table is transformed as the relative abundance table. The ASVs' sequences are used to evaluate the ASV distance matrix defined in Section 4.3.

2. Weights calculation: evaluate weights $w(s; s')$ by applying propagation and separation approach to ASV relative abundance table and ASV distance matrix. We can obtain a weighted ASV table.

3. Differential ASV detection: identify differential ASVs by applying ASV-weighted RDB test to ASV relative abundance table.

Through these three steps, the MsRDB test identifies a collection of differentially abundant ASVs.

4.7 Results Interpretation in MsRDB Test

To transfer the results obtained by the MsRDB test into knowledge, we still need to interpret these differentially abundant ASVs. We consider two aspects of MsRDB results interpretation: abundance change and taxonomy assignment.

- (**Abundance change**) The framework of the reference-based hypothesis provides a natural way to interpret the results obtained from the compositional data. Specifically, we can regard the collection of non-differential ASVs $\hat{\mathcal{S}}_0$ as a reference set and compare everything with this estimated reference set. More specifically, we can always compare the relative abundance with respect to the reference set directly

$$\mathbf{P}_{k,j}(s|\hat{\mathcal{S}}_0) = \frac{\mathbf{P}_{k,j}(s)}{\sum_{s' \in \hat{\mathcal{S}}_0} \mathbf{P}_{k,j}(s')}, \qquad j = 1, \ldots, m_k \text{ and } k = 1, 2.$$

A change in the compositional data is interpreted as a change with respect to the estimated reference set. In the box plots of this work, we always plot the relative abundance with respect to the reference $\mathbf{P}_{k,j}(s|\hat{\mathcal{S}}_0)$ rather than the original relative abundance $\mathbf{P}_{k,j}(s)$.

- (**Taxonomy assignment**) Since we may find difficulty in assigning taxonomy to some of the ASVs, we opt first to cluster these differentially abundant ASVs into small groups. Specifically, we construct a graph for differentially abundant ASVs by thresholding the ASV distance matrix and then apply a graph-based clustering method for the resulting graph. After the small groups are constructed, we assign taxonomy to each small group of differential ASVs. The benefit of assigning taxonomy to the clusters is that it allows detecting unknown differentially abundant ASVs and assigns different taxonomy rank to different ASV groups.

4.8 Covariate Balancing

In an observational study, we also observe several additional covariates $\mathbf{X}_{k,j}$, which might be related to treatment assignment and compositional data. the MsRDB test can work with covariate balancing techniques, such as the weighting method (Imbens and Rubin, 2015), to reduce the potential confounding effect. The weighting method here is different from the ASV-weighted method discussed in the previous section. The weighting method aims to assign weights for each subject so that the distributions of the covariates in each population are roughly the same. Specifically, after the weights $w_{k,j}$ are assigned to each subject, we can consider a subject-weighted version of mean and variance instead of standard mean and

variance in the original MsRDB test. In particular, we choose the empirical balancing calibration weighting method (CAL) proposed by Chan et al. (2016), which provides a nonparametric way to estimate weights.

Acknowledgments

S. Wang acknowledges support from NSF Grant DMS-2113458.

Data Availability

All three data sets can be downloaded from Qiita (`https://qiita.ucsd.edu/`). Data set in Yatsunenko et al. (2012) is under study ID 850. Data set in Vangay et al. (2018) is under study ID 12080. Data set in Bokulich et al. (2014) is under study ID 2019.

Code Availability

All analyses can be found under `https://github.com/lakerwsl/MsRDB-Manuscript-Code`.

References

A. Amir, D. McDonald, J. A. Navas-Molina, E. Kopylova, J. T. Morton, Z. Zech X., E. P. Kightley, L. R. Thompson, E. R. Hyde, A. Gonzalez, and R. Knight. Deblur rapidly resolves single-nucleotide community sequence patterns. *MSystems*, 2(2):e00191–16, 2017.

M. W. Ariefdjohan, A. Dilk, O. N. Brown-Esters, and D. A. Savaiano. Chapter 37 - intestinal microbiota and diet in health. In A. M. Coulston, C. J. Boushey, M. G. Ferruzzi, and L. M. Delahanty, editors, *Nutrition in the Prevention and Treatment of Disease (Fourth Edition)*, pages 811–834. Academic Press, fourth edition edition, 2017. ISBN 978-0-12-802928-2.

N. A. Bokulich, J. H. Thorngate, P. M. Richardson, and D. A. Mills. Microbial biogeography of wine grapes is conditioned by cultivar, vintage, and climate. *Proceedings of the National Academy of Sciences*, 111(1):E139–E148, 2014.

B. Brill, A. Amir, and R. Heller. Testing for differential abundance in compositional counts data, with application to microbiome studies. *arXiv preprint arXiv:1904.08937*, 2019.

B. J. Callahan, P. J. McMurdie, M. J. Rosen, A. W. Han, A. J. A. Johnson, and S. P. Holmes. Dada2: high-resolution sample inference from illumina amplicon data. *Nature Methods*, 13(7):581–583, 2016.

K. C. G. Chan, S. C. P. Yam, and Z. Zhang. Globally efficient non-parametric inference of average treatment effects by empirical balancing calibration weighting. *Journal of the Royal Statistical Society. Series B, Statistical methodology*, 78(3):673, 2016.

J. Chen, E. King, R. Deek, Z. Wei, Y. Yu, D. Grill, and K. Ballman. An omnibus test for differential distribution analysis of microbiome sequencing data. *Bioinformatics*, 34(4): 643–651, 2018.

S. F. Clarke, E. F. Murphy, K. Nilaweera, P. R. Ross, F. Shanahan, P. W. O'Toole, and P. D. Cotter. The gut microbiota and its relationship to diet and obesity: new insights. *Gut Microbes*, 3(3):186–202, 2012.

G. M. Douglas, V. J. Maffei, J. R. Zaneveld, S. N. Yurgel, J. R. Brown, C. M. Taylor, C. Huttenhower, and M. G. Langille. Picrust2 for prediction of metagenome functions. *Nature Biotechnology*, 38(6):685–688, 2020.

A. D. Fernandes, J. M. Macklaim, T. G. Linn, G. Reid, and G. B. Gloor. Anova-like differential gene expression analysis of single-organism and meta-rna-seq. *PLoS One*, 8(7): e67019, 2013.

J. F. Gentleman and R. C. Mullin. The distribution of the frequency of occurrence of nucleotide subsequences, based on their overlap capability. *Biometrics*, pages 35–52, 1989.

G. B. Gloor, J. M. Macklaim, V. Pawlowsky-Glahn, and J. J. Egozcue. Microbiome datasets are compositional: and this is not optional. *Frontiers in microbiology*, 8:2224, 2017.

M. Hamady and R. Knight. Microbial community profiling for human microbiome projects: tools, techniques, and challenges. *Genome research*, 19(7):1141–1152, 2009.

G. W. Imbens and D. B. Rubin. *Causal inference in statistics, social, and biomedical sciences.* Cambridge University Press, 2015.

S. Janssen, D. McDonald, A. Gonzalez, J. A. Navas-Molina, L. Jiang, Z. Z. Xu, K. Winker, D. M. Kado, E. Orwoll, M. Manary, S. Mirarab, and R. Knight. Phylogenetic placement of exact amplicon sequences improves associations with clinical information. *Msystems*, 3 (3):e00021–18, 2018.

H. Li. Microbiome, metagenomics, and high-dimensional compositional data analysis. *Annual Review of Statistics and Its Application*, 2:73–94, 2015.

Y. Li, H. Zhu, D. Shen, W. Lin, J. H. Gilmore, and J. G. Ibrahim. Multiscale adaptive regression models for neuroimaging data. *Journal of the Royal Statistical Society: Series B*, 73(4):559–578, 2011.

H. Lin and S. D. Peddada. Analysis of compositions of microbiomes with bias correction. *Nature Communications*, 11(1):1–11, 2020a.

H. Lin and S. D. Peddada. Analysis of microbial compositions: a review of normalization and differential abundance analysis. *NPJ biofilms and microbiomes*, 6(1):1–13, 2020b.

S. Mandal, W. Van Treuren, R. A. White, M. Eggesbø, R. Knight, and S. D. Peddada. Analysis of composition of microbiomes: a novel method for studying microbial composition. *Microbial ecology in health and disease*, 26(1):27663, 2015.

B. D. Martin, D. Witten, and A. D. Willis. Modeling microbial abundances and dysbiosis with beta-binomial regression. *Annals of Applied Statistics*, 14(1):94–115, 2020.

M. R. McLaren, A. D. Willis, and B. J. Callahan. Consistent and correctable bias in metagenomic sequencing experiments. *Elife*, 8:e46923, 2019.

V. Meslier, M. Laiola, H. M. Roager, F. De Filippis, H. Roume, B. Quinquis, R. Giacco, I. Mennella, R. Ferracane, N. Pons, E. Pasolli, A. Rivellese, L. O. Dragsted, P. Vitaglione, S. O. Ehrlich, and D. Ercolini. Mediterranean diet intervention in overweight and obese subjects lowers plasma cholesterol and causes changes in the gut microbiome and metabolome independently of energy intake. *Gut*, 69(7):1258–1268, 2020.

J. T. Morton, C. Marotz, A. Washburne, J. Silverman, L. S. Zaramela, A. Edlund, K. Zengler, and R. Knight. Establishing microbial composition measurement standards with reference frames. *Nature Communications*, 10(1):1–11, 2019.

J. N. Paulson, O. C. Stine, H. C. Bravo, and M. Pop. Differential abundance analysis for microbial marker-gene surveys. *Nature Methods*, 10(12):1200–1202, 2013.

J. Polzehl and V. Spokoiny. Propagation-separation approach for local likelihood estimation. *Probability Theory and Related Fields*, 135(3):335–362, 2006.

J. Polzehl and V. G. Spokoiny. Adaptive weights smoothing with applications to image restoration. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 62(2):335–354, 2000.

D. Vandeputte, G. Kathagen, K. D'hoe, S. Vieira-Silva, M. Valles-Colomer, J. Sabino, J. Wang, R. Y. Tito, L. De Commer, Y. Darzi, S. Vermeire, G. Falony, and J. Raes. Quantitative microbiome profiling links gut community variation to microbial load. *Nature*, 551(7681):507–511, 2017.

P. Vangay, A. J. Johnson, T. L. Ward, G. A. Al-Ghalith, R. R. Shields-Cutler, B. M. Hillmann, S. K. Lucas, L. K. Beura, E. A. Thompson, L. M. Till, R. Batres, B. Paw, S.L. Pergament, P. Saenyakul, M. Xiong, A. D. Kim, G. Kim, D. Masopust, E. C. Martens, C. Angkurawaranon, R. McGready, P. C. Kashyap, K. A. Culhane-Pera, and D. Knights. Us immigration westernizes the human gut microbiome. *Cell*, 175(4):962–972, 2018.

S. Wang. Robust differential abundance test in compositional data. *arXiv preprint arXiv:2101.08765*, 2021.

S. Wang, E. T. Arena, J. T. Becker, W. M. Bement, N. M. Sherer, K. W. Eliceiri, and M. Yuan. Spatially adaptive colocalization analysis in dual-color fluorescence microscopy. *IEEE Transactions on Image Processing*, 28(9):4471–4485, 2019.

S. Weiss, Z. Z. Xu, S. Peddada, A. Amir, K. Bittinger, A. Gonzalez, C. Lozupone, J. R Zaneveld, Y. Vázquez-Baeza, A. Birmingham, et al. Normalization and microbial differential abundance strategies depend upon data characteristics. *Microbiome*, 5(1):27, 2017.

E. S. Wright. Using decipher v2. 0 to analyze big biological sequence data in r. *R Journal*, 8(1), 2016.

T. Yatsunenko, F. E. Rey, M. J. Manary, I. Trehan, M. G. Dominguez-Bello, M. Contreras, M. Magris, G. Hidalgo, R. N. Baldassano, A. P. Anokhin, A. C. Heath, B. Warner, J. Reeder, J. Kuczynski, J. G. Caporaso, C. A. Lozupone, C. Lauber, J. C. Clemente, D. Knights, R. Knight, and J. I. Gordon. Human gut microbiome viewed across age and geography. *Nature*, 486(7402):222–227, 2012.

Supplement Material

Practical Considerations

To implement the MsRDB test, we need to specify the choices of several tuning parameters. We need to choose the kernel $\mathbf{K}_s$ and radii $r_1 < \ldots < r_V$ together. To simplify the implementation, we adopt the idea from the k-nearest neighbor algorithm. Specifically, we choose $K_s(x) = \mathbf{I}(x < 1)$. The radius r_v at ASV s is chosen in the following way: we first sort the distance $d(s, s')$ in a sense that

$$d(s, s'_{(1)}) \leq d(s, s'_{(2)}) \leq \ldots \leq d(s, s'_{(|\mathcal{S}|)});$$

the radius $r_v = d(s, s'_{(k_v)})$ is chosen for a predefined integer k_v. Equivalently, we include k_v neighbors at the iteration v and assign the weights of these k_v neighbors as 1. We choose k_v as a geometric sequence, that is, $k_v = \lceil k^{v/V} \rceil$, where $V = V_U$ is the largest number of iterations, and k is the number of neighbors in the last iteration. In all numerical experiments, we choose $V = 10$. The main advantage of using a strategy in the k-nearest neighbor algorithm is that the total number of weights we need to store is just $|\mathcal{S}| \times k$, so the computation complexity of the weights update is also $|\mathcal{S}| \times k$.

There are many different options for $\mathbf{K}_a$ and h. Based on our experience, we choose $\mathbf{K}_a(x) = \exp(-2x^2)$ and $h = 10\sqrt{\log(|\mathcal{S}|)}$ in our implementation. These parameters are mainly used to separate the ASVs with different levels of differential abundance. In the stopping criteria, we choose $V_L = 5$, $H = 2\sqrt{\log(|\mathcal{S}|)}$ and $V_U = V = 10$. V_L cannot be set as a too small number, e.g. 1, since the first a few iterations might not be stable. The computational complexity relies on V_U, as it controls the number of iterations we need to evaluate.

In the ASV-weighted RDB test, we use the same choices of parameters as the original RDB test. As we always aim to control FDR, the critical value for directional testing is chosen adaptively, as discussed in Section 4 of Wang (2021). The covariate balancing method we used in the MsRDB test is the weighting method implemented in `ATE` R package.

Simulation Setup

The simulated ASV data set is generated from a real gut microbiota data set collected in Yatsunenko et al. (2012). This data set includes V4 16S rRNA data from 528 subjects. The data set is trimmed at length 100 and denoised by Deblur method (Amir et al., 2017). We keep 1965 ASVs which appear in more than 3% of all subjects. To simulate the data set, we consider the following procedure:

1. We randomly draw m subjects as the treated group and m subjects as the control group.

2. We randomly select s ASVs and their neighbors as differential ASVs. The distance between ASVs is defined by the hamming distance between aligned sequences and calculated by function `DistanceMatrix` in `DECIPHER` R package. The number of neighbors is selected randomly between 10 and 15.

3. For each selected differential ASV and its neighbors, the effect size is randomly chosen between $1 + \lambda$ and $1 + 2\lambda$. The count data in the treated group are multiplied by the chosen effect sizes.

4. To mimic the experimental bias, we multiply the count data of each ASV by a measurement efficiency constant randomly drawn between 1 and 10.

In this simulation setup, m is the sample size, λ is the effect size, and s is the number of differential ASVs (sparsity). Specifically, we consider three sets of simulation experiments:

- We first investigate the influence of sample size, so we choose $m = 50, 100, 200, 400$, $\lambda = 10$, and $s = 20$. The results are summarized in Figure 3.

- We next investigate the influence of effect size, so we choose $m = 300$, $\lambda = 2, 4, 6, 8$, and $s = 20$. The results are summarized in Figure S1.

- Finally, we investigate the influence of the number of differential ASVs, so we choose $m = 200$, $\lambda = 8$, and $s = 5, 10, 15, 20$. The results are summarized in Figure S2.

Differential Abundance Analysis in the Study of Immigration

Taxonomy in the immigration study data set (Vangay et al., 2018) is assigned by function `assignTaxonomy` in `dada2` R package with training files from the Silva Project's version 138.1 release. The differential abundance analysis includes 14471 ASVs assigned to kingdom

Figure S1: **FDR and power comparisons in simulated data set when the effect size is different.** Left and right figures show the FDR and power of various versions of RDB methods when the effect sizes are 2, 4, 6, and 8. The dashed line in the left figure is the target level of FDR at 10%. The results in this figure show that the power becomes larger when the effect size increases.

Figure S2: **FDR and power comparisons in simulated data set when the number of differentially abundant ASVs is different.** Left and right figures show the FDR and power of various versions of RDB methods when the numbers of differentially abundant ASVs are 5, 10, 15, and 20. The dashed line in the left figure is the target level of FDR at 10%. The results in this figure show that the performance of various methods is relatively stable when the number of differentially abundant ASVs is different.

Bacteria. Besides the microbiome data, we also observe several extra variables in this observational study. In particular, we include age and BMI into our analysis, as they might bring potential confounding effects. The degree of covariance balancing in age and BMI suggests that neither variable is well balanced, so we must adjust these two covariates in differential abundance analysis (Figure S3). We adopt the weighting method implemented in `ATE` R package for the RDB and the MsRDB tests to balance covariates. In the MsRDB test,

the distance matrix between ASVs' sequences is calculated by function `DistanceMatrix` in `DECIPHER` R package. In the MsRDB test, the number of neighbors in the last iteration is $k = 20$.

Figure S3: **Degree of covariance balancing in age and BMI in immigration study.** This figure compares the distribution of covariates among HmongThai, Hmong2nd, and Control. Left is age, and right is BMI.

Figure S4: **Taxa detected by MsRDB test on the microbiota data set in immigration study.** The reference set in all box plots is all non-differentially abundant ASVs revealed by the MsRDB test. (A) The box plots show the relative abundance with respect to the reference set in all ASVs assigned to genus *Ruminococcus torques* (left), in significant ASVs within *Ruminococcus torques* (right), and in the rest of ASVs within *Ruminococcus torques* (middle). (B) The box plot shows the relative abundance with respect to the reference set in all significant ASVs assigned to the NA genus.

Differential Abundance Analysis in the Study of Wine Grape

Similar to the previous data set, we assign taxonomy of ASVs in wine grape data set (Bokulich et al., 2014) by function `assignTaxonomy` in `dada2` R package. The distance matrix in the MsRDB test is also calculated by function `DistanceMatrix` in `DECIPHER` R package. In the MsRDB test, the number of neighbors in the last iteration is $k = 15$. In clustering analysis, we first construct a graph where two significant ASVs are connected if they are in each other k nearest neighbor. Then, each connected subgraph is a cluster, and the small clusters with a total number of reads smaller than 10 are removed from the results.

Figure S5: **Comparisons between ASV-wise analysis (ANCOM-BC), taxon-wise analysis (ANCOM-BC), and the MsRDB test on the immigration microbiota data set.** In this figure, ANCOM-BC is applied in ASV-wise analysis and taxon-wise analysis. (A-C) shows the overlap of results obtained by different analysis strategies in pairwise comparisons of three groups of people. The three rows are the comparisons of HmongThai vs. Control, Hmong2nd vs. HmongThai, and Hmong2nd vs. Control.

Figure S6: **Comparisons between ASV-wise analysis (ALDEx2), taxon-wise analysis (ALDEx2), and the MsRDB test on the immigration microbiota data set.** In this figure, ALDEx2 is applied in ASV-wise analysis and taxon-wise analysis. (A-C) shows the overlap of results obtained by different analysis strategies in pairwise comparisons of three groups of people. The three rows are the comparisons of HmongThai vs. Control, Hmong2nd vs. HmongThai, and Hmong2nd vs. Control.

Figure S7: **Comparisons between ASV-wise analysis and MsRDB test on the grape microbiota data set.** This figure shows the overlap of identified ASV by ASV-wise analysis and the MsRDB test. Left is Sonoma vs. Napa, middle is Central Coast vs. Napa, and right is Central Coast vs. Sonoma.