Visual category representations in the infant brain

Siying Xie[1]*, Stefanie Hoehl[2,3], Merle Moeskops[1], Ezgi Kayhan[2,4], Christian Kliesch[2,5], Bert Turtleton[1], Moritz Köster[1,2,9], Radoslaw M. Cichy[1,6,7,8,9]*

[1]Department of Education and Psychology, Freie Universität Berlin; 14195 Berlin, Germany.

[2]Max Planck Institute for Human Cognitive and Brain Sciences; 04103 Leipzig, Germany.

[3]Department of Developmental and Educational Psychology, University of Vienna; 1010 Wien, Austria.

[4]Department of Developmental Psychology, University of Potsdam; 14469 Potsdam, Germany.

[5]Department of Psychology, Johannes-Gutenberg-University Main; 55122 Mainz, Germany.

[6]Berlin School of Mind and Brain, Faculty of Philosophy, Humboldt-Universität zu Berlin; 10117 Berlin, Germany.

[7]Einstein Center for Neurosciences Berlin, Humboldt-Universität Berlin; 10117 Berlin, Germany.

[8]Bernstein Center for Computational Neuroscience Berlin, Humboldt-Universität Berlin; 10115 Berlin, Germany.

[9]These authors contributed equally to this work.

*Corresponding author. Emails: rmcichy@zedat.fu-berlin.de (RMC); siying.xie@outlook.com (SX).

KEYWORDS

SUMMARY

Visual categorization is a human core cognitive capacity[1,2] that depends on the development of visual category representations in the infant brain[3–7]. However, the exact nature of infant visual category representations and their relationship to the corresponding adult form remains unknown[8]. Our results clarify the nature of visual category representations from electroencephalography (EEG) data in 6- to 8-month-old infants and their developmental trajectory towards adult maturity in the key characteristics of temporal dynamics[2,9], representational format[10–12], and spectral properties[13,14]. Temporal dynamics change from slowly emerging, developing representations in infants to quickly emerging, complex representations in adults. Despite those differences, infants and adults already partly share visual category representations. The format of infants' representations is visual features of low to intermediate complexity, whereas adults' representations also encode high complexity features. Theta band neural oscillations form the basis of visual category representations in infants, and these representations are shifted to the alpha/beta band in adults. Together, we reveal the developmental neural basis of visual categorization in humans, show how information transmission channels change in development, and demonstrate the power of advanced multivariate analysis techniques in infant EEG research for theory building in developmental cognitive science.

RESULTS & DISCUSSION

The ability to recognize and categorize visual objects effortlessly and within the blink of an eye is a core human cognitive capacity[1,2] that develops through learning and interaction with the environment. Behavioral research in infants using looking times[6,7,15] and neural markers of attention provides evidence for visual category processing[16] and learning[5,17] already within the first year of life.

In adults fundamental research in human and non-human primates has described the nature of the neural representations underlying mature visual categorization abilities, revealing their temporal dynamics[2,9], what features they encode[10–12], their cortical locus[11,18], and how they relate to neural oscillations[13,14]. In contrast, these key characteristics of visual category representations[19–23] are less well understood in infants due to strong methodological challenges in human and non-human infant neuroimaging research[8,24,25]. In particular, research using EEG – the workhorse of infant neuroimaging for decades – has yielded insights that are principally limited in two ways. One research approach focused on assessing the successful outcome of visual categorization rather than the underlying representations themselves[26]. Thus, the insights gained about representations are indirect. Another research approach did assess underlying representations directly but was limited to the category of faces[3,27] for which known neural markers exist. Thus, the generalizability from the unique and small stimulus subset to the broad set of visual categories of the visual world remains unclear.

Here we overcome this double impasse to reveal the nature of general visual category representations for various object categories in 6- to 8-month-old infants from EEG data. We do so by leveraging an integrated multivariate analysis framework of multivariate classification[9] and direct quantitative comparison[28] of the infant to adult EEG data and deep learning models of vision[12].

The temporal dynamics of visual category representations

Infant participants ($n = 40$) viewed 128 images of real-world objects from four categories (i.e., toys, bodies, houses and faces, **Fig. 1a, Supplementary Fig. 1,2**) while we acquired EEG data. Images were presented for 2s every 2.7–2.9s. For direct comparison we acquired EEG data in adult participants ($n = 20$) viewing the same stimulus set with an adapted experimental design (**Supplementary Fig. 2**). We consider the epoch of –100ms to +1,000ms with respect to stimulus onset in our analyses.

73
Figure 1 Experimental design and results of time-resolved multivariate analysis. (a) The stimulus set comprised
32 cut-out images from four categories each: toys, headless bodies, houses and faces (full set see **Supplementary**
Fig. 1). We omitted all human face images in this version due to insufficient resources on the preprint server to
check for consent for the public display of them. **(b)** Time-resolved multivariate analysis on EEG data. First, for
every time point in the epoch, we extracted condition-specific EEG sensor activation values and formed them into
response vectors. Then, using a leave-one-out cross-validation scheme we trained and tested a support vector
machine to pairwise classify visual object category from the response vectors. The results (decoding accuracy, 50%
chance level) were aggregated in a decoding accuracy matrix of size 4 × 4, indexed in rows and columns by the
conditions classified. The matrix is symmetric along the diagonal, and the diagonal is undefined. Averaging the
lower triangular part of the matrix resulted in grand average decoding accuracy as a measure of how well category is
discriminated by visual representations at a particular time point. **(c, d)** The grand average time course of visual
category decoding in infants **(c)** and adults **(d)**. **(e, f)** Results of category classification in EEG channel-space
searchlight analysis for infants **(e)** and adults **(f)**. **(g, h)** Results of time-generalization analysis for infants **(g)** and
adults **(h)**. Peak latencies and on- and offsets of significance with 95% confidence intervals (CIs) are listed in
Supplementary Table 1a,b. Rows of asterisks indicate significant time points (infant $n = 40$, adult $n = 20$, right-

tailed sign permutation tests, cluster-defining threshold $P < .005$, corrected significance level $P < .05$). Horizontal
error bars indicate 95% CIs. The gray vertical line indicates onset of image presentation.

To reveal the time course with which visual category is discriminated by visual representations
we used time-resolved multivariate pattern analysis[9] (**Fig. 1b**). We report peak latency (95%
confidence intervals (CIs) in brackets) as the time point during neural processing when category
information was most explicit, as well as onset and offset of significance for each group.

In infants (**Fig. 1c**), the classification curve rose gradually from 100ms onwards, reaching
significance at 252ms (250–254ms), followed by a broad peak at 416ms (268–462ms) and a
gradual decline. This pattern of result did not depend on any particular object or category
(**Supplementary Fig. 3a,b),** and emerged equivalently for alternative common analysis schemes
(**Supplementary Fig. 3c–e**). In contrast, in adults, the classification curve had a different shape
(**Fig. 1d**). It emerged earlier (significant at 72ms (72–74ms)) and faster, peaking at 154ms (144–
176ms) than in infants ($P < .001$, bootstrap test, **Supplementary Table 1a**). Searchlight analysis
in EEG channel space revealed that information about visual category representations was
highest in EEG channels overlying occipitoparietal cortex in both infants (**Fig. 1e**) and adults
(**Fig. 1f**).

This multivariate approach constitutes a novel analytical access point to visual category
representations in infants from EEG data. It shows that visual category representations emerge in
similar cortical structures, but slower and later in infants than adults.

The rise and fall of the classification curves in a few hundred milliseconds might indicate rapid
changes in the underlying visual representations[2,9], or slow ramping up of persistent
representations, or a combination of both. To investigate this, we assessed the temporal stability
of visual representations using time-generalization analysis[29]. We determined how well
classifiers trained on predicting visual category from EEG at one time point perform when tested
at other time points. Lack of generalization across time indicates transience of the underlying
visual representation, whereas generalization across time indicates persistence.

In both infants (**Fig. 1g**) and adults (**Fig. 1h**), classification accuracy was highest along the
diagonal (i.e., similar time points for training and testing) with a broadening over time (white
dotted ellipse). This result suggests common neural mechanisms of a rapid sequence of
processing steps that result in an outcome held online for further use, indicated by rapidly
changing transient representations at earlier time points and more slowly changing persistent
representations at later time points, respectively.

In addition to this general similarity between infants and adults, two notable differences were
indicative of incomplete development of feedforward and feedback information processing in
infants. For one, early after stimulus onset when neural processing is dominantly feedforward, in
adults, we observed high classification accuracy trailing the diagonal narrowly (**Fig. 1h**, 50–
200ms, dotted square), indicating rapid changing representations. Infants did not exhibit such
signals. This pattern suggests incomplete development of feedforward visual information
processing mechanisms in infants. Secondly, in adults, the classifier generalized well for the time
point combination of 100–200ms and 200–1,000ms (**Fig. 1h**, white striped rectangle). This
suggests highly persistent representations, likely emerging in the early visual cortex[9]. There were
no such signals in infants. This indicates incomplete neural structures for recurrent processing
that maintain visual information online for long stretches of time.

Shared visual category representations between infants and adults

Figure 2 Category representations shared between infants and adults. (a) We used RSA to relate category representations in infants and adults. We interpret decoding accuracy as a dissimilarity measure on the assumption that the more dissimilar two representations are, the better the classifier performs. This allowed us to use time-resolved decoding accuracy matrices as representational dissimilarity matrices (RDMs) that summarize representational similarities between category representations. We compared RDMs (Spearman's *R*) in infants (average across participants) and adults (for each participant separately) for all time point combinations (t_x, t_y), assigning the values to a time-generalization matrix indexed in rows and columns by the time in adults (t_x) and infants (t_y). **(b)** Average time-generalization matrix relating category representations in infants and adults over time. For statistical details, see **Supplementary Table 1c**. The gray lines indicate image onset. Black outlines indicate time point combinations with significant correlation ($n = 20$, right-tailed sign permutation tests, cluster-defining threshold $P < .005$, corrected significance level $P < .05$).

The results so far show that we identified visual category representations in both infants and adults and that their time courses have both similar and different aspects. However, we have not tested whether infants and adults have similar category representations. An alternative hypothesis is that we observe time courses of category classification for infants and adults, but those are unrelated rather than shared representations. Direct identification of shared representations between infants and adults is challenging due to differences in the time course over which the representations emerge, and the EEG channel spaces differ. We used a time-generalization variant of representational similarity analysis (RSA)[28] (**Fig. 2a**) to overcome these hurdles. In short, we abstracted multivariate signals from the incommensurate infant and adult EEG channel spaces to a common representational dissimilarity space, and we compared the signals across all time point combinations.

We observed similarity in visual category representations between infants and adults at the time point combinations of 160–540ms in infants, and 100–1,000ms in adults (**Fig. 2b**, peak latency in infants: 200ms (200–360ms); in adults: 120ms (120–1,000ms)). This result was similarly achieved for alternative processing and data aggregation choices (**Supplementary Fig. 4**). Our findings establish quantitatively and directly that infants and adults share visual category representations.

In sum, the emerging picture is one of not yet fully developed dynamics of adult-like visual category representations in infants. Representations in infants emerged later, slower, and lacked particular components of feedforward and recurrent processing, possibly related to immature myelination[30] and synaptic connectivity[31]. Nevertheless, representations in infants and adults shared large-scale temporal dynamics that encoded visual category information similarly,

consistent with previous showing partly adult-like behavioral[3,5,7,15] and neural[19,20] category
sensitivity in the first year of age.

Our approach goes beyond previous EEG work in developmental visual neuroscience in three
ways. First, rather than relying on indirect inference from attentional markers indicating
successful categorization[26], our approach assessed representations directly as they emerge with
millisecond resolution. Second, our approach is not limited to the face category and face-specific
EEG components[3,27], but allows the study of potentially any visual category. Third, our approach
enabled a new quantitative comparison[28] of infant and adult visual category representations.

Our results make direct predictions for the detailed developmental trajectory of visual category
representations[32]. We expect category representations to emerge increasingly earlier and with
faster temporal dynamics with increasing age, with additional feedforward and feedback
components appearing at critical stages until a mature adult-like system emerges. Our approach
makes these predictions immediately testable in future studies using other age groups between
early infancy and adulthood.

More broadly, our multivariate EEG analysis approach demonstrates a novel access point to
largely unmapped neural representations in the infant brain, with strong potential to inform
theories of cognitive development for cognitive capacities that emerge in the first year of life,
such as object learning[5,6,17], speech processing[33], and core knowledge systems[34]. Combined with
human infant fMRI[19,20,25] and behavioral assessment[15] in a common framework[35], this promises
to reveal the unknown spatiotemporal neural dynamics underlying cognitive functions in infants
in the future.

The format of visual category representations

Figure 3 The format of category representations in infants and results. (a) We characterized what type of visual
features are encoded in category representations in infants and adults by relating their category representations to
computational models using RSA. For this we ran the stimulus images through a Gabor filter bank and the VGG-19
deep neural network trained on object categorization. We constructed RDMs from their unit activation patterns
(visualized in **Supplementary Fig. 5**). We then compared model RDMs to infant and adult neural RDMs
(Spearman's *R*), constructed as the average of RDMs over time from time-resolved category classification in the
95% CIs around peak latency (see **Fig. 1c,d**). **(b, c)** Results for infants **(b)** and adults **(c)** at the whole-model level.
(d, e) Results for infants **(d)** and adults **(e)** at the DNN layer level. Error bars represent standard errors of the mean.
Asterisks indicate significant correlations between model RDMs and neural RDMs (infant *n* = 40, adult *n* = 20, two-
tailed sign-permutation tests, *P* < .05, FDR-corrected). Statistical details (i.e., correlations and *P*-values) are in
Supplementary Table 3.

The time-resolved multivariate pattern analysis revealed the presence and dynamics of visual
category representations in the infant and adult brain. However, by itself, it is unable to specify
their format, i.e., what type of visual features they encode. We hypothesized that adults would
encode visual features represented at all levels of the visual processing hierarchy from low- to
high complexity[10,2]. Instead, infants would encode visual features rather of low- and mid-
complexity, as predicted from visual behavior[7,26] and anatomical development patterns[32] of the
infant visual brain.

To determine the format of category representations, we related them to computational models of
vision (**Fig. 3a**). We probed two types of models: a Gabor wavelet pyramid model as a model of
simple visual features[36], and the deep neural network VGG-19 model[37] trained on object
categorization, which exhibits a hierarchy of low-to-high complexity features along with its

layers, and predicts activity along the visual processing hierarchy of the adult human brain
well[12,38].

Assessing first the Gabor model and an aggregated summary of the VGG model across layers,
we found similar representations between both models and infant and adult visual representations
(**Fig. 3b,c**). This indicates that low complexity, simple features contribute to category
representations. We then conducted a finer investigation of VGG at the level of layers.
Considering each layer separately, we found that in infants, middle layers predicted brain activity
best, with layer groups 3 and 4 being significant (**Fig. 3d**). In contrast, layers at all stages were
significantly predictive in adults (**Fig. 3e**). This pattern of results was also achieved for other
types of deep neural network architectures (**Supplementary Fig. 6**) and independent of data
selection choices (**Supplementary Fig. 7**), demonstrating the robustness of the result.

Together, this shows that in infants, category representations are in the format of low- and
intermediate-complexity features, whereas in adults, the category is additionally discriminated by
representations encoding features of high complexity.

Previous research investigating the format of infant visual category representations tested
hypotheses one by one through experimental manipulation, for example, determining whether
infants are sensitive to stimulus inversion[27] or tolerant to changes in viewing conditions[39].
Instead, our approach allows the comparison of any number of hypotheses as captured in
explicit, image-computable computational models to capture infant visual category
representations in the future increasingly accurately. To speed up this process, we make the data
publicly available.

Our findings further suggest constraints for artificial intelligence research. The biological brain
inspired the engineering of deep learning models, but the models' learning has remained
biologically unrealistic[12,38,40] and is perceived as a major impediment to building better models.
We suggest that models of human visual categorization striving for increased biological realism
should follow a similar developmental trajectory of representations as described here.

Spectral properties of visual category representations

Neural oscillations underlie the formation and communication of visual representations[14,41–43].
Here we determined the neural oscillatory signature of visual category representations in infants.
For this, we resolved EEG data in distinct frequency bins from 2 to 30Hz and performed time-
resolved visual category classification on each bin separately (**Fig. 4a**). In infants (**Fig. 4b**), we
observed significant category classification accuracy in a specific cluster in the theta band with a
peak at 4.63Hz (2.91–6.73Hz) and 400ms (160–580ms). This result reveals theta oscillations as
the oscillatory basis of visual category representations in infants. In contrast, in adults (**Fig. 4c**)
the cluster extended across the whole frequency range and time course investigated. This result
shows that the oscillatory basis of visual category representations in adults is broadband. Note
that the observed differences in infants and adults are not a trivial consequence of differences in
EEG power spectra, as those were similarly broadband in both infants and adults
(**Supplementary Fig. 8**).

Figure 4 Spectral characterization of infant and adult category representations. (a) Category classification based on frequency-resolved EEG data. We first decomposed EEG data in time and frequency using *Morlet* wavelets for each trial and each channel, yielding a trial-wise representation of induced oscillatory power. We then conducted time-resolved multivariate classification of category separately on each frequency bin. This yielded a 4 × 4 matrix of decoding accuracies at each time point and frequency bin, which we either averaged to obtain grand average category classification **(b, c)** or used as an RDM in RSA **(d, e)**. **(b, c)** Results of time- and frequency-resolved MVPA for infants **(b)** and adults **(c)**. **(d)** RSA procedure linking oscillation-based visual category representations in infants and adults. We first created a single aggregate infant oscillatory RDM by averaging decoding accuracy matrices based on the extent of the cluster in the infant data. We compared (Spearman's *R*) this aggregate infant RDM to time- and frequency- resolved RDMs for each participant in the adult sample. This yielded a two-dimensional matrix indicating in which frequency range and when category representations are similar between infants and adults. **(e)** Similarity between infant theta-based category representations and adult category representations resolved in time and frequency. The gray vertical lines indicate onset of image presentation. Black outlines indicate time point combinations with significant results (infants *n* = 40, adults *n* = 20, right-tailed permutation test, cluster-defining threshold *P* < .005, corrected significance level *P* < .05). For statistical details see **Supplementary Table 3.**

The observed pattern of results is consistent with two alternative hypotheses about the relationship between the oscillatory basis of visual category representations in infants and adults. One hypothesis is that there is a direct match in frequency, suggesting that peak classification in infants and adults is at similar frequencies (i.e., at 4.63Hz and 5.59Hz, respectively). Another hypothesis is an upward shift across age, made plausible by the observations that brain rhythms increase in frequency during infant development[44].

To arbitrate between those hypotheses, we determined which frequency band and time points category representations in adults were similar to infant category representations identified in the theta band (**Fig. 4d**. We found a cluster of significant correlations with a peak at 17.13Hz (9.78–

20.65 Hz) at 120ms (120–360ms) (**Fig. 4e).** A supplementary data aggregation scheme yielded
an equivalent pattern (**Supplementary Fig. 9**). This demonstrates in a direct and quantitative
way an upward shift in the oscillatory basis of visual category representations from the theta
range in infants to the alpha/beta range in adults.

One interpretation of these findings is that in infants, category representations are processed in
neural networks for learning and memory associated with the theta rhythm[45,46], whereas in
adults, equivalent category representations are processed quickly in fully developed semantic
networks associated with the alpha/beta rhythms[47,48]. Alternatively, the frequency shift might be
due to more efficient axonal transmission as a result of improved myelination[30] that may enable
higher neural oscillations to emerge in the same neural circuits, consistent with increases in the
prevalent frequency in the EEG across development[44]. On this account, our finding suggests a
novel general developmental trajectory for neural communication channels in the human brain:
specific information-processing mechanisms working at low frequency in infants are shifted up
in frequency gradually across development, and the size of this shift depends on the differences
in neural circuit myelination.

The nature and developmental trajectory of infant to adult visual category representations

In sum, our results reveal the nature and developmental trajectory of the infant to adult visual
category representations, from infancy to adulthood. Temporal dynamics change from slowly to
quickly emerging in time, the format from visual features up to intermediate complexity to
features of high complexity, and the oscillatory basis from the theta to the alpha/beta frequency.
These results provide insight into visual category representations that underlie the development
of fast and efficient visual categorizations skills in humans. They also further reveal how cortical
information transmission channels change in human development and demonstrate the power of
advanced multivariate analysis techniques in infant EEG research for developmental cognitive
science.

SUPPLEMENTAL INFORMATION

Supplemental information can be found at [link to be inserted].

ACKNOWLEDGMENTS

R.M.C is supported by Deutsche Forschungsgemeinschaft (DFG) grants (CI241/1-1, CI241/3-1, CI241/7-1) and by a European Research Council Starting Grant (ERC-2018-StG). S.X. is supported by a scholarship by the Chinese Scholarship Council. M.K. and S.H. were supported by the DFG and FWF jointly (grant numbers: KO 6028/1-1; I 4332-B), and S.H. also by the Max Planck Society. Computing resources were provided by the high-performance computing facilities at ZEDAT, Freie Universitaet Berlin.

AUTHOR CONTRIBUTIONS

Conceptualization: RC, SX, MK, SH, BT. Methodology: SX, RC, MK. Software: SX, MK. Formal analysis: SX, MM. Investigation: EK, CK, Resources: SX, RC, MK. Data curation: SX. Writing - original draft preparation SX, RC. Writing - review and editing: RC, SX, MK, SH, BT. Visualization: SX. Supervision: RC, MK. Project administrations: RC, SH, MK. Funding acquisition: RC, SH and MK.

DECLARATION OF INTERESTS

The authors declare no competing interests.

REFERENCES

1. Potter, M. (1975). Meaning in visual search. Science *187*, 965–966.

2. Thorpe, S., Fize, D., and Marlot, C. (1996). Speed of processing in the human visual system. Nature *381*, 520–522.

3. de Haan, M., and Nelson, C.A. (1999). Brain activity differentiates face and object processing in 6-month-old infants. Developmental Psychology *35*, 1113–1121.

4. Maurer, D., Lewis, T.L., Brent, H.P., and Levin, A.V. (1999). Rapid improvement in the acuity of infants after visual input. Science *286*, 108–110.

5. Mareschal, D., and Quinn, P.C. (2001). Categorization in infancy. Trends in Cognitive Sciences *5*, 443–450.

6. Pascalis, O., Haan, M. de, and Nelson, C.A. (2002). Is face processing species-specific during the first year of life? Science *296*, 1321–1323.

7. Aslin, R.N. (2007). What's in a look? Developmental Science *10*, 48–53.

8. Aslin, R.N., and Fiser, J. (2005). Methodological challenges for understanding cognitive development in infants. Trends in Cognitive Sciences *9*, 92–98.

9. Cichy, R.M., Pantazis, D., and Oliva, A. (2014). Resolving human object recognition in space and time. Nature Neuroscience *17*, 455–462.

10. Haxby, J.V., Gobbini, M.I., Furey, M.L., Ishai, A., Schouten, J.L., and Pietrini, P. (2001). Distributed and overlapping representations of faces and objects in ventral temporal cortex. Science *293*, 2425–30.

11. Grill-Spector, K., and Malach, R. (2004). The human visual cortex. Annual Review of Neuroscience *27*, 649–677.

12. Yamins, D.L.K., and DiCarlo, J.J. (2016). Using goal-driven deep learning models to understand sensory cortex. Nature Neuroscience *19*, 356–365.

13. Singer, W. (1993). Synchronization of cortical activity and its putative role in information processing and learning. Annual Review of Physiology *55*, 349–374.

14. Fries, P. (2015). Rhythms for cognition: communication through coherence. Neuron *88*, 220–235.

15. Spriet, C., Abassi, E., Hochmann, J.-R., and Papeo, L. (2022). Visual object categorization in infancy. Proceedings of the National Academy of Sciences of the United States of America *119*.

16. Rakison, D.H., and Poulin-Dubois, D. (2001). Developmental origin of the animate–inanimate distinction. Psychological Bulletin *127*, 209–228.

17. Stahl, A.E., and Feigenson, L. (2015). Observing the unexpected enhances infants' learning and exploration. Science *348*, 91–94.

18. Martin, A., Wiggs, C.L., Ungerleider, L.G., and Haxby, J.V. (1996). Neural correlates of category-
specific knowledge. Nature *379*, 649–52.

19. Deen, B., Richardson, H., Dilks, D.D., Takahashi, A., Keil, B., Wald, L.L., Kanwisher, N., and Saxe,
R. (2017). Organization of high-level visual cortex in human infants. Nature Communications *8*,
13995.

20. Kosakowski, H., Cohen, M., Takahashi, A., Keil, B., Kanwisher, N., and Saxe, R. (2021). Selective
responses to faces, scenes, and bodies in the ventral visual pathway of infants. Current Biology *32*,
265–274.

21. Arcaro, M.J., and Livingstone, M.S. (2017). A hierarchical, retinotopic proto-organization of the
primate visual system at birth. eLife *6*, e26196.

22. Arcaro, M.J., Schade, P.F., and Livingstone, M.S. (2019). Body map proto-organization in newborn
macaques. Proceedings of the National Academy of Sciences of the United States of America *116*,
24861–24871.

23. Livingstone, M.S., Vincent, J.L., Arcaro, M.J., Srihasam, K., Schade, P.F., and Savage, T. (2017).
Development of the macaque face-patch system. Nature Communications *8*, 14897.

24. Ellis, C.T., Skalaban, L.J., Yates, T.S., Bejjanki, V.R., Córdova, N.I., and Turk-Browne, N.B. (2020).
Re-imagining fMRI for awake behaving infants. Nature Communications *11*, 4523.

25. Yates, T.S., Ellis, C.T., and Turk-Browne, N.B. (2021). The promise of awake behaving infant fMRI
as a deep measure of cognition. Current Opinion in Behavioral Sciences *40*, 5–11.

26. Hoehl, S. (2016). The development of category specificity in infancy – What can we learn from
electrophysiology? Neuropsychologia *83*, 114–122.

27. Conte, S., Richards, J.E., Guy, M.W., Xie, W., and Roberts, J.E. (2020). Face-sensitive brain
responses in the first year of life. Neuroimage *211*, 116602.

28. Kriegeskorte, N. (2008). Representational similarity analysis – connecting the branches of systems
neuroscience. Frontiers in Systems Neuroscience *2*, 4.

29. King, J.-R., and Dehaene, S. (2014). Characterizing the dynamics of mental representations: the
temporal generalization method. Trends in Cognitive Sciences *18*, 203–210.

30. Deoni, S.C.L., Mercure, E., Blasi, A., Gasston, D., Thomson, A., Johnson, M., Williams, S.C.R., and
Murphy, D.G.M. (2011). Mapping infant brain myelination with magnetic resonance imaging.
Journal of Neuroscience *31*, 784–791.

31. Huttenlocher, P.R., and Dabholkar, A.S. (1997). Regional differences in synaptogenesis in human
cerebral cortex. Journal of Comparative Neurology *387*, 167–178.

32. Johnson, M.H. (2001). Functional brain development in humans. Nature Reviews Neuroscience *2*,
475–483.

33. Kuhl, P.K., Williams, K.A., Lacerda, F., Stevens, K.N., and Lindblom, B. (1992). Linguistic
experience alters phonetic perception in infants by 6 months of age. Science *255*, 606–608.

34. Spelke, E.S., and Kinzler, K.D. (2007). Core knowledge. Developmental Science *10*, 89–96.

35. Cichy, R.M., and Oliva, A. (2020). A M/EEG-fMRI fusion primer: resolving human brain responses
in space and time. Neuron *107*, 772–781.

36. Jones, J.P., and Palmer, L.A. (1987). An evaluation of the two-dimensional Gabor filter model of
simple receptive fields in cat striate cortex. Journal of Neurophysiology *58*, 1233–1258.

37. Simonyan, K., and Zisserman, A. (2015). Very deep convolutional networks for large-scale image
recognition. arXiv Preprint, arXiv:1409.1556.

38. Kietzmann, T.C., McClure, P., and Kriegeskorte, N. (2019). Deep neural networks in computational
neuroscience. In Oxford Research Encyclopedia of Neuroscience. Oxford University Press.
10.1093/acrefore/9780190264086.013.46.

39. de Heering, A., and Rossion, B. (2015). Rapid categorization of natural face images in the infant right
hemisphere. eLife *4*, e06564.

40. Hassabis, D., Kumaran, D., Summerfield, C., and Botvinick, M. (2017). Neuroscience-inspired
artificial intelligence. Neuron *95*, 245–258.

41. Berger, H. (1929). Über das Elektrenkephalogramm des Menschen. Archiv fuer Psychiatrie und
Nervenkrankheiten *87*, 527–570.

42. Buzsáki, G., and Draguhn, A. (2004). Neuronal oscillations in cortical networks. Science *304*, 1926–
1929.

43. Uhlhaas, P.J., Roux, F., Rodriguez, E., Rotarska-Jagiela, A., and Singer, W. (2010). Neural
synchrony and the development of cortical networks. Trends in Cognitive Sciences *14*, 72–80.

44. Marshall, P.J., Bar-Haim, Y., and Fox, N.A. (2002). Development of the EEG from 5 months to 4
years of age. Clinical Neurophysiology *113*, 1199–1208.

45. Ward, L.M. (2003). Synchronous neural oscillations and cognitive processes. Trends in Cognitive
Sciences *7*, 553–559.

46. Buzsáki, G. (2005). Theta rhythm of navigation: link between path integration and landmark
navigation, episodic and semantic memory. Hippocampus *15*, 827–840.

47. Jensen, O., and Mazaheri, A. (2010). Shaping functional architecture by oscillatory alpha activity:
gating by inhibition. Frontiers in Human Neuroscience *4*.

48. Klimesch, W. (2012). Alpha-band oscillations, attention, and controlled access to stored information.
Trends in Cognitive Sciences *16*, 606–617.

49. Oostenveld, R., Fries, P., Maris, E., and Schoffelen, J.-M. (2010). FieldTrip: open source software for
advanced analysis of MEG, EEG, and invasive electrophysiological data. Computational Intelligence
and Neuroscience *2011*.

50. Tadel, F., Baillet, S., Mosher, J.C., Pantazis, D., and Leahy, R.M. (2011). Brainstorm: a user-friendly
application for MEG/EEG analysis. Computational Intelligence and Neuroscience *2011*, 1–13.

51. Carlson, T., Tovar, D.A., Alink, A., and Kriegeskorte, N. (2013). Representational dynamics of
object vision: The first 1000 ms. Journal of Vision *13*, 1–19.

52. Chang, C., and Lin, C. (2001). LIBSVM: a library for support vector machines. ACM Transaction on
Intelligent Systems and Technology *2*, 1–27. 10.1145/1961189.1961199.

53. Kriegeskorte, N., Goebel, R., and Bandettini, P. (2006). Information-based functional brain mapping.
Proceedings of the National Academy of Sciences of the United States of America *103*, 3863–3868.

54. Kaiser, D., Oosterhof, N.N., and Peelen, M.V. (2016). The neural dynamics of attentional selection in
natural scenes. Journal of Neuroscience *36*, 10522–10528.

55. Kriegeskorte, N., Mur, M., Ruff, D.A., Kiani, R., Bodurka, J., Esteky, H., Tanaka, K., and Bandettini,
P.A. (2008). Matching categorical object representations in inferior temporal cortex of man and
monkey. Neuron *60*, 1126–1141.

56. Kriegeskorte, N., and Kievit, R.A. (2013). Representational geometry: integrating cognition,
computation, and the brain. Trends in Cognitive Sciences *17*, 401–412.

57. Guggenmos, M., Sterzer, P., and Cichy, R.M. (2018). Multivariate pattern analysis for MEG: a
comparison of dissimilarity measures. Neuroimage *173*, 434–447.

58. Kay, K.N., Naselaris, T., Prenger, R.J., and Gallant, J.L. (2008). Identifying natural images from
human brain activity. Nature *452*, 352–5.

59. Simonyan, K., Vedaldi, A., and Zisserman, A. (2013). Deep inside convolutional networks:
visualising image classification models and saliency maps. arXiv preprint, arXiv:1312.6034.

60. Bau, D., Zhou, B., Khosla, A., Oliva, A., and Torralba, A. (2017). Network dissection: quantifying
interpretability of deep visual representations. arXiv preprint, arXiv:1704.05796.

61. Güçlü, U., and Gerven, M.A.J. van (2015). Deep neural networks reveal a gradient in the complexity
of neural representations across the ventral stream. Journal of Neuroscience *35*, 10005–10014.

62. Cichy, R.M., Khosla, A., Pantazis, D., Torralba, A., and Oliva, A. (2016). Comparison of deep neural
networks to spatio-temporal cortical dynamics of human visual object recognition reveals hierarchical
correspondence. Scientific Reports *6*, 27755.

63. Eickenberg, M., Gramfort, A., Varoquaux, G., and Thirion, B. (2017). Seeing it all: convolutional
network layers map the function of the human visual system. Neuroimage *152*, 184–194.

64. Khaligh-Razavi, S.-M., and Kriegeskorte, N. (2014). Deep supervised, but not unsupervised, models
may explain IT cortical representation. PLoS Computational Biology *10*, e1003915.

65. Yamins, D.L.K., Hong, H., Cadieu, C.F., Solomon, E.A., Seibert, D., and DiCarlo, J.J. (2014).
Performance-optimized hierarchical models predict neural responses in higher visual cortex.
Proceedings of the National Academy of Sciences of the United States of America *111*, 8619–8624.

66. Schrimpf, M., Kubilius, J., Lee, M.J., Ratan Murty, N.A., Ajemian, R., and DiCarlo, J.J. (2020).
Integrative benchmarking to advance neurally mechanistic models of human intelligence. Neuron
108, 413–423.

67. Vedaldi, A., and Lenc, K. (2015). MatConvNet - convolutional neural networks for MATLAB. In
Proceedings of the 23rd ACM International Conference on Multimedia, 689–692.
10.1145/2733373.2807412.

68. DiCarlo, J.J., Zoccolan, D., and Rust, N.C. (2012). How does the brain solve visual object
recognition? Neuron *73*, 415–434.

69. Nili, H., Wingfield, C., Walther, A., Su, L., Marslen-Wilson, W., and Kriegeskorte, N. (2014). A
toolbox for representational similarity analysis. PLoS Computational Biology *10*, e1003553.

70. Nichols, T.E., and Holmes, A.P. (2002). Nonparametric permutation tests for functional
neuroimaging: a primer with examples. Human Brain Mapping *15*, 1–25.

71. Maris, E., and Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-data.
Journal of Neuroscience Methods *164*, 177–190.

STAR METHODS

RESOURCE AVAILABILITY

Lead contact

Further information and requests for the resources should be directed to and will be fulfilled by the lead contact, Radoslaw M. Cichy (rmcichy@zedat.fu-berlin.de).

Materials availability

This study did not generate new unique reagents.

Data and code availability

Full data will be available upon publication here: [*OSF link to be inserted upon acceptance*].

Example data for review is available here:
https://osf.io/ruxfg/?view_only=919a62ecab944e99a80b9a467951d2e1.

Custom code is available here: https://github.com/anonymturtle/VCR_infant.

EXPERIMENTAL MODEL AND SUBJECT DETAILS

Two independent pools of participants took part in this study: 6–8 months old infants and young adults. The infant sample was assessed at the Max Planck Institute for Human Cognitive and Brain Sciences in Leipzig, Germany. It comprised 48 participants, of which 8 were excluded due to insufficient data, yielding a final sample analyzed of 40 infant participants (gender: 19 female, age: mean ± SD: 214.9 ± 14.76 days). The adult sample was assessed at the Freie Universität Berlin, Germany. It comprised 20 participants of which none was excluded (gender: 11 female, age: mean ± SD: 26.1 ± 3.81 years). Caregivers of all infants and all adult participants gave written informed consent. The study was conducted according to the Declaration of Helsinki and the infant and adult protocols were approved by the respective local ethic committees.

METHOD DETAILS

Stimuli

The stimulus set consisted of 32 object images in each of the four categories included: houses, toys, faces, and bodies. This yielded a total set of $4 \times 32 = 128$ object images. All object images were cut-out from color photographs (**Supplementary Fig. 1**). We analyzed the data at the level of category.

Experimental procedure in the infant sample

In the infant experiment, participants were presented with 272 trials divided into four blocks. Each block had the same basic structure. At the beginning of each block four stimuli (one stimulus per object category) were separately presented three times in randomized order. Thereafter participants were presented with a random sequence of images comprising the same four stimuli seven more times, intermixed with 28 other images (seven images per category) presented only once. This experimental design was chosen because it allows assessing the effect of object image repetition of infant brain responses, but this question is orthogonal to the ones pursued here and will be reported separately.

Each trial consisted of a fixation dot presented for a variable duration of 700–900ms, followed by a stimulus presented for 2,000ms at the center of the screen (**Supplementary Fig. 2a**). To

capture the attention of the infants and direct their gaze to the screen we implemented two
measures. First, we presented a yellow duck image and duck sound for 1,000ms at the beginning
of each block and thereafter every 10 trials. Second, each stimulus was presented together with
one of ten arbitrary sounds that were assigned randomly at each trial.

During the assessment, infants sat on their care giver's lap at a viewing distance of about 80 cm
from a 17-in. CRT screen. The object images were presented at the center of the screen,
subtending a visual angle of approximately 5.0°. To monitor infants' gaze, we recorded videos of
infants' faces throughout the experiment.

Experimental procedure in the adult sample

We adapted the experimental design for the adult sample. In short, all images were shown
equally often, with higher number of repetitions, at shorter presentation times and higher
presentation rates that in the infant study (**Supplementary Fig. 2b**).

The first 3 participants were presented with 1,280 trials divided into 5 runs. In each run each
object image was presented twice. The other 17 participants were presented with 3,840 trials
divided into 10 runs. In each run each object image was presented three times. In each run,
images were presented in random order, and runs were separated by breaks that were self-paced
by the participants.

Each trial consisted of the presentation of a fixation cross with a variable duration of 600–800ms,
followed by a stimulus presentation for 500ms. Stimuli were presented at the center of the screen
at a visual angle of approximately 7.0°.

Participants were instructed to keep fixation on the center of the screen throughout the
experiment. To ensure that participants attended to the stimuli and to avoid contamination of the
relevant recording times with blink artefacts, participants were instructed to press a button and
blink their eyes in response to a paper clip image that was shown randomly every 4 to 6 trials
(average 5 trials). Paper clip trials were excluded from all further analysis.

EEG acquisition and preprocessing

<u>Infant sample</u>

EEG data for the infant sample were recorded in a shielded room using 30 Ag/AgCl ring
electrodes and a TMSi 32-channel REFA amplifier at a sampling rate of 500 Hz. Electrodes were
placed according to the standard 10-20 system. Electrodes V+Fp2 and V– recorded the vertical
electrooculogram (VEOG), and electrodes H-F9 and HF+10 recorded the horizontal
electrooculogram (HEOG), Cz served as the online reference. We conducted preprocessing using
the Fieldtrip toolbox[49]. The continuous EEG data was segmented for each trial into epochs. For
subsequent time-resolved multivariate analysis we extracted the epoch from –200ms to
+1,000ms with respect to image onset. For analysis that was additionally resolved in frequency
we used longer epochs to allow better estimation at lower frequencies from –500ms to +1,000ms.

We removed all trials during which participants did not gaze at the screen for 1,000ms after
stimulus onset as assessed by visual inspection of the video recordings. In this reduced trial set
(mean ± SD: 139.6 ± 47.76 trials) we removed noisy channels (mean ± SD: 1.25 ± 1.32) and
replaced them by interpolated data from adjacent electrodes. We further conducted independent
component analysis (ICA) and removed components related to eye-movement and muscle
artifacts as identified by visual inspection.

 Adult sample

EEG data for the adult sample were recorded using an EASYCAP 64-channel system and a
Brainvision actiCHamp amplifier at a sampling rate of 1,000Hz. Data were filtered online
between 0.3 and 100 Hz. Electrodes were placed according to the standard 10-10 system.
Electrode Fz served as the online reference. We conducted preprocessing using the Brainstorm 3
toolbox[50]. Up to two noisy channels were removed for each participant as identified by visual
inspection. We conducted ICA to identify and remove eye-movement and muscle artifact
components by visual inspection of independent components. The continuous EEG data were
then segmented for each trial into epochs from –200ms to +1,000ms (for time-resolved analysis)
and from –500ms to +1,000ms (for time- and frequency resolved analysis).

Time-frequency decomposition

We decomposed the EEG time series into frequency-specific components by convolving the data
with complex Morlet wavelets separately for each trial and sensor. The wavelets had a constant
length of 2,600ms and were logarithmically spaced in 30 frequency bins between 2Hz and 30Hz.
We obtained the absolute power values for each time point and frequency bin by taking the
square root of the resulting time-frequency coefficients. We normalized these power values to
reflect relative changes (expressed in dB) with respect to the pre-stimulus baseline (–300ms to –
100ms with respect to stimulus onset). We downsampled the time-frequency representations to a
temporal resolution of 50 Hz (by averaging data in 20ms-bins) to increase the signal-to-noise
ratio of subsequent analyses. This yielded for each trial a power value for each time point and
frequency bin.

Multivariate classification of visual category from EEG data

To characterize the temporal dynamics with which visual category representations emerge in
infant and adult brains we conducted multivariate EEG classification using linear support vector
machines (SVMs). We analyzed the infant and the adult data set separately and equivalently.

We conducted two common variants of multivariate EEG classification: time-resolved EEG
analysis[9,51] and time-generalization analysis[29]. We conducted the analysis separately on the adult
and infant sample, and separately for each participant. All analyses employed binary c-support
vector classification (C-SVC) with a linear kernel as implemented in the LIBSVM toolbox[52]. The
details of the time-resolved and the time-generalization analysis are as follows.

Time-resolved classification

We used time-resolved multivariate pattern analysis on EEG data (**Fig. 1b**) to determine the time
course with which visual category representations emerge in infant and adult brains. For each
time point of the EEG epoch (from –200ms to +1,000ms), we extracted trial-specific EEG
channel activations (i.e., 25 in infants and 63 in adults) and arranged them into pattern vectors
for each of the four category conditions (i.e., face, house, body, and toy) of the stimulus set. To
increase the signal-to-noise ratio (SNR), we randomly assigned raw trials into four bins of
approximately equal size each and averaged them into four pseudo-trials. We used a leave-one-
pseudo-trial-out cross validated classification approach. We trained the SVM classifier to
pairwise decode any two conditions using three of the four pseudo-trials for training. We used
the fourth left-out pseudo-trial for testing, yielding classification accuracy (chance level 50%) as
a result. The procedure was repeated 100 times, each time with a new random assignment of
trials to pseudo-trials. The resulting decoding accuracy was averaged across repetitions and

assigned to a decoding accuracy matrix of size 4×4, with rows and columns indexed by the
conditions classified. The matrix is symmetric across the diagonal, with the diagonal undefined.
This procedure yielded one decoding matrix for every time point.

In addition to classifying visual category from broadband responses (i.e., single trial raw
unfiltered waveforms), we classified object categories from oscillatory responses. This analysis
followed the same rationale as the classification analysis described above, with the only
difference that classification was conducted on power value patterns instead of raw activation
value patterns. The analysis was conducted separately for each frequency bin separately. This
resulted in a decoding accuracy matrix of size 4×4 as defined above for every time point and
every frequency bin.

Time generalization analysis

We used time-generalization classification analysis[29] to determine how visual representations
emerging at different time points during the dynamics of visual perception relate to each other.
For time and memory efficiency, we downsampled the EEG data to a sampling rate of 50 Hz by
averaging the raw EEG data in 20ms bins. The procedure was equivalent to the time-resolved
classification analysis with the only difference that classifiers trained on data from a particular
time point were not only tested on left out data from the same time point, but iteratively on data
from the same and all other time points. The idea is that successful classifier generalization
across time points indicates similarity of visual representations over time. This analysis yielded
thus a size 4×4 decoding accuracy matrix indexed in rows and columns by the conditions
compared for all time point combinations from –200 to +1,000ms. We averaged the entries of the
decoding accuracy matrix at each time point, yielding a temporal generalization matrix indexed
in rows and columns by training and testing time.

Sensor-space searchlight analysis

We performed a sensor-space searchlight analysis[53,54] to localize in EEG channel space which
channels contributed to the classification of category. For each EEG channel we defined a
neighborhood as a sphere of the 10 (for adults) or 5 (for infants) closest EEG channels. For each
EEG channel we then performed time-resolved category classification analysis, limiting data
entering the analysis to its neighboring channels. Averaging across all pairwise category
classifications yielded one decoding accuracy for each time point and for each EEG channel. We
further averaged the results in 200ms bins, yielding a single EEG channel searchlight map of
grand average decoding accuracy for each time bin.

Comparing visual representations in infants and adults

We determine whether infants and adults have similar visual category representations using
representational similarity analysis (RSA)[55,56]. The idea is that infants and adults share
representations of category if they treat the same categories as similar or dissimilar. We
determined this in a two-step process.

In a first step, for each age group independently condition-specific multivariate activity patterns
(adults: 63 electrodes; infants: 25 electrodes) were compared for dissimilarity. Dissimilarity was
determined for all pairwise combinations of conditions, and dissimilarity values were aggregated
in so-called representational dissimilarity matrices (RDMs) indexed in rows and columns by the
conditions compared (here: 4×4 RDMs indexed by the 4 object categories). RDMs thus provide
a statistical summary of the similarity and thus representational relations between visual category

representations. The RDMs gained from the infant and adult sensor space separately have the
same definition and dimensionality and are thus directly comparable. Thus, in a second step, the
infant RDM and the adult RDMs are related to each other by determining their similarity.

We applied RSA to two different types of data: evoked responses (i.e., recorded voltage signals)
and oscillatory responses (i.e., spectral power). In both cases we re-used the results of the
classification analysis described above for the definition of RDMs. Classification accuracy can
be interpreted as a dissimilarity measure on the assumption that the more dissimilar activation
patterns are for two conditions, the easier they are to classify[9,57]. We detail the different RSA
procedures below. To reduce visual complexity of the analysis we subsampled the results of the
classification analysis by binning them in 10ms bins.

<u>Relating visual category representations in infants and adults based on raw broadband time</u>
<u>courses</u>

We investigated whether infants and adults share common visual representations based on
broadband responses. As visual representations in adults and infants likely emerge with different
time courses, we related their visual representations in a representational similarity time-
generalization analysis. As RDMs we used time-point specific decoding accuracy matrices (**Fig.**
2a). We first averaged infant RDMs across all participants to increase SNR, resulting in one
average infant RDM per time point. We then correlated (Spearman's R) the average infant RDM
to each adult ($n = 20$) RDM across all time point combinations. This yielded 20 correlation
matrices, indexed in rows and columns by the time points compared (rows: infant time; columns:
adult time), indicating when infants and adults share category representations.

<u>Relating visual category representations in infants and adults based on frequency-specific power</u>
<u>time courses</u>

We investigated whether infants and adults share visual representations in particular frequency
bands. As RDMs we used decoding accuracy matrices from the classification analysis based on
time-frequency resolved power values. As in this analysis we could neither assume similar time
courses, nor similar roles for particular frequencies across infants and adults, we related infant
and adult representations in a time-and-frequency-generalization analysis. To do this, we first
defined a single aggregate infant RDM by averaging decoding accuracy matrices based on the
extent (time and frequency) of the significant cluster in the infant data alone (see **Fig. 4b**). To
increase signal-to-noise we only included RDMs whose average across entries in single
participants was greater than or equal to 50% decoding accuracy. Note that this criterion is
orthogonal to the hypotheses tested and thus does not bias the analysis. We compared
(Spearman's R) this single aggregate infant RDM to time- and frequency- resolved RDMs for
each participant of the adult sample ($n = 20$), separately for each frequency and time point. This
yielded 20 correlation matrices, with rows representing time points and columns representing
frequency bins, indicating when and at which frequency infants and adults share category
representations.

<u>Relating visual representations in infants and adults to computational models</u>

To characterize the format of visual category we related neural representations in infants and
results to different computational models using RSA. We constructed model RDMs from
computational models (**Fig. 3a**) that represent visual information in different formats. We
considered two types of visual computational models: a Gabor wavelet pyramid as a model of

low-level feature representations[36,58], and the VGG-19[37] deep convolutional neural network
(DNN) trained to categorize object images. Deep neural networks process visual information
along a hierarchy of increasing complexity from low to high[59,60] that has been shown to match
the processing hierarchy of the human brain[61–63] and predict human and non-human primate
brain activity better than other model class[12,64–66].

To construct model RDMs we first ran all visual stimuli in the study (i.e., 128 object images)
through the models and extracted their activation values. More specifically, for the Gabor model
we extracted a single set of model responses for Gabor wavelets differing in size, position,
orientation, spatial frequency and phase. For the DNN we used the MatConvNet toolbox[67] to
extract model neuron activation values from the rectified linear units (Relu) for each layer. We z-
transformed activation values across stimuli for each stage/layer separately and averaged the
transformed values across the 32 stimuli belonging to each of the four categories (i.e., face, body,
house and toy), resulting in four category-specific activation values. We formed the patterns into
vectors and computed the dissimilarity (1 – Pearson's R) between all pairwise combinations of
the four category activation vectors, resulting in a 4×4 RDM for each DNN layer of each DNN
separately, and one model RDM for the Gabor feature model.

To construct neural RDMs that capture category representations well we averaged decoding
accuracy matrices from time-resolved category classification (**Fig. 1c,d**) in the 95% confidence
intervals around peak latency in time-resolved category classification. Our rationale was that
peak latency is the time point when categories were linearly best separable and thus their
representations most explicit[68]. To increase signal-to-noise we only included RDMs whose
average across entries in single participants was greater than or equal to 50% decoding accuracy.
Note that this criterion is orthogonal to the hypotheses tested and thus unbiased. This yielded a
single neural RDM for every infant and adult participant. We then related infant and adult neural
RDMs to model RDMs using Spearman's R, yielding a single correlation value for each model
RDM and participant.

To allow assessing the models' predictivity with respect to the noise in the data we calculated an
upper and lower bound for the noise ceiling[69], that is the predictions a perfect model may reach
given the noise in the data. This procedure was conducted separately for the infant and the adult
sample. To estimate the upper bound we correlated (Spearman's R) each participant's neural
RDM with the mean neural RDM across all participants. To estimate the lower bound we
correlated (Spearman's R) each participant's neural RDM with the mean neural RDM excluding
that participant iteratively for all participants. We averaged the results, yielding estimates of the
lower and upper noise ceiling for infants and adults.

QUANTIFICATION AND STATISTICAL ANALYSIS

We used non-parametric statistical inference for random-effects inference to avoid assumptions
about the distribution of the data[70,71]. We used permutation tests for cluster-size inference, and
bootstrap tests for confidence intervals on maxima, cluster onset/offset, and peak-to-peak latency
differences. The sample size (n) for infants was 40 and for adults 20. Tests were either two- or
right-tailed and are indicated for each result separately.

 Permutation tests

We tested the statistic of interest (i.e., mean decoding accuracy or correlation coefficient in RSA
across participants) using sign permutation tests. The null hypothesis was that the statistic of
interest was equal to chance (i.e., 50% decoding accuracy, a Spearman's R of 0). Under the null
hypothesis, we could permute the category labels of the EEG data, which effectively corresponds
to a sign permutation test that randomly multiplies participant-specific data with $+1$ or $–1$. For
each permutation sample, we recomputed the statistic of interest. Repeating this permutation
procedure 10,000 times, we obtained an empirical distribution of the data. We converted the
original statistic (i.e., correlation coefficient, the decoding time courses, time-time matrices of
correlation coefficients or decoding accuracies, and time-frequency decoding matrices) into P-
values (correlation coefficients), 1-dimensional (time courses), or 2-dimensional (time-
generalization or time-frequency) P-value matrices.

We controlled the family-wise error rate using cluster-size inference. We first thresholded P-
value time courses or maps at $P < .005$ (cluster-definition threshold) to define supra-threshold
clusters by contiguity. These supra-threshold clusters were reported significant only if the size
exceeded a threshold, estimated as follows: the previously computed permutation samples were
also converted to P-value time courses/matrices and also thresholded to define resampled
versions of supra-threshold clusters. These clusters were used to construct an empirical
distribution of maximum cluster size and estimate a threshold of 5% of the right tail of this
distribution (i.e., the corrected P-values is $P < .05$).

Bootstrap tests

We calculated 95% confidence intervals for the onsets of the first significant cluster and the peak
latency of the observed effects. To achieve this, we created 1,000 bootstrapped samples by
sampling the participants with replacement. For each bootstrap sample, we determined the peak
latency as well as onsets of the first significant cluster and the offset of the last significant
cluster. This resulted in empirical distributions of peak, onset and offset latencies on which we
determined 95% confidence intervals.

To calculate confidence intervals on mean peak-to-peak latency differences, we created 1,000
bootstrapped samples by sampling the participant-specific latencies with replacement. This
yielded an empirical distribution of mean peak-to-peak latencies. If the 95% confidence interval
did not include 0, we rejected the null hypothesis of no peak-to-peak latency differences. The
threshold $P < .05$ was corrected for multiple comparisons whenever appropriate using FDR
correction.