Omnipose: a high-precision morphology-independent solution for bacterial cell segmentation

Kevin J. Cutler[1], Carsen Stringer[2], Paul A. Wiggins[1,3,*] and Joseph D. Mougous[4,5,*]

[1]Department of Physics, University of Washington, Seattle, WA 98195, USA

[2]HHMI Janelia Research Campus, Ashburn, VA, USA

[3]Department of Bioengineering, University of Washington, Seattle, WA 98195, USA

[4]Department of Microbiology, University of Washington, Seattle, WA 98109, USA

[5]Howard Hughes Medical Institute, University of Washington, Seattle, WA 98195, USA

* To whom correspondence should be addressed:

Email – pwiggins@uw.edu, mougous@uw.edu

Abstract

Advances in microscopy hold great promise for allowing quantitative and precise

readouts of morphological and molecular phenomena at the single cell level in bacteria.

However, the potential of this approach is ultimately limited by the availability of

methods to perform unbiased cell segmentation, defined as the ability to faithfully

identify cells independent of their morphology or optical characteristics. In this study, we

present a new algorithm, Omnipose, which accurately segments samples that present

significant challenges to current algorithms, including mixed bacterial cultures,

antibiotic-treated cells, and cells of extended or branched morphology. We show that

Omnipose achieves generality and performance beyond leading algorithms and its

predecessor, Cellpose, by virtue of unique neural network outputs such as the gradient of

the distance field. Finally, we demonstrate the utility of Omnipose in the context of

characterizing extreme morphological phenotypes that arise during interbacterial

antagonism. Our results distinguish Omnipose as a uniquely powerful tool for answering

diverse questions in bacterial cell biology.

Introduction

Introduction

Although light microscopy is a valuable tool for characterizing cellular and sub-

cellular structures and dynamics, quantitative analysis of microscopic data remains a

persistent challenge (1). This is especially pertinent to the study of bacteria, many of

which have dimensions in the range of optical wavelengths. Thus, their cell body is

composed of a small number of pixels (*e.g.,* ~100-300 px^2 for *E. coli* at 100x

magnification). At this scale, accurate subcellular localization requires defining the cell

boundary with single-pixel precision. The process of defining cell boundaries within

micrographs is termed cell segmentation and this is a critical first step in current image

analysis pipelines (2, 3).

In addition to their small size, bacteria adopt a wide range of morphologies.

Although many commonly studied bacteria are well-approximated by idealized rods or

spheres, there is growing interest in bacteria with more elaborate shapes (4). Some

examples include Streptomycetales, which form long filamentous and branched hyphal

structures (5), and Caulobacterales, which generate extended appendages distinct from

their cytoplasm (6). Furthermore, microfluidic devices are allowing researchers to capture

the responses of bacteria to assorted treatments such as antibiotics, which often result in

highly irregular morphologies (7). Whether native or induced, atypical cell morphologies

present a distinct problem at the cell segmentation phase of image analysis (8, 9). This is

compounded when such cells are present with those adopting other morphologies, as is

the case in many natural samples of interest (10). To date, there are no solutions for

segmenting bacterial cells of assorted shape and size in a generalizable manner (1).

Cell segmentation is a complex problem that extends beyond microbiological

research, thus many solutions are currently available in image analysis programs (8, 9,

11-27). Most of these solutions use traditional image processing techniques such as the

application of an intensity threshold to segment isolated cells; however, this approach

does not perform well for cells in close contact and it requires extensive parameter-tuning

in order to optimize for a given cell type. SuperSegger was developed to address these

issues specifically in bacterial phase contrast images (13). This program utilizes both

traditional image filtering techniques and a shallow neural network to correct for errors

that thresholding and watershed segmentation tend to produce.

Deep neural networks (DNNs) are now widely recognized as superior tools for

cell segmentation (28). Unlike traditional image processing, machine-learning approaches

such as DNNs require training on a ground-truth dataset of cells and corresponding

labels. Trained DNNs are thus limited in applicability to images that are representative of

those in the training dataset. Early DNN approaches were based on the Mask R-CNN

architecture (24), whereas more recent algorithms such as StarDist, Cellpose, and MiSiC

are based on the U-Net architecture (12, 15, 26). Pachitariu and colleagues showed that

Cellpose outperforms Mask R-CNN and StarDist on a variety of cell types and cell-like

objects, distinguishing it as a general solution for cell segmentation (12). Notably, the

representation of bacteria in their study was limited. MiSiC was developed as a general

DNN-based solution for bacterial segmentation; however, the authors of MiSiC did not

provide comparisons to other DNN algorithms (15). Here, we evaluated the performance

of state-of-the-art cell segmentation algorithms on a diverse collection of bacterial cells.

Our findings motivated the design of a new algorithm, Omnipose, that significantly

outperforms all previous cell segmentation algorithms across a wide range of bacterial

cell sizes, morphologies, and optical characteristics. We have made Omnipose and all

associated data immediately available to researchers, and we anticipate that our model –

without retraining – can be applied to diverse bacteriological systems. Furthermore,

following the incorporation of additional ground truth data, Omnipose could serve as a

platform for segmenting various eukaryotic cells and extended, anisotropic objects more

broadly.

Results

Evaluation of bacterial cell segmentation algorithms

Numerous image segmentation algorithms have been developed, and the

performance of many of these on bacterial cells is documented (1). These broadly fall

into three categories: (*i*) traditional image processing approaches (*e.g.,* thresholding,

watershed), (*ii*) traditional/machine learning hybrid approaches, and (*iii*) deep neural

network (DNN) approaches. Given the goal of developing software with the capacity to

recognize bacteria universally, we sought to identify strongly performing algorithms for

further development. An unbiased, quantitative comparison of cell segmentation

algorithms on bacterial cells has not been performed; thus, we selected one or more

representatives from each category for our analysis: Morphometrics (23) (*i*), SuperSegger

(13) (*ii*), Mask R-CNN (27), StarDist (26), MiSiC (15), and Cellpose (12) (*iii*). For a

detailed review of these choices, see Methods.

For training and benchmarking these algorithms, we acquired micrographs of

assorted bacterial species representing diverse morphologies and optical characteristics.

Many studies of bacteria involve mutations or treatments that cause extreme

morphologies. To capture this additional diversity, we included wild-type and mutant

bacteria grown in the presence of two beta-lactam antibiotics, cephalexin and aztreonam,

and A22, which targets MreB (29). Finally, based on our interest in microbial

communities, we acquired images of mixtures of bacteria which display distinct

morphologies and optical characteristics. In total, we collected 4833 images constituting

approximately 700,900 individual cells deriving from 14 species (Table S1). Next, we

developed a streamlined approach for manual cell annotation and applied it to these

images (see Methods), yielding 46,000 representative annotated cells that serve as our

ground-truth dataset. We arbitrarily split this data into a 27,000-cell training set and a

19,000-cell benchmarking set. Relevant cellular metrics did not differ substantially

between the groups, confirming that the benchmarking set faithfully represents the

training set (Fig. S1).

To facilitate direct comparison of the algorithms, we first optimized their

performance against our data. For the DNN approaches, each algorithm was trained on

our dataset using developer-recommended parameters. Morphometrics and SuperSegger

cannot be automatically optimized using ground-truth data; therefore, we manually

identified settings that optimized the performance of these algorithms against our dataset

(see Methods). As a quantitative measure for algorithm performance, we compared their

average Jaccard Index (JI) as a function of intersection over union (IoU) threshold – a

well-documented approach for evaluating image segmentation (Fig. 1A) (30, 31). IoU

values lie between zero and one, with values greater than 0.8 marking the point at which

masks become indistinguishable from ground truth by the expert human eye (Fig. S2)

(30). This analysis showed that DNN-based approaches significantly outperform other

algorithms. However, within the DNN group, substantial differences in performance were

observed; Cellpose and StarDist outperform Mask R-CNN and MiSiC at high IoU

thresholds. The performance of all algorithms varied greatly across the images in our

ground-truth dataset, with much of this variability delineated by cell type and

morphology categories (Fig. 1B-G). Whereas all other algorithms exhibited visible

segmentation errors in two of the three cell categories we defined, errors by Cellpose –

the best overall performing algorithm at high IoU thresholds – were only apparent in

elongated cells (Fig. 1H-J).

Motivation for a new DNN-based segmentation algorithm

Our comparison revealed that Cellpose offers superior performance relative to the

other segmentation algorithms we analyzed, and for this reason, we selected this

algorithm for further development. Notably, even at the high performance levels of

Cellpose, only 83% of predictions on our benchmarking dataset are above 0.8 IoU. This

limits the feasibility of highly quantitative studies such as those involving subcellular

protein localization or cell–cell interactions.

Cellpose utilizes a neural network that is trained on ground-truth examples to

transform an input image into several intermediate outputs, including a scalar probability

field for identifying cell pixels (Fig. S3A, panels *i-iii*) (12). Cellpose is unique among

DNN algorithms by the addition of a vector field output, which is defined by the

normalized gradient of a heat distribution from the median cell pixel coordinate (Fig.

S3A, panels *iv,v*). This vector field directs pixels toward a global cell center via Euler

integration, allowing cells to be segmented based on the points at which pixels coalesce

(Fig. S3B). In contrast to other algorithms, this approach for reconstructing cells is size-

and morphology-independent, insofar as the cell center can be correctly defined.

To further interrogate the accuracy of Cellpose on our dataset, we evaluated its

performance as a function of cell size. We compared cell area against the number of

segmentation errors, calculated as the number of redundant or missing masks

corresponding to each ground-truth cell mask. This revealed a strong correlation between

cell size and segmentation errors, with the top quartile of cells accounting for 83% of all

errors (Fig. 2A). To understand the source of these errors, we inspected the flow field

output of many poorly segmented cells across a variety of species and growth conditions.

This showed that elongated cells, an important morphology often seen in both wild-type

and mutant bacterial populations, are particularly susceptible to over-segmentation (Fig.

2B). We attribute this to the multiple sinks apparent in the corresponding flow fields. In

the Cellpose mask reconstruction algorithm, pixels belonging to these cells are guided

into multiple centers per cell, fragmenting the cell into many separate masks.

We hypothesized that the observed defect in Cellpose flow field output is a

consequence of two distinct flow field types arising from our training dataset: those

where the median pixel coordinate, or 'center', lies within the cell (97.8%) and those

where it lies outside the cell (2.2%). In the latter, Cellpose projects the center point to the

nearest boundary pixel, ultimately leading to points of negative divergence on the cell

periphery that are chaotically distributed (Fig. 2C-E). On the contrary, non-projected

centers maintain a uniform field magnitude along the entire boundary and adhere to the

global symmetries of the cell (Fig S4A,D). A similar issue is also encountered in cells

with centers that are not projected but lie close to the boundary (Fig. S4B-D). Cells with a

center point closer than 0.3 times the mean cell diameter (a factor of 0.2 off-center) to the

boundary account for an additional 8.5% of our data. Neural networks can be exquisitely

sensitive to the outliers in their training data (32); therefore, we suspect that this small

fraction of corrupt flow fields has significantly impacted the performance of Cellpose.

Development of a new DNN-based segmentation algorithm

160   As there exists no straightforward means of defining a cell center for irregular

objects, we sought to develop a segmentation algorithm that operates independently of

cell center identification. We built our new algorithm, which we named Omnipose,

around the scalar potential known as the distance field (or distance transform), which

describes the distance at any point $\vec{x}$ in a bounded region Ω to the closest point on the

boundary $\partial\Omega$. Notably, this widely utilized construct is one of the intermediate outputs of

StarDist (32). Whereas in StarDist it is used to seed and assemble star-convex polygons,

its use in Omnipose is to define a new flow field within the Cellpose framework. The use

of a distance field has several advantages. First, the distance field is defined by the

eikonal equation $\left|\vec{\nabla}\Phi(\vec{x})\right| = 1$, and so its gradient has unit magnitude throughout the

bounded region for which it is calculated. This grants it faster convergence and better

numerical stability when compared to alternative solutions producing similar fields (*e.g.,*

screened Poisson; see Methods) (Figure S5A). Second, the distance field is independent

of morphology and topology, meaning that it is applicable to all cells. Lastly, the

resulting flow field points uniformly from cell boundaries toward the local cell center,

coinciding with the medial axis, or skeleton, that is defined by the stationary points of the

distance field (Figure S5B). This critical feature allows pixels to remain spatially

clustered after Euler integration, solving the problem of over-segmentation seen in

Cellpose.

One challenge to using the distance field as the basis to our approach is that

traditional distance field algorithms like FMM (Fast Marching Method) are sensitive to

boundary pixilation (33), causing artifacts in the flow field that extend deep into the cell.

These artifacts are sensitive to pixel-scale changes at the cell perimeter, which we

reasoned would interfere with the training process. To solve this, we developed an

alternative approach based on FIM (Fast Iterative Method) that produces smooth distance

fields for arbitrary cell shapes and sizes (Fig. 3A, and see Methods) (34). The

corresponding flow field is relatively insensitive to boundary features at points removed

from the cell boundary, a critical property for robust and generalized prediction by the

Cellpose network.

The use of the distance field additionally required a unique solution for mask

reconstruction. Whereas the pixels in a center-seeking field converge on a point, standard

Euler integration under our distance-derived field tends to cluster pixels into multiple thin

fragments along the skeleton, causing over-segmentation (Fig. 3B). We solved this with a

suppression factor of $(t + 1)^{-1}$ in each time step of the Euler integration. This reduces

the movement of each pixel after the first step $t = 0$, facilitating initial cell separation

while preventing pixels from clustering into a fragmented skeleton formation. The wider

distribution resulting from our suppression factor allows pixels to remain connected,

thereby generating a single mask for each cell in conjunction with a standard automated

pixel clustering algorithm (*e.g.,* DBSCAN) (35).

Omnipose demonstrates unprecedented segmentation accuracy of bacterial cells

With solutions to the major challenges of cell center-independent segmentation

incorporated into Omnipose, we proceeded to benchmark its performance. Remarkably,

across the IoU threshold range 0.5-1.0, Omnipose averages a JI >10-fold above that of

Cellpose (Fig. 4A). The difference in performance between the algorithms is particularly

pronounced within the high IoU range (0.75-1.0), where we observe an average of 170-

fold higher JI for Omnipose. At the 0.5-5 μm scale and with a typical microscope

configuration, quantitative measurements rely upon IoU values in this range, thus

Omnipose is uniquely suited for the microscopic analysis of bacterial cells.

To dissect the contributions of the individual Omnipose innovations to the overall

performance of the algorithm, we isolated the mask reconstruction component of

Omnipose and applied it to the Cellpose network output. This augmentation of Cellpose

modestly improved its performance to a roughly equivalent extent across all IoU

thresholds (Fig. 4A). Based on this, we attribute the remaining gains in performance by

Omnipose to its unique network outputs and our improvements to the Cellpose training

framework (see Methods).

Our analyses illuminated critical flaws in prior DNN-based approaches for the

segmentation of elongated cells, effectively preventing these algorithms from

generalizable application to bacteria (Fig. 1). To determine whether Omnipose overcomes

this limitation, we evaluated its performance as a function of cell area. Cell area serves as

a convenient proxy for cell length in our dataset, which is composed of both branched

and unbranched elongated cells. Whereas the Cellpose cell error rate remains above 9%

and increases exponentially with cell size, Omnipose displays a consistent error rate that

remains below 4% for all percentiles (Fig. 4B). Thus, Omnipose performance is

independent of cell size and shape, including those cells with complex, extended

morphologies (Fig. 4C,D).

Omnipose permits sensitive detection of cellular intoxication

Our laboratory recently described an interbacterial type VI secretion system-

delivered toxin produced by *Serratia proteamaculans*, Tre1 (36). We showed that this

toxin acts by ADP-ribosylating the essential cell division factor FtsZ; however, we were

unable to robustly evaluate the consequences of Tre1 intoxication on target cell

morphology owing to segmentation challenges. Here we asked whether Omnipose could

permit straightforward and sensitive detection of intoxication by Tre1. To this end, we

incubated *S. proteamaculans* wild-type or a control strain expressing inactive Tre1

(*tre1^{E415Q}*) with target *E. coli* cells and imaged these mixtures after a fixed period of 20

hours. Owing to the unique capabilities of Omnipose, we were able to include dense

fields of view, incorporating >300,000 cells in our analysis.

Among the cells identified by Omnipose, we found a small proportion were

elongated and much larger than typical bacteria (Fig. 5A,B and Fig. S6A). These cells

were only detected in mixtures containing active Tre1, and the apparent failure of the

cells to septate is consistent with the known FtsZ-inhibitory activity of the toxin. The *S.*

proteamaculans strain background we employed in this work expresses the green

fluorescent protein. Corresponding fluorescence images allowed us to unambiguously

assign the enlarged cell population to *E. coli* (Fig. 5C). Next, we subjected the same

images to cell segmentation with StarDist, Cellpose, and MiSiC, the three top-performing

algorithms in our initial survey. Each of these algorithms fail to identify this population

of cells to high precision (Fig. 5D,E). Close inspection reveals three distinct modes of

failure (Fig. 5E and Fig. S6B). In the case of StarDist, elongated (non-star-convex) cells

are split into multiple star-convex subsets that do not span the entire cell. Cellpose detects

entire elongated cells, but it breaks them up into a multitude of smaller masks.

Conversely, MiSiC detects all cells but fails to properly separate them, making the area

measurement exaggerated in many cases. Taken together, these data illustrate how the

enhanced cell segmentation performance of Omnipose can facilitate unique insights into

microbiological systems.

Discussion

Confronted with the importance of segmentation accuracy to the success of work

within our own laboratory, we were motivated to characterize the performance of several

existing cell segmentation algorithms. Recent developments in deep learning have greatly

improved these algorithms; however, significant challenges remain (1, 30). Although

isolated cells without cell-to-cell contact can be segmented with high precision by any of

the packages we tested, segmentation becomes significantly more challenging when cells

form microcolonies, adopt irregular morphologies, or when fields are composed of cells

with multiple shapes and sizes. Such difficulties are compounded in time-lapse studies,

where the significance of segmentation errors often grows exponentially with time.

Experimental design can help mitigate certain segmentation challenges; however, the

recent emphasis on non-model organisms and microbial communities renders this an

increasingly undesirable solution (37).

This work provides the most comprehensive side-by-side quantitative comparison

of cell segmentation algorithm performance to-date. As expected, machine-learning-

based approaches outperform others, yet insights into general image segmentation

strategies can be gained from each of the methods we examined. Two of the six

algorithms we tested utilize traditional image thresholding and watershed segmentation:

Morphometrics and SuperSegger (13, 23). Each program tends to under-segment adjacent

cells and over-segment large cells, behaviors previously linked to thresholding and

watershed processes, respectively (1, 38). Given that SuperSegger was motivated at least

in-part to mitigate these issues, we postulate that traditional image segmentation

approaches are ultimately limited to specialized imaging scenarios. Although we classify

MiSiC as a DNN-based approach, this algorithm also relies on thresholding and

watershed segmentation to generate cell masks from its network output (15). The network

output of MiSiC is more uniform than unfiltered phase contrast images, yet this pre-

processing does not fully abrogate the typical errors of thresholding and watershed

segmentation. We therefore conclude that, even when combined with neural networks as

seen in MiSiC, thresholding and watershed cannot be effectively used for general cell

segmentation tasks.

A successful DNN-based algorithm is composed of a robust, consistent neural

network output, and an appropriate mask reconstruction process based on this output. In

the case of Mask R-CNN, bounding boxes for each cell are predicted along with a

probability field that localizes a cell within its bounding box (39). Masks are generated

by iterating over each box and thresholding the probability field. Despite the widespread

adoption of Mask R-CNN, we found this algorithm did not perform exceptionally well in

our study. Our results suggest that this is due to dense cell fields with overlapping

bounding boxes, a feature known to corrupt the training process and produce poor

network outputs for Mask R-CNN (40). By contrast, the StarDist network makes robust

predictions, but it fails to assemble accurate cell masks because the cells in our dataset

are not well approximated by star-convex polygons (26). The errors we encountered with

Cellpose can be attributed to both neural network output and mask reconstruction. In

Omnipose, we specifically addressed these two issues via the distance field and

suppressed Euler integration, respectively, yielding a remarkably precise and

generalizable image segmentation tool. Omnipose effectively leverages the strongest

features of several of the DNN approaches we tested, namely the distance field of

StarDist, the boundary field of MiSiC, and the mask reconstruction framework of

Cellpose.

We have designed Omnipose for use by typical research laboratories and we have

made its source code and training data publicly available. For images of bacteria under

phase contrast, researchers will not need to provide new ground truth data or retrain the

model. In this study, we emphasized morphological diversity, but we further accounted

for differences in optical features between bacterial strains, slide preparation techniques,

and microscope configurations. For example, the images in our ground-truth dataset

originate from four different researchers using distinct microscopes, objectives, sensors,

illumination sources, and acquisition settings. We further introduced extensive test-time

augmentations that simulate variations in image intensity, noise, gamma, clipping, and

magnification. Lastly, bacterial strains exhibit a wide range of intrinsic contrast and

internal structure, often exacerbated by antibiotic treatment or revealed by dense cell

packing. Internal structure can cause over-segmentation, so we included many cells with

this characteristic in our dataset.

Although we have highlighted the utility of Omnipose in the context of bacterial

phase contrast images, it can also be used to segment a variety of cells (or cell-like

objects) captured with one or multiple imaging modalities. The cyto2 dataset of Cellpose

consists of a large set of user-submitted images and corresponding ground-truth

annotations, which we used to train a separate Omnipose model (12, 30). Despite modest

improvements in speed and accuracy relative to Cellpose, we note that the absolute

performance of Omnipose on the cyto2 dataset is lower than what we obtained on our

bacterial dataset (Fig. S7). We reason that two variables may account for this

discrepancy. First, the cyto2 dataset is sourced from many contributors, such that

consistency and quality of annotation cannot be verified. Second, although our bacterial

dataset is quite diverse, it is uniform relative to the tremendous diversity of images

present in the cyto2 dataset (*e.g.,* apples, seashells, plant cells, animal cells, etc.). We

therefore postulate that domain and modality uniformity is required to replicate our

results with Omnipose on non-bacterial datasets.

We anticipate that the unprecedented performance of Omnipose may permit

access to information from microscopy images that was previously inaccessible. For

instance, images deriving from natural microbial communities could be accurately

characterized with regard to internal structure, autofluorescence, and morphology at the

single-cell level. This data could be used to estimate diversity, a novel methodology that

would complement existing sequencing-based metrics (41). It is worth noting that

phenotypic diversity often exceeds genetic diversity (42); therefore, even in a relatively

homogeneous collection of organisms, precise segmentation could allow classes

representing distinct states to be identified. A microscopy-based approach also offers the

opportunity to characterize spatial relationships between cells, information that is

exceptionally difficult to recover in most biomolecular assays.

Methods

Phase contrast and fluorescence microscopy

In-house imaging was performed on a Nikon Eclipse Ti-E wide-field epi-fluorescence microscope, equipped with a sCMOS camera (Hamamatsu) and X-cite LED for fluorescence imaging. We imaged through 60X and 100X 1.4 NA oil-immersion PH3 objectives. The microscope was controlled by NIS-Elements. Cell samples were spotted on a 3% (w/v) agarose pad placed on a microscope slide. The microscope chamber was heated to 30°C or 37°C when needed for time-lapse experiments.

Several images in our dataset were taken by two other laboratories using three distinct microscope/camera configurations. The Brun lab provided images of *C. crescentus* acquired on a Nikon Ti-E microscope equipped with a Photometrics Prime 95B sCMOS camera. Images were captured through a 60X Plan Apo λ 100X 1.45 NA oil Ph3 DM objective. The Wiggins lab provided *E. coli* and *A. baylyi* time lapses from both a Nikon Ti-E microscope as well as a custom-built tabletop microscope, both described in previous studies (43, 44).

Sample preparation

To image antibiotic-induced phenotypes, cells were grown without antibiotics overnight in LB, back-diluted, and spotted on agarose pads with 50µg/mL A22 or 10µg/mL cephalexin. Time lapses were captured of *E. coli* DH5α and *S. flexneri* M90T growing on these pads. *E. coli* CS703-1 was back-diluted into LB containing 1µg/mL aztreonam and spotted onto a pad without antibiotics (45). Cells constitutively expressed GFP to visualize cell boundaries.

H. pylori LSH100 grown with and without Aztreonam was provided by the

Salama lab (46, 47). Samples were fixed and stained with Alexaflour 488 to visualize the

cell membrane. Images were taken on LB pads. The typical technique of allowing the

spot to dry on the pad caused cells to curl up on themselves, so our images were taken by

placing the cover slip on the pad immediately after spotting and applying pressure to

force out excess media.

C. crescentus was cultivated and imaged by the Brun lab (48, 49). Cells were

grown in PYE, washed twice in water prior to 1:20 dilution in Hutner base-imidazole-

buffered-glucose-glutamate (HIGG media) and grown at 26°C for 72h. Cells were spotted

on a 1% agarose PYE pads prior to imaging.

S. pristinaespiralis NRRL 2958 was grown using the following media recipe:

Yeast extract 4g/L, Malt extract 10g/L, Dextrose 4g/L, Agar 20g/L. This media was used

to first culture the bacteria in liquid overnight and then on a pad under the microscope.

This strain forms aggregates in liquid media, so these aggregates were allowed to grow

for several hours on a slide in the heated microscope chamber until we could see

individual filaments extending from the aggregates. Fields of view were selected and

cropped to exclude cell overlaps. Autofluorescence was captured to aid in manual

segmentation.

Mixtures of *S. proteamaculans* attTn7::Km-gfp *tre1* or *tre1*^{E415Q} and *E. coli* were

spotted on a PBS pad to prevent further growth. Phase-contrast images of the cells were

acquired before and after a 20hr competition on a high-salt LB plate. Fluorescence

images in the GFP channel were also acquired to distinguish *S. proteamaculans* from

unlabeled *E. coli*.

All other individual strains in Table S1 were grown overnight, diluted 1:100 into

fresh LB media, and grown for 1-3 hours before imaging. Mixtures were made by

combining back-diluted cells roughly 1:1 by OD_{600}.

Manual cell annotation

Manual annotation began with loading the images into MATLAB, normalizing

the channels, registering the fluorescence channel(s) to phase (when applicable), and

producing boundary-enhanced versions of phase and fluorescence. Where possible,

fluorescence data was primarily used to define cell boundaries. In addition to a blank

channel to store manual labels, all processed phase and fluorescence images were then

automatically loaded as layers into an Adobe Photoshop document. We used 4-6 unique

colors and the Pencil tool (for pixel-level accuracy and no blending) to manually define

cell masks. Due to the 4-color theorem (50), this limited palette was sufficient to clearly

distinguish individual cells from each other during annotation. This color simplification is

not found in any segmentation GUI, and it enabled faster manual annotation by reducing

the need to select new colors. It also eliminated the confusion caused by the use of

similar but distinct colors in adjacent regions, which we suspect is the principal cause for

the misplaced mask pixels that we observed in other datasets (*e.g.,* cyto2).

The cell label layer was then exported as a PNG from Photoshop, read back into

MATLAB, and converted from the repeating N-color labels to a standard 16-bit integer

label matrix, where each cell is assigned a unique integer from 1 to the number of cells

(background is 0). Because integer labels cannot be interpolated, we then performed a

non-rigid image registration of the phase contrast channel to the binary label mask to

achieve better phase correlation to ground truth masks. All images in our ground-truth

dataset have been registered in this manner.

Choosing Segmentation algorithms

Three main factors contributed to the choice of algorithms highlighted in this

study: (*i*) specificity to bacterial phase contrast images, (*ii*) success and community

adoption, especially for bioimage segmentation, and (*iii*) feasibility of installation,

training, and use. SuperSegger, Morphometrics, and MiSiC were selected because they

specifically targeted the problem of bacterial phase contrast segmentation (15, 23, 51).

Packages such as BactMAP, BacStalk, Cellprofiler, CellShape, ColiCoords, Cytokit,

MicroAnalyzer, MicrobeJ, Oufti, and Schnitzcells incorporate limited novel segmentation

solutions and instead aim to provide tools for single-cell analysis such as lineage tracing

and protein tracking (8, 9, 14, 18-20, 25, 52-54). Furthermore, the segmentation that these

programs perform depends broadly on thresholding and watershed techniques; therefore,

Morphometrics is a reasonable proxy for their segmentation capabilities. We were unable

to locate code or training data for BASCA (11). Ilastik is a popular interactive machine-

learning tool for bioimage segmentation, but training it using a manual interface was not

feasible on a large and diverse dataset such as our own (21). Among DNN approaches,

Mask R-CNN was selected because it is a popular architecture for handling typical image

segmentation tasks. It was also used in the segmentation and tracking package Usiigaci

(24). U-Net architectures have been implemented in a number of algorithms, including

DeLTA, PlantSeg, MiSiC, StarDist, and Cellpose (12, 15, 17, 22, 26). DeLTA was not

included in this study because it operates similarly to MiSiC and was designed

specifically for mother machine microfluidics analysis. DeLTA 2.0 was recently released

to additionally segment confluent cell growth on agarose pads, but it remains quite

similar to MiSiC in implementation (55). PlantSeg could, in principle, be trained on

bacterial micrographs, but we determined that its edge-focused design meant to segment

bright plant cell wall features would not offer any advancements over the remaining U-

Net methods that we tested.

Training and tuning segmentation algorithms

All segmentation algorithms have tunable parameters to optimize performance on

a given dataset. These include pre-processing such as image rescaling (often to put cells

into a particular pixel diameter range), contrast adjustment, smoothing, and noise

addition. Morphometrics and SuperSegger were manually tuned to give the best results

on our benchmarking dataset. The neural network component of SuperSegger was not

retrained on our data, as this is a heavily manual process involving toggling watershed

lines on numerous segmentation examples. DNN-based algorithms are automatically

trained using our dataset, and the scripts we used to do so are available in our GitHub

repository. We adapted our data for MiSiC by transforming our instance labels into

interior and boundary masks. Training documentation for MiSiC is not published, but our

training and evaluation parameters were tuned according to correspondence with the

MiSiC authors. Cellpose and StarDist were trained with the parameters provided in their

excellent documentation. StarDist has an additional tool to optimize image pre-

processing parameters on our dataset, which we utilized.

Evaluating segmentation algorithms

All algorithms were evaluated on our benchmarking dataset with manually or

automatically optimized parameters. We provide both the raw segmentation results for all

test images by each tested algorithm as well as the models and model-training scripts

required to reproduce our results. Before evaluating IoU or JI, small masks at image

boundaries were removed for both the ground-truth and predicted masks. IoU and JI are

calculated on a per-image basis and, where shown, are averaged with equal weighting

over the image set or field of view.

Our new metric, the number of segmentation errors per cell, was calculated by

first measuring the fraction of each predicted cell that overlaps with each ground truth

cell. A predicted cell is assigned to a ground-truth cell if the overlap ratio is ≥ 0.75,

meaning that at least three quarters of the predicted cell lies within the ground-truth cell.

If several predicted cells are matched to a ground-truth cell, the number of surplus

matches is taken to be the number of segmentation errors. If no cells are matched to a

ground-truth cell, then the error is taken to be 1.

Leveraging Omnipose to accelerate manual annotation

Omnipose was periodically trained on our growing dataset to make initial cell

labels. These were converted into an N-color representation and loaded into Photoshop

for manual correction. A subset of our cytosol GFP channels were sufficient for training

Omnipose to segment based on fluorescence, and the resulting trained model enabled

higher-quality initial cell labels for GFP-expressing samples than could be achieved from

intermediate phase contrast models (*e.g., V. cholerae*).

Defining the Omnipose prediction classes

Omnipose predicts four classes: two flow components, the distance field, and a

boundary field. Our distance field is found by solving the eikonal equation

$$\left|\vec{\nabla}\phi(\vec{x})\right| = \frac{1}{f(\vec{x})}$$

where f represents the speed at a point $\vec{x}$. The Godunov upwind discretization of the

eikonal equation is

$$\left(\frac{\max\left(\phi_{i,j} - \min\left(\phi_{i-1,j}, \phi_{i+1,j}\right), 0\right)}{\Delta x}\right)^2 + \left(\frac{\max\left(\phi_{i,j} - \min\left(\phi_{1,j-1}, \phi_{i,j+1}\right), 0\right)}{\Delta y}\right)^2 = \frac{1}{f_{i,j}}$$

Our solution to this equation is based on the Improved FIM Algorithm 1.1 of (34),

as follows. Our key contribution to this algorithm is the addition of ordinal sampling to

boost both convergence and smoothness of the final distance field.

2D update function for $\phi_{i,j}$ on a cartesian grid

1. Find neighboring points for cardinal axes ($\Delta x = \Delta y = \delta$):

$$\phi^{\mathrm{minx}} = \min\left(\phi_{i-1,j}, \phi_{i+1,j}\right), \qquad \phi^{\mathrm{miny}} = \min\left(\phi_{i,j-1}, \phi_{i,j+1}\right)$$

2. Find neighboring points for ordinal axes ($\hat{x} \cdot \hat{a} = \hat{y} \cdot \hat{b} = \frac{\sqrt{2}}{2}, \frac{\Delta a}{\Delta x} = \frac{\Delta b}{\Delta y} = \sqrt{2}\delta$):

$$\phi^{\mathrm{mina}} = \min\left(\phi_{i-1,j-1}, \phi_{i+1,j+1}\right), \qquad \phi^{\mathrm{minb}} = \min\left(\phi_{i+1,j-1}, \phi_{i-1,j+1}\right)$$

3. Calculate update along cardinal axes:

if $\left|\phi^{\mathrm{minx}} - \phi^{\mathrm{miny}}\right| > \frac{\sqrt{2}\delta}{f_{i,j}}$:

$$U^{xy} = \min\left(\phi^{\mathrm{minx}}, \phi^{\mathrm{miny}}\right) + \frac{\delta}{f_{i,j}}$$

else:

$$U^{xy} = \frac{1}{2}\left(\phi^{\mathrm{minx}} + \phi^{\mathrm{miny}} + \sqrt{2\left(\frac{\delta}{f_{i,j}}\right)^2 - (\phi^{\mathrm{minx}} - \phi^{\mathrm{miny}})^2}\right)$$

501   4. Calculate update along ordinal axes:

502   **if** $\left|\phi^{\text{mina}} - \phi^{\text{minb}}\right| > \frac{2\delta}{f_{i,j}}$:

503
$$U^{ab} = \min\left(\phi^{\text{mina}}, \phi^{\text{minb}}\right) + \frac{\sqrt{2}\delta}{f_{i,j}}$$

504   **else**:

505
$$U^{ab} = \frac{1}{2}\left(\phi^{\text{mina}} + \phi^{\text{minb}} + \sqrt{4\left(\frac{\delta}{f_{i,j}}\right)^2 - (\phi^{\text{mina}} - \phi^{\text{minb}})^2}\right)$$

506   5. Update with geometric mean:

507
$$\phi_{i,j} = \sqrt{U^{xy}U^{ab}}$$

This update rule is repeated until convergence (Fig. S5). We take $\delta = f_{i,j}$ to

obtain the signed distance field used in Omnipose. The flow field components are defined

by the normalized gradient of this distance field ϕ. The boundary field is defined by

points satisfying $0 < \phi < 1$. For network prediction, the boundary map is converted to

the logits (inverse sigmoid) representation, such that points in the range $[0,1]$ are mapped

to $[-5,5]$. For consistent value ranges across prediction classes, the flow components are

multiplied by 5 and all background values of the distance field ($\phi = 0$) are set to -5.

Omnipose network architecture

The DNN used for Omnipose is a minor modification of that used in Cellpose: a

U-net architecture with two residual blocks per scale, each with two convolutional layers

(12). Omnipose introduces a dropout layer before the densely connected layer (56), which

we incorporated into the shared Cellpose and Omnipose architecture moving forward.

However, Cellpose models utilized in this study are trained without dropout.

Rescaling flow field by divergence

During training, the ground truth data is augmented by a random affine

transformation. The original implementation, and the one which yields the best results,

linearly interpolates the transformed field. This reduces the magnitude of the otherwise

normalized field in regions of divergence, *i.e.,* at boundaries and skeletons. A

renormalized field (obtained either from the transformed field or as the normalized

gradient of the transformed heat distribution) often has artifacts at cell boundaries and

skeletons, so the interpolated field effectively reduces the influence of these artifacts on

training. We reason that this feature explains the superior performance of interpolated

field training over renormalized fields, despite the latter being the nominal goal of the

algorithm.

Pixels at cell boundaries, however, consequently do not move far (less than 1px)

under Euler integration due to the low magnitude of the predicted field at cell boundaries.

Our solution in Omnipose is to rescale the flow field by the magnitude of the divergence.

The divergence is most positive at the cell boundaries (where pixels need to move) and

most negative at cell skeletons (where pixels need to stop). We therefore rescale the

divergence from 0 to 1 and multiply the normalized flow field by this new magnitude

map. This forces boundary pixels of neighboring cells to quickly diverge and allow for

accurate pixel clustering to obtain the final segmentation.

Novel diameter metric

The size models of Cellpose are trained to estimate the average cell 'diameter',

taken to be the diameter of the circle of equivalent area:

546
$$d = 2\text{R} = 2\sqrt{\frac{A}{\pi}} \qquad (*)$$

This metric as a basis for rescaling is problematic when cells are growing in

length but not width (Fig. S7D). Log-phase bacterial cell area grows exponentially with

time, and so too does the scale factor, eventually resulting in a rescaled image that is too

small for Cellpose to segment.

The average of the distance field, however, does not change for filamentous

bacteria, as the width – and therefore the distance to the closest boundary – remains

constant. To define a formula consistent with the previous definition in the case of a

circular cell, we consider mean of the distance field over the cell:

555
$$\bar{\phi} = \frac{1}{\pi R^2} \int_0^{2\pi} \int_0^R (R - r) r \, dr \, d\theta = \frac{1}{\pi R^2} \left(\frac{\pi}{3} R^3 \right) = \frac{R}{3}$$

556   This allows us to define a new 'effective diameter' as

557
$$d = 2R = 6\bar{\phi} \qquad (**)$$

Aside from agreeing with the previous scaling method $(*)$ for round

morphologies, this definition exhibits excellent consistency across time (Fig. S7C). This

consistency is also critical for training on datasets with wide distributions in cell areas

that require rescaling, such as the Cellpose datasets. Finally, the raw distance field output

of Omnipose can directly be used directly in $(**)$ to estimate average cell diameter,

which is used in our code to automatically toggle on features that improve mask

reconstruction performance for small cells.

Gamma augmentation

To make the network robust against changes in exposure/contrast, the training

images are now raised to a random power (gamma) between 0.5 and 1.25, simulating the

varying levels of contrast that are observed experimentally with different light sources,

objectives, and exposure times.

Alleviating class imbalance

Class imbalance remains a challenge in many machine learning applications (57).

In our dataset, foreground pixels (cells) take up anywhere from 1 to 75 percent of a given

training image, with the rest being background pixels that the network must only learn to

ignore (*i.e.*, assign a constant output of -5 for distance and boundary logits). We

implemented several changes to the loss function to emphasize foreground objects,

including weighting by the distance field and averaging some loss terms only over

foreground pixels. Our training augmentation function also attempts many random crop

and resizing passes until a field of view with foreground pixels is selected (this may take

several attempts for sparse images, but adds very little time to training).

Image normalization

To manage different image exposure levels, Cellpose automatically rescales

images such that pixels in the 1st percentile of intensity are set to 0 and those in the 99th

percentile are sent to 1. This percentile rescaling is preferred over blind min-max

rescaling because bubbles or glass can cause small bright spots in the image. However,

we found that images containing single cells (low intensity) in a wide field of media

(high intensity) would become badly clipped due to the foreground-background class

imbalance. To solve this, we changed the percentile range from 0.01 to 99.99.

Data availability

Ground truth images and labels generated for this study are available through the

paperswithcode database (https://paperswithcode.com/).

Code availability

Python and MATLAB scripts generated for this study is available from GitHub at

https://github.com/kevinjohncutler/omnipose. Omnipose is available as part of the

Cellpose package at https://github.com/mouseland/cellpose.

Acknowledgements

The authors wish to thank members of the Mougous and Wiggins laboratories for helpful
suggestions, Teresa Lo for assistance with image acquisition, Sophie Sichel and Nina
Salama lab for growing, fixing, and staining *H. pylori* samples for in-house imaging, and
David Kysela, Maxime Jacq and Yves Brun for providing *C. crescentus* images. This
work was supported by the NIH (AI080609 to JDM, GM128191 to PAW,
T32GM008268 to KJC). JDM is an HHMI Investigator.

Competing interests

The authors declare no competing interests.

Author contributions

KJC, PAW and JDM conceived the study. KJC performed experiments, analyzed data,
and wrote the code. KJC, PAW, and JDM wrote the manuscript. CS edited the
manuscript and assisted in code development.

Author Information

Correspondence and requests for materials should be addressed to J.D.M.
(mougous@u.washington.edu) or P.A.W. (pwiggins@uw.edu).

References

1. H. Jeckel, K. Drescher, Advances and opportunities in image analysis of bacterial
cells and communities. *FEMS Microbiol Rev* **45** (2021).

2. A. Bali, S. N. Singh (2015) A Review on the Strategies and Techniques of Image
Segmentation. in *IEEE Xplore* (IEEE), pp 113-120.

3. A. M. Lucas *et al.*, Open-source deep-learning software for bioimage
segmentation. *Mol Biol Cell* **32**, 823-829 (2021).

4. D. T. Kysela, A. M. Randich, P. D. Caccamo, Y. V. Brun, Diversity Takes Shape:
Understanding the Mechanistic and Adaptive Basis of Bacterial Morphology.
PLoS Biol **14**, e1002565 (2016).

5. S. E. Jones, M. A. Elliot, 'Exploring' the regulation of Streptomyces growth and
development. *Curr Opin Microbiol* **42**, 25-30 (2018).

6. P. D. Caccamo, Y. V. Brun, The Molecular Basis of Noncanonical Bacterial
Morphology. *Trends Microbiol* **26**, 191-208 (2018).

7. B. Behera *et al.*, Emerging technologies for antibiotic susceptibility testing.
Biosens Bioelectron **142**, 111552 (2019).

8. A. Paintdakhi *et al.*, Oufti: an integrated software package for high-accuracy,
high-throughput quantitative microscopy analysis. *Molecular microbiology* **99**,
767-777 (2016).

9. A. Ducret, E. M. Quardokus, Y. V. Brun, MicrobeJ, a tool for high throughput
bacterial cell detection and quantitative analysis. *Nat Microbiol* **1**, 16077 (2016).

10. C. Tropini, K. A. Earle, K. C. Huang, J. L. Sonnenburg, The Gut Microbiome:
Connecting Spatial Organization to Function. *Cell Host Microbe* **21**, 433-442
(2017).

11. A. D. Balomenos *et al.*, Image analysis driven single-cell analytics for systems
microbiology. *BMC Syst Biol* **11**, 43 (2017).

12. C. Stringer, T. Wang, M. Michaelos, M. Pachitariu, Cellpose: a generalist
algorithm for cellular segmentation. *Nature methods* **18**, 100-106 (2021).

13. S. Stylianidou, C. Brennan, S. B. Nissen, N. J. Kuwada, P. A. Wiggins,
SuperSegger: robust image segmentation, analysis and lineage tracking of
bacterial cells. *Molecular microbiology* **102**, 690-700 (2016).

14. R. van Raaphorst, M. Kjos, J. W. Veening, BactMAP: An R package for
integrating, analyzing and visualizing bacterial microscopy data. *Molecular*
microbiology **113**, 297-308 (2020).

15.   S. Panigrahi *et al*., Misic, a general deep learning-based method for the high-
655   throughput cell segmentation of complex bacterial communities. *Elife* **10** (2021).

656   16.   D. Bannon *et al*., DeepCell Kiosk: scaling deep learning-enabled cellular image
657   analysis with Kubernetes. *Nature methods* **18**, 43-45 (2021).

658   17.   J. B. Lugagne, H. Lin, M. J. Dunlop, DeLTA: Automated cell segmentation,
659   tracking, and lineage reconstruction using deep learning. *PLoS computational*
660   *biology* **16**, e1007673 (2020).

661   18.   J. H. Smit, Y. Li, E. M. Warszawik, A. Herrmann, T. Cordes, ColiCoords: A
662   Python package for the analysis of bacterial fluorescence microscopy data. *PLoS*
663   *One* **14**, e0217524 (2019).

664   19.   E. Czech, B. A. Aksoy, P. Aksoy, J. Hammerbacher, Cytokit: a single-cell
665   analysis toolkit for high dimensional fluorescent microscopy imaging. *BMC*
666   *Bioinformatics* **20**, 448 (2019).

667   20.   C. McQuin *et al*., CellProfiler 3.0: Next-generation image processing for biology.
668   *PLoS Biol* **16**, e2005970 (2018).

669   21.   S. Berg *et al*., ilastik: interactive machine learning for (bio)image analysis. *Nature*
670   *methods* **16**, 1226-1232 (2019).

671   22.   A. Wolny *et al*., Accurate and versatile 3D segmentation of plant tissues at
672   cellular resolution. *Elife* **9** (2020).

673   23.   T. Ursell *et al*., Rapid, precise quantification of bacterial cellular dimensions
674   across a genomic-scale knockout library. *BMC Biol* **15**, 17 (2017).

675   24.   H. F. Tsai, J. Gajda, T. F. W. Sloan, A. Rares, A. Shen, Usiigaci: Instance-aware
676   cell tracking in stain-free phase contrast microscopy enabled by machine learning.
677   *SoftwareX* **9**, 230-237 (2019).

678   25.   J. Reiner, G. Azran, G. Hyams, MicroAnalyzer: A Python Tool for Automated
679   Bacterial Analysis with Fluorescence Microscopy. *arXiv*
680   https://arxiv.org/abs/2009.12684 (2020).

681   26.   U. Schmidt *et al*., *Cell Detection with Star-Convex Polygons*, Medical Image
682   Computing and Computer Assisted Intervention -- MICCAI 2018 (2018),
683   https://link.springer.com/chapter/10.1007/978-3-030-00934-2_30, pp. 265-273.

684   27.   K. He, G. Gkioxari, P. Dollar, R. Girshick, Mask R-CNN. *arXiv*
685   https://arxiv.org/abs/1703.06870 (2018).

686   28.   K. Shal, M. S. Choudhry, Evolution of Deep Learning Algorithms for MRI-Based
687   Brain Tumor Image Segmentation. *Crit Rev Biomed Eng* **49**, 77-94 (2021).

688   29.   G. J. Bean *et al.*, A22 disrupts the bacterial actin cytoskeleton by directly binding
689   and inducing a low-affinity state in MreB. *Biochemistry* **48**, 4852-4857 (2009).

690   30.   R. F. Laine, I. Arganda-Carreras, R. Henriques, G. Jacquemet, Avoiding a
691   replication crisis in deep-learning-based bioimage analysis. *Nature methods* **18**,
692   1136-1144 (2021).

693   31.   A. A. Taha, A. Hanbury, Metrics for evaluating 3D medical image segmentation:
694   analysis, selection, and tool. *BMC Med Imaging* **15**, 29 (2015).

695   32.   W. Lu *et al.*, Unsupervised Sequential Outlier Detection With Deep Architectures.
696   *IEEE Trans Image Process* **26**, 4321-4330 (2017).

697   33.   J. A. Sethian, A. Vladimirsky, Ordered upwind methods for static Hamilton-
698   Jacobi equations. *Proc Natl Acad Sci U S A* **98**, 11069-11074 (2001).

699   34.   Y. Huang, Improved Fast Iterative Algorithm for Eikonal Equation for GPU
700   Computing. *arXiv* http://arXiv:2106.15869v3 (2021).

701   35.   M. Ester, H. P. Kreigel, J. Sander, X. Xu, A density-based algorithm for
702   discovering clusters in large spatial databases with noise. 10.1.1.121.9220 (1996).

703   36.   S. Y. Ting *et al.*, Bifunctional Immunity Proteins Protect Bacteria against FtsZ-
704   Targeting ADP-Ribosylating Toxins. *Cell* **175**, 1380-1392 (2018).

705   37.   J. A. Cusick, C. L. Wellman, G. E. Demas, The call of the wild: using non-model
706   systems to investigate microbiome-behaviour relationships. *J Exp Biol* **224**
707   (2021).

708   38.   Z. Wang, Cell Segmentation for Image Cytometry: Advances, Insufficiencies, and
709   Challenges. *Cytometry A* **95**, 708-711 (2019).

710   39.   C. He *et al.*, Genome-resolved metagenomics reveals site-specific diversity of
711   episymbiotic CPR bacteria and DPANN archaea in groundwater ecosystems. *Nat
712   Microbiol* **6**, 354-365 (2021).

713   40.   S. Looi (2019) rotated_maskrcnn. (GitHub).

714   41.   R. Bharti, D. G. Grimm, Current challenges and best-practice protocols for
715   microbiome analysis. *Brief Bioinform* **22**, 178-193 (2021).

716   42.   W. K. Smits, O. P. Kuipers, J. W. Veening, Phenotypic variation in bacteria: the
717   role of feedback regulation. *Nat Rev Microbiol* **4**, 259-271 (2006).

718   43.   J. Bailey *et al.*, Essential gene deletions producing gigantic bacteria. *PLoS
719   genetics* **15**, e1008195 (2019).

44. J. A. Cass, S. Stylianidou, N. J. Kuwada, B. Traxler, P. A. Wiggins, Probing
bacterial cell biology using image cytometry. *Molecular microbiology* **103**, 818-
828 (2017).

45. B. M. Meberg, F. C. Sailer, D. E. Nelson, K. D. Young, Reconstruction of
Escherichia coli mrcA (PBP 1a) mutants lacking multiple combinations of
penicillin binding proteins. *J Bacteriol* **183**, 6148-6149 (2001).

46. A. C. Lowenthal *et al.*, Functional analysis of the Helicobacter pylori flagellar
switch proteins. *J Bacteriol* **191**, 7147-7156 (2009).

47. J. A. Taylor *et al.*, Distinct cytoskeletal proteins define zones of enhanced cell
wall synthesis in Helicobacter pylori. *Elife* **9** (2020).

48. M. Evinger, N. Agabian, Envelope-associated nucleoid from Caulobacter
crescentus stalked and swarmer cells. *J Bacteriol* **132**, 294-301 (1977).

49. P. D. Caccamo, M. Jacq, M. S. VanNieuwenhze, Y. V. Brun, A Division of Labor
in the Recruitment and Topological Organization of a Bacterial Morphogenic
Complex. *Curr Biol* **30**, 3908-3922 e3904 (2020).

50. N. Robertson, D. P. Sanders, P. Seymour, R. Thomas, A new proof of the four-
colour theorem. *Electron. Res. Announc. Amer. Math. Soc.*
https://doi.org/10.1090/S1079-6762-96-00003-0 (1996).

51. S. Stylianidou, C. Brennan, S. B. Nissen, N. J. Kuwada, P. A. Wiggins,
SuperSegger: robust image segmentation, analysis and lineage tracking of
bacterial cells. *Molecular microbiology* **102**, 690–700 (2016).

52. R. Hartmann, M. C. F. van Teeseling, M. Thanbichler, K. Drescher, BacStalk: A
comprehensive and interactive image analysis software tool for bacterial cell
biology. *Molecular microbiology* **114**, 140-150 (2020).

53. A. Goni-Moreno, J. Kim, V. de Lorenzo, CellShape: A user-friendly image
analysis tool for quantitative visualization of bacterial cell factories inside.
Biotechnol J **12** (2017).

54. J. W. Young *et al.*, Measuring single-cell gene expression dynamics in bacteria
using fluorescence time-lapse microscopy. *Nature protocols* **7**, 80-88 (2011).

55. O. M. O'Connor, R. N. Alnahhas, J. B. Lugagne, M. J. Dunlop, DeLTA 2.0: A
deep learning pipeline for quantifying single-cell spatial and temporal dynamics.
bioRxiv https://doi.org/10.1101/2021.08.10.455795 (2021).

56. N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, R. Salakhutdinov,
Dropout: a simple way to prevent neural networks from overfitting. *The Journal*
of Machine Learning Research **15**, 1929-1958 (2014).

57.   H. Kaur, H. S. Pannu, A. K. Malhi, A Systematic Review on Imbalanced Data
Challenges in Machine Learning: Applications and Solutions. *ACM Computing*
Surveys **52**, 1-36 (2019).

58.   B. M. Meberg, F. C. Sailer, D. E. Nelson, K. D. Young, Reconstruction of
Escherichia coli mrcA (PBP 1a) mutants lacking multiple combinations of
penicillin binding proteins. *J Bacteriol* **183**, 6148–6149 (2001).

59.   V. Barbe *et al.*, Unique features revealed by the genome sequence of
Acinetobacter sp. ADP1, a versatile and naturally transformation competent
bacterium. *Nucleic Acids Res* **32**, 5766-5779 (2004).

60.   Y. Yu *et al.*, Genomic patterns of pathogen evolution revealed by comparison of
Burkholderia pseudomallei, the causative agent of melioidosis, to avirulent
Burkholderia thailandensis. *BMC microbiology* **6**, 46 (2006).

61.   A. Allue-Guardia, M. Echazarreta, S. S. K. Koenig, K. E. Klose, M. Eppinger,
Closed Genome Sequence of Vibrio cholerae O1 El Tor Inaba Strain A1552.
Genome Announc **6** (2018).

62.   C. K. Stover *et al.*, Complete genome sequence of Pseudomonas aeruginosa
PA01, an opportunistic pathogen. *Nature* **406**, 959–964 (2000).
772

Figure 1. Quantitative comparison of segmentation methods distinguishes Cellpose as a high performing algorithm. (**A-G**) Comparison of segmentation algorithm performance on our test dataset. (**A**) Overall performance measured by Jaccard Index (JI). The JI was calculated at the image level and values averaged across the dataset are displayed. Algorithm abbreviations defined in B-G. (**B-G**) Algorithm performance partitioned by cell type (Simple, n=12,869; Abx/mutant, n=6,138; Elongated, n=46). Images were sorted into types as defined in Supplemental Table 1 (Abx, antibiotic). (**H-J**) Representative micrographs of cell type partitions analyzed in B-G, indicated by vertical bars at right. Ground-truth masks and predicted mask outlines generated by the indicated algorithm are displayed. Mean matched IoU values for cells shown are displayed within each micrograph. Bacteria displayed are (H) *Vibrio cholerae*, *Pseudomonas aeruginosa*, *Bacillus subtilis*, *Staphylococcus aureus*, (I) aztreonam-treated *Escherichia coli* CS703-1, and (J) *Streptomyces pristinaespiralis*. All images scaled equivalently; scale bar is 1mm.

Figure 2. Cellpose over-segments extended, anisotropic cells. (**A**) Single-cell analysis of segmentation error as a function of cell area. Color represents density on a log scale. Gray box represents the top quartile of cell areas. (**B**) Representative examples exhibiting problematic flow fields. Corresponding boundary pixel trajectories are shown in black and final pixel locations in red. Predicted mask overlays are shown with mean matched IoU values. (**C**) Analysis of stochastic center-to-boundary distances. Distance from the center (median pixel coordinate) to each boundary pixel is normalized to a maximum of 1. Position along the boundary is normalized from -1 to 1 and centered on the point closest to the median pixel. Center-to-boundary for the cell in panel D is highlighted in black. (**D**) Representative cell with median coordinate outside the cell body (black X). Cellpose projects this point to the global minima of this function (green dot), but several other local minima exist (blue dots). (**E**) The heat distribution resulting from a projected cell center (black arrow). The normalized gradient corresponds to the divergence shown. Scale bars are 1 μm.

Figure 3. Core innovations of Omnipose. (**A**) Comparison of distance field algorithms and corresponding flow fields. Fast Marching Method (FMM) produces ridges in the distance field resulting from pixelation on the cell mask boundary. Our smooth FIM algorithm minimizes these features. The difference image (FIM – FMM) highlights artifacts in the FMM method. Flow fields are calculated as the normalized gradient of the distance field. Boundary pixelation affects the FMM flow field deep into the cell, regardless of cell size. (**B**) Comparison of mask reconstruction algorithms on a smooth flow field (not shown). Left: boundary pixel trajectories and resulting mask outlines from standard Euler integration. Right: Trajectories and mask outlines under suppressed Euler integration. Red dots indicate the final positions of all cell pixels, not only the boundary pixels for which trajectories are displayed. Scale bars are 1 μm.

Figure 4. Omnipose outperforms Cellpose. (**A**) Omnipose IoU distribution on our dataset compared to the next highest performing algorithm in each of three cell categories. (**B**) Example micrographs and Omnipose segmentation. Mean matched IoU values shown. (**C**) Overall performance measured by Jaccard Index (JI). The hybrid method (gray) is a variant of Cellpose that uses the original center-seeking flow output and the mask reconstruction of Omnipose. Gray box represents IoU ≥ 0.8. (**D**) Quantification of segmentation performance by cell size. The percent of cells with at least one segmentation error is computed for cells in each area percentile group from 1 to 100. Gray box represents the top quartile. Scale bars are 1 μm.

Figure 5. Sensitive detection of a toxin-induced morphological phenotype. (**A**) Fluorescence/area population profile according to Omnipose segmentation in control and experimental conditions. K-means clustering on GFP fluorescence distinguishes *S. proteamaculans tre1/tre1^{E415Q}* (light/dark green markers) from *E. coli* (gray markers). (**B**) Example of extreme filamentation of *E. coli* in response to active Tre1. (**C**) Omnipose accurately segments all cells in the image. Largest cell indicated with black arrow. (**D**) MiSiC predicts large cell masks over both species. Cellpose and StarDist fail to predict any cells above 15μm^2. (**E**) Example segmentations show that MiSiC masks are not single-cell accurate. Cellpose over-segments long cells and under-segments neighboring cells. StarDist predicts incomplete cell masks. Mask mergers cause some *E. coli* to be misclassified as *S. protea*. Scale bar is 1 μm.

Figure S1. Test dataset is representative of the training dataset. (**A**) Mean diameter, defined in Methods. (**B**) Cell area. (**C**) Cell perimeter. P-values are displayed for the two-sided KS test.

Figure S2. IoU values for synthetic cell of typical size/resolution. (**A**) 0-12 pixel displacement of cell mask (red outline) and corresponding IoU values. (**B**) IoU decreases non-linearly for curved regions such as this synthetic cell.

Figure S3. Details of the Cellpose algorithm. (**A**) Stages of the Cellpose training pipeline. Ground truth masks (*i*) are converted to cell probability (*ii*) by binary thresholding and a heat distribution (*iii*) by simulated diffusion from the median pixel coordinate. The flow field (*iv*) is defined by the normalized gradient of (*iii*). Color-magnitude representations of this vector field follow the flow legend diagram. The phase, cell probability, and flow fields are used to train the network. (**B**) Stages of the cellpose prediction pipeline. Phase images are processed by the trained cellpose network into the intermediate flow field and cell probability outputs (*i-ii*). A binary threshold is applied to the probability to identify cell pixels (*iii*). Pixels are Euler-integrated under the flow field until they converge at common points. Boundary pixel trajectories are depicted in *iv*. Each pixel is assigned a unique label corresponding to the center to which it converged (*v*). This segmentation result is commonly depicted in an outline view (*vi*). Scale bar is 1 μm.

Figure S4. Median coordinates are asymmetrically localized. (**A**) Center-to-boundary distance highlighted for two cells with non-projected median coordinates. Dashed lines indicate the larger of the two minima along the medial axis. (**B**) Rod-shaped *E.coli* with symmetric median coordinate. Symmetry of the center is reflected in A by equal high and low points corresponding to the extremal points along the long and short axes of the cell. (**C**) Curved *B. subtilis* with median coordinate asymmetrically close to the cell boundary. This asymmetry is reflected in A by a secondary minimum above the global minimum corresponding to the diametrically opposing point along the short axis of the cell. (**D**) These centers result in distinct flow fields reflecting the (a)symmetric of the cell center. Scale bar is 1 μm. Images scaled equivalently.

Figure S5. Comparison of three algorithms for computing center-independent flow fields. Each is defined by a partial differential equation with the mask at the source: time-independent heat equation, the screened Poisson equation, and the Eikonal equation. We solve these equations with iterative relaxation (see Methods). (**A**) Two example cells, the first drawn from our dataset with a mean diameter of 37px and a synthetic rod-shaped cell with a mean diameter of 192px. Cell (*i*) exhibits heat-derived flow components pointing toward the skeleton near boundaries and toward the global cell center at the skeleton. Center-seeking flow components become problematic for mask reconstruction for more complicated cell geometries, namely those with oscillating thickness. The screened Poisson and Eikonal equations produce nearly identical flow fields (same direction, normalized magnitude). Cell (*ii*) reveals a core flaw in the screened Poisson solution: its derivative exceeds our available numerical precision, leading to a vanishing flow field at the center where the solution plateaus. Any cells of this size or larger will exhibit this issue. (**B**) Convergence measured by the average difference at each iteration (maximum normalized to 1) for cells (*i,ii*). Our Eikonal solution converges faster than the other methods by a wide margin at typical cell diameters (*i*).

Figure S6. Controls and additional examples. (**A**) Controls segmented by StarDist, Cellpose, and MiSiC. Notably, Cellpose and MiSiC exhibit an enrichment of larger cells even in the control, a consequence of both under-segmented (merged) cells as well as fragments of over-segmented large cells. (**B**) Cells 2 and 3 highlighted in orange and gray plotted in Fig. 5A,D. Scale bars are 1 μm.

Figure S7. Omnipose can be applied to non-bacterial datasets. (**A**) Performance of Omnipose on the cyto2 dataset. (**B-C**) Comparison of diameter metrics on a mutant bacterial microcolony. Scale bar is 1 μm.

Supplemental Table 1.

Species	Strain	Image count	Cell Count	Cells in GT	Percent of GT	Notes
Escherichia coli	DH5α	1378	98200	9733	20.6	Dense microcolonies grown on minimal media. Thin phenotype. ITPG-induced GFP cytosol marker. Time lapse. Imaged by the Wiggins lab.
		141	4536	4395	9.3	Dense microcolonies on LB. Time lapse. Imaged by the Wiggins lab.
		2	2277	-	-	Treatment with cephalexin. Tn7::GFP. Imaged by the Mougous lab.
	CS703-1 (58)	80	23169	1299	2.6	Mutant grown on LB and aztreonam. Elongated and branching phenotypes. Time lapse. Imaged by the Mougous lab.
Shigella flexneri	M90T	117	256618	1409	3.0	Treatment with A22. Tn7::GFP. Frames selected from time lapse after 1hr growth. Imaged by the Mougous lab.
		6	4482	4318	9.2	Treatment with cephalexin. Tn7::GFP. Frames selected from time lapse after 1hr growth. Imaged by the Mougous lab.
Francisella tularensis subsp. novicida	U112	5	20166	496	1.1	Small and extremely low-contrast cells. Tn7::GFP. Imaged by the Mougous lab.
Acinetobacter baylyi	ADP1 (59)	2169	60601	3336	7.1	Deletion of essential gene *murA*. Rounded phenotype. Time lapse. Imaged by the Wiggins lab.
		241	1313	1133	2.4	Deletion of essential gene *ftsN*. Filamentous phenotype. Time lapse. Imaged by the Wiggins lab.
		540	10013	2227	4.7	Deletion of essential gene *dnaA*. Filamentous phenotype. Time lapse. Imaged by the Wiggins lab.
Burkholderia thailandensis	E264 (60)	30	62005	5122	10.9	Selected panels from a self-intoxication experiment. Cells exhibit internal structure and low contrast in microcolonies. Tn7::GFP. Time lapse. Imaged by the Mougous lab.
Helicobacter pylori	LHS100 (46)	15	13014	-	-	Helical phenotype. Grown, fixed, and stained with Alexaflour 488 in the lab of

					Nina Salama. Imaged by the Mougous lab.
		19	1668	701	1.5	Treated with aztreonam. Filamentous, helical phenotype. Grown, fixed, and stained with Alexaflour 488 in the lab of Nina Salama. Imaged by the Mougous lab.
Caulobacter crescentus	NA1000 (48)	4	1787	756	1.6	Grown on low phosphate media to induce stalk phenotype. Cultivation and imaging done in the lab of Yves Brun.
Streptomyces pristinaespiralis	NRRL 2958	17	2339	270	0.6	Grown on rich media to induce filamentous phenotype. Imaged by the Mougous lab.
Vibrio cholerae	A1552 (61)	2	2627	2265	4.8	Cells have short but curved morphology and form dense, low-contrast microcolonies. Tn7::GFP. Obtained from the lab of Fitnat Yildiz. Imaged in the Mougous lab.
Serratia proteamaculans *E. coli*	568 DH5α	43	100146	1244	2.6	1:1 mixture. *S.p.* labelled via Tn7::GFP, *E.c.* unlabeled. Time lapse. Imaged in the Mougous lab.
Pseudomonas aeruginosa *Staphylococcus aureus*	PAO1 (62) USA300	3	2662	3688	7.8	1:1 mixture. *P.a.* labelled via Tn7::GFP, *S.a.* unlabeled. Imaged in the Mougous lab.
P. aeruginosa *S. aureus* *V. cholerae* *Bacillus subtilis*	PAO1 USA300 A1552 HM1350	21	33281	4678	9.9	1:1:1:1 mixture. *P.a.* and *V.c.* labelled via Tn7::GFP, *S.a.* and *B.s.* labelled with red membrane dye. Imaged in the Mougous lab.
		4833	700904	47070	100	