Coupled yawing and orbital rotation in kinesin motility revealed by polarization measurement of gold nanorods

Mitsuhiro Sugawa[1,2*], Yohei Maruyama[1], Masahiko Yamagishi[1], Robert A. Cross[3] and Junichiro Yajima[1,2,4*]

[1]Department of Life Sciences, Graduate School of Arts and Sciences, The University of Tokyo, 3-8-1, Komaba, Meguro-ku, Tokyo 153-8902, Japan

[2]Komaba Institute for Science, The University of Tokyo, 3-8-1, Komaba, Meguro-ku, Tokyo 153-8902, Japan

[3]Center for Mechanochemical Cell Biology, Warwick Medical School, Coventry, CV4 7AL, UK

[4]Research Center for Complex Systems Biology, The University of Tokyo, 3-8-1, Komaba, Meguro-ku, Tokyo 153-8902, Japan

Corresponding to Mitsuhiro Sugawa, Junichiro Yajima

Email: mitsuhiro-sugawa@g.ecc.u-tokyo.ac.jp, yajima@bio.c.u-tokyo.ac.jp

Abstract

Kinesin motor domains generate impulses of force and movement that have both translational and rotational components, raising the question of how the rotational component contributes to motor functions. We used a new assay in which kinesin-coated gold nanorods (kinesin-GNRs) move on suspended microtubules, for two plus-end-directed and weakly-processive kinesins: single-headed KIF1A, dimeric ZEN-4. Polarization of the light scattered by two types of kinesin-GNRs periodically oscillated as they orbited the microtubule along a left-handed helical trajectory. Our analyses revealed that each kinesin-GNR unidirectionally rotates about its yaw axis as it translocates, and that the period of this yaw-axis rotation corresponds to two periods of its left-handed helical orbit around the microtubule axis. Theoretical analyses suggest that the yaw-axis rotation enhances biased lateral displacement of the kinesin team. Our study reveals biaxial rotation as a new mode of motility in kinesin teams that may help the team to sidestep roadblocks.

Introduction

Kinesins are adenosine 5'-triphosphate (ATP)-driven and microtubule-based molecular motors with multiple mechanical functions, including cargo transport along microtubules, the regulation of microtubule dynamics, and the sliding of bundled microtubules(1–3). Recent advances in techniques for 3D particle tracking and simultaneous measurements of force and torque have revealed that kinesins have translational and rotational degrees of freedom on microtubules, such that their motilities consist of both helical(4–8) and rotational(9) motions. For example, single-molecule kinesin-1 dimers unidirectionally rotate their stalk domain as they move processively via a hand-over-hand mechanism, especially at high ATP concentration(9). Mutagenic elongation of the neck linker of kinesin-1 dimers increases the probability of protofilament switching during stepping along the microtubule(10), so that the neck-linker mutant dimers retain processivity but switch protofilaments more readily, driving left-handed helical motion of multiple motor-coated beads around the axis of the microtubule (6). These studies suggest that the protofilament-tracking ability of wild type kinesin-1 dimers may derive from their rotary hand-over-hand mechanism(9) and their neck stability(6, 8). Wild-type kinesin-2 and -8, which have longer neck-linker domains than kinesin-1, and kinesin-6, which has an atypical neck region, do not track protofilaments. All these kinesins move towards microtubule plus ends along left-handed helical trajectories, as shown in a bead assay(6, 11), a microtubule surface-gliding assay(8, 11–13) and a single-molecule tracking assay(8). Furthermore, teams of non-processive dimeric kinesin-14 Ncd(14–16), which moves towards microtubule minus ends, as well as teams of truncated single-headed kinesins-1(17, 18), -3(19), -5(4, 20) and -6(11) motors have all been shown to drive corkscrewing motions of microtubules in surface-gliding assays. The handedness of these motions is consistent. Whilst plus-end directed kinesins move along a left-handed helix, minus-ended kinesins move along a right-handed helix. These helical motilities imply that the stroke (the unitary impulse of force and movement generated by the motor domains) has an off-axis component, driven either by conformational changes in the motor domain or by the directionally biased selection of microtubule binding sites (or potentially both)(6, 8, 11, 15, 17, 19). The underlying mechanisms and functional relevance of the torque component remain elusive.

To gain further insight, we have developed a novel motility assay in which gold nanorods (GNRs), coated with a team of kinesin molecules, move unhindered along suspended microtubules. Our assay uses light scattered by the kinesin-coated GNRs to track their position, and the polarization of the scattered light to report their orientation. We performed the GNR motility assay on three plus-end-directed kinesins: single-headed KIF1A, dimeric ZEN-4.

Results

GNR imaging for particle tracking and polarization measurements. We developed a motility

assay based on tracking of kinesin-coated GNRs. Focusing of light scattered by the GNRs allows

positional tracking, whilst the ratio of the polarization of this scattered light in orthogonal directions

reports the orientation of the GNR as it moves over the microtubule surface (Fig. 1A and Materials

and Methods). GNR images were obtained by laser dark-field imaging using highly inclined

illumination with nearly total internal reflection angle[21, 22] via a perforated dichroic mirror[23].

The position of each GNR spot was measured in three dimensions using a cylindrical lens[24] (Fig.

S1). Polarization measurements of GNRs were performed using a combination of the polarized

incident laser beam and a polarizing beam displacer, which two orthogonal polarization signals

were projected on the camera, allowing us to measure 0° to 180° GNR orientations in the sample

plane (Fig. 1B and Materials and Methods). Kinesin constructs were prepared with a biotinylated

peptide (Avi-tag) fused to their C-terminus. Biotinylated GNRs (40 nm × 68 nm) were coated in

streptavidin and biotinylated kinesin molecules were attached to this streptavidin layer (Materials

and Methods). We used the GNR with relative low aspect ratio to detect various rotations of kinesin

coated GNR (kinesin-GNR) on the microtubule. A GNR with higher aspect ratio may inhibit rotations

of a kinesin-GNR, since the parallel longitudinal axis alignment of the kinesin-GNR and the

microtubule is most stable in terms of the number of kinesin molecule that can attach to the

microtubule. Maximum capacity of kinesin molecules attached to the GNR used in this study is

roughly estimated to be about 100 molecules (surface area of GNR/occupied area of kinesin ≈ 1.1

$\times 10^4$ nm^2/10^2 nm^2) and about one fourth of the attached kinesin molecules could generate driving

force and torque on the microtubule. Microtubules were suspended on microbeads (0.5 μm) via the

antigen–antibody system for β-tubulin, so that kinesin-coated GNRs were free to orbit the

microtubules between bead-attachment points (Fig. 1C). Control experiments established that the

Z-displacement of GNR in the range of ±200 nm had negligible effect on the GNR polarization

measurement in our experimental system (Fig. S2). Using the GNR motility assay, we performed

a comparative analysis of two plus-end-directed kinesins, which have distinctive properties of

processivity and oligomeric state: biased-diffusional motile and single-headed human kinesin-3

(KIF1A)[25] and weakly processive and dimeric *Caenorhabditis elegans* kinesin-6 (ZEN-4)[26].

GNR motility assay for single-headed KIF1A. We performed the GNR motility assay for single-

headed KIF1A (1-366 amino acid residues (AAs))[25] at a saturating ATP concentration (2 mM

ATP). GNRs carried multiple KIF1A molecules, allowing GNRs to move processively along

microtubules. We found that the light-scattering intensities of each pair of KIF1A-coated GNR

(KIF1A-GNR) spots, corresponding to orthogonal polarization signals from a single GNR,

periodically oscillated in intensity during helical movement, with an increase in each signal

corresponding to a decrease in the other (13 particles out of 62 tested KIF1A-GNRs) (Fig. 2A and
Movie S1). The degree of polarization (DOP) as a function of the summed-intensity of the two GNR
spots depicted an elliptical trajectory, indicating continuous rotations of the polarization (Fig. 2B).
The *X-Y-Z*-trajectory of the KIF1A-GNR showed steady left-handed helical motion around the
microtubule long axis (Fig. 2C). Figure 2D shows that the time trajectories of the *X-* and *Y-*
displacements, the DOP and summed-intensity, and the polarization angle as viewed from above
the glass substrate. The time trajectory of the polarization angle exhibited continuous
counterclockwise rotations during the left-handed helical motion of the KIF1A-GNR around the
microtubule. The *Y*-displacement and the polarization signals of the KIF1A-GNR exhibited strong
cross-correlation and periodicity (Fig. 2E), indicating that the GNR polarization were synchronized
with the helical motion on the microtubule. We also observed clockwise and oscillatory rotations of
the GNR polarization, synchronized with the helical motion of KIF1A-GNRs (Fig. 3A and 3B). The
translational velocity (parallel to the microtubule axis) was 0.51 ± 0.12 μm s^{-1} (mean ± standard
deviation (SD), *n* = 13 GNRs), which is nearly equal to the microtubule sliding velocity of 0.49 μm
s^{-1} in the surface-gliding assay (Fig. S3). The pitch of the helical motion measured in the *X-Y-*
trajectory was 0.69 ± 0.36 μm (mean ± SD, *n* = 33 cycles in 13 KIF1A-GNRs), which is slightly
shorter than that of the corkscrewing of microtubules on a surface of KIF1A of 0.89 ± 0.21 μm
(mean ± SD, *n* = 35 cycles in 5 microtubules) ($P \ll 0.01$, Welch's *t* test). The displacement in the
microtubule axis during one periodic change in the GNR polarization signals (hereafter referred to
as polarization pitch) was 0.69 ± 0.37 μm (mean ± SD, *n* = 33 cycles in 13 KIF1A-GNRs), which
was almost equal to that of the helix pitch (Fig. 3C). We note that the measured helix pitch is a
combination of the helix pitch exerted by motors on the straight microtubule lattice and any
supertwist pitch of the microtubule, with the supertwist depending on the number of the
protofilaments. However, when the measured pitch is less than 1 μm, as it is here, the supertwist
of the microtubule has negligible influence on the measured pitch (Fig. S4 and Materials and
Methods). We therefore report the uncorrected helix pitch unless otherwise mentioned.
126
Helical and yaw-axis rotations of kinesin-coated GNRs. The GNR motility assays of KIF1A
revealed that the polarization of KIF1A-GNRs rotated periodically whilst moving along a helical
trajectory toward microtubule plus ends. As a control to check whether rotation of the GNR
polarization is coupled to helical orbiting of the supertwist of the microtubules or not, we studied
GNRs coated with multiple kinesin-1 coated GNRs, which faithfully track protofilaments(6) rather
than side-stepping. Polarization angle of the kinesin-1 coated-GNRs did not exhibit unidirectional
rotation along a long-pitch helical path in our observation (Fig. S5). When the orientation of a
kinesin-GNR relative to the microtubule axis is constant during helical motion, unidirectional
rotations of the GNR polarization are never observed (Fig. 4A and Movie S2). Therefore, we

hypothesized that unidirectional rotations of the GNR polarization are generated by rotations in
three axes (rolling, yawing, pitching) of the kinesin-GNR during helical motion. We note that
considering symmetry of gold nanorods and geometries of our polarization measurement, pitching
and yawing of the GNR cannot be distinguished from each other in our polarization measurement.
However, as shown below, the experimental results can be well explained by the combination of
rolling and yawing in the kinesin-GNR. We constructed a model, in which a kinesin-coated GNR
unidirectionally rotates about its yaw and roll axes during the short-pitch helical motion around the
microtubule long axis (Movie S3). At first, time trajectories of the kinesin-coated GNR are given by

$$R_{\text{Roll}}(\omega_{\text{Roll}}t)R_{\text{Yaw}}(\omega_{\text{Yaw}}t)p_0 + helix(t), \tag{1}$$

where $R_{\text{Roll}}(\omega_{\text{Roll}}t)$ is rolling matrix with the angular velocity ω_{Roll}, $R_{\text{Yaw}}(\omega_{\text{Yaw}}t)$ is yawing matrix
with the angular velocity ω_{Yaw}, and $helix(t)$ is a helical displacement as functions of time t, and p_0
is an initial position of a kinesin-GNR with an initial phase angle φ. Note that the initial phase angle
φ is defined by the relative angle to the microtubule axis when the kinesin-coated GNR is at the
top position of its helical trajectory. The polarization angle measured in this study is the orientation
of the GNR projected in the X-Y-plane. Then, time trajectories of the GNR angle in the X-Y-plane
are given by

$$\arctan[\cos(\omega_{\text{Roll}}t)\cdot\tan(\varphi + \omega_{\text{Yaw}}t)], \tag{1}$$

Results of KIF1A-GNRs were well explained when $\omega_{\text{Roll}} = \pm2\omega_{\text{Yaw}}$. This means that a KIF1A-coated
GNR unidirectionally rotates 180° about its short (yaw) axis in one period of short-pitch helical
motion around the microtubule long axis. The three types of rotations of the GNR polarization angle
(counterclockwise, oscillatory, and clockwise rotations) can be reproduced by different initial phase
angles (φ) of the model (Fig. 4B and Movie S4). For example, rotations of the GNR polarization are
counterclockwise at $\varphi = 0°$, oscillatory at $\varphi = 45°$ and 135°, and clockwise at $\varphi = 90°$. Since the
initial phase angle φ is a random variable in the assay, our model is consistent with experimental
results in which these three types of polarization rotations of KIF1A-GNRs were observed.

In this model, the GNR yawing direction is also a determinant of apparent rotational patterns of
the GNR polarization in the sample plane. Pearson's correlation coefficient between the Y
displacement and the angle of a kinesin-GNR is negative when it yaws clockwise and positive when
counterclockwise (Fig. 4B and Fig. S6). Estimated by the correlation coefficient between the Y-
displacement and the polarization angle, 8 out of 13 KIF1A-GNRs exhibited clockwise yawing whilst
5 out of 13 KIF1A-GNRs counterclockwise yawing (see also Fig. 2D and Fig.3A and B). The
directionalities of yawing of these kinesin-coated GNRs were not significantly different from an
equal probability using binomial test ($P > 0.5$).

GNR motility assay for dimeric ZEN-4. We performed the GNR motility assay for the weakly-

processive dimeric kinesin, ZEN-4 (1-555 AAs)(26), again at a saturating ATP concentration (2
mM) (Materials and Methods). We again found that the polarization signals of the ZEN4-coated
GNRs (ZEN4-GNR) periodically changed, correlated with the *Y*-displacements during steady
forward movement (13 particles out of 49 tested ZEN4-GNRs) (Fig. 5A). The analyses revealed
the counter-clockwise, clockwise, and oscillatory rotations of these ZEN4-GNRs. The forward
velocity of the ZEN4-GNR was 0.39 ± 0.05 μm s^{-1} (mean ± SD, *n* = 13 ZEN4-GNRs), which is
comparable to the velocity in the bead assay(11). The polarization pitch of the ZEN4-GNR was
0.67 ± 0.20 μm (mean ± SD, *n* = 34 cycles in 13 ZEN4-GNRs) in the microtubule axis, which is
equal to the helix pitch of 0.67 ± 0.21 μm (mean ± SD, *n* = 34 cycles in 13 ZEN4-GNRs) (Fig. 5B).
Thus, whilst ZEN4-GNRs moved more slowly than KIF1A-GNRs, the polarization rotation of ZEN4-
GNRs was again phase-locked to their helical motion, as for KIF1A-GNRs. These results indicate
that ZEN4-GNRs also unidirectionally rotates 180° about its short (yaw) axis in one period of short-
pitch helical motion around the microtubule long axis. Estimated by the correlation coefficient
between the *Y*-displacement and the polarization angle, 5 out of 13 ZEN4-GNRs exhibited
clockwise yawing, whilst 8 out of 13 ZEN4-GNRs counterclockwise yawing. The directionalities of
yawing of these ZEN4-GNRs were not significantly different from an equal probability using
binomial test (*P* > 0.5).

Unidirectional rotation of microtubule on single ZEN4-GNR. Our proposed model, in which
kinesin-GNRs rotate around their yaw axes as they move along and around the microtubule long
axis, predicts that immobilized kinesin-GNRs might drive rotation of an overlying short microtubule
about both its long and short axes. To test the rotational motility of the kinesin-GNRs during
translation, we performed the surface-gliding assay for ZEN4-GNRs, in which ZEN4-GNR particles
were sparsely attached on the glass surface (3-8 particles per 100 μm^2) (Materials and Methods).
We found that the short microtubules unidirectionally rotated on ZEN4-GNRs while only their ends
were in contact with the GNRs (Fig. 6 and Movie S6). In the geometry of observation images, we
observed both counterclockwise rotation (*n* = 4 microtubules) and clockwise rotation (*n* = 4
microtubules). These observations also support a model in which kinesin-coated GNRs moving
along a microtubule are driven to undergo both helical and yaw-axis rotations.

Analysis of the kinesin-GNR motility by 2D ratchet mechanism. We found that the polarization
and helix pitches were comparable among KIF1A- and ZEN4-GNRs (0.7-0.8 μm) (*P* > 0.05 for
Welch's *t* test), despite substantial differences in their forward velocities (*P* < 0.01 for adjusted
pairwise comparisons using Welch's *t* test with the Holm method). The helix pitch is given by P_{Helix}
= $2\pi V_X/\omega_{Helix}$, where P_{Helix} is the pitch size of helix, V_X is the forward velocity, and ω_{Helix} is the angular
velocity in the *Y*-*Z*-plane. We see that the forward velocities are different among KIF1A- and ZEN4-

GNRs but the pitches are comparable, so that the ratios of V_X to ω_{Helix} are thus almost equal. This

means that the angular velocity of helical motion is directly proportional to the forward velocity for

two kinesin constructs, suggesting that the off-axis component is intrinsic to each power stroke.

This relationship can be well modeled by a 2D noise-driven ratchet mechanism, as proposed by

Mitra *et al*. for single-headed KIF1A(19). Based on this mechanism, we now consider how yawing

of the kinesin-coated GNRs influences its motility. Since a kinesin-coated GNR rotated 180° about

its yaw axis in one period of a helical trajectory with the helix pitch of about 700 nm, the GNR

rotates 2° ≈ 180°/(700 nm/8 nm) with 8 nm of forward displacement, which is equivalent to the

length of the tubulin dimer. The 2° rotation generates at most ±1 nm ≈ ±20~34 nm × tan(2°) of

lateral displacements of the kinesin molecules bound on the GNR (40 nm in diameter and 68 nm

in length) (Fig. 7A). Lateral displacement (*d*) of 1 nm is equivalent to 0.2 ≈ 1 nm/5.1 nm(29) in the

asymmetry factor (α) toward the off-axis, which would be sufficient to influence the noise-driven

ratchet mechanism (Fig. 7B). A recent discussion by Mitra et al. indicates that around 1 μm of a

helix pitch is reproduced by the 2D Brownian ratchet model with a slight off-axis asymmetry (α_Y =

0.53) relative to the on-axis asymmetry (α_X = 0.27)(19).

We evaluated the off-axis fluxes of three particles differing in their starting positions for diffusion

(−*d*, 0, +*d*) in the noise-driven ratchet model with asymmetry potentials (α) after $1/\gamma$ units of time(30)

(Materials and Methods):

$$J_0 = \frac{\gamma}{4}\left\{ \mathrm{erfc}\left[\frac{\alpha}{2}\sqrt{\gamma}\right] - \mathrm{erfc}\left[\frac{1-\alpha}{2}\sqrt{\gamma}\right]\right\} \tag{2}$$

$$J_{\pm d} = \frac{\gamma}{4}\left\{ \mathrm{erfc}\left[\frac{\alpha\mp d}{2}\sqrt{\gamma}\right] - \mathrm{erfc}\left[\frac{1-\alpha\pm d}{2}\sqrt{\gamma}\right]\right\} \tag{3}$$

where J_0 represents the flux of particles starting diffusion at 0 and $J_{\pm d}$ represents the flux of particles

starting diffusion at ±*d*. In calculations with α = 0.53 and γ = 160 s^{-1} (Materials and Methods), the

absolute values of J_{+d} and J_{-d} increased with d along a sigmoidal curve and the net flux, $J_{-d} + J_0 +$

J_{+d} described the convex downward function of which the value reached a minimum at *d* = 0.5 (Fig.

7C and 7D). Importantly, the slight displacement (*d* < 0.2) is sufficient to cause biased flux because

$|J_{-d}|$ is much larger than $|J_{+d}|$ (Fig. 7C, inset). These suggest that unidirectional rotation of a motor-

coated cargo enhances the sideward bindings of motor molecules toward the biased direction.

Monte Carlo simulation of motor team with torque generation. To further explore the

consequences of combined rotational and helical motion of kinesin-coated GNRs, we performed

simple Monte Carlo simulations of the two-state noise-driven ratchet model. In this simulation,

multiple particles, which are linked to a rigid body cargo with a spring, stochastically take biased

forward and/or sideward steps on the 2D lattice and generate torque to twist the spring and then

rotate the cargo when taking a step (Fig. 8A). Based on the force- and moment-balance equations,

the cargo moves and rotates around the center of the joint points connecting the particles in the

attached state (Materials and Methods). Additionally, the twist angle ($\Delta\theta$) of the cargo driven by the

torque generated by the particles taking a step is given by $\Delta\theta = (N_{step}\,\theta_{step} + b_\theta)/N_{on}$, where N_{step} is

the number of particles taking a step and generating a torque in a unit of time; N_{on} is the number of

particles bound to the rail in the unit of time; b_θ is the rotational diffusion of the cargo with a normal

distribution with zero mean and a standard deviation of σ_θ; θ_{step} is the twist angle of the spring driven

by the torque T_{step} generated by the single particle, assuming that θ_{step} is proportional to T_{step}

(Materials and Methods). Note that the rotational diffusion of the cargo (b_θ) is negligible for the

particle formation using Fig. 8 (Materials and Methods).

First, we optimized the parameters for the biased forward and sideward movement of the cargo

without torque generation ($\theta_{step} = 0$), matching the ~0.8-μm helix pitch of KIF1A and ZEN-4 in the

gliding assay, which is the ratio of forward steps to leftward steps (~100/13) (Fig. 8B). We note that

the simulation without torque generation often showed unidirectional rotation of the cargo, but the

period of rotation was irregular and uncorrelated with the 13-lattice period of the Y-displacements

modeled as the 13-protofilament microtubule. We then performed the simulation with torque

generation. When θ_{step} was approximately $-3°$ to $-4°$, the cargo exhibited periodical clockwise

rotation and the period of rotation closely matched the 13-lattice period (Fig. 8C and Fig. S7).

Correlation between counterclockwise rotation and sideward movement of the cargo was also

reproduced when θ_{step} was $+4°$ (Fig. S8). The lateral displacement in a calculation time in the

presence of torque ($\theta_{step} = -4°$) increased about 1.3-fold, compared with that in the absence of

torque ($\theta_{step} = 0°$). Taken together, the Monte Carlo simulations are consistent with the analysis by

the noise-driven ratchet model showing that unidirectional rotation of a motor-coated cargo

enhances the sideward bindings of motor molecules toward the biased direction (Fig. 7).

Discussion

We developed the GNR motility assay and harnessed it to analyses cargo rotations driven by

teams of single-headed KIF1A, dimeric ZEN-4. For these kinesins, ~20% of the kinesin-coated

GNRs showed periodic changes in the GNR polarization signal, phase locked to the orbit of the

GNR around the microtubule, over multiple orbital periods. For the remaining ~80% of records, we

did not observe periodic variation in the GNR polarization signals. The low probability of observation

suggests that stable periodic polarization rotations were observed only when the plane of yawing

of the kinesin-GNRs about its short axis was nearly parallel to the longitudinal axis of the

microtubule. Due to the relatively low aspect ratio of the GNRs we used, the elevation angles of

the long axis of the kinesin-GNRs might tend to change, resulting in unstable polarization

fluctuations in the majority of the kinesin-GNRs. However, GNRs with higher aspect ratio may

inhibit yawing of the kinesin-GNR, since the parallel longitudinal axis alignment of the kinesin-

coated GNR and the microtubule is most stable in terms of the number of kinesin molecule
interacting with the microtubule.

In the GNR assay experiments, each kinesin-coated GNR exhibited specific directionality of
yawing, which is consistent with previous single-molecule measurements for the kinesin-1 dimer[9].
Although the detailed mechanism of directional yawing of a kinesin team remains unclear, not only
the power stroke in the motor domain but also the formation of kinesin molecules on the GNR and
further the configuration of the kinesin-GNR and the microtubule might be involved.

A recent single-molecule study of the kinesin-1 dimer construct revealed that it unidirectionally
rotates the stalk domain by ~1° with 8-nm steps at high ATP conditions and in the presence of an
external force[9]. Therefore, the estimated θ_{step} of 4° might be reasonable especially in the absence
of an external force. Previous structural studies of kinesin-1 and KIF1A revealed that
rearrangement in the motor domain from the pre-stroke state to the post-stroke state generates
global rotation of the motor domain[31–33]. The rotation of the kinesin motor domain may generate
a torque (Supplementary text). The neck-to-tail region is critical for torque transmission from the
head domain to the cargo. In the case of ZEN-4, its neck domain contains a non-canonical long
sequence; however, high-speed AFM imaging of a ZEN-4 dimer revealed a distinctive globular
mass in the neck region[34]. Thus, the non-canonical neck-domain of ZEN-4 may be a stiffness
component rather than a flexible linker.

Ideas and speculations. Previous studies proposed that sideward stepping of kinesins and dynein
allows them to bypass roadblocks on a microtubule[6–8, 11, 13, 35]. We further performed Monte
Carlo simulations of bypassing of a roadblock with various multiple-motor motilities, especially
changing the two parameters: the off-axis asymmetry, α_Y, and the torque generation, θ_{step} (Fig. 8D
and Materials and Methods). The simulation results in the case of α_Y = 0.5 and θ_{step} = 0° showed
that the motor team failed to bypass it within the calculation time (Fig. 8D, the most left), whilst the
off-axis asymmetry (α_Y = 0.58 and θ_{step} = 0°) allow to avoid the roadblock (Fig. 8D, second from the
left). Moreover, the simulation results in the case of α_Y = 0.5 and θ_{step} = −4° indicate that the
rotational motility also helps the motor team avoid the roadblock (Fig. 8D, second from the right).
Interestingly, the motors with off-axis asymmetry (α_Y = 0.58) and torque generation (θ_{step} = −4°)
exhibited a 'spin move' (i.e., a combination of spinning and sideward motion), and further increased
the probability of bypassing the roadblock (Fig. 8D, the most right). The evasion time by the spin
move was 2.6-fold faster than that by only sideward stepping. Our theoretical analyses with a noise-
driven 2D ratchet model and Monte Carlo simulations showed that unidirectional rotation enhances
the biased sideward movement of kinesin-bound cargo and further that the evasion time by the
spin move was faster than that by only sideward stepping. Therefore, the spin move of a kinesin
team may help sustained transport of a cargo in situations where the microtubule lattice is crowded

with microtubule associated proteins, motor proteins, and other lattice-binders. Rotational and translational dynamics of endosomes in cells are not always correlated(36). Distinct changes in the rotational state of endosomes during pausing in translational motion(36) may be related to the spin move of a motor team during sidestepping an obstacle.

In summary, this study reveals that in kinesin teams, the production of torque drives not only orbital motion of the kinesin team around the microtubule axis, but also coupled yaw-axis rotation of the team and its attached cargo. We propose based on quantitative simulations that this combination of properties enables cargos bound to multiple kinesins more efficiently to bypass roadblocks. Our work provides new insights into the structural basis of kinesin motor stepping(33, 37) and into the implications of their translational and rotational degrees of freedom for their cellular function(36).

Materials and Methods

Gold nanorod imaging. Fig. 1A shows a schematic drawing of the laser dark-field microscope system used for gold nanorod (GNR) imaging. The laser dark-field optical system was constructed on an inverted microscope (Ti; Nikon, Tokyo, Japan), equipped with variable-angle epi-illumination(21, 22) and a custom-built perforated dichroic mirror (PDM) (Sigma Koki, Tokyo, Japan). The PDM had an elliptical hole (short axis = 6 mm; long axis = 8.5 mm) at its center position, which made a circular window when viewed from the optical axis. The scattered light from the GNRs was transmitted through this central circular window. Illumination was performed using a 635-nm diode laser (MRL-III-635L-10mW; CNI laser, Changchun, China), which was further attenuated by neutral density filters (ND) and converted to circularly polarized light by a quarter-wave plate (WPQ-6328-4M; Sigma Koki, Tokyo, Japan). The collimated and circularly polarized incident beam was focused by a lens (L1 in Fig. 1A, f = 220 mm) onto the back focal plane of the objective lens (PlanApo N, 60×, NA 1.42; Olympus, Tokyo, Japan). GNR images were obtained by laser dark-field imaging using highly inclined illumination with nearly total internal reflection angle. The back focal plane was focused outside a camera port of the microscope with an achromatic lens (L3 in Fig. 1A, f = 60 mm) to make an equivalent back focal plane for constructing the optics for polarization measurements and 3D tracking.

For polarization measurements, the scattered light from a GNR illuminated by polarized incident beam was further split into two orthogonally polarized components by a polarization beam displacer (BD40; Thorlabs, Tokyo, Japan), which was set in the optical path between the relay optics constructed by two lenses (L3 (f = 60 mm) and L4 (f = 120 mm) in Fig. 1A)(38). Two separated and polarized light beams were imaged as two spots on a CMOS camera (LDH2500; Digimo, Tokyo,

Japan). The orientations of the two orthogonally separated polarization components of the beam

displacer were diagonal relative to the transmission axis of the polarization filter. For angular

calibration, a linear polarizer was additionally set at the position between L2 and L3 and rotated

from 0° to 180° in 10° intervals (Fig. 1B).

For 3D tracking, concave and convex cylindrical lenses (CnC (f = −200 mm) and CvC (f = 200

nm)) were set in front of the camera(24). The interval between CnC and CvC was 13 mm.

Calibration of 3D tracking along the Z-axis was performed by moving the objective in 50-nm

intervals (Fig. S1), using a custom-built stage equipped with a pulse motor (SGSP-13ACT; Sigma

Koki, Tokyo, Japan) and a controller (QT-CM2; Chuo Precision Industrial, Tokyo, Japan). We

analyzed the widths of the GNR spots along the X-axis (S_X) and the Y-axis (S_Y) obtained by 2D-

Gaussian fits. The calibration factor for the z-displacement obtained from the ratio of S_Y to S_X was

0.98 μm/ratio.

The temperature of the sample stage was controlled using a custom-built water-circulating

temperature control system. Image acquisition in the GNR motility assay was performed at 100

frames/s with the commercial software for the CMOS camera (Digimo, Tokyo, Japan). The data

were saved as eight-bit AVI files. The effective pixel size of the detector was 42 nm. Image analysis

and further analyses were performed using custom software written in LabVIEW (National

instruments, Tokyo, Japan).

Polarization measurements. For polarization measurements, the scattered light from a GNR

illuminated by polarized incident beam was split into two polarized components by the polarization

beam displacer as mentioned above. Thus, the intensities of two polarized GNR spots as functions

of the GNR orientation (θ) are expressed by

$$I_{\text{bottom}} = I_0 \cdot \cos^2(\theta + \zeta) \cdot \cos^2(\theta + \zeta - \eta) + b \tag{4}$$

$$I_{\text{upper}} = I_0 \cdot \cos^2(\theta + \zeta) \cdot \cos^2(\theta + \zeta - \eta + \pi/2) + b \tag{5}$$

where I_0 is the amplitude; θ is the GNR orientation in the sample plane; ζ and η are phase angles

of polarization of the incident beam in the sample plane and the beam displacer, respectively; and

b is the background intensity. The observed intensity profiles in Fig. 1B were well fitted by these

functions with I_0 = 127.5 ± 3.3, ζ = 99.3° ± 0.8°, η = 45.3° ± 0.7°, and b = 19.5 ± 0.9. GNR angles

in the sample plane were obtained by fitting an ellipse function to the plot of the degree of

polarization ($I_{\text{bottom}} - I_{\text{upper}}$)/($I_{\text{bottom}} + I_{\text{upper}}$) as a function of the summed-intensity ($I_{\text{bottom}} + I_{\text{upper}}$), as

shown in Fig. 1B.

Kinesin constructs. In all kinesin constructs used in this study, the functional sequence Avi-His,

which consists of the Avi-tag (GLNDIFEAQKIEWHE) for biotinylation and the 6×His-tag for

histidine-affinity purification, was fused to the C-terminus of truncated kinesin domains. For the

monomeric KIF1A construct, the fragment of human KIF1A (1–366 amino acid residues (AAs))
obtained from a human cDNA library was cloned into eGFP-Avi-His/pColdIII plasmids. eGFP
stabilized the solubility of the truncated KIF1A sample. In addition, for the surface-gliding assay of
the KIF1A construct, we used the construct of human KIF1A (1–366 AAs) cloned into mRuby-Zdk1-
His/pColdIII plasmids. For the dimeric ZEN-4 construct, the fragment of C. elegans ZEN-4 (1–555
AAs) obtained from CBD-TEV-ZEN4/pGEX-6p plasmids(34) was cloned into Avi-His/pET32a
plasmids. For the monomeric and dimeric kinesin-1 constructs, the fragments of rat kinesin-1 (1–
430 AAs for the dimeric constructs(27)) were cloned into Avi-His/pColdIII plasmids. All constructs
were verified by DNA sequencing.
395
Expression and purification of kinesin. For expression and purification of the kinesin constructs,
the proteins were expressed in *Escherichia coli* strain BL21 Star (DE3) cells using 0.4 mM
Isopropyl-β-D-thiogalactopyranoside (IPTG) (Sigma) for 9 to12 hours at 20 °C. The collected cells
were lysed in lysis buffer (50 mM potassium phosphate; pH 7.4, 350 mM NaCl, 1 mM $MgCl_2$, 10
μM ATP, 1 mM DTT, 0.1% Tween20, 10% glycerol, protease inhibitors, 50 mM imidazole) and
sonicated in iced water for 15 minutes. The bacterial lysate was centrifuged for 20 minutes at
260,000g at 4 °C to remove cell debris and insoluble proteins. The clarified supernatant was purified
with the His-tag affinity by chromatography with a HisTrap HP Ni^{2+}sepharose column (GE
Healthcare). The collected peak fraction was further purified through a HiTrap desalting column
(GE Healthcare) to exchange the buffer (20 mM potassium phosphate; pH 7.4, 1 mM $MgCl_2$, 1 mM
DTT, 10 μM ATP) containing 80 mM NaCl for the KIF1A and the kinesin-1 constructs, or 250 mM
NaCl for the ZEN-4 construct.
For the KIF1A construct, we further purified the active proteins based on their affinity for
microtubules. KIF1A and microtubules were mixed and incubated for 15 minutes in the presence
of 1 mM AMPPNP. The mixture was centrifuged for 20 minutes at 260,000g at 25 °C to remove
unbound KIF1A molecules. The pellet was resuspended in ATP-containing buffer (20 mM PIPES-
KOH; pH 7.4, 5 mM $MgCl_2$, 10 mM potassium acetate, 250 mM NaCl, 20 μM paclitaxel, 5 mM ATP)
and incubated for 15 minutes at 23 °C for detachment of KIF1A molecules from the microtubules.
Microtubules were removed by centrifugation (260,000g, 15 minutes, 23 °C).
The purified proteins were flash-frozen and stored in liquid nitrogen. The concentration of
proteins was estimated using the Bradford method with the use of BSA as a standard.
417
418 **Purification of tubulin.** Tubulin was purified from porcine brains through four cycles of
419 temperature-regulated polymerization and depolymerization in a high-molarity PIPES buffer to
420 remove contaminating MAPs(39). The purified tubulin was flash-frozen and stored in liquid nitrogen.
421

Preparation of Cy5-microtubules. Tubulin stock solution (~6 mg mL^{-1}, 50 μL) and Cy5-labelled

tubulin solution (~20 mg mL^{-1}, 1 μL, ~50% labelled) were mixed on ice and then diluted twofold

with chilled BRB80 buffer (80 mM PIPES-KOH; pH 6.8, 1 mM MgCl$_2$, 1 mM EGTA). One microliter

each of GTP (100 mM), and MgCl$_2$ (100 mM) was added to the diluted tubulin solution. The tubulin

solution was incubated at 37 °C for 1 hour for polymerization and stabilized with 20 μM paclitaxel.

The Cy5-microtubules were further purified by centrifugation. Ray et al. reported that polymerization

in PIPES buffer results in ~60% of 14-protofilament microtubules and ~30% of 13-protofilament

microtubules(40).

Preparation of protein-G-coated beads and streptavidin-coated gold nanorods. For

preparation of protein G-coated beads, carboxylate-modified fluorescent microbeads (0.5 μm;

Thermo Fisher Scientific, USA) were diluted in the activation buffer (100 mM MES; pH 6.0). EDC

and sulfo-NHS were added to the bead solution and incubated for 15 minutes at room temperature.

The beads were then washed with 100 mM HEPES buffer at pH 8.0. Protein-G was then added to

the bead solution and reacted for 2 hours at room temperature. Any unreacted amine reactive

groups were quenched by adding excess glycine. Excess proteins were removed by centrifugation

(21,000*g*, 15 minutes, 23 °C). The beads were resuspended in BRB80 buffer.

For preparation of streptavidin-coated GNRs, biotin-labelled GNRs (5 nM) (C12-40-600-TB;

Nanopartz, CO, USA) and streptavidin (5 mg mL^{-1}) were mixed. After 15 minutes' incubation,

excess streptavidin was removed by centrifugation (4,000*g*, 3 minutes, 23 °C) and then the pellet

was resuspended in Milli-Q water and sonicated for 2 s. The procedure for removing excess

streptavidin was repeated twice.

GNR motility assays. Streptavidin-coated GNR (2 μL, 5 nM) and kinesin sample (2 μL, 1-2 μM)

were mixed and incubated for at least 15 minutes at room temperature. For the assay of KIF1A, 2

μL of 0.2% Tween20 was further added to the mixture of kinesin and GNR. For the assay for ZEN-

4, 0.5 μL of 5 M NaCl and 2 μL of 0.2% Tween20 were further added to the mixture of kinesin and

GNR.

A flow chamber (sample volume of about 5 μL) was prepared using two coverslips (24 mm × 32

mm and 18 mm × 18 mm) stuck by double-sided tape. Protein-G-coated bead solution was

nonspecifically absorbed to the coverslip. After 3 minutes' incubation, the flow chamber was

washed with 20 μL of 1 mg mL^{-1} BSA and further incubated for 3 minutes. The flow chamber was

washed with 20 μL of BRB80. Then, 10 μL of 20 μg mL^{-1} anti-β -tubulin antibody solution (sc-58884;

Santa Cruz, USA) was flowed to the flow chamber. After 3 minutes' incubation, the flow chamber

was washed with 20 μL of BRB80. Then, 10 μL of Cy5-lablled microtubule solution (~2 μM tubulin

concentration) was flowed into the flow chamber such that the microtubules bound to the beads

(Fig. 1C). After 3 minutes' incubation, the flow chamber was washed with 20 μL of 1 mg mL^{-1}

casein. After 3 minutes' incubation, the flow chamber was washed with 20 μL of the motility buffer

(20 mM PIPES-KOH; pH 7.4, 4 mM MgCl$_2$ and 10 mM potassium acetate) containing the kinesin-

coated GNRs (~100 pM), ATP (2 mM), the ATP regeneration system (0.8 mg mL^{-1} creatine kinase,

10 mM creatine phosphate), the oxygen scavenger system (3 mg mL^{-1} glucose, 50 U mL^{-1} glucose

oxidase, 1200 U mL^{-1} catalase), and 1 mg mL^{-1} casein. The GNR assays were performed at 27 °C.

Image acquisition was performed at 100 frames s^{-1}.

Surface-gliding assays for KIF1A with QD-coated microtubules. Qdot525 (QD)-coated and

Cy5-labelled microtubules were prepared as previously described(18). The surface-gliding assays

were performed in flow chambers assembled from two coverslips attached using double-sided

tapes. Before the assay, kinesin stock solution was diluted to 1 μM with motility buffer. Five

microliters of a 5 mg mL^{-1} solution of protein G (Sigma-Aldrich, Tokyo, Japan) was added to the

flow chamber (about 5 μL). After 5 minutes' incubation, the flow chamber was washed with 20 μL

of BRB80 buffer, followed by another 5 minutes of incubation with 5 μL of 0.05 mg mL^{-1} anti-His-

tag antibody. The flow chamber was washed with 20 μL of BRB80 buffer, and then 5 μL of 0.5 mg

mL^{-1} casein solution was added. After 5 minutes' incubation, the flow chamber was washed with

20 μL of BRB80 buffer. Then, 10 μL of KIF1A solution (1 μM) was added to the flow chamber. The

flow chamber was then washed with 20 μL of BRB80 after 5 minutes' incubation, and 20 μL of QD-

coated microtubule solution (0.05-0.1 μM tubulin) was added to the flow chamber. Finally, the flow

chamber was washed with 20 μL of BRB80 buffer after 5 minutes' incubation, and 20 μL of motility

buffer containing 3 mM ATP, 20 μM paclitaxel, 0.5% β-mercaptoethanol, 0.25 mg mL^{-1} casein, ATP

regeneration and oxygen scavenger systems were added. Fluorescent images of the QD- and Cy5-

labelled microtubules were captured using TIRF microscopy at 25 °C. Corkscrewing pitches in the

surface-gliding assay were determined by measuring the longitudinal displacement of the QDs in

each period of oscillation of the lateral displacement along the microtubule axis.

Surface-gliding assays for ZEN4-GNR. Preparations of Cy5-labelled microtubules and ZEN4-

GNR were prepared as described above. Surface-gliding assays were performed in flow chambers

assembled from two coverslips attached using double-sided tape. The ZEN4-GNR solution was

diluted to ~50 pM with motility buffer and added to the flow chamber (about 5 μL). After 5 minutes'

incubation, the flow chamber was washed with 20 μL of BRB80 buffer, followed by 5 minutes'

incubation with 10 μL of 0.5 mg mL^{-1} casein solution. The flow chamber was then washed with 20

μL of BRB80 buffer, and 20 μL of Cy5-labelled microtubule solution (2 mM ATP, Cy5-labelled

microtubules, 0.25 mg mL^{-1} casein, and ATP regeneration and oxygen scavenger systems in

motility buffer) were added. The assays were performed at 27 °C. Image acquisition of the Cy5-

labelled microtubules was performed at 10 frames s^{-1}.

Quantification and statistical analysis. Polarization and position data of the observed kinesin-

coated GNRs were obtained by image analysis with software written in LabVIEW (National

instruments, Tokyo, Japan). Velocities of the kinesin-coated GNRs were determined by fitting the

trace of the longitudinal displacement along the microtubule axis (*X*-direction) with a linear function.

Rotation and helix pitches in the GNR assays were determined by measuring the *X*-displacements

in the periods of oscillations of the angle- and *Y*-trajectories, respectively. Statistical hypothesis

testing was performed using *R* statistical software.

Correction of the measured pitch. The measured pitch (P_{Measured}) comprised two helical

elements: the helix pitch exerted by motors (P_{Motor}) without supertwist of the microtubule, and the

supertwist of the microtubule depending on the number of the protofilaments (P_{MT}). P_{Measured} is given

by

508
$$\frac{1}{P_{\text{Measured}}} = \frac{1}{P_{\text{Motor}}} + \frac{1}{P_{\text{MT}}} \tag{6}$$

The PMT of 12-, 13-, and 14-protofilament microtubules is estimated to be about −3.4, −24.8, and

6.8 μm, respectively (we assign a positive value to the pitch in the left-handed helix)(40). When the

absolute value of P_{Measured} is much smaller than the absolute value of P_{MT} (< ~1 μm), P_{Motor} is not

appreciably changed by the supertwist (Fig. S4).

Mathematical model of helical and rotational motion of a kinesin-coated GNR on a

microtubule. The GNR motility assay revealed that KIF1A-, ZEN4-, and sK1-GNRs unidirectionally

rotate about the GNR's short axis, moving along the left-handed helix track. The helix track of the

center position of a GNR is given by

518
$$helix(X(t), Y(t), Z(t)) = (vt, h \cdot \cos(\pi/2 - \omega_{\text{Helix}}t), h \cdot \sin(\pi/2 - \omega_{\text{Helix}}t)) \tag{7}$$

519   where *v* is the translational velocity along the *X*-axis, ω_{Helix} is the angular velocity in the *Y*-*Z*-plane,

520   and *h* is the radius of the helix. Assuming that the long axis of the GNR is parallel to the *X*-*Y*-plane

521   under the initial conditions, the initial position matrix p_0 consisting of the tip, center, and end

522   positions of the GNR is given by

523
$$p_0(\text{tip, center, end}) = \begin{pmatrix} r \cdot \cos(\varphi) & 0 & r \cdot \cos(\varphi + \pi) \\ r \cdot \sin(\varphi) & 0 & r \cdot \sin(\varphi + \pi) \\ 0 & 0 & 0 \end{pmatrix} \tag{8}$$

524   where *r* is the radius along the long axis of the GNR and φ is its phase angle. Because a kinesin-

525   coated GNR unidirectionally rotates about its short axis and further around the microtubule, the

526   resultant rotation comprises yawing and rolling. We assume that a kinesin-coated GNR would not
527   rotate about the pitch axis. Matrices of yawing and rolling are given by

528
$$R_{\text{Yaw}}(\omega_{\text{Yaw}}t) = \begin{pmatrix} \cos(\omega_{\text{Yaw}}t) & -\sin(\omega_{\text{Yaw}}t) & 0 \\ \sin(\omega_{\text{Yaw}}t) & \cos(\omega_{\text{Yaw}}t) & 0 \\ 0 & 0 & 1 \end{pmatrix}$$
(9)

529
$$R_{\text{Roll}}(\omega_{\text{Roll}}t) = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos(\omega_{\text{Roll}}t) & -\sin(\omega_{\text{Roll}}t) \\ 0 & \sin(\omega_{\text{Roll}}t) & \cos(\omega_{\text{Roll}}t) \end{pmatrix}$$
(10)

530   where ω_{Yaw} and ω_{Roll} are the angular velocities of yawing and rolling, respectively. Taken together,
531   the helical and rotational trajectory of a motor-coated GNR is written as

532
$$R_{\text{Roll}}(\omega_{\text{Roll}}t)R_{\text{Yaw}}(\omega_{\text{Yaw}}t)p_0 + helix(t)$$
(11)

By calculating $R_{\text{Roll}}R_{\text{Yaw}}p_0$, the time trajectory of the GNR orientation in the X-Y-plane is obtained
(Equation (1)). Our analyses indicate that kinesin-coated GNRs rotate 180° in one period of the
helix. This is the case of $\omega_{\text{Helix}} = \omega_{\text{Roll}} = \pm 2\omega_{\text{Yaw}}$. The calculated helical and rotational trajectories of
a kinesin-coated GNR and the time trajectories of the GNR orientation with different phase angles
are shown in Fig. 4, Fig. S6, and Movies S2, S4, and S5.

Evaluation of particle flux in the noise-driven ratchet model. The previous study by Astumian
and Bier(30) clarified the particle flux in the two-state, noise-driven ratchet model. Following their
discussions, we evaluated the particle flux for different start positions, because sideward
translations (±d) of motors takes place owing to the rotation of their cargo (see Fig. 7A). In the two-
state ratchet model, when the barrier moves to the down state, the particles start to diffuse. The
probability density function of a diffusing particle at the start position of +d in the X-direction is given
by

546
$$P_{+d}(x;t) = \frac{1}{2\sqrt{\pi t}}\exp\left[-\frac{(x-d)^2}{4t}\right]$$
(12)

547   After $1/\gamma$ units of time, the probability that the particle is located to the right of α is given by

548
$$\int_{\alpha}^{\infty} P_{+d}(x;1/\gamma)\,dx = \frac{\gamma}{4}\text{erfc}[\frac{\alpha-d}{2}\sqrt{\gamma}]$$
(13)

549   and the probability that it on the left of $-1+\alpha$ is given by

550
$$\int_{-\infty}^{-1+\alpha} P_{+d}(x;1/\gamma)\,dx = \frac{\gamma}{4}\text{erfc}[\frac{1-\alpha+d}{2}\sqrt{\gamma}]$$
(14)

The particle flux, J_{+d} (Equation (3)) is given by equation (13) and equation (14). Similarly, J_{-d}
(Equation (3)) and J_0 (Equation (2)) are also obtained.
Following the probability density function of a diffusing particle, the standard deviation of diffusion
is given by $\sqrt{2/\gamma}$. When γ is 160 s^{-1}, $\sqrt{2/\gamma} \approx 0.11$, which is equal to the value of σ in the Monte
Carlo simulations (see below).

Monte Carlo simulations. We performed Monte Carlo simulations to model the observed

rotational and helical motion. In the simulation, each particle is linked to a rigid body as a cargo

with a spring (spring constant, k) and the joint points linking the particles and the cargo are fixed.

The particles stochastically attach and dissociate from the rail (on-time constant, τ_{on}; off-time

constant, τ_{off}). A detached particle diffuses around the joint point (standard deviation of diffusion,

σ) in the X-Y-plane. When the diffusing particle overrides the asymmetric barrier (asymmetric

factors, α_X and α_Y) at the last time of diffusion, the particle takes a step in the X-Y-direction. The

force- and moment-balance equations are given by $\sum_{i}^{Non} k\vec{d_i} = 0$ and $\sum_{i}^{Non} k\vec{d_i} \times \vec{l_i} = 0$, where k is

the spring constant; $\vec{d_i}$ is an extension vector of the spring of the i-th particle that is bound to the

rail; $\vec{l_i}$ is the position vector of the i-th joint relative to the center of the joint points connecting the

particles that are bound to the rail; and N_{on} is the number of the particles bound to the rail. In the

simulation, $\vec{d_i}$ is the displacement between the i-th particle and the i-th joint position. Furthermore,

torque rotating the cargo is exerted by the particle when it takes a step. A twist angle ($\Delta\theta$) of the

cargo by the torque generated by the particle taking a step is given by $\Delta\theta = (N_{step}\theta_{step} + b_\theta)/N_{on}$, and

$\theta_{step} = T_{step}L/KG$, where N_{step} is the number of particles taking steps; N_{on} is the number of particles

bound to the rail; θ_{step} is the twist angle of the spring; b_θ is the rotational diffusion of the cargo as a

normal distribution with zero mean and a standard deviation of σ_θ; T_{step} is the torque force generated

by the single particle; L is the length of the spring; G is the modulus of rigidity of the spring; and K

is the polar moment of inertia of area of the spring. We thus assume that the twist angle θ_{step} is

proportional to the torque force T_{step}. The value of θ_{step} as the torque force was given in the

simulation. After calculating the force and moment balance equations, the cargo additionally rotates

$\Delta\theta$ degrees about the center of the joint points connecting the particles that are bound to the rail.

A roadblock in the simulation allowed the off-state particles to diffuse above it, whereas the on-

state particles could not attach to the roadblock except at its edges. We used the roadblock with a

width of 40 lattices and a length of 30 lattices.

The simulation was developed in LabVIEW (National Instruments). LabVIEW source code and

executable software for the Monte Carlo simulations used in this study are available from GitHub

(https://github.com/MitsuSGW/MonteCarlo-MotorTeam-Sim.git). The values for the parameters

used in the simulation were: τ_{on} = 40 units of time; τ_{off} = 10 units of time; α_X = 0.12 units of lattice

size; α_Y = 0.58 units of lattice size; σ = 0.11 units of lattice size; θ_{step} = 4°; b_θ = 0. The value of σ

was determined by the evaluation of particle flux in the noise-driven ratchet model mentioned in

the previous subsection. The rotational diffusion of the cargo (b_θ) is negligible in the case of the

particle formation used in Fig. 8 (Fig. S9).

Statistical analysis. Statistical analysis of two groups was performed with Welch's two-tailed t

test. Statistical analysis to compare the observed frequencies of two categories was performed with

two-sided binomial test of the null hypothesis that the probability of success in a Bernoulli

experiment is 0.5. $P < 0.05$ was considered as statistically significant. Values are represented as

means ± SD as indicated in the figures.

Author Contributions: M.S. and J.Y. designed research; M.S. performed experiments, analyzed

data, and performed simulations; Y.M., and M.Y. contributed new reagents; M.S., R.A.C. and J.Y.

wrote the paper.

Competing Interest Statement: Authors declare that they have no competing interests.

Acknowledgments: CBD-TEV-ZEN4/pGEX-6p plasmid was a gift from Prof. Masanori Mishima.

We thank Prof. TOYOSHIMA Y. Yoko and SAITO Kei for critical discussion; Adam Brotchie, PhD,

from Edanz Group (www.edanzediting.com/ac) for editing a draft of this manuscript. This work is

supported by Ministry of Education, Culture, Sports, Science and Technology Japan (MEXT)

grants KAKENHI JP19K06593 and JP19H03190 (to M.S.), JP20K06635 (to J.Y.): MEXT grants

KAKENHI Grant-in-Aid for Scientific Research on Innovative Areas JP21H00386 and

JP21H05868 (to J.Y.): Research Foundation for Opto-Science and Technology Japan (to M.S).

References

1. R. D. Vale, The molecular motor toolbox for intracellular transport. *Cell* **112**, 467–480 (2003).

2. N. Hirokawa, Y. Noda, Y. Tanaka, S. Niwa, Kinesin superfamily motor proteins and intracellular transport. *Nat. Rev. Mol. Cell Biol.* **10**, 682–696 (2009).

3. K. J. Verhey, J. W. Hammond, Traffic control: Regulation of kinesin motors. *Nat. Rev. Mol. Cell Biol.* **10**, 765–777 (2009).

4. J. Yajima, K. Mizutani, T. Nishizaka, A torque component present in mitotic kinesin Eg5 revealed by three-dimensional tracking. *Nat. Struct. Mol. Biol.* **15**, 1119–21 (2008).

5. B. Nitzsche, F. Ruhnow, S. Diez, Quantum-dot-assisted characterization of microtubule rotations during cargo transport. *Nat. Nanotechnol.* **3**, 552–556 (2008).

6. M. Brunnbauer, *et al.*, Torque Generation of Kinesin Motors Is Governed by the Stability of the Neck Domain. *Mol. Cell* **46**, 147–158 (2012).

7. M. Bugiel, E. Schäffer, Three-Dimensional Optical Tweezers Tracking Resolves Random Sideward Steps of the Kinesin-8 Kip3. *Biophys. J.* **115**, 1993–2002 (2018).

8. A. Mitra, F. Ruhnow, S. Girardo, S. Diez, Directionally biased sidestepping of Kip3/kinesin-8 is regulated by ATP waiting time and motor–microtubule interaction strength. *Proc. Natl. Acad. Sci.* **115**, E7950–E7959 (2018).

9. A. Ramaiya, B. Roy, M. Bugiel, E. Schäffer, Kinesin rotates unidirectionally and generates torque while walking on microtubules. *Proc. Natl. Acad. Sci.* **114**, 10894–10899 (2017).

10. A. Yildiz, M. Tomishige, A. Gennerich, R. D. Vale, Intramolecular strain coordinates kinesin stepping behavior along microtubules. *Cell* **134**, 1030–41 (2008).

11. Y. Maruyama, *et al.*, CYK4 relaxes the bias in the off-axis motion by MKLP1 kinesin-6. *Commun. Biol.* **4** (2021).

12. X. Pan, S. Acar, J. M. Scholey, Torque generation by one of the motor subunits of heterotrimeric kinesin-2. *Biochem. Biophys. Res. Commun.* **401**, 53–57 (2010).

13. V. Bormuth, *et al.*, The highly processive kinesin-8, Kip3, switches microtubule protofilaments with a bias toward the left. *Biophys. J.* **103**, L4–L6 (2012).

14. R. A. Walker, E. D. Salmon, S. A. Endow, The Drosophila claret segregation protein is a minus-end directed motor molecule. *Nature* **347**, 780–782 (1990).

15. B. Nitzsche, *et al.*, Working stroke of the kinesin-14, ncd, comprises two substeps of different direction. *Proc. Natl. Acad. Sci.* **113**, E6582–E6589 (2016).

16. A. Mitra, *et al.*, Kinesin-14 motors drive a right-handed helical motion of antiparallel microtubules around each other. *Nat. Commun.* **11**, 1–11 (2020).

17. J. Yajima, R. A. Cross, A Torque Component in the Kinesin-1 Power Stroke. *Nat. Chem. Biol.* **1**, 338–341 (2005).

18. M. Yamagishi, S. Fujimura, M. Sugawa, T. Nishizaka, J. Yajima, N-terminal β-strand of
single-headed kinesin-1 can modulate the off-axis force-generation and resultant rotation
pitch. *Cytoskeleton* **77**, 351–361 (2020).

19. A. Mitra, *et al.*, A Brownian ratchet model explains the biased sidestepping of single-
headed kinesin-3 KIF1A. *Biophys. J.* **8**, 1–9 (2019).

20. M. Yamagishi, Y. Maruyama, M. Sugawa, J. Yajima, Characterization of the motility of
monomeric kinesin-5/Cin8. *Biochem. Biophys. Res. Commun.* **555**, 115–120 (2021).

21. C. A. Konopka, S. Y. Bednarek, Variable-angle epifluorescence microscopy: A new way to
look at protein dynamics in the plant cell cortex. *Plant J.* **53**, 186–196 (2008).

22. M. Tokunaga, N. Imamoto, K. Sakata-Sogawa, Highly inclined thin illumination enables
clear single-molecule imaging in cells. *Nat. Methods* **5**, 159–61 (2008).

23. H. Ueno, *et al.*, Simple dark-field microscopy with nanometer spatial precision and
microsecond temporal resolution. *Biophys. J.* **98**, 2014–2023 (2010).

24. T. M. Watanabe, *et al.*, Four-dimensional spatial nanometry of single particles in living
cells using polarized quantum rods. *Biophys. J.* **105**, 555–564 (2013).

25. Y. Okada, N. Hirokawa, A processive single-headed motor: Kinesin superfamily protein
KIF1A. *Science.* **283**, 1152–1157 (1999).

26. A. Hutterer, M. Glotzer, M. Mishima, Clustering of Centralspindlin Is Essential for Its
Accumulation to the Central Spindle and the Midbody. *Curr. Biol.* **19**, 2043–2049 (2009).

27. J. Yajima, M. C. Alonso, R. a Cross, Y. Y. Toyoshima, Direct long-term observation of
kinesin processivity at low load. *Curr. Biol.* **12**, 301–6 (2002).

28. E. Berliner, E. C. Young, K. Anderson, H. K. Mahtani, J. Gelles, Failure of a single-headed
kinesin to track parallel to microtubule protofilaments. *Nature* **373**, 718–721 (1995).

29. D. Chrétien, S. D. Fuller, Microtubules switch occasionally into unfavorable configurations
during elongation. *J. Mol. Biol.* **298**, 663–676 (2000).

30. R. D. Astumian, M. Bier, Fluctuation driven ratchets: Molecular motors. *Phys. Rev. Lett.*
72, 1766–1769 (1994).

31. M. Kikkawa, N. Hirokawa, High-resolution cryo-EM maps show the nucleotide binding
pocket of KIF1A in open and closed conformations. *EMBO J.* **25**, 4187–4194 (2006).

32. L. Cao, *et al.*, The structure of apo-kinesin bound to tubulin links the nucleotide cycle to
movement. *Nat. Commun.* **5** (2014).

33. W. Hwang, M. J. Lang, M. Karplus, Kinesin motility is driven by subdomain dynamics.
eLife **6**, 1–25 (2017).

34. T. Davies, *et al.*, CYK4 Promotes Antiparallel Microtubule Bundling by Optimizing MKLP1
Neck Conformation. *PLoS Biol.* **13**, 1–26 (2015).

35. S. Can, M. a Dewitt, A. Yildiz, Bidirectional helical motility of cytoplasmic dynein around

microtubules. *eLife*, e03205 (2014).

36.   L. Kaplan, A. Ierokomos, P. Chowdary, Z. Bryant, B. Cui, Rotation of endosomes
demonstrates coordination of molecular motors during axonal transport. *Sci. Adv.* **4**
(2018).

37.   W. Hwang, M. J. Lang, M. Karplus, Force generation in kinesin hinges on cover-neck
bundle formation. *Structure* **16**, 62–71 (2008).

38.   S. Enoki, *et al.*, High-Speed Angle-Resolved Imaging of a Single Gold Nanorod with
Microsecond Temporal Resolution and One-Degree Angle Precision. *Anal. Chem.* **87**,
2079–2086 (2015).

39.   M. Castoldi, A. V Popov, Purification of brain tubulin through two cycles of polymerization-
depolymerization in a high-molarity buffer. *Protein Expr. Purif.* **32**, 83–8 (2003).

40.   S. Ray, E. Meyhöfer, R. A. Milligan, J. Howard, Kinesin follows the microtubule's
protofilament axis. *J. Cell Biol.* **121**, 1083–1093 (1993).

    Figures and Tables

    Figure 1. GNR motility assay. (**A**) Schematic drawing of the optics for the gold nanorod (GNR)

motility assay. OBJ, objective lens; PDM, perforated dichroic mirror; QWP, quadruple wave plate;

pBD, polarizing beam displacer; CL, cylindrical lens; CAM, CMOS camera; L, lens. (**B**) Calibration

for polarization measurements. (upper) Series of pairs of scattered-light spots of microbeads (0.1

μm) modulated by a polarizer, which was located in front of L3, for emulating GNR spots with

various orientations in the plane. (lower left) Intensity profiles of a pair of scattered-light spots (I_{bottom},

I_{upper}) shown in the upper images. The plots of I_{bottom} and I_{upper} were fitted by intensity functions of

the GNR orientation (Materials and Methods). (lower right) Degree of polarization (DOP), (I_{bottom} −

I_{upper})/(I_{bottom} + I_{upper}) as a function of the normalized summed-intensity of two scattered-light spots,

(I_{bottom} + I_{upper}). (**C**) (top) Schematic drawing of the GNR motility assay in which a kinesin-coated

GNR moves along a microtubule suspended with fluorescent microbeads (0.5 μm) attached to a

glass substrate. (bottom) Fluorescence image of Cy5-labelled microtubules suspended on

fluorescent microbeads. The bright spots are the fluorescent microbeads.

Figure 2. Typical data of the GNR motility assay for KIF1A. (**A**) Montage of scattered-light

images of one KIF1A-coated GNR (KIF1A-GNR) moving around a microtubule every 0.2 s in the

presence of 2 mM ATP. The frame rate was 100 frames s^{-1}. Scale bar, 2 μm. (**B**) Degree of

polarization (DOP) as a function of the summed-intensity of the two KIF1A-GNR spots shown in

(A). The red line represents an ellipse fit. (**C**) 3D trajectory of the KIF1A-GNR shown in (D) through

a moving-average filter of 15 frames. (**D**) The time trajectories of the *X*- and *Y*-displacements

(upper), the DOP and summed-intensity of the two spots (middle), and the estimated angle (bottom)

of KIF1A-GNR shown in (A). The value of *r* is Pearson's correlation coefficient between the *Y*-

displacement and the angle. (**E**) Cross-correlation functions (CCFs) between the *Y*-displacement

and the polarization signals.

Figure 3. Coupled polarization rotation and helical motion of KIF1A-GNRs. (**A, B**) The time trajectories of the *X*- and *Y*-displacements (upper), the degree of polarization (DOP) and summed-intensities of the two spots (middle), and the estimated angles (bottom) of KIF1A-GNRs. The time trajectories of the polarization in the image plane show clockwise rotation in (A) and oscillatory rotation in (B). The value of *r* is Pearson's correlation coefficient between the *Y*-displacement and the angle. (**C**) Distribution of the helix and polarization pitches of KIF1A-GNRs. The helix and polarization pitches are the displacements during one periodic change in the *Y*-displacement and the polarization, respectively. The red line represents a linear fit ($y = ax$) of which the slope (*a*) is 0.97 ($R^2 = 0.95$).

Figure 4. Interpretation of the observed polarization rotations and translational movement of the kinesin-coated gold nanorods (GNRs). (**A, B**) (left) Montage of the projection images of a GNR in the *X-Y* plane, obtained by a model of a motor-coated GNR with no yawing (A) or 180° clockwise yawing during one period of helical motion (B). (right) Time trajectories of the *Y*-displacement and angle of a motor-coated GNR with different initial phase angles ($\varphi = 0°, 45°, 90°,$ and 135°). The value of *r* is Pearson's correlation coefficients between the *Y*-displacement and the angle. Trajectories of a motor-coated GNR in the case of counterclockwise yawing are shown in Fig. S6. See also Movies S2 and S4.

Figure 5. GNR motility assay for ZEN-4. (**A**) Typical time trajectories of the *X*- and *Y*-
displacements (upper), the degree of polarization (DOP) and summed-intensity of the two spots
(middle), and the estimated angles (bottom) of ZEN-4-coated gold nanorods (ZEN4-GNRs). The
three trajectories represent counterclockwise (left), clockwise (middle), and oscillatory (right)
rotations of the GNR polarization in the sample plane. The value of *r* is Pearson's correlation
coefficient between the *Y*-displacement and the angle. (**B**) Distribution of the helix and polarization
pitches of ZEN4-GNRs. The red lines represent linear fits ($y = ax$) of which the slopes (*a*) are 0.99
($R^2 = 0.97$).

Figure 6. Surface-gliding assay for ZEN-4 coated gold nanorods (ZEN4-GNRs). (**A**) Schematic

drawing of the surface-gliding assay, whereby the generation of force and torque rotate a Cy5-

labelled microtubule (Cy5-microtubule) on the ZEN4-GNR. (**B**) Montage of fluorescence images of

Cy5-microtubules every six frames (600 ms), showing that the short Cy5-microtubule continuously

rotated (yellow arrowhead). Scale bar, 2 μm. GNR image of the same region-of-interest of the Cy5

images is also shown (right upper). (**C**) Time trajectory of the microtube orientation.

Figure 7. Mechanistic model for the clockwise rotation and helical motion of kinesin-coated gold nanorods (GNRs). (A) By rotation of the GNR, motors in the posterior and anterior positions relative to the rotation axis move laterally with displacement of ±d. (B) This situation can be modeled using the noise-driven ratchet model with asymmetry potentials (α) and three different starting positions of the particles (−d, 0, +d). (C, D) Fluxes of three particles at the starting positions of diffusion in the noise-driven ratchet with asymmetry potentials after 1/γ units of time (Materials and Methods). (C) Fluxes of three particles, J_{-d}, J_0, and J_{+d} as a function of d with α = 0.53 and γ = 160 s^{-1}. (D) Net flux, J_{-d} + J_0 + J_{+d} as a function of d.

A

Arrangement of joint points

Torque (θ_{step})

Joint point

Diffuse (σ)

Detach ($1/\tau_{on}$)

Attach ($1/\tau_{off}$)

n-1   n-1+α   n   n+α   n+1

Particle taking a step

Force and moment

Attached particle

Displacement and rotation of cargo

Attached particle

B $\theta_{step} = 0°$

— Mot0
— Mot1
— Mot2

Mot1
Mot0
Mol2

C $\theta_{step} = -4°$

— Mot0
— Mot1
— Mot2

D

($\alpha_Y = 0.5$; $\theta_{step} = 0°$)   ($\alpha_Y = 0.58$; $\theta_{step} = 0°$)   ($\alpha_Y = 0.5$; $\theta_{step} = -4°$)   ($\alpha_Y = 0.58$; $\theta_{step} = -4°$)

Bypass: 0%   74%   62%   100%

— Mot0
— Mol1
— Mol2

Figure 8. Monte Carlo simulation of the model for kinesin-coated gold nanorods. (A)
Schematic description of the model. Particles (blue balls) are linked to a rigid body as a cargo
(orange square) with a spring (green line), and the formation of their joint points (yellow circle or
square) are fixed relative to the cargo axis. Particles repeatedly detach and attach to the 2D lattice
rail with rate constants of $1/\tau_{on}$ and $1/\tau_{off}$, respectively. A detached particle diffuses around the joint
points with a standard deviation of σ. When the particle passes over the barrier with an asymmetric
factor (α), at the last time of diffusion, it will attach to the neighboring binding site and generate
torque, twisting the spring by θ_{step}. Translational and rotational motions of the cargo are driven by
the balances of force and moment (torque). **(B, C)** Simulation results without and with torque
generation ($\theta_{step} = 0°$ in (B) and $\theta_{step} = -4°$ in (C)). The parameters are specified in Methods. (left)
Typical *X-Y*-trajectories of three representative particles (black, magenta, and green filled circles)
represent biased forward, sideward and rotational motions of the cargo. (right) Time trajectories of
the angle and *Y*-displacement, and their cross-correlation function (CCF). The axes of the angle
and the *Y*-direction are converted to 180°- and 13-lattice periods, respectively. **(D)** Typical
examples of simulations of bypassing an obstacle. α_Y and θ_{step} are the sideward asymmetric and
torque parameters, respectively (see the main text). The percentages represent the probabilities of
success in bypassing the roadblock (blue rectangle) within a calculation time of 55,000 and out of
300 trials.

Supplementary Information for

Coupled yawing and orbital rotation in kinesin motility revealed by

polarization measurement of gold nanorods

Mitsuhiro Sugawa*, Yohei Maruyama, Masahiko Yamagishi, Robert A. Cross and Junichiro

Yajima*

Mitsuhiro Sugawa, Junichiro Yajima

Email: mitsuhiro-sugawa@g.ecc.u-tokyo.ac.jp, yajima@bio.c.u-tokyo.ac.jp

This PDF file includes:

Supplementary text

Figures S1 to S8

Legends for Movies S1 to S6

SI References

Other supplementary materials for this manuscript include the following:

Movies S1 to S6

Supplementary Information Text

Torque-generation property built into the kinesin motor domain. The rotational work was

estimated to be ~30 pN nm in one ATPase cycle of single-molecule kinesin-1(1); thus, the torque

T_{step} for a θ_{step} of 4° can be estimated to be 430 pN nm ($\approx$ 30 pN nm/0.07 rad). In solid mechanics,

the twist angle of an object is given by $\theta_{step} = T_{step}L/(KG)$, where T_{step} is the torque, L is the length

of the spring, G is the modulus of rigidity of the spring, and K is the polar moment of inertia of the

object. Because kinesin molecules were bound to streptavidin molecules attached to a gold

nanorod, the motor molecule could be roughly approximated as a cylinder with a diameter (d) of ~5

nm and length (L) of ~12 nm. The polar moment of inertia of a cylinder is given by $K = (\pi d^4)/32$.

Finally, we obtained the modulus of rigidity of the spring G (= $T_{step}L/(K\theta_{step})$) of ~1.2 GPa. The

Young's modulus of the spring is thus estimated to be ~3 GPa at a Poisson ratio of 0.25, which are

comparable to the values for actin, tubulin, and coiled-coil (~2 GPa) (2). Therefore, the torque may

be generated by conformational changes in the kinesin motor domain.

Figure S1. Calibration of GNR displacements along the Z-axis. (**A**) Scattered images of a single

GNR bound to the coverslip, taking 50-nm steps along the Z-axis. (**B**) Time trajectories of the widths

of the GNR spot images in (A) along the *X*-axis (S_X, black line) and *Y*-axis (S_Y, red line). The widths

were the standard deviations obtained by 2D Gaussian fits. (**C**) Time trajectory of the ratio of S_Y to

S_X, which represents the *Z*-displacement of the GNR.

Figure S2. Stability of gold-nanorod (GNR) polarization against the *Z*-displacement. (**A**) Fluorescent image of antibody-coated microbeads (arrowheads) and microtubules, and dark-field image of the microbeads (arrowheads) and the GNRs coated with kinesin-1 (Kin1-GNR) (magenta region of interest). Microtubules were suspended on the microbeads via antigen-antibody system for the β tubulin. The single Kin1-coated GNR was bound on the suspended microtubule in the presence of 1 mM AMPPNP. (**B**) Montage of one pair of the scattered images of the single Kin1-coated GNR shown in the magenta region of interest in (A). The objective lens repeatedly moved ±400-nm along the *Z*-axis. (**C**) Time trajectories of the *Z*- and *Y*-displacements, the degree of polarization (DOP), and the summed-intensity of the single Kin1-coated GNR shown in (B). The *Z*-displacement trajectory was obtained from the upper-left spot in (B).

every 2.5 sec

Figure S3. Surface-gliding assay of KIF1A. (**A**) Fluorescence images of Qdot525s and a Cy5-
labelled microtubule in the surface-gliding assay of KIF1A. (**B**) Trajectory of the Qdot525 spot in
the region of interest in (A), which exhibits a stable sinewave, suggesting the repetitive
corkscrewing motions of the microtubule. A corkscrewing pitch of the microtubule was determined
by measuring the *X*-displacement in each period of oscillation along the *Y*-axis. The translational
velocity was 0.49 ± 0.02 μm/s (mean ± SD, *n* = 5 microtubules) and the corkscrewing pitch was
0.89 ± 0.21 μm (mean ± SD, *n* = 35 revolutions).

Figure S4. Relationship between measured pitches, pitches of motors and supertwist of
microtubules. (**A, B**) Pitches of motors (P_{Motor}) as a function of measured pitch ($P_{Measured}$) and
supertwists (P_{MT}) of 12-, 13-, and 14-protofilament microtubules (12-pf, 13-pf, and 14-pf,
respectively). P_{Motor} is given by $P_{Motor}^{-1} = P_{Measured}^{-1} - P_{MT}^{-1}$. The dashed blue line, the black line,
and the doted-and-dashed red line represent the calculation for 12-pf (P_{MT} = −3.4 µm), 13-pf (P_{MT}
= −24.8 µm), and 14-pf (P_{MT} = 6.8 µm), respectively.

Figure S5. Typical time trajectories of kinesin-1 coated GNR. Time trajectories of the *X*- and

Y-displacements (upper), the DOP and summed-intensity of the two spots (middle), and the

estimated angle (bottom) of the kinesin-1 coated GNR.

Figure S6. Calculated trajectories of a motor-coated GNR in the case of counterclockwise
yawing by the proposed model. Calculation of time trajectories of the angle and the *X-Y-*
trajectories of a motor-coated GNR using the proposed model with different phase angles (0°, 45°,
90°, and 135°), in which the kinesin-coated GNR rotates 180° counterclockwise about its yaw axis
in one period of helical trajectory. See also Movie S5.

Figure S7. Typical results of the Monte Carlo simulations. Time trajectories of angle of the

cargo, the 13-period displacement along the *Y*-axis, and the cross-correlation functions (CCFs)

between them, in the range of θ_{step} from 0° to −7°.

Figure S8. Simulation results with torque generation (θ_{step} = +4°). (**A**) Typical *X-Y*-trajectories
of three particles (magenta, black, and green filled circles). (**B**) Time trajectories of the angle and
the *Y*-displacement of the cargo and their cross-correlation function (CCF), corresponding to (A).
The axes of the *Y*-direction are converted into a 13-lattice period.

Figure S9. Simulation results with torque generation (θ_{step} = −4°) and additional noise (σ_θ =
8°) in various formations of particles on a cargo. (**A-D**) (left) formations of particles bound on a
cargo at initial time. Black dots represent the positions of the particles. (middle) Typical time
trajectories of the angle and the *Y*-displacement of the cargo. The axis of the *Y*-direction is
converted into a 13-lattice period. (right) Averaged cross-correlation efficiency (CCF) between the

angle and the *Y*-displacement (*n* = 100 simulations). Error bars represent standard deviation.

881
Movie S1 (separate file). Corresponds to Fig. 2A.

Movie S2 (separate file). Corresponds to Fig. 4A.

Movie S3 (separate file). Animation movie of the proposed movement of a kinesin-coated gold

nanorod on the microtubule.

Movie S4 (separate file). Corresponds to Fig. 4B.

Movie S5 (separate file). Corresponds to Fig. S6.

Movie S6 (separate file). Corresponds to Fig. 6.

889
890
891   **SI References**

892   1. A. Ramaiya, B. Roy, M. Bugiel, E. Schäffer, Kinesin rotates unidirectionally and generates
893   torque while walking on microtubules. *Proc. Natl. Acad. Sci.* **114**, 10894–10899 (2017).

894   2. J. Howard, "Mass, Stiffness, and Damping of Proteins" in *Mechanics of Motor Proteins*
895   *and the Cytoskeleton*, (Sinauer, 2005), pp. 29–47.