TreeSearch: morphological phylogenetic analysis in R

Martin R. Smith

Department of Earth Sciences, Durham University, Lower Mountjoy, Durham, DH1 3LE, UK;

martin.smith@durham.ac.uk

Running head: Parsimony analysis in R

____

Abstract.—TreeSearch is an R package for phylogenetic analysis, optimized for morphological

datasets. Tree search may be conducted using under equal or implied step weights with an

explicit (albeit inexact) allowance for inapplicable character entries, avoiding some of the pitfalls

inherent in standard parsimony methods. Profile parsimony and user-specified optimality criteria

are supported.

A graphical interface, which requires no familiarity with R, is designed to help a user to

improve the quality of datasets through critical review of underpinning character codings; and to

obtain additional information from results by identifying and summarising clusters of similar

trees, mapping the distribution of trees, and removing 'rogue' taxa that obscure underlying

relationships.

Taken together, the package aims to support methodological rigour at each step of data

collection, analysis, and the exploration of phylogenetic results.

Key words

phylogenetic software, morphological phylogenetic analysis, implied weights, parsimony,

inapplicable characters.

Even in the phylogenomic era, morphological data make an important contribution to

phylogenetic questions. Phenotypic data improve the accuracy and resolution of phylogenetic

reconstruction even when outnumbered by molecular characters, and are the only way to

incorporate the unique perspective on historical events that fossil taxa provide (Wiens 2004;

Wortley and Scotland 2006; Koch and Parry 2020; Asher and Smith 2021).

One challenge with morphological analysis is the treatment of inapplicable character

states: for example, 'tail colour' cannot logically be ascribed either of the states 'red' or 'blue' in

a taxon that lacks a tail (Maddison 1993). This situation can profoundly mislead phylogenetic

analysis, and is not handled appropriately by either Fitch (1971) parsimony or the Mk model

(Lewis 2001).

Solutions to this issue have recently been proposed (Brazeau et al. 2019; Tarasov 2019;

Goloboff et al. 2021; Hopkins and St. John 2021). Where a single 'principal' character

(e.g. 'tail') exhibits n 'contingent' characters (e.g. 'tail colour,' 'tail covering'), 'exact' solutions

(Tarasov 2019; Goloboff et al. 2021) require the construction of multi-state hierarchies

containing $O(2^n)$ entries, meaning that analysis is only computationally tractable for simple

hierarchies with few contingent characters. Moreover, these approaches cannot accommodate

characters that are contingent on more than one principal character: for example, characters

describing appendages on a differentiated head may be contingent on the presence of the two

characters 'appendages' and 'differentiated head.'

Such situations can be approached using the flexible but approximate parsimony

approach proposed by Brazeau et al. (2019). TreeSearch scores trees using the "Morphy" C

implementation of this algorithm (Brazeau et al. 2017). Where Morphy implements rapid tree

search under equal step weights, TreeSearch also implements implied step weighting (Goloboff

1993), a method which consistently finds more accurate and precise trees than equal weights

parsimony (Goloboff et al. 2008, 2018a; Smith 2019a).

There has been lively discussion as to whether, with the rise of probabilistic approaches,

parsimony remains a useful tool for morphological phylogenetics (e.g. O'Reilly et al. 2016;

Puttick et al. 2017; Brown et al. 2017; Sansom et al. 2018; Goloboff et al. 2018b).

Notwithstanding scenarios that go beyond the limits of parsimony, such as the principled

incorporation of stratigraphic data and other prior knowledge (e.g. Guenser et al. 2021), neither

parsimony nor probabilistic methods consistently recover 'better' trees when gains in accuracy

are balanced against losses in precision (Smith 2019a). Even if probabilistic methods may

eventually be improved through the creation of more sophisticated models that better reflect the

nature of morphological data (Goloboff et al. 2018a; Tarasov 2019), parsimony analysis remains

a useful tool – not only because treatments of inapplicable character states are presently

available, but also because its simplicity can facilitate a deeper understanding of the

underpinning data.

Whatever method is used to find phylogenetic trees, a single consensus tree may fail to

convey all the signal in a set of phylogenetic results (Wilkinson 1994, 1996, 2003; Wright and

Lloyd 2020). A set of optimal trees can be better interpreted through an exploration of tree space

(Smith 2022a); by examining consensus trees generated from clusters of similar trees (Stockham

et al. 2002); and by automatically identifying, annotating and removing 'wildcard' taxa (Smith

2022b) whose 'rogue' behaviour may reflect underlying character conflict or ambiguity (Kearney

2002). These methods are not always easy to integrate into phylogenetic workflows, so are not

routinely included in empirical studies.

TreeSearch provides functions that allow researchers to engage with the three main

aspects of morphological phylogenetic analysis: dataset construction and validation;

phylogenetic search, including with inapplicable data; and the interrogation of optimal tree sets.

These functions can be accessed through command-line functions, documented within the

package and at ms609.github.io/TreeSearch/, or via an integrated graphical user interface (GUI),

with options to save outputs in graphical formats or as Nexus or Newick files for further

analysis.

IMPLEMENTATION

Dataset review

Ultimately, the quality of a dataset plays a central role in determining the reliability of

phylogenetic results, with changes to a relatively small number of character codings potentially

exhibiting an outsized impact on reconstructed topologies (Goloboff and Sereno 2021).

Nevertheless, dataset quality does not always receive commensurate attention (Simões et al.

2017). One step towards improving the rigour of morphological datasets is to annotate each cell

in a dataset with an explicit justification for each taxon's coding (Sereno 2009), which can be

accomplished in Nexus-formatted data files (Maddison et al. 1997) using software such as

MorphoBank (O'Leary and Kaufman 2011).

TreeSearch presents such annotations alongside a reconstruction of each character's states

on an optimal tree, with inapplicable states mapped according to the algorithm of Brazeau et al.

(2019). Neomorphic (presence/absence) and transformational characters (Sereno 2007) are

distinguished by reserving the token 0 to solely denote the absence of a neomorphic character,

with tokens 1 … n used to denote the n states of a transformational character (Brazeau et al.

2019).

This visualization of reconstructed character transitions can help to identify cases where

the formulation of characters has unintended consequences (Wilkinson 1995; Brazeau 2011);

where inapplicable states have been inconsistently applied (Brazeau et al. 2019); where

taphonomic absence is wrongly coded as biological absence (Donoghue and Purnell 2009);

where previous datasets are uncritically recycled (Jenner 2001); or where taxa are coded with

more confidence than a critical evaluation of available evidence can truly support. Insofar as the

optimal tree and the underlying characters are reciprocally illuminating (Mooi and Gill 2016),

successive cycles of phylogenetic analysis and character re-formulation can improve the integrity

of morphological datasets, and thus increase their capacity to yield meaningful phylogenetic

results (Hennig 1966).

Tree search

The TreeSearch GUI uses the routine `MaximizeParsimony()` to search for optimal trees using

tree bisection and reconnection (TBR) searches and the parsimony ratchet (Nixon 1999). This

goes beyond the heuristic tree search implementation in the R package "phangorn" (Schliep

2011) by conducting tree rearrangements in C, allowing faster computation; and in supporting

TBR rearrangements, which explore larger neighbourhoods of tree space: TBR evaluates more

trees than nearest-neighbour interchanges or subtree pruning and regrafting, leading to additional

computational expense that is offset by a decreased likelihood that search will become trapped in

a local optimum (Goeffon et al. 2008; Whelan and Money 2010).

By default, search begins from a greedy addition tree generated by function

`AdditionTree()`, which selects taxa in a random order, attaching each taxon in turn to the

growing tree at the most parsimonious location. Search may also be started from neighbour-

joining trees, or the results of a previous search.

Search commences by conducting TBR rearrangements – a hill-climbing approach that

locates a locally optimal tree from which no tree accessible by a single TBR rearrangement has a

better score. A TBR iteration breaks a randomly selected edge in the focal tree, and reconnects

each possible pair of edges in the resultant sub-trees to produce a list of candidate trees. Entries

that are inconsistent with user-specified topological constraints are removed; remaining trees are

inserted into a queue in a random sequence and scored in turn. If the score of a candidate tree is

at least as good as the best yet encountered (within the bounds of an optional tolerance parameter

ϵ, which allows the retention of almost-optimal trees in order to improve accuracy (e.g. Smith

2019a)), this tree is used as the starting point for a new TBR iteration. Otherwise, the next tree in

the list is considered. TBR search continues until the best score is found a specified number of

times; a specified number of TBR break points have been evaluated without any improvement to

tree score; or a set amount of time has passed.

When TBR search is complete, iterations of the parsimony ratchet (Nixon 1999) are

conducted in order to search areas of tree space that are separated from the best tree yet found by

'valleys' that cannot be traversed by TBR rearrangements without passing through trees whose

optimality score is below the threshold for acceptance. Each ratchet iteration begins by

resampling the original matrix. A round of TBR search is conducted using this resampled matrix,

and the tree thus produced is used as a starting point for a new round of TBR search using the

original data.

After a specified number of ratchet iterations, an optional final round of TBR search

allows a denser sampling of optimal trees from the final region of tree space.

During tree search, all trees whose score is within ϵ of the best score are retained, and

tagged with the iteration in which they were first identified. This allows the progress of tree

search to be visualized in tree space (Fig. 1; after Whidden and Matsen 2015).

More flexible, if less computationally efficient, tree searches can be conducted at the

command line using the `TreeSearch()`, `Ratchet()` and `Bootstrap()` commands, which

support custom tree optimality criteria (e.g. Hopkins and St. John 2021).

Tree scoring

Trees may be scored using equal weights, implied weighting (Goloboff 1993), or profile

parsimony (Faith and Trueman 2001). The function `TreeLength()` calculates tree score using

the "Morphy" phylogenetic library (Brazeau et al. 2017), which implements the Fitch (1971) and

Brazeau et al. (2019) algorithms. Morphy returns the equal weights parsimony score of a tree

against a given dataset. Implied weights and profile parsimony scores are computed by first

making a separate call to Morphy for each character in turn, passed as a single-character dataset;

then passing this value to the appropriate weighting formula and summing the total score over all

characters.

Implied weighting is an approximate method that treats each additional step in a character

as less surprising – and thus requiring less penalty – than the previous step. Each additional step

demonstrates that a character is less reliable for phylogenetic inference, and thus more likely to

contain additional homoplasy. The score of a tree under implied weighting is $\sum \frac{e_i}{e_i + k}$, where e_i

denotes the number of extra steps observed in character i, and is derived by subtracting the

minimum score that the character can obtain on any tree from the score observed on the tree in

question (Goloboff 1993). The minimum length of a tree is one less than the number of unique

applicable tokens that must be present.

Profile parsimony (Faith and Trueman 2001) represents an alternative formulation of how

surprising each additional step in a character is (Arias and Miranda-Esquivel 2004): the penalty

associated with each additional step in a character is a function of the probability that a character

will fit at least as well as is observed on a uniformly selected tree. On this view, an additional

step is less surprising if observed in a character where there are more opportunities to observe

homoplasy, whether because a character contains fewer ambiguous codings (a motivation for the

'extended' implied weighting of Goloboff (2014)) or because states are distributed more evenly

in a character, whose higher phylogenetic information content (Thorley et al. 1998) corresponds

to a lower proportion of trees in which no additional steps are observed.

TreeSearch calculates the profile parsimony score by computing the logarithm of the

number of trees onto which a character can be mapped using m steps, using theorem 1 of Carter

et al. (1990). As computation for higher numbers of states (Maddison and Slatkin 1991) is more

computationally complex, the present implementation is restricted to characters that contain two

applicable tokens, and uses the Fitch (1971) algorithm.

Visualization

The distribution of optimal trees, however obtained, can be visualized interactively through

mappings of tree space (Hillis et al. 2005; Smith 2022a) using the TreeSearch GUI.

The GUI supports the use of information theoretic distances (Smith 2020a); the quartet

distance (Estabrook et al. 1985); or the Robinson–Foulds distance (Robinson and Foulds 1981)

to construct tree spaces, which are mapped into 2–12 dimensions using principle coordinates

analysis (Gower 1966). The degree to which a mapping faithfully depicts original tree-to-tree

distances is measured using the product of the trustworthiness and continuity metrics (Venna and

Kaski 2001; Kaski et al. 2003; Smith 2022a), a composite score denoting the degree to which

points that are nearby when mapped are truly close neighbours (trustworthiness), and the degree

to which nearby points remain nearby when mapped (continuity). A visualization of stress is

provided by plotting the minimum spanning tree (Gower and Ross 1969); contortions in this tree

indicate that mapping has distorted original distances (Smith 2022a).

Figure 1. Three-dimensional map visualizing tree search progress. Optimal trees belong to

two statistically distinct clusters with strong support (silhouette coefficient > 0.7),

characterized by different relationships between certain taxa (plotting symbols). Although

multiple ratchet iterations have visited each cluster, limited overlap between ratchet

iterations suggests that a continuation of tree search may sample novel optimal trees. A

simple minimum spanning tree (grey) indicates that the mapping does not exhibit severe

distortion.

To relate the geometry of tree space to the underlying trees, each point in tree space may

be annotated according to the optimality score of its corresponding tree under a selected step

weighting scheme; by the relationships between chosen taxa that are inferred by that tree; and by

the search iteration in which the tree was first found by tree search (Fig. 1).

The latter feature can be used to evaluate whether a continuation of tree search is likely to

yield more optimal trees. For example, if the trees retained are first found only in later rounds of

tree search, this recent improvement in tree score suggests that a global optimum may not yet

have been reached. Alternatively, if each individual ratchet iteration samples a separate region of

tree space, it is likely that the landscape of optimal trees contains isolated 'islands' (Bastert et al.

2002), some of which may remain to be found. Continuing tree search until additional ratchet

iterations no longer locate new clusters of trees will reduce the chance that optimal regions of

tree space remain unvisited.

As the identification of clusters from mappings of tree space can be misleading (Smith

2022a), TreeSearch identifies clusters of trees from tree-to-tree distances using K-means

clustering, partitioning around medoids and hierarchical clustering with minimax linkage

(Hartigan and Wong 1979; Murtagh 1983; Bien and Tibshirani 2011; Maechler et al. 2019).

Clusterings are evaluated using the silhouette coefficient, a measure of the extent of overlap

between clusters (Kaufman and Rousseeuw 1990). The clustering with the highest silhouette

coefficient is depicted if the silhouette coefficient exceeds a user-specified threshold; the

interpretation of the chosen threshold according to Kaufman and Rousseeuw (1990) is displayed

to the user. Plotting a separate consensus tree for each cluster often reveals phylogenetic

information that is concealed by polytomies in the single 'plenary' consensus of all optimal trees

(Stockham et al. 2002).

Plenary consensus trees can also lack resolution because of wildcard or 'rogue' taxa, in

which conflict or ambiguity in their character codings leads to an unsettled phylogenetic position

(Wilkinson 1994, 2003; Kearney 2002). TreeSearch detects rogue taxa using a heuristic approach

(Smith 2022b) that seeks to maximize the phylogenetic information content (*sensu* Thorley et al.

1998) of a consensus tree created after removing rogue taxa from input trees. The position of an

excluded taxon is portrayed by shading each edge or node of the consensus according to the

number of times the specified taxon occurs at that position on an underlying tree (Fig. 2; after

Klopfstein and Spasojevic 2019), equivalent to the 'branch attachment frequency' of "Phyultity"

(Smith and Dunn 2008).

Identifying taxa with an unstable position, and splits with low support, can help an

investigator to critically re-examine character codings; to this end, each edge of the resulting

consensus can be annotated with the frequency of the split amongst the tree set, or with a

concordance factor (Minh et al. 2020) denoting the strength of support from the underlying

dataset.

Figure 2. Reduced consensus of 150 cladograms generated by analysis of data from Wills et al. (2012) under different parsimony methods by Brazeau et al. (2019), as displayed in the TreeSearch graphical user interface. Removal of taxa reveals strong support for relationships that would otherwise be masked by rogues such as *Palaeoscolex*, whose position in optimal trees is marked by the highlighted edges.

AVAILABILITY

TreeSearch can be installed through the Comprehensive R Archive Network (CRAN) using

`install.packages("TreeSearch");` the graphical user interface is launched with the command

`TreeSearch::EasyTrees()`. It has been tested on all widely available operating systems and

requires only R packages available from the CRAN repository. Source code is available at

https://github.com/ms609/TreeSearch/, and is permanently archived at Zenodo

(https://dx.doi.org/10.5281/zenodo.1042590). Documentation is online at

https://ms609.github.io/TreeSearch/.

`# Note: Until the updated version 5.5-2 of the underlying package 'ape' is`

`# available on CRAN, the latest version of TreeSearch and its dependencies`

`# should be installed using:`

`  install.packages("remotes")`

`  remotes::install_github("emmanuelparadis/ape")`

`  remotes::install_github("ms609/TreeTools@rogue")`

`  remotes::install_github("ms609/TreeDist")`

`  remotes::install_github("ms609/Rogue")`

`  remotes::install_github("ms609/TreeSearch")`

`# The GUI can then be launched with:`

`  library("TreeSearch")`

`  EasyTrees()`

ACKNOWLEDGEMENTS

I thank Alavya Dhungana and Joe Moysiuk for feedback on preliminary versions of the software.

Functionality in TreeSearch employs the underlying R (R Core Team 2021) packages

"ape" (Paradis and Schliep 2019), "phangorn" (Schliep 2011), "Quartet" (Sand et al. 2014; Smith

261 2019b), "Rogue" (Smith 2022b), "shiny" (Chang et al. 2021), "shinyjs" (Attali 2020), "TreeDist"

262 (Smith 2020b), and "TreeTools" (Smith 2019c).

263 DISCLOSURE STATEMENT

264 I am aware of no conflict of interest.

265 REFERENCES

266 Arias J.S., Miranda-Esquivel D.R. 2004. Profile parsimony (PP): An analysis under implied

267  weights (IW). Cladistics. 20:56–63.

268 Asher R.J., Smith M.R. 2021. Phylogenetic signal and bias in paleontology. Systematic

269  Biology.:syab072.

270 Attali D. 2020. Shinyjs: Easily improve the user experience of your shiny apps in seconds.

271 Bastert O., Rockmore D., Stadler P.F., Tinhofer G. 2002. Landscapes on spaces of trees. Applied

272  Mathematics and Computation. 131:439–459.

273 Bien J., Tibshirani R. 2011. Hierarchical clustering with prototypes via minimax linkage. Journal

274  of the American Statistical Association. 106:1075–1084.

275 Brazeau M.D. 2011. Problematic character coding methods in morphology and their effects.

276  Biological Journal of the Linnean Society. 104:489–498.

277 Brazeau M.D., Guillerme T., Smith M.R. 2019. An algorithm for morphological phylogenetic

278  analysis with inapplicable data. Systematic Biology. 68:619–631.

Brazeau M.D., Smith M.R., Guillerme T. 2017. MorphyLib: A library for phylogenetic analysis

of categorical trait data with inapplicability.

Brown J.W., Parins-Fukuchi C., Stull G.W., Vargas O.M., Smith S.A. 2017. Bayesian and

likelihood phylogenetic reconstructions of morphological traits are not discordant when

taking uncertainty into consideration: A comment on Puttick *et al.* Proceedings of the Royal

Society B: Biological Sciences. 284:20170986.

Carter M., Hendy M., Penny D., Székely L.A., Wormald N.C. 1990. On the distribution of

lengths of evolutionary trees. SIAM Journal on Discrete Mathematics. 3:38–47.

Chang W., Cheng J., Allaire J., Sievert C., Schloerke B., Xie Y., Allen J., McPherson J., Dipert

A., Borges B. 2021. Shiny: Web application framework for R.

Donoghue P.C.J., Purnell M.A. 2009. Distinguishing heat from light in debate over controversial

fossils. BioEssays. 31:178–189.

Estabrook G.F., McMorris F.R., Meacham C.A. 1985. Comparison of undirected phylogenetic

trees based on subtrees of four evolutionary units. Systematic Zoology. 34:193–200.

Faith D.P., Trueman J.W.H. 2001. Towards an inclusive philosophy for phylogenetic inference.

Systematic Biology. 50:331–350.

Fitch W.M. 1971. Toward defining the course of evolution: Minimum change for a specific tree

topology. Systematic Biology. 20:406–416.

Goeffon A., Richer J.-M., Jin-Kao Hao. 2008. Progressive Tree Neighborhood applied to the

Maximum Parsimony problem. IEEE/ACM Transactions on Computational Biology and

Bioinformatics. 5:136–145.

Goloboff P.A. 1993. Estimating character weights during tree search. Cladistics. 9:83–91.

Goloboff P.A. 2014. Extended implied weighting. Cladistics. 30:260–272.

Goloboff P.A., Carpenter J.M., Arias J.S., Esquivel D.R.M. 2008. Weighting against homoplasy

improves phylogenetic analysis of morphological data sets. Cladistics. 24:758–773.

Goloboff P.A., Laet J.D., Ríos-Tamayo D., Szumik C.A. 2021. A reconsideration of inapplicable

characters, and an approximation with step-matrix recoding. Cladistics. 37:596–629.

Goloboff P.A., Sereno P.C. 2021. Comparative cladistics: Identifying the sources for differing

phylogenetic results between competing morphology-based datasets. Journal of Systematic

Palaeontology.:1–26.

Goloboff P.A., Torres A., Arias J.S. 2018a. Weighted parsimony outperforms other methods of

phylogenetic inference under models appropriate for morphology. Cladistics. 34:407–437.

Goloboff P.A., Torres Galvis A., Arias J.S. 2018b. Parsimony and model-based phylogenetic

methods for morphological data: Comments on O'Reilly *et al.* Palaeontology. 61:625–630.

Gower J.C. 1966. Some distance properties of latent root and vector methods used in

multivariate analysis. Biometrika. 53:325–338.

Gower J.C., Ross G.J.S. 1969. Minimum spanning trees and single linkage cluster analysis.

Journal of the Royal Statistical Society. Series C (Applied Statistics). 18:54–64.

Guenser P., Warnock R.C.M., Pett W., Donoghue P.C.J., Jarochowska E. 2021. Does time matter

in phylogeny? A perspective from the fossil record. bioRχiv.

Hartigan J.A., Wong M.A. 1979. Algorithm AS 136: A *K*-means clustering algorithm. Journal of

the Royal Statistical Society. Series C (Applied Statistics). 28:100–108.

Hennig W. 1966. Phylogenetic systematics. Urbana: The University of Illinois Press.

Hillis D.M., Heath T.A., St. John K. 2005. Analysis and visualization of tree space. Systematic

Biology. 54:471–482.

Hopkins M.J., St. John K. 2021. Incorporating hierarchical characters into phylogenetic analysis.

Systematic Biology.:syab005.

Jenner R.A. 2001. Bilaterian phylogeny and uncritical recycling of morphological data sets.

Systematic Biology. 50:730–742.

Kaski S., Nikkilä J., Oja M., Venna J., Törönen P., Castrén E. 2003. Trustworthiness and metrics

in visualizing similarity of gene expression. BMC Bioinformatics. 4:48.

Kaufman L., Rousseeuw P.J. 1990. Partitioning around medoids (Program PAM). Finding

groups in data: An introduction to cluster analysis. John Wiley & Sons, Ltd. p. 68–125.

Kearney M. 2002. Fragmentary taxa, missing data, and ambiguity: Mistaken assumptions and

conclusions. Systematic Biology. 51:369–381.

Klopfstein S., Spasojevic T. 2019. Illustrating phylogenetic placement of fossils using

RoguePlots: An example from ichneumonid parasitoid wasps (Hymenoptera,

Ichneumonidae) and an extensive morphological matrix. PLOS ONE. 14:e0212942.

Koch N.M., Parry L.A. 2020. Death is on our side: Paleontological data drastically modify

phylogenetic hypotheses. Systematic Biology. 69:1052–1067.

Lewis P.O. 2001. A likelihood approach to estimating phylogeny from discrete morphological

character data. Systematic Biology. 50:913–925.

Maddison D.R., Swofford D.L., Maddison W.P. 1997. NEXUS: An extensible file format for

systematic information. Systematic Biology. 46:590–621.

Maddison W.P. 1993. Missing data versus missing characters in phylogenetic analysis.

Systematic Biology. 42:576–581.

Maddison W.P., Slatkin M. 1991. Null models for the number of evolutionary steps in a

character on a phylogenetic tree. Evolution. 45:1184–1197.

Maechler M., Rousseeuw P., Struyf A., Hubert M., Hornik K. 2019. Cluster: Cluster Analysis

Basics and Extensions. Comprehensive R Archive Network. 2.1.0.

Minh B.Q., Hahn M.W., Lanfear R. 2020. New methods to calculate concordance factors for

phylogenomic datasets. Molecular Biology and Evolution. 37:2727–2733.

Mooi R.D., Gill A.C. 2016. Hennig's auxiliary principle and reciprocal illumination revisited. In:

Williams D., Schmitt M., Wheeler Q., editors. The Future of Phylogenetic Systematics.

Cambridge: Cambridge University Press. p. 258–285.

Murtagh F. 1983. A survey of recent advances in hierarchical clustering algorithms. The

Computer Journal. 26:354–359.

Nixon K.C. 1999. The Parsimony Ratchet, a new method for rapid parsimony analysis.

Cladistics. 15:407–414.

O'Leary M.A., Kaufman S. 2011. MorphoBank: Phylophenomics in the "cloud." Cladistics.

27:529–537.

O'Reilly J.E., Puttick M.N., Parry L., Tanner A.R., Tarver J.E., Fleming J., Pisani D., Donoghue

P.C.J. 2016. Bayesian methods outperform parsimony but at the expense of precision in the

estimation of phylogeny from discrete morphological data. Biology Letters. 12:20160081.

Paradis E., Schliep K. 2019. Ape 5.0: An environment for modern phylogenetics and

evolutionary analyses in R. Bioinformatics. 35:526–528.

Puttick M.N., O'Reilly J.E., Tanner A.R., Fleming J.F., Clark J., Holloway L., Lozano-

Fernandez J., Parry L.A., Tarver J.E., Pisani D., Donoghue P.C.J. 2017. Uncertain-tree:

Discriminating among competing approaches to the phylogenetic analysis of phenotype

data. Proceedings of the Royal Society B: Biological Sciences. 284:20162290.

R Core Team. 2021. R: A language and environment for statistical computing.

Robinson D.F., Foulds L.R. 1981. Comparison of phylogenetic trees. Mathematical Biosciences.

53:131–147.

Sand A., Holt M.K., Johansen J., Brodal G.S., Mailund T., Pedersen C.N.S. 2014. tqDist: A

library for computing the quartet and triplet distances between binary or general trees.

Bioinformatics. 30:2079–2080.

Sansom R.S., Choate P.G., Keating J.N., Randle E. 2018. Parsimony, not Bayesian analysis,

recovers more stratigraphically congruent phylogenetic trees. Biology Letters.

14:20180263.

Schliep K.P. 2011. Phangorn: Phylogenetic analysis in R. Bioinformatics. 27:592–593.

Sereno P.C. 2007. Logical basis for morphological characters in phylogenetics. Cladistics.

23:565–587.

Sereno P.C. 2009. Comparative cladistics. Cladistics. 25:624–659.

Simões T.R., Caldwell M.W., Palci A., Nydam R.L. 2017. Giant taxon-character matrices:

Quality of character constructions remains critical regardless of size. Cladistics. 33:198–

219.

Smith M.R. 2019a. Bayesian and parsimony approaches reconstruct informative trees from

simulated morphological datasets. Biology Letters. 15:20180632.

Smith M.R. 2019b. Quartet: Comparison of phylogenetic trees using quartet and bipartition

measures. Comprehensive R Archive Network.:doi:10.5281/zenodo.2536318.

Smith M.R. 2019c. TreeTools: Create, modify and analyse phylogenetic trees. Comprehensive R

Archive Network.:doi:10.5281/zenodo.3522725.

Smith M.R. 2020a. Information theoretic Generalized Robinson–Foulds metrics for comparing

phylogenetic trees. Bioinformatics. 36:5007–5013.

Smith M.R. 2020b. TreeDist: Calculate and map distances between phylogenetic trees.

Comprehensive R Archive Network.:doi:10.5281/zenodo.3528123.

Smith M.R. 2022b. Using information theory to detect rogue taxa and improve consensus trees.

Systematic Biology.:accepted MS.

Smith M.R. 2022a. Robust analysis of phylogenetic tree space. Systematic Biology.:in review.

Smith S.A., Dunn C.W. 2008. Phyutility: A phyloinformatics tool for trees, alignments and

molecular data. Bioinformatics. 24:715–716.

Stockham C., Wang L.-S., Warnow T. 2002. Statistically based postprocessing of phylogenetic

analysis by clustering. Bioinformatics. 18:S285–S293.

Tarasov S. 2019. Integration of anatomy ontologies and evo-devo using structured Markov

models suggests a new framework for modeling discrete phenotypic traits. Systematic

Biology. 68:698–716.

Thorley J.L., Wilkinson M., Charleston M. 1998. The information content of consensus trees. In:

Rizzi A., Vichi M., Bock H.-H., editors. Advances in Data Science and Classification.

Berlin: Springer. p. 91–98.

Venna J., Kaski S. 2001. Neighborhood preservation in nonlinear projection methods: An

experimental study. Artificial Neural Networks ICANN 2001.:485–491.

Whelan S., Money D. 2010. The prevalence of multifurcations in tree-space and their

implications for tree-search. Molecular Biology and Evolution. 27:2674–2677.

Whidden C., Matsen F.A. 2015. Quantifying MCMC exploration of phylogenetic tree space.

Systematic Biology. 64:472–491.

Wiens J.J. 2004. The role of morphological data in phylogeny reconstruction. Systematic

Biology. 53:653–661.

Wilkinson M. 1994. Common cladistic information and its consensus representation: Reduced

Adams and reduced cladistic consensus trees and profiles. Systematic Biology. 43:343–368.

Wilkinson M. 1995. A comparison of two methods of character construction. Cladistics. 11:297–

308.

Wilkinson M. 1996. Majority-rule reduced consensus trees and their use in bootstrapping.

Molecular Biology and Evolution. 13:437–444.

Wilkinson M. 2003. Missing entries and multiple trees: Instability, relationships, and support in

parsimony analysis. Journal of Vertebrate Paleontology. 23:311–323.

Wills M.A., Gerber S., Ruta M., Hughes M. 2012. The disparity of priapulid, archaeopriapulid

and palaeoscolecid worms in the light of new data. Journal of Evolutionary Biology.

25:2056–2076.

Wortley A.H., Scotland R.W. 2006. The effect of combining molecular and morphological data

in published phylogenetic analyses. Systematic Biology. 55:677–685.

Wright A.M., Lloyd G.T. 2020. Bayesian analyses in phylogenetic palaeontology: Interpreting

the posterior sample. Palaeontology. 63:997–1006.