Body shape as a visual feature: evidence from spatially-global attentional modulation in

human visual cortex

Abbreviated title: Body shape as a visual feature

Sushrut Thorat[1], Marius V. Peelen[1]

[1]Donders Institute for Brain, Cognition and Behaviour, Radboud University, Nijmegen, The

Netherlands.

Corresponding author:

Marius V. Peelen

Donders Institute for Brain, Cognition and Behaviour

Radboud University

Thomas van Aquinostraat 4, 6525 GD Nijmegen, The Netherlands

Email: marius.peelen@donders.ru.nl

Conflict of interest statement: The authors declare no competing financial interests.

Acknowledgements: This project has received funding from the European Research Council

(ERC) under the European Union's Horizon 2020 research and innovation programme (grant

agreement No. 725970).

Abstract

Feature-based attention modulates visual processing beyond the focus of spatial attention.

Previous work has reported such spatially-global effects for low-level features such as color and

orientation, as well as for faces. Here, using fMRI, we provide evidence for spatially-global

attentional modulation for human bodies. Participants were cued to search for one of six object

categories in two vertically-aligned images. Two additional, horizontally-aligned, images were

simultaneously presented but were never task-relevant across three experimental sessions.

Analyses time-locked to the objects presented in these task-irrelevant images revealed that

responses evoked by body silhouettes were modulated by the participants' top-down attentional

set, becoming more body-selective when participants searched for bodies in the task-relevant

images. These effects were observed both in univariate analyses of the body-selective cortex

and in multivariate analyses of the object-selective visual cortex. Additional analyses showed

that this modulation reflected response gain rather than a bias induced by the cues, and that it

reflected enhancement of body responses rather than suppression of non-body responses.

These findings provide evidence for a spatially-global attention mechanism for body shapes,

supporting the rapid and parallel detection of conspecifics in our environment.

Introduction

The capacity limits of the human visual system require selecting visual input for further processing and conscious access (Carrasco, 2011; Chun et al., 2011). One way to do this is to select specific locations of the visual field through spatial attention and eye movements. However, when searching for task-relevant objects in our environment, the location of these objects is typically not yet known. In this case, selection may operate at the level of visual features, using a selection mechanism termed feature-based attention (Maunsell and Treue, 2006). To be an effective selection mechanism, feature-based attention would need to operate in parallel across the whole or part of the visual field, in order to then guide spatial attention to the location of the target object (Wolfe, 1994). While this could be a plausible mechanism of attentional selection, it raises a core question: what are the features of feature-based attention?

At a neural level, it has been proposed that feature-based attention may be restricted to features to which sensory neurons are systematically tuned (Maunsell and Treue, 2006). Accordingly, the neural mechanisms of feature-based attention have been studied extensively with experiments involving low-level features for which such tuning has been established, such as the orientations of Gabor patches (Kamitani and Tong, 2005; Liu et al., 2007; Jehee et al., 2011) and the movement direction of random dot patterns (Treue and Trujillo, 1999; Saenz et al., 2002; Serences and Boynton, 2007). These experiments assessed how making one feature task-relevant influenced the responses of neurons that were selective or non-selective to that feature. A common finding was that attending to a low-level feature increased the responses of neurons selective to that feature and decreased the responses of neurons non-selective to that feature (Maunsell and Treue, 2006). Crucially, such modulations were shown to occur for stimuli presented in spatially-unattended and task-irrelevant locations (Treue and Trujillo, 1999; Saenz et al., 2002; Serences and Boynton, 2007; Zhang and Luck, 2009), providing evidence for a

spatially-global mechanism of feature-based attention that can be distinguished from the effects

of spatial attention.

In the present study, we tested whether global attentional modulation can similarly be

observed for the shape of the human body, a category of high social and biological significance

that is selectively represented in high-level visual cortex (Downing et al., 2001; Peelen &

Downing, 2005). Behavioral studies have shown that bodies, like faces, gain preferential access

to awareness (Stein et al., 2012) and automatically attract attention (Downing et al., 2004; Ro et

al., 2007). There is also behavioral evidence for spatially-global attention effects for bodies: in a

series of studies, spatial attention was captured by body silhouettes when participants searched

for people in scenes presented in different parts of the visual field (Reeder and Peelen, 2013;

Reeder et al., 2015). Finally, an fMRI study reported spatially-global modulation of multivoxel

activity patterns distinguishing natural scenes with people from natural scenes with cars (Peelen

et al., 2009). However, in that study, the relative contributions of scene context and of body,

face, and car features could not be distinguished, such that it remains unknown whether

feature-based attention effects exist for human bodies.

Here, we used fMRI to test for spatially-global attentional modulation of body processing

in visual cortex. Participants detected the presence of bodies or one of five other categories

(beds, bottles, cars, chairs, lamps) in task-relevant vertically-aligned images, thereby

manipulating the top-down attentional set. To test for spatially-global attentional modulation, all

analyses focused on responses evoked by objects that were concurrently presented at locations

that were never relevant for the object detection task across three experimental sessions (Fig.

1A). The inclusion of five non-body categories reduced the possibility that participants could use

a low-level feature to detect the presence of bodies, for example by looking for vertical (bodies)

vs horizontal (e.g., cars) stimuli: lamps and bottles shared the vertical orientation with bodies

(Fig 1D). To further reduce this possibility, each category was represented by a large and

diverse set of exemplars cropped out of scene photographs. Finally, the use of silhouettes

avoided possible low-level differences between categories in texture and color, and ensured

that attention was guided by body shape rather than facial features (Störmer et al., 2019).

(A) Main experiment block structure

(B)

(C) Baseline experiment mini-block structure   (D) Objects

Figure 1: Experimental design. (A) The main experiment was designed to reveal the modulatory

influence of feature-based attention on object responses evoked by stimuli presented at task-irrelevant

locations (horizontal boxes). In each block (49 trials), participants had to search for the cued object

category (e.g., car) in the vertical boxes, while objects were simultaneously presented in the horizontal

boxes. (B) The spatial layout of the search display. (C) The baseline experiment was included to localize

body-selective regions of interest (for the univariate analyses) and to obtain prototypical object category

response patterns (for the multivariate analyses). Responses evoked by task-irrelevant objects in the

main experiment were compared to these responses. Participants had to indicate if one of the edges of

the two boxes thickened. The object category and location (horizontal or vertical boxes) varied across the

mini-blocks. Unlike in the main experiment, the stimuli were not backward masked in order to increase

visibility. (D) Exemplars of the six object categories: chairs, lamps, beds, cars, human bodies, bottles.

Fifty exemplars were used for each category.

Materials and Methods

Participants

Twenty-three healthy adult volunteers with normal or corrected-to-normal vision gave written informed consent and participated in the experiment. All participants took part in three experimental sessions, on different days. One participant was excluded because of low performance on the visual search task (the difference between the proportion of false alarms and hits was lower than two standard deviations from the average difference). Twenty-two participants (mean age: 25.36 years; age range: 20-32 years; 11 female) were included in the reported analyses. The study was approved by the local ethics committee (CMO Arnhem-Nijmegen).

Experimental Paradigm

In the main experiment, on each trial, the display contained two boxes in the horizontal and vertical locations (Fig. 1). The vertical boxes had a white bounding frame, signifying their relevance. Each of the four boxes contained a random image containing the average power spectrum of the objects from the six categories with random phases. Objects were mixed with these random images. On each trial, an exemplar from one of the six categories could be presented in one of the two vertical boxes (1/7 probability each) or no object would be presented (1/7 probability). Simultaneously, an exemplar from one of the six categories could be presented in both the horizontal boxes (1/7 probability each) or no object would be presented (1/7 probability). Each block consisted of 49 trials to fill the co-occurrence matrix of the horizontal and vertical object conditions, such that the conditions presented in the horizontal and vertical boxes were orthogonal to each other.

In each block of the main experiment, participants would either search for one of the six categories in the vertical boxes or would detect a thickening of the frames of the bounding

boxes in the vertical location (for trial layout, see Fig. 1). Participants pressed the response

button when the cued object category was shown in one of the vertical locations, which

occurred on 7/49 trials. Participants had to respond within 1.2s. The brief presentation duration

(67 ms) required participants to maintain fixation to be able to detect the target in one of the two

vertical locations. Participants were instructed that they could ignore the objects presented at

the horizontal locations. In the thickening condition, participants had to indicate, by pressing the

response button, when one of the sides of the two bounding boxes became thicker than the

others (thickening occurred on 7/49 trials in all blocks). Data from these thickening task blocks

in the main experiment were not further analyzed because the within-block comparisons

provided a more stringent test of our hypotheses, controlling for block-based effects (e.g.,

related to the processing of the category cue itself). The simultaneously presented objects in the

horizontal boxes were always task-irrelevant. Each run contained four blocks, all containing a

different search condition, such that across the seven search runs in each fMRI session each

search block occurred four times. Feedback about search performance was provided at the end

of each block.

In addition to the main experiment, participants completed a "baseline" experiment. This

experiment was included to localize body-selective regions of interest (for the univariate

analyses) and to obtain prototypical object category response patterns (for the multivariate

analyses). In the baseline experiment, in different blocks, exemplars of one of the six categories

or scrambled exemplars of one of the six categories were presented in both the boxes in either

the horizontal or vertical locations (the other location left empty). These objects were mixed with

a random image containing the average power spectrum of the objects from the six categories

with random phases. The seven object conditions (six object categories and a scrambled

objects condition containing a mix of scrambled objects from the six categories) and two

presentation locations were blocked into mini-blocks containing 18 trials each. In each mini-

block, participants had to search for thickening of the frames of the boxes where objects were

being presented (1/7 probability of presence; each pair of thickening events had at least two

non-thickening trials between them). Each block contained seven mini-blocks, with distinct

object-location pairing, such that across the four blocks in each baseline experiment run, each

type of block occurred twice. At the end of each block performance feedback was provided.

Each participant attended three experimental sessions. The first behavioral session

required each participant to get exposed to the entire set of objects followed by the completion

of one run of the baseline experiment and two runs of the main experiment. The second and the

third sessions involved fMRI. In each of those sessions, the participant first browsed through the

entire set of objects at their own pace, and then performed one run of the main experiment

during the anatomical scan. This was followed by the functional recordings as the participants

performed one run of the baseline experiment followed by four runs of the main experiment

followed by one run of the baseline experiment followed by three runs of the main experiment.

Stimuli

The stimulus presentation dimensions are shown in Fig. 1B. We acquired 50 exemplar

silhouettes in real-world poses for each of the six categories of interest (beds, bottles, cars,

chairs, lamps, and human bodies; shown in Fig. 1D). We obtained scenes containing the

relevant objects from the SUN2012 database (Xiao et al., 2010) and Google images which were

"Labelled for non-commercial reuse with modifications", cropped out the objects, scaled them

such than on one of the axes of the objects extended throughout the image, and converted

them to silhouettes.

On each trial, the chosen exemplars were shown in the boxes, embedded in noise as

mentioned above. The location of the objects within the boxes was jittered to increase

variability. Objects that extended throughout the image horizontally were presented in one of

three places within the box: touching the upper side, centered, or touching the lower side of the

box. Similarly, objects that extended throughout the image vertically could be placed touching

the left side, centered, or the right side of the box. The horizontally-placed boxes in the display

contained the same stimulus (Fig. 1C).

fMRI data acquisition and preprocessing

Functional (echo-planar imaging (EPI) sequence; 66 transverse slices per volume; resolution:

2x2x2mm; repetition time (TR): 1s; time to echo (TE): 35.2ms; flip angle: 60°; 6x multi-band

acceleration factor) and anatomical (MPRAGE sequence; 192 sagittal slices; TR: 2.3s; TE:

3.03ms; flip angle: 8°; 1x1x1mm resolution; FOV: 256mm) images were acquired with a 3T

MAGNETOM Skyra MR scanner (Siemens AG, Healthcare Sector, Erlangen, Germany) using a

32-channel head coil.

The functional data were analyzed using MATLAB (2017a) and SPM12. During

preprocessing, within each session, the functional volumes were realigned, co-registered to the

structural image, re-sampled to a 2×2×2mm grid, and spatially normalized to the Montreal

Neurological Institute 305 template included in SPM12. Data were high-pass filtered with a cut-

off of 128s. Temporal autocorrelations were accounted for using the AR(1) method in SPM. A

gaussian filter (FWHM 3 mm) was applied to smooth the images.

Statistical analysis

For each participant, general linear models (GLMs) were created to model the conditions in the

experiment. In the main experiment, the GLM included regressors for the 49 conditions of

interest: 7 attention blocks x 7 stimulus conditions presented in the task-irrelevant (horizontal)

locations. As this was an event-related design, the onsets of the stimuli were modelled as

impulse functions (delta functions) and the time series was convolved with the canonical HRF.

In the baseline experiment, the GLM included regressors for the 14 conditions of interest: 7

stimulus conditions x 2 presentation locations. As this was a block-design, the mini-blocks

corresponding to each stimulus condition were modelled as boxcars and the time series was

convolved with the canonical HRF. Separate GLMs were executed for each run of the main and

baseline experiments. The acquired regression weights were averaged across repetitions of the

corresponding conditions across the runs. Regressors of no interest were also included to

account for differences in the mean MR signal across scans and for head motion within scans.

In the univariate analysis, the regression weights (betas) from the GLM were compared

between conditions after averaging across the voxels of a region of interest (ROI). In the

multivariate analysis, the pattern of betas from the GLM across the voxels of an ROI were

compared between conditions using Kendall's tau correlation coefficient (τ) as a metric for

similarity. Before comparing the betas between the main and baseline experiments, the data

were mean-centered: the mean across all main experiment condition betas was subtracted from

those condition betas (separately for each voxel), and the mean across all baseline experiment

condition betas were subtracted from those condition betas.

Regions of interest

All ROIs were defined across both hemispheres (except FBA, which was limited to the right

hemisphere). In the multivariate analysis, we focused on two ROIs, the lateral-occipital cortex

(LOC) and the early visual cortex (EVC). The LOC ROI was defined using a group-constrained

subject-specific method (Fedorenko et al., 2010). The group-level ROI was defined by first

contrasting the average response to the 6 object categories with the response to the scrambled

objects in the baseline experiment. Threshold-free cluster enhancement (TFCE; Smith and

Nichols, 2009) with a permutation test was used to correct for multiple comparisons (at $p < 0.05$)

across the whole brain. The resulting voxels were intersected with the lateral occipital cortex

ROI from Julian et al. (Julian et al., 2012) to obtain the group-level LOC ROI. Then, for each

participant, the 1000 most object-selective voxels (average object response - scrambled

stimulus response, in the baseline experiment horizontal conditions) within the group-level LOC

ROI were selected for further analysis. The EVC ROI was defined at the individual participant

level as the 1000 most responsive voxels (average object response > 0, in the baseline

experiment horizontal conditions) in Brodmann area 17 (corresponding to V1; Wohlschläger et

al., 2005). Brodmann area 17 was taken from the Brodmann atlas available in SPM12.

In the univariate analysis we focused on two body-selective ROIs, the extrastriate body

area (EBA; Downing et al., 2001) and the fusiform body area (FBA; Peelen and Downing, 2005).

The ROIs were defined using the method described above for LOC. The group-level ROI was

defined by first contrasting the response to bodies with the average response to the other 5

categories in the baseline experiment. TFCE was used to correct for multiple comparisons (at p

< 0.05) across the whole brain. The resulting voxels were intersected with ROIs from Julian et

al. (2012): the extrastriate body area ROI to obtain the group-level EBA ROI and the fusiform

face area (FFA) ROI to obtain the group-level FBA ROI (FBA is not provided, but the FFA and

FBA closely overlap at the group-level; Peelen and Downing, 2005). Then, for each participant,

the 20 most body-selective voxels (body response - average response to other objects, in the

baseline experiment horizontal conditions) within the group-level ROIs were selected for further

analysis.

Multivariate analysis approach

In the multivariate analyses, we correlated multivoxel activity patterns evoked by the task-

irrelevant objects in the main experiment with multivoxel activity patterns evoked by the clearly

visible objects in the baseline experiment, using Kendall rank-ordered correlation; τ. We expect

to find stronger correlations between corresponding object categories (e.g., between bodies in

the main experiment and bodies in the baseline experiment), than between non-corresponding

categories (e.g. between bodies in the main experiment and beds in the baseline experiment).

As such, the difference between corresponding and non-corresponding category correlations is

a measure of category processing (Peelen et al., 2009), analogous to decoding accuracy. Here,

we computed *proximity* to the categories in the baseline experiment as the correlation with that

category minus the correlation with the other categories in the baseline experiment. For

example, for bodies, the proximity to bodies (in the baseline experiment) is the correlation

between bodies in the main experiment and bodies in the baseline experiment minus the

average correlation between bodies in the main experiment and the other five categories in the

baseline experiment.

Image-based discriminability approach

To rule out that bodies differed systematically from the other objects in terms of low-level

features, we used representations of the exemplars in the layers of a convolutional neural

network (trained for object recognition in natural images; CNN; AlexNet: Krizhevsky et al., 2012)

to test for image-based categorizability differences across the categories. Output activations at

each layer corresponding to 50 exemplars of each of the six categories, embedded in noise as

in the fMRI experiment, in the three possible locations defined by the shapes (see the

subsection on Stimuli), were extracted. Balanced linear support vector machines (SVM) were

trained to classify between the images of one category (150 images each) as opposed to the

other categories. 10-fold cross-validated classification accuracies were reported for each

category for each layer of the CNN.

Results

In the main experiment, participants detected the presence of object silhouettes belonging to one of six categories (Fig. 1D), in different blocks. Throughout the experiment, only the vertically-aligned locations were relevant for the detection task (Fig. 1A). Each block started with a category cue (e.g. "Car") indicating the target category for that block (Fig. 1A), followed by 49 object detection trials. In 42 trials (6/7th), one of the two task-relevant locations contained a briefly-presented object (67 ms) within phase-scrambled noise (Fig. 1B), with each category presented equally often (7 trials each). In the remaining 7 trials (1/7th) no object was presented.

Crucially, in 6/7th of the trials, two objects were simultaneously presented in the horizontally-aligned locations (Fig. 1A). These objects were briefly presented (67 ms), embedded in noise, and backward masked. This was done to reduce the possibility of participants moving their eyes (and/or spatial attention) to the task-irrelevant objects. Objects at the horizontal locations were never relevant for the participants and participants were instructed that these could be completely ignored. The occurrence probabilities of the categories were the same as for the task-relevant locations. The 7 vertical and 7 horizontal conditions were fully crossed within each block, resulting in 49 trials, which were presented in random order. Trials were coded according to the categories presented in the horizontally aligned (task-irrelevant) locations, as these were the focus of our analyses.

Task performance (task-relevant locations)

Averaged across the two fMRI sessions and across object search blocks, participants had a hit rate of 78.3% (proportion of the target-present trials where participants responded) and a false alarm rate of 5.6% (proportion of the target-absent trials where participants responded), resulting in an average d' (zscore(hit rate) - zscore(false alarm rate)) of 2.7 (beds: 2.0; cars: 2.4; bottles: 2.6; bodies: 2.9; chairs: 2.9; lamps: 3.3). Note that this was the performance for the task-relevant stimuli presented at the vertical locations. All fMRI analyses focused on the

objects presented at the task-irrelevant horizontal locations. For responses to objects at the

task-irrelevant locations, we refer the reader to the section *The relationship between attentional*

modulation and behavioral responses.

Univariate results in EBA and FBA

Previous research has shown that bodies evoke a selective univariate response in two focal

regions of high-level visual cortex: the extrastriate body area (EBA; Downing et al., 2001) and

the fusiform body area (FBA; Peelen & Downing, 2005). Here, EBA and FBA were defined

based on responses in the baseline experiment (see Material and Methods). We tested for

spatially-global attention effects for bodies in these ROIs by comparing body-selective

responses in EBA and FBA evoked by task-irrelevant bodies across target detection blocks in

the main experiment. Betas were averaged across the voxels of each ROI to acquire one beta

per condition for each ROI. For each category, the beta corresponding to within-block trials in

which no objects were presented was subtracted to account for block effects. Responses to

non-body objects and non-body detection blocks were averaged, such that we had 4 values for

each ROI: body and non-body stimuli, presented in the body and non-body detection blocks.

The difference between body and non-body stimuli within each block is a measure of body

selectivity.

A 2 (ROI) x 2 (attention: body, other categories) repeated-measures ANOVA on body

selectivity (response to bodies minus average response to other categories) revealed a main

effect of attention ($F_{1,21}$ = 7.2, p = 0.014, η^2_p = 0.25), reflecting stronger body selectivity in body

attention blocks than non-body attention blocks (Fig. 2A). This attention effect interacted with

ROI ($F_{1,21}$ = 4.6, p = 0.043, η^2_p = 0.18), being stronger for EBA than FBA. When analyzed

separately, both EBA and FBA showed an attention effect, such that body selectivity was higher

in body detection blocks than in other category detection blocks (EBA: $F_{1,21}$ = 7.4, p = 0.013, η^2_p

= 0.26; FBA: $F_{1,21}$ = 4.4, p = 0.049, η^2_p = 0.17; Fig. 2A). The attention effect was consistent

across ROI sizes (Fig. 5). In EBA, bodies evoked a selective response in both the body

detection blocks (t_{21} = 4.6, p < 0.001, d = 1.00) and the other category detection blocks (t_{21} =

4.4, p < 0.001, d = 0.96), while in FBA body selectivity was only positive in the body detection

blocks (t_{21} = 2.5, p = 0.02, d = 0.55; other category detection blocks: t_{21} = 0.8, p = 0.42, d =

0.17).

The attention effect for bodies in EBA and FBA could reflect enhanced responses to

bodies presented in body detection blocks, but may also (or additionally) reflect reduced

responses (suppression) to the other categories presented in body detection blocks. To test

these alternatives, we compared body and object-evoked responses across the body and

object-detection blocks (after subtracting the response to blanks within each block). Averaged

across ROIs, there was a higher response to bodies in body detection blocks than in other

category detection blocks, which was marginally significant (paired t-test, t_{21} = 2.1, p = 0.05, d =

0.46; Fig. 2B). There was no evidence that the response to the other objects was suppressed,

with equally strong responses in both blocks (paired t-test, t_{21} = 0.19, p = 0.85, d = 0.04). These

effects were also observed, though weaker, in each ROI separately (statistics provided in Fig.

2B).

These results provide the first evidence for spatially-global attentional modulation for

body silhouettes, show that these effects are strongest in EBA, and link these effects to

enhancement of body responses rather than suppression of non-body responses.

Figure 2: Univariate attention effect in body-selective ROIs. (A) Body selectivity (response to body - average response to other objects) was higher when bodies were attended, in both ROIs. This provides evidence for spatially-global attentional modulation for body silhouettes. (B) Across ROIs, the response to bodies (corrected for block-wise differences by subtracting the corresponding blank responses) was enhanced while the responses to other categories remained unchanged. Error bars indicate 95% confidence intervals for the measures indicated on the y-axes. The asterisks indicate p-values for the t-tests of the corresponding comparisons (*p< 0.05, **p<0.01, ***p< 0.001). EBA and FBA ROIs are displayed together with MNI z-coordinates.

Multivariate results in LOC

Previous studies have shown that multivoxel activity patterns in object-selective cortex distinguish between object shapes (Haushofer et al., 2008; Op de Beeck et al., 2008; Eger et al., 2008). This gave us another opportunity to test for spatially-global effects of attention,

including for non-body categories. Here, instead of body selectivity, we used proximity (Pr) as

dependent measure. Proximity was based on correlations between response patterns in the

main experiment and response patterns in the baseline experiment, following previous work

(Peelen et al., 2009). Proximity reflects how similar a category's response pattern in the main

experiment is to a category's response pattern in the baseline experiment, relative to the other

categories in the baseline experiment (Materials and Methods). For example, for bodies, the

proximity to bodies (in the baseline experiment) is the correlation between bodies in the main

experiment and bodies in the baseline experiment minus the average correlation between

bodies in the main experiment and the other five categories in the baseline experiment.

Attentional modulation for bodies in LOC

The proximity to bodies is shown in Fig. 3A. A 2 (attention: body, other categories) x 2 (stimulus

presented: body, other categories) repeated-measures ANOVA revealed a significant interaction

($F_{1,21}$ = 30.4, $p < 0.001$, η^2_p = 0.59), reflecting a stronger difference between the proximities for

body and non-body categories when participants attended to bodies (t_{21} = 9.9, $p < 0.001$, d =

2.2) than when they attended to the other categories (t_{21} = 8.1, $p < 0.001$, d = 1.8). The

multivariate attention effect in LOC was consistent across ROI sizes (Fig. 5). These results

provide further evidence for spatially-global attentional modulation of body processing.

The attention effect for bodies in LOC could reflect enhanced proximity to bodies for the

bodies presented in body detection blocks, but may also (or additionally) reflect reduced

proximity to bodies (suppression) for the other categories presented in body detection blocks.

To test for body-selective enhancement, we compared the proximity (to bodies in the baseline

experiment) for bodies in the body detection blocks with the corresponding proximity of other

objects in the body detection blocks. To account for overall differences between blocks (e.g.,

related to the cue or to block-based attentional bias), we subtracted the proximity to bodies for

the within-block trials in which no objects were presented. Results showed that proximity to

bodies was significantly enhanced for bodies presented in the body detection blocks as

compared with bodies presented in the other detection blocks (t_{21} = 3.5, p = 0.002, d = 0.76;

blue comparison in Fig. 3B). There was no evidence for suppression: proximity to bodies was

not different for objects presented in the body detection blocks as compared with objects

presented in the other detection blocks (t_{21} = 0.3, p = 0.78, d = 0.06; green comparison in Fig.

3B). The difference between these effects (red comparison in Fig. 3B) corresponds to the same

multivariate attention effect as shown in Fig. 3A. These results show that the multivariate

attention effect was primarily driven by the enhancement of body-selective response patterns, in

line with the univariate results (Fig. 2).

Figure 3: Probing the multivariate attention effect for bodies in LOC. (A) The selective proximity for

bodies (proximity to bodies for Body vs Other) is higher when bodies are attended, which is evidence for

a multivariate attention effect in LOC (comparison highlighted in red), reflecting response gain. (B)

Proximity (to bodies) of bodies and other categories were compared between the body attention blocks

and the other category attention blocks, corrected for block-wise differences by subtracting the proximity

(to bodies) to blank responses within blocks. When bodies were attended, the proximity of bodies was

enhanced, whereas the proximity of the other categories was not affected (inset: gray objects correspond

to attention-dependent representations and black to benchmark representations). This indicated that the

multivariate attention effect for bodies in LOC (the comparison corresponding to the red bar) was driven

primarily by enhancement of body-selective response patterns when bodies were attended. 95%

confidence intervals for the measures indicated on the y-axes are shown. The asterisks indicate the p-

values for the t-tests of the corresponding comparisons (*p< 0.05, **p<0.01, ***p< 0.001). Blue:

attentional modulation for bodies; green: attentional modulation for other categories.

The relationship between attentional modulation and univariate body selectivity of LOC voxels

Next, we tested whether the multivariate attention effect observed for bodies in LOC depended

on the (univariate) body-selectivity of voxels included in LOC. To this end, we computed the

multivariate attention effect for bodies in an ROI that consisted of LOC voxels that responded

less strongly to bodies than to other categories in the baseline experiment (on average 330.8

out of the original 1000 voxels satisfied this criterion). Results were compared with a size-

matched ROI consisting of randomly-sampled LOC voxels (size-matching done within each

participant; sampled 100 times). Attentional modulation was computed in the same way as for

the whole LOC in the original analysis (red comparison in Fig. 3). Attentional modulation was

stronger for the size-matched ROI than the non-selective ROI (t_{21} = 3.1, p = 0.006, d = 0.68).

However, attentional modulation was significant even in the non-selective ROI (t_{21} = 2.1, p =

0.047, d = 0.46). These results suggest that the attentional modulation in LOC was partly but

not exclusively driven by body-selective voxels.

Attentional modulation for non-body categories in LOC

Using the multivariate analysis framework outlined above for bodies, we can similarly test for

spatially-global attentional modulation for the other categories. For each non-body category, we

computed the multivariate attention effect as was done for bodies, now using the proximity to

that category in the baseline experiment. To reduce the complexity of the ANOVA and the

corresponding visualization of the data, we used *selective proximity* as the dependent measure.

Selective proximity is the proximity difference between the corresponding and non-

corresponding categories (e.g., the difference between the two left-most data points in Fig. 3A).

As an intuition for what this new measure represents, note that in the case of bodies, selective

proximity is analogous to the body selectivity measure in the univariate analysis.

In LOC, a 6 (category of interest) x 2 (category attended/unattended) repeated-

measures ANOVA on these selective proximities revealed a significant interaction ($F_{5,105} = 3.9$,

$p = 0.003$, $\eta^2_p = 0.16$; Fig. 3A), indicating that attention differentially affected the selective

proximity of the six categories. Six paired-sample t-tests showed that attentional modulation was

significant for bodies ($t_{21} = 5.5$, $p_{bonf} < 0.001$, $d = 1.2$; red comparison in Fig. 4A), as already

shown in the previous analyses (Fig. 3). No significant multivariate attention effect was

observed for the other categories ($t_{21} < 2.4$, $p_{bonf} > 0.1$, $d < 0.5$; for all tests; Fig. 4A).

Attentional modulation in EVC

The same analysis was conducted in early visual cortex (EVC; see Materials and Methods). A 6

(category of interest) x 2 (category attended/unattended) repeated-measures ANOVA on

selective proximities revealed a marginally significant interaction ($F_{5,105} = 2.2$, $p = 0.06$, $\eta^2_p =$

0.095; Fig. 4B), no significant main effect of attention ($F_{1,21} = 0.6$, $p = 0.4$, $\eta^2_p = 0.028$), and a

marginally significant main effect of category ($F_{5,105} = 2.2$, $p = 0.06$, $\eta^2_p = 0.096$). Paired-sample

t-tests showed no significant attentional modulation for any of the categories ($|t_{21}| < 2.2$, $p_{bonf} >$

0.1, $d < 0.48$; for all tests). Finally, attentional modulation for bodies was significantly stronger in

LOC than in EVC ($t_{21} = 2.9$, $p = 0.01$, $d = 0.63$).

Figure 4: Multivariate attention effect. The selective proximities, for the attended and unattended

conditions, are shown for the six categories in the two ROIs. The multivariate attention effect is the

difference between attended and unattended selective proximity (comparison highlighted in red). A) In

LOC, we find evidence for attentional modulation of the selective proximities of bodies. B) No attentional

modulation was found in EVC. Error bars indicate 95% confidence intervals for the selective proximities.

The asterisks denote Bonferroni corrected p-values for the t-tests of the twelve comparisons related to

selective proximities, and Bonferroni corrected p-values for the t-tests of the six comparisons related to

selective proximity modulations (*p< 0.05, **p<0.01, ***p< 0.001).

The relationship between attentional modulation and behavioral responses

In both multivariate and univariate analyses, we found that the body-selective response elicited

by body silhouettes in task-irrelevant locations was enhanced in body detection blocks

compared with other category detection blocks. This raises the question of whether this

attentional modulation affected behavior in the detection task. Particularly, did participants

disproportionally false alarm to the bodies at task-irrelevant locations when detecting bodies at

task-relevant locations? Because of the orthogonal design, each category (+blank stimulus) in

the irrelevant location appeared equally often with each category (+blank stimulus) in the

relevant location. Therefore, when the target category (e.g., bodies) appeared at the task-

irrelevant location no target was presented at the task-relevant locations in most trials (6/7th),

and participants had to withhold their response. For these trials, we tested whether responses

(i.e., false alarms) depended on the combination of the category presented and the category

that was the target in that block. To this end, for each category, we computed the difference

between the false alarm rate (FA) to that category and the average FA to the other categories,

separately for each block. We then compared this ΔFA for trials in which the object matched the

target category (e.g., bodies presented in body blocks) and trials in which the object

mismatched the target category (e.g., bodies presented in bed blocks).

A 2 (matching, non-matching) x 6 (target category) repeated-measures ANOVA on ΔFA

revealed a significant interaction ($F_{5,105}$ = 3.3, p = 0.008, η^2_p = 0.14; Fig. 6). Six paired-sample t-

tests showed that ΔFA was stronger when the object matched the target category for all

categories (t_{21} > 2.9, p_{bonf} < 0.05, d > 0.63, for all non-body categories, biggest difference of

6.5% for cars; bodies: t_{21} = 2.79, p_{bonf} = 0.066, difference of 3.7%, d = 0.61). These results show

that participants disproportionally false alarmed when the target category was shown at the

task-irrelevant location. Contrary to the fMRI results, however, this effect was relatively weak for

bodies.

Figure 5: The influence of voxel selection on body attention effects. The univariate attention effects,

for EBA and FBA, and the multivariate attention effects, for LOC and EVC, for bodies, are shown as a

function of the number of voxels selected within each ROI. The attention effects for bodies observed in

EBA, FBA, and LOC, are observed regardless of the number of voxels selected. Error bars indicate 95%

confidence intervals for the attention effects.

Figure 6: The relationship between attentional modulation and behavioral responses. Participants

disproportionally false alarmed when the target category was shown at the task-irrelevant location

(matching>non-matching) but this effect was relatively weak for bodies. Error bars indicate 95%

confidence intervals for ΔFA. The asterisks denote instances where t-tests returned $p_{bonf} < 0.05$ for the

corresponding comparisons (*$p < 0.05$, **$p < 0.01$, ***$p < 0.001$).

Image-based discriminability

In all fMRI analyses, we found that bodies were more strongly represented and more strongly

modulated by attention than the other categories. This could reflect an interesting property of

bodies, for example, related to the life-time relevance of detecting conspecifics or to the

increased familiarity with body shapes. However, it could potentially also reflect uncontrolled

image-based differences: perhaps the body silhouettes included in the study stood out from the

other objects in terms of low-level features. To exclude this possibility, we decoded object

categories from the object exemplar representations in the layers of a convolutional neural

network trained for object recognition (Materials and Methods). For each of the 6 categories, in

each layer of the CNN, one-vs-all linear discriminant classifiers were trained to discriminate

each category from the other categories using the 50 exemplars of each category presented in

the fMRI experiment. 10-fold cross-validation accuracies were analyzed across the objects.

As shown in Fig. 7, bodies were less discriminable than most other categories in the

early layers of the CNN. It is only in the mid to final layers - where overall classification is almost

at ceiling - that the classification accuracy for bodies is similar to the average accuracies for the

other categories. This result shows that the image-based discriminability was, if anything, lower

for bodies than for the other objects.

Figure 7: Hierarchical image-based discriminability of the exemplars used in the fMRI experiment.

One-vs-all classifiers were trained for each of the six categories, on the output activations of each layer of

a convolutional neural network trained for object recognition (AlexNet). 10-fold crossvalidation accuracies

are shown for all the objects in addition to the average accuracies for the non-body objects (termed

'Other'). Discriminability based on low-level features (corresponding to the early layers of the AlexNet)

was, if anything, lower for the human bodies than for the other objects. Therefore, it is unlikely that the

body-selective fMRI results reflect a distinct low-level property of bodies. 'Conv' refers to the convolutional

layers of AlexNet and 'FC' refers to the fully-connected layers.

Discussion

Across multiple analyses, we found convincing evidence that attention to human bodies

enhanced visual cortex responses selective to bodies presented at task-irrelevant locations.

This modulation reflected response gain rather than a generic bias, and could not be explained

by low-level feature similarity of bodies. These results indicate that spatially-global attentional

modulation – a hallmark of feature-based attention – can be found for features diagnostic of the

presence of the human body.

The attentional effects observed here for body silhouettes are unlikely to reflect attention

to low-level features such as orientation or color, for several reasons. First, we included a

relatively large number of object categories in the experiment to ensure that participants could

not detect objects based on low-level features, as these were shared with other categories (e.g.,

bottles were vertical, similar to bodies). Second, we presented object silhouettes instead of

photographs to avoid possible low-level differences between categories in texture or color.

Third, the image-based discriminability for each category, established using a convolutional

neural network (CNN), indicated that bodies were difficult to discriminate from other categories

based on low-level features encoded in the early layers of the CNN. Finally, the fMRI results

showed attentional modulation in object-selective cortex (LOC) and body-selective EBA/FBA,

but not early visual cortex (EVC), indicating an attentional modulation at a higher level of visual

processing.

Our results are in line with the feature similarity gain modulation model (FSGM; Maunsell

& Treue, 2006) by showing that feature-based attention enhanced the response to the voxels '

preferred stimuli. Specifically, attention to bodies made the response pattern evoked by task-

irrelevant bodies more similar to prototypical body response patterns established in a separate

baseline experiment. Furthermore, these attention effects were strongest in body-selective

voxels of LOC. Finally, reliable univariate attention effects were observed in independently-

defined body-selective regions (EBA/FBA). It should be noted that we did not find evidence that

responses to the other categories were suppressed, as proposed by FSGM. However, the

response to other categories was low and any suppression (posited to be smaller in magnitude

than enhancement by FSGM) might not be observable in this case.

The finding of spatially-global modulation for human bodies adds to previous evidence

for global modulation for faces. Specifically, in one study, peripherally presented and task-

irrelevant faces evoked a stronger face-selective N170 electro-encephalography (EEG)

response when participants attended to faces than to houses (Störmer et al., 2019).

Furthermore, in fMRI, responses to peripheral faces in the face-selective fusiform face area

(FFA) were more strongly modulated by the task-set of the participants (i.e., whether or not they

focused on faces) than by spatial attention (Reddy et al., 2007). Together with the current

findings, these results provide evidence for spatially-global attentional modulation for bodies and

faces, two socially relevant categories that are selectively represented in the visual cortex

(Downing et al., 2006; Kanwisher, 2010).

While these results suggest that bodies and faces may be special – reflecting their

unique social and biological significance – we do not rule out that spatially-global attentional

modulation may also exist for other highly-familiar object categories. For example, behavioral

studies showed that animals and vehicles could be detected in the near-absence of spatial

attention (Li et al., 2002; but see Cohen et al., 2011), with category-based attention facilitating

object detection independently of spatial attention (Stein and Peelen, 2017). Indeed, based on

the overlap in human and animal features in detection tasks (Evans and Treisman, 2005), it is

plausible that our results would generalize to other animals, particularly those that activate

body-selective regions (Downing et al., 2006). Similarly, extensive experience with particular

objects may drive selective neural tuning (Gauthier and Logothetis, 2000; McGugin et al., 2012;

Frank et al., 2014) and give rise to similar behavioral advantages as those observed for bodies

(Hershler and Hochstein, 2009; Golan et al., 2014; Reeder et al., 2016; Stein et al., 2016).

Taking everything together, the evidence suggests that features that are diagnostic of

bodies meet many of the previously proposed criteria for basic features: showing spatially-global

attentional modulation (Maunsell and Treue, 2006), being processed "early, automatically, and

in parallel across the visual field" (Treisman and Gelade, 1980), and being represented

selectively in the visual system (Treisman, 2006). Indeed, Treisman (2006) proposed that the

feature detectors of the feature integration theory are not necessarily limited to low-level

features such as orientation and color. Raising the possibility that there may be animal feature

detectors, Treisman (2006) noted that animal features may not necessarily be more complex for

the visual system than colors, line orientations, or direction of motion. By providing evidence for

spatially-global attentional modulation for human bodies, our results support this proposal.

Our findings raise the question of what features are attended when attention is directed

to bodies. Addressing this question for animals, Treisman (2006) suggested that: "participants

may be set to sense, in parallel, a highly overlearned vocabulary of features that characterize a

particular semantic category." One possibility is thus that attention to bodies is mediated by

attention to a set of mid-level features that are diagnostic of human bodies (Ullman et al., 2002;

Reeder and Peelen, 2013). Alternatively, attention may be directed to holistic representations of

body shape (Reed et al., 2003; Stein et al., 2012). Future studies could test these alternatives

by measuring global attentional modulation for various body-related features, body parts, and

inverted bodies at the task-irrelevant location while participants attend to bodies at the task-

relevant locations (Reeder and Peelen, 2013).

To conclude, the current results provide evidence for spatially-global attentional

modulation for human bodies in high-level visual cortex, linking this modulation to body-selective

representations in univariate and multivariate analyses. Combining these results with previous

behavioral and neuroimaging studies, we propose that bodies may be processed as basic

features, supporting the rapid and parallel detection of conspecifics in our environment even

outside the focus of spatial attention.

References

Carrasco M (2011) Visual attention: The past 25 years. Vision Research 51:1484–1525.

Chun MM, Golomb JD, Turk-Browne NB (2011) A Taxonomy of External and Internal Attention.

Annu Rev Psychol 62:73–101.

Cohen MA, Alvarez GA, Nakayama K (2011) Natural-Scene Perception Requires Attention.

Psychol Sci 22:1165–1172.

Downing PE, Bray D, Rogers J, Childs C (2004) Bodies capture attention when nothing is

expected. Cognition 93:B27–B38.

Downing PE, Chan AW-Y, Peelen MV, Dodds CM, Kanwisher N (2006) Domain Specificity in

Visual Cortex. Cerebral Cortex 16:1453–1461.

Downing PE, Jiang Y, Shuman M, Kanwisher N (2001) A Cortical Area Selective for Visual

Processing of the Human Body. Science 293:2470–2473.

Evans KK, Treisman A (2005) Perception of Objects in Natural Scenes: Is It Really Attention

Free? Journal of Experimental Psychology: Human Perception and Performance 31:1476–1492.

Fedorenko E, Hsieh P-J, Nieto-Castañón A, Whitfield-Gabrieli S, Kanwisher N (2010) New

Method for fMRI Investigations of Language: Defining ROIs Functionally in Individual Subjects.

Journal of Neurophysiology 104:1177–1194.

Frank SM, Reavis EA, Tse PU, Greenlee MW (2014) Neural mechanisms of feature conjunction

learning: Enduring changes in occipital cortex after a week of training: Neural Mechanisms of

Feature Conjunction Learning. Hum Brain Mapp 35:1201–1211.

Gauthier I, Logothetis NK (2000) Is face recognition not so unique after all? Cognitive

Neuropsychology 17:125–142.

Golan T, Bentin S, DeGutis JM, Robertson LC, Harel A (2014) Association and dissociation

between detection and discrimination of objects of expertise: Evidence from visual search. Atten

Percept Psychophys 76:391–406.

Haushofer J, Livingstone MS, Kanwisher N (2008). Multivariate patterns in object-selective

cortex dissociate perceptual and physical shape similarity. PLoS Biol. 6 (7), e187.

Hershler O, Hochstein S (2009) The importance of being expert: Top-down attentional control in

visual search with photographs. Attention, Perception & Psychophysics 71:1478–1486.

Jehee JFM, Brady DK, Tong F (2011) Attention Improves Encoding of Task-Relevant Features

in the Human Visual Cortex. Journal of Neuroscience 31:8210–8219.

Julian JB, Fedorenko E, Webster J, Kanwisher N (2012) An algorithmic method for functionally

defining regions of interest in the ventral visual pathway. NeuroImage 60:2357–2364.

Kamitani Y, Tong F (2005) Decoding the visual and subjective contents of the human brain. Nat

Neurosci 8:679–685.

Kanwisher N (2010) Functional specificity in the human brain: A window into the functional

architecture of the mind. Proceedings of the National Academy of Sciences 107:11163–11170.

Krizhevsky A, Sutskever I, Hinton GE (2012) ImageNet classification with deep convolutional

neural networks. Adv Neural Inform Process Syst 1:1097–1105.

Li FF, VanRullen R, Koch C, Perona P (2002) Rapid natural scene categorization in the near

absence of attention. Proceedings of the National Academy of Sciences 99:9596–9601.

Liu T, Larsson J, Carrasco M (2007) Feature-Based Attention Modulates Orientation-Selective

Responses in Human Visual Cortex. Neuron 55:313–323.

Maunsell JHR, Treue S (2006) Feature-based attention in visual cortex. Trends in

Neurosciences 29:317–322.

McGugin RW, Gatenby JC, Gore JC, Gauthier I (2012) High-resolution imaging of expertise

reveals reliable object selectivity in the fusiform face area related to perceptual performance.

Proceedings of the National Academy of Sciences 109:17063–17068.

Op de Beeck HP, Torfs K, Wagemans J (2008). Perceived shape similarity among unfamiliar

objects and the organization of the human object vision pathway. J. Neurosci. 28 (40), 10111–

10123.

Peelen MV, Downing PE (2005) Selectivity for the Human Body in the Fusiform Gyrus. Journal

of Neurophysiology 93:603–608.

Peelen MV, Fei-Fei L, Kastner S (2009) Neural mechanisms of rapid natural scene

categorization in human visual cortex. Nature 460:94–97.

Peelen MV, Kastner S (2011) A neural basis for real-world visual search in human

occipitotemporal cortex. Proceedings of the National Academy of Sciences 108:12125–12130.

Reddy L, Moradi F, Koch C (2007) Top–down biases win against focal attention in the fusiform

face area. NeuroImage 38:730–739.

Reed CL, Stone VE, Bozova S, Tanaka J (2003) The body-inversion effect. Psychological

Science 14:302–308.

Reeder RR, Peelen MV (2013) The contents of the search template for category-level search in

natural scenes. Journal of Vision 13:13–13.

Reeder RR, Stein T, Peelen MV (2016) Perceptual expertise improves category detection in

natural scenes. Psychon Bull Rev 23:172–179.

Reeder RR, van Zoest W, Peelen MV (2015) Involuntary attentional capture by task-irrelevant

objects that match the search template for category detection in natural scenes. Atten Percept

Psychophys 77:1070–1080.

Ro T, Friggel A, Lavie N (2007) Attentional biases for faces and body parts. Visual Cognition

15:322–348.

Saenz M, Buracas GT, Boynton GM (2002) Global effects of feature-based attention in human

visual cortex. Nat Neurosci 5:631–632.

Serences JT, Boynton GM (2007) Feature-Based Attentional Modulations in the Absence of

Direct Visual Stimulation. Neuron 55:301–312.

Smith S, Nichols T (2009) Threshold-free cluster enhancement: Addressing problems of

smoothing, threshold dependence and localisation in cluster inference. NeuroImage 44:83–98.

Stein T, Peelen MV (2017) Object detection in natural scenes: Independent effects of spatial

and category-based attention. Atten Percept Psychophys 79:738–752.

Stein T, Reeder RR, Peelen MV (2016) Privileged Access to Awareness for Faces and Objects

of Expertise. Journal of Experimental Psychology: Human Perception and Performance 42:788–

798.

Stein T, Sterzer P, Peelen MV (2012) Privileged detection of conspecifics: Evidence from

inversion effects during continuous flash suppression. Cognition 125:64–79.

Störmer VS, Cohen MA, Alvarez GA (2019) Tuning Attention to Object Categories: Spatially

Global Effects of Attention to Faces in Visual Processing. Journal of Cognitive Neuroscience

31:937–947.

Treisman A (2006) How the deployment of attention determines what we see. Visual Cognition

14:411–443.

Treisman AM, Gelade G (1980) A Feature-Integration Theory of Attention. Cognitive Psychology

12:97–136.

Treue S, Trujillo JCM (1999) Feature-based attention influences motion processing gain in

macaque visual cortex. Nature 399:575–579.

Ullman S, Vidal-Naquet M, Sali E (2002) Visual features of intermediate complexity and their

use in classification. Nat Neurosci 5:682–687.

Wohlschläger AM, Specht K, Lie C, Mohlberg H, Wohlschläger A, Bente K, Pietrzyk U, Stöcker

T, Zilles K, Amunts K, Fink GR (2005) Linking retinotopic fMRI mapping and anatomical

probability maps of human occipital areas V1 and V2. NeuroImage 26:73–82.

Wolfe JM (1994) Guided search 2.0. A revised model of visual search. Psychon Bull Rev 1:202–

238.

Xiao J, Hays J, Ehinger KA, Oliva A, Torralba A (2010) SUN database: Large-scale scene

recognition from abbey to zoo. In: 2010 IEEE Computer Society Conference on Computer

Vision and Pattern Recognition, pp 3485–3492. San Francisco, CA, USA: IEEE. Available at:

http://ieeexplore.ieee.org/document/5539970/ [Accessed October 1, 2021].

Zhang W, Luck SJ (2009) Feature-based attention modulates feedforward visual processing.

Nat Neurosci 12:24–25.