Does the brain care about averages? A simple test

A. Tlaie,[1,2] K. A. Shapcott,[1] T. van der Plas,[3] J. Rowland,[3] R. Lees,[3] J. Keeling,[3]

A. Packer,[3] P. Tiesinga,[4] M. L. Schölvinck,[1,*] and M. N. Havenith[1,4,*]

[1]*Ernst Strüngmann Institute for Neuroscience, 60528 Frankfurt am Main, Germany*

[2]*Laboratory for Clinical Neuroscience, Centre for Biomedical Technology, Universidad Politécnica de Madrid, Spain*

[3]*Department of Physiology, Anatomy, and Genetics, University of Oxford, Oxford OX1 3PT, UK*

[4]*Department of Neuroinformatics, Donders Institute, Radboud University,*

Heyendaalseweg 135, 6525 AJ Nijmegen, The Netherlands

Trial-averaged metrics, e.g. tuning curves or population response vectors, are a ubiquitous way of characterizing neuronal activity. But how relevant are such trial-averaged responses to neuronal computation itself? Here we present a simple test to estimate whether average responses reflect aspects of neuronal activity that contribute to neuronal processing. The test probes two assumptions implicitly made whenever average metrics are treated as meaningful representations of neuronal activity:

1. Reliability: Neuronal responses repeat consistently enough across trials that they convey a recognizable reflection of the average response to downstream regions.

2. Behavioural relevance: If a single-trial response is more similar to the average template, it is more likely to evoke correct behavioural responses.

We apply this test to two data sets: (1) Two-photon recordings in primary somatosensory cortices (S1 and S2) of mice trained to detect optogenetic stimulation in S1; and (2) Electrophysiological recordings from 71 brain areas in mice performing a contrast discrimination task (Steinmetz et al. 2019, Nature). Under the highly controlled settings of data set 1, both assumptions were largely fulfilled: Single-trial responses were approximately as related to the average as would be expected if they represented discrete, down-sampled versions of the average response. Moreover, better-matched single-trial responses predicted correct behaviour. In contrast, the less restrictive paradigm of data set 2 met neither assumption, with the match between single-trial and average responses being neither reliable nor predictive of behaviour. We conclude that in data set 2, average responses do not seem particularly relevant to neuronal computation, potentially because information is encoded more dynamically when behaviour is less tightly restricted. Most importantly, we encourage researchers to apply this simple test of computational relevance whenever using trial-averaged neuronal metrics, in order to gauge how representative cross-trial averages are in a given context.

* These authors contributed equally.

Introduction

Brain dynamics are commonly studied by recording neuronal activity over many trials and averaging them. Trial-averaging has been applied to single neurons by describing their average response preferences [1–6] and, more recently, to neural populations [7–9]. The latter has revealed several unique phenomena: for instance, the adaptation of neuronal responses to the statistics of the perceptual environment [10] and orthogonalized neuronal coding of stimulus information, behavioural choices and memory [8, 11, 12].

These studies share the view that trial-averaged population activity is meaningful. For instance, upon finding that with repeated stimulus exposure, average population responses become more discriminative of behaviourally relevant stimuli [3, 4], it is implicitly assumed that this will improve an animal's ability to perceive these stimuli correctly. Related to this assumption is the notion that deviations from the average population response represent 'noise' of one form or another. The exact interpretation of such neuronal noise has been debated [13], ranging from truly random and meaningless activity [14–17], to neuronal processes that are meaningful but irrelevant for the neuronal computation at hand [18–20], to an intrinsic ingredient of efficient neuronal coding [21–23]. Nevertheless, in all of these cases a clear distinction is being made between neuronal activity that is directly related to the cognitive process under study (e.g. perceiving a specific stimulus) – which is typically approximated by a trial-averaged neuronal response – and 'the rest'. While this framework has undoubtedly been useful for characterizing the general response dynamics of neuronal networks, it remains an outstanding issue whether trial-averaged population activity is used to transmit information between neurons. In other words, neuroscientists care about average population responses, but does the brain?

There is evidence in both directions: Studies highlighting the large inter-trial variability of neuronal responses [19, 20, 24–26] suggest that average responses fail to capture ongoing neuronal dynamics. Then there is the simple fact that outside the lab, stimuli generally do not repeat, which renders pooled responses across stimulus repetitions a poor basis for neuronal coding. On the other hand, the fact that perceptual decisions can be altered by shifting neuronal activity away from the average [27–30] indicates that at least in typical lab experiments [31], average population responses matter [32].

In this paper, we formally test to what extent the assumptions inherent in the computation of average neuronal responses actually hold in different experimental contexts. Specifically, if neuronal coding and the resulting behaviour rely on average 'response templates' of population activity, two assumptions should be satisfied (Fig. 1):

1. Reliability: The responses of task-relevant neuronal populations repeat consistently enough to provide a recognizable reflection of the average response to downstream regions.

2. Behavioural relevance: If a single-trial response better matches the average response template, it should be more successful in evoking correct behavioural responses.

Results

To test these two assumptions across a range of experimental conditions, we examined two complementary data sets featuring neuronal recordings in behaving mice. One data set was acquired under extremely tightly controlled experimental settings; the other data set was acquired under less stringent experimental conditions.

Data set 1 consists of two-photon calcium imaging recordings in primary and secondary somatosensory cortex (S1 and S2) as mice detected a small optogenetic stimulus in S1 [33] (Fig 2A). Mice were trained to lick for reward in

A   Reliability assumption

B   Behavioral relevance assumption

FIG. 1. **Two assumptions underlying the computation of average population responses.** A) Reliability: single-trial responses correlate better with the trial-averaged response to the same stimulus, than with the trial-averaged response to a different stimulus. B) Behavioural relevance: better matched single-trial responses lead to more efficient behaviour.

response to the optogenetic activation of 5 to 150 randomly selected S1 neurons; for all of the analyses that we carried out, we left out those trials where 150 neurons were stimulated, as they were originally used to ease animal training. On 33% of trials, there was a sham stimulus during which no optogenetic stimulation was given (stimulus absent condition). Simultaneously, using gCAMP6s, $250 - 631$ neurons were imaged in S1 and $45 - 288$ in S2. Data set 1 thus represents a benchmark case of strong experimental control focused on a small set of cortical areas. Particularly, in this case the stimulus directly drives the neuronal response, skipping upstream neuronal relays.

   To probe the computational role of averages within this tightly controlled setting, we first computed average population responses for the two experimental conditions: Optogenetic S1 stimulation present versus absent. Since optogenetic stimulation could target different numbers of neurons ranging from 5 to 50, for the purpose of this analysis we pooled all stimulation intensities into the 'stimulus present'. We did this because the low trial numbers per stimulation intensity would have made cross-trial averaging largely meaningless, and because the population averages of different stimulus intensities were highly correlated (see Fig. S2A).

   Average response *templates* were computed as the mean fluorescence ($\Delta F/F$) of each neuron in a time window of 0.5 s following the stimulation offset (Fig. 2B). Since optogenetic stimulation caused light artifacts in the two-photon recordings, the stimulation period itself was excluded from analysis. We next quantified how well single-trial responses correlated with their corresponding average template (stimulation present or absent) (Fig. 2C, left; see also [34]).

FIG. 2. **Single-trial responses are stimulus-specific for Data set 1.** A) Animals report whether they perceived the optogenetic stimulation of somatosensory neurons (S1) through licking to receive reward. This panel was adapted from [33] with permission from the authors. B) Trial-average population responses ('templates') for S1 (orange) and S2 (brown), under optogenetic stimulation (top) or no stimulation (bottom) conditions. Neurons are sorted the same under both conditions. C) Distribution of the correlations between single-trial responses and the matching (left) and non-matching (middle) trial-averaged response templates. Box: 25^{th} and 75^{th} percentile. Center line: median. Whiskers: 10^{th} and 90^{th} percentile. Dotted lines: median of bootstrapped data. The difference between the correlations to the matching and non-matching templates gives the Specificity Index (right).

Correlations in S1 ranged from $r = -0.13$ to 0.64 ($n = 1795$ trials; $p < 0.001$), suggesting that single-trial responses represented the template quite faithfully. In S2, correlations were more broadly distributed, ranging from -0.29 to 0.71 ($n = 1795$ trials).

To assess if single-trial responses can be regarded as a down-sampled or 'noisy' version of the average template, we repeatedly computed a bootstrapped response vector for each trial based on the neurons' average response preferences (Fig. S3, Methods). These surrogate data correlated only slightly better to the template than the original data in both S1 and S2 (Fig. 2C), suggesting that in Data set 1, single-trial responses can be interpreted as mostly reliable samples of the respective average template.

Strong correlations between single-trial responses and the population template may partially stem from neurons' basic firing properties, which would not be task-related. To estimate the stimulus specificity of the correlations we observed, we also computed single-trial correlations to the incorrect template (e.g. 'stimulus absent' for a trial

featuring optogenetic stimulation). Correlations to the incorrect template were significantly lower than to the correct one (Fig. 2C, middle, Mann-Whitney U-test, $p = 5.98 * 10^{-169}, p = 4.86 * 10^{-51}$ for S1 and S2, respectively). To quantify this directly, we defined the *specificity index*, which measures, on a single-trial basis, the excess correlation to the correct template with respect to the incorrect template. Since the specificity index subtracts two correlation coefficients, it is bounded between -2 and 2. The specificity indices of single-trial responses indicate clear stimulus-specificity (in S1 it ranged from -0.17 to 0.6 and a median of 0.16; in S2 it ranged from -0.3 to 0.51 and a median of 0.11) (Fig 2C, right). Note that while single-trial correlations to the average template scale with the amount of inter-trial variability in a data set, the Specificity Index is largely independent of inter-trial variability, because it reflects the differential match of single-trial responses to the correct versus incorrect template (see Fig. S6). Together, these results indicate that single-trial responses in Data set 1 were strongly and selectively correlated to the corresponding average template, largely fulfilling Assumption 1.

Next, we set out to test if the correlation between single-trial responses and average templates predicted the animal's licking behaviour (see Fig 3A, left, for an example session). To this end, we separately examined the single-trial correlations in trials that resulted in hits, misses, correct rejections (CRs) or false positives (FPs) (Fig 3A, right). For the trials where optogenetic stimulation was present, single-trial correlations in S1 were significantly lower in miss trials than in hit trials across both brain areas, suggesting that a better match to the average template did indeed produce hit trials more often (Fig. 3B, Mann-Whitney U-test, $p = 4.96e-68$). Similarly, while single-trial correlations were overall lower in the absence of optogenetic stimulation, correct rejections nevertheless featured significantly higher correlations than false positives (Fig. 3B, Mann-Whitney U-test, $p = 2.82e-17$ for the hit/miss comparison, for each area). The same pattern held true for S2, though overall correlations were marginally smaller and the difference between correct and incorrect trials was somewhat less pronounced (Fig 3B; $p = [2.02e-50, 1.37e-11]$ for the hits/misses and CR/FP comparisons, respectively). To quantify directly to what extent single-trial correlations predicted behaviour, we computed the Behavioural Relevance Index (Ω) as $\Omega = max(A, 1-A)$, where A is the Vargha-Delaney's effect size [35] (Methods). The Behavioural Relevance Index is bounded between 0.5 and 1, with 0.5 indicating complete overlap (stochastic equality) between the distributions and 1 meaning no overlap at all (absolute stochastic dominance). For those trials where there was stimulation (hits and misses), Ω in S1 and S2 were 0.86 and 0.81, respectively (Fig. 3 C), suggesting that in both areas, single-trial responses that were better matched to the cross-trial average resulted in more successful behaviour, fulfilling Assumption 2. When there was no stimulation, these values were 0.69 and 0.65. Together, these results indicate that in Data set 1, cross-trial averages are both reliable and behaviourally relevant enough to serve a computationally meaningful function.

Building on these results, we set out to determine how computationally meaningful cross-trial averages might be within the less restrictive experimental paradigm of Data set 2.

Data set 2 contains high-density electrophysiological (Neuropixel) recordings across 71 brain regions (Fig. 4A, right) in mice performing a two-choice contrast discrimination task [30]. Mice were presented with two gratings of varying contrast (0, 25, 50 or 100%) appearing in their left and right hemifield. To receive reward, animals turned a small steering wheel to bring the higher-contrast grating into the center, or refrained from moving the wheel if no grating appeared on either side (Fig. 4A, left). When both stimulus contrasts were equal, animals were randomly rewarded for turning right or left. Those trials were discarded in our analysis since there is no 'correct' behavioural response. Data set 2 thus allowed us to test the computational relevance of averages across a wide range of brain areas within a less tightly controlled behavioural paradigm.

FIG. 3. **Better template-matching predicts better behaviour.** A) Licking times for an example session (left) and for all sessions (right). The stimulation window is shown in blue, the analysis window in pink. B) Reliability of single-trial responses, as quantified by the Specificity Index, split out by hits, misses, correct rejections and false positives. C) Behavioural Relevance indices for these categories.

Since this data set contains neuronal recordings from 71 brain areas, not all of which may be directly involved in the perceptual task at hand, we used a data-driven approach to identify to what extent neuronal population activity predicted the presented stimulus and/or the animal's target choice. We trained a decoder (Multinomial GLM, Methods) based on single-trial population vectors, to identify either target choice (left/right/no turn) or stimulus condition (higher contrast on left/right, zero contrast on both). For the neuronal response vectors, we considered neuronal activity $0 - 200ms$ post-stimulus onset (Fig. S4). We then computed the mutual information between the decoder predictions and the real outcomes (Fig. 4B; Methods).

Many brain areas contained little task-relevant information (shown in grey in Fig. 4B). We therefore used an elbow

FIG. 4. **Single-trial responses are hardly stimulus-specific for Data set 2.** A) Animals move a steering wheel to bring the higher-contrast grating stimulus into the centre (left), while being recorded from 71 brain areas (right). B) Stimulus and target choice information decoded by a multinomial GLM decoder (Methods) from the neuronal activity in all recorded brain areas. Each point represents the median (dot location) and standard deviation across sessions (dot size) of one brain area (see in-figure labels). Colours (blue, red, purple) represent those areas where (stimulus, choice, both) information was above an elbow criterion. C) We repeated the decoding with other models (see labels) and then performed a hierarchical clustering of the total mutual information of the ranked brain areas (rows). The 14 areas we found with the GLM (see B) are consistently found with other decoders. D) Specificity Index of the selected areas, defined as the difference in the correlations between single-trial responses and the matching (cartoon, left) and non-matching (cartoon, right) trial-averaged response templates. Box: 25^{th} and 75^{th} percentile. Center line: median. Whiskers: 10^{th} and 90^{th} percentile. Shaded areas: 5^{th} and 95^{th} percentiles of bootstrapped data. Dotted lines (surrogates): medians of the bootstrapped values for each recorded area.

criterion (Methods) to determine a threshold for selecting brain areas that provided the highest information on either stimulus ($I_{stim}^{thr} = 0.242$ bits; blue areas), choice ($I_{choice}^{thr} = 0.248$ bits; red areas), or both (i.e. both thresholds exceeded; purple areas). These areas seem largely congruent with the literature. For instance, primary visual cortex (VISp) is expected to reflect the visual stimulus, while choice information is conveyed e.g. by the ventral anterior-lateral complex of the thalamus (VAL) – known to be a central integrative center for motor control [36]. As an example of a both choice- and stimulus-informative area, we see caudoputamen (CP) - involved in goal-directed behaviours [37], spatial learning [38], and orienting saccadic eye movements based on reward expectancy [39]. To further validate our selection of relevant brain areas, we repeated the analysis with other five decoders (Fig. 4C). We ranked the total amount of Mutual Information per area (stimulus + choice information), using each of these models. Finally, we performed a hierarchical clustering and show that the areas we identified in Fig. 4B consistently appeared in the top performing cluster (Fig. 4C). Together, these results converged on a group of 14 brain areas that conveyed significant task information regardless of the decoder approach.

Having identified task-relevant brain areas, we used neuronal recordings from those informative areas to test the two assumptions set out above. First, we computed the average population response templates for different experimental conditions. To avoid working with trial numbers as low as n=2 for specific contrast combinations, we pooled several contrast levels (e.g. 50% right – 0% left and 100% right – 50% left) into two conditions: Target stimulus on the left or on the right. This pooling strategy seemed particularly appropriate since average responses to the individual contrast levels were very comparable (Fig. S2), and were meant to result in the same behavioural response.

To test the first assumption, as we did for Data set 1, we quantified how well single-trial responses correlated with the template for a given stimulus (Fig. S3 A; see also [34]). Median correlations ranged from $r = 0.56$ to 0.89 across all brain areas ($n = 89$ to 3560 trials per brain area; all $p < 0.001$), suggesting that single-trial responses were similar to the template. To address how different these correlations were from those that we would get if single-trials were random samples of the template, we computed 100 bootstrapped response vectors for each trial (Fig. S3 B; Methods). Each bootstrapped response contained the same number of spikes as the original trial, but the neurons that produced these spikes were chosen randomly according to their spiking probability, according to the average template. These surrogate data uniformly correlated better to the template than the original data (Fig. S3 B). This indicates that single-trial responses in Data set 2 exhibited more variation than explained by (Poissonian) down-sampling. As in Data set 1, single-trial correlations again scaled with the amount of inter-trial variability, reflected for instance by the Fano Factor (S5). Note that the Fano Factors for all analysed brain areas in Data Set 2 fell within the range of previously reported results [40, 41] (Fig. S5 B), suggesting that Data set 2 provides a representative benchmark for neuronal activity in these brain areas.

Next, we estimated the stimulus specificity of the observed correlations by computing single-trial correlations to the incorrect template (e.g. 'target right' for the left target; see Fig 4D, top). These were marginally lower than to the correct template (Fig. S3 B). However, the correlation difference was so small compared to the spread of single-trial correlations that correlations to the correct and incorrect templates were largely indistinguishable. Consistent with this, the Specificity Indices across brain areas in Data set 2 were mostly positive but rarely exceeded 0.1 (Fig. 4D, bottom). In other words, correlations between single-trial responses and template were largely stimulus-independent. This lack of response specificity was again not directly predicted by the amount of inter-trial variability, because the Specificity Index reflects the differential link to correct versus incorrect template rather than the overall reproducibility of neuronal responses (see Fig. S5 B).

These results tally with recent work demonstrating how strongly non-task-related factors drive neuronal responses even in primary sensory areas like visual cortex [19, 20, 42–46]. However, the animal still needs to arrive at a perceptual choice. If trial-averaged templates are relevant to this perceptual decision, single-trial responses that are more dissimilar to the template should be more difficult to process, and hence lead to less efficient behaviour [30].

To test if the match between single-trial responses and the average template predicted target choices (animal steering right or left, see Fig. 5A), we compared single-trial correlations for hit trials (correct target choice) and miss trials (incorrect target or no response). Single-trial correlations were marginally lower in miss trials than in hit trials across most brain areas, suggesting that a better match to the average template did indeed lead to hit trials slightly more often (Fig. 5B; Supp. Results). However, the difference between the correlations was small, leading to Behavioural Relevance indices between 0.51 and 0.66. According to the Vargha & Delaney's effect size, such values would be considered largely negligible, indicating that single-trial correlations are not a reliable way to predict subsequent behaviour in Data set 2 (Ω; Fig. 5C; see also [35]).

Together, these results suggest that in Data set 2, the relation between single-trial responses and trial-averaged templates is neither reliable nor specific, and does not appear to substantially inform subsequent behavioural choices. However, this estimate may present a lower bound for several reasons. First, while the task information conveyed by cross-trial averages seemed to be limited in the recorded population of neurons, it might be sufficient to generate accurate behaviour when scaled up to a larger population. To explore this possibility, we sub-sampled the population of recorded neurons in each brain area from $N/10$ to N. We then extrapolated how the specificity and behavioural relevance indices would evolve with a growing number of neurons. This indicated that in Data set 2, average template matching is unlikely to become more consistent, specific or behaviourally relevant with more neurons (Fig. 6A, right). This did not seem to be a general feature of our extrapolation approach: in Data set 1, the Specificity Index appeared to remain largely stable with growing n, but Ω rose steeply, indicating that with a larger number of neurons, the match of individual trials to the average template would more strongly predict behaviour (Fig. 6A, left).

Alternatively, while cross-trial averages may not perform well in Data set 2 when computed for all recorded neurons, there may be a 'supergroup' of highly reliable neurons, which might then drive downstream processing [47, 48]. However, a jackknife procedure (i.e. removing one neuron at a time from the data; see Methods) revealed no neurons that particularly boosted single-trial correlations, Specificity, or Behavioural Relevance (Fig. S5). In some areas (e.g. RN or SNr), there seemed to be at least some neurons that contributed substantially to single-trial correlations, but this was not the general tendency: most specificity index and relevance index distributions were symmetrical. This also held for Data set 1, implying that in both data sets, any sub-set of neurons could convey the average template to approximately the same extent.

In addition, by pooling stimulus pairs with large and small contrast differences into just two stimulus categories - 'target left' and 'target right' - we may have caused the resulting average templates to appear less distinctive. Specifically, difficult stimulus pairs might 'blur the boundaries' between average templates. To estimate to what extent the poor specificity of single-trial responses in Data Set 2 was caused by difficult stimulus conditions, we computed Specificity Index and Behavioural Relevance separately for difficult and easy trials. Both Specificity and Relevance increased significantly in a majority of brain areas when only taking into account stimulus pairs with large contrast differences (see Fig. S8). This suggests that in Data Set 2, average population firing rates were both specific and behaviourally relevant on a single-trial level when processing coarse stimulus information. In contrast, average population firing rates were neither specific not behaviourally relevant when animals were engaged in finer contrast

FIG. 5. **Single-trial responses are barely behaviourally relevant for Data set 2.** A) Task. Mice bring the higher contrast stimulus to the centre by steering a wheel, or refrain from moving the wheel when no stimulus is present (left, middle) with high proficiency (right). B) Specificity index for the selected areas, split by hits and misses. C) Behavioural relevance for selected brain areas.

discrimination. In this context, it is important to note that animals were also highly successful in discriminating these difficult stimulus pairs. This suggests that fine contrast discrimination relied on other coding modalities than average firing rates.

Another potential limiting factor of our analysis could be that in the more complex behavioural context of Data set 2, template-matching may occur in a way that could not be captured by simple correlations. To explore this scenario, we repeated all previous analyses, but characterized population responses using Principal Component Analysis (PCA) via Singular Value Decomposition (SVD), and quantified their resemblance (normalized distance, see Methods) to the

average template in this dimensionally-reduced space. In both data sets, stimulus specificity increased marginally, but behavioural relevance decreased (Fig. S8). This suggests that cross-trial averages extracted via PCA were more reliable across trials, but less predictive of behaviour. The decrease in behavioural relevance was particularly steep in Data set 1, indicating that raw firing rates were more instructive to the animals' choices than dimensionally-reduced features of neuronal activity (Fig. S8).

Finally, neuronal responses may reflect a multi-factorial conjunction of response preferences to a wide range of stimulus features and behavioural variables. To test this hypothesis, we quantified whether single-trial correlations to the average would become more consistent or predictive of target choice when additional variables were taken into account. While we can of course neither know nor measure all variables that would be potentially relevant to such a multi-factorial response landscape, we tested two factors as a benchmark. As a first test, we accounted for potential modulating variables in an agnostic way by clustering the neuronal population responses from all trials according to similarity. Such clusters might reflect different spontaneously occurring processing states that the animal enters into for reasons (e.g. locomotion, satiation, learning etc.) that may remain unknown to the experimenter. After computing the Silhouette Index, which measures cluster compactness (Fig. S9), we decided to group trials into two clusters. We again repeated all analyses of response specificity and behavioural relevance within each of these trial clusters. As expected, given that trials were chosen based on similarity, response specificity rose from a median value of 0.07 to 0.15 in Data set 2. In contrast, in Data set 1, the Specificity Index was largely unchanged. This aligns with the fact that clusters in Data set 1 were less compact (Fig. S9 A) and thus trial-grouping improved trial homogeneity less markedly. In contrast, trial-grouping had an overall negative effect on Behavioral Relevance in both data sets. Data set 1 featured mixed effects across areas, with a median change of 0.04, while Data set 2 showed a steep decrease from a median value of 0.83 to 0.54 (Fig. 6 B, bottom).

As a second benchmark, we accounted for spontaneous fluctuations of attentional state as reflected by pupil size. Such fluctuations are a ubiquitous and well-documented phenomenon that has previously been shown to strongly impact neuronal population activity [44, 49, 50]. We therefore used attentional state (estimated by pupil size) as a representative example of known behavioural modulators of neuronal responses. To this end, we computed cross-trial averages for sub-groups of trials in which the animal exhibited similar pupil sizes. If population responses are modulated by attentional state [44, 49, 50], examining only trials that occurred during similar attentional states should reduce unexplained variability. However, grouping trials by average pupil size did not improve specificity or behavioural relevance in Data set 2 (Fig 6C; Data set 1 did not contain measurements of pupil size).

Together, these analyses suggest that the missing link between single-trial responses and cross-trial averages in Data set 2 is not explained by unmeasured confounding factors, non-linear interactions or lack of neurons, but rather a systemic feature of the data set. Fig. 7 summarizes the outcomes of different analysis approaches. In all cases, Data set 1 shows better stimulus-specificity and behavioural relevance than Data set 2. Furthermore, we show that an alternative template-matching procedure (i.e., Z-scoring the neural responses over trials, denoted by z-FRates) might improve stimulus-specificity in Data set 2, but it does nothing for its Behavioural Relevance Index and it heavily decreases it in Data set 1.

Discussion

The present study set out to formally test how informative average population responses are to the brain in different contexts. If cross-trial averages are computationally relevant, single-trial responses should be sufficiently reliable and

FIG. 6. **Control analyses for both data sets.** A) We subsampled the neuronal populations to check whether we could extrapolate a marked benefit from adding neurons when performing template-matching. Increasing the number of sampled neurons left the Specificity Indices for both Data sets largely unchanged (top), and yielded slight increases in Ω (bottom). We then clustered trials based on the similarity in their neural response (B) and pupil size (C). Neither of these clusterings made template-matching more stimulus-specific or behaviorally relevant.

specific to resemble the correct average template, and better-matching single-trial responses should evoke more efficient behaviour. To directly quantify to what extent these two conditions are fulfilled in a given data set, we developed two simple metrics: (1) The Specificity Index, which captures whether a single-trial response is more related to the average response of the true experimental condition than to the average responses of other experimental conditions; and (2) The Behavioural relevance Index, which reflects whether higher single-trial correlations to the correct average template result in more behaviourally successful trials.

Based on these metrics, we find that the two assumptions of cross-trial averaging are largely fulfilled in one of the two data sets examined here: Data set 1 required mice to respond by licking when they detected a highly controlled optogenetic stimulus in S1. In this setting, single-trial responses correlated strongly and specifically with the

FIG. 7. Summary of the results in both data sets.Y-axis shows the various methods used before specificity (left) and relevance (right) indices are computed.

correct average template. In addition, lower single-trial correlations often resulted in incorrect behavioural responses, suggesting that the match between individual responses and average templates did indeed inform decision making. This success is particularly surprising because optogenetic stimulation targeted a somewhat overlapping but randomly selected population of 5 to 150 neurons in each new trial. Thus, even though optogenetic stimulation varied randomly, it seemingly managed to recruit a reproducible network of neurons within the analysis time window of 500 ms post-stimulation. This suggests that the population responses highlighted by our analyses of Data set 1 rely on 'hub neurons' that are activated by various different stimulation patterns. Moreover, this is in line with the results shown in [33], where they were able to find a consistent weighted set of neurons across trials that encode stimulus response.

In contrast, in Data set 2 mice used a steering wheel to select the higher-contrast of two gratings. In this context, single-trial correlations were robust but not stimulus-specific, implying that they mostly reflected factors such as baseline firing rates rather than conveying stimulus information. Correcting for such baseline differences in firing rate, as done by PCA, did not improve the Specificity index of single-trial correlations. Moreover, single-trial responses that better resembled the correct template hardly increased an animal's chance of choosing the correct target. Further analyses indicated that these results would not improve with more neurons, or by taking into account complementary variables such as behavioural state. This suggests that in Data set 2, average population responses were not the central mechanism driving perceptual decision-making.

The disparity of outcomes between the two data sets examined here could be due to several factors. In many ways, Data set 1 offers an ideal case for average population responses to play a functional role: Stimulation is highly controlled, and takes place directly within the recorded brain area rather than being relayed across several synapses; behavioural responses (in the form of licking) are short and stereotyped, reducing movement-related neuronal dynamics; and animals are explicitly trained to detect a difference in the average amount of neuronal activity within S1. In other words, even if sensory stimuli were typically not encoded in average S1 population firing rates, animals

in Data set 1 may have essentially learned to 'count S1 spikes for reward'. By comparison, Data set 2 features less controlled visual stimulation since animals can look at either of the two stimuli freely; modulation of the stimulus signal by several synaptic relays; additional neuronal dynamics driven by increased and more complex spontaneous movement in the form of wheel turning; and of course the fact that animals are free to process the difference in grating contrast in ways other than average population firing. Thus, while the two data sets examined here are clearly not sufficient to draw general conclusions, our results may point towards a scenario where cross-trial averages are more computationally relevant in settings featuring strong stimulus control and expert or over-trained behaviours. This would mean that especially in order to understand more naturalistic neuronal computations, cross-trial averages might not be helpful.

An alternative possibility is that we underestimated the computational role of cross-trial averages in Data set 2 due to idiosyncrasies of the paradigm and of our analyses. First, task-relevant stimulus information in Data set 2 had to be computed by comparing visual inputs across brain hemispheres, but we only had access to neuronal activity from one hemisphere. Thus, recording from both hemispheres might have yielded more informative population templates. Nevertheless, the animal is proficient in this visual 2AFC task, which means that even if some brain areas (e.g. primary visual cortex) do not integrate information from both hemi-fields, some downstream area(s) should receive the result of the cross-hemisphere computations needed to initiate the correct behavioural response. Since this data set is arguably the most complete set of neuronal recordings to date regarding the number of recorded brain areas, it seems unlikely that not a single area consistently represents integrated stimulus information from both hemi-fields.

Another limitation of the average templates computed in Data set 2 may be that each one encompasses several contrast combinations. However, as the neuronal responses to the stimulus pairs subsumed in the same template were highly correlated to each other (Fig. S2), the precision lost by pooling across stimulus pairs appears negligible. This notion is further supported by the fact that we also pooled stimulus categories for Data set 1 by considering all trials with stimulation protocols targeting from 5 to 50 neurons within the category 'stimulus present'. Yet in this case, pooling trials of different stimulus intensities clearly did not significantly hamper the computational relevance of cross-trial averages. Finally, since the two pooled stimulus categories in Data set 2 mapped onto the two distinct behavioural response options (i.e. turn the wheel left or right), basic information on which hemi-field contains the higher-contrast stimulus should be reflected in at least some brain areas in order to drive the corresponding behavioural response – a notion that is also borne out by the decoder analysis (Fig. 4B, C).

Finally, the stimulus-related response templates explored here may generally underestimate the computational power of average responses by ignoring the many stimulus and behavioural factors at play at any moment in time [5, 19, 20, 42, 44–46, 51], only some of which will be known or accessible to the experimenter. This can make neuronal responses appear highly unpredictable, while they are actually shaped systematically and reliably by a set of unmeasured, or 'latent', variables. In principle, downstream neurons may be able to disentangle these factors to distill e.g. stimulus-related information.

We investigated this idea in two different ways. First, we grouped trials by pupil size, which is known to reflect spontaneous fluctuations in attentional state that strongly shape neuronal population activity [44, 49, 50]. Second, to account for modulating variables in a more agnostic way, we searched for distinct trial clusters that featured similar neuronal population responses. Such clusters might reflect different processing states that the animal enters into for reasons (e.g. locomotion, satiation, learning etc.) that may remain unknown to the experimenter. If either of these variables formed part of the 'multi-factorial average response curve' of the recorded neurons, then only considering

trials recorded during a similar attentional state (as measured by pupil size) or within the same trial cluster should increase the specificity and behavioural relevance of the resulting cross-trial averages by removing one source of response modulation that was previously unaccounted for. This was the case in Data set 1 but not in Data set 2, suggesting that even when more latent variables are accounted for, averages may still not the most accurate way to reflect information processed by the brain.

In addition, several recent papers have argued that factors such as stimulus properties, behavioural choices, and retrieved memories are encoded along largely orthogonal dimensions in neuronal response space [8, 11, 12]. If this is true, then extracting cross-trial averages via a dimensionality-reduction technique like PCA should enable us to dissociate them from other, orthogonally-coded, types of information, and thereby significantly improve their computational relevance even in the presence of other modulating factors. This scenario held to some extent for Data set 1, where single-trial response vectors as extracted by PCA became more specific to the average template, but not more behaviourally relevant. In Data set 2, applying PCA did not result in any substantial improvements. It is possible that these outcomes depend on the choice of dimensionality-reduction technique. We chose PCA as a benchmark due to its simplicity and ubiquitous use, but other approaches like non-Negative Matrix Factorization [52] might yield different results [53]. If they were to prove more successful, this would argue in favour of analyses characterizing average neuronal response preferences simultaneously for multiple, potentially non-linearly interacting factors [54]. In this case, we would suggest that the neuroscience community abandons single-feature response averages in favour of average multi-feature response 'landscapes'. This would involve finding routine metrics to track ubiquitous latent variables like behavioural state [44, 46, 55–57] throughout a wide range of experiments.

Crucially, our results suggest that the utility of trial-averaged responses can vary dramatically across different contexts. The relevance of template matching is likely to shift depending on behavioural context, stimuli, species – as well as the aspect of neuronal activity that is averaged, such as neuronal firing rates, firing phase, coherence etc. [30]. Similarly, dimensionality-reduction techniques may improve the reliability of cross-trial averages in some cases (such as Data set 1), but not in others (as in Data set 2). We therefore encourage researchers to compute simple 'rule-of-thumb' metrics such as the Specificity and Behavioural relevance index in order to estimate what computational role cross-trial averages may play for the experimental paradigms, neuronal computations and neuronal response metrics that they study. Over time, we hope that this practice will generate a 'map' of contexts in which cross-trial averages are computationally meaningful - and motivate the field to restrict the usage of cross-trial averages to cases when they are in fact relevant to the brain.

Ideas and Speculation

If classical trial-averaged population responses appear largely irrelevant to ongoing neuronal computations at least in some contexts, how then could stimulus and target choice information be encoded in such contexts? First, information may be encoded mostly in joint neuronal dynamics that are not captured by static (single- or multi-feature) response preferences. Analyses that take into account such dynamics, e.g. by tracking and/or tolerating ongoing rotations and translations in neuronal space [57–60] or by explicitly including shared variability in their readout [61, 62], often provide vastly more informative and stable neuronal representations [58, 59]. Consistent with this, the decoder analyses (Fig. 4) extracted information more successfully – most likely because decoders rely on co-variability and co-dependencies between input data and the class labels, which are smoothed over by trial-averaging.

Second, while here we have tested cross-trial averages of population firing rates as a benchmark of basic analysis practices in neuroscience, other aspects of neuronal activity might be more informative - and as a result also potentially

lead to more informative cross-trial averages. For instance, transiently emerging functional assemblies [63–65], phase relationships between neuronal sub-populations [66–68] or the relative timing of action potentials [69–71] may provide an avenue of information transmission that is entirely complementary to population firing rates.

Finally, by tracking more stimulus and behavioural variables at the same time, we can further explore how they dynamically influence overlapping and separate aspects of neuronal activity ([9, 55, 56, 72–75]). Over time, we hope that this will shape our understanding of neuronal activity as an ongoing interaction rather than a static snapshot. No matter which of these approaches turns out to be most successful, it is important to recognize that time-averaged population responses may, at least in some contexts, not be a fitting way to describe how the brain represents information.

Acknowledgements

We thank Jonathan Pillow, Viola Priesemann, Nick Steinmetz, Cyrille Rossant, Miles Wells and Mike X Cohen for valuable input on earlier versions of the manuscript.

[1] W. T. Newsome, K. H. Britten, and J. A. Movshon, Nature **341**, 52 (1989).

[2] G. B. Keller, T. Bonhoeffer, and M. Hübener, Neuron **74**, 809 (2012).

[3] J. Poort, A. G. Khan, M. Pachitariu, A. Nemri, I. Orsolic, J. Krupic, M. Bauza, M. Sahani, G. B. Keller, T. D. Mrsic-Flogel, *et al.*, Neuron **86**, 1478 (2015).

[4] V. Dragoi, J. Sharma, and M. Sur, Neuron **28**, 287 (2000).

[5] R. N. Ramesh, C. R. Burgess, A. U. Sugden, M. Gyetvan, and M. L. Andermann, Neuron **100**, 900 (2018).

[6] P. Bao, L. She, M. McGill, and D. Y. Tsao, Nature **583**, 103 (2020).

[7] M. J. Goard, G. N. Pho, J. Woodson, and M. Sur, elife **5**, e13764 (2016).

[8] S. W. Failor, M. Carandini, and K. D. Harris, bioRxiv (2021).

[9] M. C. Aoi, V. Mante, and J. W. Pillow, Nature neuroscience **23**, 1410 (2020).

[10] H. J. Ladret, N. Cortes, L. Ikan, F. Chavane, C. Casanova, and L. U. Perrinet, bioRxiv (2021).

[11] A. Libby and T. J. Buschman, Nature neuroscience **24**, 715 (2021).

[12] S. B. M. Yoo and B. Y. Hayden, Neuron **105**, 712 (2020).

[13] L. Q. Uddin, Trends in Cognitive Sciences **24**, 734 (2020).

[14] M. Kafashan, A. W. Jaffe, S. N. Chettih, R. Nogueira, I. Arandia-Romero, C. D. Harvey, R. Moreno-Bote, and J. Drugowitsch, Nature communications **12**, 1 (2021).

[15] M. M. Churchland, M. Y. Byron, J. P. Cunningham, L. P. Sugrue, M. R. Cohen, G. S. Corrado, W. T. Newsome, A. M. Clark, P. Hosseini, B. B. Scott, *et al.*, Nature neuroscience **13**, 369 (2010).

[16] M. R. Cohen and J. H. Maunsell, Nature neuroscience **12**, 1594 (2009).

[17] M. Gur and D. M. Snodderly, Cerebral cortex **16**, 888 (2006).

[18] N. Roth and N. C. Rust, Journal of neurophysiology **121**, 115 (2019).

[19] S. Musall, M. T. Kaufman, A. L. Juavinett, S. Gluf, and A. K. Churchland, Nature neuroscience **22**, 1677 (2019).

[20] C. Stringer, M. Pachitariu, N. Steinmetz, C. B. Reddy, M. Carandini, and K. D. Harris, Science **364** (2019).

[21] L. Waschke, N. A. Kloosterman, J. Obleser, and D. D. Garrett, Neuron (2021).

[22] M. Valente, G. Pica, G. Bondanelli, M. Moroni, C. A. Runyan, A. S. Morcos, C. D. Harvey, and S. Panzeri, Nature Neuroscience , 1 (2021).

[23] D. Festa, A. Aschner, A. Davila, A. Kohn, and R. Coen-Cagli, Nature Communications **12**, 1 (2021).

[24] C. E. Schoonover, S. N. Ohashi, R. Axel, and A. J. Fink, Nature , 1 (2021).

[25] D. Shimaoka, N. A. Steinmetz, K. D. Harris, and M. Carandini, Elife **8**, e43533 (2019).

[26] M. Carandini and C. Stevens, PLoS biology **2**, e264 (2004).

[27] N. T. Robinson, L. A. Descamps, L. E. Russell, M. O. Buchholz, B. A. Bicknell, G. K. Antonov, J. Y. Lau, R. Nutbrown, C. Schmidt-Hieber, and M. Häusser, Cell **183**, 1586 (2020).

[28] C. D. Salzman, K. H. Britten, and W. T. Newsome, Nature **346**, 174 (1990).

[29] P. Zatka-Haas, N. A. Steinmetz, M. Carandini, and K. D. Harris, bioRxiv , 501627 (2021).

[30] N. A. Steinmetz, P. Zatka-Haas, M. Carandini, and K. D. Harris, Nature **576**, 266 (2019).

[31] C. R. Fetsch, N. N. Odean, D. Jeurissen, Y. El-Shamayleh, G. D. Horwitz, and M. N. Shadlen, Elife **7**, e36523 (2018).

[32] C. D. Salzman, C. M. Murasugi, K. H. Britten, and W. T. Newsome, Journal of Neuroscience **12**, 2331 (1992).

[33] J. M. Rowland, T. L. van der Plas, M. Loidolt, R. M. Lees, J. Keeling, J. Dehning, T. Akam, V. Priesemann, and A. M. Packer, bioRxiv (2021).

[34] M. Carandini, D. Shimaoka, L. F. Rossi, T. K. Sato, A. Benucci, and T. Knöpfel, Journal of Neuroscience **35**, 53 (2015).

[35] A. Vargha and H. D. Delaney, Journal of Educational and Behavioral Statistics **25**, 101 (2000).

[36] A. P. Tlamsa and J. C. Brumberg, Somatosensory & motor research **27**, 34 (2010).

[37] H. H. Yin and B. J. Knowlton, Nature Reviews Neuroscience **7**, 464 (2006).

[38] W. E. DeCoteau, C. Thorn, D. J. Gibson, R. Courtemanche, P. Mitra, Y. Kubota, and A. M. Graybiel, Proceedings of the National Academy of Sciences **104**, 5644 (2007).

[39] R. Kawagoe, Y. Takikawa, and O. Hikosaka, Journal of neurophysiology **91**, 1013 (2004).

[40] A. B. Graf, A. Kohn, M. Jazayeri, and J. A. Movshon, Nature neuroscience **14**, 239 (2011).

[41] A. S. Charles, M. Park, J. P. Weller, G. D. Horwitz, and J. W. Pillow, Neural computation **30**, 1012 (2018).

[42] M. L. Schölvinck, A. B. Saleem, A. Benucci, K. D. Harris, and M. Carandini, Journal of Neuroscience **35**, 170 (2015).

[43] C. M. Niell and M. P. Stryker, Neuron **65**, 472 (2010).

[44] M. Vinck, R. Batista-Brito, U. Knoblich, and J. A. Cardin, Neuron **86**, 740 (2015).

[45] J. Fournier, A. B. Saleem, E. M. Diamanti, M. J. Wells, K. D. Harris, and M. Carandini, Current Biology **30**, 3811 (2020).

[46] W. E. Allen, M. Z. Chen, N. Pichamoorthy, R. H. Tien, M. Pachitariu, L. Luo, and K. Deisseroth, Science **364** (2019).

[47] C. Stringer, M. Michaelos, D. Tsyboulski, S. E. Lindo, and M. Pachitariu, Cell **184**, 2767 (2021).

[48] J. Pérez-Ortega, T. Alejandre-García, and R. Yuste, Elife **10**, e64449 (2021).

[49] R. S. Larsen and J. Waters, Frontiers in neural circuits **12**, 21 (2018).

[50] D. Crombie, M. A. Spacek, C. Leibold, and L. Busse, Available at SSRN 3832144 (2021).

[51] A. Lak, M. Okun, M. M. Moss, H. Gurnani, K. Farrell, M. J. Wells, C. B. Reddy, A. Kepecs, K. D. Harris, and M. Carandini, Neuron **105**, 700 (2020).

[52] J. K. Liu, H. M. Schreyer, A. Onken, F. Rozenblit, M. H. Khani, V. Krishnamoorthy, S. Panzeri, and T. Gollisch, Nature communications **8**, 1 (2017).

[53] E. A. Pnevmatikakis, D. Soudry, Y. Gao, T. A. Machado, J. Merel, D. Pfau, T. Reardon, Y. Mu, C. Lacefield, W. Yang, *et al.*, Neuron **89**, 285 (2016).

[54] S. Sadeh and C. Clopath, bioRxiv (2022).

[55] M. N. Havenith, P. M. Zijderveld, S. van Heukelum, S. Abghari, J. C. Glennon, and P. Tiesinga, Scientific reports **8**, 1 (2018).

[56] M. N. Havenith, P. M. Zijderveld, S. van Heukelum, S. Abghari, P. Tiesinga, and J. C. Glennon, Scientific reports **9**, 1 (2019).

[57] O. G. Sani, H. Abbaspourazad, Y. T. Wong, B. Pesaran, and M. M. Shanechi, Nature Neuroscience **24**, 140 (2021).

[58] G. Okazawa, C. E. Hatch, A. Mancoo, C. K. Machens, and R. Kiani, Cell **184**, 3748 (2021).

[59] J. A. Gallego, M. G. Perich, S. N. Naufel, C. Ethier, S. A. Solla, and L. E. Miller, Nature communications **9**, 1 (2018).

[60] R. J. Low, S. Lewallen, D. Aronov, R. Nevers, and D. W. Tank, BioRxiv, 418939 (2018).

[61] C. Pandarinath, D. J. O'Shea, J. Collins, R. Jozefowicz, S. D. Stavisky, J. C. Kao, E. M. Trautmann, M. T. Kaufman, S. I. Ryu, L. R. Hochberg, *et al.*, Nature methods **15**, 805 (2018).

[62] J. S. Montijn, G. T. Meijer, C. S. Lansink, and C. M. Pennartz, Cell reports **16**, 2486 (2016).

[63] C. D. Harvey, P. Coen, and D. W. Tank, Nature **484**, 62 (2012).

[64] D. J. Foster, Annu. Rev. Neurosci **40**, 9 (2017).

[65] A. D. Grosmark and G. Buzsáki, Science **351**, 1440 (2016).

[66] T. Womelsdorf, J.-M. Schoffelen, R. Oostenveld, W. Singer, R. Desimone, A. K. Engel, and P. Fries, science **316**, 1609 (2007).

[67] U. Rutishauser, I. B. Ross, A. N. Mamelak, and E. M. Schuman, Nature **464**, 903 (2010).

[68] J. Duprez, R. Gulbinaite, and M. X. Cohen, NeuroImage **207**, 116340 (2020).

[69] M. N. Insanally, I. Carcea, R. E. Field, C. C. Rodgers, B. DePasquale, K. Rajan, M. R. DeWeese, B. F. Albanna, and R. C. Froemke, Elife **8**, e42409 (2019).

[70] M. N. Havenith, S. Yu, J. Biederlack, N.-H. Chen, W. Singer, and D. Nikolić, Journal of neuroscience **31**, 8570 (2011).

[71] B. Sotomayor-Gómez, F. P. Battaglia, and M. Vinck, (2021).

[72] B. Bagi, M. Brecht, and J. I. Sanguinetti-Scheck, Current Biology (2022).

[73] E. J. Dennis, A. El Hady, A. Michaiel, A. Clemens, D. R. G. Tervo, J. Voigts, and S. R. Datta, Journal of Neuroscience **41**, 911 (2021).

[74] S. Ebrahimi, J. Lecoq, O. Rumyantsev, T. Tasci, Y. Zhang, C. Irimia, J. Li, S. Ganguli, and M. J. Schnitzer, Nature **605**, 713 (2022).

[75] B. R. Cowley, A. J. Calhoun, N. Rangarajan, J. W. Pillow, and M. Murthy, bioRxiv (2022).

[76] H. B. Mann and D. R. Whitney, The annals of mathematical statistics , 50 (1947).

[77] D. S. Kerby, Comprehensive Psychology **3**, 11 (2014).

[78] T. Akiba, S. Sano, T. Yanase, T. Ohta, and M. Koyama, in *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining* (2019) pp. 2623–2631.

[79] J. Bergstra, R. Bardenet, Y. Bengio, and B. Kégl, Advances in neural information processing systems **24** (2011).

[80] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, *et al.*, the Journal of machine Learning research **12**, 2825 (2011).

[81] P. Domingos and M. Pazzani, Machine learning **29**, 103 (1997).

[82] R. T. Rockafellar, Princeton, NJ (1970).

[83] R. Q. Quiroga and S. Panzeri, Nature Reviews Neuroscience **10**, 173 (2009).

[84] C. E. Shannon, The Bell system technical journal **27**, 379 (1948).

[85] N. M. Timme and C. Lapish, eneuro **5** (2018).

[86] T. M. Cover and J. A. Thomas, Elements of Information Theory **1**, 279 (1991).

[87] M. L. Waskom, Journal of Open Source Software **6**, 3021 (2021).

[88] B. W. Silverman, **26** (1986).

[89] V. Satopaa, J. Albrecht, D. Irwin, and B. Raghavan, in *2011 31st international conference on distributed computing systems workshops* (IEEE, 2011) pp. 166–171.

[90] K. Pearson, The London, Edinburgh, and Dublin philosophical magazine and journal of science **2**, 559 (1901).

[91] D. D. Lee and H. S. Seung, Nature **401**, 788 (1999).

[92] P. C. Hansen, BIT Numerical Mathematics **27**, 534 (1987).

[93] A. Mathis, P. Mamidanna, K. M. Cury, T. Abe, V. N. Murthy, M. W. Mathis, and M. Bethge, Nature neuroscience **21**, 1281 (2018).

[94] S. Butterworth *et al.*, Wireless Engineer **7**, 536 (1930).

[95] B. Hoeks and W. J. Levelt, Behavior Research methods, instruments, & computers **25**, 16 (1993).

[96] O. E. Kang, K. E. Huffer, and T. P. Wheatley, PloS one **9**, e102463 (2014).

SUPPLEMENTARY MATERIAL

METHODS

We have released all the scripts and data files to reproduce these analyses, they can be found at the following URL: https://github.com/atlaie/BrainAveraging. They are written in Python 3 and rely on several libraries.

Specificity index

With the intent of characterizing whether the neural response is more similar to the appropriate template (i.e., the one corresponding to the stimulus that was actually presented in that trial) or the other one, we introduced a simple quantity we termed specificity index. It is defined as:

$$\rho_i = cor(\lambda_{correct}, r_i) - cor(\lambda_{wrong}, r_i) \tag{1}$$

where cor is the Pearson correlation, λ denotes a given neural template and r_i is the population vector of the i^{th} trial. Thus, the specificity index captures the differential similarity of a given neural response to each of the templates. It is key to note that, given that the Pearson correlation is bounded between -1 and 1, the specificity index can attain values between -2 and 2 and, as we were just interested in its sign and global tendencies, we did not introduce any normalization factor.

Behavioral relevance

As a way to quantify the overlap between the hit and miss distributions we basically used Vargha-Delaney's A effect size [35] (also known as *measure of stochastic superiority*). This is an effect size derived from the Mann-Whitney U-test –a non-parametric statistical test that is particularly useful when distributions are not Gaussian [76]. Furthermore, A is especially interpretable. As it is related to the U statistic, it can be thought of [77] as the probability of a randomly selected point from one distribution (X) being higher than another randomly selected point from the other distribution (Y). Before computing the U-statistic, we have to:

1. Pool all data points into one group and sort them from low to high values.

2. Assign ranks to each sorted data point. If there is a tie (i.e., two repeated values), their rank is taken to be the average of the ranks for the entire pooled group.

3. Compute R_X and R_Y as the sum of the ranks of each of the groups.

Finally, the $U-$statistic will be given by:

$$U = \min(U_X, U_Y), \tag{2}$$

with $U_X = n_X\left(n_Y + \frac{n_X+1}{2}\right) - R_X$ and equivalently if we flip the X and Y labels. Having computed the U-statistic, our measure of Behavioral Relevance (Ω) is given by

$$\Omega = \max(A, 1 - A), \quad \text{with } A = \frac{\frac{U_X}{n_X} - \frac{n_X+1}{2}}{n_Y} \tag{3}$$

Thus, Ω is bounded between 0.5 and 1. If there is no overlap, $\Omega = 1$. In this extreme case, one distribution would have complete stochastic dominance over the other. If X and Y are totally overlapping, $\Omega = 0.5$ and, thus, the more

its value deviates from 0.5, the less overlapping the distributions are. Note that we dropped the subscripts for Ω; this is due to its definition being symmetrical for X and Y, because of the $max(\cdot)$ operation. This can be easily shown, as:

$$A_{X,Y} = 1 - A_{Y,X} \implies \Omega_{X,Y} = \max(A_{X,Y}, 1 - A_{X,Y}) = \max(A_{X,Y}, A_{Y,X}) = \max(1 - A_{Y,X}, A_{Y,X}) = \Omega_{Y,X} \quad (4)$$

Thus, the definition of the Behavioral Relevance index is independent of the order in which we take the statistical test.

Yule-Kendall index

In order to assess how symmetrical the jackknifed distributions shown in Fig. S6 are, we relied on the Yule-Kendall index, which is computed as:

$$\gamma = \frac{Q(3/4) + Q(1/4) - 2Q(1/2)}{Q(3/4) - Q(1/4)}, \quad (5)$$

where Q is the quantile function. We chose this measure because it works for non-normal distributions and because it is non-dimensional (thus allowing direct comparison between data sets).

Decoders

In order to select the most informative brain areas for Data set 2 in a data-driven way, we made use of different decoders. For each experimental session, there are several recorded regions. Thus, we trained independent decoders using the single-trial population vector for each region. The labels to be predicted would be either choice (left wheel turn, right wheel turn or no movement) or stimulus (right-higher contrast, left-higher contrast, both equal).

We split the data following a $80 - 20$ ratio (train-test). Given the imbalanced nature of the dataset, we used a stratified (i.e., ensuring that all classes are fairly represented across each fold) $10-$repeated $5-$fold Cross-Validation to fine-tune each model's hyperparameters using a Bayesian approach and checked that the model performance was above majority class (i.e., always predicting the most abundant label) and random models.

In the following, let assume we want to classify N input variables (x_i, with $i = 1, ..., N$) into target variables that can belong to K classes (i.e., $y_i \in \{1, ..., K\}$).

Bayesian optimization

Hyperparameter optimization is arguably one of the bottlenecks when deploying Machine Learning techniques. Fortunately, in the last years, the field is rapidly evolving and we now have access to quick and intuitive libraries that alleviate greatly these tasks. One of these libraries is *Optuna* [78]. We relied on Tree-structured Parzen Estimators (TPEs) [79] to speed up hyperparameter search.

For each model, we chose different hyperparameters to be optimized, which we will detail in the following descriptions. We relied on the SciKit-Learn package in Python [80] to implement all of the classifiers.

Gaussian Naive Bayes

Naive Bayes assumes independent features [81]. In terms of the covariance matrices, this model assumes they are diagonal. Particularly, the Gaussian Naive Bayes (GNB) model assumes that the class-conditional densities are normally distributed as:

$$P(\mathbf{x}|y = c, \mu_c, \Sigma_c) = \mathcal{N}(\mathbf{x}|\mu_c, \Sigma_c) \tag{6}$$

where μ and Σ are the class-specific mean vector and class-specific covariance matrix, respectively. In order to compute the class posterior, we can simply make use of Bayes' theorem

$$P(y = c|\mathbf{x}, \mu_c, \Sigma_c) = \frac{P(\mathbf{x}|y = c, \mu_c, \Sigma_c)P(y = c)}{\sum_{k=1}^{K} P(\mathbf{x}|y = k, \mu_k, \Sigma_c)P(y = k)}. \tag{7}$$

So, in order to classify $\mathbf{x}$ into a class c:

$$\hat{h}(\mathbf{x}) = \underset{c}{\operatorname{argmax}} \, P(y = c|\mathbf{x}, \mu_c, \Sigma_c) \tag{8}$$

For this classifier, we did not perform any hyperparameter tuning.

k-Nearest Neighbors

This model relies on the assumption that the closer two points are, the more similar they are and the more likely it is that they belong to the same class. It is implemented as follows: for any given point x_i, compute its distance to the rest of the points; then, select the k points that are closest; out of those, apply a majority vote rule. As a summary: the most prevalent class of the k closest points to x_i will determine the class that we predict for it.

For this classifier, we optimized the number of nearest neighbors and the leaf size of the k-d Tree algorithm.

Random Forest

This model makes use of several Decision Trees (DTs) to solve supervised learning problems. DTs are non-parametric models that split the data using a given number (depth) of conditional steps - populated with at least with some number of data points (minimum sample split). When we aggregate several DTs (using a technique known as bootstrap aggregating or *bagging*), we end up with a *Random Forest* (RF). Specifically, we sample with replacement from the data and feed these subsamples to different trees. Finally, we use a majority vote for each tree's output as the RF prediction. This procedure reduces the variance in the model (i.e., mitigates overfitting) but has a minimal effect on its bias (i.e., underfitting is still a risk). Therefore, ideally we would like to use DTs that are unstable (high variance)

but very little bias. In order to check the model performance, we compute its out-of-bag (oob) error - cases in the training data that are not in a significant part of the bootstrapped samples.

For this model, we optimized the number of DTs, their maximum depth and the minimum sample split.

Generalized Linear Model

We trained a multinomial Generalized Linear Model (GLM) with a L2-regularization. This model states that the probability of a particular data point y_i belonging to class c is given by:

$$p\left(y_i = c \mid x_i\right) = \frac{e^{w_c \cdot x_i + b_c}}{\sum_{j=1}^{K} e^{w_j \cdot x_i + b_j}} \tag{9}$$

After having the probabilities of y_i belonging to each class c, the highest one will be taken to be 1 and the rest will be set to 0. Therefore, the objective is to find the weight vector w_c that minimizes the distance between the predicted $(\hat{y}_i)$ and the actual (y_i) class labels by optimizing (in this case, minimizing) the following loss function:

$$L\left(\hat{y}_i, y_i\right) = -\log\left(\frac{e^{w_c \cdot x_i + b_c}}{\sum_{j=1}^{K} e^{w_j \cdot x_i + D_i}}\right) + \lambda \left\|w_c\right\|_2^2 \tag{10}$$

where $\|w_c\|_2^2$ is the L2-norm of the weight vector for class c, accounting for the L2-regularization term, with λ modulating its strength. The inverse of λ $(C = 1/\lambda)$ is the hyperparameter we optimized for this model.

Support Vector Machines

This class of models rely on finding the hypersurface that maximizes the separation between classes in the data. To this end, it is important to first find the *support vectors* (SVs), which are the closest ones to the surface. There are two main types of Support Vector Machines (SVMs): linear SVMs and kernel-based SVMs. The difference is that, in the former, the separating hypersurface is a hyperplane (i.e., a non-curved hypersurface), while, in the latter, it is is allowed to be curved. Mathematically, the *linear* version of this model is the solution to the following optimization problem:

$$\min_{\omega_i \in \mathbb{R}^N} \quad \mathcal{C}(\omega_i) \tag{11}$$

where

$$\mathcal{C}(\omega_i) = C \sum_{i=1}^{N} \overbrace{\max\left(0, 1 - y_i x_i\right)}^{\text{Hinge loss}} + \overbrace{||\omega||^2}^{\text{L2-reg.}} \tag{12}$$

In order to arrive to the equivalent one for the non-linear SVM, we can take advantage of the fact that this problem satisfies some conditions [82] that allow us to construct its dual form. It takes the form of:

$$\mathcal{C}_D(\alpha_i) = \sum_{i=1}^{N} \alpha_i - \frac{1}{2} \sum_{i=1}^{N} \alpha_i \alpha_j y_i y_j K(\mathbf{x_i}, \mathbf{x_j}), \quad \text{with} \quad 0 \leq \alpha_i \leq C, \sum_{i=1}^{N} \alpha_i y_i = 0 \tag{13}$$

where $K(\mathbf{x_i}, \mathbf{x_j})$ is the kernel (it can be linear or not) and C is the regularization strength. In this work, we chose Radial Basis Functions (RBF) as our kernel. These are given by:

$$K(\mathbf{x_i}, \mathbf{x_j}) = \exp\left(-\gamma ||\mathbf{x}_i - \mathbf{x}_j||^2\right) \tag{14}$$

where γ is the reach parameter (i.e., how far we want two separate points influence each other).

For these decoders, we optimized the regularization strength (C) and, only for the RBF, the reach coefficient (γ).

Mutual Information

After having trained each decoder, we separately computed the Mutual Information between the predicted and the test class labels, as a proxy of the amount of stimulus – or choice – information there was in the population vector.

This quantity is defined in the context of classical Information Theory [83, 84] and we can compute it for two discrete stochastic variables X and Y. Assuming these have a joint probability mass function given by $p_{X,Y}(x,y) = P(Y = y \mid X = x) \cdot P(X = x)$ and that each of them follows a marginal probability distribution given by $p_X = \sum_{y \in Y} p_{X,Y}(x,y)$, one can mathematically define the Mutual Information between X and Y as:

$$I(X;Y) = \sum_{x \in X} \sum_{y \in Y} p(X,Y) \log\left(\frac{p_{X,Y}(x,y)}{p_X p_Y}\right) \tag{15}$$

Intuitively, one can understand $I(X;Y)$ as the uncertainty reduction in X that follows if Y is measured (or vice versa, as $I(X;Y)$ is invariant when swapping X and Y). If (and only if) they are independent of each other, then $I(X;Y) = 0$. Therefore, this is a strictly non-negative quantity. It is noteworthy that $I(X;Y)$ captures all linear and nonlinear dependencies between X and Y, thus generalizing the notion of correlation measures. For further discussion of this measure, see [85, 86].

Hierarchical clustering

After having computed the resulting Mutual Information for all areas, sessions and decoders, we aimed to check the stability of the selection of the most informative brain areas, so that results were not highly dependent on which model we used to choose them. To do that, we used an unsupervised method, known as hierarchical clustering. Particularly, our vectors were the aggregated information (stimulus + choice) that each decoder extracted, over all brain areas. Once we have the pairwise distance between points (proximity matrix), this method can be understood in an iterative manner: merge the closest points in a cluster, then merge the closest clusters and repeat until only a single cluster (encompassing all points) remains. For Fig. 4, we used the Euclidean metric to compute the proximity matrix.

To implement this algorithm, we relied on the Seaborn [87] (Python package) implementation of *clustermap*.

Elbow method

In order to select a threshold when selecting the task-related areas based on their stimulus and choice information (Figure 4 in the main text), we used the data to compute the Kernel Density Estimate, via Gaussian kernels [88]. After having extracted these, we used the method discussed in [89] to find the point of maximum curvature. We made use of the kneed Python package, implemented by the same authors [89].

Surrogate models

Calcium imaging data

For this data set, we pooled together those trials within the same stimulus set: on the one hand, when stimulation was given; on the other hand, those trials without any stimulus. For each of those trial groups, and for each neuron, we built a Gaussian distribution with mean and variance given by the trial-average and trial-variance. We then sampled 200 random values for each stimulus set and correlated each of them with the template.

Spike data

We were interested in comparing the experimental neuronal population response with a downsampled version of the trial-averaged template. To do that, we built our surrogate models by constructing $N(= 100)$ random vector with the following constraints:

1. Its size is equal to the number of neurons comprising the neural population for that area and that session.

2. The probability that at n spikes are allocated at a particular location m (i.e., that neuron m has spiked n times) is given by $P_{m,n} = \left(\frac{\lambda_m}{\sum_m \lambda_m} \right)^n$, where λ_m is the m^{th} element of the template vector.

3. The total number of spikes is constant and equal to the total recorded number of spikes for that area and that session.

By imposing these constraints, we are testing the alternative hypothesis that neurons are independent from each other (uncorrelated) and it is therefore equivalent to keeping the single-trial population statistical response, while scrambling across trials. This is also the same as drawing single-neuron responses from the underlying template distribution following a Poisson process. Thus, the bootstrapped responses contain the same number of spikes as the original trial, but the neurons that produced these spikes are randomly chosen according to their probability of occurrence in the average template.

Templates and distances in PCA space

As an alternative to Pearson's correlation, we applied Principal Component Analysis (PCA) [90]. We chose PCA over non-Negative Matrix Factorization [91] or other more advanced dimensionality reduction techniques such as

LFADS [61] or PSID [57] because we wanted to keep all analyses as general as we possibly could. Thus, we computed the truncated Singular Value Decomposition (tSVD) [92] for the matrix consisting of Z-scored single-trial population vectors, for a given area and session. Then, we extracted the knee (elbow) using the aforementioned method, to select the number of components based on the variance explained. After the number of components has been selected, we projected each single-trial into this (dimensionally-reduced) space and computed the Euclidean distance between this new vector and the template (also projected into this space). We normalized by the distance between the projection of the two templates in this new space.

Specificity Index for PCA distances

Since in PCA analyses we dealt with distances rather than correlations (i.e., differences rather than similarities), we inverted the computation of the Specificity Index in this context so that positive values continued to signify a stronger relation between single trial response and correct template than incorrect template. The corresponding formula is:

$$\rho_i^{PCA} = \frac{d(\lambda_{wrong}^{PCA}, r_i^{PCA}) - d(\lambda_{correct}^{PCA}, r_i^{PCA})}{d_{ref}} \tag{16}$$

where d stands for Euclidean distance and r_i^{PCA} is the PCA-projected version of the population vector measured in the i^{th} trial; λ_{wrong}^{PCA} and $\lambda_{correct}^{PCA}$ are the PCA-projected version of the trial-average templates (wrong and correct, respectively). Finally, $d_{ref} = d(\lambda_{wrong}^{PCA} - \lambda_{correct}^{PCA})$, which we took to be the reference distance.

Pupil size

As a way to account for the animal's behavioral state, we grouped together trials that had a similar pupil size. Firstly, we low-pass filtered the recorded pupil size (that came as an output of DeepLabCut [93]) using a Butterworth filter [94] of order 4. We chose to filter out any frequency above $1 Hz$, as we were interested in slow variations in pupil size, which have been linked to attentional state [95, 96]. We then computed the mean pupil size in the same time window we used for the neural analyses (200 ms after stimulus presentation). Finally, we ranked all sizes over trials and grouped them in brackets of 10 percentiles (e.g., trials with a pupil size between the 32^{th} percentile and the 42^{th} one would be grouped). Within the selected group, we repeated the template-matching algorithm that we used in the main text, tailoring the average to those trials that shared a similar pupil size.

k-Means clustering

In order to group trials according to similarity in the recorded neural response, we used k-Means clustering. This algorithm, after randomly initializing k centroids (one per cluster), is as follows: (1) Compute the distance between each data point and these k centroids. (2) Each point will belong to the cluster with the closest centroid. (3) New centroids will be given by the actual points belonging to a cluster.(3) Repeat until convergence (when centroids move no more). As this is an unsupervised method, we used the elbow method to select the number of k centroids in which

706 to cluster the data S7. Finally, as we did for the pupil size grouping, we repeated the template-matching algorithm
707 that we used in the main text, tailoring the average to those trials that belonged to the same cluster.

SUPPLEMENTARY RESULTS

Figure 5

To estimate stimulus-specificity, we computed single-trial correlations to the incorrect template. These resulting
correlations are marginally lower than those for the correct template (Fig. 5A; difference between median correlations:
0.03 ± 0.02 across areas; t-test for dependent samples; $n = 89$ to 3560 trials per area; $t = 3.0$ to 27.2; all $p < 0.01$,
corrected for multiple comparisons using FDR with a family-wise error rate of $\alpha = 0.05$). However, the correlation
difference (0.03 ± 0.02 across areas) is so small compared to the spread of single-trial correlations (standard deviation:
0.04 to 0.39) that correlations to the correct and incorrect templates were largely indistinguishable. Furthermore,
task-relevant brain areas did not show more specific correlations than control areas (mean correlation difference
for task-relevant areas: $0.031; n = 9$; for comparison areas: $0.022; n = 62$; Welch's t-test: $t = 1.17, p = 0.27$).Thus,
correlations between single-trial responses and template are largely stimulus-independent. To quantify this, we defined
the specificity index, which measures the single-trial correlation to the correct template minus the incorrect template
(Fig. 5B). Most values are positive, indicating that single-trial responses were generally more similar to the correct
than incorrect template (t-test for difference from zero; $n = 89$ to 3560 trials per cortical area; $t = 3.0 to 27.2$; all
$p < 0.01$, corrected for multiple comparisons). However, the distributions rarely exceeded 0.1 (Fig. 5B). Therefore,
across the examined brain areas, single-trial responses were barely more similar to the correct template than to the
incorrect one.

To test if the match between single-trial responses and the correct template predicted target choices, we split by
hit (trials where the animal chose the correct target) and miss trials (no response or wrong target). Single-trial
correlations were lower in miss trials than in hit trials across most brain areas, suggesting that a better match to the
average template did indeed tend to produce hit trials more often (Fig. 5C). However, overall the difference between
the correlations was small, as quantified by the Behavioral Relevance Ω (Fig. 5E). There were some exceptions
(MOs, $\Omega = 0.66, p = 0.0142, n_{hit} = 2057, n_{miss} = 667$), potentially because hit and miss trials are associated with
fundamentally different motor responses (miss trials include trials with no choice). Yet the overall pattern suggests
that template matching has low - and inconsistent - predictive power regarding perceptual decision-making. It is
however possible that the important factor for perceptual decision making is not the overall correlation between the
single-trial response and the correct response template, but whether it resembles the correct more than the incorrect
template. However, splitting specificity indices by hit and miss trials again shows no consistent difference (Fig. 5D),
indicating that single-trial responses that were more specific to the correct template did not lead to improved target
choices.

Figure 6

739 From the main results, it seems that single-trial responses are less correlated to the average than a bootstrapped
740 version of it, and that they are only slightly predictive of subsequent behaviour, in only a few brain areas. However,

the available information might be more than enough to generate accurate perceptions and behaviour when scaled up to the number of neurons actually involved in the task. To explore this possibility, we first sub-sampled the population of recorded neurons in each brain area at 10 different levels from $N/10$ to N. We then extrapolated how metrics like the Specificity Index would evolve as the number of available neurons grew. Stimulus-specificity tended to grow with sample size (Fig. 6A) for Data set 2 but not for Data set 1, raising doubts for the argument that maybe in a realistic population sampled by a downstream neuron (e.g. 30.000 inputs), template matching would be quite strong. Indeed even if the Specificity Index increases in Data set 2, the rate of change is not remarkable. However, as we can see in the bottom part of that plot, Ω did increase for both data sets, and the rate of change is substantial for some areas in Data set 2 (and for both areas in Data set 1). In other words, the single-trial match to the average template may become more indicative of subsequent behavioural choices with larger neuron numbers, even if they are not more stimulus-specific.

Supplementary Figure 8

Together, the template-matching results for Data set 2 suggest that the relation between single-trial population responses and their trial-averaged response templates is both less strong and less stimulus-specific than what one would expect from a down-sampled representation of the average. Most importantly, single-trial responses that better resembled the correct time-averaged template did not evoke better target choices. One possibility is that 'average template matching' happens in a multi-dimensional way. To take a first step at exploring this possibility, we repeated the analyses shown in Fig. 5 by characterizing population responses using Principal Component Analysis (PCA) via Singular Value Decomposition (SVD), and quantifying their resemblance to an average template in this dimensionally-reduced space (Fig. S8).

Generally, the resulting single-trial response vectors did overall not represent their corresponding average vectors more effectively than the Pearson correlation averages we had explored previously. In PCA space, single-trial vectors matched average vectors more closely than would be predicted from bootstrapping (Fig. S7A), but the match was nevertheless weak: the distance between a single-trial vector and its corresponding average template was typically $5 - 10$ times larger than the distance between correct and incorrect template. Consistently with this, the specificity of single-trial responses for the correct average template was low, even more so than for linear correlations (Fig. S7C; t-test for difference from Zero: $n = 90$ to 3123; $t = 0.6$ to 17.0; $p < 0.01$ except for $p(EPd) = 0.04$ and $p(SI) = 0.56$, corrected for multiple comparisons using a FDR procedure with a family-wise error rate of $\alpha = 0.05$). Specificity indices were clustered tightly around zero. Given that PCA vector distances are not upper-bounded to 1 and often took on values between 5 and 10 (Fig. S8A), specificity indices < 1 imply negligible differences between the single-trial distances to correct and incorrect templates S8B. Single-trial responses that were more similar and/or specific to the correct average vector also resulted in only slightly more correct behavioural choices (Fig. S8C-E; Mann-Whitney's U-test for differences in single-trial distances in hit and miss trials: $n = 90$ to 3123, Ω between 0.38 and 0.55; all $p < 0.01$; Mann-Whitney's U-test for differences in single-trial specificity in hit and miss trials: $n = 90$ to 3123, Ω between 0.5 and 0.61; all $p < 0.01$; corrected for multiple comparisons). Overall, these results demonstrate that just like for Pearson correlations, resemblance of single-trial to average vectors in PCA space did not seem to drive neuronal processing in a decisive way across most brain areas. However, since PCA is a linear method too, this still leaves open the possibility that non-linear methods may reveal accurate template matching of single trials.

FIG. S1. Example of neuronal responses for both Data sets. A) For Data set 1, we show a session, for all neurons over time, aligning the responses to stimulus onset (pink). Traces of individual cells are depicted in light gray, their trial-average in black. In cyan, we show the analysis window ($500ms$), within which we take the time-average (colored dots; blue for S1, orange for S2) that we use to construct the population vectors we used for the analyses. B) Spike traces for different representative areas in Data set 2 (a stimulus informative one [blue, primary visual cortex, VISpm], a choice-informative one [red, ventral anterior-lateral complex of the thalamus, VAL] and a both-informative one [purple, anterior cingulate area, ACA]). Each one comes from a different session and has a different number of neurons. As before, in pink we show the stimulus presentation and in cyan the analysis window ($200ms$) that we used to construct the population vectors in the analyses.

In addition, by pooling stimulus pairs with large and small contrast differences into just two stimulus categories - 'target left' and 'target right' - we may have caused the resulting average templates to appear less distinctive. Specifically, difficult stimulus pairs might 'blur the boundaries' between average templates. To estimate to what

FIG. S2. Correlations between response templates for different stimulus constellations. A) For Data set 1, we pool together those trials with a low number of stimulated neurons ($n \in [5, 20]$) and compare the trial-averaged response with those trials with a higher number of stimulated neurons ($n \in [30, 50]$). Their correlation generally exceed 0.6, suggesting that one template should be sufficient to represent different contrast constellations. B) For Data set 2, we compute the similarity between templates (for each contrast level: $0.25, 0.5, 1$, referred to as low, mid and high, respectively) for each screen (left, right). Their correlation is generally above 0.8, so grouping them together should provide a coherent representation.

extent the poor specificity of single-trial responses in Data Set 2 was caused by difficult stimulus conditions, we computed Specificity Index and Behavioural Relevance separately for difficult and easy trials. Both Specificity and Relevance increased significantly in a majority of brain areas when only taking into account stimulus pairs with large contrast differences (see Fig. S8). This suggests that in Data Set 2, average population firing rates were both specific and behaviourally relevant on a single-trial level when processing coarse stimulus information. In contrast, average population firing rates were neither specific not behaviourally relevant when animals were engaged in finer contrast discrimination. In this context, it is important to note that animals were also highly successful in discriminating these difficult stimulus pairs. This suggests that fine contrast discrimination relied on other coding modalities than average firing rates.

FIG. S3. **Single-trial responses are not stimulus-specific for Data set 2.** A) Distribution of the correlations between single-trial responses and the matching trial-averaged response templates. The top diagram shows the criterion to "match" single-trial responses with the trial-average. Box: 25^{th} and 75^{th} percentile. Center line: median. Whiskers: 10^{th} and 90^{th} percentile. Dotted lines: median of bootstrapped data. B) Same as A) but for the non-matching combinations. C) Distribution of the correlations between single-trial responses and the matching trial-averaged response templates, split by behavioural outcome. It can be seen that these distributions are practically identical for all regions.

FIG. S4. **Representation of the bootstrapping procedures.** A) In the first data set, we created the templates based on the time-average for each neuron, for each trial. We then constructed a Gaussian distribution centered around the trial-average and with a spread equal to the trial-variance. We repeated this for each neuron and then sample 200 times for each stimulus set. B) For data set 2, we fixed the number of spikes on each trial, but randomly assigned to a neuron with a probability according to how often it spiked in the average template. We repeated this procedure 100 times.

FIG. S5. **Reaction time distribution.** General distribution for reaction times, over all sessions, split by hits and misses. Consistent with the literature, misses significantly (Mann-Whitney's U-test, $p = 1.88 * 10^{-172}, A = 0.68$) imply longer reaction times. The vertical line indicates the width of the time window in which we have performed all of our analyses ($200ms$). We have selected our analysis window of because of its likely relevance to stimulus processing and behavioural decision making.

FIG. S6. **Population variability is not predictive of stimulus-specificity.** A) Scatter of the Specificity Index for different population variances. There is virtually no correlation for both regions. B) Fano factor distribution over all recorded regions. As for Data set 1, variability is uncorrelated with the Specificty Index and it is, thus, not capturing the same effect.

FIG. S7. **Specificity Index and Behavioral Relevance for all areas**. Same as Fig. 5B,E, but without pre-selecting informative areas. Results are preserved in general: across areas, single-trial responses are barely stimulus-specific (Specificity Indices are tightly clustered around 0, with a median value of 0.019) and not very behaviourally relevant (median value of $\Omega = 0.57$).

FIG. S8. **Easy trials are more stimulus-specific and behaviourally relevant than difficult trials for Data set 2.**
A) Task structure and behavioural proficiency; easy trials are taken to be the extremal cases: low contrast shown on one screen and a high one in the other. B) Distribution of the Specificity Index for easy and difficult trials, over the selected areas. In color, significant comparisons. Box: 25^{th} and 75^{th} percentile. Center line: median. Whiskers: 10^{th} and 90^{th} percentile. Dotted lines: median of bootstrapped data. C) Behavioural relevance (Ω) for easy and difficult trials, over all selected areas. D) Same as B) but for all recorded areas. E) Same as C), but for all recorded areas. Average responses are more behaviourally relevant for easy than for difficult trials (right).

FIG. S9. **Jackknife analyses.** We remove one neuron at a time and compute the impact in the Specificity Index, calculated as $SpecIdx_i^{JK} = n \cdot SpecIdx - (n-1) \cdot SpecIdx^{\neg i}$, for neuron i. We show the symmetry (γ) of each distribution around 0 using Yule's coefficient (Methods). This measure is bounded between -1 and 1, with each of them meaning completely skewed towards negative or positive values, respectively. A) Change in single-trial correlations to the correct average template when one individual neuron was removed. Data points: Trials. Colors: see inset legend. B) Same for single-trial specificity.

FIG. S10. **Unsupervised trial-clustering for both data sets.** Silhouette Index (SI) for both Data sets. This quantity measures cluster compactness (see Methods), with 0 indicating complete overlap between spread clusters and 1 meaning perfectly separated ones. Different colors represent a different number of clusters, from $k = 2$ to $k = 5$. A) SI for Data set 1. In this case, clusters are not compact and they are better distinguishable (for both brain areas) when $k = 2$. B) SI for Data set 2. Clusters are more compact than in the previous case, with $k = 2$ also being the best option. Thus, for analyses in the main text, we decided to group trials into two clusters.

FIG. S11. **PCA is not helpful in making single-trial responses more stimulus-specific or behaviorally relevant for Data set 2.** A) Distribution of single-trial normalized distances in PCA space (Methods) between response vectors and the trial-averaged response template for the correct (top) and wrong (bottom) stimulus constellation. B) Same as B, but the Specificity index of single-trial responses across brain areas, defined as the difference between the normalized distance to the wrong and correct template. Solid gray line highlights the Specificity Index of 0.0, which translates to exactly equal correlation to correct and wrong template. Dotted lines represent the specificity index of the medians of the bootstrapped values for each recorded area. C) Same as A (top), split by hits and misses. These distributions almost completely overlap, for all brain areas. D) Same as B, split by hits and misses. As in the previous panel, these distributions are practically coincident. E) Behavioral Relevance Index for all brain areas. They range from 0.50 to 0.62, with $\Omega = 0.5$ meaning perfect overlap.

FIG. S12. **PCA is helpful in making single-trial responses more stimulus-specific but heavily reduces behaviorally relevant for Data set 1.** A) Same as Fig. S8B, for Data set 1. B) Same as Fig. S8E, for Data set 1. In this case, the Specificity Index increased modestly (from 0.13 to 0.21) at the expense of severely hindering behavioral relevance (from 0.83 to 0.52).