Information flow across the cortical timescales hierarchy during

narrative construction

Claire H. C. Chang[1,*], Samuel A. Nastase[1,*], and Uri Hasson[1]

1. Princeton Neuroscience Institute, Princeton University, Princeton, New Jersey,

08540, USA.

* To whom correspondence should be addressed:

Claire H. C. Chang, claire.hc.chang@gmail.com; Samuel A. Nastase,

sam.nastase@gmail.com

Competing Interest Statement: The authors declare no competing financial interests.

Classification: biological science, neuroscience

Keywords: cortical hierarchy, naturalistic stimuli, fMRI, functional connectivity,

language processing

Abstract

When listening to spoken narratives, we must integrate information over multiple,

concurrent timescales, building up from words to sentences to paragraphs to a coherent

narrative. Recent evidence suggests that the brain relies on a chain of hierarchically

organized areas with increasing temporal receptive windows to process naturalistic

narratives. We hypothesized that the structure of this cortical processing hierarchy

should result in an observable sequence of response lags between networks comprising

the hierarchy during narrative comprehension. This study uses functional MRI to

estimate the response lags between functional networks during narrative

comprehension. We use inter-subject cross-correlation analysis to capture network

connectivity driven by the shared stimulus. We found a fixed temporal sequence of

response lags—on the scale of several seconds—starting in early auditory areas,

followed by language areas, the attention network, and lastly the default mode network.

This gradient is consistent across eight distinct stories but absent in data acquired

during rest or using a scrambled story stimulus, supporting our hypothesis that narrative

construction gives rise to inter-network lags. Finally, we build a simple computational

model for the neural dynamics underlying the construction of nested narrative features.

Our simulations illustrate how the gradual accumulation of information within the

boundaries of nested linguistic events, accompanied by increased activity at each level

of the processing hierarchy, can give rise to the observed lag gradient.

Significance Statement

Our findings reveal a consistent, stimulus-driven gradient of lags in connectivity along the cortical processing hierarchy—from early auditory cortex to the language network, then to the default mode network—during the comprehension of naturalistic, spoken narratives. We provide a simple computational model for the neural dynamics underlying the construction of nested narrative features, allowing us to systematically explore the conditions under which the lag gradient emerges and synthesize our results with previous findings based on simple well-controlled language stimuli. Our results illustrate the isomorphism between hierarchically structured neural dynamics and hierarchically structured, real-world narrative inputs.

Introduction

Narratives are composed of nested elements that must be continuously integrated to construct a meaningful whole, building up from words to phrases to sentences to a coherent narrative (1). Recent evidence suggests that the human brain relies on a chain of hierarchically organized brain areas with increasing temporal receptive windows (TRWs) to process this temporally evolving, nested structure (Fig. 1A). This cortical hierarchy was first revealed by studies manipulating the temporal coherence of naturalistic narratives (2, 3). These studies reported a topography of processing timescales where early auditory areas respond reliably to rapidly-evolving acoustic features, adjacent areas along the superior temporal gyrus respond reliably to information at the word level, and nearby language areas respond reliably only to

coherent sentences. Finally, areas at the top of the processing hierarchy in the default

mode network (DMN) integrate slower-evolving semantic information over many

minutes (4).

This cortical hierarchy of increasing temporal integration windows is thought to be a

fundamental organizing principle of the brain (5, 6). The cortical hierarchy of TRWs in

humans has been described using fMRI (2, 3, 7, 8) and ECoG (9). Recent work has

shown that deep language models also learn a gradient or hierarchy of increasing

TRWs (10–12), and that manipulating the temporal coherence of narrative input to a

deep language model yields representations closely matching the cortical hierarchy of

TRWs in the human brain (13). Furthermore, the cortical hierarchy of TRWs matches

the intrinsic processing timescales observed during rest in humans (9, 14, 15) and

monkeys (16). This cortical topography also coincides with anatomical and functional

gradients such as long-range connectivity and local circuitry (17–19), which have been

shown to yield varying TRWs (20, 21).

Fig. 1. Narrative construction in the hierarchical processing framework. (A) The

proposed cortical hierarchy of increasing temporal receptive windows (adapted from

(5)). (B) Each level of the processing hierarchy continuously accumulates information

over inputs from the preceding level. For example, phrases built over words are

constructed into sentences. The accumulated information is flushed out at structural

boundaries. (C) Each level of the processing hierarchy provides the building blocks for

the next level, which naturally leads to longer temporal receptive windows,

corresponding to linguistic units of increasing sizes. This model of narrative construction

along the cortical processing hierarchy implies a gradient of response lags across the

cortical hierarchy.

The proposal that the cortex is organized according to a hierarchy of increasing TRWs

implies that each area "chunks" and integrates information at its preferred temporal

window and that narrative construction proceeds along the cortical hierarchy. For

example, an area that processes phrases receives information from areas that process

words (Fig. 1B), which are further transmitted to areas that integrate phrases into

sentences. At the end of each phrase, information is rapidly cleared to allow for real-

time processing of the next phrase (1, 7). The chunking of information at varying

granularity is supported by recent studies that used data-driven methods to detect

boundaries as shifts between stable patterns of brain activity (22, 23).

This model of narrative construction (Fig. 1C) predicts a gradient of response lags

across the cortical processing hierarchy; namely, shorter temporal lags among adjacent

areas along the processing hierarchy than regions further apart in the cortical hierarchy.

In the current study, we test this prediction by comparing response fluctuations elicited

by spoken narratives in different brain areas using lag-correlation. We extract the lag

with the peak correlation to estimate inter-region temporal difference. To focus on

neural responses to linguistic and narrative information, we used inter-subject functional

connectivity (ISFC) analysis (24, 25). Unlike traditional within-subject functional

connectivity (WSFC), ISFC effectively filters out the idiosyncratic fluctuations that drive

intrinsic functional correlations within subjects. Isolating stimulus-locked neural activity

from intrinsic neural activity allows us for the first time to observe the temporal dynamics

of narrative construction across the cortical hierarchy. We predicted that ISFC analysis

would reveal an inter-region lag gradient during the comprehension of intact narrative,

but not during scrambled-story or rest, which do not involve narrative construction.

Finally, we provide a computational model to clearly illustrate how the construction of

nested narrative features could give rise to the observed lag gradient, and how the lag

gradient deteriorates without naturalistic inputs.

Results

To test the hypothesis that narrative construction will yield a gradient of response lags

across brain regions, we first divided the neural signals into six networks by applying k-

means clustering to WSFC measured during rest (SI Appendix, Fig. S1). We labeled

these networks based on anatomical correspondence with previously defined functional

regions following Simony and colleagues (25), including the auditory (AUD), ventral

language (vLAN), dorsal language (dLAN), default mode network (DMN), and attention

(ATT) networks, aligning with the previously documented TRW hierarchy (SI Appendix,

Fig. S2).

We computed lag-ISFC (i.e. cross-correlation) at varying temporal lags between all

pairs of networks (Fig. 2A and SI Appendix, Fig. S3). The lags with maximum ISFC (i.e.

"peak lag") for each seed-target pair were extracted as an index for the temporal gaps in

the stimulus-driven processing between each pair of networks. The extracted peak lags

were color-coded to construct the network × network peak lag matrix (Fig. 2B and 2C).

In the following, we describe the observed lag gradient in detail and several control

analyses. Finally, we simulated the nested narrative structure and the corresponding

brain responses to explore how different integration functions at different timescales

could give rise to the observed lag gradient.

Fig. 2. Construction of the inter-network peak lag matrix. (A) Lag-ISFC (cross-

correlation) between seed-target network pairs were computed using the leave-one-

subject out method. The dLAN network is used as an example seed network for

illustrative purposes. (B) The matrix depicts ISFC between the dLAN seed and all six

target networks at varying lags. The lag with the peak correlation value (colored vertical

bars) was extracted and color-coded according to lag. For visualization, the lag-ISFCs

were z-scored across lags. (C) The network × network peak lag matrix (p < .05, FDR

corrected). Warm colors represent peak lags following the seed network, while cool

colors represent peak lags preceding the seed network; zeros along the diagonal

capture the intra-network ISC. An example story ("Sherlock") is shown for illustrative

purposes.

Fixed lag gradient across cortical networks

The average lag-ISFC across stories was computed for each seed network (Fig. 3A,

left). The lag-ISFC between a seed network and the same network in other subjects

always peaked at lag 0, reflecting the strong stimulus-locked within-network

synchronization reported in the ISC literature (3, 26, 27) (SI Appendix, Fig. S3).

Interestingly, however, non-zero peak lags were found between different networks.

Relative to a low-level seed, putatively higher-level networks showed peak connectivity

at increasing lags. For example, the stimulus-induced activity in dLAN lagged 1 TR (1.5

s) behind activity in AUD, whereas the activity in DMNb lagged 4 TRs (6 s) behind

activity in dLAN. Importantly, regardless of the choice of seed, the target networks

showed peak connectivity in a fixed order progressing through AUD, vLAN, dLAN,

DMNa, ATT, and DMNb.

To summarize the findings, we color-coded the peak lags and collated them into a peak

lag matrix where each row corresponds to a seed network and each column

corresponds to a target network (Fig. 3A, right; see SI Appendix, Fig. S4 for the lag-

ISFC waveforms). The white diagonal indicates a peak at zero lag within each area,

reflecting the intra-network synchronization across subjects (i.e. ISC) (SI Appendix, Fig.

S3), while the cool-to-warm color gradient indicates a fixed order of peak lags. For

example, the first row shows a white-to-warm gradient, reflecting that when AUD served

as the seed, other networks were either synchronized with or followed AUD, but never

preceded it. Conversely, the cool-to-white gradient of the last row indicates that all other

networks preceded the DMNb seed. The lag gradient can also be observed in individual

stories (SI Appendix, Fig. S5), although these patterns are noisier than the averaged

results. The lag gradient proceeded in a fixed order across all networks, suggesting that

bottom-up narrative construction is reflected in lagged connectivity between stages

along the cortical hierarchy from AUD up to DMNb. Similar results were obtained when

we defined the ROIs using the TRW hierarchy (SI Appendix, Fig. S2D).

Fig. 3. The peak lag matrix across eight stories reveals a fixed lag gradient across

networks, which is abolished during scrambled narratives and rest. (A) The network ×

network peak lag matrix is based on the averaged lag-ISFC across eight stories. For

visualization, lag-ISFC curves at left were z-scored across lags. (B) Peak lag matrix

based on responses to a scrambled story stimulus (scrambled words). (C) Peak lag

matrix based on resting-state data. Peak lag matrices are thresholded at p < .05 (FDR

corrected).

Temporal scrambling abolishes the lag gradient

We hypothesized that the lag gradient reflects the emergence of macroscopic story

features (e.g. narrative situations or events) integrated over longer periods of time in

higher-level cortical networks (22, 23). To support this point, we next used the same

procedure to compute the peak lag matrix for a temporally scrambled version of one

story ("Pie Man"; as for the results of intact "Pie Man", please see *SI Appendix, Fig. S5*).

In this dataset, the story stimulus was spliced at the word level and scrambled, thus

maintaining similar low-level sensory statistics while abolishing the slower-evolving

narrative content. The peak lag matrix for the scrambled story revealed synchronized

responses at lag 0 both within and between the AUD and vLAN networks, but no

significant peaks within or between other networks (Fig. 3B). This reflects low-level

speech processing limited to the word level and indicates that disrupting the narrative

structure of a story abolishes the temporal propagation of information to higher-level

cortical areas.

No lag gradient during rest

As an additional control, we also examined whether the lag gradient observed during

the intact story could be detected during rest. The resting state is dominated by intrinsic

fluctuations and there is no external stimulus to drive synchronized brain activity across

subjects as well as propagation of activity across cortical areas. As expected, no

significant ISFC peaks were found (Fig. 3B). This provides further evidence that the

observed lag gradient is driven by the stimulus itself.

Idiosyncratic within-subject fluctuations obscure the lag gradient

We next asked whether the inter-network lag gradient observed during spoken stories

can be observed using traditional WSFC. As expected, WSFC analysis revealed a

strong peak correlation at lag zero within each network, but also a peak correlation at

lag zero across all networks such that no gradient was observed (SI Appendix, Fig. S6).

This result supports the claim that ISFC analysis filters out intrinsic signal fluctuations

that propagate across brain areas, revealing the propagation of shared story information

across networks (24, 25). This result also verifies that intrinsic, inter-network differences

in hemodynamic responses cannot account for the lag gradient; otherwise, WSFC

should show a similar lag pattern as ISFC.

Lag gradient across fine-grained subnetworks

To verify that the peak lag gradient could also be observed at a finer spatial scale, we

further divided each of the six networks into ten subnetworks, again by applying k-

means clustering to resting-state WSFC (k = 10 within each network). The peak lag

matrix between the sixty subnetworks was generated using the same methods as in the

network analysis (SI Appendix, Fig. S7A). We also visualized the brain map of lags

between one selected seed (posterior superior/middle temporal gyrus) and all the target

subnetworks (SI Appendix, Fig. S7B). Similar to the network level analysis, the peak lag

between the subnetworks revealed a gradient from the early auditory cortex to the

language network (auditory association cortex), then to the DMN.

Dominant bottom-up lag gradient across networks

We adopted a method introduced by Mitra and colleagues (28) to discern whether there

are multiple parallel lag sequences between networks. We applied principal component

analysis (PCA) to the inter-network peak lag matrix (Fig. 3A) and examined the

cumulative variance accounted for across principal components. Our results revealed

that, at the coarse level of the cortical networks used here, the first principle component

explains 88.8% of the variance in our lag matrix (SI Appendix, Fig. S8). This suggests

that there is a single, unidirectional lag gradient across networks.

The lag gradient is not driven by transient linguistic boundary effects

Prior work has reported that scene/situation boundaries in naturalistic stimuli elicit

transient brain responses that vary across regions (29–34). To test whether this

transient effect could drive the gradient observed in our lag matrix, we computed lag-

ISFC after regressing out the effects of word, sentence, and paragraph boundaries in

two stories with time-stamped annotations. As shown in SI Appendix, Fig. S9, the

regression model successfully removed transient effects of the boundaries from the

fMRI time series. Critically, however, the lag gradient remained qualitatively similar

when accounting for boundaries, indicating that the observed lag gradient does not

result from transient responses to linguistic boundaries in the story stimulus.

Reproducing the lag gradient by simulating narrative construction

Narratives have a multi-level nested hierarchical structure (35) and are reported to elicit

neural processing at increasingly long timescales along the cortical hierarchy (22, 23).

To better understand how the construction of nested narrative features could give rise to

the long inter-network lag gradient we observed, with up to 9-second lags, we created a

simulation capturing the hierarchically nested temporal structure of real-world narratives

and the corresponding hierarchy of cortical responses.

Fig. 4. Simulating narrative construction and the corresponding brain responses. (A)

The construction of the nested narrative structure, simulated by sampling boundary

intervals from actual word durations and recursively integrating them to obtain structural

boundaries at higher levels. (B) Information accumulation at different levels is generated

by a linearly increasing temporal integration function. We postulated that information

accumulation is accompanied by increased activity. (C) BOLD responses generated by

HRF convolution. This visualization is based on parameters estimated from a spoken

story stimulus (Table S1).

To match the six networks discussed so far, we simulated story features emerging

across six distinct timescales, which roughly correspond to words, phrases, sentences,

2–3 sentences, and paragraphs. The initial level of the simulated narrative hierarchy

was populated with relatively brief low-level units, with boundary intervals sampled from

actual word durations in a spoken story (SI Appendix, Fig. S10). These simulated

"words" were integrated into "phrases" of varying lengths with a mean length of three

words to obtain second-level boundaries (Fig. 4A). All "phrase"-level boundaries were

also "word"-level boundaries. A six-level structure was ultimately generated by

recursively applying this procedure. Since paragraphs are often separated in real stories

by longer silent periods (SI Appendix, Fig. S11), we inserted pauses at top-level (sixth-

level) boundaries. The bottom-up construction of narrative structure gives rise to inter-

level alignment and increasing processing timescales at higher levels, as proposed in

the hierarchical processing framework (5, 6, 18).

The simulated response amplitudes were generated using a linearly increasing temporal

integration function (Fig. 4B), based on prior work showing that information

accumulation is accompanied by gradually increasing activation within

phrases/sentences (36–41) and paragraphs (29, 32) (a similar sentence/paragraph

length effect was also observed in our data; see SI Appendix, Fig. S12). The linearly

increasing temporal integration function accumulates activity derived from lower-level

units within the interval between unit boundaries at the current levels and flushes out

the accumulated activity at unit boundaries of the current level. To account for

hemodynamic lag in the fMRI signal, we applied a canonical hemodynamic response

function (HRF) to the simulated response amplitudes (Fig. 4C). We averaged the inter-

level lag correlations across thirty different simulated structures (equivalent to 30

different stories) and extracted the peak lags. This peak-lag analysis parallels the

analysis previously applied to the fMRI data.

The simulation allows us to systematically manipulate the narrative structure and the

temporal integration function to reveal the conditions under which the lag gradient

emerges. We first performed the simulation with a set of "natural" parameters roughly

motivated by the temporal properties of our narrative stimuli and a simple temporal

integration function reflecting linear temporal accumulation (Table S1).

This simple simulation is sufficient to reproduce the inter-network lag gradient observed

in the fMRI data (Fig. 5A; as well as the ISFC at lag zero; SI Appendix, Fig. S13). In

addition, we also compared the spectral properties of the simulated and real BOLD

signals (SI Appendix, Fig. S14). We first computed the average power spectral density

(PSD) across stories. Replicating results reported by Stephens and colleagues (15), we

found stronger low-frequency fluctuations in regions with longer TRWs. Computing the

PSD of the simulated brain responses similarly revealed increased low-frequency power

in responses to high-level structures with longer intervals between boundaries. We then

adjusted one parameter at a time to explore the parameter space constrained by natural

speech.

Fig. 5. Simulated peak lag matrix. (A) Simulating the peak lag matrix observed during

story-listening fMRI data (Fig. 3A) using parameters derived from a story stimulus (the

same parameters as in Fig. 4 and Table S1). (B) Simulating the lag matrix observed

during scrambled story (scrambled words) (Fig. 3B), by setting mean unit length = 1 and

unit length variance = 0. (C) Lag matrix from the non-nested structure, created by

combining levels extracted from independently generated nested structures, which

disrupts the nesting relationship between different levels, similar to the scrambled story,

while preserving the spectral properties of individual time series (p < .05, FDR

correction).

Key parameters for the emergence of a lag gradient

Within the bounds of natural speech (SI Appendix, Fig. S15), we observed that the

simulated inter-network lag gradient is robust to varying lengths of linguistic/narrative

units (mean: 2–4; variance: 0.1–1; longer length generated longer units, often with the

top layers exceeding the length of the simulated story, i.e. 3000 words). The duration of

inter-paragraph pauses was estimated from two stories ("Sherlock" and "Merlin"; SI

Appendix, Fig. S11) (mean length: 1.5–4.5 sec; pause effect size: 0.01–1 SD of

simulated activity). We also found that the model, similar to neural responses as

observed by Lerner and colleagues (42), was robust to variations in speech rate (0.5–

1.5, relative to "Sherlock" speech rate). However, the lag gradient deteriorates with

parameters outside of the bounds of natural speech, for example, when the inter-

paragraph pause is set to 0 sec. We also simulated brain responses to word-scrambled

stories by setting mean unit length = 1 and unit length variance = 0. With this setting,

word-level units are never integrated into larger units (the units at each level correspond

to individual words from the first level). No information integration is involved, resulting

in flat activations and eliminating the difference in spectral properties of time series from

different levels. No lag gradient is observed in this case (Fig. 5B).

Next, we computed inter-level lag-correlation using simulated responses to different

nested structures (similar to responses to different stories), which preserves the spectral

properties of individual time series while disrupting their nesting relationship. No

significant lag-correlation was found when violating the nested structure of naturalistic

narrative (Fig. 5C). In addition to the aforementioned linearly increasing integration

function, we also explored several other temporal integration functions. We found that

linearly and logarithmically increasing functions both yielded the inter-network lag

gradient, but not the symmetric triangular or boxcar functions. The linearly decreasing

function resulted in a reversed lag gradient (Fig. 6). These results suggest that the

hierarchically nested structure that naturally arises from bottom-up narrative

construction and a monotonically increasing integration function are key to the

emergence of the lag gradient.

Fig. 6. Lag matrices generated using different temporal integration functions (p < .05,

FDR correction). The linearly and logarithmically increasing temporal integration

functions yield a simulated peak lag matrix similar to the one observed in fMRI data; the

symmetric triangle and boxcar functions, as well as the linearly decreasing function, do

not.

Discussion

By applying lag-ISFC to a collection of fMRI datasets acquired while subjects listened to

spoken stories, we revealed a temporal progression of story-driven brain activity along a

cortical hierarchy for narrative comprehension (Fig. 3A). The temporal cascade of

cortical responses summarized by the inter-network lag gradient was consistent across

stories as well as at coarse- and fine-grained functional network definitions (SI

Appendix, Fig. S7). The results are in line with the hierarchical processing framework,

which proposes a gradual emergence of narrative features of increasing duration and

complexity along the processing hierarchy, from early sensory areas into higher-order

cortical areas (Fig. 1). In support of our interpretation, we found that the lag gradient is

absent during rest when there is no stimulus-evoked processing (Fig. 3B), and also

when the temporal structure of the story is disrupted due to word scrambling (Fig. 3C).

We observed inter-network lags on the scale of several seconds (up to 9 seconds),

reflecting the temporal structure of real-world narratives, which integrate sounds into

words, sentences, and ideas over many seconds. Such long lags cannot be explained

by regional variations in neurovascular coupling (43) or transient activity impulses at

event boundaries. If the lag gradient only reflects variations in neurovascular coupling

across regions, it should be present both when we isolate stimulus-driven activity using

ISFC and when we examine idiosyncratic neural responses using WSFC. Instead,

however, the lag gradient was detected only with ISFC, but not WSFC (SI Appendix,

Fig. S6). Furthermore, differences in the hemodynamic response function across brain

areas are usually reported at shorter timescales (e.g. ~1–2 seconds) (44, 45) than the

0–9-second inter-network lag differences observed here in the context of narrative

comprehension (Fig. 3). In addition, we found that transient event boundaries (29–34)

did not account for the lag gradient (SI Appendix, Fig. S9).

Our simulation illustrates how narrative construction can give rise to the inter-network

lag gradient by identifying three necessary conditions: (a) a cortical hierarchy of

increasing processing timescales (Fig. 1 & Fig. 4) (5); (b) hierarchically nested

linguistic/narrative events of increasing size along the processing hierarchy (Fig. 5B &

5C) (22, 23); and (c) gradual increasing brain activity, along with information

accumulation, within the boundaries of events at each processing level (29, 32, 36–41),

combined with a reset of activity (buffer clearing) at event boundaries (7) (see temporal

integration function in Fig. 1B and Fig. 6). In this simple model, information integration at

varying granularity (e.g. word, sentence, and paragraph) is sufficient to yield the inter-

network lag gradient (Fig. 5) and spectral properties observed in the fMRI data (SI

Appendix, Fig. S14). Minor adjustments to other parameters within the bounds of

natural speech (i.e. speech rate, silent pause, and length of linguistic/narrative unit) did

not change the gradient pattern (SI Appendix, Fig. S15).

The simulation provides a simple model which bridges the discovery of TRWs using

natural stimuli (2, 42) and the accumulation of activity within linguistic units found using

simple, well-controlled stimuli (e.g. sentences with similar structures) (36–41).

Importantly, we note that our model is not the only one that could generate the predicted

lag gradient. Our aim is to combine separate findings that point to the same cortical

hierarchy with the simplest model possible. In addition, narrative processing is unlikely

to be purely unidirectional (46). The lag gradient only captures the dominant process of

bottom-up narrative construction (SI Appendix, Fig. S8). More studies are needed to

examine recurrent or bidirectional connectivity, causal relations between networks, and

nonstationary information flow over time.

Our results are also consistent with reports on the spatiotemporal dynamics of brain

responses to naturalistic stimuli. A hierarchically nested spatial activation pattern has

been revealed using movie, spoken story, and music stimuli (22, 23, 47). Chien and

colleagues (7) reported a gradual alignment of context-specific spatial activation

patterns, which was rapidly flushed at event boundaries, similar to the temporal

integration function we adopted here. Taken together, the empirical findings, combined

with our simulation, indicate that the spatiotemporal neural dynamics reflect the

structure of naturalistic, ecologically-relevant inputs (6) and that such information is

preserved even with the poor temporal resolution of fMRI. Although the current findings

are derived from listener-listener coupling, the inter-regional dynamics may shed light

on the lags observed in speaking-listener coupling (48–53). Given a particular seed

region in the speaker's brain, we would expect to observe coupling at differing lags for

different target regions in the listener's brain, and these lags may vary based on the

temporal structure of the speaker's narrative.

Our results demonstrate both the importance of using inter-subject methods to isolate

stimulus-driven signals and the value of data aggregation. The fact that we obtained

non-zero inter-network lag only with ISFC but not WSFC (SI Appendix, Fig. S6)

indicates that stimulus-driven network configuration may be masked by the idiosyncratic

fluctuations that dominate WSFC analyses (24, 25). Furthermore, although the inter-

network lags could be observed within individual stories (SI Appendix, Fig. S5), the

gradient pattern is much clearer after aggregating across stories (Fig. 3). Data

aggregation is particularly important when using naturalistic stimuli because it is

impossible to control the structure of each narrative (e.g. speaking style, duration,

complexity, and content) (35, 54–56, 56). With these methods, we are able to reveal the

inter-network lag gradient driven by naturalistic narratives, as predicted by the model

shared information flow along the cortical processing hierarchy. Further work will be

needed to examine recurrent or bidirectional information flow and to decode the content

of narrative representations—specific to each story—as they are transformed along the

cortical hierarchy.

Materials and Methods

fMRI datasets

This study relied on eight openly available spoken story datasets. Seven datasets were

used from the "Narratives" collection (OpenNeuro:

https://openneuro.org/datasets/ds002245) (57), including "Sherlock" and "Merlin" (18

participants, 11 females) (52), "The 21st year" (25 participants, 14 females) (58), "Pie

Man (PNI)", "I Knew You Were Black", "The Man Who Forgot Ray Bradbury", and

"Running from the Bronx (PNI)" (48 participants, 34 females). One dataset was used

from Princeton Dataspace: "Pie Man" (36 participants, 25 females)

(https://dataspace.princeton.edu/jspui/handle/88435/dsp015d86p269k) (25).

Two non-story datasets were also included as controls: a word-scrambled "Pie Man"

(36, participants, 20 females) dataset and a resting-state dataset (36 participants, 15

females) (see the Princeton DataSpace URL above) (25).

All participants reported fluency in English and were 18–40 years in age. The criteria of

participant exclusion have been described in previous studies for

"Sherlock", "Merlin", "The 21st year", and "Pie Man." For "Pie Man (PNI)", "I Knew You

Were Black", "The Man Who Forgot Ray Bradbury", and "Running from the Bronx

(PNI)," participants with comprehension scores 1.5 standard deviations lower than the

group means were excluded. One participant was excluded from "Pie Man (PNI)" for

excessive movement (translation along the z-axis exceeding 3 mm).

All participants provided informed, written consent, and the experimental protocol was

approved by the institutional review board of Princeton University.

fMRI preprocessing

fMRI data were preprocessed using FSL (https://fsl.fmrib.ox.ac.uk/), including slice time

correction, motion correction, and high-pass filtering (140 s cutoff). All data were aligned

to standard 3 × 3 × 4 mm Montreal Neurological Institute space (MNI152). A gray matter

mask was applied.

Functional networks

Following Simony and colleagues (25), we defined 6 intrinsic connectivity networks

within regions showing reliable responses to spoken stories. Voxels showing top 30%

ISC in at least 6 out of the 8 stories were included. Using the k-means method (L1

distance measure), these voxels were clustered according to their group-averaged

within-subject functional connectivity with all the voxels during resting. We refer to these

functional networks as the auditory (AUD), ventral language (vLAN), dorsal language

(dLAN), attention (ATT), and default mode (DMNa and DMNb) networks (SI Appendix,

Fig. S1A). To ensure that our results hold for finer-grained functional networks, we

further divided each of the six networks into ten subnetworks, again by applying k-

means clustering to resting-state WSFC (k=10 within each superordinate network).

To compare these intrinsic functional networks to the TRW hierarchy, we computed the

TRW index (i.e. intact > word-scrambled story ISC) following (8) for voxels within

regions showing reliable responses to spoken stories, using the intact and word-

scrambled Pie Man. Six TRW networks were then generated by splitting the TRW

indices into six bins by five quantiles (SI Appendix, Fig. S2).

WSFC, ISFC, and ISC

In this study, within-subject functional connectivity (WSFC) refers to within-subject inter-

region correlation, while inter-subject functional connectivity (ISFC) refers to inter-

subject inter-region correlation. Inter-subject correlation (ISC) refers to a subset of

ISFC, namely, ISFC between homologous regions (SI Appendix, Fig. S3). ISFC and

ISC were computed using the leave-one-subject-out method, i.e. correlation between

the time series from each subject and the average time series of all the other subjects

(24).

Before computing the correlation, the first 25 and last 20 volumes of fMRI data were

discarded to remove large signal fluctuations at the beginning and end of time course

due to signal stabilization and stimulus onset/offset. We then averaged voxelwise time

series across voxels within network/region masks and z-scored the resulting time

series.

Lag-correlations were computed by circularly shifting the time series such that the non-

overlapping edge of the shifted time series was concatenated to the beginning or end.

The left-out subject was shifted while the average time series of the other subjects

remained stationary. Fisher's z transformation was applied to the resulting correlation

values prior to further statistical analysis.

ISFC lag matrix

We computed the network × network × lag-ISFC matrix (SI Appendix, Fig. S3) and

extracted the lag with peak ISFC (correlation) value for each network pair (Fig. 2). The

peak ISFC value was defined as the maximal ISFC value within the window of lags from

-15 to +15 TRs; we required that the peak ISFC be larger than the absolute value of any

negative peak and excluded any peaks occurring at the edge of the window.

To obtain the mean ISFC across stories, we applied two statistical tests. Only ISFC that

passed both tests were considered significant. First, we performed a parametric one-

tailed one-sample t-test to compare the mean ISFC against zero (N = 8 stories) and

corrected for multiple comparisons by controlling the false discovery rate (FDR; (59); 6

seed × 6 target × 31 lags; q < .05).

Second, to exclude ISFC peaks that only reflected shared spectral properties, we

generated surrogates with the same mean and autocorrelation as the original time

series by time-shifting and time-reversing. We computed the correlation between the

original seed and time-reversed target with time-shifts of -100 to +100 TRs. The

resulting ISFC values were averaged across stories and served as a null distribution. A

one-tailed z-test was applied to compare ISFCs within the window of lag -15 to +15 TRs

against this null distribution. The FDR method was used to control for multiple

comparisons (seed × target × lags; q < .05). When assessing ISFC for each story, only

this second test was applied and all possible time-shifts were used to generate the null

distribution.

Principal component analysis of the lag matrix

We examined whether multiple lag sequences similarly contributed to the lag matrix,

using the method introduced by Mitra and colleagues (28). We applied PCA to the lag

matrix obtained from the averaged ISFC across stories, after transposing the matrix and

zero-centering each column. Each principal component represents a pattern of relative

lags, in other words, lag sequences. We computed the proportion of overall variance in

the lag matrix accounted for by each component in order to determine whether more

than one component played an important role.

Word/sentence/paragraph boundary effect

To test the transient effect of linguistic boundaries on inter-network lag, we computed

the lag-ISFC after regressing out activity impulses at boundaries. A multiple regression

model was built for each subject. The dependent variable was the averaged time series

of each network, removing the first 25 scans and the last 20 scans as in the ISFC

analysis. The regressors included an intercept, the audio envelope, and three sets of

finite impulse functions (-5 to +15 TRs relative to boundary onset), corresponding to

word, sentence, and paragraph (event) boundaries. We then recomputed lag-ISFC

based on the residuals of the regression model.

Word/sentence/paragraph length effect

We replicated the sentence length (36–41) and paragraph length (29, 32) effect with the

"Sherlock" and "Merlin" datasets, which were collected from the same group of

participants. The onsets and offsets of each word, sentence, and paragraph (event)

were manually time-stamped. Given the low temporal resolution of fMRI (TR = 1.5 sec)

and the difficulty of labeling the onset/offset of each syllable, they were estimated by

dividing the duration of each word by the number of syllables it contains.

We built individual GLM models that included regressors corresponding to the presence

of syllable, word, sentence, and paragraph respectively, accompanied by three

parametric modulators: accumulated syllable number within words, accumulated word

number within sentences, and accumulated sentence number within paragraphs. These

parametric regressors were included to test whether brain activations accumulate

toward the end of word/sentence/paragraph; the longer the word/sentence/paragraph

the stronger the activations. In addition to the regressors of interest, one regressor was

included for speech segments without clear paragraph labels. We did not orthogonalize

the regressors to each other.

Effect maps of the three parametric modulators (i.e. word length, sentence length, and

paragraph length) from the individual level models of both stories were smoothed with a

Gaussian kernel (FWHM = 8 mm) and input to three group-level models to test the

word, sentence, and paragraph length effects respectively (flexible factorial design

including the main effects of story and participant; $p < .005$, not corrected). We

observed sentence and paragraph length effects. Using the same threshold, no word

length effect was observed,

Power-spectral density analysis

We performed spectral analyses following (15). We estimated the power spectrum of

the primary auditory area and a DMN area (precuneus). As for the connectivity analysis,

we cropped the first 25 and last 20 scans and z-scored the time series. For each story,

the resulting time series were averaged across subjects and normalized across time.

The power spectrum of the group-mean time series was estimated using Welch's

method with a Hamming window of width 99 sec (66 TRs) and 50% overlap (based on

the parameters from (15)). The power spectra of individual voxels were averaged within

the anatomical masks of left Heschl's gyrus and left precuneus from the AAL atlas. The

mean spectra across stories were then computed.

Simulating the construction of nested narrative structures and the corresponding

BOLD responses

To illustrate how information accumulation at different timescales could account for the

inter-network lag gradient during story-listening, we simulated the construction of nested

narrative structures closely following the statistical structure of real spoken stories and

generated BOLD responses at each processing level. To build the first level of a nested

structure, we sampled a sequence of 3000 word durations with replacement from

"Sherlock," which is the longest example of spontaneous speech among our datasets,

recorded from a non-professional speaker without rehearsal or script (SI Appendix, Fig.

S10). Boundaries between units at the first level were set up accordingly.

Unit length

First-level units were integrated into units of the next level with a lognormal distributed

unit length; e.g. integrating three words into a phrase (unit length = 3) (SI Appendix, Fig.

S10). Boundaries between second-level units were inserted accordingly. Second-level

units were integrated into the third-level units following the same method. A nested

structure of six levels was thus generated.

Temporal integration function

Postulating that information accumulation is accompanied by increased activity, brain

responses within each level of the nested structure were generated as a function of unit

length. For example, a linear temporal integration function generates activity [1 2 3] for a

"phrase" (i.e. a Level 2 unit) consisting of three "words" (i.e. Level 1 units). The first

(word) level integration was computed based on syllable numbers sampled from

"Sherlock" along with word durations.

Pause length and pause effect size

In naturalistic narratives, boundaries between high-level units are often accompanied by

silent pauses (SI Appendix, Fig. S11). Therefore, we inserted pauses with normally

distributed lengths at the boundaries of the highest level units (SI Appendix, Fig. S10).

Activity during the pause period was set as 0.1 standard deviations below the minimum

activity of each level.

To account for HRF delay in fMRI signals, we applied the canonical hemodynamic

response function provided by the software SPM (https://www.fil.ion.ucl.ac.uk/spm/) (60)

and resampled the output time series from a temporal resolution of 0.001 sec to 1.5 sec

to match the TR in our data. We ran 30 simulations for each set of simulation

parameters. Each simulation produced different narrative structures (equivalent to

different stories). The peak lag of the mean inter-level correlation across simulations

was extracted and thresholded using the same method as in the ISFC analysis (Fig. 2).

To examine whether the simulated and real fMRI signals shared similar power spectra,

we also applied the power-spectral density analysis to the simulated BOLD responses

at each of the six levels and averaged across thirty simulations.

We started with a set of reasonable parameters (SI Appendix, Table 1) (speech rate =

1, relative to "Sherlock"; unit length mean = 3; unit length variance = 0.5; temporal

integration function = linearly increasing; mean pause length = 3 sec; pause effect size

= 0.1 SD of the simulated activity) and explored alternative parameter sets within the

bound of natural speech to test whether inter-level lag was robust to parameter

changes.

Data availability

600   This study relied on eight openly available spoken story datasets. Seven datasets were

601   used from the "Narratives" collection (OpenNeuro:

602   https://openneuro.org/datasets/ds002245) (57), One dataset was used from Princeton

603   Dataspace: "Pie Man" (36 participants, 25 females)

604   (https://dataspace.princeton.edu/jspui/handle/88435/dsp015d86p269k) (25).

Acknowledgment

606   This study is supported by the National Institute of Mental Health (R01-MH112357 and

607   DP1-HD091948).

References

1. M. H. Christiansen, N. Chater, The Now-or-Never bottleneck: A fundamental constraint on language. *Behav. Brain Sci.* **39** (2015).

2. U. Hasson, E. Yang, I. Vallines, D. J. Heeger, N. Rubin, A hierarchy of temporal receptive windows in human cortex. *J. Neurosci.* **28**, 2539–2550 (2008).

3. Y. Lerner, C. J. Honey, L. J. Silbert, U. Hasson, Topographic mapping of a hierarchy of temporal receptive windows using a narrated story. *J. Neurosci.* **31**, 2906–2915 (2011).

4. Y. Yeshurun, M. Nguyen, U. Hasson, The default mode network: where the idiosyncratic self meets the shared social world. *Nat. Rev. Neurosci.* **22**, 181–192 (2021).

5. U. Hasson, J. Chen, C. J. Honey, Hierarchical process memory: Memory as an integral component of information processing. *Trends Cogn. Sci.* **19**, 304–313 (2015).

6. S. J. Kiebel, J. Daunizeau, K. J. Friston, A hierarchy of time-scales and the brain. *PLoS Comput. Biol.* **4**, e1000209 (2008).

7. H. Y. S. Chien, C. J. Honey, Constructing and forgetting temporal context in the human cerebral cortex. *Neuron* **106**, 675-686.e11 (2020).

8. Y. Yeshurun, M. Nguyen, U. Hasson, Amplification of local changes along the timescale processing hierarchy. *Proc. Natl. Acad. Sci.*, 201701652 (2017).

9. C. J. Honey, *et al.*, Slow cortical dynamics and the accumulation of information over long timescales. *Neuron* **76**, 423–434 (2012).

10. M. E. Peters, M. Neumann, L. Zettlemoyer, W. T. Yih, Dissecting contextual word embeddings: Architecture and representation. *Proc. 2018 Conf. Empir. Methods Nat. Lang. Process. EMNLP 2018*, 1499–1509 (2018).

11. J. Vig, Y. Belinkov, Analyzing the structure of attention in a transformer language model. *Proc. 2019 ACL Workshop BlackboxNLP Anal. Interpret. Neural Netw. NLP*, 63–76 (2019).

12. P. F. Dominey, Narrative event segmentation in the cortical reservoir. *PLOS Comput. Biol.* **17**, e1008993–e1008993 (2021).

13. C. Caucheteux, A. Gramfort, J.-R. King, Model-based analysis of brain activity reveals the hierarchy of language in 305 subjects in *Conference on Empirical Methods in Natural Language Processing*, (2021).

14. R. V. Raut, A. Z. Snyder, M. E. Raichle, Hierarchical dynamics as a macroscopic organizing principle of the human brain. *Proc. Natl. Acad. Sci.* **117**, 20890–20897 (2020).

15. G. J. Stephens, C. J. Honey, U. Hasson, A place for time: The spatiotemporal structure of neural dynamics during natural audition. *J. Neurophysiol.* **110**, 2019–2026 (2013).

16. J. D. Murray, *et al.*, A hierarchy of intrinsic timescales across primate cortex. *Nat. Neurosci.* **17**, 1661–1663 (2014).

17. A. T. Baria, *et al.*, Linking human brain local activity fluctuations to structural and
functional network architectures. *NeuroImage* **73**, 144–155 (2013).

18. J.-P. Changeux, A. Goulas, C. C. Hilgetag, A connectomic hypothesis for the
hominization of the brain. *Cereb. Cortex*, 1–25 (2020).

19. J. M. Huntenburg, P. L. Bazin, D. S. Margulies, Large-scale gradients in human
cortical organization. *Trends Cogn. Sci.* **22**, 21–31 (2018).

20. R. Chaudhuri, K. Knoblauch, M. A. Gariel, H. Kennedy, X.-J. Wang, A large-scale
circuit mechanism for hierarchical dynamical processing in the primate cortex.
Neuron **88**, 419–431 (2015).

21. M. Demirtaş, *et al.*, Hierarchical heterogeneity across human cortex shapes large-
scale neural dynamics. *Neuron* **101**, 1181-1194.e13 (2019).

22. C. Baldassano, *et al.*, Discovering event structure in continuous narrative
perception and memory. *Neuron* **95**, 709-721.e5 (2017).

23. L. Geerligs, M. van Gerven, K. L. Campbell, U. Güçlü, A nested cortical hierarchy
of neural states underlies event segmentation in the human brain. *bioRxiv*,
2021.02.05.429165 (2021).

24. S. A. Nastase, V. Gazzola, U. Hasson, C. Keysers, Measuring shared responses
across subjects using intersubject correlation. *Soc. Cogn. Affect. Neurosci.* **14**,
667–685 (2019).

25. E. Simony, *et al.*, Dynamic reconfiguration of the default mode network during
narrative comprehension. *Nat. Commun.* **7**, 12141 (2016).

26. U. Hasson, Y. Nir, I. Levy, G. Fuhrmann, R. Malach, Intersubject synchronization of
cortical activity during natural vision. *Science* **303**, 1634–1640 (2004).

27. J. P. Kauppi, I. P. Jääskeläinen, M. Sams, J. Tohka, Inter-subject correlation of
brain hemodynamic responses during watching a movie: Localization in space and
frequency. *Front. Neuroinformatics* **4**, 5 (2010).

28. A. Mitra, A. Z. Snyder, T. Blazey, M. E. Raichle, Lag threads organize the brain's
intrinsic activity. *Proc. Natl. Acad. Sci. U. S. A.* **112**, E7307 (2015).

29. Y. Ezzyat, L. Davachi, What constitutes an episode in episodic memory? *Psychol.*
Sci. **22**, 243–252 (2011).

30. N. K. Speer, J. M. Zacks, J. R. Reynolds, Human brain activity time-locked to
narrative event boundaries. *Psychol. Sci.* **18**, 449–455 (2007).

31. C. Whitney, *et al.*, Neural correlates of narrative shifts during auditory story
comprehension. *NeuroImage* **47**, 360–366 (2009).

32. T. Yarkoni, N. K. Speer, J. M. Zacks, Neural substrates of narrative
comprehension and memory. *NeuroImage* **41**, 1408–1425 (2008).

33. J. M. Zacks, *et al.*, Human brain activity time-locked to perceptual event
boundaries. *Nat. Neurosci.* **4**, 651–655 (2001).

34. J. M. Zacks, N. K. Speer, K. M. Swallow, C. J. Maley, The brain's cutting-room
floor: Segmentation of narrative cinema. *Front. Hum. Neurosci.* **4**, 1–15 (2010).

35. R. M. Willems, S. A. Nastase, B. Milivojevic, Narratives for neuroscience. *Trends*
Neurosci. **43**, 271–273 (2020).

36. C. H. C. Chang, S. Dehaene, D. H. Wu, W. J. Kuo, C. Pallier, Cortical encoding of
linguistic constituent with and without morphosyntactic cues. *Cortex* **129**, 281–295
(2020).
37. E. Fedorenko, *et al.*, Neural correlate of the construction of sentence meaning.
Proc. Natl. Acad. Sci. **113**, E6256–E6262 (2016).
38. L. Giglio, M. Ostarek, K. Weber, P. Hagoort, Commonalities and asymmetries in
the neurobiological infrastructure for language production and comprehension.
Cereb. Cortex (2021) https:/doi.org/10.1093/cercor/bhab287.
39. W. Matchin, C. Hammerly, E. Lau, The role of the IFG and pSTS in syntactic
prediction: Evidence from a parametric study of hierarchical structure in fMRI.
Cortex **88**, 106–123 (2017).
40. M. J. Nelson, *et al.*, Neurophysiological dynamics of phrase-structure building
during sentence processing. *Proc. Natl. Acad. Sci. U. S. A.* **114**, E3669–E3678
(2017).
41. C. Pallier, A.-D. A. Devauchelle, S. Dehaene, Cortical representation of the
constituent structure of sentences. *Proc. …* **108**, 2522–2527 (2011).
42. Y. Lerner, C. J. Honey, M. Katkov, U. Hasson, Temporal scaling of neural
responses to compressed and dilated natural speech. *J. Neurophysiol.* **111**, 2433–
2444 (2014).
43. D. Rangaprakash, G. R. Wu, D. Marinazzo, X. Hu, G. Deshpande, Hemodynamic
response function (HRF) variability confounds resting-state fMRI functional
connectivity. *Magn. Reson. Med.* **80**, 1697–1713 (2018).
44. M. G. Bright, D. P. Bulte, P. Jezzard, J. H. Duyn, Characterization of regional
heterogeneity in cerebrovascular reactivity dynamics using novel hypocapnia task
and BOLD fMRI. *NeuroImage* **48**, 166–175 (2009).
45. D. A. Handwerker, J. M. Ollinger, M. D'Esposito, Variation of BOLD hemodynamic
responses across subjects and brain regions and their effects on statistical
analyses. *NeuroImage* **21**, 1639–1651 (2004).
46. M. J. Pickering, C. Gambi, Predicting while comprehending language: A theory
and review. *Psychol. Bull.* **144**, 1002–1044 (2018).
47. J. A. Williams, *et al.*, High-order areas and auditory cortex both represent the high-
level event structure of music. *bioRxiv*, 2021.01.26.428291 (2021).
48. L. Liu, *et al.*, The "two-brain" approach reveals the active role of task-deactivated
default mode network in speech comprehension. *Cereb. Cortex* (2022)
https:/doi.org/10.1093/cercor/bhab521.
49. M. Nguyen, *et al.*, Teacher–student neural coupling during teaching and learning.
Soc. Cogn. Affect. Neurosci. **17**, 367–376 (2022).
50. G. J. Stephens, L. J. Silbert, U. Hasson, Speaker-listener neural coupling underlies
successful communication. *Proc. Natl. Acad. Sci. U. S. A.* **107**, 14425–14430
(2010).
51. P. D. Antonenko, R. Davis, J. Wang, M. Celepkolu, On the Same Wavelength:
Exploring Team Neurosynchrony in Undergraduate Dyads Solving a Cyberlearning

Problem With Collaborative Scripts. *Mind Brain Educ.* **13**, 4–13 (2019).

52. A. Zadbood, J. Chen, Y. C. Leong, K. A. Norman, U. Hasson, How we transmit
memories to other brains: constructing shared neural representations via
communication. *Cereb. Cortex* **27**, 4988–5000 (2017).

53. L. J. Silbert, C. J. Honey, E. Simony, D. Poeppel, U. Hasson, Coupled neural
systems underlie the production and comprehension of naturalistic narrative
speech. *Proc. Natl. Acad. Sci. U. S. A.* **111**, E4687–E4696 (2014).

54. L. S. Hamilton, A. G. Huth, The revolution will not be controlled: natural stimuli in
speech neuroscience. *Lang. Cogn. Neurosci.* **35**, 573–582 (2020).

55. H. Lee, B. Bellana, J. Chen, What can narratives tell us about the neural bases of
human memory? *Curr. Opin. Behav. Sci.* **32**, 111–119 (2020).

56. S. Sonkusare, M. Breakspear, C. Guo, Naturalistic stimuli in neuroscience:
Critically acclaimed. *Trends Cogn. Sci.* **23**, 699–714 (2019).

57. S. A. Nastase, *et al.*, The "Narratives" fMRI dataset for evaluating models of
naturalistic language comprehension. *Sci. Data* **8**, 250–250 (2021).

58. C. H. C. Chang, C. Lazaridi, Y. Yeshurun, K. A. Norman, U. Hasson, Relating the
past with the present: Information integration and segregation during ongoing
narrative processing. *J. Cogn. Neurosci.* **33**, 1106–1128 (2021).

59. Y. Benjamini, Y. Hochberg, Controlling the False Discovery Rate: A Practical and
Powerful Approach to Multiple Testing. *J. R. Stat. Soc. Ser. B Methodol.* **57** (1995).

60. W. Penny, K. Friston, J. Ashburner, S. Kiebel, T. Nichols, *Statistical parametric*
mapping: The analysis of functional brain images (2007)
https://doi.org/10.1016/B978-0-12-372560-8.X5000-1.

Supplementary Information for

Narrative construction drives a gradient of response lags across the cortical
timescales hierarchy

Claire H. C. Chang1,*, Samuel A. Nastase1,*, and Uri Hasson1

1. Princeton Neuroscience Institute, Princeton University, Princeton, New Jersey, 08540, USA.

* To whom correspondence should be addressed:

Claire H. C. Chang, claire.hc.chang@gmail.com

Samuel A. Nastase, sam.nastase@gmail.com

This PDF file includes:

Figures S1 to S15

Tables S1

Fig. S1. Averaged fMRI response time series for six intrinsic functional networks while

subjects listened to a spoken story. (A) Functional networks defined by applying k-

means clustering to WSFC measured during rest and labeled based on anatomical

correspondence with previously defined functional regions following (25) (AUD:

auditory; vLAN: ventral language; dLAN: dorsal language; DMN: default mode network;

ATT: attention network). (B) Averaged fMRI responses time series in the "Sherlock"

dataset, extracted from the predefined network masks. Two example segments of the

response time series are highlighted at the bottom right. The peaks of the fluctuations in

a given window are indicated by colored vertical lines. Note the stereotyped lag in both

positive and negative BOLD fluctuations across networks; e.g. signal deflections in the

dark blue auditory network tend to precede deflections in the cyan/green language

networks, which tend to precede deflections in the yellow/red default mode networks.

Fig. S2. Lag gradient between networks defined by TRW indices. (A) Networks

generated by splitting the TRW indices (intact > scrambled story ISC) into 6 bins by five

quantiles. (B) networks defined by applying k-mean clustering to resting WSFC (SI

Appendix, Fig. S1). (C) Networks defined by TRW index show a similar topographic

gradient as the networks defined by resting-state WSFC, from the auditory areas to

DMN, which is manifested by the significant correlation between the two sets of

networks index. Random jitters are added to better show the overlapped data points.

(D) Peak lag matrix between networks defined by TRW index across seven stories (p

< .05, FDR corrected). "Pie Man" was excluded from this analysis since it was used to

compute the TRW index.

ISFC:
seed x target network at lag 0

Lag-ISFC:
seed x target x lag

One seed lag-ISFC:
target x lag

Fig. S3. The relationship between inter-subject functional connectivity (ISFC), inter-

subject-correlation (ISC), and lag-ISFC. This figure shows real data from the "Sherlock"

story.

Fig. S4. Lag-ISFC curves between the six functional networks, corresponding to the left

panel of Fig. 3A. Fisher's z transformation was applied to the R-values before

averaging. Vertical lines indicate significant R peaks (p < .05, FDR correction).

Fig. S5. The network × network peak lag matrix based on the lag-ISFC in each

individual story (p < .05, FDR corrected).

Fig. S6. The network × network peak lag matrix based on the averaged lag-WSFC

across eight stories (p < .05, FDR corrected).

Fig. S7. Subnetwork × subnetwork peak lags based on the averaged lag-ISFC across

eight stories (p < .05, FDR corrected). The subnetworks were created by dividing each

of the six main functional networks (SI Appendix, Fig. S1) into 10 subnetworks, applying

k-means clustering to resting-state WSFC (k = 10 within each network). (A) The peak

lag matrix. (B) The brain map of significant peak lags between one seed subnetwork

(posterior superior/middle temporal gyrus) and all the sixty subnetworks.

A

B

Fig. S8. Principal component analysis of the inter-network lag matrix across eight

stories (Fig. 3A). (A) The percentage of variance explained by each principal

component. (B) Relative-lag values from each principal component. Line thickness

indicates the percentage of variance explained by that component.

Fig. S9. Boundary effect on the network x network peak lag matrix across stories. (A) The fMRI signals around word, sentence, and paragraph boundaries before and after regressing out the boundary effects. Shaded areas indicate 95% confidence intervals across subjects. (B) The peak lag matrix before and after regressing out the boundary effects (p < .05, FDR corrected).

833   Fig. S10. The distributions of word duration, unit length, and pause length with the

834   simulation parameters described in Table S1.

836   Fig. S11. The silent pause between paragraphs shown in real spoken stories. Shaded

837   areas indicate 95% confidence intervals.

Sentence/Paragraph length effect

Fig. S12. Sentence and paragraph length effects in two time-stamped stories

("Sherlock" & "Merlin") (p < .005, uncorrected). Significant length effect indicates

activation accumulation from the start toward the end of sentences or paragraphs.

Fig. S13. ISFC matrices at lag 0 in real and simulated stories (the same simulation

parameters as in Table S1).

Fig. S14. Power spectral densities of real (left) and simulated (right, the same

parameter set as Table S1) BOLD responses to stories. PSD of the actual BOLD data

exhibited stronger low-frequency fluctuations at regions with longer temporal receptive

windows. Simulated BOLD responses show a similar pattern.

Fig. S15. Robust lag gradient within the parameter space bound by natural speech (the same parameters as in Table S1 unless otherwise indicated) (p < .05, FDR correction).

853   Table S1. A set of exemplar stimulation parameters motivated by a spoken story

854   ("Sherlock"). SD: standard deviation.

Exemplar simulation parameters	
speech rate (relative to "Sherlock")	1
mean unit length	3
unit length variance	0.5
temporal integration function	linearly increasing
mean pause length	3 sec
pause length effect size (in SD of the simulated activity)	0.1