Title:

Online Phylogenetics using Parsimony Produces Slightly Better Trees and is Dramatically More Efficient

for Large SARS-CoV-2 Phylogenies than *de novo* and Maximum-Likelihood Approaches

Authors:

Bryan Thornlow[1,2,*,#], Alexander Kramer[1,2,#], Cheng Ye[3], Nicola De Maio[4], Jakob McBroome[1,2], Angie S.

Hinrichs[2], Robert Lanfear[5], Yatish Turakhia[3], Russell Corbett-Detig[1,2,*]

Affiliations:

[1]Department of Biomolecular Engineering, University of California, Santa Cruz; Santa Cruz, CA

95064, USA

[2]Genomics Institute, University of California, Santa Cruz; Santa Cruz, CA 95064, USA

[3]Department of Electrical and Computer Engineering, University of California, San Diego; San

Diego, CA 92093, USA

[4]European Molecular Biology Laboratory, European Bioinformatics Institute (EMBL-EBI),

Wellcome Genome Campus; Cambridge CB10 1SD, UK

[5]Department of Ecology and Evolution, Research School of Biology, Australian National

University; Canberra, ACT 2601, Australia

*Correspondence to bthornlo@ucsc.edu and rucorbet@ucsc.edu

[#]These authors contributed equally to this work.

Abstract:

Phylogenetics has been foundational to SARS-CoV-2 research and public health policy, assisting in

genomic surveillance, contact tracing, and assessing emergence and spread of new variants. However,

phylogenetic analyses of SARS-CoV-2 have often relied on tools designed for *de novo* phylogenetic

inference, in which all data are collected before any analysis is performed and the phylogeny is inferred

once from scratch. SARS-CoV-2 datasets do not fit this mould. There are currently over 10 million

sequenced SARS-CoV-2 genomes in online databases, with tens of thousands of new genomes added

every day. Continuous data collection, combined with the public health relevance of SARS-CoV-2, invites

an "online" approach to phylogenetics, in which new samples are added to existing phylogenetic trees

every day. The extremely dense sampling of SARS-CoV-2 genomes also invites a comparison between

likelihood and parsimony approaches to phylogenetic inference. Maximum likelihood (ML) methods are

more accurate when there are multiple changes at a single site on a single branch, but this accuracy

comes at a large computational cost, and the dense sampling of SARS-CoV-2 genomes means that

these instances will be extremely rare because each internal branch is expected to be extremely short.

Therefore, it may be that approaches based on maximum parsimony (MP) are sufficiently accurate for

reconstructing phylogenies of SARS-CoV-2, and their simplicity means that they can be applied to much

larger datasets. Here, we evaluate the performance of *de novo* and online phylogenetic approaches, and

ML and MP frameworks, for inferring large and dense SARS-CoV-2 phylogenies. Overall, we find that

online phylogenetics produces similar phylogenetic trees to *de novo* analyses for SARS-CoV-2, and that

MP optimizations produce more accurate SARS-CoV-2 phylogenies than do ML optimizations. Since MP

is thousands of times faster than presently available implementations of ML and online phylogenetics is

faster than *de novo*, we therefore propose that, in the context of comprehensive genomic epidemiology

of SARS-CoV-2, MP online phylogenetics approaches should be favored.

Key words:

SARS-CoV-2, phylogenetics, parsimony, maximum likelihood, optimization

Introduction:

The widespread availability and extreme abundance of pathogen genome sequencing has made phylogenetics central to combatting the pandemic. Communities worldwide have begun implementing genomic surveillance by systematically sequencing the genomes of a percentage of local cases (Deng et al. 2020; Lu et al. 2020a; Meredith et al. 2020; Park et al. 2021). This has been invaluable in tracing local transmission chains (Bluhm et al. 2020; Lam 2020), understanding the genetic makeup of viral populations within local communities (Gonzalez-Reiche et al. 2020; Franceschi et al. 2021; Thornlow et al. 2021a), uncovering the means by which viral lineages have been introduced to new areas (Castillo et al. 2020), and measuring the relative spread of specific variants (Skidmore et al. 2021; Umair et al. 2021). Phylogenetic approaches for better understanding the proximate evolutionary origins of the virus (Li et al. 2020), as well as to identify recombination events (Jackson et al. 2021; Turakhia et al. 2021b) and instances of convergent evolution (Kalantar et al. 2020; Peng et al. 2021) have greatly informed our understanding of the virus. Phylogenetic visualization software including Auspice (Hadfield et al. 2018) and Taxonium (Sanderson 2021a) have also become widely used for public health purposes.

A comprehensive, up-to-date phylogenetic tree of SARS-CoV-2 is important for public health officials and researchers. A tree containing all available sequences can sometimes facilitate identification of epidemiological links between samples that might otherwise be obscured in subsampled phylogenies. Conversely, these approaches can often rule out otherwise plausible transmission histories. Such information can also help to identify the likely sources of new viral strains in a given area (Moreno et al. 2020; Tang et al. 2021). Additionally, using up-to-date information enables us to find and track quickly growing clades and novel variants of concern (Annavajhala et al. 2021; Tegally et al. 2021), as well as to measure the spread of known variants at both global and community scales. Furthermore, comprehensive phylogenies can facilitate identification of recombinant viral genomes (Turakhia et al. 2021b), natural selection at homoplasious positions (van Dorp et al. 2020), variation in mutation rates (De Maio et al. 2021a), and systematic recurrent errors (Turakhia et al. 2020). This also facilitates

naming lineages of interest, which has been especially important in tracking variants of concern during

the pandemic (*e.g.* B.1.1.7 or "Alpha" and B.1.617.2 or "Delta") (Rambaut et al. 2020).

SARS-CoV-2 presents a unique set of phylogenetic challenges. First, the unprecedented pace

and scale of whole-genome sequence data has forced the phylogenetics community to place runtime

and scalability at the center of every inference strategy. More than 10 million SARS-CoV-2 genome

sequences are currently available, with tens of thousands being added each day. Prior to the pandemic,

de novo phylogenetics, or approaches that infer phylogenies from scratch, have been the standard, as

there has rarely been a need to re-infer or improve pre-existing phylogenies on a daily basis. Re-inferring

a tree of more than 10 million samples daily, however, is extremely costly, and has brought a renewed

focus on methods for adding new samples to existing phylogenetic trees (Matsen et al. 2010; Berger et

al. 2011; Izquierdo-Carrasco et al. 2014; Fourment et al. 2018; Barbera et al. 2019). This approach has

been called "online phylogenetics" (Gill et al. 2020), and has important advantages in the context of the

pandemic and beyond. Online phylogenetics is appealing for the genomic surveillance of any pathogen,

because iterative optimization should decrease computational expense, allowing good estimates of

phylogenies to be made readily available.

Second, SARS-CoV-2 genomes are much more closely related than sequences in most other

phylogenetic analyses. Because the advantages of maximum likelihood methods decrease for closely

related samples and long branches are relatively rare in the densely sampled SARS-CoV-2 phylogeny

(Felsenstein 1978; Hendy and Penny 1989; Philippe et al. 2005), this suggests that phylogenetic

inferences based on maximum parsimony, a much faster and simpler phylogenetic inference method,

could be better suited for online phylogenetic analyses of SARS-CoV-2 genomes (Wertheim et al. 2021).

The principle of maximum parsimony is that the tree with the fewest mutations should be favored, and it

is sometimes described as a non-parametric phylogenetic inference method (Sullivan and Swofford

2001; Kolaczkowski and Thornton 2004). Additionally, because parsimony-based tree optimization does

not require estimation of ancestral character state uncertainty at all positions in the phylogeny like ML

optimization does, parsimony uses much less memory.

Here, we evaluate approaches that would enable one to maintain a fully up-to-date and

comprehensive global phylogeny of SARS-CoV-2 genome sequences (McBroome et al. 2021).

Specifically, we investigate tradeoffs between online and *de novo* phylogenetics and between maximum

parsimony and maximum likelihood approaches when the aim is for an analysis to scale to millions of

sequences, with tens of thousands of new sequences being added daily. We chose to compare

maximum parsimony and maximum likelihood (and omit other approaches like neighbor-joining) because

they were the most effective methods at inferring large SARS-CoV-2 phylogenies based on previous

analyses (Lanfear and Mansfield 2020), and because the most efficient distance-based methods are

quadratic in memory usage so cannot scale to estimating trees from datasets of more than a few

hundred thousand sequences (Wang et al. 2022). We mimic the time-course of the pandemic by

introducing increasingly large numbers of SARS-CoV-2 genome sequences proportionately to their

reported sampling dates.

We evaluate potential online phylogenetics approaches by iteratively adding samples to existing

trees and optimizing the augmented phylogeny with different tools that have been proposed for this

purpose during the pandemic. In particular, we evaluate matOptimize, IQ-TREE 2, and FastTree 2.

Between each optimization step, we use UShER (Turakhia et al. 2021a) to add samples to trees by

maximum parsimony. matOptimize is a parsimony optimization approach that uses subtree pruning and

regrafting (SPR) moves to minimize the total mutations in the final tree topology (Ye et al. 2022) . IQ-

TREE 2 uses nearest neighbor interchange (NNI) to find the tree with the highest likelihood given an

input multiple sequence alignment (Minh et al. 2020). FastTree 2 uses a pseudo-likelihood approach that

employs minimum-evolution SPR and/or NNI moves and maximum-likelihood NNI moves while using

several heuristics to reduce the search space (Price et al. 2010). The likelihood-based approaches

evaluated here report branch lengths in substitutions per site. Parsimony-based matOptimize reports

branch lengths in total substitutions, which can be converted to the latter by dividing by the genome

length. These branch lengths may be interpreted as is or used as an initial estimate for other distance

measures, for example in the construction of time trees (Sanderson 2021b).

Results from our comparisons demonstrate that for the purposes of SARS-CoV-2 phylogenetics,

in which samples are numerous and closely related and inference speed is of high significance,

parsimony-based online phylogenetics applications are clearly most favorable and are also the only

immediately available methods capable of producing daily phylogenetic estimates of all available SARS-

CoV-2 genomes (Turakhia et al. 2021a). We note that matOptimize is used to maintain such a phylogeny

comprising over 9 million genomes as of April 2022 (McBroome et al. 2021). As similarly vast datasets

will soon be available for many species and pathogens, we expect that online approaches using

parsimony or pseudo-likelihood optimization will become increasingly central to phylogenetic inference.

Results and Discussion:

Online phylogenetics is an alternative to de novo phylogenetics for ongoing studies.

The vast majority of phylogenetics during the pandemic has consisted of *de novo* phylogenetics

approaches (Hadfield et al. 2018; Li et al. 2020; Lu et al. 2020a, 2020b; Meredith et al. 2020), in which

each phylogeny is inferred using only genetic variation data, and without a guide tree (Fig. 1). This

strategy for phylogenetic inference has long been the default, as in most instances in the past, data are

collected just once for a project, and more relevant data are rarely going to be made available in the near

future. This process is well characterized and has been foundational for many phylogenetics studies

(Hug et al. 2016; Parks et al. 2018; Lu et al. 2020b), and most phylogenetics software is developed with

de novo phylogenetics as the primary intended usage.

A challenging aspect of pandemic phylogenetics is the need to keep up with the pace of data

generation as genome sequences continuously become available. To evaluate phylogenetics

applications in the pandemic (Fig. 1), we split 233,326 samples dated from December 23, 2019 through

January 11, 2021 into 50 batches according to their date of collection. Each batch contains roughly 5,000

samples. Samples in each batch were collected within a few days of each other, except in the first

months of the pandemic when sample collection was more sparse. We also constructed a dataset of

otherwise similar data simulated from a known phylogeny (see Methods). The intent of this scheme is to

roughly approximate the data generation and deposition that occurred during the pandemic. All datasets

are available from the repository associated with this project (Thornlow et al. 2021b), for reproducibility

and so that future methods developers can directly compare their outputs to our results. We performed

online and *de novo* phylogenetics using a range of inference and optimization approaches. Since

thousands of new sequences are added to public sequence repositories each day, we terminated any

phylogenetic inference approaches that took more than 24 hours, because such phylogenies would be

obsolete for some public health applications by the time they were inferred.

Figure 1: Phylogenies may be optimized from scratch using de novo phylogenetics or iteratively

using online phylogenetics. *In de novo phylogenetics (top), trees are repeatedly re-inferred from*

scratch. Conversely, online phylogenetics (bottom) involves placement of new samples as they are

collected. Intermittent optimization steps (not depicted) after new samples are placed can help overcome

errors from previous iterations. Online phylogenetics is expected to be much faster and require less

memory than de novo phylogenetics.

Analyses using simulated data suggest that online phylogenetics is more accurate for SARS-

CoV-2.

We first compared matOptimize (commit 66ca5ff, conda version 0.4.8) (Ye et al. 2022), IQ-TREE

2 (Minh et al. 2020), and FastTree 2 (Price et al. 2010) using both online and *de novo* phylogenetics

strategies using simulated data that we designed to closely mimic real SARS-CoV-2 datasets. All online

phylogenomics workflows used UShER (Turakhia et al. 2021a) to add new sequences to the previous

tree (see Methods) as to our knowledge it is the only software package that is fast enough to perform

under real time constraints. We chose these three tools based on their widespread usage among SARS-

CoV-2 phylogenetics applications (*e.g.* matOptimize is part of the UShER suite (Turakhia et al. 2021a),

IQ-TREE 2 is used by (COVID-19 Genomics UK (COG-UK) Consortium 2020; Lanfear and Mansfield

2020) and FastTree 2 is used by (Hadfield et al. 2018)) as well as to cover several different

methodologies.

Simulating an alignment based on a known tree ensures that there is a ground truth for

comparison to definitively assess each optimization method. We used an inferred global phylogeny as a

template to simulate a complete multiple sequence alignment using phastSim (De Maio et al. 2021b). We

subsampled this simulated alignment into 50 progressively larger sets of samples, ranging in number of

samples from 4,676 to 233,326 (see Methods), to examine each of the three optimization methods in

both online and *de novo* phylogenetics. We then computed the Robinson-Foulds distance for unrooted

trees of each iteration, after condensing identical samples and collapsing very short branches, to the

global mutation-annotated tree on which the simulation was based, pruned to contain only the relevant

samples, and normalized by the maximum possible Robinson-Foulds distance between the trees (Fig. 2,

Fig. S3) (Steel and Penny 1993).

All online phylogenetics methods noticeably outperformed their *de novo* counterparts. Overall,

online matOptimize produced phylogenies with the lowest Robinson-Foulds distance to the ground truth

for the majority of iterations (Fig. 2). Online IQ-TREE 2 performed similarly, but was able to complete

only 25 of the 50 iterations due to its extreme computational resource requirements. For example, for the

14th phylogeny of 60,571 sequences, which was the last phylogeny produced using under 200 GB of

RAM in under 24 hours by all six methods, we found Robinson-Foulds distances of 1696, 2590, and

2130 for *de novo UShER*+matOptimize, FastTree 2, and IQ-TREE 2 respectively, and distances of 1557,

2111, and 1618 for online matOptimize, FastTree 2, and IQ-TREE 2, respectively.

There are several possible explanations for the improved performance of online phylogenetics

relative to *de novo* approaches. First, the radius for SPR moves when optimizing a large tree is

insufficiently large to find improvements that are more readily applied when the tree contains fewer

samples as in early rounds of online phylogenetics. In online phylogenetics, these improvements carry

over to subsequent trees, while in *de novo*, they do not. The radius is defined as the phylogenetic

distance of the search space when moving a node to a more optimal position. As the phylogeny

increases in size, the distance from a node to its optimal position is likely to also increase, necessitating

a larger SPR move radius to make equivalent improvements in larger trees. Second, large clades

consisting primarily of samples with branch length zero might further reduce the ability of optimization

methods to find improvements by indirectly limiting search space due to the increased number of edges

when represented internally as a bifurcating tree. It may sometimes be possible to explore moves across

such tree regions during online phylogenetics in early iterations when the polytomy is relatively small.

Third, online phylogenetics facilitates tree optimization by providing an exceptionally good initial tree that

has already been heavily optimized in previous iterations. We expect that this approach will typically

outperform parsimony and neighbor-joining initial trees that are used in most *de novo* phylogenetic

inference approaches. Finally, because each online experiment began with a small tree inferred *de novo*

by stepwise sample addition with UShER, it is possible that these initial trees are more optimal than initial

trees produced during *de novo* inference by the other software we evaluated, perhaps because UShER

prefers the reference nucleotide in cases of ambiguous internal character states.

Figure 2: Online matOptimize produces phylogenies most similar to ground truth on simulated

data. *For each batch of samples, we calculated the Robinson-Foulds distance between the tree*

produced by a given optimization software and the ground truth tree pruned to contain only the relevant

samples. We then normalized these values by the maximum possible Robinson-Foulds distance

between the two trees (see Figure S3), which is equal to 2n-6 where n equals the number of samples in

each tree (Steel and Penny 1993). We terminated FastTree and IQ-TREE after the first phylogeny that

took more than 24 hours to optimize.

Analyses using real data suggest that online phylogenetics is more efficient than *de novo* and
produces similarly optimal phylogenies.

While analyses using simulated data offer the ability to compare to a known ground truth, assessing the performance of each method on real SARS-CoV-2 data may more accurately reflect practical use of each method. Therefore, we also tested each optimization strategy on 50 progressively larger sets of real SARS-CoV-2 samples and calculated the parsimony score and likelihood of each optimized tree, as well as the run-time and peak RAM usage of each software package used (Fig. 3). To accomplish this, we subsampled our global phylogeny, which was produced using stringent quality control steps (see Methods), as before, to mimic the continuous accumulation of samples over the course of the pandemic.

Online optimizations are generally much faster than *de novo* phylogenetic inference. For example, IQ-TREE 2 achieves a roughly four-fold faster run-time for online optimizations compared to inferring the tree *de novo* (Fig. 3c). The 11th iteration, which has 47,819 sequences and was the last to be completed by both online and *de novo* IQ-TREE 2, took 22 hours 50 minutes for *de novo* IQ-TREE 2 but only 5 hours 26 minutes for online IQ-TREE 2. *De novo* UShER+matOptimize was the only *de novo* method to finish all trees in fewer than 24 hours, but its speed for each daily update pales in comparison to online matOptimize. Online matOptimize is several orders of magnitude faster than its *de novo* counterpart, and its optimizations for the largest phylogenies take roughly 30 seconds, while *de novo* tree inference with UShER can take several hours for trees consisting of more than 100,000 samples (Fig. 3c). However, whether a software package is used for online or *de novo* phylogenetics does not strongly affect its peak memory usage.

We also found that online phylogenetics strategies produce trees very similar in both parsimony score and likelihood to their *de novo* counterparts, with differences of less than 1% in all cases (Fig. 3a-b). For example, in the 11th iteration containing 47,819 sequences, online IQ-TREE 2 produces a tree with a parsimony score of 32,005, whereas *de novo* IQ-TREE 2 produces a tree with parsimony score 32,149. Our results suggest that in addition to the computational savings that allow online phylogenetics

approaches to continuously stay up-to-date, online phylogenetics approaches also produce trees with

similar parsimony scores and likelihoods to their *de novo* counterparts.

Under pandemic time constraints, parsimony-based optimization methods have favorable metrics

compared to ML methods for SARS-CoV-2 phylogenies.

In the case of both *de novo* and online phylogenetics, the parsimony-based matOptimize

outperforms both FastTree 2 and IQ-TREE 2 in runtime and peak memory usage. For the sixth iteration

(26,486 samples), which was the largest phylogeny inferred by all online methods in under 24 hours and

using under 200 GB of RAM, online FastTree 2 required nearly 24 hours and 30.3 GB of RAM, and

online IQ-TREE 2 required 1 hour 45 minutes and 72 GB of RAM. By contrast, matOptimize used only 6

seconds and 0.15 GB of RAM. This iteration contained roughly 10% as many samples as the 50th and

final iteration (233,326 total samples), which online matOptimize completed in 32 seconds using 1.41 GB

of RAM at peak usage. Even this largest tree represents only a very small fraction of the more than 10

million currently available SARS-CoV-2 genomes, indicating that, among the approaches we evaluated,

matOptimize is the only viable option for maintaining a comprehensive SARS-CoV-2 phylogeny via

online phylogenetics.

In addition to its scalability, matOptimize outperforms ML optimization methods under 24-hour

time constraints in both the parsimony and likelihood scores of the trees that it infers. For the sixth

iteration (26,486 samples), we found parsimony scores of 16,130, 16,179, and 16,290 for online

matOptimize, IQ-TREE 2, and FastTree 2 respectively. While all methods produce phylogenies with

parsimony scores within 1% of each other, matOptimize is consistently the lowest. However,

matOptimize was developed to optimize by parsimony, while the other methods were developed for ML

optimizations. Unexpectedly, we found log-likelihood scores of -233,414.277, -233,945.528, and -

235,177.396 for matOptimize, IQ-TREE 2, and FastTree 2 respectively, indicating that matOptimize

produces preferable phylogenies based on likelihood as well. We used a Jukes-Cantor (JC) model to

calculate likelihoods due to time constraints in calculation for more complex substitution models, but a

Generalised Time Reversible (GTR) model with specified rate parameters produced strongly correlated

likelihoods (Fig. S1). Specifically, we fit a generalized linear model using a Gamma family (inverse link

function) to predict the likelihood of the tree under the JC model using the iteration of tree construction

and the GTR likelihood as predictors. We examined the six trees from the first and second iteration (12 in

total). We found that the GTR likelihood was significantly correlated with the JC likelihood ($p < 2.27 \times 10^{-5}$).

Parsimony optimization produces comparable or more favorable SARS-CoV-2 trees than the most

thorough maximum likelihood methods.

We also compared the performance of *de novo* inference with UShER+matOptimize to state-of-

the-art methods without a 24-hour limit on runtime. In three iterations of increasing size (~4.5k, ~8.9k,

and ~13.2k samples), we inferred trees from real and simulated data using UShER+matOptimize, IQ-

TREE 2 with stochastic search enabled, and RAxML-NG. With the parameters used here, IQ-TREE 2

performs stochastic NNI moves in addition to hill-climbing NNI. RAxML-NG is a maximum likelihood

approach that uses SPR moves to search tree-space for higher likelihood phylogenies (Kozlov et al.

2019). We allowed each experiment to run for up to two weeks. All programs completed successfully on

the first iteration. RAxML-NG did not terminate within two weeks for the second and third iterations. On

real data, we found that UShER+matOptimize produced trees with higher log-likelihoods than IQ-TREE 2

and RAxML-NG across all three iterations (Fig. 4A). Under the substitution model parameters estimated

by IQ-TREE 2, the log-likelihoods for the first iteration were -73780.756, -73828.271, and -73782.289 for

UShER+matOptimize, IQ-TREE 2, and RAxML-NG respectively. Under the parameters estimated by

RAxML-NG, the log-likelihoods for the first iteration were -73754.894, -73801.935, and -73756.246 for

UShER+matOptimize, IQ-TREE 2, and RAxML-NG respectively. On simulated data,

UShER+matOptimize produced trees closer to the ground truth than the other methods when measured

by quartet distance across all three iterations (Fig. 4B). By RF distance, the UShER+matOptimize trees

were closest to the ground truth for the second and third iterations, but the RAxML-NG tree was closest

to ground truth in the first iteration (Fig. 4C). We therefore conclude that parsimony-based tree inference

can perform equivalently or better than state of the art maximum likelihood approaches but do this in a

tiny fraction of the time, making it by far the most suitable approach for pandemic-scale phylogenetics of

SARS-CoV-2.

 Figure 3: In practice, optimization by parsimony is more effective for SARS-CoV-2 data than

 optimization by ML. *We calculated (A) the parsimony score for each tree using matUtils, (B) the log-*

 likelihood of each tree using IQ-TREE 2, (C) runtime and (D) peak memory usage of each optimization.

 (A) and (B) are normalized by the value obtained for the matOptimize online approach such that all other

 methods are expressed as a ratio. Strategies that surpassed 24 hours (C) or the allowable RAM usage

 (D) were terminated prior. In most cases, with the notable exception of FastTree 2, online phylogenetics

 (solid lines) perform better than de novo phylogenetics (dashed lines). We ran all matOptimize analyses

 using an instance with 15 CPUs and 117.2 GB of RAM, and we ran all IQ-TREE 2 and FastTree 2

 analyses on an instance with 31 CPUs and 244.1 GB of RAM, but limited each command to 15 threads

 for equivalence with matOptimize.

 Figure 4: de novo matOptimize produces similar or more favorable trees compared to the most

 thorough maximum-likelihood inference program*s. We ran these methods for up to two weeks each*

 *to infer trees de novo from the three smallest iterations of real and simulated data. For real data **(A),** log-*

 likelihoods were computed under the model parameters estimated by IQ-TREE 2 at each iteration.

 Values are normalized by the value of the matOptimize approach such that all other methods are

 *expressed as a ratio. For simulated data **(B, C)**, the reported quartet distances **(B)** are similarly*

 normalized by the value of the matOptimize approach such that other methods are expressed as a ratio.

 *RF distances **(C)** are normalized by the maximum possible RF distance of 2n-6, where n is the number*

 of leaves in each tree. For all panels, the second and third iterations of RAxML-NG (which did not

 terminate within two weeks) are omitted.

Parsimony and likelihood are strongly correlated when optimizing large SARS-CoV-2

phylogenies.

While our comparisons of online and *de novo* as well as parsimony-based and ML optimizations

of cumulative pandemic-style data demonstrated practical performance, the largest trees completed by

all methods in these experiments represent only a small fraction of available SARS-CoV-2 data. It is also

crucial that we identify the optimal ways to produce a large phylogeny from already aggregated data. We

therefore evaluated phylogenetic inference methods for optimizing a tree of 364,427 SARS-CoV-2

genome sequences, without constraining methods according to time or memory requirements. We

optimized this global phylogeny using matOptimize (Ye et al. 2022), IQ-TREE 2 (Minh et al. 2020), and

FastTree 2 (Price et al. 2010). Overall, we found that matOptimize produced the tree with the lowest

parsimony score across all methods in roughly one hour (Table 1).

We found that after each of the six iterations of FastTree 2 optimization, the likelihood and

parsimony improvements are strongly linearly correlated (Fig. 5). This suggests that changes achieved

by maximizing parsimony will also optimize likelihood for SARS-CoV-2 data. That is, for extremely

densely sampled phylogenies wherein long branches are especially rare, parsimony and likelihood of

phylogenies, and tree moves to optimize either are highly correlated. However, despite the strength of

this correlation, we find an extreme disparity in practical usage when optimizing by either metric.

Parsimony-based methods are far more time- and data-efficient, and presently available ML approaches

quickly become prohibitively expensive. For example, while the 6 iterations of FastTree did result in large

improvements in both likelihood and parsimony score, the resulting tree would be out of date long before

the 10.5-day optimization had completed. Moreover, we applied matOptimize to the tree output by the

sixth iteration of FastTree, achieving a parsimony score of 293,866 (improvement of 288) in just 16

minutes, indicating that even after 10.5 days, additional optimization was still possible. This suggests

that, for the purposes of optimizing even moderately large SARS-CoV-2 trees, parsimony-based

methods should be heavily favored due to their increased efficiency.

Method	Iterations	Runtime (H:M:S)	Final Parsimony Score (Percent Change from Starting Tree)
IQ-TREE 2	2	24:30:52	294,258 (0.67)
FastTree 2	6	252:02:49	294,154 (0.71)
matOptimize	1	1:12:03	294,022 (0.75)

Table 1: We applied each of the three optimization methods to a starting tree of 364,427 SARS-CoV-2

samples, which had an initial parsimony score of 296,247. We first ran 2 iterations of IQ-TREE 2

optimization, using an SPR radius of 20 on the first and 100 on the second. We also used an SPR radius

of 10 on one iteration of matOptimize, and six iterations of pseudo-likelihood optimization using FastTree

2, which we terminated after roughly 10.5 days.

Figure 5. Improvement in likelihood and parsimony have a linear relationship for our optimized

global tree. *We optimized our initial global tree using 6 iterations of FastTree and measured the total*

parsimony and the likelihood after each, finding a linear relationship (Pearson correlation, rho = -1.0, p <

2.9×10^{-7}).

Conclusions

The SARS-CoV-2 pandemic has made phylogenetics central to efforts to combat the spread of

the virus, but has posed challenges for many commonly used phylogenetics frameworks. A major

component of this effort relies on a comprehensive, up-to-date, global phylogeny of SARS-CoV-2

genomes. However, the scale and continuous growth of the data have caused difficulties for standard *de*

novo phylogenetic methods. Here, we find that online phylogenetics methods are practical, pragmatic,

and accurate for inferring daily phylogenetic trees from a large and densely-sample virus outbreak.

One counterintuitive result is that parsimony-based optimizations outperform sufficiently efficient

ML approaches regardless of whether phylogenies are evaluated using parsimony or likelihood. This

might be a consequence of the fact that parsimony scores and likelihoods are strongly correlated across

phylogenies inferred via a range of phylogenetic approaches. The extremely short branches (Fig. S2) on

SARS-CoV-2 phylogenies mean that the probability of multiple mutations occurring at the same site on a

single branch is negligible. Stated another way, SARS-CoV-2 is approaching a "limit" where parsimony

and likelihood are nearly equivalent. In turn, because of their relative efficiency, parsimony-based

methods are able to search more of the possible tree space in the same amount of time, thereby

resulting in trees with better likelihoods and lower parsimony scores than trees optimized using currently-

available ML software packages. We emphasize that this does not bear on the relative merits of the

underlying principles of ML and MP, but instead reflects the utility of methods that have been applied

during the pandemic. Nevertheless, this observation does suggest that in some cases, MP optimization

may provide a fast and accurate starting point for ML optimization methods. Indeed, many popular

phylogenetics software, such as RAxML (Stamatakis 2014) and IQ-TREE (Minh et al. 2020) already use

stepwise-addition parsimony trees as initial trees for their optimization. Our results suggest that further

optimization of these initial trees using MP may provide benefits in speed *and* accuracy for some

datasets, even when the target is an estimate of the ML tree.

As sequencing technologies progress and become more readily available, sample sizes for

phylogenetic analyses of major pathogens and highly-studied organisms will necessarily continue to

increase. Today, SARS-CoV-2 represents an extreme with respect to the total number of samples

relative to the very short branch lengths on the phylogeny. However, the global sequencing effort during

the pandemic suggests that the public health sphere has a strong interest in the increased application of

whole-genome sequencing to study the genomic contents, evolution, and transmission history of major

and emerging human pathogens. We expect that million-sample datasets will become commonplace in

the near future. Parsimony-based methods like matOptimize show promise for huge datasets with short

branch lengths. Similarly, recently developed parsimony-based likelihood approximations may ultimately

be similarly scalable and accurate (De Maio et al. 2022). Online phylogenetics using both of these

methods will be a fruitful avenue for future development and application to accommodate these datasets.

Methods

We first developed a "global phylogeny", from which all analyses in this study were performed.

We began by downloading VCF and FASTA files corresponding to March 18, 2021 from our own daily-

updated database (McBroome et al. 2021). The VCF file contains pairwise alignments of each of the

434,063 samples to the SARS-CoV-2 reference genome. We then implemented filters, retaining only

sequences containing at least 28,000 non-N nucleotides, and fewer than two non-[ACGTN-] characters.

We used UShER to create a phylogeny from scratch using only the remaining 366,492 samples. To

remove potentially erroneous sequences, we iteratively pruned this tree of highly divergent internal

branches with branch parsimony scores greater than 30, then terminal branches with branch parsimony

scores greater than 6, until convergence, resulting in a final global phylogeny containing 364,427

samples. The branch parsimony score indicates the total number of substitutions along a branch. Similar

filters based on sequence divergence are used by existing SARS-CoV-2 phylogenetic inference

methods. For full reproducibility, files used for creating the global phylogeny can be found in

subrepository 1 on the project GitHub page (Thornlow et al. 2021b).

Following this, we tested several optimization strategies on this global phylogeny, hereafter the

"starting tree". We used matOptimize, FastTree 2, and maximum parsimony (MP) IQ-TREE 2. MP IQ-

TREE 2 uses parsimony as the optimality criterion in contrast to the maximum likelihood mode used in all

other experiments, which was infeasible on a dataset of this size. In these optimization experiments, we

used experimental versions of MP IQ-TREE 2 that allow finer control of parsimony parameters (specific

versions are listed in the supplemental Github repository). In one experiment, we used the starting tree

and its corresponding alignment and ran five iterations of MP IQ-TREE 2, varying the SPR radius from

20 to 100 in increments of 20. Experiments on a small dataset indicated that there is little or no

improvement in parsimony score beyond a radius of 100. Separately, we tested another strategy that

applied two iterations of MP IQ-TREE 2 to the starting tree, the first iteration using an SPR radius of 20

and the second using a radius of 100. Finally, we tested a strategy of six iterations of pseudo-likelihood

optimization with FastTree 2 followed by two iterations of parsimony optimization with matOptimize. The

tree produced by this strategy, hereafter the "ground truth" tree, had the highest likelihood of all the

strategies we tested. This tree (after_usher_optimized_fasttree_iter6.tree) and files for these optimization

experiments can be found in subrepository 2.

In the multifurcating ground truth tree of 364,427 samples, there are 265,289 unique (in FASTA

sequence) samples. There are 447,643 nodes in the tree. For reference, a full binary tree with the same

number of leaves has 728,853 nodes. 23,437 of the 29,903 sites in the alignment are polymorphic (they

display at least two non-ambiguous nucleotides). Homoplasies are common in these data. In the starting

tree, 19,090 sites display a mutation occurring on at least two different branches, and 4,976 sites display

a mutation occurring more than ten times in the tree.

To mimic pandemic-style phylogenetics, we separated a total of 233,326 samples from the

starting tree of 364,427 samples into 50 batches of ~5,000 by sorting according to the date of sample

collection. We then set up two frameworks for each of the three software packages (matOptimize

(commit 66ca5ff, conda version 0.4.8), maximum-likelihood IQ-TREE 2 (multicore version 2.1.3 COVID-

edition), and FastTree 2 (Double Precision version 2.1.10)). The online phylogenetics frameworks began

by using UShER to infer a small tree *de novo* from the first batch of samples, followed by alternating

steps of optimization using one of the three evaluated methods and placement of additional samples with

UShER. In *de novo* phylogenetics, we supplied each software package with an alignment corresponding

to all samples in that batch and its predecessors (or VCF for matOptimize) without a guide tree. For both

cases, each tree is larger than its predecessor by ~5,000 samples, and each tree necessarily contains all

samples in the immediately preceding tree. For FastTree 2, we used 2 rounds of subtree-prune-regraft

(SPR) moves (-spr 2), maximum SPR length of 1000 (-sprlength 1000), zero rounds of minimum

evolution nearest neighbor interchanges (-nni 0), and the Generalised Time Reversible + Gamma

(GTR+G) substitution model (-gtr -gamma). For IQ-TREE 2, we used a branch length minimum of

0.000000001 (-blmin 1e-9), zero rounds of stochastic tree search (-n 0), and the GTR+G substitution

model (-m GTR+G). With these parameters, IQ-TREE 2 constructs a starting parsimony tree and then

performs hill-climbing NNI steps to optimize likelihood, avoiding the significant time overhead of

stochastic search. We ran all matOptimize analyses using an instance with 15 CPUs and 117.2 GB of

RAM, and we ran all IQ-TREE 2 and FastTree 2 analyses on an instance with 31 CPUs and 244.1 GB of

RAM, but we limited each command to 15 threads for equivalence with matOptimize. Files for all

simulated data experiments can be found in subrepository 3.

To generate our simulated data, we used the SARS-CoV-2 reference genome (GISAID ID:

EPI_ISL_402125; GenBank ID: MN908947.3) (Shu and McCauley 2017; Sayers et al. 2021) as the root

sequence and used phastSim (De Maio et al. 2021b) to simulate according to the ground truth phylogeny

described above. Intergenic regions were evolved using phastSim using the default neutral mutation

rates estimated in ref. (De Maio et al. 2021a), with position-specific mean mutation rates sampled from a

gamma distribution with alpha=beta=4, and with 1% of the genome having a 10-fold increase mutation

rate for one specific mutation type (SARS-CoV-2 hypermutability model described in ref. (De Maio et al.

2021b)). Evolution of coding regions was simulated with the same neutral mutational distribution, with a

mean nonsynonymous/synonymous rate ratio of omega=0.48 as estimated in (Turakhia et al. 2021a),

with codon-specific omega values sampled from a gamma distribution with alpha=0.96 and beta=2.

Rates for each intergenic and coding region were not normalized in order to have the same baseline

neutral mutation rate distribution across the genome.

We repeated our iterative experiments using *de novo* and online matOptimize, IQ-TREE 2 and

FastTree 2 on this simulated alignment, using the same strategies as before. However, instead of

computing parsimony and likelihood scores, we computed the Robinson-Foulds (RF) distance (Robinson

and Foulds 1981) of each optimization to the ground truth tree, pruned to contain only the samples

belonging to that batch. To calculate each RF distance, we used the -O (collapse tree) argument in

matUtils extract (McBroome et al. 2021) and then used the dist.topo command in the *ape* package in R

(Paradis and Schliep 2019), comparing the collapsed optimized tree and the pruned, collapsed ground

truth tree at each iteration. We computed normalized RF distances as a proportion of the total possible

RF distance, which is equivalent to two times the number of samples in the trees minus six (Steel and

Penny 1993).

Eliminating the 24-hour runtime restriction, we also repeated the first three *de novo* iterative

experiments on both real and simulated data to compare UShER+matOptimize, IQ-TREE 2 with

stochastic search, and RAxML-NG. These iterations of ~4.5k, ~8.9k, and ~13.2k samples were allowed

to run for up to 14 days. For runs that did not terminate within this time (the second and third iterations of

RAxML-NG), we used the best tree inferred during the run for comparisons. We ran IQ-TREE 2 and

RAxML-NG under the GTR+G model with the smallest minimum branch length parameter that did not

cause numerical errors. To compare the trees inferred from real data, we computed log-likelihoods under

the GTR+G model for all trees, fixing the model parameters to those estimated by IQ-TREE 2 during tree

inference. We also compared the log-likelihoods of the trees under the parameters estimated by RAxML-

NG for the first iteration, but could not do so for the second and third iterations which did not terminate in

under two weeks. We allowed optimization of branch lengths during likelihood calculation. For the

UShER+matOptimize trees, before computing likelihoods, we converted the branch lengths into units of

substitutions per site by dividing each branch length by the alignment length (29,903). To compare the

trees inferred from simulated data, we computed the RF and quartet distances of each tree to the

corresponding ground truth tree described above.

Figure S1: Log-likelihoods calculated using Generalised Time Reversible (GTR) and Jukes-Cantor

(JC) models are correlated. *We calculated log-likelihoods for each de novo and online method as in*

Figure 2B using (A) GTR+G and (B) JC models, which suggest that relative performance of each method

is consistent across models, and significantly correlated with each other. All values are normalized by the

value obtained for the matOptimize online approach, such that other methods are expressed as a ratio.

Figure S2: Most branches in the ground truth phylogeny are extremely short. *In our optimized*

global SARS-CoV-2 phylogeny, the majority of branch lengths are zero. This low amount of divergence

yields many identical nodes in the tree and demonstrates that the probability of observing multiple

mutations at a single site along the same branch is negligible. These characteristics may help explain the

ability of parsimony-based inference methods to outperform likelihood optimization on SARS-CoV-2 data.

Figure S3: Temporal patterns in simulated SARS-CoV-2 data may affect Robinson-Foulds (RF)

distance normalization. *The RF distances for each tree in Figure 2 are normalized against the*

maximum possible RF distance for that tree. While the raw RF distances are approximately continuously

increasing (A), they do not increase linearly with the maximum RF distance, leading to the pattern

observed in Figure 2. A potential explanation for this is the variation in sequence diversity over simulated

time. The ratio of the number of total mutations in the tree (parsimony score) to the number of samples in

the inferred trees at each iteration (B) approximates the average divergence between samples in each

tree. The initial drop in divergence per sample may contribute to the more rapid increase in RF distance

because there is less phylogenetic signal to facilitate the resolution of correct topologies. As the

divergence subsequently increases, tree inference improves before the RF distances stabilize and begin

to increase approximately linearly.

Acknowledgments: We gratefully acknowledge the authors from the originating laboratories responsible for obtaining each sample, as well as the submitting laboratories where the genome data were generated and shared, on which this research is based.

Funding: This work was supported by National Institutes of Health (R35GM128932 to R.C.D., T32HG008345 (B.T. and J.M.), F31HG010584 to B.T.), Alfred P. Sloan Foundation fellowship, University of California Office of the President Emergency COVID-19 Research Seed Funding (R00RG2456 to R.C.-D.), European Molecular Biology Laboratory (to N.D.M.), Australian Research Council (DP200103151 to R.L.), Chan-Zuckerberg Initiative grant (to R.L.), and by Eric and Wendy Schmidt by recommendation of the Schmidt Futures program.

Competing interests: R.L. worked as an advisor to GISAID from mid 2020 to late 2021. The remaining authors declare no competing interests.

References:

Annavajhala M.K., Mohri H., Wang P., Nair M., Zucker J.E., Sheng Z., Gomez-Simmonds A., Kelley A.L.,

Tagliavia M., Huang Y., Bedford T., Ho D.D., Uhlemann A.-C. 2021. A Novel and Expanding SARS-

CoV-2 Variant, B.1.526, Identified in New York. medRxiv.

Barbera P., Kozlov A.M., Czech L., Morel B., Darriba D., Flouri T., Stamatakis A. 2019. EPA-ng:

Massively Parallel Evolutionary Placement of Genetic Sequences. Syst. Biol. 68:365–369.

Berger S.A., Krompass D., Stamatakis A. 2011. Performance, accuracy, and Web server for evolutionary

placement of short sequence reads under maximum likelihood. Syst. Biol. 60:291–302.

Bluhm A., Christandl M., Gesmundo F., Klausen F.R., Mančinska L., Steffan V., França D.S., Werner

A.H. 2020. SARS-CoV-2 transmission routes from genetic data: A Danish case study. PLOS ONE.

15:e0241405.

Castillo A.E., Parra B., Tapia P., Acevedo A., Lagos J., Andrade W., Arata L., Leal G., Barra G., Tambley

C., Tognarelli J., Bustos P., Ulloa S., Fasce R., Fernández J. 2020. Phylogenetic analysis of the first

four SARS-CoV-2 cases in Chile. J. Med. Virol. 92:1562–1566.

COVID-19 Genomics UK (COG-UK) Consortium. 2020. An integrated national scale SARS-CoV-2

genomic surveillance network. Lancet Microbe. 1:e99–e100.

De Maio N., Kalaghatgi P., Turakhia Y., Corbett-Detig R., Minh B.Q., Goldman N. 2022. Maximum

likelihood pandemic-scale phylogenetics. bioRxiv.:2022.03.22.485312.

De Maio N., Walker C.R., Turakhia Y., Lanfear R., Corbett-Detig R., Goldman N. 2021a. Mutation Rates

and Selection on Synonymous Mutations in SARS-CoV-2. Genome Biol. Evol. 13.

De Maio N., Weilguny L., Walker C.R., Turakhia Y., Corbett-Detig R., Goldman N. 2021b. phastSim:

efficient simulation of sequence evolution for pandemic-scale datasets. bioRxiv.

Deng X., Gu W., Federman S., du Plessis L., Pybus O.G., Faria N.R., Wang C., Yu G., Bushnell B., Pan

C.-Y., Guevara H., Sotomayor-Gonzalez A., Zorn K., Gopez A., Servellita V., Hsu E., Miller S.,

Bedford T., Greninger A.L., Roychoudhury P., Starita L.M., Famulare M., Chu H.Y., Shendure J.,

Jerome K.R., Anderson C., Gangavarapu K., Zeller M., Spencer E., Andersen K.G., MacCannell D.,

Paden C.R., Li Y., Zhang J., Tong S., Armstrong G., Morrow S., Willis M., Matyas B.T., Mase S.,

Kasirye O., Park M., Masinde G., Chan C., Yu A.T., Chai S.J., Villarino E., Bonin B., Wadford D.A.,

Chiu C.Y. 2020. Genomic surveillance reveals multiple introductions of SARS-CoV-2 into Northern

California. Science. 369:582–587.

Felsenstein J. 1978. Cases in which Parsimony or Compatibility Methods will be Positively Misleading.

Syst. Biol. 27:401–410.

Fourment M., Claywell B.C., Dinh V., McCoy C., Matsen F.A. Iv, Darling A.E. 2018. Effective Online

Bayesian Phylogenetics via Sequential Monte Carlo with Guided Proposals. Syst. Biol. 67:490–502.

Franceschi V.B., Caldana G.D., de Menezes Mayer A., Cybis G.B., Neves C.A.M., Ferrareze P.A.G.,

Demoliner M., de Almeida P.R., Gularte J.S., Hansen A.W., Weber M.N., Fleck J.D., Zimerman R.A.,

Kmetzsch L., Spilki F.R., Thompson C.E. 2021. Genomic epidemiology of SARS-CoV-2 in Esteio,

Rio Grande do Sul, Brazil. BMC Genomics. 22:371.

Gill M.S., Lemey P., Suchard M.A., Rambaut A., Baele G. 2020. Online Bayesian Phylodynamic

Inference in BEAST with Application to Epidemic Reconstruction. Mol. Biol. Evol. 37:1832–1842.

Gonzalez-Reiche A.S., Hernandez M.M., Sullivan M.J., Ciferri B., Alshammary H., Obla A., Fabre S.,

Kleiner G., Polanco J., Khan Z., Alburquerque B., van de Guchte A., Dutta J., Francoeur N., Melo

B.S., Oussenko I., Deikus G., Soto J., Sridhar S.H., Wang Y.-C., Twyman K., Kasarskis A., Altman

D.R., Smith M., Sebra R., Aberg J., Krammer F., García-Sastre A., Luksza M., Patel G., Paniz-

Mondolfi A., Gitman M., Sordillo E.M., Simon V., van Bakel H. 2020. Introductions and early spread

of SARS-CoV-2 in the New York City area. Science. 369:297–301.

Hadfield J., Megill C., Bell S.M., Huddleston J., Potter B., Callender C., Sagulenko P., Bedford T., Neher

R.A. 2018. Nextstrain: real-time tracking of pathogen evolution. Bioinformatics. 34:4121–4123.

Hendy M.D., Penny D. 1989. A Framework for the Quantitative Study of Evolutionary Trees. Syst. Biol.

38:297–309.

Hug L.A., Baker B.J., Anantharaman K., Brown C.T., Probst A.J., Castelle C.J., Butterfield C.N.,

Hernsdorf A.W., Amano Y., Ise K., Suzuki Y., Dudek N., Relman D.A., Finstad K.M., Amundson R.,

Thomas B.C., Banfield J.F. 2016. A new view of the tree of life. Nat Microbiol. 1:16048.

Izquierdo-Carrasco F., Cazes J., Smith S.A., Stamatakis A. 2014. PUmPER: phylogenies updated

perpetually. Bioinformatics. 30:1476–1477.

Jackson B., Boni M.F., Bull M.J., Colleran A., Colquhoun R.M., Darby A.C., Haldenby S., Hill V., Lucaci

A., McCrone J.T., Nicholls S.M., O'Toole Á., Pacchiarini N., Poplawski R., Scher E., Todd F.,

Webster H.J., Whitehead M., Wierzbicki C., COVID-19 Genomics UK (COG-UK) Consortium, Loman

N.J., Connor T.R., Robertson D.L., Pybus O.G., Rambaut A. 2021. Generation and transmission of

interlineage recombinants in the SARS-CoV-2 pandemic. Cell. 184:5179–5188.e8.

Kalantar K.L., Carvalho T., de Bourcy C.F.A., Dimitrov B., Dingle G., Egger R., Han J., Holmes O.B.,

Juan Y.-F., King R., Kislyuk A., Lin M.F., Mariano M., Morse T., Reynoso L.V., Cruz D.R., Sheu J.,

Tang J., Wang J., Zhang M.A., Zhong E., Ahyong V., Lay S., Chea S., Bohl J.A., Manning J.E., Tato

C.M., DeRisi J.L. 2020. IDseq—An open source cloud-based pipeline and analysis service for

metagenomic pathogen detection and monitoring. Gigascience. 9.

Khan A., Zia T., Suleman M., Khan T., Ali S.S., Abbasi A.A., Mohammad A., Wei D.-Q. 2021. Higher

infectivity of the SARS-CoV-2 new variants is associated with K417N/T, E484K, and N501Y

mutants: An insight from structural data. J. Cell. Physiol. 236:7045–7057.

Kolaczkowski B., Thornton J.W. 2004. Performance of maximum parsimony and likelihood phylogenetics

when evolution is heterogeneous. Nature. 431:980–984.

Kozlov A.M., Darriba D., Flouri T., Morel B., Stamatakis A. 2019. RAxML-NG: a fast, scalable and user-

friendly tool for maximum likelihood phylogenetic inference. Bioinformatics. 35:4453–4455.

Lam T.T.-Y. 2020. Tracking the Genomic Footprints of SARS-CoV-2 Transmission. Trends Genet.

36:544–546.

Lanfear R., Mansfield R. 2020. roblanf/sarscov2phylo: 13-11-20. .

Li X., Giorgi E.E., Marichannegowda M.H., Foley B., Xiao C., Kong X.-P., Chen Y., Gnanakaran S.,

Korber B., Gao F. 2020. Emergence of SARS-CoV-2 through recombination and strong purifying

selection. Sci Adv. 6.

Lu J., du Plessis L., Liu Z., Hill V., Kang M., Lin H., Sun J., François S., Kraemer M.U.G., Faria N.R.,

McCrone J.T., Peng J., Xiong Q., Yuan R., Zeng L., Zhou P., Liang C., Yi L., Liu J., Xiao J., Hu J.,

Liu T., Ma W., Li W., Su J., Zheng H., Peng B., Fang S., Su W., Li K., Sun R., Bai R., Tang X., Liang

M., Quick J., Song T., Rambaut A., Loman N., Raghwani J., Pybus O.G., Ke C. 2020a. Genomic

Epidemiology of SARS-CoV-2 in Guangdong Province, China. Cell. 181:997–1003.e9.

Lu R., Zhao X., Li J., Niu P., Yang B., Wu H., Wang W., Song H., Huang B., Zhu N., Bi Y., Ma X., Zhan

F., Wang L., Hu T., Zhou H., Hu Z., Zhou W., Zhao L., Chen J., Meng Y., Wang J., Lin Y., Yuan J.,

Xie Z., Ma J., Liu W.J., Wang D., Xu W., Holmes E.C., Gao G.F., Wu G., Chen W., Shi W., Tan W.

2020b. Genomic characterisation and epidemiology of 2019 novel coronavirus: implications for virus

origins and receptor binding. Lancet. 395:565–574.

Matsen F.A., Kodner R.B., Armbrust E.V. 2010. pplacer: linear time maximum-likelihood and Bayesian

phylogenetic placement of sequences onto a fixed reference tree. BMC Bioinformatics. 11:538.

McBroome J., Thornlow B., Hinrichs A.S., Kramer A., De Maio N., Goldman N., Haussler D., Corbett-

Detig R., Turakhia Y. 2021. A Daily-Updated Database and Tools for Comprehensive SARS-CoV-2

Mutation-Annotated Trees. Mol. Biol. Evol. 38:5819–5824.

Meredith L.W., Hamilton W.L., Warne B., Houldcroft C.J., Hosmillo M., Jahun A.S., Curran M.D., Parmar

S., Caller L.G., Caddy S.L., Khokhar F.A., Yakovleva A., Hall G., Feltwell T., Forrest S., Sridhar S.,

Weekes M.P., Baker S., Brown N., Moore E., Popay A., Roddick I., Reacher M., Gouliouris T.,

Peacock S.J., Dougan G., Török M.E., Goodfellow I. 2020. Rapid implementation of SARS-CoV-2

sequencing to investigate cases of health-care associated COVID-19: a prospective genomic

surveillance study. Lancet Infect. Dis. 20:1263–1271.

Minh B.Q., Schmidt H.A., Chernomor O., Schrempf D., Woodhams M.D., von Haeseler A., Lanfear R.

2020. IQ-TREE 2: New Models and Efficient Methods for Phylogenetic Inference in the Genomic

Era. Mol. Biol. Evol. 37:1530–1534.

Moreno G.K., Braun K.M., Riemersma K.K., Martin M.A., Halfmann P.J., Crooks C.M., Prall T., Baker D.,

Baczenas J.J., Heffron A.S., Ramuta M., Khubbar M., Weiler A.M., Accola M.A., Rehrauer W.M.,

O'Connor S.L., Safdar N., Pepperell C.S., Dasu T., Bhattacharyya S., Kawaoka Y., Koelle K.,

O'Connor D.H., Friedrich T.C. 2020. Revealing fine-scale spatiotemporal differences in SARS-CoV-2

introduction and spread. Nat. Commun. 11:5558.

Paradis E., Schliep K. 2019. ape 5.0: an environment for modern phylogenetics and evolutionary

analyses in R. Bioinformatics.

Park A.K., Kim I.-H., Kim J., Kim J.-M., Kim H.M., Lee C.Y., Han M.-G., Rhie G.-E., Kwon D., Nam J.-G.,

Park Y.-J., Gwack J., Lee N.-J., Woo S., No J.S., Lee J., Ha J., Rhee J., Yoo C.-K., Kim E.-J. 2021.

Genomic Surveillance of SARS-CoV-2: Distribution of Clades in the Republic of Korea in 2020.

Osong Public Health Res Perspect. 12:37–43.

Parks D.H., Chuvochina M., Waite D.W., Rinke C., Skarshewski A., Chaumeil P.-A., Hugenholtz P. 2018.

A standardized bacterial taxonomy based on genome phylogeny substantially revises the tree of life.

Nat. Biotechnol. 36:996–1004.

Peng J., Liu J., Mann S.A., Mitchell A.M., Laurie M.T., Sunshine S., Pilarowski G., Ayscue P., Kistler A.,

Vanaerschot M., Li L.M., McGeever A., Chow E.D., Marquez C., Nakamura R., Rubio L., Chamie G.,

Jones D., Jacobo J., Rojas S., Rojas S., Tulier-Laiwa V., Black D., Martinez J., Naso J., Schwab J.,

Petersen M., Havlir D., DeRisi J., IDseq Team. 2021. Estimation of secondary household attack

rates for emergent spike L452R SARS-CoV-2 variants detected by genomic surveillance at a

community-based testing site in San Francisco. Clin. Infect. Dis.

Philippe H., Zhou Y., Brinkmann H., Rodrigue N., Delsuc F. 2005. Heterotachy and long-branch

attraction in phylogenetics. BMC Evol. Biol. 5:50.

Price M.N., Dehal P.S., Arkin A.P. 2010. FastTree 2--approximately maximum-likelihood trees for large

alignments. PLoS One. 5:e9490.

Rambaut A., Holmes E.C., O'Toole Á., Hill V., McCrone J.T., Ruis C., du Plessis L., Pybus O.G. 2020. A

dynamic nomenclature proposal for SARS-CoV-2 lineages to assist genomic epidemiology. Nature

Microbiology. 5:1403–1407.

Robinson D.F., Foulds L.R. 1981. Comparison of phylogenetic trees. Math. Biosci. 53:131–147.

Sanderson T. 2021a. taxonium: Explore very large trees in the browser. Github.

https://github.com/theosanderson/taxonium

Sanderson T. 2021b. Chronumental: time tree estimation from very large phylogenies.

bioRxiv.:2021.10.27.465994.

Sayers E.W., Cavanaugh M., Clark K., Pruitt K.D., Schoch C.L., Sherry S.T., Karsch-Mizrachi I. 2021.

GenBank. Nucleic Acids Res. 49:D92–D96.

Shu Y., McCauley J. 2017. GISAID: Global initiative on sharing all influenza data – from vision to reality.

Eurosurveillance. 22.

Skidmore P.T., Kaelin E.A., Holland L.R.A., Maqsood R. 2021. Emergence of a SARS-CoV-2 E484K

variant of interest in Arizona. medRxiv.

Stamatakis A. 2014. RAxML version 8: a tool for phylogenetic analysis and post-analysis of large

phylogenies. Bioinformatics. 30:1312–1313.

Steel M.A., Penny D. 1993. Distributions of tree comparison metrics—some new results. Syst. Biol.

Sullivan J., Swofford D.L. 2001. Should We Use Model-Based Methods for Phylogenetic Inference When

We Know That Assumptions About Among-Site Rate Variation and Nucleotide Substitution Pattern

Are Violated? Systematic Biology. 50:723–729.

Tang J.W., Toovey O.T.R., Harvey K.N., Hui D.D.S. 2021. Introduction of the South African SARS-CoV-2
variant 501Y.V2 into the UK. J. Infect. 82:e8–e10.

Tegally H., Wilkinson E., Giovanetti M., Iranzadeh A., Fonseca V., Giandhari J., Doolabh D., Pillay S.,
San E.J., Msomi N., Mlisana K., von Gottberg A., Walaza S., Allam M., Ismail A., Mohale T., Glass
A.J., Engelbrecht S., Van Zyl G., Preiser W., Petruccione F., Sigal A., Hardie D., Marais G., Hsiao
N.-Y., Korsman S., Davies M.-A., Tyers L., Mudau I., York D., Maslo C., Goedhals D., Abrahams S.,
Laguda-Akingba O., Alisoltani-Dehkordi A., Godzik A., Wibmer C.K., Sewell B.T., Lourenço J.,
Alcantara L.C.J., Kosakovsky Pond S.L., Weaver S., Martin D., Lessells R.J., Bhiman J.N.,
Williamson C., de Oliveira T. 2021. Detection of a SARS-CoV-2 variant of concern in South Africa.
Nature. 592:438–443.

Thornlow B., Hinrichs A.S., Jain M., Dhillon N., La S., Kapp J.D., Anigbogu I., Cassatt-Johnstone M.,
McBroome J., Haeussler M., Turakhia Y., Chang T., Olsen H.E., Sanford J., Stone M., Vaske O.,
Bjork I., Akeson M., Shapiro B., Haussler D., Kilpatrick A.M., Corbett-Detig R. 2021a. A new SARS-
CoV-2 lineage that shares mutations with known Variants of Concern is rejected by automated
sequence repository quality control. bioRxiv.

Thornlow B., roblanf, Corbett-Detig R., Turakhia Y., Cheng Y. 2021b. bpt26/parsimony: .

Tian F., Tong B., Sun L., Shi S., Zheng B., Wang Z., Dong X., Zheng P. 2021. Mutation N501Y in RBD of
Spike Protein Strengthens the Interaction between COVID-19 and its Receptor ACE2.
bioRxiv.:2021.02.14.431117.

Turakhia Y., Thornlow B., Hinrichs A.S., De Maio N., Gozashti L., Lanfear R., Haussler D., Corbett-Detig
R. 2021a. Ultrafast Sample placement on Existing tRees (UShER) enables real-time phylogenetics
for the SARS-CoV-2 pandemic. Nat. Genet. 53:809–816.

Turakhia Y., Thornlow B., Hinrichs A.S., Mcbroome J. 2021b. Pandemic-Scale phylogenomics reveals

elevated recombination rates in the SARS-CoV-2 spike region. bioRxiv.

Umair M., Ikram A., Salman M., Khurshid A., Alam M., Badar N., Suleman R., Tahir F., Sharif S.,

Montgomery J., Whitmer S., Klena J. 2021. Whole-genome sequencing of SARS-CoV-2 reveals the

detection of G614 variant in Pakistan. PLoS One. 16:e0248371.

Wang W., Barbetti J., Wong T., Thornlow B., Corbett-Detig R., Turakhia Y., Lanfear R., Minh B.Q. 2022.

DecentTree: Scalable Neighbour-Joining for the Genomic Era. bioRxiv.:2022.04.10.487712.

Wertheim J.O., Steel M., Sanderson M.J. 2021. Accuracy in near-perfect virus phylogenies. Syst. Biol.

Ye C., Thornlow B., Hinrichs A., Torvi D., Lanfear R., Corbett-Detig R., Turakhia Y. 2022. matOptimize: A

parallel tree optimization method enables online phylogenetics for SARS-CoV-2.

bioRxiv.:2022.01.12.475688.

741