scBERT as a Large-scale Pretrained Deep Language Model for Cell Type Annotation of Single-cell RNA-seq Data

Fan Yang[1,#], Wenchuan Wang[1,2,#], Fang Wang[1,#], Yuan Fang[1,3,4], Duyu Tang[1], Junzhou Huang[5], Hui Lu[2,6,*], Jianhua Yao[1,*]

1, AI Lab, Tencent, Shenzhen, 518000, China.

2, SJTU-Yale Joint Center for Biostatistics and Data Science, Department of Bioinformatics and Biostatistics, School of Life Science and Biotechnology, Shanghai Jiao Tong University, Shanghai, 200240, China.

3, Department of Molecular and Cellular Biology, Harvard University, Cambridge, MA 02138, USA.

4, Department of Immunology, Harvard Medical School, Boston, MA 02115, USA.

5, Department of Computer Science and Engineering, the University of Texas at Arlington, Arlington, TX 76019, USA.

6, Center for Biomedical Informatics, Shanghai Engineering Research Center for Big Data in Pediatric Precision Medicine, Shanghai Children's Hospital, Shanghai, 200240, China.

[#]These authors contributed equally: Fan Yang, Wenchuan Wang, Fang Wang.

*These authors jointly supervised this work: Hui Lu, Jianhua Yao.

Hui Lu (huilu@sjtu.edu.cn)

Jianhua Yao (jianhuayao@tencent.com)

Abstract

Annotating cell types based on the single-cell RNA-seq data is a prerequisite for researches on disease progress and tumor microenvironment. Here we show existing annotation methods typically suffer from lack of curated marker gene lists, improper handling of batch effect, and difficulty in leveraging the latent gene-gene interaction information, impairing their generalization and robustness. We developed a pre-trained deep neural network-based model scBERT (single-cell Bidirectional Encoder Representations from Transformers) to overcome the challenges. Following BERT's approach of pre-train and fine-tune, scBERT obtains a general understanding of gene-gene interaction by being pre-trained on huge amounts of unlabeled scRNA-seq data and is transferred to the cell type annotation task of unseen and user-specific scRNA-seq data for supervised fine-tuning. Extensive and rigorous benchmark studies validated the superior performance of scBERT on cell type annotation, novel cell type discovery, robustness to batch effect, and model interpretability.

Single-cell RNA sequencing (scRNA-seq) has been extensively used for the characterization of complex

tissues and organisms at single-cell level[1–3], which has revolutionized transcriptomic studies. Accurate

cell type annotation on scRNA-seq is critical for biological and medical researches[4]. Cell type annotation

methods can be categorized into three types: annotation using marker genes, correlation-based methods,

and annotation by supervised classification[5].

Cluster-then-annotate is the commonly-used manner[6] where manually curated marker genes identified

from literatures are employed to assign cell types for clusters derived from unsupervised learning[5].

However, selecting the marker genes depends on researchers' prior knowledge, and is therefore prone to

bias and errors[7]. Additionally, maker genes for interested cell types are not always available, and novel

cell types don't have marker gene sets yet. Besides, most cell types are determined by a set of genes

instead of a single marker gene[8]. Without a proper method to integrate the expression information of

multiple marker genes, it is difficult to guarantee a unified and accurate cell type assignment for each

cluster[9,10]. For example, some automatic annotation methods are built upon the hypothesis that marker

genes should have high expression in cells. However, even some well-documented marker genes do not

have high expression in all the cells in the corresponding cell types[11]. Therefore, the absence or

fluctuation of the expression of these marker genes might significantly affect the preciseness of marker-

gene-based methods.

Instead of relying on a spot of marker genes, correlation-based methods measure the correlation of gene

expression profiles between the query samples and reference dataset[5]. These methods are potentially

affected by the batch effect across platforms and experiments[12]. Although there exist batch-effect

correction methods, it's still challenging to distinguish true biological diversity from technical differences

and thus preserve important biological variations[13]. Meanwhile, the commonly-used similarity measures

(i.e. cosine similarity, Spearman's correlation, and Pearson correlation) may not be robust or efficient for

measuring the distance between two sets of high-dimensional sparse scRNA-seq data[14].

Annotation by supervised/semi-supervised classification mehods follows the classic paradigm in machine

learning (ML) that recognizes patterns in the gene expression profiles and then transfers the labels from

labeled datasets to unlabeled datasets[5]. They are widely used recently due to their robustness to noise and

variability of data, and their independence of artificially selected marker genes. Nevertheless, most of

these methods need to perform highly-variable-gene (HVG) selection and dimensionality reduction before

inputting the data into the classifier due to their limited model capacity[15–19]. However, HVGs are variable

across different batches and different datasets, hindering their generalization ability across cohorts[16].

Dimensionality reduction like PCA may lose high-dimensional information as well as gene-level

independent interpretability. Furthermore, the parameter settings of HVG selection and PCA in these

methods are far to reach a consensus and inevitably introduce artificial bias for performance evaluation[15–

19]. Given that the HVGs are selected based on the expression variance across the whole dataset where the

dominant cell types account for the most variance, there is a risk of overlooking the key genes of rare cell

types. Selecting HVGs ignores co-occurrence and biological interaction of genes (especially HVG and

non-HVG), which are useful for cell type annotation[20]. Besides, simple classifiers such as fully connected

networks couldn't efficiently capture gene-gene interactions. Therefore, a new method with improved

pattern recognition ability is required to overcome the above issues of under-fitting to large-scale datasets.

Recently, a growing number of deep learning-based methods have been applied to scRNA-seq data

analyses and achieved superior performance[21–23]. BERT (the Bidirectional Encoder Representations from

Transformers) is a state-of-the-art (SOTA) Transformer-based language representation learning model. It

has made breakthrough progress in the fields of natural language processing (NLP) due to the powerful

self-attention mechanism and long-range information integration capability introduced by Transformer

layers[24,25]. BERT's paradigm of pre-training and fine-tuning enables the use of large-scale unlabeled data

to improve the generalizability of AI model. Inspired by such exciting progress, we developed scBERT

(*single-c*ell *B*idirectional *E*ncoder *R*epresentations from *T*ransformers) model for the cell annotation task

of scRNA-seq data. Following the pre-training and fine-tuning paradigm, we validated the power of

applying self-supervised learning on large-scale unlabeled scRNA-seq data to improve the model's

generalizability and overcome the batch effect. Extensive benchmarking indicated that scBERT can

provide robust and accurate cell type annotations with gene level interpretability. To the best of our

knowledge, scBERT pioneered the application of Transformer architectures in scRNA-seq data analysis

with innovatively designed embeddings for genes.

Results

The scBERT algorithm.

The original BERT[25] proposed a revolutionary recipe that generates a generic knowledge of language by pre-training and then transferring the knowledge to downstream tasks of different configurations using fine-tuning. Following BERT's mentality and paradigm, we developed a novel and unified architecture named scBERT (Fig.1), which learns a general scRNA-seq knowledge by being pre-trained on millions of unlabelled scRNA-seq data with a variety of cell types from different sources, and assigns cell types by simply plugging in a classifier and fine-tuning the parameters supervised by reference datasets. Pre-training enables the model to learn general syntax of gene-gene interactions, which helps to remove the batch effects across datasets and improve the generalizability (Extended Data Figure 1a). Fine-tuning ensures that the output embedding for each gene encodes context information that is more relevant to the transcriptional profiles of the reference dataset. To annotate a query cell, scBERT computes the probability for the cell to be any cell type labeled in the reference dataset by mining the high-level implicit patterns (Extended Data Figure 1b). Of note, if there is no cell type to assign with high confidence, the query cell would be labeled as 'unassigned' to prevent incorrect assignment and to allow novel cell type discovery. The scBERT model has some innovative designs compared to the original BERT model to unleash the power of BERT in the cell type annotation task.

First, the embedding of BERT includes token embedding and position embedding[25]. Our design of embeddings is similar to BERT in some aspects while having unique features to leverage gene knowledge. The token embedding of the original BERT is a discrete variable (standing for a word), while the raw expression input to our model is a continuous variable (standing for the expression of a gene in a single cell) with biological and technical noise. We draw on the bag-of-words technology in the NLP[26] field to bin the expressions of genes (which could be considered as the gene transcript frequency in each cell), thus converting them to discrete values with additional benefits of the reduction of the data noise to some extent. Since shuffling the columns of our input doesn't change its meaning (like the extension of

BERT to understand tabular data with TaBERT[27]), absolute positions are meaningless for gene. Instead,

gene embeddings were obtained from the gene2vec[28] to represent the gene identity (each gene has a

unique gene2vec embedding) and could be viewed as a relative embedding[26] to capture semantic

similarity from the aspect of general co-expression. The co-expression genes retain closer representations,

and distributed representation of genes has been proved to be useful for capturing gene-gene

interactions[28]. In this way, scBERT formalizes information on the gene expressions for the Transformer

efficiently and generates single-cell specific embedding (abbr. scBERT embedding) that represents the

cell-specific expression (Extended Data Figure 1c) after pre-training.

Second, existing single-cell methods have to preprocess the raw data with selection or manipulation of

genes (i.e., HVG selection, manually selecting marker genes, and PCA) due to the limited model

capability on efficiently modeling high-dimension data[9,10,29–32]. They would unavoidably bring artificial

bias and overfitting problem, which in turn may severely impair their generalizability. Conversely,

Transformer with large receptive filed could effectively leverage the global information possessed in

scRNA-seq data and learn comprehensive global representation for each cell by unbiasedly capturing

long-range gene-gene interaction. Due to the computational complexity, the input sequence of

Transformer is limited to the length of 512, while most of the scRNA-seq data contain over 10,000 genes.

Therefore, we replaced the Transformer encoder used in BERT with Performer[33] to improve the

scalability of the model to tolerate over 16,000 gene inputs. With Performer, scBERT keeps the full gene-

level interpretation, abandons the use of HVGs and dimensionality reduction, and lets discriminative

genes and useful interaction come to the surface by themselves (Extended Data Figure 1d). Thus, scBERT

allows for the discovery of gene expression patterns and longe-range dependency for cell type annotation

in an unbiased data-driven manner. scBERT is stable and robust, instead of relying heavily on the

hyperparameter selection (Extended Data Figure 1e).

Evaluating cell type annotation robustness on intra-dataset.

We first benchmarked the performance of scBERT against comparison methods on 9 scRNA-seq datasets,

covering 17 major organs/tissues, more than 50 cell types, over 500,000 cells, and mainstream single-cell

omics technologies (i.e., Drop-seq, 10X, SMART-seq, and Sanger-Nuclei), comprehensively considering

the diversity of data size and data complexity[34] (Supplementary Table 1). For comparison, marker-gene-

based methods (SCINA, Garnett, scSorter), correlation-based methods (Seurat v4, SingleR, scmap_cell,

scmap_cluster, Cell_ID(c), Cell_ID(g)), and ML-based methods (SciBet, scNym) were used

(Supplementary Table 2). For each of the datasets, we applied the 5-fold cross-validation strategy to avoid

the influence of random results on the conclusion. scBERT surpassed the performance of comparison

methods in both accuracy and macro F1 score on most of the datasets (Fig. 2a, Extended Data Figure 2).

Among the intra-dataset, Zheng68K dataset from human peripheral blood mononuclear cells (PBMC) is

the most representative dataset for benchmarking cell type annotation methods. Due to the severe cell

type imbalance and the extremely high similarity between subtypes, even the SOTA method could not

achieve an accuracy above 0.71. The performance of scBERT with completely deletion of reported

marker genes is already on par with the best performance of existing methods (Extended Data Figure 1b),

demonstrating the superior of scBERT's pattern recognition ability on gene expressions compared with

those methods heavily depending on known marker genes. With the addition of marker genes, scBERT

could capture more comprehensive gene expression patterns constructed by marker genes. With all genes

as inputs, scBERT significantly surpassing SOTA methods with a large margin (Fig. 2b-c, Extended Data

Figure 3, Extended Data Figure4a) (scBERT F1 score=0.691, accuracy=0.759; best F1 score of other

methods=0.659, accuracy=0.704) on overall cells, and achieved the highest performance (F1 score=0.788

vs. 0.617, P-value=$9.025e^{-5}$;accuracy=0.801 vs. 0.724, P-value=$2.265e^{-5}$) for CD8+ cytotoxic T cells and

CD8+/CD45RA+ T cells that are highly similar and hard to distinguish in previous studies[35]. The results

indicated that scBERT could recognize underlying gene expression patterns and long-range gene-gene

dependency after pre-training, capture diverse feature subspace by multi-head attention and enjoy

comprehensive high-level representation of cell-type-specific global information.

Notably, the list of the top-tier methods changes across different tasks and datasets while scBERT is

always among it. For instance, the top-tier methods on inter-dataset (i.e., scNym and Seurat) performed

badly on Xin dataset in Fig.2. These uncertainties in performance reflect the limitations of the comparison

methods in their generalizability, as well as the generalization of our method across all the benchmarking

datasets.

To explore whether the number of cells of a reference dataset affects the performance of scBERT, we

constructed a series of reference datasets from the Zheng 68K dataset by uniformly subsampling it

proportionally from 10% to 90% (Fig. 2d). With only 30% cells from Zheng 68K dataset), scBERT

beated all comparison moethods, and its performance improved rapidly as reference cell number

increased.

We next tested the robustness of scBERT when the distributions of cell types were severely biased. Four

cell types from the Zheng 68K dataset (CD8+ cytotoxic T cells, CD19+ B cells, CD34+ cells,

CD8+/CD45RA+ naive cytotoxic cells) with transcriptomic similarity between each pair, were selected

for class-imbalanced tests. scBERT surpassed all comparison methods (accuracy=0.840 and F1

score=0.826). Seurat misidentifed CD8+ cytotoxic T cells to CD8+/CD45RA+ naive cytotoxic cells and

SingleR misclassified all CD19+ B cells due to their rarity, while scBERT performed the least

misclassification rate even though high similarity exists between the two cell populations (Fig. 2e,

Extended Data Figure 4b). Overall, the results indicate that scBERT is robust to class-imbalanced datasets.

Cell type annotation across cohorts and organs.

In real-world circumstances, the reference dataset and query dataset are always sourced from multiple

studies, and even different sequencing platforms, where the batch effects can lead to poor performance on

cell type annotation (Fig.3a). Here, we benchmarked scBERT and comparison methods by employing a

leave-one-dataset-out strategy with human pancreas datasets generated by distinct sequencing techniques

(Baron[36], Muraro[37], Segerstolpe[38], and Xin[39]) (Fig.3, Extended Data Figure 5). ML-based methods

(scBERT, scNym, and SciBet) achieved the best results, indicating that cell-type-specific patterns could

be discovered by pattern recognition without being affected by batch effects, while Seurat relies on

compulsive batch correction before the annotation. For cross-cohort data, scBERT achieved a superior

performance with accuracy of 0.992 compared to scNym (accuracy=0.904) with a large margin (about

10%)and outperformed other popular methods (accuracy: SciBet 0.985, Seurat 0.984, SingleR 0.987)

(Fig.3b). scBERT correctly annotated most cells (> 97%) in the Muraro dataset and over 99% in the other

three datasets, demonstrating the superb and stable performance of our method in cross-cohort tasks. In

the contrast, scNym misclassified the alpha cells as beta cell type and was confused with the beta and

delta cells (Fig.3e-f). We then used cells from different organs to benchmark the performance of scBERT

and comparison methods on cross-organ dataset. The experiment results demonstrated that scBERT is on

par with comparison methods on cross-organ task (Extended Data Figure 5b). scBERT showed its

robustness in identifying cells from different sequencing technologies, experiments, different disease

states (type 2 diabetes (T2D) and health), and even different organs.

Discovery of novel cell types.

The reference dataset may not cover all cell types present in the query dataset in most tasks. The marker-

based methods are hindered by the manually selected marker of known cell types and might be difficult to

distinguish unseen cell types, while the correlation-based methods usually force the model to assign a

novel class to a closest known class. The ML-based methods could automatically and actively detect the

novel cell types by checking the predicted probability. Besides, scBERT enjoys potential advantages.

First, the multi-head attention mechanism allows scBERT to extract information from different

representation subspaces, which might benefit for capturing the subtle difference between novel cell type

and known cell types. Second, during pre-training on large-scale diverse data set, scBERT possibly has

seen the novel cells and learnt their unique patterns. Third, Transformer with large receptive filed could

effectively learn comprehensive global representation by capturing long-range gene-gene interaction,

which may better characterize and distinguish novel cells. [41]Not surprisingly, scBERT performed the best

on novel cell types and achieved the first-class performance on the known cell types (Fig.4). CellID_cell

performed well on known cell types, while failed to discover any novel cells. SciBet and scmap_cluster is

prone to assigning "unknown" labels to those cells from known types, which greatly reduce their accuracy

of known cell type classification. Compared to SciBet and scmap_cluster, our method achieves the

superior accuracy on both the novel class (scBERT=0.329 vs. SciBet=0.174 and scmap_cluster=0.174)

and known classes (scBERT=0.942 vs. SciBet=0.784 and scmap_cluster=0.666). Taken together, these

results suggested that scBERT can correctly discover novel cell types that are not present in original

reference datasets and remain accurate prediction performance of other cell types.

Investigating scBERT model interpretability.

Existing ML methods select HVG or reduce dimension due to their simplified network architecture and

low model capacity hence destroying the gene-level interpretability. In contrast, the attention mechanism

employed in scBERT naturally provides hints for the decision-making of the model using every

individual gene.

Here, we took the Muraro dataset as an illustration and top-attention gene lists were produced for the

four kinds of pancreas islet cells, with well-studied biological functions (Fig.5a). The top-attention

genes included reported markers of specific cell types (i.e., LOXL4 for alpha cell and ADCYAP1 for

beta cell[40])(Extended Data Figure 6a). Almost all the top-attention genes except markers were

identified as differentially expressed genes using DESeq[41], as potential novel markers (Fig. 5c,

Extended Data Figure. 6b). For instance, SCD5 hasn't been reported as a cell-type-specific marker

for beta cells, but in a GWAS study, a novel loci for T2D susceptibility was fine-mapped to a coding

variant of SCD[42]. The results demonstrated that scBERT could facilitate understanding the cell type

annotated and provide some support for further biological findings.

Enrichment analysis was performed for the top 50 attention gene lists using various gene-set libraries and

the results revealed there were some interesting relationships between top enriched terms and the

corresponding cell types (Fig.5b, Supplementary Table 3-15). In particular, with the cell-type-associated

gene-set library from PanglaoDB, the top-one-enriched term for each type always hits the true cell

population. As another example, insulin secretion and AMPK signal pathway, the top-two-enriched

KEGG pathways in beta cells, are vital to beta cell function. Furthermore, the scBERT embedding is

more distinguishable for cell type annotation than the raw gene expression based on the clustering

performance (ARI: 0.95 vs. 0.87), indicating the efficiency of scBERT in learning single-cell-specific

representation, which can be used for downstream analysis (Fig.5d).

Discussion

In order to improve the generalization ability of the cell type annotation algorithm and the interpretability of individual gene importance, we developed scBERT, a deep learning model with a multi-head attention mechanism and self-supervised strategy, to learn domain-irrelevant gene expression patterns and interaction from the whole genome expression of large-scale unlabeled scRNA-seq data, transfer the general knowledge to cell type annotation task by fine-tuning, and trace back to the importance of each individual gene for model interpretability. By systematically analyzing the components of scBERT, we gain several insights of the application of Transformer in single-cell data analysis (i.e., benefit of pre-training, recognization of non-marker pattern, detection of subtle gene-gene interaction, single-cell specific embedding and hyperparameters sensitivity) (systematic analysis in Method, extended data figure 1).

scBERT surpasses the existing advanced methods on diverse benchmarks collectively involving 9 single-cell datasets, 17 major organs/tissues, more than 50 cell types, over 500,000 cells, and the mainstream single-cell omics technologies (i.e., Drop-seq, 10X, SMART-seq, and Sanger-Nuclei), indicating its generalization and robustness. Notably, we employed the accuracy, macro-F1 score, and confusion matrix as evaluation metrics for benchmarking the performance of cell type annotation methods on their classification ability for a fair comparison in this study.

To the best of our knowledge, there is currently no research on applying Transformer architectures to gene expression data analysis. The originally designed end-to-end scBERT framework with gene expression embedding and self-learning strategy has superior performance, interpretability, and generalization potential on cell type annotation task. Beyond that, scBERT can also be migrated to other tasks by simply modifying output and supervision signals. scBERT, as an effective cell type annotation tool, has been released on the platform for public usage. We hope that scBERT could improve understanding of cell-type-associated gene-gene interaction and nurture the revolution of AI paradigm in single-cell RNA-seq analysis.

Despite the above advantages, the scBERT may face potential limitations including gene expression

embedding, modeling gene interactions, and the masking strategy during the pre-training stage.

First, the token embedding of the original BERT is for discrete variable (standing for a word), while the

expression input is a continuous variable (standing for the expression of a gene in a single cell), which

may have biological and technical noise. scBERT converts them to discrete values and could thus reduce

some data noise compared with existing methods which utilize the expression values directly. However, it

sacrifices some data resolution and there is still room for optimizing the embedding of gene expression

for model input. Our approach for binning the expression may cause some resolution loss. Second, gene

interactions usually exist in the form of networks (i.e., gene regulatory networks and biological signaling

pathways)[43], and this kind of prior knowledge hasn't been explicitly incorporated in scBERT.

Aggregating information from neighbors within a graph neural network based on biological networks

may better mimic the gene-gene interaction. The idea could be applied to the single-cell analysis by

building cell-level graph using the scRNA-seq data. From this point of view, it can be foreseen that

Transformers for graph[44] may be the future development direction of scBERT[45]. Third, the efficiency of

masking during pre-training is another point worth optimizing. Current masking strategy in scBERT is

simplified with non-zero masking. With the zero-inflated input[46], the model might be inclined to output

all zeros for the reconstruction task during pre-training. Therefore, we masked the non-zero values and

calculated the loss based on the non-zero values during pre-training. However, masking only the non-zero

values may lower the utilization of the single-cell data for pre-training, due to their minority. Advanced

masking strategy tailored for single-cell data could be introduced to improve the computational efficiency

of the masking process.

For future work, we would like to explore the versatility and flexibility of scBERT in a variety of

downstream tasks (i.e., gene-gene interaction, batch correction, clustering, differential analysis in disease

conditions)[47].

Methods

The scBERT model

The scBERT model adopts the advanced paradigm of BERT and tailor the architecture to solve single cell data analysis. The connections of our model with BERT are given as follows.

First, scBERT follows BERT's revolutionary recipe to conduct self-supervised pretraining[25] and to use Transformer as the model backbone[33].

Second, our design of embeddings is similar to BERT in some aspects while having unique features to leverage gene knowledge. From this perspective, our expression embedding could be viewed as the token embedding of BERT. Since shuffling the columns of our input does not change its meaning (like the extension of BERT to understand tabular data with TaBERT[27]), absolute positions are meaningless for gene. Instead, we use gene2vec to produce gene embeddings, which could be viewed as relative embeddings[26] that capture the semantic similarity between any of two genes.

Third, Transformer with global receptive field could effectively learn global representation and long-range dependency without absolute position information, achieving excellent performance on non-sequential data (i.e., images, tables)[24,27].

Gene embedding. In NLP, the inputs of the BERT model are word embeddings, a set of real-valued vectors in a predefined vector space that represent individual words. The word embedding technology helps to better represent the text by assuring the words with similar meanings have a similar representation[47]. While from the aspect of scRNA-seq, the inputs are constituted by individual genes and a predefined vector space is in need for representing the similarity between genes. Hence we employed gene2vec[28] to specifically encode gene embeddings. In this way, the difficulty of model training is reduced, with the help of the inter-gene relationship provided by prior knowledge.

Expression embedding. In spite of the gene embedding, there is also a challenge on how to utilize the transcription level of each gene, which is actually a single continuous variable. It's worth noting that the

frequency of the word occurrence in a text is valuable information for text analysis and is often

transformed as bag-of-words by term frequency statistic analysis for downstream tasks in the area of

NLP[48]. The gene expression can also be considered as the occurrence of each gene that has already been

well-documented in a biological system. From this insight, we applied the conventionally-used term

frequency analysis method that discretizes the continuous expression variables by binning and converts

them into 200-dimensional vectors, which are used as token embedding for the scBERT model.

Model Building. The quadratic computational complexity of the BERT model with Transformer as the

basic unit does not scale very well to long sequence while the gene number of scRNA-seq can be up to

more than 20,000. To this end, a matrix decomposition version of the Transformer, Performer was

employed to enlarge the sequence length. The regular dot-product attention in Transformer is a mapping

of Q, K, V, which are encoded representations of the input *queries*, *keys*, and *values* created for each unit

respectively. The bidirectional attention matrix is formulated as:

$$Att(Q, K, V) = D^{-1}(QK^T)V, \qquad D = diag(QK^T 1_L) \qquad (1)$$

332 where $Q = W_q X, K = W_K X, V = W_V X$ are linear transformations of the input X, and W_Q, W_K, W_V are the

333 weight matrices as parameters. 1_L is the all-ones vector of length L, and $diag(\cdot)$ is a diagonal matrix with

334 the input vector as the diagonal.

335 The attention matrix in Performer is described as follows:

$$\widehat{Att}(Q, K, V) = \widehat{D}^{-1}\big(Q'((K')^T V)\big), \qquad \widehat{D} = diag\big(Q'((K')^T 1_L)\big) \qquad (2)$$

336 where $Q' = \emptyset(Q), K' = \emptyset(K)$, and the function $\emptyset(x)$ is defined as:

$$\emptyset(X) = \frac{c}{\sqrt{m}} f(\omega^T X) \qquad (3)$$

where c is a positive constant, ω is a random feature matrix, and m is the dimesionality of the matrix.

Here, we constructed our model with 6 Performer enocoder layers and 10 heads for each layer.

The model training process contains two stages: self-supervised learning on unlabeled data to get a pre-

trained model and supervised learning on the specific cell type annotation tasks to get the fine-tuned

model.

Self-supervised learning on unlabeled data. In this study, we followed the conventional self-learning

strategy of the BERT model in NLP tasks by randomly masking the input data value and making a

prediction based on the remaining inputs. Considering the dropout zeros phenominan[49], we randomly

masked the non-zero gene expression and then reconstructed the original inputs by model predictions

using the remaining genes. We ultilized cross-entropy loss as the reconstruction loss , formulated as:

$$L_{Rec} = -\sum_{i=1}^{M}\sum_{j=1}^{N} y_{i,j} \log(p_{i,j}) \qquad (4)$$

where M is the number of cells, N is the number of masked gene expression values, while $y_{i,j}$ and $p_{i,j}$ are

the true expression and predicted expression of gene j in cell i respectively. Through this self-supervised

strategy, the model can learn general deep representations of gene expression patterns on the large amount

of unlabeled data which might alleviate the efforts of the downstream fine-tuning process.

Supervised learning on specific tasks. The output of scBERT was a 200-dimension feature corresponding

to each gene and a one-dimensional convolution was applied for abstract information extraction for each

gene feature. Then a 3-layer neural network was applied as the classification head and transformed the

gene features into the probability for each cell type. Cross-entropy loss was also employed as the cell type

label prediction loss, calculated as:

$$L_{Pred} = -\sum_{i=1}^{M} z_i \log(q_i) \qquad (5)$$

where z_i and q_i indicates the ground truth cell type label and predicted label of cell i.

Datasets

Since the model training consists of two stages: self-supervised learning on unlabeled data and fine-tuning

on task-specific data, the dataset used in the two stages were collected from different sources to avoid

data leakage. In the first stage, large amounts of data without annotations were used for general pattern

learning. In the second stage, task-specific data with well-annotated cell labels were required for the

subsequential systematic benchmarking of scBERT and SOTA methods. To this end, we only included

scRNA-seq datasets that provided highly credible cell type annotation and had been cited by the majority

of the cell type annotation methods for performance evaluation.

The Panglao dataset. The Panglao dataset[50] was downloaded from the PanglaoDB website

(https://panglaodb.se/). In brief, PanglaoDB integrated 209 human single-cell datasets consisting of 74

tissues, and 1,126,580 cells that originated from different experiment sources via various platforms. In

this study, we used scRNA-seq data from PanglaoDB for first stage pre-training. No annotations or cell

labels were used at the first stage since the self-learning strategy was employed and only the genes and

their expression level were needed as inputs for the scBERT model.

Zheng68k dataset. The Zheng68k is a classic PBMC dataset by 10X CHROMIUM that is widely used for

cell type annotation performance acessment[35]. It contains about 68, 000 cells within eleven subtypes of

cells: CD8+ Cytotoxic T cells (30.3%), CD8+/CD45RA+ Naive Cytotoxic cells (24.3%), CD56+ NK

cells (12.8%), CD4+/CD25 T Reg cells (9.0%), CD19+ B cells (8.6%), CD4+/CD45RO+ Memory cells

(4.5%), CD14+ Monocyte cells (4.2%), Dendritic cells (3.1%), CD4+/CD45RA+/CD25- Naive T cells

(2.7%), CD34+ cells (0.4%), CD4+ T Helper2 cells (0.1%). Zheng68k dataset contains rare cell types and

the distribution of cell types in this dataset is imbalanced. Meanwhile, strong correlations between cell

types make it difficult to differentiate them.

Pancreas datasets. The pancreas datasets consist of Baron, Muraro, Segerstolpe, and Xin. The cell type

labels were aligned and four cell types were included. The Baron dataset was downloaded from the Gene

Expression Omnibus (GEO) (accession number: GSE84133), the protocol was inDrop[36]. The Muraro

dataset was downloaded from GEO (accession number: GSE85241), the protocol was CEL-Seq2[37]. The

Segerstolpe dataset was accessed from ArrayExpress (accession number: E-MTAB-5061), the protocol

was Smart-Seq2[38]. The Xin dataset was downloaded from GEO (accession number: GSE81608), the

protocol was SMARTer[39]. The above pancreas datasets were generated from different experiment

platforms (Supplemental Table 1).

MacParland dataset. MacParland dataset[51] from human liver tissue contains 20 hepatic cell populations

from the transcriptional profiling of 8444 cells by 10X CHROMIUM. We downloaded the data from

GEO (accession number: GSE115469) and generated the cell type annotation following the authors'

reported procedure.

Heart datasets. The heart datasets contain one large dataset[52] for pre-training and Tucker dataset[53] for

benchmarking and evaluation in the hyperparameter sensitivity analysis. The large heart dataset for pre-

training contains 451,513 cells from 11 cell types by 4 different sequencing platforms (Harvard-Nuclei,

Sanger-Nuclei, Sanger-Cells, and Sanger-CD45) and was downloaded from the website

(https://data.humancellatlas.org/explore/projects/ad98d3cd-26fb-4ee3-99c9-8a2ab085e737). The Tucker

dataset contains 287,269 cells from 11 cell types via single nuclear RNA sequencing and was downloaded

from the website (https://singlecell.broadinstitute.org/single_cell/study/SCP498/transcriptional-and-

cellular-diversity-of-the-human-heart).

Lung dataset. The lung dataset was from human lung tissue and analyzed for COVID-19 related disease

mechanism[54]. The dataset contains samples from 12 donors by 10X Genomics sequencing, and 39,778

cells from 9 cell types. The data was downloaded from the website

(https://doi.org/10.6084/m9.figshare.11981034.v1).

Human Cell Atlas dataset. The Human Cell Atlas dataset[55] contains 84,363 cells from 27 cell types

among 15 major organs (skin, esophagus, trachea, heart, spleen, common bile duct, stomach, liver, blood,

lymph node, small intestine, bladder, rectum, marrow, muscle) by HiSeq X Ten sequencing. The dataset

was downloaded from GEO (accession number: GSE159929).

Data preprocessing

408   As for the data provided in gene expression matrix format, log-normalization using a size factor of 10,

409   000 and quality control by filtering cell outliers with less than 200 genes expressed were performed on the

410   data. As for the input of scBERT, no dimension reduction or HVG selection was processed since scBERT

411   has a capacity of more than 20,000 genes as input and retains full gene-level interpretability.

Comparison methods

For benchmarking, we implemented SOTA methods from the three categories, marker-based, correlation-

based and supervised classification. Among them, SCINA, Garnett, and scSorter stand for the annotation

using marker gene databases; Seurat, SingleR, CellID, and scmap are correlation-based methods; scNym

and Scibet are the SOTA methods that conduct annotation by supervised/semi-supervised classification.

Notably, this categorization depends on how the most important process is conducted. As for marker

gene-based annotation, CellMarker database with manually curated cell-type markers using a

literature search of over 100 000 papers was applied for the marker database[56]. No manual selection

of the marker genes was included for an unbiased and fair comparison of all the methods.

scNym. scNym is a recently proposed semi-supervised learning annotation method that leverages the

unlabeled target data through training a domain adversary[57]. It requires no prior manual specification of

marker genes. It makes use of the target data by domain adaptation and achieved the SOTA performance

on several tasks. However, users have to endure the inconvenience that they must re-train the model on

each batch of the new coming data.

SciBet. Scibet is a supervised classification method that selects genes using E-test for multinomial model

building and annotates cell types for a new cell in the test set[29]. We adopted SciBet in R package for

benchmarking.

Seurat. As a popular single-cell data analysis pipeline, Seurat is widely used by biologists and clinical

experts. Seurat maps the query samples to the reference dataset in a reference-based annotation manner[58].

In this study, we adopted the implementation of the cell type annotation of Seurat V4.0 and followed the

cell type annotation tutorial provided by Seurat for benchmarking.

SingleR. SingleR is a reference-based analysis method that calculates the Spearman coefficient on

variable genes and aggregates the coefficients to score the cell for each cell type[59]. It iterates the above

process by subsampling top genes until the most closely related cell types are distinguished. The SingleR

package was applied for benchmarking.

CellID. CellID is a clustering-free multivariant statistical method for cell type annotation that performs

dimensionality reduction, evaluates gene-to-cell distance, and extracts gene signatures for cells (cell-to-

cell strategy) and groups (group-to-cell strategy)[30]. In this study, both strategies from the R package were

used for benchmarking.

scmap. scmap is a reference-based annotation method including two strategies: scmap_cluster and

scmap_cell. scmap_cluster maps individual cells from query samples to certain cell types in the reference

dataset while scmap_cell maps individual cells from query samples to individual cells in a reference

dataset[31]. Both scmap_cluster and scmap_cell perform feature selection and calculate the distance (cosin

and euclidean distance). The reference is searched for the nearest neighbors to a query cell. We used the R

package of scmap for the scmap-cluster and scmap_cell tools.

SCINA. SCINA is a typical marker gene-based annotation method that requires a list of marker genes for

different cell types and identifies the cell types based on the assumption that there exists a bimodal

distribution for each marker gene and the higher modes belong to the relevant cell type[9]. We used the

Scina package for benchmarking.

Garnett. Garnett requires a user-defined cell hierarchy of cell types and marker genes as input. Garnett

aggregates marker gene scores using term frequency-inverse document frequency transformation and uses

an elastic-net regression-based model for annotation[10]. We adopted the original R package to use the

garnet model for benchmarking.

scSorter. Scsorter employs marker genes and the HVGs for clustering and cell type annotation based on

the observation that most marker genes do not consistently preserve high expression levels in all the cells

that belong to the related cell types[32]. Here we adopted the R implement of Scsorter.

Benchmarking

To assess the performance of the annotation methods under different scenarios, 9 pairs of reference and

test datasets were generated and the performance was evaluated using scBERT and all the above methods.

The details were listed below.

Performance on intra-dataset data using cross-validation. The PBMC data from Zheng68k with high

inter-class similarity, the Pancreas datasets (Baron, Muraro, Segerstolpe, and Xin), the MacParland

dataset, the Tucker dataset, the Lung dataset,t and the Human Cell Atlas dataset were employed for

testing the performance on the intra-dataset in a 5-fold cross-validation manner. Notably, the reference

dataset in this section also refers to the training dataset for the supervised methods, including scBERT.

Performance on the inter-dataset data. To evaluate the robustness of the methods on cross-cohort data

with batch effects from different single-cell sequencing platforms, we tested the methods on four pancreas

datasets (Baron, Muraro, Segerstolpe, and Xin), taking three datasets as the training set and the remaining

one as the test set each time. Considering the difference in cell populations among these datasets, all

datasets were aligned, retaining only four kinds of pancreas islet cells (alpha cell, beta cell, delta cell, and

gamma cell) that are common in these datasets. To evaluate the robustness of the methods on cross-organ

data, we tested the methods on three major organ (esophagus, rectum an stomach) from Human Cell Atlas

dataset.

The influence of reference cell amount on the performance. The number of reference cells is prone to

influence the model performance. In this study, 10%, 30%, 50%, 70%, and 90% of the PBMC cells from

the Zheng 68K dataset were randomly selected as the reference for finetuning while the remaining as the

query samples for testing.

Class-imbalanced data tests. Following the construction method for class-imbalanced data[4], we collected

four PBMC cell types, CD19+B, CD8+Cytotoxic T, CD34+, and CD8+/CD45RA Naïve Cytoxic cells

that contain various levels of similarity across cell types from Zheng68K data. The cells of the four types

were randomly selected with the cell numbers 10000, 100, 10000, and 100 as reference data for

finetuning. As for model testing, 100 cells were randomly selected per cell type as query data.

Novel cell type detection. Human liver tissue was used to assess the unknown cell type identification.

Here we adopted MacParland dataset[51] from human liver tissues with 8,434 cells belonging to 14 cell

types. In this experiment, we took four immune cells for novel cell type simulation, which were absent

from other liver datasets. Following the schema proposed in the previous study[7], we performed leave-out

one cell type evaluation by removing one cell type from the reference dataset while keeping the cell type

groups in the query dataset. The evaluation process was iterated on each cell type. At present, there is no

unified quantitative evaluation metrics for detection of novel cell type. Some approaches compute the

accuracy by putting the novel class together with known classes, which unavoidably overwhelms the

models' accuracy for rare and novel cell types. Besides accurately detecting novel cell types, a good cell

type annotation method should maintain the ability to accurately discriminate known cell types. In this

regard, we evaluate the accuracy of novel cell type and known cell types, separately. Notably, we

employed a strict evaluation method for novel cell types with the accuracy calculated on the union set of

cells with the novel cell type label and the cells that are predicted as novel cell types.

Assessment on the necessity of self-learning. To illustrate the necessity of the self-learning process of

scBERT, the performance gain was evaluated on the model after self-learning and finetuning compared to

the model training from scratch.

Evaluation metrics. Cell type annotation performance of each method at cell-level and cell-type-level was

evaluated using the metrics of accuracy and macro F1 score, respectively. Since cell type annotation task

and cell clustering task are not equivalent, those metrics assessing the quality and distance of clusters are

excluded from this study.

Sensitivity analysis on the hyperparameters. The influence of the hyperparameters (size of the embedding

vector, the binning setting, the number of encoder layers, and the number of heads for each layer) were

systematically estimated on the heart datasets with large-scale heart dataset (451,513 cells) as the pre-

training dataset and the Tucker dataset as the evaluation dataset.

Scalability. When evaluating on the large Tucker datasets with 287,269 cells, those comparison methods

implemented in R faced severe problem in scalability due to their poor memory management. For instance,

CellID met the memory bottleneck when calculating a matrix of 50,000 × 230,000 and we made efforts to split

the matrix into pieces to avoid memory overflow. Conversely, benefiting from mini-batch sampling and the

efficient Performer encoder, scBERT could easily deal with large-scale datasets at both the pre-training and the

fine-tuning stage.

Marker genes for the marker-based comparison methods. To avoid bias introduced by marker selection, well-

documented marker lists associated with well-defined cell types from CellMarker[56] were used.

Systematic analysis of scBERT.

Pre-training versus not pre-training. Following the BERT's pre-training and fine-tuning paradigm, our

method is prone to generate an efficient encoder and provide a general embedding that better represents

the gene expression of each cell by revealing critical patterns with lower data noise. The results of

ablation study on model performance with and without pre-training (Extended Data Figure 1a) proved the

essentiality of pre-training for the model's down-streaming task (i.e., cell type annotation) with a

relatively large and significant difference in the bioinformatics field. The scBERT model extracts the

useful attention pattern on gene expressions and interactions from a large scale of various scRNA-seq

data, alleviating the efforts of the fine-tuning process on the specific downstream tasks.

Feasibility on classifying with gene expression patterns. It's well known that marker genes play a key role

in cell type annotation for marker gene-based annotation and most of the reference-based annotation.

Even some of the supervised-based methods are heavily dependent on the prior marker gene knowledge.

Among the current mainstream methods that use marker genes for classification, some methods utilize the

gene expression pattern for cell type annotation. Both kinds of methods were reported to achieve good

performance on variable cell type annotation tasks, indicating that both types of data imply discriminative

information for different cell types. To investigate the effect of marker genes and the discriminant ability

of remaining expression patterns consisting of only the non-marker genes, we conducted experiments

where marker genes were eliminated gradually, leaving the remaining expression profiles for cell type

annotation (Extended Data Figure 1b, Supplementary Table 16). The results proved that the marker genes

are important for the cell type annotation. However, in addition to the marker genes, there are still

informative gene patterns that have good distinguishing power on cell type classification. With deletion of

100% marker genes, scBERT can still efficiently learn the informative gene patterns and achieve the

performance on par with the best performance achieved by comparison methods with all marker genes on

the representative Zheng68K dataset (Extended Data Figure 1b). We also explored detected gene lists

from scBERT and other ML method (i.e., scNym) and non-ML method (i.e. Seurat) on MacParland and

Baron, respectively (Supplemental Table 17-18). Consistent with above experiment on the deletion of

markers, we could observe that ML-based methods tend to learn high-level implicit cell-type-specific

patterns (i.e. discovering some genes with high rank across cell types), whereas non-ML based methods

usually simply find differentially expressed genes using statistics analysis. The results indicated that

attention mechanism, saliency mechanism, and statistics analysis could gain complementary information

from different perspectives on mining pattern of single-cell data.

General gene embedding vs. single-cell specific embedding. Gene2vec is based on bulk data[28], which

measures the average expression of genes from tissues and is the sum of cell type-specific gene

expression weighted by cell type proportions[60]. In this regard, gene2vec maintains the general co-

expression patterns of genes but stays away from strong noise and high sparsity of single-cell sequencing.

Therefore, we utilized gene2vec as our gene embedding to represent the gene identity (each gene has a

unique gene2vec embedding) and the semantic similarity from the aspect of general co-expression pattern.

The encoder of scBERT could also learn single-cell specific embedding (we briefly call it scBERT

embedding) that represents the cell-specific expression. To illustrate the evolvement of the embedding (or

representation) during the model learning, we visualized the examples of gene2vec embedding and the

scBERT embedding in Extended Data Figure 1b. Our model could generate different representations of

the same gene for different cell inputs, while gene2vec generated all the same representation of the same

gene for different cell inputs. We observed that the scBERT embedding exhibits cell-type-specific

representation (the example representation of gene is significantly enriched in alpha cell type), which is

naturally suitable for down-streaming cell type annotation task. Furthermore, the cell-type specific

representation learns some correlation beyond gene2vec. Benefiting from the attention mechanism of the

Performer, the model could detect the subtle gene interaction patterns that can only be seen in single-cell

data after model training on scRNA-seq data (Extended Data Figure1d). It could be observed that some

genes have strong attention weights to all other genes, indicating that it plays a critical role in identifying

the implicit patterns, which is consistent with the conclusion of the detected gene lists in Supplementary

Table 17-18.

Influence of hyperparameters. A systematic investigation of the sensitivity of hyperparameters including

the number of bins, the size of scBERT embedding vector, the number of attention heads, and the number

of Performer encoder layers was performed on scBERT (Extended Data Figure 1b). First, the expression

embedding by ranking the raw expression into 7 bins is suitable for scBERT. Increasing the bin numbers

to 9 hampers the model performance, indicating that ranking the gene expression would denoise the raw

data and improve scBERT's efficiency in learning meaningful patterns. In the contrast, reducing the bin

numbers would also affect the model performance, due to the loss of gene expression information (i.e.,

blurring the relatively large gene expression difference). The above experimental results proved that the

proper design of bin number that balances the denoising and reserving expression information would

benefit the model performance. Second, the gene2vec provided an embedding of 200 dimensions and

achieved the best performance compared to other dimensions. Reduction of the dimension of scBERT

embedding vector in the latent space would impair the model's representation ability and performance

(especially when the dimension is 50). Third, the Performer with 10 attention heads is suitable for our

method. Decreasing the number of attention heads might reduce the model representation ability due to

fewer representative subspaces. Increasing the number of attention heads seems to have limited influence

on the performance. However, the over-parameterized model (with 20 attention heads) faces a risk of

over-fitting, especially when applying to small datasets. Similarly, the model performs stable with 4 and 6

of Performer encoder layers but might suffer from under-fitting or over-fitting problem when decreasing

or increasing the number of layers. Overall, the small fluctuations of the above parameters had little effect

on the performance of the model, which also verified the robustness of scBERT.

Model interpretability.

We conducted a comprehensive interpretability analysis to explore the key genes for decision-making

since scBERT models were built on the self-attention mechanism and all genes' representation remained

at the end of our workflow. The attention weights reflect the contribution of each gene and the interaction

of gene pairs. The attention weights can be obtained from equation (1) modified by replacing V with V^0,

where V^0 contains one-hot indicators for each position index. We integrated all the attention matrices into

one matrix by taking an element-wise average across all attention matrices in multi-head multi-layer

Performers. In this average attention matrix, each value $A(i, j)$ represented how much attention from gene

i was paid to gene j. In order to focus on the importance of genes to each cell, we summed the attention

matrix along with columns into an attention-sum vector, and its length is equal to the number of genes. In

this way, we could obtain the top attention genes corresponding to a specific cell type compared to other

cell types. The attention weights were visualized and the top genes were sent to Enrichr[33] for enrichment

analysis.

Enrichment analysis was performed for the top-50-attention gene lists using various gene-set libraries and

the results revealed there were some interesting relationships between top-enriched terms and the

corresponding cell types.

Statistical analysis

604   The Wilcoxon test was applied for the significance test. Cross-validation was employed in all the

605   benchmarking experiments and standard deviations were drawn in the figures. The significance was

606   calculated by wilconxon test on the paired groups. Jaccard index was used for similarity measure for the

607   detected gene lists by different methods. Adjusted Rand Index (ARI) was applied to for similarity

608   measure for clusters.

Data Availability

All data used in this study are publicly available and the usages are fully illustrated in the Method section.

The published Panglao dataset was downloaded from the PanglaoDB website (https://panglaodb.se/). The

published Zheng68k dataset was downloaded from the "Fresh 68K PBMCs" on the website

(https://support.10xgenomics.com/single-cell-gene-expression/datasets (SRP073767))[35]. The published

pancreatic datasets were downloaded from the github (https://hemberg-lab.github.io/scRNA.seq.datasets/

(Baron: GSE84133, Muraro: GSE85241, Segerstolpe: E-MTAB-5061, Xin: GSE81608))[36–39]. The

MacParland dataset was downloaded from the repository (https://www.ncbi.nlm.nih.gov/geo/

(GSE115469))[51]. The heart datasets were downloaded from the websites

(https://data.humancellatlas.org/explore/projects/ad98d3cd-26fb-4ee3-99c9-8a2ab085e737 and

https://singlecell.broadinstitute.org/single_cell/study/SCP498/transcriptional-and-cellular-diversity-of-

the-human-heart)[52,53]. The lung dataset for COVID-19 study was downloaded from the website

(https://doi.org/10.6084/m9.figshare.11981034.v1)[54]. The adult human cell atlas of 15 major organs

dataset was downloaded from the website (https://www.ncbi.nlm.nih.gov/geo/ (GSE159929))[55].

Code Availability

The source code of the preprocessing, scBERT modeling, and fintuning processes are freely available on

Github (link:https://github.com/TencentAILabHealthcare/scBERT, DOI: 10.5281/zenodo.6572672)[61]

with detailed instructions. The source codes of the other comparison methods are publicly available (web

links and package versions are listed in Supplementary Table 2).

Acknowledgements

We thank Biaobin Jiang and Yan Ji for their valuable suggestions on model building and experimental

design. We thank Tao Shen for advice on the large-scale model pre-training. H.L. was supported by the

National Key R&D Program of China [2018YFC0910500]; SJTU-Yale Collaborative Research Seed

Fund; the Neil Shen's SJTU Medical Research; Key-Area Research and F.Y. was supported by

Development Program of Guangdong Province (2021B0101420005).

Author Contributions

F.Y. and J.Y. conceived and designed the project. W.W. developed and implemented the algorithms

under the guidance of F.Y. and J.Y.. W.W. and F.W. collected the datasets. W.W., F.Y., and F.W.

conducted the experiments, data analysis and method comparison. F.Y. and W.W.completed the figures

and manuscript with the guidance of J.Y. and H.L.. Y.F. and F.W. polished the manuscript and figures.

D.T. gave suggestions on the design of transformer architecture and applying NLP technology. J.H. gave

suggestions on improving the manuscript. F.Y. and F.W. revised the figures and manuscript. All authors

reviewed and approved the manuscript. F.Y., W.W., and F.W. contributed equally.

Competing Interests

The authors declare no competing interests.

Figure Legends

Figure 1. Overview of the scBERT model.
a, Self-supervised learning on unlabeled data and fine-tuning on task-specific data. At the self-supervised
pre-training stage, unlabeled data were collected from PanglaoDB. Masked expression embedding and
gene embedding were added as input and then fed into the Performer blocks. The reconstructor was used
to generate outputs. Outputs for masked genes were used to calculate the reconstruction loss. At the
supervised fine-tuning stage, the task-specific scRNA-seq data were input into the pretrained encoder.
The output representation then passed a 1-dimensional convolution layer and a classifier to generate the
cell type prediction. $\oplus$: element-wise addition. The Performer encoder is the component that is shared
between the models used in the pre-training and fine-tuning stages. The reconstructor and the classifier
are independently and separately employed for the models during the pre-training and fine-tuning
processes.

b, Illustration of the embeddings of scBERT. The preprocessed scRNA-seq data are first converted into
discretized expression, and then the non-zero expressions are randomly masked. Taking the first gene as
an example, the gene embedding E_{G1} (represents the gene identity from gene2vec falling into the first bin)
and the expression embedding E_{B2} (represents the gene expression falling into the second bin and being
transformed to the same dimension as the E_{G1}) are summed and fed into scBERT to generate
representations for genes. The representations are then used for pre-training or finetuning.

Figure 2. Benchmarking and robustness evaluation by intra-dataset cross-validation.
a, Performance of cell type annotation methods measured by accuracy and F1 score on n=9 datasets using
5-fold cross-validation. Box plots show the median (center lines), interquartile range (hinges), and 1.5
times the interquartile range (whiskers). The accuracy of the Zheng68K, Baron, Muraro, Xin, Segerstolpe
and MacParland datasets is shown from left to right. The F1 score of these datasets is shown in Extended
Data Figure 2a. The performance of SCINA, Garnett and scSorter is shown in Extended Data Figure 2b.

The results of Tucker dataset, Lung dataset and Human Cell Atlas dataset are shown in Extended Data
Figure 2c-d.

b, t-SNE plot of the whole Zheng68K dataset (n= 68,450 cells). Left panel is colored by expert-annotated
cell types from the original research, right panel is colored by scBERT prediction results. The t-SNE plots
of the annotation of comparison methods are shown in Extended Data Figure 3.

c, Heatmaps for the confusion matrices of the cross-validation results on the Zheng68K dataset for
scBERT, Seurat and CellID_cell. The confusion matrices of other methods are included in Extended Data
Figure 4a.

d, The influence on the cell type annotation performance by splitting different proportions of the
Zheng68K dataset as the reference set for fine-tuning. The standard deviations are shown as the error bar.

e, Heatmap for the confusion matrices of scBERT of cross-validation on the imbalanced dataset
reconstructed from Zheng68K dataset. The confusion matrices of other methods are included in Extended
Data Figure 4b. The detailed reconstruction process is introduced in the method section.

Figure 3. Performance of scBERT across independent datasets generated by different single-cell sequencing technologies.

Figure 3. Performance of scBERT across independent datasets generated by different
single-cell sequencing technologies.
a, t-SNE representation of 10,220 cells from four independent datasets (Baron, Muraro, Segerstolpe, and
Xin) generated by different sequencing platforms (inDrop, CEL-Seq2, SMART-Seq2, and SMARTer).
Cells are colored by the source of datasets.

b, t-SNE representation of alpha, beta, delta, and gamma cells from four pancreas datasets colored by the
annotated cell types provided by the atlas from the original paper.

c, Comparison of accuracy and F1 score of inter-dataset cross-validation among different methods. The
lower and upper hinges denote the first and third quartiles, with the whiskers in the range of 1.5 times the
interquartile.

d, Zoomed-in plot of accuracy and F1 score of the top tier methods. The lower and upper hinges denote
the first and third quartiles, with the whiskers in the range of 1.5 times the interquartile.

e, t-SNE representation of alpha, beta, delta, and gamma cells from four pancreas datasets (left), beta cells
from Muraro dataset (middle), and alpha cells from Segerstolpe dataset (right) colored by scBERT
prediction.

f, t-SNE representation of alpha, beta, delta, and gamma cells from four pancreas datasets (left), beta cells
from Muraro dataset (middle), and alpha cells from Segerstolpe dataset (right) colored by scNym
prediction. t-SNE plots of other comparison methods are shown in Extended Data Figure 5a.

Figure 4. Identification of novel cell types.

Figure 4. Identification of novel cell types.
a, Performance of scBERT on the MacParland dataset from human liver tissue by removing alpha-beta T
cell, gamma-delta T cell, mature B cell, and plasma cell populations respectively during the scBERT
training process. The accuracy and F1 score of both novel cell types and known cell types are shown in
the boxplots. Box plot shows the median (center lines), interquartile range (hinges), and 1.5 times the
interquartile range (whiskers).

b, The confidence scores provided by scBERT for the cell types of MacParland (left), the cells with low
probability of model prediction (probability<0.5) for all known cell types are assigned as potential novel

cell types. Sankey plot comparing scBERT predictions on known and novel cell types with original cell-
type annotations for the MacParland dataset (right), where plasma cells are labeled as novel cell type
since they are unseen by the scBERT training process.

Figure 5. Model interpretability.
a, Heatmap for the attention weights provided by scBERT on Pancreas cell type annotation task. The
detailed attention estimation process is described in Method section. Top 10 genes with highest attention
weights are listed for each cell type. Complete top gene list is in Supplementary Table 3.

b, The results of enrichment analysis of the top attention genes from scBERT, with the complete
information in Supplementary Table 4-15.

c, Dotplot showing z-scores among the 10 genes receiving highest attention and the cell types. As shown
in the legend, the size and color of each dot reflect the z-score.

d, UMAP representation of alpha, beta, delta, and gamma cells from Muraro dataset colored by cell types.
Left UMAP is based on the scBERT embedding of each cell, while right UMAP is based on the raw
expression of each cell. The ARI score is calculated and shown in the plot.

References

1.   Plass, M. *et al.* Cell type atlas and lineage tree of a whole complex animal by single-cell transcriptomics. *Science (1979)* **360**, (2018).

2.   Cao, J. *et al.* The single-cell transcriptional landscape of mammalian organogenesis. *Nature 2019 566:7745* **566**, 496–502 (2019).

3.   Schaum, N. *et al.* Single-cell transcriptomics of 20 mouse organs creates a Tabula Muris. *Nature 2018 562:7727* **562**, 367–372 (2018).

4.   Zhao, X., Wu, S., Fang, N., Sun, X. & Fan, J. Evaluation of single-cell classifiers for single-cell RNA sequencing data sets. *Briefings in Bioinformatics* **21**, 1581–1595 (2020).

5.   Pasquini, G., Rojo Arias, J. E., Schäfer, P. & Busskamp, V. Automated methods for cell type annotation on scRNA-seq data. *Computational and Structural Biotechnology Journal* **19**, 961–969 (2021).

6.   Cao, Y., Wang, X. & Peng, G. SCSA: A Cell Type Annotation Tool for Single-Cell RNA-seq Data. *Frontiers in Genetics* **0**, 490 (2020).

7.   Huang, Q., Liu, Y., Du, Y. & Garmire, L. X. Evaluation of Cell Type Annotation R Packages on Single-cell RNA-seq Data. *Genomics, Proteomics & Bioinformatics* (2020) doi:10.1016/J.GPB.2020.07.004.

8.   Moffitt, J. R. *et al.* Molecular, spatial, and functional single-cell profiling of the hypothalamic preoptic region. *Science (1979)* **362**, (2018).

9.   Zhang, Z. *et al.* SCINA: A Semi-Supervised Subtyping Algorithm of Single Cells and Bulk Samples. *Genes 2019, Vol. 10, Page 531* **10**, 531 (2019).

10.   Pliner, H. A., Shendure, J. & Trapnell, C. Supervised classification enables rapid annotation of cell atlases. *Nature Methods 2019 16:10* **16**, 983–986 (2019).

11.   Grabski, I. N. & Irizarry, R. A. A PROBABILISTIC GENE EXPRESSION BARCODE FOR ANNOTATION OF CELL-TYPES FROM SINGLE CELL RNA-SEQ DATA A PREPRINT. (2020) doi:10.1101/2020.01.05.895441.

12.   Haghverdi, L., Lun, A. T. L., Morgan, M. D. & Marioni, J. C. Batch effects in single-cell RNA-sequencing data are corrected by matching mutual nearest neighbors. *Nature Biotechnology 2018 36:5* **36**, 421–427 (2018).

13.   Tran, H. T. N. *et al.* A benchmark of batch-effect correction methods for single-cell RNA sequencing data. *Genome Biology 2020 21:1* **21**, 1–32 (2020).

14.   Serra, A., Coretto, P., Fratello, M. & Tagliaferri, R. Robust and sparse correlation matrix estimation for the analysis of high-dimensional genomics data. *Bioinformatics* **34**, 625–634 (2018).

758   15.   Ma, F. & Pellegrini, M. ACTINN: automated identification of cell types in single cell
759   RNA sequencing. *Bioinformatics* **36**, 533–538 (2020).

760   16.   Alquicira-Hernandez, J., Sathe, A., Ji, H. P., Nguyen, Q. & Powell, J. E. scPred:
761   accurate supervised method for cell-type classification from single-cell RNA-seq
762   data. *Genome Biology 2019 20:1* **20**, 1–17 (2019).

763   17.   Cao, Z.-J., Wei, L., Lu, S., Yang, D.-C. & Gao, G. Searching large-scale scRNA-seq
764   databases via unbiased cell embedding with Cell BLAST. *Nature Communications
765   2020 11:1* **11**, 1–13 (2020).

766   18.   Xie, P. *et al.* SuperCT: a supervised-learning framework for enhanced
767   characterization of single-cell transcriptomic profiles. *Nucleic Acids Research* **47**,
768   e48–e48 (2019).

769   19.   Li, C. *et al.* SciBet as a portable and fast single cell type identifier. *Nature
770   Communications 2020 11:1* **11**, 1–8 (2020).

771   20.   Qiu, P. Embracing the dropouts in single-cell RNA-seq analysis. *Nature
772   Communications 2020 11:1* **11**, 1–9 (2020).

773   21.   Wang, T. *et al.* MOGONET integrates multi-omics data using graph convolutional
774   networks allowing patient classification and biomarker identification. *Nature
775   Communications 2021 12:1* **12**, 1–13 (2021).

776   22.   Wang, T. *et al.* BERMUDA: a novel deep transfer learning method for single-cell
777   RNA sequencing batch correction reveals hidden high-resolution cellular subtypes.
778   *Genome Biology 2019 20:1* **20**, 1–15 (2019).

779   23.   Menden, K. *et al.* Deep learning–based cell composition analysis from tissue
780   expression profiles. *Science Advances* **6**, (2020).

781   24.   Parmar, N. *et al.* Image Transformer. 4055–4064 Preprint at
782   https://proceedings.mlr.press/v80/parmar18a.html (2018).

783   25.   Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep
784   Bidirectional Transformers for Language Understanding. *NAACL HLT 2019 - 2019
785   Conference of the North American Chapter of the Association for Computational
786   Linguistics: Human Language Technologies - Proceedings of the Conference* **1**,
787   4171–4186 (2018).

788   26.   XLNet: Generalized Autoregressive Pretraining for Language Understanding.
789   https://proceedings.neurips.cc/paper/2019/hash/dc6a7e655d7e5840e66733e9ee
790   67cc69-Abstract.html.

791   27.   Yin, P., Neubig, G., Yih, W. & Riedel, S. TaBERT: Pretraining for Joint Understanding
792   of Textual and Tabular Data. 8413–8426 (2020) doi:10.18653/V1/2020.ACL-
793   MAIN.745.

28.   Du, J. *et al.* Gene2vec: distributed representation of genes based on co-expression.
BMC Genomics 2019 20:1 **20**, 7–15 (2019).

29.   Li, C. *et al.* SciBet as a portable and fast single cell type identifier. *Nature*
Communications 2020 11:1 **11**, 1–8 (2020).

30.   Cortal, A., Martignetti, L., Six, E. & Rausell, A. Gene signature extraction and cell
identity recognition at the single-cell level with Cell-ID. *Nature Biotechnology 2021*
39:9 **39**, 1095–1102 (2021).

31.   Kiselev, V. Y., Yiu, A. & Hemberg, M. scmap: projection of single-cell RNA-seq data
across data sets. *Nature Methods 2018 15:5* **15**, 359–362 (2018).

32.   Guo, H. & Li, J. scSorter: assigning cells to known cell types according to marker
genes. *Genome Biology 2021 22:1* **22**, 1–18 (2021).

33.   Choromanski, K. *et al.* Rethinking Attention with Performers. (2020).

34.   Abdelaal, T. *et al.* A comparison of automatic cell identification methods for single-
cell RNA sequencing data. *Genome Biology 2019 20:1* **20**, 1–19 (2019).

35.   Zheng, G. X. Y. *et al.* Massively parallel digital transcriptional profiling of single
cells. *Nature Communications 2017 8:1* **8**, 1–12 (2017).

36.   Baron, M. *et al.* A Single-Cell Transcriptomic Map of the Human and Mouse
Pancreas Reveals Inter- and Intra-cell Population Structure. *Cell Systems* **3**, 346-
360.e4 (2016).

37.   Muraro, M. J. *et al.* A Single-Cell Transcriptome Atlas of the Human Pancreas. *Cell*
Systems **3**, 385-394.e3 (2016).

38.   Segerstolpe, Å. *et al.* Single-Cell Transcriptome Profiling of Human Pancreatic Islets
in Health and Type 2 Diabetes. *Cell Metabolism* **24**, 593–607 (2016).

39.   Xin, Y. *et al.* RNA Sequencing of Single Human Islet Cells Reveals Type 2 Diabetes
Genes. *Cell Metabolism* **24**, 608–615 (2016).

40.   Nica, A. C. *et al.* Cell-type, allelic, and genetic signatures in the human pancreatic
beta cell transcriptome. *Genome Research* **23**, 1554–1562 (2013).

41.   Anders, S. & Huber, W. Differential expression analysis for sequence count data.
Nature Precedings 2010 1–1 (2010) doi:10.1038/npre.2010.4282.1.

42.   Mahajan, A. *et al.* Fine-mapping type 2 diabetes loci to single-variant resolution
using high-density imputation and islet-specific epigenome maps. *Nature Genetics*
2018 50:11 **50**, 1505–1513 (2018).

43.   Hwang, S. *et al.* HumanNet v2: human gene networks for disease research. *Nucleic*
Acids Research **47**, D573–D580 (2019).

44.   Do Transformers Really Perform Badly for Graph Representation?
829   https://proceedings.neurips.cc/paper/2021/hash/f1c1592588411002af340cbaedd
830   6fc33-Abstract.html.

831   45.   Yun, S., Jeong, M., Kim, R., Kang, J. & Kim, H. J. Graph Transformer Networks.
832   *Advances in Neural Information Processing Systems* **32**, (2019).

833   46.   McDavid, A. *et al.* Data exploration, quality control and testing in single-cell qPCR-
834   based gene expression experiments. *Bioinformatics* **29**, 461–467 (2013).

835   47.   Goldberg, Y. Neural Network Methods for Natural Language Processing.
836   *http://dx.doi.org/ 10.2200/S00762ED1V01Y201703HLT037* **10**, 1–311 (2017).

837   48.   Zhang, Y., Jin, R. & Zhou, Z.-H. Understanding bag-of-words model: a statistical
838   framework. *International Journal of Machine Learning and Cybernetics 2010 1:1* **1**,
839   43–52 (2010).

840   49.   Kharchenko, P. v, Silberstein, L. & Scadden, D. T. Bayesian approach to single-cell
841   differential expression analysis. *Nature Methods 2014 11:7* **11**, 740–742 (2014).

842   50.   Franzén, O., Gan, L.-M. & Björkegren, J. L. M. PanglaoDB: a web server for
843   exploration of mouse and human single-cell RNA sequencing data. *Database* **2019**,
844   46 (2019).

845   51.   MacParland, S. A. *et al.* Single cell RNA sequencing of human liver reveals distinct
846   intrahepatic macrophage populations. *Nature Communications 2018 9:1* **9**, 1–21
847   (2018).

848   52.   Litviňuková, M. *et al.* Cells of the adult human heart. *Nature 2020 588:7838* **588**,
849   466–472 (2020).

850   53.   Tucker, N. R. *et al.* Transcriptional and Cellular Diversity of the Human Heart.
851   *Circulation* **142**, 466–482 (2020).

852   54.   Lukassen, S. *et al.* SARS-CoV-2 receptor ACE2 and TMPRSS2 are primarily expressed
853   in bronchial transient secretory cells. *The EMBO Journal* **39**, e105114 (2020).

854   55.   He, S. *et al.* Single-cell transcriptome profiling of an adult human cell atlas of 15
855   major organs. *Genome Biology* **21**, 1–34 (2020).

856   56.   Zhang, X. *et al.* CellMarker: a manually curated resource of cell markers in human
857   and mouse. *Nucleic Acids Research* **47**, D721–D728 (2019).

858   57.   Kimmel, J. C. & Kelley, D. R. Semi-supervised adversarial neural networks for single-
859   cell classification. *Genome Research* **31**, gr.268581.120 (2021).

860   58.   Hao, Y. *et al.* Integrated analysis of multimodal single-cell data. *Cell* **184**, 3573-
861   3587.e29 (2021).

862   59.   Aran, D. *et al.* Reference-based analysis of lung single-cell sequencing reveals a
863   transitional profibrotic macrophage. *Nature Immunology 2019 20:2* **20**, 163–172
864   (2019).

865   60.   Wang, X., Park, J., Susztak, K., Zhang, N. R. & Li, M. Bulk tissue cell type
866   deconvolution with multi-subject single-cell expression reference. *Nature*
867   *Communications 2019 10:1* **10**, 1–9 (2019).

868   61.   Yang, F. et al. scBERT as a Large-scale Pretrained Deep Language Model for Cell
869   Type Annotation of Single-cell RNA-seq. *Zenodo* doi:10.5281/zenodo.6572672
870   (2022).

Figure 1

a

b

Figure 2

Figure 3

Figure 4

Figure 5