Image-based representation of massive spatial transcriptomics datasets

Stephan Preibisch[1,#], Nikos Karaiskos[2] & Nikolaus Rajewsky[2,3,4,5,#]

[1]Janelia Research Campus, Howard Hughes Medical Institute, Ashburn, VA, USA
[2]Systems Biology of Gene Regulatory Elements, Berlin Institute for Medical Systems Biology, Max Delbrück Center for Molecular Medicine in the Helmholtz Association, Berlin, Germany
[3]Humboldt-Universität zu Berlin, Institut für Biologie, 10099 Berlin, Germany
[4]DZHK (German Center for Cardiovascular Research), Partner Site Berlin, Berlin, Germany
[5]Department of Pediatric Oncology, Universitätsmedizin Charité, Berlin, Germany

[#]Correspondence: preibischs@janelia.hhmi.org, rajewsky@mdc-berlin.de

Abstract

We present STIM, an imaging-based computational framework for exploring, visualizing and processing high-throughput spatial sequencing datasets. STIM is built on the powerful, scalable ImgLib2, N5 and BigDataViewer (BDV) image data frameworks and enables novel development or transfer of existing computer vision techniques to the sequencing domain characterized by datasets with irregular measurement-spacing and arbitrary spatial resolution, such as spatial transcriptomics data generated by multiplexed targeted hybridization or spatial sequencing technologies. We illustrate STIM's capabilities by representing, interactively visualizing, 3D rendering, automatically registering and segmenting publicly available spatial sequencing data from 13 serial sections of mouse brain tissue by adapting tried-and-tested algorithms.

Main

Several recent technological breakthroughs have triggered the rapid development of numerous high-throughput spatial transcriptomics methods over the last few years. These fluorescent RNA hybridization-based[1,2] or array-based RNA capture, barcoding, and subsequent sequencing[3–8] techniques provide (typically at single-cell or subcellular resolution) molecular readouts within the native spatial context of a tissue, which is critical for understanding cellular interactions in healthy and diseased states[9]. Thus, we anticipate the production of a steeply growing number of spatial transcriptomics data sets important for basic life science as well as clinical/medical research and applications. The handling and analyses of these datasets pose several complex challenges: (a) size – spatial sequencing generates several gigabytes of data for a single tissue slice and we anticipate them to increase (b) heterogeneity – datasets greatly differ in the number of genes and transcripts

captured, their spatial resolution, and tissue architecture (c) spatial transcriptomics data are in contrast to image data usually irregularly spaced (d) three-dimensional (3D) integration – data from slices need to be integrated into a 3D molecular map (e) access and analyses – the need to easily share and interactively interrogate spatial transcriptomics data, and (f) flexibility and long-term availability – the need for open source, community-based approaches.

A growing number of methods are developed specifically to visualize and analyze spatial transcriptomics data[3,10–17] (**Supplementary Methods**). Here, we show that powerful methods from the computer vision field that have been developed by a large scientific community for decades, can alternatively be adapted to meet the challenges that spatial transcriptomics methods face. Specifically, we present the "Spatial Transcriptomics Imaging Framework" (STIM), a computational, scalable and extendable toolkit based on ImgLib2[18] that allows efficient handling, processing (including integration of 2D data into 3D molecular maps), visualization and analysis of high-throughput spatial -omics datasets. We demonstrate the power of our approach by applying STIM to spatial sequencing data from adjacent slices of mouse brain to integrate them into a 3D molecular map of the cerebellum, visualize the data and perform a simple, machine learning-based segmentation task.

Results

ImgLib2[18] defines an image as a function f that maps coordinates C in n-dimensional space R^n to a value T

$$f: C \rightarrow T, \; C \subset R^n.$$

This definition illustrates that ImgLib2 natively supports regularly as well as irregularly spaced datasets (**Supplementary Fig. 1**). Furthermore, its generic, interface-driven design imposes no constraints on dataset size (biggest currently available implementation supports 4096 petabyte), dimensionality or data type, which is highlighted by the fact that many of the largest biological image datasets ever acquired[19,20] were reconstructed using ImgLib2, the ImgLib2-backed BDV[21,22] and the N5 (zarr-compatible) file format[23]. STIM builds on these frameworks to provide fast, random and distributed read&write access, interactive visualization and efficient processing of spatial transcriptomics data. First, STIM supports re-saving input datasets from the standardized text- or comma-separated formats into an N5 container (**Fig 1a,b**) while optionally log-normalizing the data. Coordinate- and gene expression data can be loaded fast and memory-efficiently in blocks using the Imglib2-cache framework, which can be accessed as values or as rendered images (**Fig. 1b,c**). ImgLib2 provides nearest-neighbor and linear interpolation for mapping irregularly-spaced samples onto pixel grids necessary for visualization. For a more realistic rendering at arbitrary resolutions we implemented a rendering method based on Gaussian distributions (**Fig. 1, Methods, Supplementary Methods**). Spatial image filtering, also referred to as digital filtering, is an established, powerful technique to enhance certain aspects of a signal that is represented as discrete samples (e.g. an image) using mathematical operations[24]. While such

filtering is mathematically directly applicable to irregularly-spaced data, it is not widely available as efficient implementations require fast k-nearest neighbor search. To ease this barrier, we added a generic framework based on ImgLib2 using kd-trees for applying filters (e.g. Mean, Median, Gaussian) to irregularly-spaced data that can easily be extended (**Fig. 1c**). All operations are implemented virtually allowing interactive access to and rendering of the data using BDV.

We demonstrate STIM's capabilities as follows. First, STIM can be used to filter the data and smoothen it, for instance by applying a Median filter or others (**Fig. 1c**). Second, tried-and-tested image registration techniques can be used to align datasets stemming from consecutive sections of the same tissue as described below (**Fig. 1d,e**). Third, STIM offers an interactive visualization and exploration of the data through BDV in 2D and 3D, including the visualization of metadata -- such as cell type annotation -- together with gene expression in every spatial unit (**Supplementary Fig. 2, Supplementary Movie 2**). Additionally, we show that existing machine learning segmentation can be straightforward applied to spatial transcriptomics data and we highlight the applicability of existing 3D rendering methods (**Fig. 2/Supplementary Movie, Supplementary Methods**).

Figure 1: STIM applies state-of-the-art imaging techniques to store, visualize, and analyze massive amounts of spatial transcriptomics datasets. *a, Spatial transcriptomics datasets can be represented as images with the number of genes per spatial unit corresponding to a number of different colors. b, Expression and spatial data is stored in N5 containers for*

efficiency and scalability and is accessible within the provided Java and Python frameworks.
c, *STIM provides classical value access operations such as filtering irregular-spaced data,*
resulting in smoothed gene expression, or interactive rendering in 2D and 3D. ***d,*** *Schematic of*
how STIM aligns consecutive sections of spatial transcriptomics datasets. ***e,*** *Visualization of*
the spatial gene expression of three genes in four different sections of a published dataset.
Top (bottom) row: spatial gene expression profiles in the original (aligned) puck orientations.

A key example to illustrate the potential of applying computer vision techniques to
sequencing datasets, we aligned a series of consecutive brain cerebellum sections using
STIM that were published in [4] (**Fig. 2 / Supplementary Video 1**). Each of these 2D sections
contains between 12,000 and 33,000 -cells and a median of ~50 quantified molecules at
near-cellular resolution. To align the 13 sections in three dimensions we adapt an alignment
strategy originally developed for the registration of large electron and light microscopy
datasets[22,25,26]. We first apply Scale Invariant Feature Transform (SIFT)[27] in combination with
Robust Sample Consensus (RANSAC)[28] on rendered image pairs of sections (+-2 in the
z-direction, **Fig. 1d**). For each pair, we identify a set of corresponding points on a rigid 2D
transformation across an automatically selected set of genes that show high entropy in both
sections. To correctly identify as many corresponding points as possible we run SIFT
independently for each gene with a low threshold for the minimal number of required
points. RANSAC is then applied to all points again to identify those that agree on a common
transformation across genes. Next, we globally minimize the distance between all
corresponding image points across all sections, yielding a single 2D transformation for each
section (**Supplementary Methods**). In an optional refinement step, we use the Iterative
Closest Point (ICP) algorithm[29] on locations of sequenced spots rather than rendered
images, where neighboring points within a predefined radius showing most similar
expression values are assigned to be correspondences. Finally, using all ICP
correspondences, we globally solve again and identify a regularized affine transformation
model for each section that is stored in the N5 container. The resulting tissue dataset can be
rendered in 3D using STIM (**Fig. 2 / Supplementary Video 1**) and the STIM-explorer can be
used to highlight the spatial expression of interactively selected genes on the whole tissue
(**Supplementary Video 2**). Due to the robustness of SIFT, our alignment pipeline can readily
be employed for similar technologies. To further demonstrate this, we used STIM to align
serial adult mouse brain sections produced with the Visium platform (**Supplementary Fig.3**).
More generally, we anticipate STIM to process and stitch together consecutive tissue
sections from the same tissue, regardless of the underlying spatial sequencing method. This
enhances the information flow between the different sections and naturally enriches the
molecular readouts.

The alignment pipeline we developed is based on linear transformations, typically affine
transformation models regularized with rigid models. This allows the use of robust model
estimation using RANSAC, which is also able to realize if no proper alignment could be
achieved. If the alignment quality needs to be further improved, existing non-rigid

registration algorithms such as bUnwarpJ [26] can be employed. However, it is important to realize that while deformations introduced by non-rigid transformations typically do improve the alignment quality (**Supplementary Fig. 4**), it is likely to deform the sample in an unnatural way. A simple example to visualize the problem is a cone in 3D, which would be represented as circles with increasing radius along the sections (in z). Non-rigid alignment would effectively transform these circles so they show the same radius as it maximizes similarity, thus transforming the cone into a pipe. Therefore, meaningful and well-designed regularization is a necessity for employing non-rigid alignment, which has been well-studied in image analysis [34] but is, to the best of our knowledge, currently in its infancy for ST data.

Recently, several software packages for the alignment of spatial sequencing data have been developed specifically within the field of spatial transcriptomics. Probabilistic Alignment of Spatial Transcriptomics Experiments (PASTE)[30] first solves an optimal transport problem to derive a probabilistic assignment of points for pairs of consecutive slices. Based on these, a rigid transformation model is sequentially estimated for each slice. Importantly, no optimization across slices is performed, which might prove problematic once datasets increase (similar to the image stitching problem). Furthermore, the computational complexity depends cubically on the number of sequenced locations. Andersson et al. [31] relies on manual landmarks for alignment and also supports only rigid transformation models. Jones et al. [32] requires an approximate initial alignment, using for example PASTE or STIM, and applies Gaussian Process Spatial Alignment to extract warp functions for non-rigid alignment of consecutive slices, also at cubic complexity with respect to the number of sequenced locations. Our proposed alternative approaches have been tried-and-tested in image analysis for decades, work reliably and fast on multi-terabyte images while their complexity depends on the size of the rendered images, which can even be small for ST data. The complexity for transferring sequenced locations into images is equivalent to that of a kdTree lookup, which is **O(log n)**. The use of RANSAC for pairwise matching, global optimization with outlier removal across all pairwise results, as well as implementation in scalable frameworks ImgLib2 and BigDataViewer ensures that the identified alignment can be trusted and that the approach will scale to significantly larger datasets in the future.

STIM enables efficient, distributed access, processing and visualization of large-scale spatial transcriptomics datasets. Irregularly-spaced data can be spatially filtered and accessed directly as values or rendered as images. STIM thereby acts as a bridge between the fields of computer vision and genomics, which we highlight by developing an automatic workflow for the alignment of sliced spatial transcriptomics datasets. Another potential application of STIM is to perform object segmentation on subcellular, high-resolution spatial transcriptomics datasets using existing image-based machine learning solutions such as Random Forests (**Supplementary Fig. 5**) [34] or for larger future datasets StarDist[35] or CellPose[36]. We provide STIM as an extensible open source framework available on GitHub (https://github.com/PreibischLab/STIM and https://github.com/rajewsky-lab/stimwrap) with interfaces in Java, Python and on the command line. We believe that these properties of

STIM have the potential to enable the community to further unite the worlds of image analysis and genomics.

Figure 2 (Movie, submitted as Supplementary Movie 1): 3D rendering of the aligned SlideSeq dataset. *The movie shows gene calm-2 is shown in white, gene ptdgs in green, and gene mbp in red and highlights the 3D nature of the dataset after alignment when represented as an image.*

Methods

Related software

Spacemake[37] is used for processing and basic visualization only; Vitessce[10] and Loupe browser[11] are designed for visualization purposes only; Seurat[12] and squidpy[13] offer both analyzing and viewing, but 3D visualization and sections alignment are unavailable; ST Viewer[14] is tailored to datasets generated with Spatial Transcriptomics[3]; histoCAT[15] and Giotto Viewer[16] do not offer sections alignment. STUtility[17] offers a basic alignment, but requires manual registration for high-quality results.

N5 storage and normalization

STIM ingests spatial sequencing data that is stored in (compressed) text files containing locations and barcodes of sequenced spots, expression levels, and optionally cell type predictions per dataset. The current framework supports 2D and 3D coordinates, and can be readily extended. Initially, STIM re-saves the set of text-file based datasets into a common N5 container that can be accessed as one common project, e.g. the image registration pipeline can be applied to an entire or parts of a project. By default, locations and

expressions are stored with double precision and Gzip compression using a block length of 1024 for locations and a block size of 512x512 for expression values (Fig. 1b). Genes and the barcode list of each dataset together with their transformations are currently stored as metadata in the N5 container. The N5 data can be accessed in STIM/stimwrap or directly through Java and python N5 packages.

Optionally, the data can be normalized upon re-saving to N5 or at a later time. We have adopted here the standard library size normalization in log-space commonly used for scRNA-seq datasets. More specifically, if d_{ij} represents the raw count for gene i in spatial unit j, we normalize values as

$$d_{ij} \rightarrow d'_{ij} = \log_2\left(10^5 \times \frac{d_{ij}}{\sum_k d_{kj}} + 1\right)$$

where the dummy index k is used for summing over all genes within a spatial unit.

Rendering of irregularly-spaced data

Image data is typically stored in n-dimensional, integer-based cartesian coordinate systems that are natively supported by most camera chips and display devices. In contrast, spatial sequencing data consist of measurements at arbitrary, floating-point precise locations, which stem from accurately localizing sequenced locations. To render such data, they need to be mapped to an integer-based cartesian coordinate system supported by standard display devices (e.g. to a 2048x1536 pixel grid), a problem that also occurs in other dataset types such as localization-based superresolution microscopy[38] and other disciplines such as astronomy[39]. Straight-forward, fast mapping can be achieved through nearest-neighbor interpolation using kd-trees. Resulting images are effectively Voronoi-tessellations with sharp, unnatural boundaries and artificial appearance where point densities are low towards the edges (**Suppl. Fig. 6A,B**). Distance-weighted interpolation creates more natural-looking images, which, however, still contain unnatural edges as either a number of points or maximal distance for interpolation needs to be defined (**Suppl. Fig. 6C**). Large values are able to create reasonable representations in areas of high point densities, but can still produce artificial structures, especially towards the edges of the dataset (**Suppl. Fig 6D**). To overcome these issues we represent each location as a Gaussian distribution, and each pixel is rendered as the sum of all overlapping distributions, normalized by their respective weights. In order not to create hard boundaries in areas with few locations, normalization is only performed if the sum of weights is bigger than one. This mapping is fast and produces representations of the data resembling naturally-looking images that can therefore easily be processed with computer vision tools and are additionally visually pleasing (**Fig. 1, Supplementary Video 2, Supplementary Fig. 6E**).

Filtering of irregularly-spaced data

Within STIM, we implemented a framework for spatial filtering of irregularly-spaced datasets based on kd-trees. We added mean filtering, median filtering, Gaussian filtering, as well as practical filters to hide single, isolated locations and to visualize the density of locations. Adding new filters is straight-forward, and typically requires the implementation `filter.RadiusSearchFilter` class, which already provides the kd-tree search and the location to be filtered.

Such basic filtering operations can for example help to smoothen noisy spatial sequencing data, to emphasize larger structures, or to identify edges (**Fig. 1c, Supplementary Video 2**).

Pairwise SIFT registration

In order to robustly identify corresponding points between pairs of two-dimensional serial sections of spatial sequencing datasets we first employ the Scale Invariant Feature Transform (SIFT) on images of renderings of individual genes.

First, we identify a set of genes (by default 100) that are expressed in both serial sections and show the highest combined standard deviations of their expression values, thus automatically selecting genes that are likely to show patterns that are helpful to perform an alignment. The user can additionally add genes that are known to create well-structured expression renderings. Second, we compute SIFT on all pairs of genes individually, using a low minimal number of corresponding points (inliers, by default 5) on a rigid model. Finally, we perform another RANSAC consensus across the points of all genes, requiring by default at least 30 inliers. This combination of parameters was very robust in our tests and worked out of the box for SlideSeq as well as Visium datasets.

Global Optimization

In order to align more than two serial sections we first compute pairwise SIFT registrations between close-by sections (by default +-2). We then solve an optimization problem by finding a set of transformations T_V that minimize the distance between all corresponding points $C_{A,B}(g)$ of all serial sections V across all genes G by identifying [22].

$$arg\ min_{T_V} \sum_{A \epsilon V} \left(\sum_{B \epsilon V \setminus A} \left(\sum_{g \epsilon G} \left(\sum_{(a,b) \epsilon C_{A,B}(g)} \left\| R_A \overline{a} - R_B \overline{b} \right\| \right) \right) \right)$$

Finally, wrong pairs of correspondences $C_{A,B}(g)$ can be identified and removed by iteratively analyzing inconsistencies between pairwise results and the current state of the global optimization as defined by the current set of transformations T_V [26]. By default we employ rigidly regularized ($\alpha = 0.1$) affine transformation models T_V for each serial section in the

optimization process. All transformations are stored within the N5 metadata, thus all visualization tools of STIM will directly use these transformations.

ICP refinement

After global optimization based on the corresponding interest points identified by SIFT we optionally employ Iterative Closest Point (ICP) for refinement of the transformations. In contrast to the SIFT alignment step, ICP is performed on the actual coordinates of the sequenced locations. We first compute pairwise ICP's between close-by serial sections (+-2 sections) using only the expression values of genes that yielded SIFT correspondences. The basic idea of ICP is to assign nearest neighboring points as corresponding points, update the transformation based on this assignment, and iterate this procedure until convergence or a maximum number of iterations is achieved. Here, we do not simply assign nearest points to each other, but those who show the most similar expression vector in the local vicinity (by default the median distance between all sequenced locations). We optionally support RANSAC filtering on the sets of corresponding points during each ICP iteration in order to identify a consensus update vector across all neighboring points. After all pairwise ICP matchings are performed, we re-solve the global optimization problem using the corresponding points identified in the last iteration of every respective ICP run.

Data availability

All data analyzed within this work are publicly available. The datasets that were used for the alignment of mouse cerebellum sections were published in Slide-seq[4]. The 10X Visium datasets were downloaded from the 10X Genomics website.

Code availability

STIM and stimwrap are available on GitHub.

Contributions

Acknowledgements

S.P. was supported by the HFSP grant RGP0021/2018-102, MDC Berlin and HHMI Janelia. N.K. was supported by the DFG grants KA 5006/1-1 and RA 838/5-1. N.R. was supported by MDC Berlin and Charite.

Ethics declarations

Competing interests

This work is part of a larger patent application in which the authors are among the inventors. The patent application was submitted through the Technology Transfer Office of the Max-Delbrück Center (MDC), with the MDC being the patent applicant.

Bibliography

1. Lubeck, E., Coskun, A. F., Zhiyentayev, T., Ahmad, M. & Cai, L. Single-cell in situ RNA profiling by sequential hybridization. *Nat. Methods* **11**, 360–361 (2014).

2. Chen, K. H., Boettiger, A. N., Moffitt, J. R., Wang, S. & Zhuang, X. RNA imaging. Spatially resolved, highly multiplexed RNA profiling in single cells. *Science* **348**, aaa6090 (2015).

3. Ståhl, P. L. *et al.* Visualization and analysis of gene expression in tissue sections by spatial transcriptomics. *Science* **353**, 78–82 (2016).

4. Rodriques, S. G. *et al.* Slide-seq: A scalable technology for measuring genome-wide expression at high spatial resolution. *Science* **363**, 1463–1467 (2019).

5. 10X Genomics. Spatial Gene Expression - 10x Genomics. https://www.10xgenomics.com/products/spatial-gene-expression.

6. Cho, C.-S. *et al.* Microscopic examination of spatial transcriptome using Seq-Scope. *Cell* **184**, 3559-3572.e22 (2021).

7. Vickovic, S. *et al.* High-definition spatial transcriptomics for in situ tissue profiling. *Nat. Methods* **16**, 987–990 (2019).

8. Stickels, R. R. *et al.* Highly sensitive spatial transcriptomics at near-cellular resolution with Slide-seqV2. *Nat. Biotechnol.* **39**, 313–319 (2021).

9. Rao, A., Barkley, D., França, G. S. & Yanai, I. Exploring tissue architecture using spatial

transcriptomics. *Nature* **596**, 211–220 (2021).

10. Keller, M. S. *et al.* Vitessce: a framework for integrative visualization of multi-modal and spatially-resolved single-cell data. (2021) doi:10.31219/osf.io/y8thv.

11. 10X Genomics. *Loupe Browser*. (10X Genomics).

12. Hao, Y. *et al.* Integrated analysis of multimodal single-cell data. *Cell* **184**, 3573-3587.e29 (2021).

13. Palla, G. *et al.* Squidpy: a scalable framework for spatial omics analysis. *Nat. Methods* **19**, 171–178 (2022).

14. Fernández Navarro, J., Lundeberg, J. & Ståhl, P. L. ST viewer: a tool for analysis and visualization of spatial transcriptomics datasets. *Bioinformatics* **35**, 1058–1060 (2019).

15. Schapiro, D. *et al.* histoCAT: analysis of cell phenotypes and interactions in multiplex image cytometry data. *Nat. Methods* **14**, 873–876 (2017).

16. Dries, R. *et al.* Giotto: a toolbox for integrative analysis and visualization of spatial expression data. *Genome Biol.* **22**, 78 (2021).

17. Bergenstråhle, J., Larsson, L. & Lundeberg, J. Seamless integration of image and molecular analysis for spatial transcriptomics workflows. *BMC Genomics* **21**, 482 (2020).

18. Pietzsch, T., Preibisch, S., Tomancák, P. & Saalfeld, S. ImgLib2--generic image processing in Java. *Bioinformatics* **28**, 3009–3011 (2012).

19. Scheffer, L. K. *et al.* A connectome and analysis of the adult Drosophila central brain. *eLife* **9**, (2020).

20. Gao, R. *et al.* Cortical column and whole-brain imaging with molecular contrast and nanoscale resolution. *Science* **363**, (2019).

21. Pietzsch, T., Saalfeld, S., Preibisch, S. & Tomancak, P. BigDataViewer: visualization and processing for large image data sets. *Nat. Methods* **12**, 481–483 (2015).

22. Preibisch, S., Saalfeld, S. & Tomancak, P. Globally optimal stitching of tiled 3D microscopic image acquisitions. *Bioinformatics* **25**, 1463–1465 (2009).

23. GitHub - saalfeldlab/n5: Not HDF5. https://github.com/saalfeldlab/n5.

24. Oppenheim, A. V. & Schafer, R. W. *Digital Signal Processing*. 585 (Pearson, 1975).

25. Saalfeld, S., Fetter, R., Cardona, A. & Tomancak, P. Elastic volume reconstruction from series of ultra-thin microscopy sections. *Nat. Methods* **9**, 717–720 (2012).

26. Hörl, D. *et al.* BigStitcher: reconstructing high-resolution image datasets of cleared and expanded samples. *Nat. Methods* **16**, 870–874 (2019).

27. Lowe, D. G. Object recognition from local scale-invariant features. in *Proceedings of the Seventh IEEE International Conference on Computer Vision* 1150–1157 vol.2 (IEEE, 1999). doi:10.1109/ICCV.1999.790410.

28. Fischler, M. A. & Bolles, R. C. Random sample consensus: a paradigm for model fitting with applications to image analysis and automated cartography. *Commun. ACM* **24**, 381–395 (1981).

29. Arun, K. S., Huang, T. S. & Blostein, S. D. Least-squares fitting of two 3-d point sets. *IEEE Trans. Pattern Anal. Mach. Intell.* **9**, 698–700 (1987).

30. Zeira, R., Land, M., Strzalkowski, A. & Raphael, B. J. Alignment and integration of spatial transcriptomics data. *Nat. Methods* **19**, 567–575 (2022).

31. Andersson, A. *et al.* A Landmark-based Common Coordinate Framework for Spatial Transcriptomics Data. *BioRxiv* (2021) doi:10.1101/2021.11.11.468178.

32. Jones, A., Townes, F. W., Li, D. & Engelhardt, B. E. Alignment of spatial genomics and histology data using deep Gaussian processes. *BioRxiv* (2022) doi:10.1101/2022.01.10.475692.

33. Arganda-Carreras, I. *et al.* Consistent and Elastic Registration of Histological Sections

Using Vector-Spline Regularization. in *Computer vision approaches to medical image analysis* (eds. Beichel, R. R. & Sonka, M.) vol. 4241 85–95 (Springer Berlin Heidelberg, 2006).

34. Arganda-Carreras, I. *et al.* Trainable Weka Segmentation: a machine learning tool for microscopy pixel classification. *Bioinformatics* **33**, 2424–2426 (2017).

35. Schmidt, U., Weigert, M., Broaddus, C. & Myers, G. Cell Detection with Star-Convex Polygons. in *Medical Image Computing and Computer Assisted Intervention – MICCAI 2018: 21st International Conference, Granada, Spain, September 16-20, 2018, Proceedings, Part II* (eds. Frangi, A. F., Schnabel, J. A., Davatzikos, C., Alberola-López, C. & Fichtinger, G.) vol. 11071 265–273 (Springer International Publishing, 2018).

36. Stringer, C., Wang, T., Michaelos, M. & Pachitariu, M. Cellpose: a generalist algorithm for cellular segmentation. *Nat. Methods* **18**, 100–106 (2021).

37. Sztanka-Toth, T. R., Jens, M., Karaiskos, N. & Rajewsky, N. Spacemake: processing and analysis of large-scale spatial transcriptomics data. *BioRxiv* (2021) doi:10.1101/2021.11.07.467598.

38. Marin, Z. *et al.* PYMEVisualize: an open-source tool for exploring 3D super-resolution data. *Nat. Methods* **18**, 582–584 (2021).

39. Schaap, W. E. & van de Weygaert, R. Continuous Fields and Discrete Samples: Reconstruction through Delaunay Tessellations. *arXiv* (2000).