CONGA: Copy number variation genotyping in ancient genomes and low-coverage sequencing data

Arda Söylev[1*], Sevim Seda Çokoglu[2], Dilek Koptekin[3], Can Alkan[4], and Mehmet Somel[2*]

[1]*Department of Computer Engineering, Konya Food and Agriculture University, Konya, 42080, Turkey*
[2]*Department of Biology, Middle East Technical University, Ankara, 06800, Turkey*
[3]*Department of Health Informatics, Graduate School of Informatics, Middle East Technical University, Ankara, 06800, Turkey*
[4]*Department of Computer Engineering, Bilkent University, Ankara, 06800, Turkey*

[*]Corresponding authors: arda.soylev@gidatarim.edu.tr and msomel@metu.edu.tr

ABSTRACT

To date, ancient genome analyses have been largely confined to the study of single nucleotide polymorphisms (SNPs). Copy number variants (CNVs) are a major contributor of disease and of evolutionary adaptation, but identifying CNVs in ancient shotgun-sequenced genomes is hampered by (i) most published genomes being $<1\times$ coverage, (ii) ancient DNA fragments being typically <80 bps. These characteristics preclude state-of-the-art CNV detection software to be effectively applied to ancient genomes. Here we present CONGA, an algorithm tailored for genotyping deletion and duplication events in genomes with low depths of coverage. Simulations and down-sampling experiments show that CONGA can genotype deletions >1 kbps with F-scores >0.75 at $\geq 1\times$, and distinguish between heterozygous and homozygous states. Using CONGA, we analyse deletion events at 10,018 loci in 56 ancient human genomes spanning the last 50,000 years, with coverages $0.4\times$-$26\times$. We show that inter-individual genetic diversity measured using deletions and SNPs are highly correlated, as in modern-day genomes, confirming that deletion frequencies broadly reflect demographic history. We also identify signatures of strong purifying selection on deletions in ancient-genomes, such as an excess of singletons compared to those in SNPs. CONGA paves the way for systematic studies of drift, mutation load, and adaptation in ancient and modern-day gene pools through the lens of CNVs.

Keywords Genomics · ancient DNA · CNV genotyping · deletion · low coverage whole genome sequencing

Introduction

Ancient genomics, the analysis of genetic material extracted from archaeological and paleontological remains, has become a major source of information for the study of population history and evolution over the last decade (Skoglund and Mathieson, 2018; Frantz *et al.*, 2020; Shapiro and Hofreiter, 2014; Marciniak and Perry, 2017). While the number of published ancient genomes is exponentially growing, their analyses have yet been nearly exclusively limited to those of single-nucleotide polymorphisms (SNPs), while structural variations (SVs) in ancient genomes remain mostly ignored. Copy number variations (CNVs) are a common type of SVs and include deletions and duplications ranging from 50 bps to several megabasepairs. Although their number, by count, is much fewer than SNPs, the fraction of the genome affected by CNVs is well past that accounted for SNPs (Conrad *et al.*, 2010). Likewise, CNVs are a major contributor to phenotypic variation: they are frequently discovered as the basis of diverse biological adaptations (Gonzalez *et al.*, 2005; Perry *et al.*, 2007; Xue *et al.*, 2008; Chan *et al.*, 2010; McLean *et al.*, 2011; Hardwick *et al.*, 2011; Kothapalli *et al.*, 2016; Nuttle *et al.*, 2016; Hsieh *et al.*, 2019) as well as genetic diseases (reviewed in (Zhang *et al.*, 2009; Stankiewicz and Lupski, 2010; Girirajan *et al.*, 2011; Saitou and Gokcumen, 2020)). This renders the study of CNVs in ancient genomes two-fold attractive. First, as CNVs frequently serve as genetic material for adaptation, their study in ancient genomes can allow detailed temporal investigation of adaptive processes. Examples include evolutionary changes in salivary amylase copy numbers in humans and in dogs, thought to represent responses to a shift to starch-rich diets (Mathieson and Mathieson, 2018; Bergström *et al.*, 2020). Second, large deletions can be a major source of deleterious mutation load, and studying deletion frequencies in ancient genome samples from extinct species or severely

bottlenecked populations can be highly revealing about the genetic health of lineages. For instance, a study on the last surviving mammoth population on Wrangel Island reported an excess of deletions in this sample, which may have compromised the population's fitness (Rogers and Slatkin, 2017).

Despite this appeal, the impact of CNVs on evolutionary history and ancient phenotypes remains largely unexplored (Frantz *et al.*, 2020). The reason lies in the significant technical challenges in CNV detection posed by ancient genomes. State-of-the-art methods for CNV discovery from shotgun genome sequencing data require at least moderate depth of coverage (Abyzov *et al.*, 2011; Boeva *et al.*, 2012; Smith *et al.*, 2015; Alkan, 2020) and read-pair information (Rausch *et al.*, 2012; Layer *et al.*, 2014; Chen *et al.*, 2016; Eisfeldt *et al.*, 2017; Soylev *et al.*, 2017, 2019), or long reads (Chaisson *et al.*, 2015; Sedlazeck *et al.*, 2018). However, due to the degraded and elusive nature of ancient DNA, ancient genome data is frequently produced at low coverage ($<1\times$) and the molecules retrieved are typically short, between 50-80 bps. Although CNVs have been studied in a few relatively high coverage ancient genomes using CNV discovery tools (Green *et al.*, 2010; Reich *et al.*, 2010; Meyer *et al.*, 2012; Rogers and Slatkin, 2017; Bergström *et al.*, 2020), these methods are inapplicable to most ancient genome data sets, and so far, no specific algorithm for CNV identification in ancient genomes has been developed.

With the aim to fill this gap, here we present CONGA (**Co**py **N**umber Variation **G**enotyping in **A**ncient Genomes and Low-coverage Sequencing Data), a CNV genotyping algorithm tailored for ancient and other low coverage genomes, which estimates copy number beyond presence/absence of events. We use simulations and down-sampling experiments to assess CONGA's performance, and, as a sanity check, we show that deletions genotyped in low coverage ancient genomes yield signals of genetic drift and negative selection consistent with those described in present-day genomes.

Results

Motivation and overview of the algorithm

We developed CONGA to genotype given candidate CNVs in mapped read (BAM) files (Methods). The choice of CNV genotyping over CNV discovery has multiple reasons: (a) CNV discovery using low coverage ancient genomes is impractical; (b) for many species studied using ancient genomics, CNV reference sets based on high quality genomes are already available (Supplemental Note S1); (c) variants in ancient genomes will largely overlap with present-day variants in most cases; (d) genotyping has much shorter running times and lower memory usage than discovery. Indeed, although algorithms for *de novo* SNP discovery exist (Prüfer, 2018; Link *et al.*, 2017), most ancient genome studies to date have chosen genotyping known variants because of low coverage (Orlando *et al.*, 2021). It should likewise be possible to genotype CNVs in low coverage genomes with high accuracy and in short running times using depth of coverage and split-read information.

Briefly, CONGA first calculates the number of reads mapped to each given interval in the reference genome, which we call "observed read-depth". It then calculates the "expected diploid read-depth", i.e., the GC-content normalized read-depth given the genome average. Using these values, CONGA calculates the likelihood for each genotype by modeling the read-depth distribution as Poisson, similar to common CNV callers (Xie and Tammi, 2009; Chiang *et al.*, 2009; Yoon *et al.*, 2009). The genotypes can be homozygous CNV, heterozygous CNV, or no CNV. Using these likelihoods CONGA then calculates a statistic we term the C-score, defined as the likelihood of a CNV being true (in heterozygous or homozygous state) over it being false (no CNV). For genotyping duplications, CONGA also uses an additional split-read step in order to utilize paired-end information. Briefly, it splits reads and remaps the split within the genome, treating the two segments as paired-end reads (Karakoc *et al.*, 2012; Soylev *et al.*, 2019). Either type of signature, read-depth or paired-end, can be sufficient to call a duplication (Methods).

Accuracy evaluation using simulated genomes and comparison with published algorithms

To evaluate the performance of CONGA we first simulated genomes with CNVs of ancient-like characteristics. We employed VarSim (Mu *et al.*, 2015) to insert deletions and duplications into the human reference genome (GRCh37). We used three different size intervals for CNVs: small (100 bps - 1000 bps), medium (1,000 bps - 10,000 bps) and large (10,000 bps - 100,000 bps). We thus simulated three genomes, each with roughly 1,500 deletions and 1,500 duplications of a specific size range (see Supplemental Fig. S1 for the exact numbers and length distributions of CNVs inserted in each genome). We next used these genomes as input to the ancient read simulator Gargammel (Renaud *et al.*, 2017), which generates paired-end short Illumina reads with varying fragment sizes (median 66 bps) and post-mortem damage. The data was generated at various depths: $0.05\times$, $0.1\times$, $0.5\times$, $1\times$ and $5\times$ (Methods). We then used CONGA to genotype CNVs across the simulated ancient genomes, using a candidate CNV call set. In order to assess specificity and sensitivity, we also used a background (false) CNV list, prepared using published deletion and duplication calls from modern-day human long-read sequencing datasets (Audano *et al.*, 2019; Chaisson *et al.*, 2019; Zook *et al.*, 2020;

Figure 1: Overall workflow of CONGA. The first step involves initialization, where we create the input (reference) CNV file using the deletions and duplications of African populations (AFR) from Phase 3 of the 1000 Genomes Project SV call set (Sudmant *et al.*, 2015b). We apply our genotyping algorithm in the second step and create the initial CNV call set. We then perform a filtering and refining step, which is used to generate the final CNV call set.

Collins *et al.*, 2020), as well as from African populations (AFR) from Phase 3 of the 1000 Genomes Project (Sudmant *et al.*, 2015b). We mixed these false CNVs to the list of true CNVs with a ratio of approximately 10:1 (~15,000 false events vs. ~1,500 true events), and used this mixed list as the candidate CNV call set to CONGA (Methods). To assess the performance of CONGA in identifying CNVs, we further compared it with a CNV genotyping tool, GenomeSTRiP (Handsaker *et al.*, 2011, 2015), and three of the widely used CNV discovery tools: CNVnator (Abyzov *et al.*, 2011), FREEC (Boeva *et al.*, 2012) and mrCaNaVaR (Alkan *et al.*, 2009; Kahveci and Alkan, 2018; Alkan, 2020).

Table 1 shows true and false predictions by CONGA, GenomeSTRiP, FREEC and CNVnator, as well as their true positive rate (TPR), false discovery rate (FDR) and the F-score (F1) for identifying deletions and duplications of small, medium and large size (as defined above). We report results with mrCaNaVaR separately in Supplemental Table S1.A as this algorithm was specifically designed to target large duplications (>10 kbps) only.

Both genotypers, CONGA and GenomeSTRiP, achieved higher performance compared to the three CNV discovery tools (Table 1; Supplemental Table S1.A). Although this may seem expected, the fact that our candidate CNV call set included 10 times more false CNVs than true CNVs is notable, and indicates that both CONGA and GenomeSTRiP achieve non-trivial performances in distinguishing true versus false CNVs in ancient genomes.

CONGA and GenomeSTRiP had comparable performances, although CONGA had lower FDR and slightly lower recall (TPR) than the latter, leading to overall higher F-scores. We note that GenomeSTRiP was performed on each genome independently here, and its performance when genotyping multiple genomes together could be higher (Handsaker *et al.*, 2011), but may also lead to biases in heterogeneous datasets (see Discussion).

We also observed that the performance of all tools become comparable as the coverage approaches to depths of $5\times$, especially with large CNVs. For small CNVs (<1 kbps), all tools under-performed, although CONGA predictions still had higher recall and precision than the other tools (see Supplemental Fig. S2 for precision-recall curves).

The simulation results thus suggest that CONGA can efficiently and accurately genotype deletions and duplications of length >1 kbps in ancient genomes at $\geq 0.5\times$ coverage, with higher overall accuracy compared to available discovery and genotyping tools.

Copy number predictions of CNVs

Beyond the identification of deletion and duplication events, classifying individual genotypes as heterozygous or homozygous CNVs could provide valuable information for population genetic analyses of CNVs. However, predicting CNV copy numbers can be a significant challenge on low coverage ancient genomes (Kousathanas *et al.*, 2017). We thus assessed the performance of CONGA to determine the copy number of a CNV based on the likelihood model described above using our simulation data. We focused on medium and large size CNVs given the weak performance of CONGA on small CNVs. We note that CONGA only evaluates the possibility of homozygous duplications (ignores copy numbers ≥ 3). Figure 2 shows CONGA's copy number prediction performance for deletions and duplications using F-scores for each coverage tested. We found that F-scores were above 0.7 at coverages $\geq 0.5\times$. Encouragingly, CONGA had comparable power in identifying heterozygous and homozygous events of size >1 kbps (Supplemental Table S1.B).

Table 1: Summary of simulation predictions by CONGA, GenomeSTRiP, FREEC and CNVnator.

	Cov.	CONGA					GenomeSTRiP					FREEC					CNVNator				
		T	F	TPR	FDR	F1	T	F	TPR	FDR	F1	T	F	TPR	FDR	F1	T	F	TPR	FDR	F1
Dels (small) *1810 True*	.05×	1471	1887	**0.81**	0.56	0.57	829	6308	0.46	0.88	0.19	0	1221	0.00	1.00	-	3	47442	0.00	1.00	0.00
	.1×	1266	1440	**0.70**	0.53	0.56	851	4765	0.47	0.85	0.23	0	198	0.00	1.00	-	0	402	0.00	1.00	-
	.5×	1285	157	**0.71**	0.11	0.79	853	1549	0.47	0.64	0.41	0	6761	0.00	1.00	-	0	806	0.00	1.00	-
	1×	1410	46	**0.78**	0.03	0.86	888	719	0.49	0.45	0.52	0	1916	0.00	1.00	-	0	263	0.00	1.00	-
	5×	1593	8	**0.88**	0.00	0.93	917	89	0.51	0.09	0.65	20	392	0.01	0.95	0.02	341	493	0.19	0.59	0.26
Dups (small) *1751 True*	.05×	601	548	0.34	**0.48**	**0.41**	829	3834	**0.47**	0.82	0.26	0	44	0.00	1.00	-	7	47700	0.00	1.00	0.00
	.1×	719	404	0.41	**0.36**	**0.50**	1048	2691	**0.60**	0.72	0.38	0	7	0.00	1.00	-	0	28699	0.00	1.00	-
	.5×	856	64	0.49	**0.07**	0.64	1077	686	**0.62**	0.39	0.61	0	3	0.00	1.00	-	0	9	0.00	1.00	-
	1×	1155	14	**0.66**	0.01	0.79	1127	311	0.64	0.22	0.71	0	555	0.00	1.00	-	0	884	0.00	1.00	-
	5×	1448	1	**0.83**	0.00	**0.91**	888	1270	0.73	0.05	0.82	35	77	0.02	0.69	0.04	2	0	0.00	**0.00**	0.00
Dels (medium) *1680 True*	.05×	1136	1704	0.68	**0.60**	0.50	1430	5670	**0.85**	0.80	0.33	0	83	0.00	1.00	-	0	68	0.00	1.00	-
	.1×	1273	1308	0.76	**0.51**	0.60	1452	4383	**0.86**	0.75	0.39	0	237	0.00	1.00	-	1	216	0.00	1.00	0.00
	.5×	1423	171	0.85	**0.11**	0.87	1495	1467	**0.89**	0.50	0.64	239	6433	0.14	0.96	0.06	187	257	0.11	0.58	0.18
	1×	1506	53	**0.90**	0.03	0.93	1501	699	0.89	0.32	0.77	421	2135	0.25	0.84	0.20	330	257	0.20	0.44	0.29
	5×	1569	9	**0.93**	0.01	0.96	1510	102	0.90	0.06	0.92	929	485	0.55	0.34	0.60	949	423	0.56	0.31	0.62
Dups (medium) *1684 True*	.05×	792	551	0.47	**0.41**	0.52	1104	3813	**0.66**	0.78	0.33	0	3	0.00	1.00	-	0	114	0.00	1.00	-
	.1×	950	422	0.56	**0.31**	0.62	1160	2701	**0.69**	0.70	0.42	0	3	0.00	1.00	-	0	102	0.00	1.00	-
	.5×	1340	60	**0.80**	0.04	0.87	1322	685	0.79	0.34	0.72	271	15	0.16	0.05	0.28	2	4	0.00	0.67	0.00
	1×	1451	11	**0.86**	0.01	0.92	1389	333	0.82	0.19	0.82	582	937	0.35	0.62	0.36	16	2	0.01	0.11	0.02
	5×	1553	1	**0.92**	0.00	0.96	1473	95	0.87	0.06	0.91	1000	329	0.59	0.25	0.66	105	2	0.06	0.02	0.12
Dels (large) *1385 True*	.05×	1208	1812	0.87	**0.60**	0.55	1330	5891	**0.96**	0.82	0.31	0	87	0.00	1.00	-	84	131	0.06	0.61	0.11
	.1×	1251	1309	0.90	0.51	**0.63**	1337	4371	**0.97**	0.77	0.38	0	754	0.00	1.00	-	560	246	0.40	**0.31**	0.51
	.5×	1293	157	0.93	**0.11**	**0.91**	1335	1496	**0.96**	0.53	0.63	664	3136	0.48	0.83	0.26	1049	293	0.76	0.22	0.77
	1×	1299	53	0.94	**0.04**	0.95	1338	759	**0.97**	0.36	0.77	1239	156	0.89	0.11	0.89	1204	309	0.87	0.20	0.83
	5×	1299	4	0.94	**0.00**	0.97	1336	230	**0.96**	0.15	0.91	1260	154	0.91	0.11	0.90	1265	453	0.91	0.26	0.82
Dups (large) *1532 True*	.05×	1263	563	0.82	0.31	0.75	1271	3900	**0.83**	0.75	0.38	0	6	0.00	1.00	-	4	354	0.00	0.99	0.00
	.1×	1327	366	**0.87**	0.22	0.82	1327	2855	**0.87**	0.68	0.46	0	0	-	-	-	455	315	0.30	0.41	0.40
	.5×	1420	58	0.93	0.04	0.94	1424	964	**0.93**	0.40	0.73	589	97	0.38	0.14	0.53	1039	77	0.68	0.07	0.78
	1×	1426	20	0.93	0.01	0.96	1445	623	**0.94**	0.30	0.80	1305	266	0.85	0.17	0.84	1216	94	0.79	0.07	0.86
	5×	1428	9	0.93	0.01	0.96	1447	454	**0.94**	0.24	0.84	1304	294	0.85	0.18	0.83	1350	165	0.88	0.11	0.89

The table shows CNV prediction performances of CONGA, GenomeSTRiP, FREEC and CNVnator on simulated genomes with depths 0.05×, 0.1×, 0.5×, 1× and 5×, for deletions (Dels) and duplications (Dups) of multiple CNV size intervals including 100 bps - 1 kbps (small), 1 kbps - 10 kbps (medium) and 10 kbps - 100 kbps (large). Here, **T** (True) and **F** (False) refer to correct and incorrect predictions respectively, **TPR** is true positive rate (or recall) and **FDR** is false discovery rate ($1 - Precision$) of each algorithm. **F1** (F-score), is calculated as $(2 \times Precision \times Recall)/(Precision + Recall)$. Bold values in each row represent the highest TPR, lowest FDR, or highest F1 across the tools. See Supplemental Table S1.A for details and mrCaNaVaR predictions for large variations. Commands that we used to run each tool are also given in Supplemental Material. Also note that we used C-Score <0.5 for CONGA here and no read-pair or mappability filters were applied.

Down-sampling experiments with real ancient genomes

We next studied the performance of CONGA in identifying CNVs at various depths of coverage using real ancient genome data. As no ground truth CNV call-set is available, we used the following approach: (i) we chose three published ancient genomes of relatively high coverage ($\geq 9\times$), (ii) we genotyped CNVs using the full genome data with CONGA and using a modern-day human CNV call set as input, (iii) we down-sampled the ancient genome data to lower coverages, (iv) we assessed CONGA's performance in genotyping the same CNVs at low coverage (Methods).

Specifically, we selected a ($\sim 23.3\times$) ancient Eurasian genome (Yamnaya) (de Barros Damgaard *et al.*, 2018b), a $13.1\times$ ancient genome from Greenland (Saqqaq) (Rasmussen *et al.*, 2010), and a $9.6\times$ ancient genome from Ethiopia (Mota) (Llorente *et al.*, 2015). The Yamnaya genome was only available as a BAM file, while the latter two were available as FASTQ files, which we processed into BAM files (Methods). We used a list of modern-day human CNVs as candidate CNV set ($n = 17,392$ deletions and $n = 14,888$ duplications) (Methods) as input to CONGA. We thus genotyped between 688-1,581 deletions and 638-4,097 duplications across these three genomes using the full data. We then down-sampled all three BAM files to various depths, and repeated the genotyping for each genome. We estimated

Figure 2: Copy-number prediction performance of CONGA using F-score for (A) deletions and (B) duplications using medium and large CNVs merged for various coverage values.

CONGA's TPR and FDR on down-sampled genomes by treating the CNVs genotyped using the full data as ground truth (Methods).

CONGA displayed satisfactory performance in identifying deletions in all three genomes, with TPR of $>70\%$ and FDR of $<45\%$ at coverages around $0.5\times$ (Figure 3, Supplemental Table S1.C). For duplications, however, CONGA's performance was lower. At around $1\times$ coverage, duplication TPR was $>40\%$ in the Saqqaq and Mota genomes, and only 22% in the Yamnaya genome. A detailed analysis of these results suggested that pre-publication quality filtering of BAM files may have obliterated read-depth-based duplication signals in the data (Supplemental Note S2).

Overall, both our simulations and down-sampling experiments with real genomes suggest that CONGA can efficiently genotype >1 kbps deletion events at depths of coverage of $0.5\times$, and even at $0.1\times$. CONGA could thus be applied on a large fraction of ancient shotgun sequenced genomes available. In contrast, CONGA's low performance in duplication genotyping in the down-sampled Yamnaya BAM data implies that duplication genotyping across published low coverage ancient genomes is infeasible, as the data are mainly submitted in BAM format in public repositories (see Discussion). We therefore limited the analyses on real ancient genomes to deletions >1 kbps.

Technical influences on deletion genotyping

We genotyped deletions with CONGA across a diverse sample of real ancient human genomes. Our expectation was that CNVs, like SNPs, should display genome-wide similarity patterns that reflect population origin, i.e., shared genetic drift, among individuals (Conrad and Hurles, 2007; Levy-Sakin *et al.*, 2019; Almarri *et al.*, 2020). We collected BAM files for 71 ancient human genomes belonging to a time range between c.2,800-45,000 years Before Present (BP) (Supplemental Table S2) (Rasmussen *et al.*, 2014; Günther *et al.*, 2015; Hofmanová *et al.*, 2016; Jones *et al.*, 2015; Kılınç *et al.*, 2016; de Barros Damgaard *et al.*, 2018b; Gamba *et al.*, 2014; González-Fortes *et al.*, 2017; de Barros Damgaard *et al.*, 2018a; Keller *et al.*, 2012; Sikora *et al.*, 2019; Olalde *et al.*, 2014; Lazaridis *et al.*, 2014; Antonio *et al.*, 2019; Allentoft *et al.*, 2015; Haber *et al.*, 2019; Fu *et al.*, 2014; Broushaki *et al.*, 2016; Seguin-Orlando *et al.*, 2014; Jones *et al.*, 2017; Haber *et al.*, 2017; Raghavan *et al.*, 2014; Martiniano *et al.*, 2017; Krzewińska *et al.*, 2018; Yaka *et al.*, 2021). These were chosen to bear diverse characteristics, including a wide range in mean coverage ($0.04\times$-$26\times$, median = $3.45\times$), population origin (West and East Eurasia and North America), the laboratory of origin (10 different laboratories), the use of shotgun vs. whole-genome capture protocols, or the use of uracil–DNA–glycosylase (UDG) treatment (Rohland *et al.*, 2015). For genotyping, we used a candidate CNV dataset of 11,390 autosomal deletions (>1 kbps with mean 10,735 bps) identified among African populations (AFR) from Phase 3 of the 1000 Genomes Project (Sudmant *et al.*, 2015b) (Methods). Our motivation for using an African sample here was to avoid ascertainment bias (Clark *et al.*, 2005) in studying deletion frequencies, as all of the 71 ancient individuals were non-African, and thus African populations represent an outgroup to our sample set. Genotyping these 11,390 deletions across the 71 BAM files resulted in a

Figure 3: TPR vs FDR curves for deletion and duplication predictions of CONGA using Mota, Saqqaq and Yamnaya genomes down-sampled to various depths from their original coverages of $9.6\times$, $13.1\times$ and $23.3\times$, respectively. The numbers inside boxes show the down-sampled coverage values. We calculated TPR and FDR for down-sampled genomes assuming that our CONGA-based predictions with the original genomes (full data) reflect the ground truth. These predictions, in turn, were made using modern-day CNVs as candidate CNV list. The purpose of the experiment was to evaluate accuracy at lower coverage relative to the full data (Methods).

median number of 905 deletions [380-3,649] detected per genome, in either heterozygous or homozygous state. Of the 11,390 deletions, 8,106 (71%) were detected in at least one genome.

When we analysed deletion copy number (frequency) variation across the 71 ancient genomes using principal components analysis (PCA), we noticed that the genomes cluster in two groups, and that these groups reflected laboratories-of-origin, not the population-of-origin as would be expected (Figure 4A; Supplemental Fig. S3A). We found the reason for this grouping to be differential quality filtering of published BAM files among laboratories. Filtering all BAM files for MAPQ$\geq$30 and increasing the average mappability score threshold for deletion events to $\geq$0.9 effectively removed the laboratory-of-origin effect (Supplemental Fig. S4, S5, S6) (Supplemental Note S3).

We then clustered the 10,018 deletions that remained after filtering using k-means clustering, based on frequency similarities across the 71 genomes (Methods). This revealed that some singular ancient genomes behave as outliers, with unexpectedly high deletion frequencies at loci that were rarely or never identified in the rest of the 71 individuals (Supplemental Fig. S4, S5). We could visually identify 15 such outlier genomes (Supplemental Table S2). Given the close evolutionary relationship among Eurasian human populations, we reasoned that the majority of these signals are unlikely to be authentic, but rather originate from experimental artifacts, data processing artifacts, or variability of DNA preservation among samples.

Indeed, we recognized a number of attributes that could explain outlier behaviour. First, the coverage of the 15 outlier genomes was lower compared to the remaining 56 (Wilcoxon rank sum test, $p = 0.01$; Figure 6C). For instance, all three genomes with $<0.1\times$ coverage in our dataset (ne4, ko2, and DA379) were among the outliers. Second, the 15 outlier genomes had on average shorter read length compared to the rest (median = 52.7 vs. 65.8, Wilcoxon rank sum test $p < 0.001$; Supplemental Fig. S6C). One of these was the Iceman, with unusually short (50 bps) reads. UDG-treatment, meanwhile, did not appear to be related to outlier behaviour (binomial test $p > 0.10$). Finally, Bon002, the only sample produced using whole-genome capture, was among the most extreme outliers, suggesting that the capture procedure distorts coverage. Consequently we did not include these 15 genomes in further analyses.

A comparison of deletion and SNP diversity across 56 ancient genomes

The above genotyping and filtering steps resulted in a refined set of 10,018 autosomal deletions ascertained in present-day Africa and genotyped in 56 ancient Eurasian genomes, with 328-649 deletions (median = 411) detected in heterozygous or homozygous state per genome, and 28% detected in at least one genome. We used this dataset to test three hypotheses: (i) that CONGA-called deletion diversity patterns should parallel SNP diversity patterns, reflecting shared demographic history (genetic drift and admixture) among genomes, (ii) that CONGA-called deletions should be evolving under some degree of negative selection (caused by gene expression alterations, exon loss, or frame-shifts), and (iii) that variation in deletion load among genomes may be correlated with variation in deleterious SNP load. We note that the first two

Figure 4: (A) A principal components analysis of deletion frequencies across the 71 genomes. There is significant distinction between the two groups observed in PC1 that explains 18% of the total variation (Wilcoxon rank sum test on PC1 values $p < 10^{-16}$). (B) Violin plot of MAPQ scores of 514 deletions belonging to outlier cluster 7 ($k = 8$), for Group 1 ($n = 30$) and Group 2 ($n = 41$) genomes, identified in the PCA in panel A. The two distributions are significantly different (Wilcoxon rank sum test, $p < 10^{-15}$). The same pattern is observed for the 2 other outlier clusters, which also happen to have low mappability, but not the remaining 5 clusters. (C) Boxplots representing the coverages of the included and excluded genomes in the refined dataset. The excluded genomes have significantly lower coverages on average (Wilcoxon rank sum test, $p = 0.01$).

patterns (hypotheses i and ii) have been previously described using large modern-day CNV datasets (see (Conrad and Hurles, 2007; Levy-Sakin *et al.*, 2019; Almarri *et al.*, 2020) for drift, and (Conrad *et al.*, 2010; Cooper *et al.*, 2011; Sudmant *et al.*, 2015a) for selection), and our goal here was mainly to perform a sanity check and assess CONGA's effectiveness in producing reliable biological signals.

To test the first hypothesis, we compared pairwise genetic distances among the 56 individuals (Figure 5A) calculated using either SNPs or deletion genotypes. For this, we collected 5,991,735 autosomal SNPs ascertained in African Yoruba individuals in the 1000 Genomes Dataset and genotyped our 56 ancient genomes at these loci (Methods). We then calculated pairwise outgroup-f_3 statistics, a measure of shared genetic drift between a pair of genomes relative to an outgroup population (Patterson *et al.*, 2012). Using the Yoruba as outgroup, we calculated genetic distances for all pairs of ancient genomes as (1 - f_3), using either SNPs or deletions. We observed strong positive correlation between the two resulting distance matrices (Spearman $r = 0.71$, Mantel test $p = 0.001$) (Figure 5B). Summarizing SNP- and deletion-based distances using multidimensional scaling (MDS) also revealed highly similar patterns, with clear clustering among west and east Eurasian genomes observed with either type of variation (Figure 5C, D). This result was encouraging in showing that diversity patterns based on deletion genotyping with CONGA in a heterogeneous sample of low coverage ancient genomes reveals expected signals of shared demographic history.

Negative selection on deletion variants

We next studied the impact of negative (purifying) selection via the site-frequency-spectrum (SFS) of autosomal deletions across these 56 genomes, in comparison with the SNP SFS. We polarised deletions as well as SNPs using chimpanzee and bonobo genomes to represent the ancestral state, thus determining 9,579 deletions and 4,907,535 SNPs derived in the human lineage (Methods). To allow comparison with the pseudo-haploidized SNP genotype data, we randomly chose one allele per genome (i.e., deletion or no event) in the deletion dataset. Set side by side with the SNP SFS, we observed a stark excess of singletons among deletions, which is consistent with stronger negative selection on the latter (Figure 6A). The excess of undetected and singleton deletions does not appear to be related to low recall, as both high and low coverage genomes show the same trend (Supplemental Fig. S16).

If deletions are under strong negative selection we may also expect longer deletions, or deletions containing evolutionary conserved genes, to be segregating at lower frequencies. To test the first idea, we compared deletion allele frequencies with their length. As hypothesized, deletion size and its frequency were negatively correlated across the 56 genomes (Spearman correlation $r = -0.35, p < 10^{-16}$) (Figure 6B).

To test the second idea, we first determined deletions overlapping Ensembl human genes. Overall, 5% of the 9579 derived deletions overlapped minimum one gene. We then collected mouse-human dN/dS ratios, an inverse measure of protein sequence conservation (Methods). We found that deletions with lower (below average) allele frequency also had

Figure 5: (A) Geographic locations of the 56 ancient individuals. (B) Comparison of genetic distances calculated using SNPs and deletions. We calculated the Spearman correlation coefficient between two matrices and then calculated Mantel test p-value using the "mantel" function in R package "vegan" (v2.5-7). (C) and (D) represent multidimensional scaling plots that summarize outgroup-f_3 statistics calculated across all pairs among the 56 ancient individuals using SNPs and deletions, respectively.

lower dN/dS values (higher conservation) than deletions with higher (above average) allele frequency (Mann-Whitney U test, two-sided $p = 0.002$; Cohen's $d = 0.68$; Figure 6C). Both observations confirm the notion that deletions are under strong negative selection.

Finally, we asked whether inter-individual variation in the total deletion mutation burden that we measure in our dataset may be correlated with variation in the burden of functional deleterious SNPs based on their impact on protein sequence. Demographic bottlenecks can theoretically cause variable levels of mutation burden –as deletions and/or as SNPs– among ancient genomes, and these burden levels could be correlated especially if their phenotypic impacts are comparable (see Discussion). To test this we collected (a) total deletion length and (b) the number of genes affected by deletions, for each of the 56 ancient genomes (Supplemental Fig. S17). We further collected SIFT scores (an estimate of how protein sequence would be affected by a SNP (Ng and Henikoff, 2003)) for n=22,996 SNPs in our dataset, predicted to be "deleterious" or "tolerated", and used these to calculate a deleterious/tolerated ratio per genome (Methods). We then compared the deleterious/tolerated ratio-based burden levels with deletion-based mutation burden levels (total length and number of genes), but found no significant correlation (Spearman $r = 0.11$ and $r = -0.01$, respectively, $p > 0.3$; Supplemental Fig. S18B). This could be explained by lack of statistical power or differences in phenotypic impacts between deletions and SNPs (see Discussion).

Time and memory consumption

Finally, we examined time and memory requirements of CONGA. We first tested our performance of deletions with BAM files of the 71 ancient genomes presented above. This finished in ∼12 hours in total with as low as 2.2 GB of peak-memory consumption. This is ∼10 minutes per genome. In order to evaluate CONGA's performance with a higher coverage genome sample, we ran 30 genomes (randomly selected 10 CEU, 10 YRI, 10 TSI) from the 1000 Genomes Project Phase 3, which had mean 7.4× coverage (Sudmant *et al.*, 2015b). The analysis took just slightly longer, ∼15 minutes average per genome, with similar memory usage.

Figure 6: (A) The site-frequency-spectra of derived deletion alleles (on the left) and derived SNP alleles (on the right). The x-axes show mean allele frequency for each locus calculated using only those genomes where a locus has been observed (e.g. an allele observed in 10 out of 40 genomes will be represented as 25%). The two distributions are significantly different from each other (Kolmogorov-Smirnov test $p < 10^{-15}$). (B) The size distribution (in kbps) of the deletions versus mean allele frequency. The red line shows the fitting of smoothing spline and indicates a negative correlation (Spearman correlation $r = -0.35$, $p < 10^{-16}$). Both axes were log_2-scaled. (C) Boxplots representing the dN/dS values of high ($n = 25$) vs. low ($n = 376$) frequency deletions.

We also compared the time and memory requirements of CONGA, GenomeSTRiP, FREEC and CNVnator in Table 2. In order to benchmark these tools, we used a $5\times$ simulated genome (the same genome with medium sized CNVs used in the simulation experiments described above) with the same computing resources[1]. CONGA has the lowest runtime and memory footprint among the other tools.

In Supplemental Table S1.D we report the effects of parameter choices when using with CONGA on runtime and memory usage. We note that using split-reads for duplication genotyping (intended for higher coverage genomes) increases runtime and memory consumption significantly because here CONGA uses its own small-scale read mapper, which creates a bottleneck.

We further provide a comparison of CONGA's performance on genomes of various depths of coverage in Supplemental Table S1.D, calculated using the down-sampled $23\times$ Yamnaya genome (with coverages between $23\times$ and $0.07\times$).

Table 2: Time and Memory Consumption

Tools	Time (h:m)	Peak Memory Usage (GB)
CONGA	0:09	1.2
GenomeSTRiP	1:22	2.2
FREEC	0:39	7.1
CNVnator	0:32	14.1

Time and memory consumption of each algorithm for a simulated genome of $5\times$ depth of coverage with 1680 deletions and 1684 duplications. "Time" refers to wall clock time and "Peak memory usage" is the maximum resident set size. Note that GenomeSTRiP has two steps in its pipeline: preprocessing and genotyping. Here, time was calculated by summing the running times of each step, and memory by taking the maximum. For CONGA, we used default parameters used in the simulation experiments.

Discussion

Modern human genome sequencing experiments today typically reach coverages $>20\times$ and increasingly use long read technology, and such experiments can employ diverse read signatures to reliably identify CNVs (Alkan *et al.*, 2011). CONGA's approach that mainly relies on the read-depth signature is naive in comparison; however, using read-depth appears as the main practical solution given the short fragment size and the predominance of low coverage (around or $<1\times$) among ancient genome datasets.

CONGA's overall performance and utility

Despite these challenges, our experiments using simulated genomes and down-sampled real ancient FASTQ data showed that CONGA can relatively efficiently genotype deletions and duplications of size >1 kbps at $1\times$ coverage, or even

---

[1]Intel(R) Xeon(R) CPU E5-2640 v2 @ 2.00GHz: 2CPUs * 8 cores each=16 cores total and 216GB RAM

lower. CONGA outperformed two "modern DNA" CNV discovery algorithms, FREEC and CNVnator, two methods previously employed in ancient genome analyses (Smith *et al.*, 2017; Bhattacharya *et al.*, 2018). CONGA exceeded both tools in TPR and true negative rates, especially at coverages $<1\times$. This is unsurprising, as these tools were developed for discovering novel CNVs in relatively high coverage genome data. Meanwhile, compared to GenomeSTRiP, a CNV genotyper that also uses both different sources of information within a Bayesian framework (Handsaker *et al.*, 2011, 2015), CONGA performed better in achieving lower FDR rates at all coverages, while GenomeSTRiP had higher recall at coverages $0.5\times$ or below. In time and memory use, CONGA surpassed all three tools.

In terms of deletion copy number estimates, CONGA again achieved acceptable accuracy ($\sim75\%$ TPR and $<30\%$ FDR) in genomes of $0.5\times$ coverage. At lower depths of coverage and also when genotyping deletions <1 kbps, recall and/or precision were weaker. CONGA's performance on duplications was also weaker, as we discuss below.

Overall, the relatively high accuracy at $\geq0.5\times$ coverage suggests that CONGA could be used to genotype deletions across a considerable fraction of published shotgun sequenced ancient genomes. CONGA and GenomeSTRiP could also be used in parallel, as they appear to complement each other in recall and specificity. Further, GenomeSTRiP can be used in population samples for jointly genotyping low coverage genomes, which could potentially increase performance. We note, however, that joint genotyping may also create biases when both coverage and ancestry vary among co-analysed genomes.

We also note that CONGA is suitable for CNV analyses for any low depth whole-genome sequencing (WGS) experiment, beyond aDNA. Such studies are increasing in number due to the trade-off between budget limitations and the wealth of genome-wide information that can be used in population and conservation genetics (e.g. (Vieira *et al.*, 2016)).

Caveats in duplication genotyping

In simulated genome experiments, CONGA's performance in genotyping duplications was similar to that in deletions. Here, read-depth information provided comparable power as in genotyping deletions; furthermore, in identifying duplications, paired-end information from split reads alone also yielded >0.65 F-Score (i.e. without read-depth information), but only at $5\times$ coverage and with variants >10 kbps (Supplemental Table S1.E; Supplemental Fig. S13). In down-sampling experiments, CONGA showed slightly lower performance in duplication genotyping than in deletion genotyping when using two ancient genomes available as FASTQ files. However, CONGA's performance was dramatically low on the $23\times$ ancient BAM file, Yamnaya. This can be explained as follows (see Supplemental Note S2): (i) The available Yamnaya data was processed in such a way that excess reads at duplicated loci were removed. (ii) Consequently, 97% of duplications CONGA genotyped in the original ($23\times$) BAM file were called only using paired-end information, with no read-depth signal. (iii) Because paired-end information is more severely affected than read-depth information with decreasing coverage (as the former uses information from only reads that overlap breakpoints, while the latter uses information from across the length of the CNV), genotyping duplications in this BAM files became infeasible at $<5\times$ coverage.

The majority of shotgun ancient genomes in public databases are only published as BAM files. The majority of published files are also at $<5\times$ coverage. Hence, most published ancient shotgun genomes are not amenable to duplication genotyping with CONGA. This is highly unfortunate, as gene duplications are a major source of evolutionary adaptation that would be valuable to study also in ancient populations.

Caveats in deletion genotyping

Applying CONGA to genotype deletions on 71 real ancient shotgun genomes from North Eurasia and the Americas using a dataset of modern-day African deletions revealed two observations on technical aspects.

First, we saw that differences among published BAM files with respect to mapping quality filtering can create artificial deletion signals (Supplemental Note S3). Fortunately, stringent filtering of all data overcomes this issue (a solution not available for duplication genotyping).

Second, 15 of the 71 analysed genomes displayed "outlier" behaviour in their deletion frequencies. We could notice particularities in experimental protocols for some of these genomes, such as lower coverage, shorter read lengths, or the application of whole-genome hybridization capture. Our results suggest that $0.1\times$ coverage appears to be the lower threshold for deletion genotyping of >1 kbps events, which is consistent with our simulation results. We also find that whole-genome hybridization capture and extra short reads (roughly ≤55 bp) compromise deletion genotyping, while UDG-treatment does not show a significant effect. That said, we lack clear explanations for outlier deletion frequency patterns for some of these 15 genomes. For instance, the genome SI-45 has coverage $>3\times$ and an average read length of 60 bps, but nevertheless displays unusual deletion patterns. We suspect that such unexpected patterns might reflect technical peculiarities in library preparation, sequencing or data filtering. This could be investigated by future studies

compiling larger datasets (preferentially as raw FASTQ files), as well as laboratory and computational procedure details behind each genome file.

Community recommendations for improving CNV analyses in ancient genomes

The above observations mark the urgent need for new practices in producing and publishing ancient genomes to allow reliable study of CNVs beyond SNPs.

- Most published ancient genome data to date is SNP capture data, which is largely worthless for CNV analyses. Our results underscore the long-term value of shotgun sequencing data over SNP capture, as well as whole-genome capture.

- Researchers should strive to publish their data as raw FASTQ files. The main motivation behind publishing BAM files instead of raw data is to avoid publishing environmental DNA reads, which constitute a large fraction of reads from shotgun sequenced aDNA experiments. Saving microbial (e.g. pathogenic) aDNA fractions for investigations is another motivation. Nevertheless, our results show that raw FASTQ data is absolutely necessary for duplication genotyping at low coverage and also helpful against biases in deletion genotyping. In the long term, publishing raw data will be for the whole community's benefit.

- Sharing all details on DNA extraction, library construction, as well as the alignment and preprocessing steps used in creating the exact version of datasets submitted to public databases is crucial for healthy reuse of the data.

We further recommend the following for comparative CNV analyses in ancient genomes:

- Studying and normalizing mapping quality distributions across published BAM files is crucial to avoid biases. Realignment through the same pipelines would also be highly recommended.

- Given the unavoidable heterogeneity of ancient genome data sources and the sensitivity of CNV detection and genotyping tools to such heterogeneity, researchers should pay utmost care to identify and filter out genomes with abnormal patterns of CNV frequencies in aggregate datasets in advance.

Studying purifying selection and mutation loads in past populations

Our analysis of >1 kbps deletions genotyped in 56 ancient genomes revealed how variation in deletion frequencies reflect (a) demographic history, as reflected in strong correlation with SNP variation and spatial clustering, and (b) negative selection, as reflected in a steep SFS, low frequencies of large deletions, and low frequencies of deletions overlapping conserved genes. These results confirmed that deletion genotyping with CONGA in joint datasets –despite significant technical challenges– can produce biological signals well-described in present-day genomic variation (Conrad and Hurles, 2007; Conrad *et al.*, 2010; Cooper *et al.*, 2011; Levy-Sakin *et al.*, 2019; Almarri *et al.*, 2020; Sudmant *et al.*, 2015a).

Beyond replicating earlier results, we also studied possible correlation between deletion loads and deleterious SNP loads per genome, across the 56 ancient individuals. High deleterious mutation loads could arise by relaxation of negative selection due to strong bottlenecks, as suggested for Wrangel Island mammoths (Rogers and Slatkin, 2017) or dogs (Marsden *et al.*, 2016). Conversely, bottlenecks can cause high inbreeding levels, and this may lead the purging of recessive deleterious variants, as recently described for a founder population of killer whales (Foote *et al.*, 2021). In our dataset we found no significant correspondence between deletion-related loads and deleterious SNP loads. This could be due to lack of strong variability among Eurasian genomes in deleterious mutation burdens or due to low statistical power, as we only use deletions segregating in Africa. The result could also reflect differences in dominance effects or fitness effects between SNPs and deletions.

A full analysis of this question could be possible with the creation of a geographically comprehensive genomic time-series, especially genomes of non-Eurasian populations with variable demographic histories. It would further require CNV discovery in carefully processed high-coverage ancient genomes and subsequent genotyping on low coverage data using CONGA. We hope that our study opens the way for such work, bringing deeper insight into the impacts of selection and drift in humans and other species.

Methods

Among various approaches developed for CNV discovery using high throughput sequencing data, almost all use the fact that read-depth, i.e., the density of reads mapped to the reference genome, will be on average lower in deleted

regions and higher in duplicated regions (Alkan *et al.*, 2011; Ho *et al.*, 2020). The distance between paired-end reads,
their orientation, and split-read information (start and end of reads mapping to different locations) are further sources
of information used in determining CNVs. Although available CNV discovery algorithms generally perform well in
modern-day human genome sequencing data with high coverage, this is not necessarily the case for ancient genomes,
as well as other low coverage sequencing experiments (Supplemental Fig. S10, S11). The first reason is that the
majority of shotgun ancient genomes are produced at low coverage (typically $<1\times$), which limits the use of read-depth
information. Second, ancient DNA fragments are short and of variable size (typically between 50-100 bps) (Shapiro and
Hofreiter, 2014). Thus, paired-end information is absent, and available split-read information is also limited. Variability
in ancient DNA preservation and genome coverage (Pedersen *et al.*, 2014) is yet another noise source that is expected to
limit efficient CNV discovery. CONGA overcomes these limitations using genotyping instead of *de novo* discovery.
It estimates whether a candidate CNV, the location of which is provided as input, is present in a genome in BAM
format. It also estimates the genotype, i.e., the heterozygous or homozygous state. CONGA makes use of read-depth
information for deletions, and both read-depth and split-read information for duplications.

Likelihood-based read-depth calculation for deletion and duplication genotyping

The input to the algorithm is (1) a list of candidate CNV locations and CNV type, i.e., deletion or duplication, and (2) a
data set of reads aligned to the linear reference genome, e.g., using BWA (Li and Durbin, 2009), which should be in
BAM format.

In order to calculate the likelihood of a CNV at a given locus based on read-depth information, CONGA uses an
approach akin to (Soylev *et al.*, 2019). Let (S_i) be the i^{th} CNV in our CNV input list, defined by the breakpoint interval
(B_l, B_r) and the type of CNV: a deletion or duplication. At this locus, CONGA calculates the likelihood of the three
possible genotype states, k, given the read alignment data and CNV type. The genotype states are: no event ($k = 0$), a
heterozygous state ($k = 1$), or a homozygous state ($k = 2$). The likelihood, in turn, is calculated by comparing the
observed (O_i) read-depth versus the expected (E_{ik}) read-depth within (B_l, B_r), given the three different genotypes.
We detail the steps below.

1. We count the total number of mapped reads within that locus (falling fully within the interval (B_l, B_r)). This
   is the observed read-depth, (O_{RD}).

2. We calculate expected read-depth under a "no event" scenario, i.e., representing the diploid state. Here we
   account for the GC bias in high throughput sequencing data (Smith *et al.*, 2008), by using LOESS smoothing
   to normalize read-depth for GC content. Specifically, for each chromosome, we calculate the read-depth values
   per GC percentile for sliding windows of size 1,000 bps (step size = 1 bp). We then calculate the average
   read-depth per GC percentile. Then, using the chromosome-wide average GC value for the interval (B_l, B_r),
   we calculate the expected diploid read-depth, $E_{i_{k=0}}$.

3. We model the read-depth distribution as Poisson, using the expected read-depth values for $k = 0$, $k = 1$,
   $k = 2$. We calculate the probability $P(RD_{S_i}|state = k)$ as:

$$P(RD_{S_i}|state = k) = \frac{E_{ik}^{O_i} \times e^{-E_{ik}}}{O_i!},$$

where E_{i_k} is the expected read-depth given $state = k$, and O_i is the observed read-depth at that specific locus.
A typical autosomal human locus is diploid (has copy number = 2); therefore when there is no CNV event
($k = 0$), the expected value of O_i should be $E_{i_{k=0}}$.

If a genome is homozygous for a deletion, we expect no reads mapping to the region, thus $O_i \sim E_{i_{k=2}} = 0$. For
heterozygous deletions, the expected number of mapped reads in that interval will be half of the expected diploid
read-depth: $O_i \sim E_{i_{k=1}} = E_{i_{k=0}}/2$. For homozygous duplications, we expect $O_i \sim E_{i_{k=2}} = E_{i_{k=0}} \times 2$. For
heterozygous duplications, we expect $O_i \sim E_{i_{k=1}} = E_{i_{k=0}} \times 1.5$.

4. We calculate a likelihood-based score, which we term the C-score, to estimate how likely locus S_i carries a
   non-reference variant in a genome, in either one copy or two copies. For this we use the calculated likelihoods
   for the three states. We define the C-score as the maximum of the likelihoods of (S_i) being present in
   heterozygous state ($k = 1$) or in homozygous state ($k = 2$) in that genome, over the likelihood of no event
   ($k = 0$). We use the log function to avoid numerical errors.

$$C - score(S_i) = \frac{max(log(P(RD_{S_i}|k = 1)), log(P(RD_{S_i}|k = 2)))}{log(P(RD_{S_i}|k = 0))},$$

Figure 7: The figure shows our split-read approach to emulate paired-end using single-end reads. We use short-read Illumina mappings in a BAM file as input. We split each discordant read (whose mapping quality is larger than the given threshold and does not overlap with a known satellite) from the middle, keeping the initial mapping as one element and the other subsequence (split segment) as the second element of a pair. We remap the split segment to the reference genome, and evaluate the position and the orientation of both reads to identify the presence of putative CNVs.

The C-score is distributed between 0 and $+\infty$, with lower scores indicating higher likelihood of a true CNV event.

Results from our simulations and down-sampling experiments suggest that the relatively simple Poisson distribution can be effectively used to model copy number states, especially in the face of potentially non-independent errors due to ambiguous mapping of short and damaged reads or GC content heterogeneity. We note that alternative models have also been used for analysing CNVs in short read sequencing data, such as the negative binomial distribution (Miller *et al.*, 2011) or Gaussian mixed models (Handsaker *et al.*, 2011). We also note CONGA's our approach could be expanded in the future by including the evaluation of duplication events involving >2 copies, as in multicopy genes (Sudmant *et al.*, 2010).

Split-read and paired-end signatures for duplication genotyping

Beyond read-depth, information of paired-end reads or read fragments that do not linearly map to the genome can be used to identify CNVs. Ancient genomes are sometimes single-end and sometimes paired-end sequenced, but in the latter case, short overlapping reads are typically merged into a single read before alignment. Ancient genome data is thus practically single-read. However, the split-read method can be applied on single-read ancient genome data, which emulates paired-end information for genotyping duplications. This approach is visualized in Figure 7. We therefore designed CONGA to include both paired-end and single-end reads as input and evaluate the paired-end signature information.

First, assume a read of length L mapped to position pos_x in the reference genome, where pos_x is assumed to be one of the breakpoints of a putative CNV. There always exists a subsequence $\geq L/2$ that will have at least one mapping in the reference genome with some error threshold. Thus, we can split a read into two subsequences, assigning the actual mapping to one of the pairs and remapping the other subsequence ("split segment") as a second pair. There are two possible split strategies: an even decomposition, where both subsequences are of equal lengths, or an uneven decomposition, where the subsequences are of unequal lengths. Given the infeasibility of testing each split position and the fact that ancient reads are typically already short, we follow (Karakoc *et al.*, 2012) and split the read from the middle to obtain two reads with equal lengths $L/2$. If a read overlaps a duplication breakpoint, and assuming that the expected position of the breakpoint will be uniformly distributed within the read, the split segment will map to the reference genome with insert size—the distance between the split-read pairs—greater than zero.

With this simple observation, the need to observe all possible breakpoints can be eliminated. Thus, given a single-end read Rse_i, we define $Rpe_i = (l(Rpe_i[pos_x : pos_x + RL/2])$ and $r(Rpe_i[pos_y : pos_y + RL/2]))$, where pos_x is the initial mapping position of the single-end read, pos_y is the remapping position of the split read, RL is the length of the single-end read observed before the split, $l(Rpe_i[pos_x : pos_x + RL/2])$ is the left pair within pos_x and $pos_x + RL/2$ and $r(Rpe_i[pos_y : pos_y + RL/2])$ is the right pair within pos_y and $pos_y + RL/2$ of the paired-end reads. We use this information as described in the following section.

Remapping paired-reads and utilizing paired-read information

According to our remapping strategy, we use a seed-and-extend approach similar to that implemented in mrFAST (Alkan *et al.*, 2009), where a read is allowed to be mapped to multiple positions. Our main concern here is that the split segment, due to its short length, can be mapped to unrealistically high numbers of positions across the genome. To overcome this problem we use the approach developed in TARDIS (Soylev *et al.*, 2017), allowing the split segment to

be mapped only up to 10 positions within close proximity (15 kbps by default) of the original mapping position and
applying a Hamming distance threshold for mismatches (5% of the read length by default).

Based on the distance between the reads (insert-size) and orientation, we then evaluate the type of putative CNV.
As Figure 7C shows, if the split segment maps behind the initially mapped segment of the same pair to generate a
reverse-forward mapping orientation, this would be an indication of a duplication.

In order to utilize this paired-read information, for each CNV locus used as input to our algorithm, we count the number
of read-pair (i.e. split segments) that map around +/- 5 kbps of the breakpoints. Each such read-pair is treated as one
observation. We use these counts in combination with the C-score (read-depth information) to genotype duplications
(see below). We do not use this read-pair information for genotyping deletions due to its low effectiveness in our initial
trials (Supplemental Table S1.E).

Mappability filtering

The probability of unique alignment of a read of certain size varies across the genome, mainly due to repetitive
sequences. Various algorithms estimate this probability, termed mappability, across the genome for k-mers of specific
length (Koehler *et al.*, 2011; Derrien *et al.*, 2012; Karimzadeh *et al.*, 2018; Pockrandt *et al.*, 2020). This is calculated
by extracting k-mers of given length through the genome, remapping them to the reference genome, and measuring
mappability as the proportion of unique mappings (Karimzadeh *et al.*, 2018). Because low mappability regions can
be confounded with real deletions, we use mappability information to filter out CNV loci that could represent false
positives.

CONGA accepts any mappability file in BED format, where values are distributed between 0 and 1. These can then be
used to filter out CNVs for minimum mappability.

In our experiments, we used the 100-mer mappability data from the ENCODE Project (ENCODE Project Consortium,
2012), available at http://hgdownload.cse.ucsc.edu/goldenpath/hg19/encodeDCC/wgEncodeMapability/. Using this
data, for each CNV event (S_i), we calculated the average mappability value within its breakpoints. We used either of
two different minimum average mappability thresholds for the CNV events we analyzed: 0.5 (relaxed) or 0.9 (strict).
Our deletion frequency analysis results show that the strict filter is more reliable especially when analyzing data sets of
heterogeneous origin (see Results).

Simulation and down-sampling experiments

Simulating ancient genomes with implanted deletions and duplications

Our goal here was to study the performance of CONGA on different sized deletions or duplications using simulated
genomes containing implanted CNVs and to determine thresholds for reliably calling these variants. We first employed
VarSim (Mu *et al.*, 2015) to simulate and insert deletions and duplications into the human reference genome GRCh37.
We repeated this three times, for small (100 bps - 1000 bps), medium (1000 bps - 10,000 bps), and large (10,000 bps -
100,000 bps) CNVs. As a result we generated three CNV implanted genomes, with around 1500 deletions and 1500
duplications each (between 1385 and 1810). The CNVs were produced so that they were non-overlapping, and their
length distribution and exact counts are provided in Supplemental Fig. S1.

To evaluate specificity and sensitivity, we also included a background (false) CNV set in the experiment, which would
not be implanted but would be queried as part of the candidate list. This background set was prepared using recently
published deletion and duplication calls from human genome sequencing experiments (Audano *et al.*, 2019; Chaisson
et al., 2019; Zook *et al.*, 2020; Collins *et al.*, 2020) and also sequencing data from African populations (AFR) from
Phase 3 of the 1000 Genomes Project (Sudmant *et al.*, 2015b). We compiled a list of 17,392 deletions and 14,888
duplications that were non-overlapping and of size $> \sim 1000$ bps using BEDTools mergeBed (Quinlan and Hall, 2010).
When evaluating genomes with small CNVs (100 bps - 1,000 bps), we additionally included small CNVs from (Chaisson
et al., 2019). Specifically we added 4,623 deletions and 3,750 duplications of size 100 bps - 1,000 bps to the above
background list.

In order to assess CONGA's performance, we added the true CNVs generated using VarSim to this background set (and
removed overlapping CNVs from the candidate genotype set), such that only $\sim 10\%$ of the input candidate CNV list
were true events. Finally, we determined how many of these true events could be correctly called by CONGA and other
software.

Simulating ancient genome read data

We then used the above-described simulated genomes as input to Gargammel (Renaud *et al.*, 2017), which generates ancient-like Illumina reads, i.e., short reads of variable size bearing postmortem damage (i.e., C-to-T transitions at read ends) and including adapters. Gargammel is able to generate aDNA fragments with size distribution given as input, and we used a subset of (Fu *et al.*, 2014), which is default for this software. We used Gargammel to produce reads at various depths of coverage: $0.05\times$, $0.1\times$, $0.5\times$, $1\times$ and $5\times$. We then removed adapters and merged overlapping reads (Schubert *et al.*, 2016) to generate single-end Illumina reads. These reads had sizes ranging between 34 bps and 139 bps, with average 69 bps and median 66 bps (these statistics were calculated using $1\times$ coverage data, but other data also had similar distributions). We mapped the Gargammel-output reads back to the human reference genome (hg19, or GRCh37) using BWA-aln (Li and Durbin, 2009) with parameters "-l 16500 -n 0.01 -o 2" (Supplemental Material). Note that BWA-aln has been shown to be more accurate for short ancient reads than BWA-mem (Oliva *et al.*, 2021).

Evaluation of CONGA, GenomeSTRiP, CNVnator and FREEC with simulated ancient genome data

We ran CNVnator (Abyzov *et al.*, 2011), FREEC (Boeva *et al.*, 2012) and GenomeSTRiP (Handsaker *et al.*, 2011) on the simulated genomes with parameters described in the Supplemental Material and CONGA with two values for the C-score (<0.3 and <0.5). We used the above-described list of CNVs as the input candidate set for CONGA and GenomeSTRiP.

To determine true calls, we used $>50\%$ reciprocal overlap for the two CNV events (the event in the input event set and the called event) to be considered the same. This calculation was done using BEDTools (Quinlan and Hall, 2010). The number of true CNVs were: 1810 deletions and 1751 duplications for 100 bps - 1000 bps; 1680 deletions and 1684 duplications for 1000 bps - 10,000 bps; and 1385 deletions and 1532 duplications for 10,000 bps - 100,000 bps.

Down-sampling experiment with real ancient genomes

We used three relatively high coverage ($\sim23.3\times$, $\sim13.1\times$ and $\sim9.6\times$ respectively) genomes of a Yamnaya culture-related individual from early Bronze Age Karagash (hereafter Yamnaya), Kazakhstan (de Barros Damgaard *et al.*, 2018b), a Saqqaq culture-related individual from Bronze Age Greenland (hereafter Saqqaq) (Rasmussen *et al.*, 2010), and a 4500-year old East African hunter-gatherer individual from Mota Cave in Ethiopia (hereafter Mota) (Llorente *et al.*, 2015). Using this data, and the above-described 17,392 deletions and 14,888 duplications of size >1 kbps (see above) as input, we genotyped 2639 deletions and 1972 duplications in Yamnaya (deletion sizes: 1 kbps to 4 Mbps, median = 4 kbps, mean = 23 kbps; duplication sizes: 1 kbps to 28 Mbps, median = 14 kbps, mean = 80 kbps); 1581 deletions and 4097 duplications in Saqqaq (deletion sizes: 1 kbps to 5 Mbps, median = 5 kbps, mean = 17 kbps; duplication sizes: 1 kbps to 28 Mbps, median = 16 kbps, mean = 70 kbps); and 688 deletions and 638 duplications in Mota (deletion sizes: 1 kbps to 130 kbps, median = 4 kbps, mean = 7 kbps; duplication sizes: 1 kbps to 28 Mbps, median = 6 kbps, mean = 82 kbps).

We then randomly down-sampled the BAM files to various depths using Picard Tools (Pic, 2019): between 16-$0.07\times$ for Yamnaya; 9-$0.05\times$ for Saqqaq; 7-$0.03\times$ for Mota. We note that this down-sampling procedure does not produce the exact targeted depths, which is the reason why we obtain variable coverages in Fig. 3.

For calling deletions we used C-score<0.5. For calling duplications, we called events that fulfilled either of the following conditions (a) C-score<0.5, or (b) C-score<10 and read-pair support >10. Finally, treating the results of the original data as the correct call-set, we calculated TPR (true positive rate) and FDR (false discovery rate) for the down-sampled genomes. We considered CNVs with $\geq 50\%$ reciprocal overlap as representing the same event, calculated using BEDTools (Quinlan and Hall, 2010).

C-score and read-pair cutoffs and minimum CNV size

We ran CONGA with a range of parameter values for the C-score [0.1-5] and for minimum read-pair support (from 0 support to >30), and using the above-described true event sets as the input candidate set involving medium and large CNVs (1680 deletions and 1684 duplications for 1000 bps - 10,000 bps, and 1385 deletions and 1532 duplications for 10,000 bps - 100,000 bps).

We used simulation results (Supplemental Table S1.E) to choose an effective cutoff for calling CNVs. For both deletions and duplications, we decided to use C-score <0.5, which appears to yield a good trade-off between recall and precision. Specifically, in simulations, this cutoff ensured an F-score of >0.5 at $0.1\times$ for >1 kbps deletions, and superior F-scores at higher coverages (Supplemental Fig. S12).

In addition, we observed that read-pair support >10 could be useful for identifying duplications in the absence of read-depth support, but only when coverages were $\geq 1\times$ (Supplemental Table S1.E; Supplemental Fig. S13). Moreover, read-pair support was not valid for detecting deletions.

We note that CONGA outputs the C-scores and read-pair counts for all input CNVs. Users can choose alternative cutoffs to increase recall (higher C-scores) or precision (lower C-scores).

The simulation experiments showed that CONGA was not efficient in identifying events <1 kbps. CONGA therefore ignores events <1 kbps under default parameters. This can be modified by the user if needed.

Analysis of real ancient genomes

Ancient genome selection and preprocessing

We selected 71 ancient shotgun or whole-genome captured genomes from individuals excavated in West and East Eurasia and in North America (Supplemental Table S2). Our sample set belongs to a time range between c.2,800-45,000 years Before Present (BP). Samples from 10 different laboratories were selected in order to study the effects of different data production protocols on deletion genotyping. We also chose genomes with a range of coverage levels ($0.04\times$-$26\times$, median = $3.45\times$) and that included both UDG-treated and non-UDG-treated libraries. The only capture-produced data was Bon002 (Kılınç *et al.*, 2016), produced using whole-genome hybridization with myBaits (Arbor Biosciences, USA) probes.

Selected ancient genomes were mapped to the human reference genome (hg19, or GRCh37) using BWA aln/samse (0.7.15) (Li and Durbin, 2009) with parameters "-n 0.01, -o 2". PCR duplicates were removed using FilterUniqueSAM-Cons.py (Kircher, 2012). We also removed reads with $>10\%$ mismatches to the reference genome and those of size <35 bps. For preparing the "refined data set", reads with <30 mapping quality (MAPQ) were additionally removed.

Candidate CNV call set for real ancient genomes

Here our goal was to study properties of deletion variants in ancient genomes and to compare these with SNP variation in terms of demographic history and purifying selection. Polymorphism data sets can suffer from ascertainment bias in downstream evolutionary analyses (Clark *et al.*, 2005). A common practice to avoid this bias is to use SNPs ascertained in a population that is an outgroup to the focal populations. We therefore used variants ascertained in modern-day African populations for both calling SNP and deletion variants in our ancient genomes.

In order to create a candidate deletion call set to be used as input to CONGA, we downloaded deletions of size >1000 bps identified among 661 African population (AFR) genomes of the 1000 Genomes Project Phase 3 (Sudmant *et al.*, 2015b). When a deletion was located inside the breakpoints of another deletion, we removed the internal one. In addition, for pairs of deletions that had $>50\%$ overlap, we filtered out the smaller one. Finally, we filtered out deletion loci with $<50\%$ average mappability (see above). This resulted in $11,390$ autosomal >1000 bps deletions from 661 AFR genomes.

Deletion genotyping in ancient genomes: the raw data set

We genotyped all the chosen 71 ancient genomes using the 11,390 AFR autosomal deletion data set (>1 kbps with mean 10,735 bps). We used C-score <0.5 as cutoff for calling deletions. We call this the "raw data set". In total, 8,106 deletions were identified in at least one genome.

Analyzing the raw data set of ancient deletions

Cluster analyses of ancient genomes

We performed a principal components analysis (PCA) on the deletion copy number data set where we clustered the 71 ancient genomes (Figure 4A). PC1 and PC2 values were computed using the R "stats" package "prcomp" function using the default parameters (R Core Team, 2020). We also generated a heatmap summarizing deletion copy numbers using the R "gplots" package "heatmap.2" function (Warnes *et al.*, 2020) (Supplemental Fig. S3A). These analyses revealed visible differences in deletion frequency among samples reflecting the laboratory-of-origin, such that the genomes were clustered into two main groups, that we called Group 1 and Group 2. We compared PC1 values among the 10 laboratories, and between Group 1 vs. Group 2, using the Wilcoxon rank-sum test (R "stats" package "wilcox.test" function) and the Kruskal-Wallis test (R "stats" package "kruskal.test" function), respectively (R Core Team, 2020). We further tested each of the 8,106 deletions identified in at least one genome for differences in frequency among the 10

laboratories using the Kruskal-Wallis test, and corrected for multiple testing with the Benjamini-Hochberg correction (R "stats" package "p.adjust" function with the "BH" parameter) (R Core Team, 2020).

Cluster analyses of deletion events

We conducted k-means clustering analysis of deletions in the "raw data set" by using the "kmeans" function available in the R "stats" package (R Core Team, 2020), and clustering deletions based on deletion copy numbers across the 71 genomes. We set the seed 123 for reproducibility. Analysis of within-group sum of squares did not reveal an optimal k (Supplemental Fig. S6A), and therefore used both $k = 8$ and $k = 16$. After clustering, we plotted mean copy numbers of the individuals in our sample set for each cluster using the R "ggplot2" package "ggplot" function (Wickham, 2016) (Supplemental Fig. S4, S5).

We observed that Group 1 and Group 2 were different in terms of their mean copy numbers, as expected from the PCA results. We conducted the Wilcoxon rank-sum test on the mean deletion copy numbers of the two groups for each cluster (R "stats" package "wilcox.test" function) (R Core Team, 2020). We also calculated effect size in mean deletion copy numbers between Group 1 vs. Group 2 using a web-based effect size calculator (Becker, 2000).

Mappability and mapping quality analysis of deletions clusters

For deletion events in each k-means cluster, we compiled (i) average mappability values (see above) per deletion, and (ii) mapping quality (MAPQ) values of reads mapping to those locations, separately for Group 1 and Group 2 genomes. We compared these using violin plots of average mappability per deletion for each cluster ("geom_violin" function in the R "ggplot2" package)(Supplemental Fig. S7, S8, S13) (Wickham, 2016). We plotted the mean difference in MAPQ values between Group 1 and 2 versus the total difference in copy number between Group 1 and 2 using the "ggplot" function (R "ggplot2" package) (Supplemental Fig. S14) (Wickham, 2016).

Creating and analyzing the refined deletion data set and the SNP data set

SNP genotyping in ancient genomes

Following the same reasoning as above regarding ascertainment bias, we used an African population to create a SNP genotyping set for calling SNPs in the ancient genomes. Specifically, we used the 1000 Genomes Yoruba data set, which included a total of 5,987,516 autosomal bi-allelic SNPs with a minor allele frequency of $\geq 10\%$ in 108 African Yoruba genomes of the 1000 Genomes Project Phase 3 (The 1000 Genomes Project Consortium, 2015). First, all reads in all BAM files were clipped (trimmed) using the trimBam algorithm implemented in BamUtil (Jun *et al.*, 2015). Following standard practice (Mittnik *et al.*, 2018), we trimmed (a) the end 2 bases of each read for samples prepared with the Uracil-DNA-glycosylase (UDG) protocol, and (b) the end 10 bases of each read for non-UDG samples.

Using these BAM files of the 56 ancient individuals and the above-described list of 5,987,516 SNPs, we generated pseudo-haploid SNP calls at these target SNP positions by randomly selecting one read and recording the allele carried on that read as the genotype. This was performed using the pileupCaller software (https://github.com/stschiff/sequenceTools) on samtools mpileup output (base quality>30 and MAPQ>30) (Li *et al.*, 2009).

Ancestral state determination

To polarize deletion and SNP alleles for being ancestral or derived in the human lineage, we mapped loci from hg19 (GRCh37) to panTro6 (chimpanzee) and to panPan2 (bonobo) using the UCSC Genome Browser tool "liftOver" with default parameters (Kent *et al.*, 2002). For deletions, we filtered out deletions that did not fully map to either chimpanzee or bonobo reference genomes, as these could represent derived insertions in the human lineage. The remaining deletions could thus be inferred to be alleles that were derived in humans. For SNPs, we removed the positions not represent in either chimpanzee or bonobo reference genomes and assigned the ancestral state as the Pan allele, only if both chimpanzee and bonobo carried same allele. This left us with 4,907,535 SNP positions with derived allele information.

Creating the refined deletion data set

We filtered deletions in the raw data set for high mappability (≥ 0.9 average mappability), which left us with 10,018 deletions. We further removed 15 genomes identified as outliers in the k-means clustering analyses. We then selected reads with >30 mapping quality (MAPQ) in all BAM files, and we genotyped the 10,018 AFR deletions in the remaining 56 genomes. We call this the "refined data set". In addition, we created a subset of this data set than only includes the 9,579 deletions derived in the human lineage (see above). After refining our data set, we also checked

its general properties. We plotted size distribution in logarithmic scale, deletion allele frequency distribution and relative frequency distribution among observed heterozygous deletions over homozygous deletions using R's "graphics" package hist function (Supplemental Fig. S15) (R Core Team, 2020). We also plotted relative deletion (homozygous or heterozygous) frequencies of 9579 deletions for each individual in our refined data set using R's "graphics" package matplot function (R Core Team, 2020).

Genetic distance analyses using deletions and SNPs

Here our goal was to calculate pairwise genetic distances among the 56 ancient genomes using deletion allele frequencies and using SNPs, and further to compare the distances. We calculated distances using the commonly used outgroup-f_3 statistics, which measures shared genetic drift between two samples relative to an outgroup, and is implemented as qp3pop in Admixtools v.7.0 (Patterson *et al.*, 2012). The outgroup-f_3 values were calculated for each pair of 56 individuals (a) in the deletion and (b) in the SNP data sets, using the African Yoruba as outgroup in both cases. To convert the deletion data set to eigenstrat format, which Admixtools requires, we encoded the first nucleotide of each deletion as the reference allele, and the alternative allele was randomly assigned among the remaining 3 nucleotides using custom python script. We thus calculated a pairwise similarity matrix for both data sets. Genetic distances were calculated as 1-f_3. Distances were then summarized using multidimensional scaling (MDS) with the "cmdscale" function of R (R Core Team, 2020).

We further performed the Mantel test to compare the f_3-based similarity matrices calculated using SNPs and deletions. We used the "mantel" function in the R-package "vegan" with parameter "method=spearman" (Oksanen *et al.*, 2013).

Site frequency spectrum calculation for deletions and SNPs

Here our goal was to compare the SFS across deletions and SNPs called in ancient genomes. Because the ancient SNP genotypes are pseudo-haploidized, we performed the same pseudo-haploidization process on the deletion data set. For this, for any heterozygous call in the deletion data set, we randomly assigned either of the homozygous states, using the R "sample" function (i.e., we converted 1's to 0's or 2's with 50% probability). We then counted derived alleles at each locus, for deletions and for SNPs, and divided by the total number of genomes where an allele was observed at that locus (i.e., removing the missing data). We plotted the site-frequency spectrum analysis on both deletions and SNPs using R's "ggplot2" package geom_histogram function (Wickham, 2016). We also calculated the correlation between the deletion size in logarithmic scale and the frequency using R's "stats" package cor.test with method parameter set to "s" indicating Spearman's correlation (R Core Team, 2020).

Evolutionary conservation

To measure evolutionary conservation for genes that overlapped deletions, we retrieved non-synonymous (dN) and synonymous (dS) substitution rate estimates between human (GRCh37) and the mouse genome (GRCm38) per gene from Ensembl (v75) via the R package "biomaRt" (Durinck *et al.*, 2005). We queried 18,112 genes with dN, dS values and calculated the dN/dS ratio (or Ka/Ks) per gene. The ratio for genes with more than one dN or dS values were calculated as the mean dN or dS per gene. We then intersected our deletions with the genes with dN/dS values using BEDTools (Quinlan and Hall, 2010) and found 461 Ensembl (v75) human genes. Overall, 5% of the 9579 derived deletions overlapped with at least one gene, and among those deletions, each overlapped with an average of 1.33 genes. We then collected mouse-human dN/dS ratios (Methods) for these genes (n = 401, 0-0.77, median = 0.16, mean = 0.20). We divided the deletions in our data set into two groups by the deletion allele frequency per gene: high versus low frequency. We calculated the mean frequency among the 401 genes and set this value as a threshold for high and low frequency. The frequencies above the threshold were considered high and vice versa. We plotted the dN/dS ratios of the groups defined above using the R package "ggplot2" and the "geom_boxplot" function (Wickham, 2016).

Comparison with SIFT predictions

Here our goal was to study deleterious mutation loads per genome in the form of SIFT-predicted harmful SNPs and CONGA-predicted deletions, across the 56 ancient genomes. We used SIFT predictions available in Ensembl (v75) collected via the R package "biomaRt" (Durinck *et al.*, 2005, 2009). We retrieved SIFT predictions of "tolerated" and "deleterious" impact and SIFT scores for all 1000 Genomes human SNPs from Ensembl, and subsetted the African SNP set used for genotyping the ancient genomes. This resulted in 22,996 SNPs with SIFT predictions. Further, we calculated a ratio representing the total number of SIFT-predicted "deleterious" SNPs over the number of "tolerated" SNPs, for each of the 56 individuals. In addition, we calculated the total CONGA-predicted deletion length and the total number of genes overlapping CONGA-predicted deletions per individual, ignoring homozygous or heterozygous state. We plotted these three mutation load scores, i.e. SIFT-predicted deleterious/tolerated ratios per individual, the

number of affected genes, and the total deletion length, using R base function "plot" (Supplemental Fig. S17) (R Core Team, 2020). We further estimated pairwise correlations between the three scores, fitting the values into a linear model using the R "lm" function and calculating Spearman's rank correlation. We plotted the linear models using the R base function "pairs" (Supplemental Fig. S18B) (R Core Team, 2020).

Software Availability

CONGA is implemented in C programming language and its source code is available under BSD 3-clause license at https://github.com/asylvz/CONGA, as well as Supplemental Code. Simulated datasets and predictions of each tool can be accessed through Zenodo (10.5281/zenodo.5555990).

Competing interest statement

The authors declare no competing interests.

Acknowledgements

The authors would like to thank Gözde Zeliha Turan for her suggestions with mappability data and Kıvılcım Başak Vural for technical support. This work was supported by the ERC Consolidator grant "NEOGENE" (Project No.: 772390).

Author Contributions

AS developed and implemented the algorithm, performed simulations and down-sampling experiments. SSÇ and DK conducted technical and evolutionary analyses on real data. CA contributed to algorithm design. MS led the project and coordinated the activities. All authors contributed to editing the manuscript and participated in weekly discussions.

References

(2019). Picard toolkit. `https://broadinstitute.github.io/picard/`.

Abyzov, A. *et al.* (2011). CNVnator: an approach to discover, genotype, and characterize typical and atypical CNVs from family and population genome sequencing. *Genome Res*, **21**(6), 974–984.

Alkan, C. (2020). Automatic characterization of copy number polymorphism using high throuput sequencing. *Turkish Journal of Electrical Engineering & Computer Sciences*, **28**(1), 253–261.

Alkan, C. *et al.* (2009). Personalized copy number and segmental duplication maps using next-generation sequencing. *Nat Genet*, **41**(10), 1061–1067.

Alkan, C. *et al.* (2011). Genome structural variation discovery and genotyping. *Nat Rev Genet*, **12**(5), 363–376.

Allentoft, M. E. *et al.* (2015). Population genomics of bronze age eurasia. *Nature*, **522**(7555), 167.

Almarri, M. A. *et al.* (2020). Population structure, stratification, and introgression of human structural variation. *Cell*, **182**(1), 189–199.

Antonio, M. L. *et al.* (2019). Ancient rome: A genetic crossroads of europe and the mediterranean. *Science*, **366**(6466), 708–714.

Audano, P. A. *et al.* (2019). Characterizing the major structural variant alleles of the human genome. *Cell*, **176**(3), 663–675.

Becker, L. A. (2000). Effect size (es).

Bergström, A. *et al.* (2020). Origins and genetic legacy of prehistoric dogs. *Science*, **370**(6516), 557–564.

Bhattacharya, S. *et al.* (2018). Whole-genome sequencing of atacama skeleton shows novel mutations linked with dysplasia. *Genome research*, **28**(4), 423–431.

Boeva, V. *et al.* (2012). Control-FREEC: a tool for assessing copy number and allelic content using next-generation sequencing data. *Bioinformatics (Oxford, England)*, **28**, 423–425.

Broushaki, F. *et al.* (2016). Early neolithic genomes from the eastern fertile crescent. *Science*, **353**(6298), 499–503.

Chaisson, M. J. P. *et al.* (2015). Resolving the complexity of the human genome using single-molecule sequencing. *Nature*, **517**, 608–611.

Chaisson, M. J. P. *et al.* (2019). Multi-platform discovery of haplotype-resolved structural variation in human genomes. *Nature Communications*, **10**, 1784.

Chan, Y. F. *et al.* (2010). Adaptive evolution of pelvic reduction in sticklebacks by recurrent deletion of a pitx1 enhancer. *science*, **327**(5963), 302–305.

Chen, X. *et al.* (2016). Manta: rapid detection of structural variants and indels for germline and cancer sequencing applications. *Bioinformatics*, **32**, 1220–1222.

Chiang, D. Y. *et al.* (2009). High-resolution mapping of copy-number alterations with massively parallel sequencing. *Nat Methods*, **6**(1), 99–103.

Clark, A. G. *et al.* (2005). Ascertainment bias in studies of human genome-wide polymorphism. *Genome research*, **15**(11), 1496–1502.

Collins, R. L. *et al.* (2020). A structural variation reference for medical and population genetics. *Nature*, **581**(7809), 444–451.

Conrad, D. F. and Hurles, M. E. (2007). The population genetics of structural variation. *Nature genetics*, **39**(7), S30–S36.

Conrad, D. F. *et al.* (2010). Origins and functional impact of copy number variation in the human genome. *Nature*, **464**(7289), 704–712.

Cooper, G. M. *et al.* (2011). A copy number variation morbidity map of developmental delay. *Nature genetics*, **43**(9), 838–846.

de Barros Damgaard, P. *et al.* (2018a). 137 ancient human genomes from across the eurasian steppes. *Nature*, **557**(7705), 369–374.

de Barros Damgaard, P. *et al.* (2018b). The first horse herders and the impact of early bronze age steppe expansions into asia. *Science*, **360**(6396), eaar7711.

Derrien, T. *et al.* (2012). Fast computation and applications of genome mappability. *PloS one*, **7**(1), e30377.

Durinck, S. *et al.* (2005). Biomart and bioconductor: a powerful link between biological databases and microarray data analysis. *Bioinformatics*, **21**(16), 3439–3440.

Durinck, S. *et al.* (2009). Mapping identifiers for the integration of genomic datasets with the r/bioconductor package biomart. *Nature protocols*, **4**(8), 1184–1191.

Eisfeldt, J. *et al.* (2017). TIDDIT, an efficient and comprehensive structural variant caller for massive parallel sequencing data. *F1000Research*, **6**, 664.

ENCODE Project Consortium (2012). An integrated encyclopedia of DNA elements in the human genome. *Nature*, **489**, 57–74.

Foote, A. D. *et al.* (2021). Evidence of long-term purging of mutation load in killer whale genomes. *Biorxiv*.

Frantz, L. A. *et al.* (2020). Animal domestication in the era of ancient genomics. *Nature Reviews Genetics*, pages 1–12.

Fu, Q. *et al.* (2014). Genome sequence of a 45,000-year-old modern human from western siberia. *Nature*, **514**(7523), 445–449.

Gamba, C. *et al.* (2014). Genome flux and stasis in a five millennium transect of european prehistory. *Nature communications*, **5**(1), 1–9.

Girirajan, S. *et al.* (2011). Human copy number variation and complex genetic disease. *Annual review of genetics*, **45**, 203–226.

Gonzalez, E. *et al.* (2005). The influence of CCL3L1 gene-containing segmental duplications on HIV-1/AIDS susceptibility. *Science*, **307**(5714), 1434–1440.

González-Fortes, G. *et al.* (2017). Paleogenomic evidence for multi-generational mixing between neolithic farmers and mesolithic hunter-gatherers in the lower danube basin. *Current Biology*, **27**(12), 1801–1810.

Green, R. E. *et al.* (2010). A draft sequence of the Neandertal genome. *Science*, **328**(5979), 710–722.

Günther, T. *et al.* (2015). Ancient genomes link early farmers from atapuerca in spain to modern-day basques. *Proceedings of the National Academy of Sciences*, **112**(38), 11917–11922.

Haber, M. *et al.* (2017). Continuity and admixture in the last five millennia of levantine history from ancient canaanite and present-day lebanese genome sequences. *The American Journal of Human Genetics*, **101**(2), 274–282.

Haber, M. *et al.* (2019). A transient pulse of genetic admixture from the crusaders in the near east identified from ancient genome sequences. *The American Journal of Human Genetics*, **104**(5), 977–984.

Handsaker, R. E. *et al.* (2011). Discovery and genotyping of genome structural polymorphism by sequencing on a population scale. *Nat Genet*, **43**(3), 269–276.

Handsaker, R. E. *et al.* (2015). Large multiallelic copy number variations in humans. *Nat Genet*, **47**(3), 296–303.

Hardwick, R. J. *et al.* (2011). A worldwide analysis of beta-defensin copy number variation suggests recent selection of a high-expressing defb103 gene copy in east asia. *Human mutation*, **32**(7), 743–750.

Ho, S. S. *et al.* (2020). Structural variation in the sequencing era. *Nature Reviews Genetics*, **21**(3), 171–189.

Hofmanová, Z. *et al.* (2016). Early farmers from across europe directly descended from neolithic aegeans. *Proceedings of the National Academy of Sciences*, **113**(25), 6886–6891.

Hsieh, P. *et al.* (2019). Adaptive archaic introgression of copy number variants and the discovery of previously unknown human genes. *Science*, **366**(6463).

Jones, E. R. *et al.* (2015). Upper palaeolithic genomes reveal deep roots of modern eurasians. *Nature communications*, **6**(1), 1–8.

Jones, E. R. *et al.* (2017). The neolithic transition in the baltic was not driven by admixture with early european farmers. *Current Biology*, **27**(4), 576–582.

Jun, G. *et al.* (2015). An efficient and scalable analysis framework for variant extraction and refinement from population-scale dna sequence data. *Genome research*, **25**(6), 918–925.

Kahveci, F. and Alkan, C. (2018). Whole-genome shotgun sequence CNV detection using read depth. *Methods in molecular biology*, **1833**, 61–72.

Karakoc, E. *et al.* (2012). Detection of structural variants and indels within exome data. *Nat Methods*, **9**(2), 176–178.

Karimzadeh, M. *et al.* (2018). Umap and Bismap: quantifying genome and methylome mappability. *Nucleic Acids Research*, **46**(20), e120–e120.

Keller, A. *et al.* (2012). New insights into the tyrolean iceman's origin and phenotype as inferred by whole-genome sequencing. *Nature communications*, **3**(1), 1–9.

Kent, W. J. *et al.* (2002). The human genome browser at ucsc. *Genome research*, **12**(6), 996–1006.

Kılınç, G. M. *et al.* (2016). The demographic development of the first farmers in anatolia. *Current Biology*, **26**(19), 2659–2666.

Kircher, M. (2012). Analysis of high-throughput ancient dna sequencing data. In *Ancient DNA*, pages 197–228. Springer.

Koehler, R. *et al.* (2011). The uniqueome: a mappability resource for short-tag sequencing. *Bioinformatics*, **27**(2), 272–274.

Kothapalli, K. S. *et al.* (2016). Positive selection on a regulatory insertion–deletion polymorphism in fads2 influences apparent endogenous synthesis of arachidonic acid. *Molecular biology and evolution*, **33**(7), 1726–1739.

Kousathanas, A. *et al.* (2017). Inferring heterozygosity from ancient and low coverage genomes. *Genetics*, **205**(1), 317–332.

Krzewińska, M. *et al.* (2018). Ancient genomes suggest the eastern pontic-caspian steppe as the source of western iron age nomads. *Science advances*, **4**(10), eaat4457.

Layer, R. M. *et al.* (2014). LUMPY: a probabilistic framework for structural variant discovery. *Genome Biol*, **15**(6), R84.

Lazaridis, I. *et al.* (2014). Ancient human genomes suggest three ancestral populations for present-day europeans. *Nature*, **513**(7518), 409–413.

Levy-Sakin, M. *et al.* (2019). Genome maps across 26 human populations reveal population-specific patterns of structural variation. *Nature communications*, **10**, 1025.

Li, H. and Durbin, R. (2009). Fast and accurate short read alignment with Burrows-Wheeler transform. *Bioinformatics*, **25**(14), 1754–1760.

Li, H. *et al.* (2009). The sequence alignment/map format and SAMtools. *Bioinformatics*, **25**(16), 2078–2079.

Link, V. *et al.* (2017). Atlas: analysis tools for low-depth and ancient samples. *BioRxiv*, page 105346.

Llorente, M. G. *et al.* (2015). Ancient ethiopian genome reveals extensive eurasian admixture in eastern africa. *Science*, **350**(6262), 820–822.

Marciniak, S. and Perry, G. H. (2017). Harnessing ancient genomes to study the history of human adaptation. *Nature Reviews Genetics*, **18**(11), 659–674.

Marsden, C. D. *et al.* (2016). Bottlenecks and selective sweeps during domestication have increased deleterious genetic variation in dogs. *Proceedings of the National Academy of Sciences*, **113**(1), 152–157.

Martiniano, R. *et al.* (2017). The population genomics of archaeological transition in west iberia: Investigation of ancient substructure using imputation and haplotype-based methods. *PLoS genetics*, **13**(7), e1006852.

Mathieson, S. and Mathieson, I. (2018). Fads1 and the timing of human adaptation to agriculture. *Molecular biology and evolution*, **35**(12), 2957–2970.

McLean, C. Y. *et al.* (2011). Human-specific loss of regulatory dna and the evolution of human-specific traits. *Nature*, **471**(7337), 216–219.

Meyer, M. *et al.* (2012). A high-coverage genome sequence from an archaic denisovan individual. *Science*, **338**(6104), 222–226.

Miller, C. A. *et al.* (2011). ReadDepth: a parallel R package for detecting copy number alterations from short sequencing reads. *PloS one*, **6**, e16327.

Mittnik, A. *et al.* (2018). The genetic prehistory of the baltic sea region. *Nature communications*, **9**(1), 1–11.

Mu, J. C. *et al.* (2015). VarSim: a high-fidelity simulation and validation framework for high-throughput genome sequencing with cancer applications. *Bioinformatics*, **31**(9), 1469–1471.

Ng, P. C. and Henikoff, S. (2003). Sift: Predicting amino acid changes that affect protein function. *Nucleic acids research*, **31**(13), 3812–3814.

Nuttle, X. *et al.* (2016). Emergence of a homo sapiens-specific gene family and chromosome 16p11. 2 cnv susceptibility. *Nature*, **536**(7615), 205–209.

Oksanen, J. *et al.* (2013). Package 'vegan'. *Community ecology package, version*, **2**(9), 1–295.

Olalde, I. *et al.* (2014). Derived immune and ancestral pigmentation alleles in a 7,000-year-old mesolithic european. *Nature*, **507**(7491), 225–228.

Oliva, A. *et al.* (2021). Bwa-mem is not the best aligner for ancient dna short reads. *bioRxiv*.

Orlando, L. *et al.* (2021). Ancient dna analysis. *Nature Reviews Methods Primers*, **1**(1), 1–26.

Patterson, N. *et al.* (2012). Ancient admixture in human history. *Genetics*, **192**(3), 1065–1093.

Pedersen, J. S. *et al.* (2014). Genome-wide nucleosome map and cytosine methylation levels of an ancient human genome. *Genome research*, **24**(3), 454–466.

Perry, G. H. *et al.* (2007). Diet and the evolution of human amylase gene copy number variation. *Nature genetics*, **39**(10), 1256–1260.

Pockrandt, C. *et al.* (2020). Genmap: ultra-fast computation of genome mappability. *Bioinformatics*.

Prüfer, K. (2018). snpad: An ancient dna genotype caller. *Bioinformatics*, **34**(24), 4165–4171.

Quinlan, A. R. and Hall, I. M. (2010). BEDTools: a flexible suite of utilities for comparing genomic features. *Bioinformatics*, **26**(6), 841–842.

R Core Team (2020). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria.

Raghavan, M. *et al.* (2014). Upper palaeolithic siberian genome reveals dual ancestry of native americans. *Nature*, **505**(7481), 87–91.

Rasmussen, M. *et al.* (2010). Ancient human genome sequence of an extinct palaeo-eskimo. *Nature*, **463**(7282), 757–762.

Rasmussen, M. *et al.* (2014). The genome of a late pleistocene human from a clovis burial site in western montana. *Nature*, **506**(7487), 225–229.

Rausch, T. *et al.* (2012). DELLY: structural variant discovery by integrated paired-end and split-read analysis. *Bioinformatics*, **28**(18), i333–i339.

Reich, D. *et al.* (2010). Genetic history of an archaic hominin group from Denisova Cave in Siberia. *Nature*, **468**(7327), 1053–1060.

Renaud, G. *et al.* (2017). gargammel: a sequence simulator for ancient dna. *Bioinformatics*, **33**(4), 577–579.

Rogers, R. L. and Slatkin, M. (2017). Excess of genomic defects in a woolly mammoth on wrangel island. *PLoS genetics*, **13**(3), e1006601.

Rohland, N. *et al.* (2015). Partial uracil–dna–glycosylase treatment for screening of ancient dna. *Philosophical Transactions of the Royal Society B: Biological Sciences*, **370**(1660), 20130624.

Saitou, M. and Gokcumen, O. (2020). An evolutionary perspective on the impact of genomic copy number variation on human health. *Journal of molecular evolution*, **88**(1), 104–119.

Schubert, M. *et al.* (2016). Adapterremoval v2: rapid adapter trimming, identification, and read merging. *BMC research notes*, **9**(1), 1–7.

Sedlazeck, F. J. *et al.* (2018). Accurate detection of complex structural variations using single-molecule sequencing. *Nature methods*, **15**, 461–468.

Seguin-Orlando, A. *et al.* (2014). Genomic structure in europeans dating back at least 36,200 years. *Science*, **346**(6213), 1113–1118.

Shapiro, á. and Hofreiter, M. (2014). A paleogenomic perspective on evolution and gene function: new insights from ancient dna. *Science*, **343**(6169), 1236573.

Sikora, M. *et al.* (2019). The population history of northeastern siberia since the pleistocene. *Nature*, **570**(7760), 182–188.

Skoglund, P. and Mathieson, I. (2018). Ancient genomics of modern humans: the first decade. *Annual review of genomics and human genetics*, **19**, 381–404.

Smith, D. R. *et al.* (2008). Rapid whole-genome mutational profiling using next-generation sequencing technologies. *Genome Res*, **18**(10), 1638–1642.

Smith, S. D. *et al.* (2015). Grom-rd: resolving genomic biases to improve read depth detection of copy number variants. *PeerJ*, **3**, e836.

Smith, S. D. *et al.* (2017). Evolutionary adaptation revealed by comparative genome analysis of woolly mammoths and elephants. *DNA Research*, **24**(4), 359–369.

Soylev, A. *et al.* (2017). Toolkit for automated and rapid discovery of structural variants. *Methods*, **129**, 3–7.

Soylev, A. *et al.* (2019). Discovery of tandem and interspersed segmental duplications using high-throughput sequencing. *Bioinformatics*, **35**, 3923–3930.

Stankiewicz, P. and Lupski, J. R. (2010). Structural variation in the human genome and its role in disease. *Annu Rev Med*, **61**, 437–455.

Sudmant, P. H. *et al.* (2010). Diversity of human copy number variation and multicopy genes. *Science*, **330**(6004), 641–646.

Sudmant, P. H. *et al.* (2015a). Global diversity, population stratification, and selection of human copy-number variation. *Science*, **349**(6253).

Sudmant, P. H. *et al.* (2015b). An integrated map of structural variation in 2,504 human genomes. *Nature*, **526**(7571), 75–81.

The 1000 Genomes Project Consortium (2015). A global reference for human genetic variation. *Nature*, **526**(7571), 68–74.

Vieira, F. G. *et al.* (2016). Estimating ibd tracts from low coverage ngs data. *Bioinformatics*, **32**(14), 2096–2102.

Warnes, G. R. *et al.* (2020). *gplots: Various R Programming Tools for Plotting Data*. R package version 3.1.1.

Wickham, H. (2016). *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York.

Xie, C. and Tammi, M. T. (2009). Cnv-seq, a new method to detect copy number variation using high-throughput sequencing. *BMC bioinformatics*, **10**(1), 1–9.

Xue, Y. *et al.* (2008). Adaptive evolution of ugt2b17 copy-number variation. *The American Journal of Human Genetics*, **83**(3), 337–346.

Yaka, R. *et al.* (2021). Variable kinship patterns in neolithic anatolia revealed by ancient genomes. *Current Biology*, **31**(11), 2455–2468.

Yoon, S. *et al.* (2009). Sensitive and accurate detection of copy number variants using read depth of coverage. *Genome Res*, **19**(9), 1586–1592.

Zhang, F. *et al.* (2009). Copy number variation in human health, disease, and evolution. *Annual review of genomics and human genetics*, **10**, 451–481.

Zook, J. M. *et al.* (2020). A robust benchmark for detection of germline large deletions and insertions. *Nature Biotechnology*, pages 1–9.