1 ModelRevelator: Fast phylogenetic
2 model estimation via deep learning

Sebastian Burgstaller-Muehlbacher[1)5)*], Stephen M. Crotty[2)3)5)], Heiko A Schmidt[1)], Tamara
Drucks[1)] and Arndt von Haeseler[1)4)]
1) Center for Integrative Bioinformatics Vienna, Max Perutz Labs, University of Vienna and
Medical University of Vienna, Vienna BioCenter (VBC) 5, 1030 Vienna, Austria
2) School of Mathematical Sciences, University of Adelaide, Adelaide, SA 5005, Australia
3) ARC Centre of Excellence for Mathematical and Statistical Frontiers, University of Adelaide,
Adelaide, SA 5005, Australia
4) Bioinformatics and Computational Biology, Faculty of Computer Science, University of
Vienna, Währinger Straße 29, 1090 Vienna, Austria
5) These authors contributed equally to this work.
14
15 *Corresponding author: sebastian.burgstaller-muehlbacher@meduniwien.ac.at

16 Abstract

Selecting the best model of sequence evolution for a multiple-sequence-alignment

(MSA) constitutes the first step of phylogenetic tree reconstruction. Common approaches for

inferring nucleotide models typically apply maximum likelihood (ML) methods, with

discrimination between models determined by one of several information criteria. This requires

tree reconstruction and optimisation which can be computationally expensive. We demonstrate

that neural networks can be used to perform model selection, without the need to reconstruct

trees, optimise parameters, or calculate likelihoods.

We introduce ModelRevelator, a model selection tool underpinned by two deep neural

networks. The first neural network, NNmodelfind, recommends one of six commonly used

models of sequence evolution, ranging in complexity from Jukes and Cantor to General Time

Reversible. The second, NNalphafind, recommends whether or not a Γ--distributed rate

heterogeneous model should be incorporated, and if so, provides an estimate of the shape

parameter, α. Users can simply input an MSA into ModelRevelator, and swiftly receive output

recommending the evolutionary model, inclusive of the presence or absence of rate

heterogeneity, and an estimate of α.

We show that ModelRevelator performs comparably with likelihood-based methods and

the recently published machine learning method ModelTeller over a wide range of parameter

settings, with significant potential savings in computational effort. Further, we show that this

performance is not restricted to the alignments on which the networks were trained, but is

maintained even on unseen empirical data. We expect that ModelRevelator will provide a

valuable alternative for phylogeneticists, especially where traditional methods of model selection

are computationally prohibitive.

Keywords: Phylogenetic model estimation, phylogenetic inference, deep learning, machine

learning, artificial intelligence, phylogenetics, phylogenomics, rate heterogeneity across sites.

44 Introduction

Modelling the process of sequence evolution is a necessary step in carrying out

phylogenetic inference. Jukes and Cantor (Jukes and Cantor 1969) introduced the first model of

sequence evolution (JC), based on the assumptions that frequency of bases, and pairwise

substitutions between each of them, were equally likely. Since then modelling the evolutionary

process has been an area of continual and ongoing development and hundreds of models are

now available to choose from (K2P (Kimura 1980), F81 (Felsenstein 1981), HKY (Hasegawa et

al. 1985), TN93 (Tamura and Nei 1993), and GTR (Tavaré and Others 1986) to name a few).

Systematically discriminating between the available models is a problem that has been

approached in a variety of ways, including likelihood ratio tests, Bayes factors, and cross

validation. Endorsed by Posada and Buckley (Posada and Buckley 2004), the most common

current approach is to carry out maximum likelihood (ML) inference under a selection of different

models, then use an information criterion such as Akaike's Information Criterion (AIC), or the

Bayesian Information Criterion (BIC) (Posada and Crandall 1998; Johnson and Omland 2004;

Posada and Buckley 2004; Abascal et al. 2005; Posada 2008; Darriba et al. 2012;

Kalyaanamoorthy et al. 2017). Model selection software such as ModelFinder

(Kalyaanamoorthy et al. 2017) automate the process to a large extent by evaluating models

based on BIC (by default), and are employed as a matter of course as part of most phylogenetic

analyses. However, there is considerable discussion within the literature about the suitability of

information criteria as a discriminating tool within phylogenetics (Grievink et al. 2010; Jhwueng

et al. 2014; Seo and Thorne 2018; Susko and Roger 2020; Crotty and Holland 2022). Many of

the concerns raised in these articles amount to foundational assumptions of information-theory-

based model selection that are necessarily violated within a phylogenetic inference framework.

Unburdened by these foundational assumptions, a machine learning approach to the problem is

therefore immune to the inherent theoretical complications of the information theory approach.

Theoretical shortcomings aside, the rapid expansion of the size of multiple sequence

alignments (MSAs) typically available to empiricists means the computational cost of traditional

model selection methods is becoming increasingly prohibitive. Large phylogenomic alignments,

consisting of many concatenated genes, should not be assumed to have evolved

homogeneously. To address this, different models are often assigned to different sections of the

alignment (typically genes or codon positions). Methods like PartitionFinder (Lanfear et al. 2012;

Frandsen et al. 2015) accomplish this, but they require the repeated estimation of the

appropriate model, sometimes across thousands of genes (Faircloth et al. 2012; Lemmon et al.

2012; Jombart et al. 2014). Thus, model selection can become a computational bottleneck.

Although machine learning methods have found broad application in biology (Tarca et al.

2007; Kandoi et al. 2015; Leung et al. 2016; Kan 2017; Silva et al. 2019), within the field of

phylogenetics, they have thus far only been applied to a very limited extent (Tao et al. 2019;

Leuchtenberger et al. 2020; Suvorov et al. 2020; Zou et al. 2020). Further refining the scope to

model selection within phylogenetics, ModelTeller (Abadi et al. 2020), which utilises a random

forest-based machine learning approach, is the only current contribution, although it does not

focus primarily on model selection.

To address these issues, we have developed ModelRevelator, a machine learning

approach to the model selection problem that is based on neural networks with many layers

(deep learning) (LeCun et al. 2015), with the focus on finding the best model of sequence

evolution. Further, in the case that the alignment is best modelled incorporating a Γ-distributed

rates across sites component (Yang 1994), ModelRevelator provides an estimate of the shape

parameter. To show the applicability of deep learning in phylogenomics, we compare the results

offered by ModelRevelator to ModelFinder (which is representative of current standard practice)

as implemented in IQ-Tree (Nguyen et al. 2015; Minh et al. 2020). Using simulated alignments,

we assessed the performance of the two methods based on how often they correctly identified

the generative model, as well as the accuracy of topological inference carried out using their

recommendations. We find that ModelRevelator can estimate the model of sequence evolution

as well as the parameter α at a comparable accuracy to ModelFinder, with potential for

significant reduction in computational expense.

100 Methods

101 Empirical Lanfear dataset

For testing and evaluation of the neural networks and ML+BIC on empirical data, we

used a database of MSAs, collected from the literature by Rob Lanfear, and available at

https://github.com/roblanf/BenchmarkAlignments. This collection consists of protein and

nucleotide MSAs, from which we selected alignments consisting of DNA alignments of multiple

genes. These alignments originated from 31 publications, a full list of which can be found in the

supplementary material. We split the 31 multi-gene alignments by gene, resulting in 1,843

individual loci alignments, ranging from 3 to 4,836 taxa. Table 1 shows the distribution of trees

with different taxa, trees with 3 to 100 and 101 to 200 taxa being the most frequent trees in the

dataset. The length of the individual alignments range from 12bp to 11,049bp with a median

length of 261bp (see Table 2).

# of taxa	# of trees in bin
3 - 100	877
101 - 200	910
201 - 300	31
301 - 400	2
401 - 500	4
501 - 600	8
601 - 700	1
701 - 1000	1
1001 - 2000	4
2001 - 5000	5

113 *Table 1: Distribution of tree sizes in the empirical Lanfear dataset. Histogram with 200 bins.*

114 *Column '# of taxa' indicates the range of a tree size bin, column '# of trees in bin' indicates the*

115 *number of trees in each bin.*

# of bp	# of MSAs
12-100	50
101-200	483
201-300	548
301-400	231
401-500	166
501-600	91
601-700	75
701-1000	100
1001-2000	64
2001-4000	16
4001-12000	3

Table 2: Distribution of MSA length of original Lanfear MSAs. Bins for histogram = 200, Median

length: 261bp, Minimum length = 12bp, Maximum length = 11,049bp. Column '# of bp indicates

the range of MSA length bin, column '# of MSAs in bin' indicates the number of MSAs in each

bin.

We used stable IQ-Tree release 1.6.12 to carry out ML inference on the 1,843 loci

alignments under a GTR model of evolution. From the results of these analyses we constructed

distributions for the five relative substitution rate parameters (G<->T is fixed to a value of 1, with

the remaining rates expressed relatively), the empirical base frequency parameters, and the

internal and external edge length parameters. We fit splines to these distributions using the

AstroML Python package (VanderPlas et al. 2012), as shown in Supplementary Figures 1-3.

128 Simulation of training and test datasets:

We simulated all MSAs used for training and testing the neural networks using Seq-Gen

(Rambaut and Grassly 1997). We generated alignments using six models of sequence evolution

with continuous Γ-distributed rate heterogeneity across sites (Rhet): JC+G, K2P+G, F81+G,

HKY+G, TN93+G, and GTR+G; and their rate-homogeneous (Rhom) versions: JC, K2P, F81,

HKY, TN93 and GTR. We ensured that an equal number of training alignments were simulated

for each of the 12 models of sequence evolution considered.

We simulated trees by generating a random tree topology with 8, 16, 64, or 128 taxa. We then

added internal and external edge lengths drawn randomly from the edge length distributions

constructed from the Lanfear data. Depending on which model of sequence evolution was being

used to generate the MSA, we drew substitution rate and base frequency parameters as

required, from the appropriate Lanfear-based parameter distributions. For NNmodelfind, all

training MSAs were of length 1kbp. We also tried using 10kbp MSAs for training NNmodelfind

but this did not result in better performance compared to 1kbp MSA training data. For

NNalphafind, all training MSAs were of length 10kbp.

For simulating the 6 Rhet models (JC+G, K2P+G, K81+G, HKY+G, TN93+G and

GTR+G), we used a continuous Γ-distributed rate heterogeneity model of Seq-Gen with 17

distinct alpha parameter values (0.001, 0.01, 0.05, 0.1, 0.3, 0.5, 0.7, 1, 2, 3, 4, 5, 6, 7, 8, 9 and

10) (using the -a command line parameter). We generated an equal number of MSAs for each

of those individual alpha parameters.

To test NNmodelfind, NNalphafind, as well as ML approaches, a common test dataset

was created. This test dataset consisted of 8, 16, 64 and 128 taxa MSAs, and sequence lengths

of 100bp, 1kbp, 10kbp and 100kbp. For the 1kbp test dataset, we also generated MSAs with

256 and 1,024 taxa. For all combinations of taxa and sequence lengths, 512 MSAs were

generated for each Rhom model. For Rhet models, we generated 2,048 MSAs per Rhet model

and sequence length combination. These 2,048 MSAs were then divided among the 4 taxa

levels and then randomly distributed among the 17 distinct alpha parameter values, yielding, on

average, 30 MSAs per taxa level and distinct alpha parameter combination. This resulted in a

total of 98,304 MSAs in our test dataset.

159 Model selection, alpha estimation and tree reconstruction by ML:

Two different analyses have been performed using the classical ML approach, namely

model selection and parameter estimation.

For model selection, we ran ModelFinder as implemented in stable IQ-Tree release 1.6.12 but

restricted the pool of available models to the 12 models on which the networks were trained: JC,

K2P, F81, HKY, TN93, GTR, JC+G, K2P+G, F81+G, HKY+G, TN93+G, and GTR+G (using

options -mset JC,K2P,F81,HKY,TN,GTR and -mrate E,G). Furthermore, we avoided any

identical sequences to be discarded from the alignment using option -keep-ident. To infer rate

heterogeneity, we used discrete Γ-distribution approximation with 4 rate categories which is the

default in IQ-Tree for Γ models.

As the decision criterion, we used BIC as is default in IQ-Tree. To explicitly estimate the alpha

parameter, we ran ModelFinder for each alignment, but restricted the pool to include only the

heterogeneous models. We then took the reported alpha value from the best heterogeneous

model as our estimate of alpha.

According to the IQ-Tree documentation, IQ-Tree applies a lower limit of 0.02 for the

shape parameter alpha. To allow the estimation of lower alpha values we reset this limit to

0.0001 using the command line flag -amin 0.0001. For some alignments there were errors

caused by numerical issues especially for very low alpha values. We resolved these by re-

running with the -safe option as suggested by the error message of IQ-Tree.

In order to reconstruct trees for comparison, we ran IQ-Tree independently with the

model of sequence evolution chosen by ModelRevelator and ML+BIC respectively. If the model

chosen by ModelRevelator included heterogeneous rates then the alpha parameter was fixed to

the recommended value. If the model chosen by ML+BIC included heterogeneous rates then

the alpha parameter was optimised in the tree reconstruction process.

185   Data preprocessing for NNs:

To be able to use the variably-sized simulated MSAs as input for training and testing of

NNmodelfind and NNalphafind, we converted each alignment into a format of fixed-sized.

For NNmodelfind, we used summary statistics of sequence pairs of an MSA. To maximise the

information in the input, we decided to use 10,000 randomly drawn sequence pairs, ensuring

that the same sequence was not chosen for both sequences of a summary statistic to be

calculated. These 10,000 summary statistics consisted of 26 features each (substitution counts:

A-C, A-G, A-T, C-G, C-T, and G-T, in both directions = 12 features; invariant site counts: A-A, C-

C, G-G, T-T = 4 features; 4 nucleotide counts per sequence = 8 features; total transition count

and total transversion count = 2 features). This yields a total feature count for each MSA of

10,000 x 26. All of these summary statistics are normalised by the sequence length of the MSA.

For more efficient processing of the convolution layers of the ResNet-18, we reshaped these

input features into an input tensor of shape 40 x 250 x 26.

For NNalphafind, we generated normalised base composition profiles of 10,000 sites

and the 4 possible bases, yielding an input size of 10,000 x 4. We also experimented with

summary statistics incorporating column-wise transitions and transversion, however this yielded

worse performance than just base counts.

For both networks, for all MSAs which were smaller or larger than 10,000 positions, we

randomly over- or undersampled the MSA to achieve the required dimension for the input.

205   NNmodelfind architecture

Figure 1 shows the architecture of NNmodelfind. It is based on a ResNet-18 architecture

(He et al. 2015a), but with an adapted input strategy. The input, as described above, has

dimensions 40 x 250 x 26. We replaced the initial pooling layer of a ResNet-18 with 4 encoding

2D convolution layers, with 2x1 kernels and 32, 64, 96 and 96 channels. The output of the last

2D encoding layer is then passed to 4 standard ResNet-18 blocks with 3x3 convolutions and 96,

192, 384 and 768 channels. The output layer has 6 categories, one for each generative model

(JC, K2P, K81, HKY, TN93, GTR). The loss function used was a categorical cross entropy loss

function. We applied Batch Normalisation (Ioffe and Szegedy 2015) before each ReLu activation

function and L2 Regularisation (Cortes et al. 2012), for all convolution layers to improve ResNet-

18 training. Additional parameters used were a learning rate of 1×10^{-5}, Adam optimiser

(Kingma and Ba 2014) for gradient descent, He Normal initialisation (He et al. 2015b) for the

weights and zeros initialisation for biases.

Figure 1: Schematic of NNmodelfind. The architecture follows a ResNet-18, with a modified

input strategy.

NNalphafind architecture

As shown in figure 2, NNalphafind is a combination of 1D convolutions for feature

encoding and a bidirectional LSTM with an Attention layer (Raffel and Ellis 2015). The input

consists of profiles of 10,000 positions by 4 base frequencies. The 3 layers of 1D convolutions

have 256, 512 and 768 channels, followed by a bidirectional LSTM with 1,200 steps, a 1D

pooling layer with a pooling window of 4, and an Attention layer with a step dimension of 2,498.

NNalphafind has 2 outputs, a categorical output and a scalar output. The categorical output

estimates whether an MSA should be modelled with or without rate heterogeneity. The loss

function is also a categorical cross entropy loss function. The scalar output estimates the alpha

parameter, achieved by a mean absolute percentage error function.

Weights of NNalphafind were initialised using Glorot Uniform initialisation (Glorot and Bengio

2010) and biases were initialised with zeros.

Figure 2: Schematic of NNalphafind.

Training NNmodelfind and NNalphafind:

We trained NNmodelfind, as well as NNalphafind, with the training dataset described

above, using a batch size of 40 and a learning rate of 1×10^{-5} for both neural networks. For

NNmodelfind, we required 76 epochs for convergence and for NNalphafind, we required 341

epochs for convergence. We used Tensorflow 2.4 (Abadi et al. 2016) as a framework for

training and testing of our neural networks. As GPUs for training, we used Nvidia Tesla V100

with 32Gb of memory, or Nvidia RTX2080Ti with 11Gb of memory.

To avoid overfitting, we performed early stopping when:

1. there was no improvement in accuracy on the validation dataset for 5 epochs for

NNmodelfind and for 15 epochs for NNalphafind; and

2. the divergence of training and validation accuracy was not higher than 4% for

NNmodelfind and 6% for NNalphafind.

In total 242,688 MSAs were used to train the networks.

Testing NNmodelfind and NNalphafind:

For testing the neural networks, we used the datasets described earlier and the trained

models for NNmodelfind and NNalphafind. Testing was either performed using the Keras

predict() function or ONNXRuntime 1.6.0 (https://github.com/microsoft/onnxruntime).

ONNXRuntime is a dedicated neural network execution library for the open ONNX neural

network exchange format (https://onnx.ai/). In order to use ONNXRuntime, we first exported the

Keras/Tensorflow neural network graphs to the ONNX format using the tools keras2onnx and

tf2onnx of the Python package onnx 1.9.0.

Comparing ModelTeller and ModelRevelator:

For running ModelTeller, we downloaded the latest version from GitHub

(https://github.com/shiranab/ModelTeller, commit hash

897bd6925606416071dcf3c1a03422f8e7a4e7b7; ModelTeller trained models downloaded

2021-06-06) and followed the installation guidelines. Then, we ran ModelTeller on a subset of

(100bp, 1kbp and 10kbp MSAs) our common Lanfear test set MSAs, using the -m command

line parameter of ModelTeller to just provide the MSA files which should be processed. We then

took the top ranked model ModelTeller output for all further analysis. We also used the trees

which ModelTeller estimated with PhyML, which is distributed as an integral part of ModelTeller,

for comparison with ModelRevelator. The branch score distances as well as the Robinson-

Foulds distances were calculated using Treedist of the PHYLIP package

(https://evolution.genetics.washington.edu/phylip/).

Time measurements for ModelRevelator and ML:

For the neural networks, we performed all measurements using ONNXRuntime 1.6.0 for

CPUs, thus no GPU was used for inference. For comparison to single-threaded IQ-Tree, we

forced ONNXRuntime to only run on a single core by using the Linux tool *taskset*. All

benchmarks were run on the same machine equipped with two 32 core AMD Epyc 7551 CPUs

on the operating system OpenSuSE Linux 15.0.

All IQ-Tree analyses were run on the same hardware as the neural network runtime

measurements, using only one CPU core each. All runtime measurements for ModelRevelator

as well as ML+BIC were performed using a 10% representative subset of alignments sampled

from the test dataset. The reported runtimes are the averages of the measured runtimes.

279 Data availability

Python source code for executing ModelRevelator, generating training, validation and

test datasets and the Tensorflow implementations of NNmodelfind and NNalphafind of

ModelRevelator are available from https://github.com/cibiv/ModelRevelator/. NNmodelfind and

NNalphafind of ModelRevelator are also available in ONNX format in the same repository. Due

to the amount of data (240,000 MSAs of training data, 170,000 MSAs of test data, 603 GB in

total), the MSAs in phylip format and the corresponding tree files from the common test dataset

are available upon request from the authors.

ModelRevelator will also be made freely available as part of the forthcoming version of IQ-Tree

(http://www.iqtree.org),

289 Results

We introduce ModelRevelator, a machine learning-based approach to model selection

for phylogenetic inference. Users can input their MSAs to ModelRevelator. ModelRevelator will

then advise which model of sequence evolution should be used, whether a Γ-distributed rate

heterogeneity component should be included, and if so, an estimate of the shape parameter.

ModelRevelator consists of two neural networks which operate independently to provide model

recommendations that can be adopted to significantly accelerate inference time. The first

network, NNmodelfind, was trained to select a model of sequence evolution prior to

phylogenetic inference, thereby bypassing the computationally expensive procedure of

performing model selection via ML and information criteria. The second network, NNalphafind,

was trained to make recommendations with respect to rate heterogeneity, and its output is two-

fold. NNalphafind will first recommend whether the alignment is characteristic of substitution rate

heterogeneity, or whether a rate homogeneous model will suffice. If the network recommends

that a Γ-distributed rates across sites model is appropriate, it will then provide an estimate of the

shape parameter which can be incorporated into the inference. Both networks were trained on

simulated data based on empirical alignments. We show here that the networks have

comparable accuracy to traditional model selection methods, and have significant advantage in

terms of computational expense.

308   Generating testing and training data

In order to train our neural networks a large number of simulated multiple sequence

alignments (MSAs) were required. However, we were mindful that ultimately, we require the

neural networks to be useful tools for the analysis of empirical data, and thus we needed our

training MSAs to be broadly representative of empirical datasets. To this end we obtained a

large database of empirical MSAs made available to us by the Lanfear group of Australian

National University (https://github.com/roblanf/BenchmarkAlignments). From the Lanfear MSAs

we reconstructed trees via maximum likelihood inference with the stable IQ-Tree release 1.6.12,

under six different models of sequence evolution, with and without accounting for rate

heterogeneity. We thus obtained empirical distributions for internal edge lengths, external edge

lengths, substitution rates, and base frequency parameters. We fit cubic splines to these

empirical distributions, enabling us to sample random values as required.

Figure 3: Schematic illustration of the workflow followed to produce training and testing data for

the neural networks. (1) Edge lengths, substitution rates, and base frequencies are inferred

using maximum likelihood for 1,842 empirical MSAs, to form empirical distributions of these

parameters. (2) For the specified number of taxa a random tree topology is generated following

a Yule process. (3) Edge lengths for the tree are drawn randomly from the distribution of internal

and external edges obtained in (1). (4) For a given substitution model, the appropriate model

parameters are drawn from the distributions obtained in (1). (5) For a given alignment length an

MSA is simulated based on the tree and model of sequence evolution obtained from (3) and (4)

respectively, using the program seq-gen.

We then generated random tree topologies of varying sizes, and allocated edge lengths

to these topologies by randomly sampling from the external and internal edge distributions. We

also constructed models of sequence evolution by randomly sampling from the substitution rate

and base frequency distributions. These tree topologies and substitution models were then used

as input to Seq-Gen (Rambaut and Grassly 1997), in order to generate MSAs of 1kbp length for

training of the neural networks. We also generated MSAs incorporating the continuous-Γ model

of rate heterogeneity, with alpha parameters ranging from 0.001 (extreme rate heterogeneity) up

to 10 (mild rate heterogeneity). Testing data was generated in essentially the same way,

although we tested a wider range of alignment sizes, ranging from 100bp up to 100kbp.

Figure 3 illustrates the procedure we adopted for generating alignments. A fuller account of the

precise parameter settings and volume of MSAs generated can be found in the methods

section.

344   Estimating the evolutionary model

Our first objective was to train a neural network, which we have called NNmodelfind, to

successfully estimate the correct model of sequence evolution. As described in the methods

section, we trained NNmodelfind on a wide variety of simulated MSAs. The training MSAs were

generated according to one of 6 models of sequence evolution (JC, K2P, F81, HKY, TN93, and

GTR). We incorporated an equal number of MSAs that were simulated under rate

homogeneous (Rhom) and rate heterogeneous (Rhet) conditions. Rate heterogeneous

alignments were simulated with the shape parameter, alpha, taking one of 17 potential values

between 0.001 and 10. MSA size was either 8, 16, 64, or 128 taxa, with each size equally

represented in the training data. The length of all training MSAs was 1kbp. Experiments using

training data of 10kbp length did not show improvements in NNmodelfind accuracy over 1kbp

training data.

Having trained NNmodelfind, we generated test MSAs to evaluate its performance. Test

MSAs were generated using the same parameter settings as the training MSAs, with additional

MSAs generated with higher numbers of taxa (256, and 1024), and different sequence lengths

(100bp, 10kbp, and 100kbp) in order to evaluate the generalisability of NNmodelfind.

By way of comparison we used a traditional method of model selection via maximum

likelihood inference to choose the model of sequence evolution for each test MSA. We used the

ModelFinder approach within IQ-Tree, with BIC set as the discriminating criterion. We refer to

this method of model selection as ML+BIC.

Figure 4 shows the accuracy for Rhom test MSAs of length 1kbp. Figure 4a displays the

accuracies separately for the individual models and taxa levels. Figure 4b shows confusion

matrices for each method and taxa level, detailing the distribution of the inferred model for each

true model. Figure 5 shows the analogous information to Figure 4, for Rhet test MSAs. Overall,

Figures 4 and 5 indicate that NNmodelfind and ML+BIC are able to estimate the generative

model of sequence evolution with similar accuracy. There are modest differences between the

two methods, for example ML+BIC is more accurate when the true model is GTR or TN93,

whereas NNmodelfind is more accurate when the true model is F81 or HKY.

Figure 4: Model selection accuracy of NNmodelfind and ML+BIC on 1,000bp long Rhom MSAs.

(A) Blueish colours indicate results from NNmodelfind, reddish colours indicate results from

ML+BIC. Darkening bars distinguish increasing number of taxa from left to right (8, 16, 64, 128,

256 and 1024). (B) Confusion matrices for NNmodelfind and ML+BIC. Entries along the

diagonal indicate the percentage of alignments for which the correct model was identified.

Figures 4b and 5b show the confusion matrices associated with the 1kbp test

alignments. The confusion matrices reveal an interesting phenomenon in relation to the

performance of ML+BIC. For low numbers of taxa, when ML+BIC infers the incorrect model, it

almost exclusively selects a model of lower complexity than the true model. Conversely, when

the MSAs contain a high number of taxa, ML+BIC tends to err in the direction of more complex

models. This is likely a result of the fact that as the number of taxa increases, the log likelihood

scores grow and the influence of the penalty term in the BIC formula is reduced. Thus ML+BIC

tends to more complex models as the number of taxa increases. By way of comparison, the

error structure displayed by NNmodelfind does not show any strong pattern of preference for

models of lower or higher complexity, and this appears to be the case independent of the

number of taxa in the alignment. This is likely a result of the fact that the input size of

NNmodelfind is fixed and so increasing the number of taxa does not influence the error

structure.

Figure 5: Model selection accuracy of NNmodelfind and ML+BIC on 1,000bp long, Rhet MSAs.

(A) Blueish colours indicate results from NNmodelfind, reddish colours indicate results from

ML+BIC. Darkening bars distinguish increasing number of taxa from left to right (8, 16, 64, 128,

256 and 1024). (B) Confusion matrices for NNmodelfind and ML+BIC. Entries along the

diagonal indicate the percentage of alignments for which the correct model was identified.

403 Generalisation of NNmodelfind

Although NNmodelfind was trained strictly on MSAs of length 1,000bp, if it is to be of use

to empiricists then it must be reasonably generalisable on MSAs of various lengths. To

investigate its capabilities in this regard we generated test alignments that were both shorter

(100bp) and longer (10kbp and 100kbp) than the training alignments. Supplementary Figures 4 -

9 show the performance of NNmodelfind and ML+BIC for these data, in the same format as

Figures 4 and 5.

For short sequences of 100bp, the performance of NNmodelfind is poor for all models

except GTR. The confusion matrices suggest that NNmodelfind selects GTR for most MSAs,

independent of the model used to generate the alignment. Conversely, ML+BIC performs poorly

for more complex models such as GTR, but is very reliable for simpler models such as JC and

K2P. The confusion matrices suggest that ML+BIC has a tendency to select a simple model

regardless of the model used to generate the alignment. The poor performance of both methods

is likely a reflection of the high amount of stochastic noise within the short datasets, and is not

unexpected. The performance of both ML+BIC for long alignments of 10kbp and 100kbp was

excellent. Supplementary Figures 8 and 9 show that for 100kbp MSAs, ML+BIC identified the

generative model with accuracies approaching 100%, across all taxa and model combinations.

This is not unexpected, as ML is known to be statistically consistent (Truszkowski and Goldman

2016), and we would therefore expect ML+BIC to perform well for very long sequences.

NNmodelfind however saw no appreciable improvement for these longer sequences. The rate at

which NNmodelfind correctly inferred the generative model was similar for 10kbp and 100kbp as

it was for 1,000bp. One obvious explanation for this observation is that, irrespective of the actual

length of the MSA, the input size for NNmodelfind is fixed. Thus, for long alignments,

NNmodelfind samples sites from the alignment up to the required input size, and therefore does

not make full use of all the information contained within the alignment.

In addition to generalising over a wide range of sequence lengths, the performance of

NNmodelfind on varying numbers of taxa is also of interest. NNmodelfind was trained on MSAs

which ranged in size from 8 to 128 taxa. To investigate whether the performance of

NNmodelfind could be extrapolated to larger datasets, we simulated test MSAs with 256 and

1024 taxa, using the parameters estimated from the Lanfear MSAs as before. The results are

displayed in Figures 4 and 5. Figures 4a and 5a show that the performance of NNmodelfind is

not compromised by increasing the number of taxa beyond that used to train the network. For all

generative models, NNmodelfind identified the correct model at rates as good as or slightly

higher than for the smaller MSAs. For ML+BIC however, increasing taxa had a detrimental

effect on the success rate when the generative model was F81, HKY, and to a lesser extent

TN93, both with and without rate heterogeneity. The confusion matrices in Figures 4b and 5b

suggest that with these generative models, ML+BIC tended to select more complex models,

most often choosing GTR.

444   Estimating the presence and degree of rate heterogeneity

The assumption that all sites in an MSA mutate at the same rate has long been regarded

as biologically implausible. Rate heterogeneity has become an essential component of models

of sequence evolution, and is typically modeled by the discrete Γ distribution (Yang 1994). The

alpha parameter of the Γ distribution determines its shape and thus the extent of rate

heterogeneity. In conjunction with NNmodelfind, a neural network which can accurately estimate

the alpha parameter could further expedite phylogenetic reconstruction. We trained a second

neural network, NNalphafind, to first estimate whether a rate homogeneous model was

appropriate for the MSA, and if not, to then estimate the alpha parameter of the Γ-distributed

rate heterogeneity component.

As described in the methods section, NNalphafind was trained on MSAs containing 8,

16, 64 and 128 taxa. Each training MSA was 10kbp long, as opposed to the 1kbp MSAs that

were used to train NNmodelfind. NNalphafind was tested on the same test MSAs simulated to

test NNmodelfind, but for clarity we reiterate the simulation procedure here with the added detail

of the alpha parameter levels. The generative models of sequence evolution used were JC,

K2P, F81, HKY, TN93, and GTR. The amount of rate heterogeneity in the MSAs was varied by

controlling the rate parameter, alpha. In total there were 17 levels of rate heterogeneity,

represented by 17 distinct alpha values (0.001, 0.01, 0.05, 0.1, 0.3, 0.5, 0.7, 1, 2, 3, 4, 5, 6, 7, 8,

9 and 10). Small values of alpha correspond to a high degree of rate heterogeneity, whereas

large values of alpha correspond to a low degree of rate heterogeneity. With 4 taxa levels, 6

generative models, 4 sequence length levels, and 17 levels of rate heterogeneity, there were 4 x

6 x 4 x 17 = 1632 parameter combinations. For each of these parameter combinations we

simulated 30 test MSAs.

Preliminary analysis suggested that there was no relationship between the generative

model of sequence evolution and the accuracy of the alpha inference. Therefore, for simplicity,

we did not stratify the results by generative model. This meant we had 1632 / 6 = 272 parameter

combinations of interest, with each parameter combination having 180 (30 MSAs for each of the

6 different generative models) test MSAs available to evaluate performance. For each of the

272 parameter combinations we calculated the mean alpha value inferred by NNalphafind, and

also by ML+BIC. Given the range of true alpha values spanned several orders of magnitude, to

enable a simple comparison we calculated the ratio of the mean inferred alpha values and the

true alpha values. A ratio of 1 would therefore correspond to perfect inference (on average),

while scores above or below 1 would correspond respectively to an overestimation or

underestimation of the true alpha. The performance of the two methods at estimating the true

value of alpha in the generative models are summarised in heatmap form in Figure 6. The

colour scheme of the heatmap distinguishes between good inference (white), underestimation

(grey), and overestimation (red). In general, the lighter the shading the better the inference of

alpha.

Figure 6 indicates that NNalphafind generally performs better than ML+BIC at estimating

the true alpha value used to generate the data. NNalphafind was able to accurately infer the

true alpha, particularly when alpha was less than 1, indicating strong rate heterogeneity.

Conversely, ML+BIC performs particularly poorly for low alpha values (< 0.3) and performance

in this range is not strongly improved with increasing sequence length. Interestingly, the

performance of NNalphafind does clearly improve as sequence length increases, in contrast to

the performance of NNmodelfind. This is likely due to the fact that the input size of NNalphafind

is larger, and the network was trained on 10kbp alignments, as opposed to 1kbp alignments for

NNmodelfind. As such NNalphafind has the capacity to utilise the additional information in the

longer test MSAs.

Generalisation of NNalphafind

As with NNmodelfind, the results indicate that NNalphafind also generalises well to

sequence lengths that it was not trained on. NNalphafind was trained on 10kbp alignments, and

although its performance does deteriorate somewhat for 1kbp alignments, and then further for

100bp alignment, this is to be expected considering the comparative lack of information

contained within these shorter alignments. The same effect is evident in the performance of

ML+BIC and, regardless of sequence length, NNalphafind is always more accurate for low

values of alpha, and similarly accurate to ML+BIC for higher alphas. Figure 6 does not indicate

any parameter combinations where NNalphafind is clearly inferior to ML+BIC (See

supplementary fig. 10 for mean squared error of inferred alphas).

Figure 6: Ratio of mean inferred alpha value and true alpha value, stratified by inference method

(ML+BIC or NNalphafind), number of taxa (8, 16, 64, and 128), sequence length (100bp, 1kbp,

10kbp, and 100kbp), and true alpha value (17 levels ranging from 0.001 (very strong

heterogeneity) up to 10 (very weak heterogeneity)). Values close to 1 indicate accurate

inference. Colour scale indicates degree of bias in estimation. A ratio of 5 indicates a five-fold

overestimation of alpha, a ratio of 0.2 indicates a five-fold underestimation of alpha.

NNalphafind also generalised well to higher numbers of taxa, although perhaps not as well as

NNmodelfind. NNmodelfind saw no drop in performance when tested on 256-taxon and 1024-

taxon alignments, whereas the accuracy of NNalphafind's estimates was increasingly

compromised with higher taxa. That said, even at high taxa levels NNalphafind outperformed

ML+BIC for small alpha values, and was similarly accurate elsewhere.

Influence of Model Selection on Phylogenetic Inference

The primary goal of phylogenetic inference is to reconstruct accurate trees. In order to

compare the performance of ModelRevelator to ML+BIC, we reconstructed trees using the

models recommended by the two methods. When reconstructing trees using the output of

ModelRevelator, we fixed the alpha parameter (when rate heterogeneity was recommended) to

the value estimated by NNalphafind, rather than allowing it to be optimised. For each MSA, we

then compared the trees inferred via ModelRevelator and ML+BIC to the tree used to simulate

the alignment. For this, we calculated the normalised Robinson-Foulds distances (Robinson and

Foulds 1981) between the three trees. Figure 7 shows that when comparing the Robinson-

Foulds distances of the simution tree (T_{SIM}) vs the reconstructed trees ($\hat{T}_{\text{NN}}$ and $\hat{T}_{\text{BIC}}$ for

ModelRevelator and ML+BIC respectively), we observed similar distributions for both methods.

Furthermore, Figure 7 also shows that the reconstructed trees are typically much closer to each

other than they are to the simulation trees. This effect is most obvious for short sequences, with

the difference diminishing as sequence length increases. Thus, reconstructed trees, irrespective

of the reconstruction method, appear more in concordance with each other than they are with

the generative trees that were used to simulate the alignment, pointing to the same type of error

being made by both model estimation methods. An alternative viewpoint would be that both

methods are equally hindered by stochastic variation in the simulation process, resulting in

inaccurate tree reconstruction, independent of the model chosen by each method. Reinforcing

this view, Figure 7 clearly indicates that sequence length is a strong indicator of the accuracy of

tree reconstruction.

Figure 7: Estimating concordance in tree reconstruction by calculating the normalised Robinson-

Foulds distances of trees reconstructed using the model recommended by ModelRevelator

($\hat{T}_{NN}$) or ML+BIC ($\hat{T}_{BIC}$), and comparing these results to the trees used to simulate the MSAs

(T_{SIM}). Results for MSAs of length 100bp, 1kbp and 10kbp are shown in the top, middle and

bottom panel, respectively.

Generalisation to unseen empirical alignments

In addition to generalisation towards large numbers of taxa in an MSA, we also wanted

to test generalisation of ModelRevelator to other empirical datasets. This is of obvious practical

relevance, but is also important as generalisation of neural networks to potentially differently

distributed test datasets is a topic of constant discussion (Ganin and Lempitsky 2015; Sagawa

et al. 2019). We used 6,453 MSAs from the original PANDIT dataset (Whelan et al. 2006) to

perform parameter estimation and tree reconstruction by ML under a GTR+G model, with IQ-

Tree. Supplementary Figures 1 to 3 show the distributions of the edge length, substitution rate,

and base frequency parameters for both the Lanfear and PANDIT datasets. The parameters are

clearly differently distributed between the two datasets, most notably in regard to the edge

lengths.

For each PANDIT MSA, using the inferred tree and model parameters (including the

shape parameter, alpha), we then used Seq-Gen to simulate 10 MSAs (with GTR+G as the

generative model) of the same length as the PANDIT MSA, creating 64,530 simulated PANDIT-

type MSAs in total. On these PANDIT type MSAs we performed model estimation using both

ML+BIC and ModelRevelator. Figure 8 shows a concordance matrix for the results of model

selection with the two methods. Overall, ML+BIC inferred the correct model of GTR+G in 69% of

alignments, compared to just 61% for ModelRevelator. To investigate these results in more

depth, we compare the two methods on three measures: (1) the binary determination of whether

a rate heterogeneous model should be employed; (2) the decision of which of the six models of

sequence evolution should be adopted; and (3) the resulting topological accuracy of trees

inferred.

With regard to the recommendation to include a rate heterogeneous component in the

model, ML+BIC has performed better than ModelRevelator on these alignments. ML+BIC

correctly recommended rate heterogeneity in approximately 97% of alignments, compared to

approximately 79% for ModelRevelator. This means ModelRevelator is more likely than ML+BIC

to make a Type II error, that is to fail to detect the true presence of rate heterogeneity in the

data. It is worth considering here that rate heterogeneity is modelled very efficiently by the Γ

distribution, at a cost of only one parameter. This means the penalty in the BIC calculation is

quite small, but it gives increased flexibility to the model to fit more of the variability in the data

(whether that variability be phylogenetic signal or stochastic noise). The resulting increase in

likelihood is likely to dwarf the small penalty and result in an improved BIC score. We expect

that if we generated a complementary cohort of alignments without the rate heterogeneity

component, compared to ModelRevelator ML+BIC would have made more Type I errors, that is,

falsely detecting the presence of rate heterogeneity in the data. We chose not to do this

however, primarily because it is commonly recognised that rate homogeneous models are not

expected to provide a good fit to empirical alignments. One can also envisage that the signal for

rate heterogeneity would not have been strong in many alignments, due to the short sequence

lengths in the PANDIT data, and possible high alpha values in some datasets (corresponding to

weak rate heterogeneity).

ML+BIC	JC	K2P	F81	HKY	TN93	GTR	JC+G	K2P+G	F81+G	HKY+G	TN93+G	GTR+G	ModelRevelator total
JC	0.01	0.0	0.02	0.0	0.01	0.15	0.0	0.0	0.01	0.01	0.0	0.07	0.28
K2P	0.01	0.01	0.0	0.02	0.02	0.34	0.0	0.01	0.0	0.01	0.01	0.13	0.56
F81	0.0	0.0	0.08	0.01	0.01	0.18	0.0	0.0	0.01	0.0	0.0	0.07	0.36
HKY	0.0	0.0	0.03	0.06	0.06	0.43	0.0	0.0	0.0	0.03	0.01	0.15	0.77
TN93	0.0	0.0	0.01	0.0	0.02	0.16	0.0	0.0	0.0	0.0	0.01	0.07	0.27
GTR	0.0	0.0	0.0	0.0	0.01	0.59	0.0	0.0	0.0	0.0	0.0	0.14	0.74
JC+G	0.05	0.0	0.05	0.0	0.01	0.25	0.04	0.0	0.08	0.01	0.0	0.42	0.91
K2P+G	0.17	0.1	0.07	0.06	0.06	1.5	0.44	0.56	0.25	0.35	0.4	5.69	9.65
F81+G	0.01	0.0	0.24	0.01	0.01	0.35	0.01	0.0	0.26	0.01	0.02	0.35	1.27
HKY+G	0.06	0.02	0.29	0.35	0.23	2.23	0.09	0.06	0.93	1.47	0.53	5.42	11.68
TN93+G	0.03	0.01	0.06	0.03	0.13	0.58	0.04	0.04	0.3	0.18	0.74	2.28	4.42
GTR+G	0.87	0.04	2.16	0.13	0.2	8.12	2.02	1.14	5.34	1.99	1.17	45.82	69.0
ML+BIC total	1.21	0.18	3.01	0.67	0.77	14.88	2.64	1.81	7.18	4.06	2.89	60.61	100.0

ModelRevelator

Figure 8: Concordance matrix of ModelRevelator and ML+BIC estimates for MSAs simulated under PANDIT trees and parameters. The generative model for all MSAs was GTR+G. Column and row sums indicate proportion of alignments inferred for each model by ModelRevelator and ML+BIC respectively.

With respect to the recovered model of sequence evolution (ignoring whether or not rate

heterogeneity was recommended), ModelRevelator recovers the correct GTR-model for 75.49%

of alignments, whereas ML+BIC recovers the correct model for 69.74% of alignments. However,

the intersection of these groups, where both methods identified GTR, amounts to only 54.67%

of the alignments. This means that the correct generative model was solely identified by

ModelRevelator in 20.85% of alignments, and solely identified by ML+BIC in 15.08% of

alignments. Interestingly, the two methods clearly diverge on the type of error they make when

the alternate method is correct. When NNmodelfind is solely correct, ML+BIC predominantly

selects K2P or HKY, and to a lesser extent TN93. These are all models which contain

differential pairwise substitution rates between nucleotides. Conversely, when ML+BIC is solely

correct ModelRevelator predominantly selects F81 or JC, models that assume the same

pairwise substitution rates between all nucleotides.

With respect to topological inference, we again calculated the normalised Robinson-

Foulds distances between the simulation tree, T_{SIM}, and the trees inferred under the models

selected by ModelRevelator and ML+BIC, $\hat{T}_{\text{NN}}$ and $\hat{T}_{\text{BIC}}$ respectively. As before, where

ModelRevelator recommended the inclusion of a rate heterogeneous model, the estimated

alpha parameter was fixed during the inference, so that only other model parameters and edge

lengths were optimised. In order to more clearly visualise any difference between the methods,

we omitted the alignments for which both methods resulted in the same topology (64.4%). This

left 22,990 (35.6%) alignments for which the two methods returned different trees. Figure 9

displays boxplots of normalised Robinson-Foulds distances for these alignments. The boxplots

show that the results are similar between the two methods, although a marginal advantage to

using ModelRevelator over ML+BIC is observed as sequence length increases. Given the fact

that the PANDIT datasets were dissimilar to the Lanfear training data (in terms of distribution of

generating parameters), this is a very encouraging sign that ModelRevelator may perform well

on new empirical alignments generally.

Figure 9: Robinson-Foulds distances to the simulation tree for the PANDIT-based simulations.

Only MSAs for which use of ModelRevelator and ML+BIC led to discordant tree reconstructions

were included. MSAs were binned into three groups according to sequence length. MSAs

shorter than 100bp were omitted.

Comparing ModelRevelator to ModelTeller

ModelTeller (Abadi et al. 2020) is another recent, machine learning based approach for

model selection, based on random forests. We performed a comparison of ModelTeller and

ModelRevelator using the Lanfear test data (for details on the test data, see Methods), to see

how accurately each method was able to recover the model used to simulate an alignment. As

ModelTeller supports 24 models of sequence evolution (JC, K2P/K80, F81, HKY, SYM, GTR,

with modifications +I, +G, +I+G) and ModelRevelator supports 12 models of sequence

evolution, for our comparison, we chose the intersection of what is supported by both methods

(10 models of sequence evolution). When comparing ModelTeller estimates to the true model of

sequence evolution of the simulated data, we found that ModelTeller rarely returned the correct

model of sequence evolution (Fig. 10; Supplementary fig. 11-14). Furthermore, the confusion

matrices show a strong dependency on the number of taxa in the MSAs (Supplementary fig. 11-

14), as the number of taxa increases so does the complexity of the models recommended by

ModelTeller.

Figure 10: Results for ModelTeller on our Lanfear test data of 100bp, 1kbp and 10kbp MSAs.

The rows show the true simulation model of the Lanfear test data and the columns show the

percent of alignments that ModelTeller estimated each model. The final column displays the

number of alignments for which ModelTeller analysis failed.

Figure 10 also shows that there is very little consistency in the models recommended by

ModelTeller. In fact, the greatest success rate in correctly identifying the simulation model came

for GTR-simulated alignments, at just 6.17%. No particular error patterns are obvious, rather the

models chosen by ModelTeller appear to be somewhat random. It is important to make clear the

distinction between the two methods at this point. ModelRevelator is trained to identify the

model that best fits the data. On the other hand, ModelTeller aims to choose the model that

leads to the most accurate branch length estimates. It makes no claim on being able to recover

the model used to simulate the data. Therefore, its failure to reliably do so is not unexpected

and should not be viewed as a criticism of the method's performance. The two methods have

different goals, and this should be kept in mind when making comparisons between them. With

this in mind we further compared the two methods based on the accuracy of the trees (in terms

of both topology and branch length estimates) that are inferred using the recommended models.

For topological accuracy we compared the normalised Robinson-Foulds distances between the

simulation tree (T_{SIM}) and the trees inferred under models recommended by ModelTeller ($\hat{T}_{MT}$)

and ModelRevelator ($\hat{T}_{NN}$). Similarly, to compare branch length estimates we calculated the

branch score distance (Kuhner and Felsenstein 1994) instead of the normalised Robinson-

Foulds distance. Supplementary Figures 15 and 16 indicate that both methods are similarly

accurate with respect to both topology and branch length estimates.

These results indicate that while ModelTeller and ModelRevelator both lead to

comparable tree reconstruction and branch length estimates (for these data at least), only

ModelRevelator is able to infer the substitution model used to simulate the data to a reasonable

degree of accuracy.

671   Time measurements for ModelRevelator vs ML+BIC:

Given a fixed input size, the computational expense of inference using a trained neural network

is only dependent on the size of the network (number of parameters and operations).

Consequently, the time required for performing inference with NNmodelfind and NNalphafind is

independent of alignment size. Considering ModelRevelator in its entirety however, the same

cannot be said. Prior to carrying out inference with the networks, the MSA needs to be

preprocessed in order to convert it into the correct format for input. As described in the methods

section, this entails calculating summary statistics for randomly sampled taxon pairs, and the

computation cost of this step grows with sequence length. By comparison, computation time for

ML+BIC theoretically grows linearly with sequence length, and exponentially with number of

taxa in the alignment. In Figure 11, we show the computation time for ModelRevelator (MSA

preprocessing + NNmodelfind inference + NNalphafind inference) and the ML+BIC method.

Figure 11: Mean computation time for ModelRevelator (MR) (MSA preprocessing +

NNmodelfind + NNalphafind) vs ML+BIC (BIC) (full model estimation, including rate parameter

estimation).

We observe that for small MSAs (100bp to 1kbp and 8 to 16 taxa), ML+BIC is typically

faster than ModelRevelator, but the difference is somewhat negligible. For large alignments

(100kbp and 128 taxa) ModelRevelator is approximately 14 times faster than ML+BIC. In a real

world application setting, highly parallel neural network inference would be performed on a GPU

or several CPU cores. Also, for partition models, neural network batch inference would allow for

inference of many partitions at the same time.

Discussion

The neural network-based ModelRevelator appears to perform comparably to the well-

established approach of using ML inference and an information criterion (in this case BIC) to

discriminate between models. Phylogenetic estimation was found to marginally improve using

the neural networks compared to ML+BIC, with the additional benefit of significant potential

savings in computation time, depending on the size of the alignment.

Encouragingly, both neural networks which underpin ModelRevelator were found to

generalise well when tested on alignments that differed to those on which they were trained. No

appreciable deterioration in performance was observed when performing estimation on longer

sequences, or with larger numbers of taxa. Although we observe that, compared to ML+BIC,

NNmodelfind does not extract information as well from longer alignments, this does not have an

impact on tree topology. Additionally, our method outperformed ML+BIC (in terms of accuracy of

phylogenetic reconstruction) when tested on the PANDIT alignments, a set of empirical

alignments that the networks had not seen during training. This finding is of particular interest,

as it is an indication that ModelRevelator can be used with confidence by the community more

broadly.

One area in which we envisage a particular benefit of our approach is in conjunction with

partition models. Large alignments are often partitioned by gene, and/or codon position, into

hundreds or even thousands of independent blocks. PartitionFinder (Lanfear et al. 2012) relies

on information criteria to merge blocks that can be effectively modelled together, and selects

models of sequence evolution to be applied to each block. Selecting a model on a large number

of blocks can be accomplished efficiently by NNmodelfind running on a GPU, but ML+BIC would

require parallelisation on available CPU cores. Depending on the hardware available, it is likely

that the ML+BIC would be significantly slower for large projects.

Before deciding on the final architecture for NNmodelfind and NNalphafind, we experimented

widely with a range of architectures. For NNmodelfind we tried conventional multi-layer

perceptrons and convolutional neural networks as architectures, before settling on the final

ResNet-18 architecture (He et al. 2016). For NNalphafind, we tried LSTMs with or without

convolution layers for encoding, or with or without the attention layer. We found that both the

convolution encoding layers and the attention layer were crucial for achieving reasonable

estimates for alpha. We also explored using the ResNet-18 to estimate alpha but the results

were not satisfactory. Another aspect which lent itself to experimentation was how to represent

MSAs of varying size and length so that they could be input to the networks. We restricted

ourselves to a fixed input size for both networks, but experimented with different input sizes, as

well as different ways of transforming variably-sized MSAs into a fixed size input. An obvious

drawback of the fixed size input is that it is not always possible for the network to utilise all the

information available in large alignments. A promising avenue to address this might be networks

that accept graph-based representations of MSAs as their input, as explored in (Drucks 2021).

The only other tool currently employing a machine learning approach for model

estimation is ModelTeller (Abadi et al. 2020). Our simulation-based analysis of ModelTeller

suggests that it struggles to recover the actual model of sequence evolution, although that is not

the primary aim of the software. When performing a direct comparison to ModelRevelator, we

find that although the actual model of sequence evolution is rarely found by ModelTeller, there is

no appreciable difference in the accuracy of the resulting tree reconstructions. However, the

focus of both methods is different. ModelRelevator is concerned with estimating the model of

sequence evolution and the shape parameter alpha of the Γ-distribution, and is trained and

tested only on this basis. ModelTeller focuses on finding the model that yields the most accurate

edge lengths, and is trained and tested on this basis.

While some have argued that model selection is not a critical step in phylogenetic

reconstruction (Abadi et al. 2020), this view is by no means the consensus (Ripplinger and

Sullivan 2008; Hoff et al. 2016). It may be true that phylogenetic inference is robust to

misspecified substitution models in a majority of cases, nevertheless it is in the minority of cases

where this is not the case that model selection can be pivotal. Where there are contentious

topologies with conflicting evidence, having confidence in a model selection methodology can

add support to a hypothesis.

Notwithstanding our extensive explorations, we recognise the available options for

potential neural network architectures is vast. It is therefore likely that neural net architectures

exist which might yield better performance than those we present here. This fact, combined with

the recognised shortcomings of information theoretic approaches, and the absence of directly

comparable tools currently available, suggests that machine learning approaches to model

selection represent fertile ground for ongoing investigation and development.

763   Acknowledgements

764   We would like to especially thank Rob Lanfear for providing the empirical MSAs used in

765   this study. AvH is supported by a grant from the FWF (FWF I 4686 – B).

References

Abadi M., Barham P., Chen J., Chen Z., Davis A., Dean J., Devin M., Ghemawat S., Irving G., Isard M., Others. 2016. Tensorflow: a system for large-scale machine learning. OSDI. 16:265–283.

Abadi S., Avram O., Rosset S., Pupko T., Mayrose I. 2020. ModelTeller: Model Selection for Optimal Phylogenetic Reconstruction Using Machine Learning. Mol. Biol. Evol. 37:3338–3352.

Abascal F., Zardoya R., Posada D. 2005. ProtTest: selection of best-fit models of protein evolution. Bioinformatics. 21:2104–2105.

Cortes C., Mohri M., Rostamizadeh A. 2012. L2 Regularization for Learning Kernels. arXiv [cs.LG].

Crotty S.M., Holland B.R. 2022. Comparing partitioned models to mixture models: Do information criteria apply? Syst. Biol. Forthcoming.

Darriba D., Taboada G.L., Doallo R., Posada D. 2012. jModelTest 2: more models, new heuristics and parallel computing. Nat. Methods. 9:772.

Drucks T. 2021. Representation Learning for Variable-Sized Multiple Sequence Alignments. Diploma Thesis, Technische Universität Wien. .

Faircloth B.C., McCormack J.E., Crawford N.G., Harvey M.G., Brumfield R.T., Glenn T.C. 2012. Ultraconserved elements anchor thousands of genetic markers spanning multiple evolutionary timescales. Syst. Biol. 61:717–726.

Felsenstein J. 1981. Evolutionary trees from DNA sequences: a maximum likelihood approach. J. Mol. Evol. 17:368–376.

Frandsen P.B., Calcott B., Mayer C., Lanfear R. 2015. Automatic selection of partitioning schemes for phylogenetic analyses using iterative k-means clustering of site rates. BMC Evol. Biol. 15:13.

Ganin Y., Lempitsky V. 2015. Unsupervised Domain Adaptation by Backpropagation. Proceedings of the 32nd International Conference on Machine Learning. 37:1180–1189.

Glorot X., Bengio Y. 2010. Understanding the difficulty of training deep feedforward neural networks. Proceedings of the thirteenth international conference on artificial intelligence and statistics.:249–256.

Grievink L.S., Penny D., Hendy M.D., Holland B.R. 2010. Phylogenetic Tree Reconstruction Accuracy and Model Fit when Proportions of Variable Sites Change across the Tree. Syst. Biol. 59:288–297.

Hasegawa M., Kishino H., Yano T. 1985. Dating of the human-ape splitting by a molecular clock of mitochondrial DNA. J. Mol. Evol. 22:160–174.

He K., Zhang X., Ren S., Sun J. 2015a. Deep Residual Learning for Image Recognition. arXiv [cs.CV].

He K., Zhang X., Ren S., Sun J. 2015b. Delving Deep into Rectifiers: Surpassing Human-Level
Performance on ImageNet Classification. arXiv [cs.CV].

He K., Zhang X., Ren S., Sun J. 2016. Deep Residual Learning for Image Recognition. 2016
IEEE Conference on Computer Vision and Pattern Recognition (CVPR).:770–778.

Hoff M., Orf S., Riehm B., Darriba D., Stamatakis A. 2016. Does the choice of nucleotide
substitution models matter topologically? BMC Bioinformatics. 17:1–13.

Ioffe S., Szegedy C. 2015. Batch Normalization: Accelerating Deep Network Training by
Reducing Internal Covariate Shift. arXiv [cs.LG].

Jhwueng D.-C., Huzurbazar S., O'Meara B.C., Liu L. 2014. Investigating the performance of AIC
in selecting phylogenetic models. Stat. Appl. Genet. Mol. Biol. 13:459–475.

Johnson J.B., Omland K.S. 2004. Model selection in ecology and evolution. Trends Ecol. Evol.
19:101–108.

Jombart T., Cori A., Didelot X., Cauchemez S., Fraser C., Ferguson N. 2014. Bayesian
Reconstruction of Disease Outbreaks by Combining Epidemiologic and Genomic Data.
PLoS Comput. Biol. 10:e1003457.

Jukes T.H., Cantor C.R. 1969. CHAPTER 24 - Evolution of Protein Molecules. In: Munro H.N.,
editor. Mammalian Protein Metabolism. Academic Press. p. 21–132.

Kalyaanamoorthy S., Minh B.Q., Wong T.K.F., von Haeseler A., Jermiin L.S. 2017.
ModelFinder: fast model selection for accurate phylogenetic estimates. Nat. Methods.
14:587–589.

Kan A. 2017. Machine learning applications in cell image analysis. Immunol. Cell Biol. 95:525–
530.

Kandoi G., Acencio M.L., Lemke N. 2015. Prediction of Druggable Proteins Using Machine
Learning and Systems Biology: A Mini-Review. Front. Physiol. 6:366.

Kimura M. 1980. A simple method for estimating evolutionary rates of base substitutions
through comparative studies of nucleotide sequences. J. Mol. Evol. 16:111–120.

Kingma D.P., Ba J. 2014. Adam: A Method for Stochastic Optimization. arXiv [cs.LG].

Kuhner M.K., Felsenstein J. 1994. A simulation comparison of phylogeny algorithms under
equal and unequal evolutionary rates. Mol. Biol. Evol. 11:459–468.

Lanfear R., Calcott B., Ho S.Y.W., Guindon S. 2012. PartitionFinder: Combined Selection of
Partitioning Schemes and Substitution Models for Phylogenetic Analyses. Mol. Biol. Evol.
29:1695–1701.

LeCun Y., Bengio Y., Hinton G. 2015. Deep learning. Nature. 521:436–444.

Lemmon A.R., Emme S.A., Lemmon E.M. 2012. Anchored hybrid enrichment for massively
high-throughput phylogenomics. Syst. Biol. 61:727–744.

Leuchtenberger A.F., Crotty S.M., Drucks T., Schmidt H.A., Burgstaller-Muehlbacher S., von

Haeseler A. 2020. Distinguishing Felsenstein Zone from Farris Zone Using Neural
Networks. Mol. Biol. Evol. 37:3632–3641.

Leung M.K.K., Delong A., Alipanahi B., Frey B.J. 2016. Machine Learning in Genomic Medicine:
A Review of Computational Problems and Data Sets. Proc. IEEE. 104:176–197.

Minh B.Q., Schmidt H.A., Chernomor O., Schrempf D., Woodhams M.D., von Haeseler A.,
Lanfear R. 2020. IQ-TREE 2: New Models and Efficient Methods for Phylogenetic Inference
in the Genomic Era. Mol. Biol. Evol. 37:1530–1534.

Nguyen L.-T., Schmidt H.A., von Haeseler A., Minh B.Q. 2015. IQ-TREE: a fast and effective
stochastic algorithm for estimating maximum-likelihood phylogenies. Mol. Biol. Evol.
32:268–274.

Posada D. 2008. jModelTest: phylogenetic model averaging. Mol. Biol. Evol. 25:1253–1256.

Posada D., Buckley T.R. 2004. Model Selection and Model Averaging in Phylogenetics:
Advantages of Akaike Information Criterion and Bayesian Approaches Over Likelihood
Ratio Tests. Syst. Biol. 53:793–808.

Posada D., Crandall K.A. 1998. MODELTEST: testing the model of DNA substitution.
Bioinformatics. 14:817–818.

Raffel C., Ellis D.P.W. 2015. Feed-Forward Networks with Attention Can Solve Some Long-
Term Memory Problems. arXiv [cs.LG].

Rambaut A., Grassly N.C. 1997. Seq-Gen: an application for the Monte Carlo simulation of DNA
sequence evolution along phylogenetic trees. Comput. Appl. Biosci. 13:235–238.

Ripplinger J., Sullivan J. 2008. Does Choice in Model Selection Affect Maximum Likelihood
Analysis? Syst. Biol. 57:76–85.

Robinson D.F., Foulds L.R. 1981. Comparison of phylogenetic trees. Math. Biosci. 53:131–147.

Sagawa S., Koh P.W., Hashimoto T.B., Liang P. 2019. Distributionally Robust Neural Networks
for Group Shifts: On the Importance of Regularization for Worst-Case Generalization. arXiv
[cs.LG].

Seo T.-K., Thorne J.L. 2018. Information Criteria for Comparing Partition Schemes. Syst. Biol.
67:616–632.

Silva J.C.F., Teixeira R.M., Silva F.F., Brommonschenkel S.H., Fontes E.P.B. 2019. Machine
learning approaches and their current application in plant molecular biology: A systematic
review. Plant Sci. 284:37–47.

Susko E., Roger A.J. 2020. On the Use of Information Criteria for Model Selection in
Phylogenetics. Mol. Biol. Evol. 37:549–562.

Suvorov A., Hochuli J., Schrider D.R. 2020. Accurate Inference of Tree Topologies from Multiple
Sequence Alignments Using Deep Learning. Syst. Biol. 69:221–233.

Tamura K., Nei M. 1993. Estimation of the number of nucleotide substitutions in the control
region of mitochondrial DNA in humans and chimpanzees. Mol. Biol. Evol. 10:512–526.

Tao Q., Tamura K., U Battistuzzi F., Kumar S. 2019. A Machine Learning Method for Detecting
Autocorrelation of Evolutionary Rates in Large Phylogenies. Mol. Biol. Evol. 36:811–824.

Tarca A.L., Carey V.J., Chen X.-W., Romero R., Drăghici S. 2007. Machine learning and its
applications to biology. PLoS Comput. Biol. 3:e116.

Tavaré S., Others. 1986. Some probabilistic and statistical problems in the analysis of DNA
sequences. Lectures on mathematics in the life sciences. 17:57–86.

Truszkowski J., Goldman N. 2016. Maximum Likelihood Phylogenetic Inference is Consistent on
Multiple Sequence Alignments, with or without Gaps. Syst. Biol. 65:328–333.

VanderPlas J., Connolly A.J., Ivezić Ž., Gray A. 2012. Introduction to astroML: Machine learning
for astrophysics. 2012 Conference on Intelligent Data Understanding.:47–54.

Whelan S., de Bakker P.I.W., Quevillon E., Rodriguez N., Goldman N. 2006. PANDIT: an
evolution-centric database of protein and associated nucleotide domains with inferred trees.
Nucleic Acids Res. 34:D327–31.

Yang Z. 1994. Maximum likelihood phylogenetic estimation from DNA sequences with variable
rates over sites: approximate methods. J. Mol. Evol. 39:306–314.

Zou Z., Zhang H., Guan Y., Zhang J. 2020. Deep Residual Neural Networks Resolve Quartet
Molecular Phylogenies. Mol. Biol. Evol. 37:1495–1507.